31.05	13.10 Borrow	Crew	Daily	Labor- Hours	Unit	Material	2022 Ba Labor	re Costs Equipment	Total	Total Incl O&P
	BORROW	R312316-40	odipoi	110013	Oilli .	Majoriai	Luboi	Ецогритот	iolai	mer our
0020	Spread, 200 HP dozer, no compaction, 2 mile RT haul									
0200	Common borrow .	B-15	600	.047	C.Y.	12.55	2.52	4.81	19.88	- 23
0700	Screened loam	: :	600	.047	1 1	34	2.52	4.81	41.33	46.
0800	Topsoil, weed free	1 +	600	.047		20.50	2.52	4.81	27.83	31.5
0900	For 5 mile haul, add	B-34B	3 200	.040	. 🔻		2.12	3.84	5.96	7.4
	05 16 - Aggregates for Earthwork									
	16.10 Borrow									
	BORROW Spread with 200 HP dezer percompaction 2 mile PT haul	R312316-40								
0020 0100	Spread, with 200 HP dozer, no compaction, 2 mile RT haul Bank run gravel	B-15	600	.047	L.C.Y.	27.50	2.52	4.81	34.83	39
0300	Crushed stone (1.40 tons per C.Y.), 1-1/2"	013	600	.047	L.C. I.	20.50	2.52	4.01	27.83	31.
0320	3/4"		600	.047		20.50	2.52	4.81	27.83	31.
0340	1/2"		600	.047		18.55	2.52	4.81	25.88	29.
0360	3/8"		600	.047		23	2.52	4.81	30.33	34
0400	Sand, washed, concrete		600	.047		18.75	2.52	4.81	26.08	29.
0500	Dead or bank sand	1 1	600	.047	Nie I	13.70	2.52	4.81	21.03	24
0600	Select structural fill	B-15	600	.047	L.C.Y.	16.25	2.52	4.81	23.58	27
0900	For 5 mile haul, add	B-34B		.040	"	10120	2.12	3.84	5.96	7.4
	05 23 - Cement and Concrete for									
31 05	23.30 Plant Mixed Bituminous Concrete									
0010	PLANT MIXED BITUMINOUS CONCRETE									
0020	Asphaltic concrete plant mix (145 lb./C.F.)			,	Ton	68			68	75
0040	Asphaltic concrete less than 300 tons add trucking costs									
0200	All weather patching mix, hot				Ton	64.50	,	1	64.50	. 71
0250	Cold patch			1		85			85	93.
0300 1	Berm mix	1				69.50		1	69.50	76.

	3					-	
0010	PILING SPECIAL COSTS						
0011	Piling special costs, pile caps, see Section 03 30 53.40						
0500	Cutoffs, concrete piles, plain	, 1 Pile 5.50 1.455 Ea.		84.50		84.50	131
0600	With steel thin shell, add	38 .211	1	12.25		12.25	18.95
0700	Steel pile or "H" piles	19 .421		24.50	-	24.50	38
0800	Wood piles	38 .211 🔟	1	12.25	1	12.25	18.95
0900	Pre-augering up to 30' deep, average soil, 24" diameter	B-43 180 .267 L.F.		13.40	4.37	17.77	25
0920	36" diameter	1 115 .417	1	21	6.85	27.85	39
0960	48" diameter	70 .686		34.50	11.25	45.75	64
0980	60" diameter	50 .960		48.50	15.70	64.20	89.50
1000	Testing, any type piles, test load is twice the design load	 1					
1050	50 ton design load, 100 ton test	Ea.			. :	14,000	15,500
1100	100 ton design load, 200 ton test				1	20,000	22,000
1150	150 ton design load, 300 ton test		1	1	1	26,000	28,500
1200	200 ton design load, 400 ton test			-		28,000	31,000
1250	400 ton design load, 800 ton test					32,000	35,000
1500	Wet conditions, soft damp ground						- Alica
1600	Requiring mats for crane, add					40%	40%
1700	Barge mounted driving rig, add					30%	30%