09 01 Maintenance of Finishes

09 01 90 - Maintenance of Painting and Coating

09 01 90.	.94 Interior Surface Preparation	Crew	Daily Output	Labor- It Hours		2022 Bare Co Material Labor Equi	osts uipment Total	Total
0070	Wire brush							
0080	Metal, flush	1 Pord				.60 ;	.60	
0090	Metal, detail	1 1	520				.74	
0100	Metal, louvered		360	.022	. 4	1.06	1.06	1
0110	Hand wash							
0120	Wood, flush	1 Pord				18	.18	
0130	Wood, detail	11	2000			.19	.19	
0140	Wood, louvered	117	1360			.28	.28	
0150	Metal, flush	11	2160			.18	.18	
0160	Metal, detail	11	2000			.19	.19	
0170	Metal, louvered	1	1360	.006	+	.28	.28	
0400 W	Windows, per side, not incl. trim							
0410	Scrape & sand							
0420	Wood, 1-2 lite	1 Pord				1.06	1.06	
0430	Wood, 3-6 lite	117	320			1.20	1.20	
0440	Wood, 7-10 lite	11	280	.029		1.37	1.37	2
0450	Wood, 12 lite	. 117	240			1.59	1.59	
0460	Wood, Bay/Bow	1 +	360	.022	1+	1.06	1.06	1
0470	Wire brush							
0480	Metal, 1-2 lite	1 Pord				.74	.74 :	
0490	Metal, 3-6 lite	: 17	440			.87	.87	
0500	Metal, Bay/Bow	: •	520	.015	4	.74	.74	
0600 W	Walls, sanding, light=10-30%, medium=30-70%,							
0610	heavy=70-100% of surface to sand							
0650	Walls, sand							
0660	Gypsum board or plaster, light	1 Pord	d 3077				.12	
0670	Gypsum board or plaster, medium		2160			.18	.18	
0680	Gypsum board or plaster, heavy	1	923		1	.41	.41	
0690	Wood, T&G, light		2400			.16	.16	
0700	Wood, T&G, medium		1600			.24	.24	
0710	Wood, T&G, heavy	1 🕹	_ 800	.010	1 - 1	.48	.48	
0720	Walls, wash							
0730	Gypsum board or plaster	1 Pord	d 3200			.12	.12	
0740	Wood, T&G	11	3200			.12	.12	
0750	Masonry, brick & block, smooth	: 17	2800			; .14	.14	
0760	Masonry, brick & block, coarse	1 1	2000	.004	1.4	.19	.19	
8000 F	For chemical washing, see Section 04 01 30							
	For steam cleaning, see Section 04 01 30.20							
	For sand blasting, see Sections 03 35 29.60 and 05 01 10.51							

09 05 Common Work Results for Finishes

09 05 05 - Selective Demolition for Finishes

09 05 05.10 Selective Demolition, Ceilings

0010	SELECTIVE DEMOLITION, CEILINGS	R024119-1	0					-				
0200	Ceiling, gypsum wall board, furred and nailed or screwed		2 Clab	800	.020	S.F.			.91		.91	
0220	On metal frame		ţ	760	.021	1			.96		.96	
0240	On suspension system, including system		1	720	.022	-			1.01		1.01	
1000	Plaster, lime and horse hair, on wood lath, incl. lath			700	.023				1.04	1	1.04	
1020	! On metal lath		- N	570	.028	1	[1.28		1.28	
1100	Gypsum, on gypsum lath		1	720	.022			1	1.01	1	1.01	
1120	On metal lath		1 1	500	.032	1		1	1.46		1.46	