## 09 66 Terrazzo Flooring 09 66 13 - Portland Cement Terrazzo Flooring

00 //	42.40 Partland Comput Towns	(··		Labor-	llmi4	Material	2022 Bare		Total	Total
	5 13.10 Portland Cement Terrazzo	Crew J-3	Output 70	Hours .229	Unit S.F.	Material 5.05	Labor E	quipment 3.42	19.67	inci 0.
1800 1900	Not bonded, 3" total thickness, gray cement White cement, mud set	; J-3	70	.229	3.F.	5.80	11.20	3.42	20.42	2
2100	For Venetian terrazzo, 1″ topping, add	W	/ 0	,ZZ7	*	50%	50%	5.42 ;	20.42	7
	For heavy duty abrasive terrazzo, add					50%	50%			
2200		i				30/0	3070			
2700	Monolithic terrazzo, 1/2" thick	: 10	125	100	CE	2 (2	6.30	1.92	11.84	1
2710	10' panels	J-3	125 30	.128	S.F.	3.62 4.66	26	8	38.66	5
3000	Stairs, cast-in-place, pan filled treads		14	1.143	L.t.	6.90	56 ·	17.10	80	10
3100	Treads and risers		14	1.140		0.70		17.10	00 :	10
3300	For stair landings, add to floor prices	1 10 1	20	. raa	CF	r.r.;	50%	0	39.55	5
3400	Stair stringers and fascia	J-3	30		S.F.	5.55	26	8		
3600	For abrasive metal nosings on stairs, add		150	.107		10.55	5.25	1.60	17.40	2
3700	For abrasive surface finish, add		600	: .027		1.95	1.31	.40	3.66	,
3900	For raised abrasive strips, add		150	.107	L.F.		5.25	1.60	8.29	1
4000	Wainscot, bonded, 1-1/2" thick		30	.533	S.F.		26	8	38.27	5
1200	1/4" thick		40	.400	"	6.95	19.65	. 6	32.60	4
4300	Stone chips, onyx gemstone, per 50 lb. bag	1 .			Bag	20.50			20.50	2
09 6	66 16 - Terrazzo Floor Tile									
	6 16.10 Tile or Terrazzo Base									***
	TILE OR TERRAZZO BASE									
0020	Scratch coat only	1 Mstz	150	.053	S.F.	.20	2.85		3.05	
0500	Scratch and brown coat only	1 "	75	.107	#	.40	5.70		6.10	
9 66	5 16.13 Portland Cement Terrazzo Floor Tile									
0010	PORTLAND CEMENT TERRAZZO FLOOR TILE									
200	Floor tiles, non-slip, 1" thick, 12" x 12"	D-1	60	.267	S.F.	29	13.35		42.35	5
1300	1-1/4" thick, 12" x 12"		60	.267	· ·	27	13.35		40.35	5
1500	16" x 16"	2 200	50	.320	1	30	16.05		46.05	5
1600	1-1/2" thick, 16" x 16"		45	.356		27.50	17.80	1	45.30	5
1800	For Venetian terrazzo, add					8.20			8.20	
1900	For white cement, add					.75			.75	
09 66	16.16 Plastic Matrix Terrazzo Floor Tile				•					
0010	PLASTIC MATRIX TERRAZZO FLOOR TILE									
0100	12" x 12", 3/16" thick, floor tiles w/marble chips	1 Tilf	500	.016	S.F.	8.20	.85		9.05	1
0200	12" x 12", 3/16" thick, floor tiles w/glass chips		500	.016		8.80	.85		9.65	1
0300	12" x 12", 3/16" thick, floor tiles w/recycled content		500	.016	1	17.50	.85		18.35	2
09 66	5 16.30 Terrazzo, Precast									
0010	TERRAZZO, PRECAST									
0020	Base, 6" high, straight	1 Mstz	70	.114	L.F.	13.25	6.10		19.35	2
0100	Cove		60	.133	1 - mary 1	18 :	7.10		25.10	3
0300	8" high, straight		60	.133	dynagles	16.90	7.10		24	2
0400	Cove	11	50	160		26	8.55		34.55	4
0600	For white cement, add	1				.64			.64	
0700	For 16 ga. zinc toe strip, add					2.49			2.49	
0900	Curbs, 4" x 4" high	1 Mstz	40	.200		46	10.70		56.70	6
1000	8" x 8" high	. "	30	.267		50.50	14.25		64.75	7
2400	Stair treads, 1-1/2" thick, non-slip, three line pattern	2 Mstz	70	.229		57	12.20		69.20	8
2500	Nosing and two lines	1 1	70	.229		57	12.20		69.20	{
2700	2" thick treads, straight		60	.267	and the same of th	66.50	14.25		80.75	(
2800	Curved		50	.320		89.50	17.10		106.60	12
3000	Stair risers, 1" thick, to 6" high, straight sections		60	.267		17.20	14.25		31.45	4
		0	0.0			17120	11123		01110	
3100	Cove	1	50	.320		21.50	17.10		38.60	4