31 32 Soil Stabilization

31 32 13 - Soil Mixing Stabilization

			Daily	Labor-			2022 B	are Costs		Total
31 32	2 13.30 Calcium Chloride	Crew	Output	Hours	Unit	Material	Labor	Equipment	Total	Incl O&P
0010	CALCIUM CHLORIDE									
0020	Calcium chloride, delivered, 100 lb. bags, truckload lots				Ton	660			660	725
0030	Solution, 4 lb. flake per gallon, tank truck delivery				Gal.	1.58			1.58	1.74

31 33 Rock Stabilization

31 33 13 - Rock Bolting and Grouting

31	33	13.10	Rock	Bolting
----	----	-------	------	----------------

0010	ROCK BOLTING										
2020	Hollow core, prestressable anchor, 1" diameter, 5' long	2 Skwk	32	.500	Ea.	182		29.50		211.50	244
2025	•		24	.667		305		39.50		344.50	395
2060	2" diameter, 5' long		32	.500		675		29.50		704.50	785
2065	10' long		24	.667	-	1,200		39.50		1,239.50	1,375
2100	Super high-tensile, 3/4" diameter, 5' long		32	.500		48.50)	29.50		78	97
2105	10' long		24	.667		121	-	39.50		160.50	193
2160	2" diameter, 5' long		32	.500		375		29.50		404.50	460
2165	. 10' long		24	.667		675		39.50		714.50	805
4400	Drill hole for rock bolt, 1-3/4" diam., 5' long (for 3/4" bolt)	B-56	17	.941	1			48.50	93.50	142	175
4405	10' long		9	1.778				91	177 -	268	330
4420	2" diameter, 5' long (for 1" bolt)		13	1.231				63	123	186	229
4425	10' long		7	2.286	-	-	1	117	228	345	425
4460	3-1/2" diameter, 5' long (for 2" bolt)		10.	1.600	+		3	82	159	241	297
4465	10' long	B-56	5	3.200	Ea.	İ	*	164	320	484	595

31 36 Gabions

31 36 13 - Gabion Boxes

31 36 13.10 Gabion Box Systems

0010	GABION BOX SYSTEMS									
0400	Gabions, galvanized steel mesh mats or boxes, stone filled, 6" deep	B-13	200	.280	S.Y.	17.95	13.90	10.45	42.30	52
0500	9" deep		163	.344		32.50	17.05	12.85	62.40	75.50
0600	12" deep		153	.366		36	18.15	13.70	67.85	81.50
0700	. 18" deep	1	102	.549		75.50	27.50	20.50;	123.50	146
0800	36" deep	1 +	60	.933	V	84.50	46.50	35	166	201

31 37 Riprap

31 37 13 - Machined Riprap

31 37 13.10 Riprap and Rock Lining

0010	RIPRAP AND ROCK LINING										
0011	Random, broken stone										
0100	Machine placed for slope protection	B-12G	62	.258	L.C.Y.	37	14.05	13.95	65	77	
0110	3/8 to 1/4 C.Y. pieces, grouted	B-13	80	.700	S.Y. ;	73.50	34.50	26	134	162	
0200	18" minimum thickness, not grouted	"	53	1.057	"	23	52.50	39.50	115	147	
0300	Dumped, 50 lb. average	B-11A	800	.020	Ton	28.50	1.06	1.69	31.25	35	
0350	100 lb. average	Randon [700	.023		28.50	1.21	1.93	31.64	35.50	
0370	300 lb. average	1 + 1	600	.027	+ 1	28.50	1.41	2.25	32.16	36	