

07 05 Common Work Results for Thermal and Moisture Protection

07 05 05 – Selective Demolition for Thermal and Moisture Protection

07 05 05.10 Selective Demo., Thermal and Moist. Protection		Crew	Daily Output	Labor-Hours	Unit	Material	2022 Bare Costs		Total	Total Incl O&M
							Labor	Equipment		
5620	Stucco siding	1 Clab	360	.022	S.F.		1.01		1.01	1
5670	Textured plywood		725	.011			.50		.50	
5720	Vinyl siding		510	.016			.72		.72	1
5770	Corner strips		900	.009	L.F.		.41		.41	
5870	Wood, boards, vertical		400	.020	S.F.		.91		.91	
5880	Steel siding, corrugated/ribbed		402.50	.020	"		.91		.91	1
5920	Waterproofing, protection/drain board	2 Clab	3900	.004	B.F.		.19		.19	
5970	Over 1/2" thick		1750	.009	S.F.		.42		.42	
6020	To 1/2" thick		2000	.008	"		.36		.36	

07 11 Dampproofing

07 11 13 – Bituminous Dampproofing

07 11 13.10 Bituminous Asphalt Coating

0010	BITUMINOUS ASPHALT COATING									
0030	Brushed on, below grade, 1 coat	1 Rofc	665	.012	S.F.	.22	.60		.82	1
0100	2 coat	1 Rofc	500	.016	S.F.	.43	.79		1.22	1
0300	Sprayed on, below grade, 1 coat		830	.010		.22	.48		.70	1
0400	2 coat		500	.016		.42	.79		1.21	1
0500	Asphalt coating, with fibers				Gal.	10.40			10.40	11
0600	Troweled on, asphalt with fibers, 1/16" thick	1 Rofc	500	.016	S.F.	.45	.79		1.24	1
0700	1/8" thick		400	.020		.80	.99		1.79	2
1000	1/2" thick		350	.023		2.60	1.13		3.73	4

07 11 16 – Cementitious Dampproofing

07 11 16.20 Cementitious Parging

0010	CEMENTITIOUS PARGING									
0020	Portland cement, 2 coats, 1/2" thick	D-1	250	.064	S.F.	.35	3.21		3.56	5
0100	Waterproofed Portland cement, 1/2" thick, 2 coats	"	250	.064	"	2.66	3.21		5.87	7

07 12 Built-up Bituminous Waterproofing

07 12 13 – Built-Up Asphalt Waterproofing

07 12 13.20 Membrane Waterproofing

0010	MEMBRANE WATERPROOFING									
0012	On slabs, 1 ply, felt, mopped	G-1	3000	.019	S.F.	.40	.87	.18	1.45	2
0100	On slabs, 1 ply, glass fiber fabric, mopped		2100	.027		.46	1.24	.26	1.96	2
0300	On slabs, 2 ply, felt, mopped		2500	.022		.81	1.04	.22	2.07	2
0400	On slabs, 2 ply, glass fiber fabric, mopped		1650	.034		1.04	1.57	.33	2.94	4
0600	On slabs, 3 ply, felt, mopped		2100	.027		1.21	1.24	.26	2.71	3
0700	On slabs, 3 ply, glass fiber fabric, mopped		1550	.036		1.37	1.67	.36	3.40	4
0710	Asphaltic hardboard protection board, 1/8" thick	2 Rofc	500	.032		1.24	1.59		2.83	3
1000	EPS membrane protection board, 1/4" thick		3500	.005		.37	.23		.60	
1050	3/8" thick		3500	.005		.41	.23		.64	
1060	1/2" thick		3500	.005		.44	.23		.67	
1070	Fiberglass fabric, black, 20/10 mesh		116	.138	Sq.	18.05	6.85		24.90	31