19 9	91 Painting P1 23 - Interior Painting										CONTRACTOR OF THE PARTY OF THE
				Daily	Labor-			2022 Ba	re Costs		Total
	23.72 Walls and Ceilings, Interior		Crew			Unit	Material	Labor	Equipment Total	al	Incl O&P
200	For work 8'-15' H, add					S.F.		10%			
300	For work over 15' H, add		1					20%			
400	For light textured surfaces, add							10%			
410	Heavy textured, add					+		25%			
9 91	23.74 Walls and Ceilings, Interior, Zero V	OC Latex									
010	WALLS AND CEILINGS, INTERIOR, ZERO VOC LATEX										
100	Concrete, dry wall or plaster, latex, primer or sealer coat										
190	Smooth finish, cut-in by brush		1 Pord	1150	.007	L.E.	.02	.33		.35	.51
200	Brushwork	G		1150	.007	S.F.	.07	.33		.40	.57
240	Roller	G		1350	.006		.07	.28		.35	.49
280	Spray	G		2750	.003		.05	.14		.19	.27
290	Sand finish, cut-in by brush			975	.008	L.F.	.02	.39		.41	.60
300	Brushwork	G		975	.008	S.F.	.07	.39		.46	.65
340	Roller	G		1150	.007		.07	.33		.40	.57
380	Spray	G		2275	.004		.06	.17		.23	.31
790	Paint 2 coats, smooth finish, cut-in by brush	_		680	.012	L.F.	.03	.56		.59	.87
800	Brushwork	G		680	.012	S.F.	.03	.56		.59	.87
840	Roller	G		800	.010		.13	.48		.61	.86
880	Spray	G		1625	.005		.11 ;	.24		.35	.48
890	Sand finish, cut-in by brush	٩		605	.013	L.F.	.03	.63		.66	.97
900	Brushwork	G		605	.013	S.F.	.13	.63		.76	1.08
940	Roller	G		1020	.008	Э.Г.	.13	.37		.50	
980		G		1700	.005		.13	.22		.33	.71 .46
190	Spray	U		510	.005	L.E.	.05	.75		.80	
	Paint 3 coats, smooth finish, cut-in my brush	त्व									1.16
200	Brushwork	G		510	.016	S.F.	.19	.75		.94	1.32
240	Roller			650	.012		.20	.59		.79	1.09
280	. Spray	G	*	850	.009		.17	.45		.62	.86
800	For ceiling installations, add	G						25%			
200	For work 8' - 15' H, add		1					10%			
300	For work over 15' H, add		1			*		20%			
	23.75 Dry Fall Painting	~ —									
010	DRY FALL PAINTING	R099100-10									
100	Sprayed on walls, gypsum board or plaster										
220	One coat	R099100-20	1 Pord		.003	S.F.	.08	.15		.23	.31
250	Two coats			1560	.005		.17	.25		.42	.55
280	Concrete or textured plaster, one coat			1560	.005		.08	.25		.33	.45
310	Two coats			1300	.006		.17	.29 :	1	.46	.63
340	Concrete block, one coat			1560	.005		.08	.25		.33	.45
370	Two coats			1300	.006	.	.17	.29	1	.46	.63
400	Wood, one coat			877	.009		.08	.44		.52	.74
430	Two coats			650	.012	÷	.17	.59		.76	1.06
440	On ceilings, gypsum board or plaster										
470	One coat		1 Pord	1560	.005	S.F.	.08	.25		.33	.45
500	Two coats			1300	.006	11	.17	.29		.46	.63
530	Concrete or textured plaster, one coat			1560	.005		.08	.25		.33	.45
560	Two coats			1300	.006		.17	.29		.46	.63
570	Structural steel, bar joists or metal deck, one coat			1560	.005		.08	.25		.33	.45
580	Two coats		3 1	1040	.008	+	.17	.37		.54	.74