## 32 12 Flexible Paving

32 1	121	6 -	Asp	halt	<b>Paving</b>

			Daily Labor-			2022 Bare Costs				lotal
32 12	2 16.14 Asphaltic Concrete Paving	Crew	Output	Hours	Unit	Material	Labor	Equipment	Total	Incl O&P
0040	1-1/2" binder course, 1" topping	B-25C	9000	.005	S.F.	1.81	.27	.28	2.36	2.70
0042	3" binder course, 1" topping		9000	.005		2.43	.27	.28	2.98	3.39
0045	3" binder course, 3" topping		9000	.005		3.35	.27	.28	3.90	4.40
0050	4" binder course, 3" topping		9000	.005		3.76	.27	.28	4.31	4.85
0055	4" binder course, 4" topping		9000	.005		4.21	.27	.28	4.76	5.35
0300	Binder course, 1-1/2" thick		35000	.001		.62	.07	.07	.76	.86
0400	2" thick	1	25000	.002		.80	.10	.10	1 1	1.14
0500	3" thick	1	15000	.003		1.24	.16	.17	1.57	1.79
0600	4" thick	1	10800	.004		1.62	.23	.24	2.09	2.38
0800	Sand finish course, 3/4" thick	3 1	41000	.001		.33	.06	.06	.45	.52
0900	1" thick	1 4	34000	.001	ť	.40	.07	.07	.54	.63
1000	Fill pot holes, hot mix, 2" thick	B-16	4200	.008		.80	.37	.18	1.35	1.62
1100	4" thick		3500	.009		1.17	.44	.22	1.83	2.17
1120	6" thick	1 +	3100	.010		1.57	.50	.25	2.32	2.73
1140	Cold patch, 2" thick	B-51	3000	.016		1.06	.75	.11	1.92	2.40
1160	4" thick	1 1	2700	.018	1	2.02	.83	.13	2.981	3.61
1180	6" thick	1 1	1900	.025	1	3.15	1.18	.18	4.51	5.40

## 32 12 36 - Seal Coats

## 32 12 36.13 Chip Seal

0010	CHIP SEAL									
0011	Excludes crack repair and flush coat									
1000	Fine - PMCRS-2h (20lbs/sy, 1/4" (No.10), .30gal/sy app. rate)									
1010	Small, irregular areas	B-91	5000	.013	S.Y.	1.25	.69	.49	2.43	2.95
1020	Parking Lot	B-91D	15000	.007		1.25	.36	.23	1.84	2.18
1030	Roadway	"	30000	.003		1.25	.18	.12	1.55	1.78
1090	For Each .5% Latex Additive, Add	1			+	.29			.29	.32
1100	Medium Fine - PMCRS-2h (25lbs/sy, 5/16" (No.8), .35gal/sy app. rate)									
1110	Small, irregular areas	B-91	4000	.016	S.Y.	1.55	.87	.61	3.03	3.67
1120	Parking Lot	B-91D	12000	.009		1.55	.46	.29	2.30	2.71
1130	Roadway	. "	24000	.004		1.55	.23	.15	1.93	2.21
1190	For Each .5% Latex Additive, Add				Ý	.36			.36	.40
1200	Medium - PMCRS-2h (30lbs/sy, 3/8" (No.6), .40gal/sy app. rafe)									
1210	Small, irregular areas	1	3330		S.Y.	1.60	1.04	.73	3.37	4.12
1220	Parking Lot	B-91D		.010		1.60	.55	.35	2.50	2.96
1230	Roadway		20000	.005		1.60	.27	.18	2.05	2.36
1290	For Each .5% Latex Additive, Add				¥	.43			.43	.48
1300	Course - PMCRS-2h (30lbs/sy, 1/2" (No.4), .40gal/sy app. rate)									
1310	Small, irregular areas	B-91	2500	.026	S.Y.	1.56	1.39	.98	3.93	4.84
1320	Parking Lot	B-91D	7500	.014		1.56	.73	.47	2.76	3.31
1330	Roadway	"	15000	.007		1.56	.36	.23	2.15	2.51
1390	For Each .5% Latex Additive, Add	1				.43		The state of the s	.43	.48
1400	Double - PMCRS-2h (Course Base with Fine Top)									
1410	Small, irregular areas	B-91	2000		S.Y.	2.66	1.73	1.22	5.61	6.85
1420	Parking Lot	B-91D	6000	.017		2.66	.91	.58	4.15 :	4.92
1430	Roadway	; "	12000	.009		2.66	.46	.29	3.41	3.92
1490	For Each .5% Latex Additive, Add				. v	.72			.72	.79
20 40	20 44 Plank Cont									

## 32 12 36.14 Flush Coat

0010	FLUSH COAT									
0011	Fog Seal with Sand Cover (.18gal/sy, 6lbs/sy)									
1010	Small, irregular areas	B-91	2000	.032	S.Y.	1.14	1.73	1.22	4.09	5.15
1020	Parking lot		6000	.011	I	1.14	.58	.41	2.13	2.56
1030	Roadway	1	12000	.005	1	1.14	.29	.20	1.63	1.90