07 65 Flexible Flashing

| 07 65 13 | - | Laminat | ed Sh | eet F | lashing |
|----------|---|---------|-------|-------|---------|

| 13.10 Laminated Sheet Flashing | Crev | | | | Material | 2022 Ba Labor | are Costs Equipment | Total | Total Incl 0& |
|---|--|--|--|---|---|--------------------------------|--------------------------------|--------------------------------|--------------------------------|
| A but were | | | | | | | | | |
| | 1 Ro | fc 330 | .024 | S.F. | 1.62 | 1.20 | | 2.82 | . 3. |
| | : 11 | 330 | | | 1.90 | 1.20 | | 3.10 | 4 |
| | 1 | 460 | | | 3.49 | .86 | | 4.35 | 5. |
| | 1 Ro | | | | | 1.20 | | 2.82 | 3. |
| | A i V | 330 | | | 2.20 | 1.20 | | 3.40 | |
| | | 330 | | | 3.21 | 1.20 | 1 | 4.41 | 5. |
| Paperbacked 2 sides, 2 oz. | 11 | 330 | | | 2.44 | 1.20 | | 3.64 | |
| 3 oz. | | 330 | | | 2.28 | 1.20 | | 3.48 | 4 |
| 5 oz. | . 11 | 330 | | | 3.97 | 1.20 | | 5.17 | 6 |
| 7 oz. | | 330 | | , | 6.25 | 1.20 | | 7.45 | 8 |
| Mastic-backed 2 sides, copper, 2 oz. | | 330 | | | 2.32 | 1.20 | | 3.52 | |
| 3 oz. | | 330 | | | 2.63 | 1.20 | | 3.83 | |
| 5 oz. | A i i | 330 | | 1 1 | 4 | 1.20 | 1 1 | 5.20 | |
| | A i I | 330 | | | 2.09 | 1.20 | | 3.29 | 4 |
| 3 oz. | ii | 330 | | 4 1 | 2.95 | 1.20 | | 4.15 | 5 |
| 5 oz. | TI | 330 | | | 4.13 | 1.20 | | 5.33 | 6 |
| Copper-clad stainless steel, .015" thick, under 500 lb. | | 115 | | | 7.05 | 3.45 | | 10.50 | |
| Over 2000 lb. | 1 | 155 | | | 6.95 | 2.56 | | 9.51 | 11 |
| .018" thick, under 500 lb. | | 100 | | | 8.10 | 3.97 | | 12.07 | 15 |
| | 11 | 145 | | | 8.35 | 2.74 | | 11.09 | 13 |
| | | 155 | | | 4.22 | 2.56 | | 6.78 | 8 |
| 7 oz. | | 155 | | | 5.10 | 2.56 | | 7.66 | 9 |
| | 4 | 330 | | | 4.14 | 1.20 | | 5.34 | |
| 55 19 - Plastic Sheet Flashing | | | | | | | | | |
| 19.10 Plastic Sheet Flashing and Counter Flashing | | | | | | | | | |
| PLASTIC SHEET FLASHING AND COUNTER FLASHING | | | | | | | | | |
| Polyvinyl chloride, black, 10 mil | - 1 Ro | ofc 285 | .028 | S.F. | .28 | 1.39 | | 1.67 | |
| 20 mil | .]] | 285 | .028 | | .27 | 1.39 | | 1.66 | |
| 30 mil | | _ 285 | .028 | | .34 | 1.39 | | 1.73 | |
| 60 mil | 11 | 285 | .028 | | .90 | 1.39 | A I | 2.29 | |
| Black or white for exposed roofs, 60 mil | 11 | 285 | .028 | 1 | 4.89 | 1.39 | 1 | 6.28 | |
| PVC tape, 5" x 45 mils, for joint covers, 100 L.F./roll | | | | | | | | 189 | 20 |
| Polyvinyl chloride, 30 mil | 1 Ro | fc 160 | .050 | | | 2.48 | | 3.54 | |
| 55 23 - Rubber Sheet Flashing | | | | | | | | | |
| 23.10 Rubber Sheet Flashing and Counter Flashing | | | | | | | | | |
| RUBBER SHEET FLASHING AND COUNTER FLASHING | | | | | | | | | |
| EPDM 90 mils, 1" diameter pipe flashing | : 1 Ro | ofc 32 | .250 | Ea. | 22 : | 12.40 | | 34.40 | |
| 2" diameter | | . 30 | | | 4.15 | 13.25 | | 17.40 | |
| 3" diameter | : 17 | 28 | .286 | | 4.65 | 14.15 | | 18.80 | |
| 4" diameter | f | 24 | .333 | | 8.35 | 16.55 | | 24.90 | |
| 6" diameter | 1 | 22 | 1.364 | 11 + | 9.65 | 18.05 | | 27.70 | 3 |
| Rubber, butyl, 1/32" thick | 1 + | 285 | .028 | | 2.35 | 1.39 | | 3.74 | |
| 1/16" thick | [1 Ro | fc 285 | .028 | S.F. | 4.91 | 1.39 | | 6.30 | |
| Neoprene, cured, 1/16" thick | 1 1 | 285 | .028 | | 2.35 | 1.39 | | 3.74 | |
| | 13.10 Laminated Sheet Flashing LAMINATED SHEET FLASHING, Including up to 4 bends Aluminum, fobric-backed 2 sides, mill finish, .004" thick .005" thick Mastic-backed, self adhesive Mastic-coated 2 sides, .004" thick Copper, paperbacked 1 side, 2 oz. 3 oz. Paperbacked 2 sides, 2 oz. 3 oz. 5 oz. 7 oz. Mastic-backed 2 sides, copper, 2 oz. 3 oz. 5 oz. Fabric-backed 2 sides, copper, 2 oz. 3 oz. 5 oz. Copper-clad stainless steel, .015" thick, under 500 lb. Over 2000 lb018" thick, under 500 lb. Over 2000 lb. Shower pan, 3 ply copper and fabric, 3 oz. 7 oz. Stainless steel, paperbacked 2 sides, .005" thick 5 19 — Plastic Sheet Flashing 19.10 Plastic Sheet Flashing 19.10 Plastic Sheet Flashing and Counter Flashing Plastic Sheet Flashing AND COUNTER FLASHING Polyvinyl chloride, block, 10 mil 20 mil 30 mil 60 mil Black or white for exposed roofs, 60 mil PVC tope, 5" x 45 mils, for joint covers, 100 L.F./roll Polyvinyl chloride, 30 mil 5 23 — Rubber Sheet Flashing and Counter Flashing RUBBER SHEET FLASHING AND COUNTER FLASHING EPDM 90 mils, 1" diameter 3" diameter 3" diameter 3" diameter 4" diameter 4" diameter 6" diameter 8" diameter | AMINATED SHEET FLASHING, Including up to 4 bends Aluminum, fabric-backed 2 sides, mill finish, .004" thick .005" thick Mastic-coated 2 sides, .004" thick Copper, paperbacked 1 side, 2 oz. 3 oz. Paperbacked 2 sides, 2 oz. 3 oz. Paperbacked 2 sides, copper, 2 oz. 3 oz. 7 oz. Mastic-backed 2 sides, copper, 2 oz. 3 oz. Fabric-backed 2 sides, copper, 2 oz. 3 oz. 5 oz. Fobric-backed 2 sides, copper, 2 oz. 3 oz. 5 oz. Copper-clad stainless steel, .015" thick, under 500 lb. Over 2000 lb018" thick, under 500 lb. Over 2000 lb. Shower pan, 3 ply copper and fabric, 3 oz. 7 oz. Stainless steel, paperbacked 2 sides, .005" thick 5 19 — Plastic Sheet Flashing 19.10 Plastic Sheet Flashing 19.10 Plastic Sheet Flashing 19.10 Plastic Sheet Flashing and Counter Flashing PLASTIC SHEET FLASHING AND COUNTER FLASHING Polyvinyl chloride, black, 10 mil 20 mil 30 mil 60 mil Black or white for exposed roofs, 60 mil PVC tape, 5" x 45 mils, for joint covers, 100 L.F./roll Polyvinyl chloride, 30 mil 1 Rafe 5 23 — Rubber Sheet Flashing 23.10 Rubber Sheet Flashing and Counter Flashing RUBBER SHEET FLASHING AND COUNTER FLASHING EPDM 90 mils, 1" diameter pipe flashing 2" diameter 4" diameter | 13.10 Laminated Sheet Flashing Crew Output | Daily Labor Crew Output Hours Labor Crew Output Hours | 13.10 Laminated Sheet Flashing Crew Output Hours Unit | 13.10 Laminated Sheet Flashing |

8400

1/8" thick

285 .028

6.20

1.39

7.59