

09 72 Wall Coverings

09 72 20 – Natural Fiber Wall Covering

09 72 20.10 Natural Fiber Wall Covering					Daily Crew Output	Labor- Hours	Unit	Material	2022 Bare Costs		Total	Total Inc O&P
									Labor	Equipment		
0010	NATURAL FIBER WALL COVERING , including sizing; add 10-30% waste @ takeoff											
0015	Bamboo	1	Pape	640	.013	S.F.		2.72	.60		3.32	3.8
0030	Burlap			640	.013			2.72	.60		3.32	3.8
0045	Jute			640	.013			2.36	.60		2.96	3.4
0060	Sisal			640	.013			1.74	.60		2.34	2.8

09 72 23 – Wallpapering

09 72 23.10 Wallpaper

0010	WALLPAPER including sizing; add 10-30% waste @ takeoff				R097223-10							
0050	Aluminum foil	1	Pape	275	.029	S.F.		1.07	1.40		2.47	3.2
0100	Copper sheets, .025" thick, vinyl backing			240	.033			5.70	1.60		7.30	8.6
0300	Phenolic backing			240	.033			7.40	1.60		9	10.5
2400	Gypsum-based, fabric-backed, fire resistant											
2500	for masonry walls, 21 oz./S.Y.	1	Pape	800	.010	S.F.		.89	.48		1.37	1.6
2700	Small quantities			640	.013			.89	.60		1.49	1.8
3700	Wallpaper, average workmanship, solid pattern, low cost paper			640	.013			.60	.60		1.20	1.5
3900	Basic patterns (matching required), avg. cost paper			535	.015			1.35	.72		2.07	2.5
4000	Paper at \$85 per double roll, quality workmanship			435	.018			2.34	.88		3.22	3.8

09 74 Flexible Wood Sheets

09 74 16 – Flexible Wood Veneers

09 74 16.10 Veneer, Flexible Wood

0010	VENEER, FLEXIBLE WOOD											
0100	Flexible wood veneer, 1/32" thick, plain woods	1	Pape	100	.080	S.F.		2.55	3.84		6.39	8.5
0110	Exotic woods		"	95	.084	"		3.85	4.05		7.90	10.2

09 77 Special Wall Surfacing

09 77 30 – Fiberglass Reinforced Panels

09 77 30.10 Fiberglass Reinforced Plastic Panels

0010	FIBERGLASS REINFORCED PLASTIC PANELS , .090" thick											
0020	On walls, adhesive mounted, embossed surface	2	Carp	640	.025	S.F.		1.50	1.41		2.91	3.7
0030	Smooth surface			640	.025			1.97	1.41		3.38	4.2
0040	Fire rated, embossed surface			640	.025			3	1.41		4.41	5.4
0050	Nylon rivet mounted, on drywall, embossed surface			480	.033			1.50	1.88		3.38	4.4
0060	Smooth surface			480	.033			2.06	1.88		3.94	5.0
0070	Fire rated, embossed surface			480	.033			2.50	1.88		4.38	5.5
0080	On masonry, embossed surface			320	.050			1.41	2.82		4.23	5.7
0090	Smooth surface			320	.050			1.77	2.82		4.59	6.1
0100	Fire rated, embossed surface			320	.050			2.50	2.82		5.32	6.9
0110	Nylon rivet and adhesive mounted, on drywall, embossed surface			240	.067			1.63	3.75		5.38	7.4
0120	Smooth surface			240	.067			1.73	3.75		5.48	7.5
0130	Fire rated, embossed surface			240	.067			2.81	3.75		6.56	8.7
0140	On masonry, embossed surface			190	.084			1.63	4.74		6.37	8.8
0150	Smooth surface			190	.084			1.73	4.74		6.47	8.9
0160	Fire rated, embossed surface			190	.084			2.81	4.74		7.55	10.1
0170	For moldings, add	1	Carp	250	.032	L.F.		.30	1.80		2.10	3.0
0180	On ceilings, for lay in grid system, embossed surface			400	.020	S.F.		1.50	1.13		2.63	3.3
0190	Smooth surface			400	.020			1.97	1.13		3.10	3.8
0200	Fire rated, embossed surface			400	.020			3	1.13		4.13	4.9