

8 12 Metal Frames

8 12 13 - Hollow Metal Frames

8 12 13.13 Standard Hollow Metal Frames		Crew	Daily Output	Labor-Hours	Unit	Material	2022 Bare Costs		Total	Total Incl O&P
							Labor	Equipment		
00	For "A" label use same price as "B" label									
00	For baked enamel finish, add					30%	15%			
00	For galvanizing, add					20%				
00	For hospital stop, add				Ea.	284			284	315
20	For hospital stop, stainless steel, add				"	156			156	172
00	Transom lite frames, fixed, add	2 Carp	155	103	S.F.	60	5.80		65.80	74.50
00	Movable, add	"	130	123	"	80.50	6.95		87.45	99

8 12 13.25 Channel Metal Frames

10	CHANNEL METAL FRAMES										
20	Steel channels with anchors and bar stops										
00	6" channel @ 8.2#/L.F., 3' x 7' door, weighs 150#	G	E-4	13	2.462	Ea.	295	153	11.35	459.35	575
00	8" channel @ 11.5#/L.F., 6' x 8' door, weighs 275#	G		9	3.556		540	222	16.40	778.40	955
00	8' x 12' door, weighs 400#	G		6.50	4.923		785	305	22.50	1,112.50	1,375
00	10" channel @ 15.3#/L.F., 10' x 10' door, weighs 500#	G		6	5.333		980	335	24.50	1,339.50	1,600
00	12' x 12' door, weighs 600#	G		5.50	5.818		1,175	365	27	1,567	1,900
00	12" channel @ 20.7#/L.F., 12' x 12' door, weighs 825#	G		4.50	7.111		1,625	445	33	2,103	2,500
00	12' x 16' door, weighs 1000#	G		4	8		1,975	500	37	2,512	2,950
00	For frames without bar stops, light sections, deduct						15%				
00	Heavy sections, deduct						10%				

8 13 Metal Doors

8 13 13 - Hollow Metal Doors

8 13 13.13 Standard Hollow Metal Doors

STANDARD HOLLOW METAL DOORS		R081313-20									
Flush, full panel, hollow core											
When noted doors are prepared but do not include glass or louvers											
20	1-3/8" thick, 20 ga., 2'-0" x 6'-8"	G	2 Carp	20	.800	Ea.	525	45		570	640
40	2'-8" x 6'-8"	G		18	.889		485	50		535	610
60	3'-0" x 6'-8"	G		17	.941		535	53		588	670
00	3'-0" x 7'-0"	G		17	.941		540	53		593	675
20	For vision lite, add						310			310	340
40	For narrow lite, add						42			42	46
20	Half glass, 20 ga., 2'-0" x 6'-8"	G	2 Carp	20	.800		860	45		905	1,000
40	2'-8" x 6'-8"	G		18	.889		900	50		950	1,075
60	3'-0" x 6'-8"	G		17	.941		860	53		913	1,025
00	3'-0" x 7'-0"	G		17	.941		870	53		923	1,025
10	1-3/8" thick, 18 ga., 2'-0" x 6'-8"	G		20	.800		705	45		750	840
20	3'-0" x 6'-8"	G		17	.941		420	53		473	545
25	3'-0" x 7'-0"	G		17	.941		550	53		603	685
50	For vision lite, add						310			310	340
52	For narrow lite, add						42			42	46
60	Half glass, 18 ga., 2'-0" x 6'-8"	G	2 Carp	20	.800		955	45		1,000	1,125
65	2'-8" x 6'-8"	G		18	.889		990	50		1,040	1,150
70	3'-0" x 6'-8"	G		17	.941		965	53		1,018	1,125
75	3'-0" x 7'-0"	G		17	.941		805	53		858	965
00	Hollow core, 1-3/4" thick, full panel, 20 ga., 2'-8" x 6'-8"	G		18	.889		550	50		600	680
20	3'-0" x 6'-8"	G	2 Carp	17	.941	Ea.	550	53		603	685
40	3'-0" x 7'-0"	G		17	.941		560	53		613	695
80	4'-0" x 7'-0"	G		15	1.067		760	60		820	925
00	4'-0" x 8'-0"	G		13	1.231		915	69.50		984.50	1,100
00	18 ga., 2'-8" x 6'-8"	G		17	.941		650	53		703	795