33 52 Hydrocarbon Transmission and Distribution 33 52 16 - Gas Hydrocarbon Piping

22 50 1	6.23 Medium Density Polyethylene Piping	Crow	Daily Output	Labor-	Unit	tt-ti-l	2022 Bare		Tatal	Total
6616	2" IPS diameter	Crew B-20	16.67	1.440	Ea.	Material 175	Labor E	quipment	Total 248	Incl 0&P 300
6618	SDR 11.5, 1" CTS diameter		18.67	1.286	Lu.	69.50	65		134.50	174
6620	SDR 12.5, 1" CTS diameter	2 1		1.286	1	72	65		137.30	177
8100	Fittings, accessories	, ,	10.07	1.200		12	0.3		107	1//
8105	SDR 11, IPS unless noted CTS									
8110	Protective sleeves, for high volume tapping tees, butt fusion outlets	11 Skwk	16	.500	Ea.	6.65	29.50		36.15	51.50
8120	For tapping tees, socket outlets, CTS, 1/2" diameter		18	.444	[]	1.73	26		27.73	41.50
8122	1" diameter		18	.444		3.06	26		29.06	43
8124 [IPS, 1/2" diameter		18	.444		2.39	26		28.39	42
8126	3/4" diameter	; -	18	444		3.06	26		29.06	43
8128	1" diameter		18	.444		4.17	26		30.17	44
8130	1-1/4" diameter		. 18	.444		5.25	26		31.25	45.50
8205	Tapping tee test caps, type I, yellow PE cap, "aldyl style"	1.	45	.178		54	10.45		64.45	74.50
8210	Type II, yellow polyethylene cap	11	45	.178		55	10.45		65.45	75.50
8215	High volume, yellow polyethylene cap	1	45	.178		69	10.45		79.45	91.50
8250	Quick connector, female x female inlets, 1/4" N.P.T.	1	50	.160		22.50	9.40		31.90	39
8255	Test hose, 24" length, 3/8" ID, male outlets, 1/4" N.P.T.		50	.160		31	9.40		40.40	48
8260	Quick connector and test hose assembly	1	50	.160	4	54	9.40		63.40	73
8305	Purge point caps, butt fusion, SDR 10, 1-1/4" diameter	B-22C	27	.593	Ea.	39	31	9.25	79.25	99
8310	SDR 11, 1-1/4" diameter	1	27	.593	1 :	39	31	9.25	79.25	99
8315	2" diameter		24	.667		39.50	35	10.40	84.90	107
8320	3" diameter	11	24	.667	1 1	54.50	35	10.40	99.90	123
8325	4" diameter	1.1	18	.889		53.50	46.50	13.85	113.85	144
8340	Socket fusion, SDR 11, 1-1/4" diameter		27	.593	.	9.75	31	9.25	50	67.50
8345	2" diameter	11	24	.667		11.70	35	10.40	57.10	76.50
8350	3" diameter		- 24	.667		71.50	35	10.40	116.90	142
8355	4" diameter	: 1	18	.889		52.50	46.50	13.85	112.85	143
8360	Purge test quick connector, female x female inlets, 1/4" N.P.T.	-1 Skwk	50	.160		22.50	9.40		31.90	39
8365	Purge test hose, 24" length, 3/8" ID, male outlets, 1/4" N.P.T.	: 1	50	.160		31	9.40		40.40	48
8370	Purge test quick connector and test hose assembly	[]	50	.160		54	9.40		63.40	73
8405	Transition fittings, MDPE x zinc plated steel, SDR 7, 1/2" CTS x 1/2" MPT	B-22C	30	.533		30	28	8.30	66.30	83.50
8410	SDR 9.3, 1/2" IPS x 3/4" MPT	İ	28.50	.561		46.50	29.50	8.75	84.75	105
8415	SDR 10, 1-1/4" IPS x 1-1/4" MPT		27	.593		44.50	31	9.25	84.75	106
8420	SDR 11, 3/4" IPS x 3/4" MPT		28.50	.561		23.50	29.50	8.75	61.75	79.50
8425	1" IPS x 1" MPT		27	.593		29	31	9.25	69.25	88.50
8430	1-1/4" IPS x 1-1/4" MPT	: 1	17	.941		54	49	14.65	117.65	149
8435	1-1/2" IPS x 1-1/2" MPT	1 1	25.50	.627		55.50	33	9.75	98.25	121
8440	2" IPS x 2" MPT	11	24	.667	1 1	63	35	10.40	108.40	133
8445	SDR 11.5, 1" CTS x 1" MPT :	1	28	.571	+ 1	39	30	8.90	77.90	97.50

33 3	2 16.26 High Density Polyethylene Piping									
2010	HIGH DENSITY POLYETHYLENE PIPING									
2020	ASTM D2513, not including excavation or backfill									
2200	Butt fused pipe									
2205	125psi coils, butt fusion joint @ 100', 1/2" CTS diameter, SDR 7	B-220	2050	.008	L.F.	.16	.41	.12	.69	.92
2210	160psi coils, butt fusion joint @ 100', IPS 1/2" diameter, SDR 9		1950	.008	,	.21	.43	.13]	.77	1.01
2215	3/4" diameter, SDR 11		1950	.008		.31	.43	.13	.87	1.12
2220	1" diameter, SDR 11	1 1	1850	.009		.51	.45	.13	1.09	1.39
2225	1-1/4" diameter, SDR 11		1850	.009		.75	.45	.13	1.33	1.66
2230	1-1/2" diameter, SDR 11		1750	.009		1.40	.48	.14	2.02	2.41
2235	2" diameter, SDR 11		1750	.009		1.14	.48	.14	1.76	2.12
2240	3" diameter, SDR 11	1 +	1650	.010		1.88	.51	.15	2.54	3
2245	160psi 40' lengths, butt fusion joint, IPS 3" diameter, SDR 11	B-22A	660	.061		2.04	3.16	.99	6.19	8.05