05 42 Cold-Formed Metal Joist Framing

05 42 13 -	Cold-Forme	d Metal	Floor Jois	t Framing
------------	------------	---------	------------	-----------

				Daily	Labor-			2022 Bai	re Costs	1	Total
05 42	13.30 Framing, Boxed Headers/Beams		Crew	Output	Hours	Unit	Material	Labor	Equipment	Total	Incl O&P
0410	12" deep	G	2 Corp	130	.123	L.F.	10.45	6.95		17.40	22
0500	12 ga. x 10" deep	G		110	.145	1.	12.55	8.20		20.75	26
0510	12" deep	G		100	.160		13.90	9		22.90	28.50
1210	Triple, 18 ga. x 8" deep	G		170	.094		8.55	5.30		13.85	17.30
1220	10" deep	G		165	.097		10.30	5.45		15.75	19.50
1230	12" deep	G		160	.100	-	11.30	5.65		16.95	21
1300	16 ga. x 8" deep	G	2 Carp	145	.110	L.F.	9.90	6.20		16.10	20
1310	10" deep	G		140	.114		11.60	6.45		18.05	22.50
1320	12" deep	G		135	.119		12.65	6.65		19.30	24
1400	14 ga. x 10" deep	G		115	.139		13.75	7.85		21.60	27
1410	12" deep	G		110	.145		15.15	8.20		23.35	29
1500	12 ga. x 10" deep	G		90	.178		18.30	10		28.30	35
1510	12" deep	G	1 +	85	.188	+	20.50	10.60		31.10	38.50

05 42 13.40 Framing, Joists

0010 FRAMING, JOISTS, no band joists (track), web stiffeners, headers,

0020	Beams, bridging or bracing						
0025	Made from recycled materials						
0030	Joists (2" flange) and fasteners, materials only						
0220	18 ga. x 6" deep	G		L.F.	1.84	1.84	2.02
0230	8" deep	G			1.94	1.94	2.14
0240	10" deep	G			2.31	2.31	2.54
0320	16 ga. x 6" deep	G			1.98	1.98	2.18
0330	8" deep	G			2.43	2.43	2.67
0340	10" deep	G			2.77	2.77	3.05
0350	12" deep	G			3.13	3.13	3.44
0430	14 ga. x 8" deep	G			3.06	3.06	3.36
0440	10" deep	G			3.52	3.52	3.87
0450	12" deep	G			4	4	4.40
0540	12 ga. x 10" deep	G			5.10	5.10	5.60
0550	12" deep	G		+	5.80	5.80	6.40
1010	Installation of joists to band joists, beams & headers, labor only						
1220	18 ga. x 6" deep			Ea.	8.20	8.20	12.20
1230	8" deep		90178		10	10	14.90
1240	10" deep		80200	1	11.25	11.25	16.75
1320	16 ga. x 6" deep		95 .168		9.50	9.50	14.10
1330	8" deep		70 .229		12.85	12.85	19.15
1340	10" deep		60 .267		15	15	22.50
1350	12" deep		55 .291		16.40	16.40	24.50
1430	14 ga. x 8" deep		65 .246		13.85	13.85	20.50
1440	10" deep		45 .356		20	20	30

05 42 13.45 Framing, Web Stiffeners

12" deep

12 ga. x 10" deep

12" deep

1450

1540

0010	FRAMING, WEB STIFFENERS at joist bearing, fabricated from									
0020	Stud piece (1-5/8" flange) to stiffen joist (2" flange)									
0025	Made from recycled materials									
2120	For 6" deep joist, with 18 ga. x 2-1/2" stud	G	1 Carp	120	.067	Ea.	.78	3.75	4.53	6.45
2130	3-5/8" stud	G		110	.073		.93	4.09	5.02	7.10
2140	4" stud	G		105	.076		.97	4.29	5.26	7.45
2150	6" stud	G		100	.080		1.22	4.50	5.72	8.05
2160	8" stud	G		95	.084		1.63	4.74	6.37	8.85

35

40

30

.457

.400

.533

38.50

33.50

44.50

25.50

22.50

30

25.50

22.50

30