

07 24 Exterior Insulation and Finish Systems

07 24 13 – Polymer-Based Exterior Insulation and Finish System

07 24 13.10 Exterior Insulation and Finish Systems		Crew	Daily Output	Labor-Hours	Unit	Material	2022 Bare Costs		Total	Total Incl O&P
							Labor	Equipment		
0150	Heavy duty reinforcement add	J-1	914	.044	S.F.	.60	2.15	.12	2.87	4
0160	2.5#/S.Y. metal lath substrate add	1 Lath	75	.107	S.Y.	5.05	5.95		11	14.2
0170	3.4#/S.Y. metal lath substrate add	"	75	.107	"	5.15	5.95		11.10	14.4
0180	Color or texture change	J-1	1265	.032	S.F.	.76	1.56	.09	2.41	3.2
0190	With substrate leveling base coat	1 Plas	530	.015		.87	.78		1.65	2
0210	With substrate sealing base coat	1 Pord	1224	.007		.14	.31		.45	.6
0370	V groove shape in panel face				L.F.	.74			.74	.8
0380	U groove shape in panel face				"	.89			.89	.9
0440	For higher than one story, add								25%	

07 25 Weather Barriers

07 25 10 – Weather Barriers or Wraps

07 25 10.10 Weather Barriers

0010	WEATHER BARRIERS									
0400	Asphalt felt paper, #15	1 Carp	37	.216	Sq.	4.43	12.15		16.58	23
0401	Per square foot	"	3700	.002	S.F.	.04	.12		.16	.2
0450	Housewrap, exterior, spun bonded polypropylene									
0470	Small roll	1 Carp	3800	.002	S.F.	.14	.12		.26	.3
0480	Large roll	"	4000	.002	"	.06	.11		.17	.2
2100	Asphalt felt roof deck vapor barrier, class 1 metal decks	1 Rofc	37	.216	Sq.	19.85	10.70		30.55	39.9
2200	For all other decks	"	37	.216		15.40	10.70		26.10	34.5
2800	Asphalt felt, 50% recycled content, 15 lb., 4 sq./roll	1 Carp	36	.222		5.70	12.50		18.20	25
2810	30 lb., 2 sq./roll	"	36	.222		12.75	12.50		25.25	32.5
3000	Building wrap, spun bonded polyethylene	2 Carp	8000	.002	S.F.	.18	.11		.29	.3

07 26 Vapor Retarders

07 26 13 – Above-Grade Vapor Retarders

07 26 13.10 Vapor Retarders

0010	VAPOR RETARDERS									
0020	Aluminum and kraft laminated, foil 1 side	G	1 Carp	37	.216	Sq.	12	12.15	24.15	31.5
0100	Foil 2 sides	G		37	.216		17.55	12.15	29.70	37.5
0600	Polyethylene vapor barrier, standard, 2 mil	G		37	.216		2	12.15	14.15	20.5
0700	4 mil	G		37	.216		4.40	12.15	16.55	23
0900	6 mil	G		37	.216		6	12.15	18.15	24.5
1200	10 mil	G		37	.216		8.15	12.15	20.30	27
1300	Clear reinforced, fire retardant, 8 mil	G		37	.216		25.50	12.15	37.65	46
1350	Cross laminated type, 3 mil	G		37	.216		12.30	12.15	24.45	31.5
1400	4 mil	G		37	.216		13.65	12.15	25.80	33
1800	Reinf. waterproof, 2 mil polyethylene backing, 1 side			37	.216		11.50	12.15	23.65	31
1900	2 sides			37	.216		14.50	12.15	26.65	34
2400	Waterproofed kraft with sisal or fiberglass fibers			37	.216		18.05	12.15	30.20	38