Distributed Information Processing

8th Lecture

Eom, Hyeonsang (엄현상)
Department of Computer Science & Engineering
Seoul National University

©Copyrights 2026 Eom, Hyeonsang All Rights Reserved

Outline

- Distributed Shared Memory
  - Introduction
  - Memory Consistent Models
  - Memory Coherence
  - Other Consistency Models
    - Weak Consistency
    - Release Consistency
    - Entry Consistency
- Q&A

Distributed Shared Memory (DSM)

- Definition
  - Sharing Data between Processors That Do Not Share Physical Memory

Figure 18.1 on Page 750

- Comparison with Message Passing
  - No Marshalling
  - Normal Synchronization
  - Possibly Comparable Efficiency

Marshalling: Structured Data Items & Values -> External Data Representation

DSM (Cont'd)

- Implementation Approaches
  - Hardware
    - E.g., Dash Multiprocessor (64 Nodes in a NUMA)
  - Paged Virtual Memory
    - E.g., IVY
  - (Platform-Independent) Middleware
    - E.g., Linda (Collection of Immutable Data Items)

Implementing DSM as a Region in the Same Address Space of Every Process

The Page-Based Approach Is Flexible (Enabling Shared-Memory Programs to Run on Distributed-Memory Machines) Because No Particular Structure on DSM Is Required.

Memory Consistency Model

- Model Specifying the Consistency Guarantees about the Values of Read Objects
  - With Copies of Objects Read and Objects Updated by Processes

Figure 18.3 on Page 757

Could the Combination ar=0 and br=1 Occur ?

Consistency Models

- Linearizability
  - L1: R(x)a ⇒ Either W(x)a before It Or No Write before It If a Is the Initial Value of x
  - The Order Is Consistent with the Real Times
- Sequential Consistency
  - L1 & the Order Is Consistent with the Program (Execution) Order

R(x)a: a read of val. a from var. x
W(x)b: a write of val. b to var. x

Figure 18.3 on Page 757

The Combination ar=0 and br=1 Coud Not Occur Under Sequential Consistency

Consistency Models (Cont'd)

- Causal Consistency
  - Read Value Is Consistent with the Happened-before Relationship
- Illustration: Distinction between Sequential & Causal Consistency

P1: W(x)a
P2: W(x)b
P3: R(x)a R(x)b
P4: R(x)b R(x)a

→Time

The Sequence Is Causally-Consistent, But Not Sequentially-Consistent

Consistency Models (Cont'd)

- FIFO or Pipelined RAM Consistency
  - Order of Writes Issued by any Given Processes Is Consistent
- Illustration: Distinction between Causal & FIFO Consistency

P1: W(x)a

P2: R(x)a W(x)b W(x)c

P3: R(x)b R(x)a R(x)c

P4: R(x)a R(x)b R(x)c

→Time

The Sequence Is FIFO-Consistent, But Not Causal-Consistent

Summary of Consistency Models

Models Not Using Synchronization Operations

Consistency	Description
Strict	Absolute time ordering of all shared accesses matters.
Linearizability	All processes must see all shared accesses in the same order. Accesses are furthermore ordered according to a (nonunique) global timestamp
Sequential	All processes see all shared accesses in the same order. Accesses are not ordered in time
Causal	All processes see causally-related shared accesses in the same order.
FIFO	All processes see writes from each other in the order they were used. Writes from different processes may not always be seen in that order

Memory Coherence

- Sequential Consistency on a Location-by-Location Basis
  - Agreement on the Order of Writes to the Same Location without Necessarily Agreeing on the Order of Writes

Update Options

Inexpensive Reads

- Write-Update/Broadcast: Multicast of Local Updates
  - Multiple-Reader/Multiple-Writer Sharing
    - Achieving Sequential Consistency w/ totally ordered (blocking) multicast
- Write-Invalidate: Acknowledged Invalidation of Copies before the Write
  - Multiple-Reader/Single-Writer Sharing
    - Achieving Sequential Consistency

More Suited to Page-Based DSM

Other Consistency Models

- Weak Consistency (WC)
  - Accesses to Synch Vars for a Data Store Are Sequentially Consistent
  - Operations on a Synch Var Are Performed after All Previous Writes Have Completed
  - Operations Are Performed after All Previous Operations on Synch Vars Have Been Performed

A Single Operation S Synchronizes All Its Copies of the Data Store

Weak Consistency Enforces Consistency on a Group of Operations

Other Consistency Models

- Illustration: Valid vs Invalid WC Sequences

P1: W(x)a W(x)b S

P2: R(x)a R(x)b S

P3: R(x)b R(x)a S

Valid WC Sequence

→Time

P1: W(x)a W(x)b S

P2: S R(x)a

Invalid WC Sequence

Synchronization Accesses

- Characteristics
  - Concurrency
  - At Least One Write
- Types
  - *Acquire*(int &lock): // Call by Ref

```
while (testAndSet(lock)=1)
  skip;
```

The Function Sets the Lock to 1 and Returns 0 If It Is 0; Otherwise, It Returns 1

  - *Release*(int &lock): // Call by Ref

```
lock := 0;
```

Other Consistency Models

- Release Consistency (RC)
  - *Acquire* and *Release* Operations Are Sequentially Consistent
  - *Release* Operations Are Performed after All Previous Operations Have Completed
  - Operations Are Performed after All Previous *Acquire* Operations Have Been Performed

Acquire as Entering a Critical Section and Release as Leaving a Critical Section

Once a Release Has Occurred, Another Process Acquiring a Lock Can Read Only Data Modified by the Process Performing the Release

Other Consistency Models

- Illustration: Processes under RC

The Critical Sections Enforce Consistency: a=b=0 or a=b=1

```
Process 1:
    Acquire ();          // enter the critical section
    a := a + 1;
    b := b + 1;
    Release ();          // leave the critical section
Process 2:
    Acquire ();          // enter the critical section
    print ("a = ", a, "; b = ", b);
    Release ();          // leave the critical section
```

No Blocking Up to This Point: It Is When Communication Is Required

The Programmer or a Compiler Is Responsible for Labeling Reads and Writes as Releases or Acquires

Other Consistency Models

- Implementation: Lazy RC (in Contrast to the Eager RC)
  - Communication Is Delayed until the Next-Acquire Time
    - Saving the network bandwidth
- Issue: False Sharing
  - Having Data Belonging to Two Independent Processes in the Same Page with at Least One Writing Process
    - Single-Writer vs Multiple-Writer Protocols

Leading to Unnecessary Communication

Other Consistency Models

- Entry Consistency (Associating Shared Data with Synch Vars)
  - First Acquire Makes the Latest Values Visible
  - Write Requires Entering the Critical Section
  - Multiple Reads May Be Performed after the Writer Has Left It

This Avoids the Tendency to False Sharing at the Expense of Increased Programming Complexity: e.g., Midway

- Illustration: Valid Entry Consistency Sequence

P1: Acq(x) W(x) a Acq(y) W(y) b Rel(x) Rel(y)

P2: R(y) NIL Acq(x) R(x) a

P3: Acq(y)

Summary of Consistency Models

Models Using Synchronization Operations

Consistency	Description
Weak	Shared data can be counted on to be consistent only after a synchronization is done
Release	Shared data are made consistent when a critical region is exited
Entry	Shared data pertaining to a critical region are made consistent when a critical region is entered.