

# PROGRAMMING LANGUAGES:

## IMPERATIVE PROGRAM CONSTRUCTION

### 6. LOOP CONSTRUCTION II: STRENGTHENING THE INVARIANT

---

Shin-Cheng Mu

Autumn. 2021

National Taiwan University and Academia Sinica

## MAXIMUM SEGMENT SUM

---

A classical problem: given an array of integers, find largest possible sum of a consecutive segment.

`con  $N : \text{Int}$   $\{0 \leq N\}$`

`con  $f : \text{array } [0..N)$  of  $\text{Int}$`

`$S$`

`$\{r = \langle \uparrow p\ q : 0 \leq p \leq q \leq N : \text{sum } p\ q \rangle\}$`

where  `$\text{sum } p\ q = \langle \sum i : p \leq i < q : f[i] \rangle$` .

## DETAILS THAT MATTER

- Note the use of  $\leq$  and  $<$  in the specification.
- The range in  $\text{sum } p \ q$  is  $p \leq i < q$ . It computes the sum of  $f[p..q)$  — not including  $f[q]$ !
- Therefore when  $p = q$ ,  $\text{sum } p \ q$  computes the sum of an empty segment.
- In the postcondition we have  $p \leq q$  — we allow empty segments in our solution!
- We must have  $q \leq N$  instead of  $q < N$ . Otherwise segments containing the rightmost element would not be valid solutions.

## PREVIOUSLY INTRODUCED TECHNIQUES

- Replace  $N$  by  $n$ . Use  $P \wedge Q$  as the invariant, where

$$\begin{aligned} P &\equiv r = \langle \uparrow p \ q : 0 \leq p \leq q \leq n : \text{sum } p \ q \rangle , \\ Q &\equiv 0 \leq n \leq N . \end{aligned}$$

- Use  $\neg (n = N)$  as guard. This way we immediately have that  $P \wedge Q \wedge n = N$  imply the desired postcondition.
- How do we know we want  $0 \leq n \leq N$ ? It can be forced by our development later. But let's expedite the pace.
- Initialisation:  $n, r := 0, 0$ .
- Use  $N - n$  as the bound.
- To decrease the bound, let  $n := n + 1$  be the last statement of the loop.

We get this program.

```
con  $N : \text{Int}$   $\{0 \leq N\}$   
con  $f : \text{array } [0..N)$  of  $\text{Int}$   
var  $r, n : \text{Int}$   
  
 $r, n := 0, 0$   
 $\{P \wedge Q, bnd : N - n\}$   
do  $n \neq N \rightarrow ??? ; n := n + 1$  od  
 $\{r = \langle \uparrow p \ q : 0 \leq p \leq q \leq N : \text{sum } p \ q \rangle\}$ 
```

Now we need to construct the `???` part.

## CONSTRUCTING THE LOOP BODY

How to construct the ??? part?

$$\{P \wedge Q \wedge n \neq N\}$$

???

$$\{(P \wedge Q)[n \setminus n + 1]\}$$
$$n := n + 1$$
$$\{P \wedge Q\}$$

## EXAMINING THE EXPRESSION

To reason about  $P[n \setminus n + 1]$ , we calculate (assuming  $P \wedge Q \wedge n \neq N$ ):

$$\begin{aligned} & \langle \uparrow p \ q : 0 \leq p \leq q \leq n : \text{sum } p \ q \rangle [n \setminus n + 1] \\ &= \langle \uparrow p \ q : 0 \leq p \leq q \leq n + 1 : \text{sum } p \ q \rangle \\ &= \{ \text{split off } q = n + 1, \text{ see next slide} \} \\ & \quad \langle \uparrow p \ q : 0 \leq p \leq q \leq n : \text{sum } p \ q \rangle \uparrow \\ & \quad \langle \uparrow p : 0 \leq p \leq (n + 1) : \text{sum } p \ (n + 1) \rangle \\ &= \{ P_0 \} \\ & \quad r \uparrow \langle \uparrow p : 0 \leq p \leq (n + 1) : \text{sum } p \ (n + 1) \rangle . \end{aligned}$$



Therefore we wish to update  $r$  by:

$$r := r \uparrow \langle \uparrow p : 0 \leq p \leq (n+1) : \text{sum } p (n+1) \rangle .$$

But  $\langle \uparrow p : 0 \leq p \leq (n+1) : \text{sum } p (n+1) \rangle$  cannot be computed in one step!

We could compute  $\langle \uparrow p : 0 \leq p \leq (n+1) : \text{sum } p (n+1) \rangle$  in a loop...or can we store it in another variable?

## SPLITTING OFF?

Regarding the step “split off  $q = n + 1$ ”:

$$\begin{aligned} & 0 \leq p \leq q \leq n + 1 \\ &= 0 \leq p \leq q \wedge q \leq n + 1 \\ &= 0 \leq p \leq q \wedge (q \leq n \vee q = n + 1) \\ &= (0 \leq p \leq q \wedge q \leq n) \vee (0 \leq p \leq q \wedge q = n + 1) \\ &= 0 \leq p \leq q \leq n \vee (0 \leq p \leq q \wedge q = n + 1) . \end{aligned}$$

Note that for the second step to be valid, we need  $-1 \leq n$  (which is implied by  $0 \leq n \leq N$ ). Always remember to check that the range is non-empty before you split!

Therefore we have (abbreviating  $\text{sum}...$  to  $R$ ):

$$\begin{aligned} & \langle \uparrow p \ q : 0 \leq p \leq j \leq n+1 : R \rangle \\ = & \{ \text{previous calculation} \} \\ & \langle \uparrow p \ q : 0 \leq p \leq q \leq n \vee (0 \leq p \leq q \wedge q = n+1) : R \rangle \\ = & \{ \text{range split (8.16)} \} \\ & \langle \uparrow p \ q : 0 \leq p \leq q \leq n : R \rangle \uparrow \\ & \quad \langle \uparrow p \ q : 0 \leq p \leq q \wedge q = n+1 : R \rangle \\ = & \{ \text{one-point rule} \} \\ & \langle \uparrow p \ q : 0 \leq p \leq q \leq n : R \rangle \uparrow \\ & \quad \langle \uparrow p : 0 \leq p \leq n+1 : R \rangle . \end{aligned}$$

## Things to note:

- Calculation for other patterns of ranges (e.g.  $0 \leq p \leq q \leq n + 1$ ) are slightly different. Watch out!
- In practice, the “splitting off” step is but one quick step. We do not do the reasoning above in such detail.
- We show you the details above for expository purpose.
- In other problems we may see slightly different ranges, such as  $0 \leq p < q < n + 1$ . The result of splitting is different too. Take extra care!

## STRENGTHENING THE INVARIANT

Knowing that we need to update  $r$  with  $\langle \uparrow p : 0 \leq p \leq (n + 1) : \text{sum } p (n + 1) \rangle$ , let us store it in some variable! Introduce a new variable  $s$ , and *strengthen* the invariant to  $P_0 \wedge P_1 \wedge Q$ , where

$$P_0 \equiv r = \langle \uparrow p \ q : 0 \leq p \leq q \leq n : \text{sum } p \ q \rangle ,$$

$$P_1 \equiv s = \langle \uparrow p : 0 \leq p \leq n : \text{sum } p \ n \rangle ,$$

$$Q \equiv 0 \leq n \leq N .$$

## MAXIMUM SUFFIX SUM

- That is, while  $r$  is the maximum *segment* sum so far,  $s$  is the maximum *suffix* sum so far.
- We discover the need of this concept through symbolic calculation.
- This is a pattern for many “segment problems”: *to solve a problem about segments, solve a suffix problem for all prefixes.*

Q: Why don't we let  $s = \langle \uparrow p : 0 \leq p \leq n + 1 : \text{sum } p (n + 1) \rangle$ ?

A: You can do that too! Left as an exercise. We use  $n$  instead of  $n + 1$  to keep the invariant looking simple.

## CONSTRUCTING THE LOOP BODY

Therefore, a possible strategy would be:

$$\{P_0 \wedge P_1 \wedge 0 \leq n \leq N \wedge n \neq N\}$$

$$s := ???$$

$$\{P_0 \wedge P_1[n \setminus n+1] \wedge 0 \leq n+1 \leq N\}$$

$$r := r \uparrow s$$

$$\{(P_0 \wedge P_1 \wedge 0 \leq n \leq N)[n \setminus n+1]\}$$

$$n := n + 1$$

$$\{P_0 \wedge P_1 \wedge 0 \leq n \leq N\}$$

## UPDATING THE PREFIX SUM

Recall  $P_1 \equiv s = \langle \uparrow p : 0 \leq p \leq n : \text{sum } p \ n \rangle$ .

$$\begin{aligned} & \langle \uparrow p : 0 \leq p \leq n : \text{sum } p \ n \rangle [n \setminus n + 1] \\ &= \langle \uparrow p : 0 \leq p \leq n + 1 : \text{sum } p \ (n + 1) \rangle \\ &= \{ \text{splitting off } p = n + 1 \} \\ & \quad \langle \uparrow p : 0 \leq p \leq n : \text{sum } p \ (n + 1) \rangle \uparrow \\ & \quad \text{sum } (n + 1) \ (n + 1) \\ &= \{ [n + 1..n + 1] \text{ is an empty range} \} \\ & \quad \langle \uparrow p : 0 \leq p \leq n : \text{sum } p \ (n + 1) \rangle \uparrow 0 \\ &= \{ \text{splitting off } i = n \text{ in sum} \} \\ & \quad \langle \uparrow p : 0 \leq p \leq n : \text{sum } p \ n + f[n] \rangle \uparrow 0 \\ &= \{ \text{distributivity} \} \\ & \quad (\langle \uparrow p : 0 \leq p \leq n : \text{sum } p \ n \rangle + f[n]) \uparrow 0 . \end{aligned}$$

Thus,  $\{P_1\} s := ? \{P_1[n \setminus n + 1]\}$  is satisfied by  $s := (s + f[n]) \uparrow 0$ .



## A KEY PROPERTY

- The last step labelled “distributivity” uses a rule mentioned before: provided that  $\neg occurs(i, F)$  and  $R$  non-empty:

$$F + \langle \uparrow i : R : S \rangle = \langle \uparrow i : R : F + S \rangle$$

$$F + \langle \downarrow i : R : S \rangle = \langle \downarrow i : R : F + S \rangle .$$

- The rules are valid because addition distributes into maximum/minimum:

$$x + (y \uparrow z) = (x + y) \uparrow (x + z) ,$$

$$x + (y \downarrow z) = (x + y) \downarrow (x + z) .$$

- That is the key property that allows us to have an efficient algorithm for the maximum segment sum problem!
- Through calculation, we not only have an algorithm, but also identified the key property that makes it work, which 16 / 33

## DERIVED PROGRAM

```
con  $N : \text{Int } \{0 \leq N\}$   
con  $f : \text{array } [0..N) \text{ of } \text{Int}$   
var  $r, n : \text{Int}$   
  
 $r, s, n := 0, 0, 0$   
 $\{P_0 \wedge P_1 \wedge Q, bnd : N - n\}$   
do  $n \neq N \rightarrow$   
     $s := (s + f[n]) \uparrow 0$   
     $r := r \uparrow s$   
     $n := n + 1$   
od  
 $\{r = \langle \uparrow p \ q : 0 \leq p \leq q \leq N : \text{sum } p \ q \rangle\}$ 
```

$P_0 \equiv r = \langle \uparrow p \ q : 0 \leq p \leq q \leq n : \text{sum } p \ q \rangle$  ,

$P_1 \equiv s = \langle \uparrow p : 0 \leq p \leq n : \text{sum } p \ n \rangle$  ,

$Q \equiv 0 \leq n \leq N$  .

## “STRENGTHENING”?

- We say that the invariant  $P_0 \wedge P_1 \wedge Q$  is “stronger” than  $P \wedge Q$  because the former promises more.
- The resulting loop computes values for two variables rather than one.
- However, the program ends up being quicker because more results from the previous iteration of the loop can be utilised.
- It is a common phenomena: a generalised theorem is easier to prove.
- We will see another way to generalise the invariant in the rest of the course.

## LESSONS LEARNT?

*Let the symbols do the work!*

- We discover how to strengthen the invariant by calculating and finding out what is missing.
- Expressions are your friend, and blind guessing can be minimised. We always get some clue from the expressions.
- Since we rely only on the symbols, the same calculation/algorithm can be generalised to other problems (e.g. as long as the same distributivity property holds).

If we remove the pre/postconditions and the invariant, can you tell us what the program does?

- Without the assertions, programs mean nothing. The assertions are what matter about the program.
- Structured programming is not about making (the operational parts of) code easier to read/understand.
- Such efforts are bound to end in vain: even a simple three-line loop can be hard to understand if the assertions, encoding the intentions of the programmer, are stripped away.

- Instead, structured programming is about organising the code around the structure of the proofs.
- Once the pre/postconditions are given, and the invariants and bounds are determined, one can derive the code accordingly.
- It is pointless arguing, for example, “using a *break* here makes the code easier to read.”
- One shall not need to “understand” the operational parts of the code, but to check whether it meets the specification.

## NO. OF PAIRS IN AN ARRAY

---

Consider constructing the following program:

```
con  $N : \text{Int}$   $\{0 \leq N\}$ ;  $a : \text{array } [0..N)$  of  $\text{Int}$ 
```

```
var  $r : \text{Int}$ 
```

```
 $S$ 
```

```
 $\{r = \langle \#i\ j : 0 \leq i < j < N : a[i] \leq 0 \wedge a[j] \geq 0 \rangle\}$ 
```



## PREVIOUSLY INTRODUCED TECHNIQUES

- Replace  $N$  by  $n$ . Use  $P \wedge Q$  as the invariant, where

$$P \equiv r = \langle \#i, j : 0 \leq i < j < n : a[i] \leq 0 \wedge a[j] \geq 0 \rangle,$$

$$Q \equiv 0 \leq n \leq N.$$

- Use  $\neg (n = N)$  as guard. This way we immediately have that  $P \wedge Q \wedge n = N$  imply the desired postcondition.
- Initialisation:  $n, r := 0, 0$ .
- Use  $N - n$  as the bound.
- To decrease the bound, let  $n := n + 1$  be the last statement of the loop.

We get this program.

```
con  $N : \text{Int}$   $\{0 \leq N\}$ ;  $a : \text{array } [0..N) \text{ of } \text{Int}$   
var  $r, n : \text{Int}$   
 $r, n := 0, 0$   
 $\{P \wedge Q, \text{bnd} : N - n\}$   
do  $n \neq N \rightarrow \dots; n := n + 1$  od  
 $\{r = \langle \#i\ j : 0 \leq i < j < N : a[i] \leq 0 \wedge a[j] \geq 0 \rangle\}$ 
```

Now we need to construct the  $\dots$  part.

How to construct the ... part?

$$\{P \wedge Q \wedge n \neq N\}$$
$$\dots$$
$$\{(P \wedge Q)[n \setminus n + 1]\}$$
$$n := n + 1$$
$$\{P \wedge Q\}$$

## NO. OF PAIRS IN AN ARRAY

To reason about  $P[n \setminus n + 1]$ , we calculate (assuming  $P \wedge Q \wedge n \neq N$ ):

$$\begin{aligned} & \langle \#i, j : 0 \leq i < j < n + 1 : a[i] \leq 0 \wedge a[j] \geq 0 \rangle \\ = & \{ \text{split off } j = n, \text{ see the next slide} \} \\ & \langle \#i, j : 0 \leq i < j < n : a[i] \leq 0 \wedge a[j] \geq 0 \rangle + \\ & \langle \#i : 0 \leq i < n : a[i] \leq 0 \wedge a[n] \geq 0 \rangle \\ = & \{ P \} \\ & r + \langle \#i : 0 \leq i < n : a[i] \leq 0 \wedge a[n] \geq 0 \rangle \\ = & \begin{cases} r, & \text{if } a[n] < 0; \\ r + \langle \#i : 0 \leq i < n : a[i] \leq 0 \rangle, & \text{if } a[n] \geq 0. \end{cases} \end{aligned}$$

Let us try storing  $\langle \#i : 0 \leq i < n : a[i] \leq 0 \rangle$  in another variable?

## SPLITTING OFF?

For expository purpose let us exam how the splitting was done:

$$\begin{aligned} & 0 \leq i < j < n + 1 \\ &= 0 \leq i < j \wedge j < n + 1 \\ &= 0 \leq i < j \wedge (j < n \vee j = n) \\ &= (0 \leq i < j \wedge j < n) \vee (0 \leq i < j \wedge j = n) \\ &= 0 \leq i < j < n \vee (0 \leq i < j \wedge j = n) . \end{aligned}$$

The second step is valid if  $0 \leq n$ .

## A FREQUENT PATTERN

We may see this pattern often. For some  $\star$ , we need to calculate:

$$\begin{aligned} & \langle \star i j : 0 \leq i < j < n + 1 : R \rangle \\ = & \{ \text{previous calculation} \} \\ & \langle \star i j : 0 \leq i < j < n \vee (0 \leq i < j \wedge j = n) : R \rangle \\ = & \langle \star i j : 0 \leq i < j < n : R \rangle \star \\ & \langle \star i j : 0 \leq i < j \wedge j = n : R \rangle \\ = & \{ \text{one-point rule} \} \\ & \langle \star i j : 0 \leq i < j < n : R \rangle \star \\ & \langle \star i : 0 \leq i < n : R \rangle . \end{aligned}$$

Calculation for other ranges (e.g.  $0 \leq i \leq j \leq n + 1$ ) are slightly different. Watch out!

## STRENGTHENING THE INVARIANT

New plan: define

$$P_0 \equiv r = \langle \#i, j : 0 \leq i < j < n : a[i] \leq 0 \wedge a[j] \geq 0 \rangle,$$

$$P_1 \equiv s = \langle \#i : 0 \leq i < n : a[i] \leq 0 \rangle,$$

$$Q \equiv 0 \leq n \leq N,$$

and try to derive

```
con  $N : \text{Int}$   $\{N \geq 0\}$ ;  $a : \text{array}[0..N)$  of  $\text{Int}$   
var  $r, s : \text{Int}$ 
```

```
 $n, r, s := 0, 0, 0$ 
```

```
 $\{P_0 \wedge P_1 \wedge Q, \text{bnd} : N - n\}$ 
```

```
do  $n \neq N \rightarrow \dots n := n + 1$  od
```

```
 $\{r = \langle \#i, j : 0 \leq i < j < N : a[i] \leq 0 \wedge a[j] \geq 0 \rangle\}$ 
```

## UPDATE THE NEW VARIABLE

$$\begin{aligned} & \langle \#i : 0 \leq i < n : a[i] \leq 0 \rangle [n \setminus n + 1] \\ = & \langle \#i : 0 \leq i < n + 1 : a[i] \leq 0 \rangle \\ = & \{ \text{split off } i = n \text{ (assuming } 0 \leq n) \} \\ & \langle \#i : 0 \leq i < n : a[i] \leq 0 \rangle + \#(a[n] \leq 0) \\ = & \{ P_1 \} \\ & s + \#(a[n] \leq 0) \\ = & \begin{cases} s & \text{if } a[n] > 0, \\ s + 1 & \text{if } a[n] \leq 0. \end{cases} \end{aligned}$$



## RESULTING PROGRAM

```
 $n, r, s := 0, 0, 0$   
 $\{P_0 \wedge P_1 \wedge Q, bnd : N - n\}$   
do  $n \neq N \rightarrow \{P_0 \wedge P_1 \wedge Q \wedge n \neq N\}$   
  if  $a[n] < 0 \rightarrow skip$   
     $| a[n] \geq 0 \rightarrow r := r + s$   
  fi  
   $\{P_0[n \setminus n + 1] \wedge P_1 \wedge Q \wedge n \neq N\}$   
  if  $a[n] > 0 \rightarrow skip$   
     $| a[n] \leq 0 \rightarrow s := s + 1$   
  fi  
   $\{(P_0 \wedge P_1 \wedge Q)[n \setminus n + 1]\}$   
   $n := n + 1$   
od  
 $\{r = \langle \#i, j : 0 \leq i < j < N : a[i] \leq 0 \wedge a[j] \geq 0 \rangle\}$ 
```

## RESULTING PROGRAM

Since  $P_0 \wedge P_1 \wedge Q \wedge n \neq N$  is a common precondition for the **if**'s (the second **if** does not use  $P_0$ ), they can be combined:

```
 $n, r, s := 0, 0, 0$   
 $\{P_0 \wedge P_1 \wedge Q, bnd : N - n\}$   
do  $n \neq N \rightarrow \{P_0 \wedge P_1 \wedge Q \wedge n \neq N\}$   
  if  $a[n] < 0 \rightarrow s := s + 1$   
     $| a[n] = 0 \rightarrow r, s := r + s, s + 1$   
     $| a[n] > 0 \rightarrow r := r + s$   
  fi  
   $\{(P_0 \wedge P_1 \wedge Q)[n \setminus n + 1]\}$   
   $n := n + 1$   
od  
 $\{r = \langle \#i, j : 0 \leq i < j < N : a[i] \leq 0 \wedge a[j] \geq 0 \rangle\}$ 
```

## ISN'T IT GETTING A BIT TOO COMPLICATED?

- Quantifier and indexes manipulation tend to get very long and tedious.
  - Expect to see even longer expressions later!
- To certain extent, it is a restriction of the data structure we are using. With arrays we have to manipulate the indexes.
- Is it possible to use higher-level data structures? Lists? Trees?
  - Heap-allocated data structure with pointers is a horrifying beast!
  - Trying to be more abstract lead to further developments in programming languages, e.g. algebraic datatypes.