

1. .

```
8 *****
9 #include <stdio.h>
10
11 // Function to perform linear search
12 int linear_search(int arr[], int size, int target) {
13     for (int i = 0; i < size; i++) {
14         if (arr[i] == target) {
15             return i; // Return the index of the target
16         }
17     }
18     return -1; // Target not found
19 }
20
21 int main() {
22     // Test case 1: Target present
23     int arr1[] = {10, 25, 8, 14, 3, 23};
24     int size1 = sizeof(arr1) / sizeof(arr1[0]);
25     int target1 = 14;
26     int result1 = linear_search(arr1, size1, target1);
27     if (result1 != -1) {
28         printf("Target %d found at index: %d\n", target1, result1);
29     } else {
30         printf("Target %d not found in the array.\n", target1);
31     }
32
33     // Test case 2: Target absent
34
35     // Test case 2: Target absent
36     int arr2[] = {5, 7, 1, 2, 9};
37     int size2 = sizeof(arr2) / sizeof(arr2[0]);
38     int target2 = 4;
39     int result2 = linear_search(arr2, size2, target2);
40     if (result2 != -1) {
41         printf("Target %d found at index: %d\n", target2, result2);
42     } else {
43         printf("Target %d not found in the array.\n", target2);
44     }
45     return 0;
46 }
```

input

Target 14 found at index: 3
Target 4 not found in the array.

2. .

```
9  #include <stdio.h>
10
11  // Function to perform binary search
12  int binary_search(int arr[], int left, int right, int target) {
13      while (left <= right) {
14          int mid = left + (right - left) / 2; // Calculate the middle index
15
16          if (arr[mid] == target) {
17              return mid; // Target found at mid index
18          } else if (arr[mid] < target) {
19              left = mid + 1; // Continue search in the right half
20          } else {
21              right = mid - 1; // Continue search in the left half
22          }
23      }
24      return -1; // Target not present in the array
25  }
26
27  int main() {
28      // Test case 1: Searching for a value in the middle of the array
29      int arr1[] = {2, 4, 6, 8, 10, 12, 14, 16, 18, 20};
30      int target1 = 10;
31      int result1 = binary_search(arr1, 0, sizeof(arr1)/sizeof(arr1[0]) - 1, target1);
32      printf("Searching for %d... ", target1);
33      result1 != -1 ? printf("found at index %d\n", result1) : printf("not found\n");
34
35      // Test case 2: Searching for values at the edges of the array
36      int target2 = 2;
37      int result2 = binary_search(arr1, 0, sizeof(arr1)/sizeof(arr1[0]) - 1, target2);
38      printf("Searching for %d... ", target2);
39      result2 != -1 ? printf("found at index %d\n", result2) : printf("not found\n");
40
41      int target3 = 20;
42      int result3 = binary_search(arr1, 0, sizeof(arr1)/sizeof(arr1[0]) - 1, target3);
43      printf("Searching for %d... ", target3);
44      result3 != -1 ? printf("found at index %d\n", result3) : printf("not found\n");
45
46      // Test case 3: Searching for a value not present in the array
47      int target4 = 11;
48      int result4 = binary_search(arr1, 0, sizeof(arr1)/sizeof(arr1[0]) - 1, target4);
49      printf("Searching for %d... ", target4);
50      result4 != -1 ? printf("found at index %d\n", result4) : printf("not found\n");
51
52      // Test case 4: Performing a search in an empty array
53      int arr2[] = {};
54      int target5 = 3;
55      int result5 = binary_search(arr2, 0, sizeof(arr2)/sizeof(arr2[0]) - 1, target5);
56      printf("Searching for %d in an empty array... ", target5);
57      result5 != -1 ? printf("found at index %d\n", result5) : printf("not found\n");
```

```

56     printf("Searching for %d in an empty array... ", target5);
57     result5 != -1 ? printf("found at index %d\n", result5) : printf("not found\n");
58
59     return 0;
60 }
61
input
main.c: In function 'main':
main.c:55:42: warning: overflow in conversion from 'long unsigned int' to 'int' changes value from '18446744073
709551615' to '-1' [-Woverflow]
   55 |         int result5 = binary_search(arr2, 0, sizeof(arr2)/sizeof(arr2[0]) - 1, target5);
       |                                     ^~~~~~
main.c:55:19: warning: 'binary_search' accessing 4 bytes in a region of size 0 [-Wstringop-overflow=]
   55 |         int result5 = binary_search(arr2, 0, sizeof(arr2)/sizeof(arr2[0]) - 1, target5);
       |                                     ^~~~~~
main.c:55:19: note: referencing argument 1 of type 'int *'
main.c:12:5: note: in a call to function 'binary_search'
   12 | int binary_search(int arr[], int left, int right, int target) {
       |         ^~~~~~
Searching for 10... found at index 4
Searching for 2... found at index 0
Searching for 20... found at index 9
Searching for 11... not found
Searching for 3 in an empty array... not found

```

3. .

```

9  #include <stdio.h>
10
11  // Function to perform insertion sort
12  void insertion_sort(int arr[], int length) {
13      int i, key, j;
14      for (i = 1; i < length; i++) {
15          key = arr[i]; // The element to be inserted
16          j = i - 1;
17
18          // Move elements of arr[0..i-1], that are greater than key,
19          // to one position ahead of their current position
20          while (j >= 0 && arr[j] > key) {
21              arr[j + 1] = arr[j];
22              j = j - 1;
23          }
24          arr[j + 1] = key; // Insert the key at after the element just smaller than it
25      }
26  }
27
28  int main() {
29      // Example of declaring an array and calling the insertion_sort function
30      int arr[] = {9, 5, 1, 4, 3};
31      int length = sizeof(arr) / sizeof(arr[0]);
32
33      insertion_sort(arr, length);
34
35      // Code to print the sorted array
36      printf("Sorted array: ");
37      for (int i = 0; i < length; i++) {
38          printf("%d ", arr[i]);
39      }
40      printf("\n");
41
42      // Additional tests
43      // Test with an already sorted array

```

```
43 // Test with an already sorted array
44 int sorted_arr[] = {1, 2, 3, 4, 5};
45 insertion_sort(sorted_arr, sizeof(sorted_arr) / sizeof(sorted_arr[0]));
46 // Test with a reverse sorted array
47 int reverse_arr[] = {5, 4, 3, 2, 1};
48 insertion_sort(reverse_arr, sizeof(reverse_arr) / sizeof(reverse_arr[0]));
49 // Test with an array with duplicate elements
50 int duplicate_arr[] = {3, 1, 4, 1, 5, 9, 2, 6, 5, 3, 5};
51 insertion_sort(duplicate_arr, sizeof(duplicate_arr) / sizeof(duplicate_arr[0]));
52
53 // Print additional test results
54 printf("Already sorted array: ");
55 for (int i = 0; i < sizeof(sorted_arr) / sizeof(sorted_arr[0]); i++) {
56     printf("%d ", sorted_arr[i]);
57 }
58 printf("\n");
59
60 printf("Reverse sorted array: ");
61 for (int i = 0; i < sizeof(reverse_arr) / sizeof(reverse_arr[0]); i++) {
62     printf("%d ", reverse_arr[i]);
63 }
64 printf("\n");
65
66 printf("Array with duplicates: ");
67 for (int i = 0; i < sizeof(duplicate_arr) / sizeof(duplicate_arr[0]); i++) {
68     printf("%d ", duplicate_arr[i]);
69 }
70 printf("\n");
71
72 return 0;
73 }
74
```

```
Sorted array: 1 3 4 5 9
Already sorted array: 1 2 3 4 5
Reverse sorted array: 1 2 3 4 5
Array with duplicates: 1 1 2 3 3 4 5 5 5 6 9
```

4. .

```
9  #include <stdio.h>
10
11  // Function to perform selection sort
12  void selection_sort(int arr[], int length) {
13      int i, j, min_idx, temp;
14
15      // Move the boundary of the unsorted subarray one by one
16      for (i = 0; i < length-1; i++) {
17          // Find the minimum element in the unsorted array
18          min_idx = i;
19          for (j = i+1; j < length; j++) {
20              if (arr[j] < arr[min_idx]) {
21                  min_idx = j;
22              }
23          }
24
25          // Swap the found minimum element with the first element
26          temp = arr[min_idx];
27          arr[min_idx] = arr[i];
28          arr[i] = temp;
29      }
30  }
31
32  int main() {
33      // Example of declaring an array and calling the selection_sort function
34      int arr[] = {64, 25, 12, 22, 11};
35      int length = sizeof(arr) / sizeof(arr[0]);
36
37      selection_sort(arr, length);
38
39      // Code to print the sorted array
40      printf("Sorted array: ");
41      for (int i = 0; i < length; i++) {
42          printf("%d ", arr[i]);
```

```
42     printf("%d ", arr[i]);
43 }
44 printf("\n");
45
46 // Additional tests
47 // Test with an already sorted array
48 int sorted_arr[] = {1, 2, 3, 4, 5};
49 selection_sort(sorted_arr, sizeof(sorted_arr) / sizeof(sorted_arr[0]));
50 // Test with a reverse sorted array
51 int reverse_arr[] = {5, 4, 3, 2, 1};
52 selection_sort(reverse_arr, sizeof(reverse_arr) / sizeof(reverse_arr[0]));
53 // Test with an array with duplicate elements
54 int duplicate_arr[] = {3, 1, 4, 1, 5, 9, 2, 6, 5, 3, 5};
55 selection_sort(duplicate_arr, sizeof(duplicate_arr) / sizeof(duplicate_arr[0]));
56
57 // Print additional test results
58 printf("Already sorted array: ");
59 for (int i = 0; i < sizeof(sorted_arr) / sizeof(sorted_arr[0]); i++) {
60     printf("%d ", sorted_arr[i]);
61 }
62 printf("\n");
63
64 printf("Reverse sorted array: ");
65 for (int i = 0; i < sizeof(reverse_arr) / sizeof(reverse_arr[0]); i++) {
66     printf("%d ", reverse_arr[i]);
67 }
68 printf("\n");
69
70 printf("Array with duplicates: ");
71 for (int i = 0; i < sizeof(duplicate_arr) / sizeof(duplicate_arr[0]); i++) {
72     printf("%d ", duplicate_arr[i]);
73 }
74 printf("\n");
75
```

```
75
76     return 0;
77 }
```

input

Sorted array: 11 12 22 25 64
Already sorted array: 1 2 3 4 5
Reverse sorted array: 1 2 3 4 5
Array with duplicates: 1 1 2 3 3 4 5 5 5 6 9