

Architectures for Rainfall Property Estimation From Polarimetric Radar

Scott Collis¹ scollis@anl.gov, Scott Giangrande², Jonathan Helmus¹ and Silke Troemel³

1: Argonne National Laboratory, Argonne, IL United States


2: Brookhaven National Laboratory, Upton, NY United States 3: Meteorologisches Institut der Universität Bonn, Bonn, Germany



CLIMATE RESEARCH FACILITY


Introducton


- Numerical simulations of decadal climate are done at resolutions far courser than the natural scale of precipitation. To even have a chance of understanding future precipitation extremes we must reconcile the relation between the statistics of broad-scale precipitation and high resolution observations.
- To this end The Department of Energy's ARM Climate Research Facility operates a network of 5 and 3 cm scanning radar
- ► Fixed sites are at the Azores, Barrow on the North Slope of Alaska and a multi-scale heterogeneous network on the Southern Great Plains of Oklahoma.



ACHIEVING INSIGHT WITH THE COMMUNITY: THE PYTHON ARM RADAR TOOLKIT

- Weather radars are not a new invention, first academic mention in Bent et al. (1943).
- Massive advances in computing and radar software has not kept up.
- ► The Python ARM Radar Toolkit, Py-ART is a data model driven architecture for interactively and offline processing of active remote sensing data. Open source and, using GitHub, community based.
- Part of a larger growing international community of codes, see Heistermann et al. (2014)
- Twenty four forks, eight active contributors from multiple agencies and nations. Broad user base.





LINKS

The Python ARM Radar




This is an open source poster for notebooks, code and tex:







RAW DATA TO QUANTITATIVE PRECIPITATION ESTIMATES

- Raw collected radar data in engineering units is unsuitable for comparison with model data
- Shorter wavelength radar have a higher attenuation cross section. However Signal to noise in phase information much higher and calibration insensitive.
- Measured phase is a mix of propagation phase, phase shift on backscatter and artifacts: $\phi_{dp}^{signal}(r) = \phi_{dp}^{prop}(r) + \delta(r) + E(r)$.
- When calculating Specific Differential Phase, K_{dp} only the propagation component should be considered, $\kappa_{dp} = \frac{d\phi_{dp}^{prop}(r)}{dr}$.
- Method of Giangrande et al. (2013) used to extract ϕ_{dn}^{prop} and a 20 point sobel filter $\mathcal{K}_{dp} = \phi_{dp}^{prop} * f_{20} = \sum_{M=0}^{19} \phi_{dp}(r-M) f(M)$ where f(M)is a linear ramp through zero.








- ▶ Specific attenuation is calculated using K_{dp} and Z_e using a method after Gu et al. (2011) and is used as a an estimator for rainfall using a method after Ryzhkov et al. (2014).
- ▶ In Giangrande et al. (2014) it was shown that specific attenuation at short wavelengths performed as well as retrievals at S-band wavelengths.

MAPPING: OBJECTIVE ANALYSIS

- ▶ Radar data is on , θ and ϕ coordinates, there is a need to estimate on different coordinates systems (Cartesian, Sigma, pressure).
- Py-ART tags each gate with an estimate of its central coordinate and inserts these into a cloud.
- For propagation insensitive variables (not radial velocity or ϕ_{dp}), gates can be drawn from mulitple radars to be estimated onto a single grid.





▶ In Py-ART the act of gridding takes in a *n-tuple* of radar objects and returns a grid object which can be saved to a CF-Radial complaint file.


mesh_mapped_x = pyart.map.grid_from_radars((xnw_radar,xsw_radar,xse_radar), grid shape=(35, 401, 401), grid_limits=((0, 17000), (-50000, 40000), (-60000, 40000)), $grid_origin = (36.57861, -97.363611),$ fields=['corrected reflectivity', 'rain rate A', 'reflectivity'], refl_field='corrected_reflectivity', max refl=100.)

ADVECTIVE INTERPOLATION


- Simply accumulating precipitation retrievals by integrating can create a "chain of pearls effect" due to the lack of spatial coherency between successive radar scans.
- ► This can create false information and skew any interpretation of the scale of rainfall.
- The solution is to calculate the image advection and then generate sub-temporal-scale images and average:








- ▶ In a nice novel twist (we Py-ART developers love applying math to radar) the advection can be determined from the cross correlation phase between the two images, $r = \mathcal{F}^{-1} \{C\}$.
- Borrowing liberally from Wikipedia:





- where \mathcal{F} is the Fourier transform, * is the complex conjugate and \circ represents element wise multiplication.
- Summing sub-sample advective interpolation steps results in an accumulation that is less affected by lack of temporal resolution.

REFERENCES

Bent, A. E., Massachusetts Institute of Technology., and Radiation Laboratory., 1943: Radar echoes from atmospheric phenomena. Radiation Laboratory, Massachusetts Institute of Technology, [Cambridge,

Giangrande, S. E., S. Collis, A. K. Theisen, and A. Tokay, 2014: Precipitation estimation from the ARM distributed radar network during the MC3e campaign. J. Appl. Meteor. Climatol., doi:10.1175/JAMC-D-13-0321.1

URL http://journals.ametsoc.org/doi/abs/10.1175/JAMC-D-13-0321.1

Giangrande, S. E., R. McGraw, and L. Lei, 2013: An application of linear programming to polarimetric radar differential phase processing. Journal of Atmospheric and Oceanic Technology, 30, 1716–1729, doi:10.1175/JTECH-D-12-00147.1.

URL http://journals.ametsoc.org/doi/abs/10.1175/JTECH-D-12-00147.1

Gu, J.-Y., A. Ryzhkov, P. Zhang, P. Neilley, M. Knight, B. Wolf, and D.-I. Lee, 2011: Polarimetric attenuation correction in heavy rain at c band. J. Appl. Meteor. Climatol., 50, 39–58, doi:10.1175/2010JAMC2258.1.

URL http://journals.ametsoc.org/doi/abs/10.1175/2010JAMC2258.1

Heistermann, M., S. Collis, M. J. Dixon, S. Giangrande, J. J. Helmus, B. Kelley, J. Koistinen, D. B. Michelson, M. Peura, T. Pfaff, and D. B. Wolff, 2014: The emergence of open source software for the weather radar community. Bull. Amer. Meteor. Soc., doi:10.1175/BAMS-D-13-00240.1.

URL http://journals.ametsoc.org/doi/abs/10.1175/BAMS-D-13-00240.1

Ryzhkov, A., M. Diederich, P. Zhang, and C. Simmer, 2014: Potential utilization of specific attenuation for rainfall estimation, mitigation of partial beam blockage, and radar networking. J. Atmos. Oceanic Technol., 31, 599-619, doi:10.1175/JTECH-D-13-00038.1.

URL http://journals.ametsoc.org/doi/abs/10.1175/JTECH-D-13-00038.1