

Running the Native Application

- native without confidential computing -

Cloning The App Repo

- Clone the example repo:

```
git clone https://github.com/scontain/java-args-env-file
Cloning into 'java-args-env-file'...
remote: Enumerating objects: 335, done.
remote: Counting objects: 100% (39/39), done.
remote: Compressing objects: 100% (29/29), done.
remote: Total 335 (delta 13), reused 16 (delta 10), pack-reused 296 (from 1)
Receiving objects: 100% (335/335), 100.38 KiB | 1.67 MiB/s, done.
Resolving deltas: 100% (206/206), done.
cd java-args-env-file/
```

Building the native App

```
./scripts/build.sh
```

```
Checking prerequisites...
```

```
All prerequisites are met.
```

```
 Building Docker image: registry.scontain.com/workshop/java-cli-env-reader:latest  
sha256:aaaf77ec95aa0850d2324acd318fdd74edf5bb621939a6d0c72524bb1c5d183a
```

```
 Pushing image to registry.scontain.com/workshop/java-cli-env-reader:latest
```

```
The push refers to repository [registry.scontain.com/workshop/java-cli-env-reader]
```

```
939184c428bd: Layer already exists
```

```
b680a522f37f: Layer already exists
```

```
24e401ec234b: Layer already exists
```

```
55068fa0fca2: Layer already exists
```

```
3d7fefe43a71: Layer already exists
```

```
77d203aef444: Layer already exists
```

```
107cbdaeec04: Layer already exists
```

```
latest: digest: sha256:692a7ae54943cfaeed829b2aea497196b2ef12074eeb73f973e21f131d08d2e8 size: 1782
```

```
 Generating Kubernetes manifests
```

```
 Creating /home/ubuntu/GIT/java-args-env-file/tmp/java-args-env-file/scripts/./generated/  
configmap.yaml for configmap
```

```
 Creating /home/ubuntu/GIT/java-args-env-file/tmp/java-args-env-file/scripts/./generated/  
deployment.yaml for deployment
```

```
 Creating /home/ubuntu/GIT/java-args-env-file/tmp/java-args-env-file/scripts/./generated/  
secret.yaml for secret
```

```
 All manifests generated in /home/ubuntu/GIT/java-args-env-file/tmp/java-args-env-file/generated
```


Deploying the app

- `./scripts/deploy.sh`

```
./scripts/deploy.sh
```

```
🚀 Deploying resources using context: <current>
```

```
configmap/java-cli-env-config created
```

```
secret/java-cli-env-secret created
```

```
deployment.apps/java-cli-env-reader created
```

```
✅ Deployment complete.
```

Showing the log

- showing the log
- Issues
 - output not very secure
 - we need to encrypt output, or
 - change the program
 - what about the visibility of secrets / config maps

```
./scripts/show-logs.sh
```

```
HOME=/root
```

```
WORKSHOP_CAS_BC_METRICS_PORT_9090_TCP_PROTO=tcp
```

```
Config File (/config/configs.yaml):
```

```
key1: value1
```

```
key2: value2
```

```
Secrets File (/config/secrets):
```

```
password: s3cr3t
```

```
my_db_encryption_key: top_secret_key
```



```
Sleeping for 1 hour to keep the container alive...
```