



```
1724
                          IT (!do_sync_sync(src_dir, / + partition, iist_oniy)) return i;
                      }
   1725
   1726
                  }
                  return found ? 0 : syntax_error("don't know how to sync %s partition", src.c_str());
   1727
   1728
              /* passthrough commands */
   1729
   1730
              else if (!strcmp(argv[0], "get-state") ||
                  !strcmp(argv[0], "get-serialno") ||
   1731
                  !strcmp(argv[0], "get-devpath"))
   1732
   1733
              {
                  return adb_query_command(format_host_command(argv[0]));
   1734
   1735
              /* other commands */
   1736
              else if (!strcmp(argv[0],"logcat") || !strcmp(argv[0],"lolcat") || !strcmp(argv[0],"longcat")) {
••• 1737
                  return logcat(argc, argv);
   1738
   1739
              else if (!strcmp(argv[0],"ppp")) {
   1740
   1741
                  return ppp(argc, argv);
   1742
              else if (!strcmp(argv[0], "start-server")) {
   1743
                  std::string error;
   1744
                  const int result = adb_connect("host:start-server", &error);
   1745
                  if (result < 0) {</pre>
   1746
                      fprintf(stderr, "error: %s\n", error.c_str());
   1747
   1748
                  return result;
   1749
   1750
```

```
|| !strcmp(argv[0],"lolcat") || !s
```



## platform\_system\_core / adb / client / commandline.cpp





```
IT (!do_sync_sync(src_dir, / + partition, list_only)) return i;
   1725
   1726
                  return found ? 0 : syntax_error("don't know how to sync %s partition", src.c_str());
   1727
   1728
              /* passthrough commands */
   1729
              else if (!strcmp(argv[0], "get-state") ||
   1730
                                                                         platform_system_core / adb / client / commandline.cpp
                  !strcmp(argv[0], "get-serialno") ||
   1731
                  !strcmp(argv[0], "get-devpath"))
   1732
   1733
                  return adb_query_command(format_host_command(argv[0]));
   1734
   1735
              /* other commands */
   1736
              else if (!strcmp(argv[0],"logcat") || !strcmp(argv[0],"lolcat") || !strcmp(argv[0],"longcat")) {
••• 1737
                  return logcat(argc, argv);
   1738
   1739
              else if (!strcmp(argv[0],"ppp")) {
   1740
                  return ppp(argc, argv);
   1741
   1742
              else if (!strcmp(argv[0], "start-server")) {
   1743
                  std::string error;
   1744
   1745
                  const int result = adb_connect("host:star
                  if (result < 0) {</pre>
   1746
   1747
                      fprintf(stderr, "error: %s\n", error.c_str());
   1748
                  return result;
   1749
   1750
```

server startup

