



By the end of this activity, you will be able to:

1. Find documents in MongoDB with specific field values.
2. Filter the results returned by MongoDB queries.
3. Count documents in a MongoDB collection and returned by queries.

Step 1. **Start MongoDB server and MongoDB shell.** Open a terminal window by clicking on the square black box on the top left of the screen.



Next, change to the *mongodb* directory, and start the server:

```
1 cd Downloads/big-data-3/mongodb
2 ./mongodb/bin/mongod --dbpath db
```

The arguments *--dbpath db* specify that the directory *db* should be used for the MongoDB directory for datafiles. After starting the MongoDB server, you will see the following lines indicating that the server is running:

```
I FTDC    [initandlisten] Initializing full-time diagnostic data capture with directory 'db/diagnostic.data'
I NETWORK [HostnameCanonicalizationWorker] Starting hostname canonicalization worker
I NETWORK [initandlisten] waiting for connections on port 27017
```

Next, let's run the MongoDB shell so that we can query the server. Open a new terminal shell window, change to the *mongodb* directory, and start the shell:

```
1 cd Downloads/big-data-3/mongodb
2 ./mongodb/bin/mongo
```

Step 2. **Show Databases and Collections.** Run the *show dbs* command to see the databases:

```
> show dbs
journaldev  0.000GB
local       0.000GB
sample     0.004GB
test       0.000GB
```

The database named *sample* has been created and loaded with Twitter JSON data. Let's switch to that database by running the *use* command:

```
> use sample
switched to db sample
```

We can see the collections in the *sample* database by running *show collections*:

```
> show collections
collection
users
```

The Twitter data is stored in the *users* collection. We can run *db.users.count()* to count the number of documents:

```
> db.users.count()
11188
```

Step 3. **Look at document and find distinct values.** We can examine the contents of one of the documents by running *db.users.findOne()*:

```
> db.users.findOne()
{
  "_id" : ObjectId("578ffa8e7eb9513f4f55a935"),
  "user_name" : "koterass",
  "retweet_count" : 0,
  "tweet_followers_count" : 461,
  "source" : "<a href='\"http://twitter.com/download/iphone\"' rel='\"nofollow\"'>Twitter for iPhone</a>",
  "coordinates" : null,
  "tweet_mentioned_count" : 1,
  "tweet_ID" : "755891629932675072",
  "tweet_text" : "RT @ochocinco: I beat them all for 10 straight hours #FIFA16KING https://t.co/BFnV6jfkBL",
  "user" : {
    "CreatedAt" : ISODate("2011-12-27T09:04:01Z"),
    "FavouritesCount" : 5223,
    "FollowersCount" : 461,
    "FriendsCount" : 619,
    "UserId" : 447818090,
    "Location" : "501"
  }
}
```

The document has several fields, e.g., *user_name*, *retweet_count*, *tweet_ID*, etc., and nested fields under *user*, e.g., *CreatedAt*, *UserId*, *Location*, etc.

We can find the distinct values for a specific field by using the *distinct()* command. For example, let's find the distinct values for *user_name*:

```
> db.users.distinct("user_name")
[
  "koterass",
  "AllieLovesR5_ID",
  "Tonkatol",
  "Gaslet",
  "Syaxmii ",
  "CamSteele_96",
```

Step 4. **Search for specific field value.** We can search for fields with a specific value using the *find()* command. For example, let's search for *user_name* with the value *ActionSportsJax*:

```
> db.users.find({user_name : "ActionSportsJax"})
{ "_id" : ObjectId("579670bfc38159226b4c8e47"), "user_name" : "ActionSportsJax", "retweet
rce" : "<a href='\"http://twitter.com/download/iphone\"' rel='\"nofollow\"'>Twitter for iPhon
unt" : 2, "tweet_ID" : "757667800521531393", "tweet_text" : "RT @wwbrown19: I'm watching
Augustine football and asked myself \"How on earth did we stop...", "user" : { "CreatedAt"
nt" : 120, "FollowersCount" : 3539, "FriendsCount" : 476, "UserId" : 35857042, "Location"
```

By appending `.pretty()` to the end of the find command, the results will be formatted:

```
> db.users.find({user_name : "ActionSportsJax"}).pretty()
{
  "_id" : ObjectId("579670bfc38159226b4c8e47"),
  "user_name" : "ActionSportsJax",
  "retweet_count" : 0,
  "tweet_followers_count" : 3539,
  "source" : "<a href='\"http://twitter.com/download/i\"' rel='\"nofollow\"'>Twitter for iPhone</a>",
  "coordinates" : null,
  "tweet_mentioned_count" : 2,
  "tweet_ID" : "757667800521531393",
}
```

Step 5. **Filter fields returned by query.** We can specify a second argument to the `find()` command to only show specific field(s) in the result. Let's repeat the previous search, but only show the `tweet_ID` field:

```
> db.users.find({user_name : "ActionSportsJax"}, {tweet_ID: 1})
{ "_id" : ObjectId("579670bfc38159226b4c8e47"), "tweet_ID" : "757667800521531393" }
```

The `_id` field is primary key for every document, and we can remove it from the results with the following filter:

```
> db.users.find({user_name : "ActionSportsJax"}, {tweet_ID: 1, _id: 0})
{ "tweet_ID" : "757667800521531393" }
```

Step 6. **Perform regular expression search.** MongoDB also supports searching documents with regular expressions. If we search for the value `FIFA` in the `tweet_text` field, there are no results:

```
> db.users.find({tweet_text: "FIFA"})
> █
```

However, if we search using a regular expression, there are many results:

```
> db.users.find({tweet_text: /FIFA/})
{ "_id" : ObjectId("578ffa8e7eb9513f4f55a935"), "user_name" : "koterass", "retweet_count" : 0, "tweet_followers_count" : 0, "source" : "<a href='\"http://twitter.com/download/iphone\"' rel='\"nofollow\"'>Twitter for iPhone</a>", "tweet_ID" : "755891629932675072", "tweet_text" : "RT @ochocinco: I beat them at KBL", "user" : { "CreatedAt" : ISODate("2011-12-27T09:04:01Z"), "FavouritesCount" : 447818090, "Location" : "501" } }
{ "_id" : ObjectId("578ffa917eb9513f4f55a939"), "user_name" : "Tonkatol", "retweet_count" : 0, "tweet_followers_count" : 0, "source" : "<a href='\"http://twitter.com\"' rel='\"nofollow\"'>Twitter Web Client</a>", "coordinates" : null, "tweet_ID" : "755891638921232384", "tweet_text" : "RT @GameSeek: Follow & Retweet for your chance to win (your choice) in our #giveaway! https://...", "user" : { "CreatedAt" : ISODate("2012-01-11T00:00:00Z"), "FriendsCount" : 2675, "UserId" : 722815650, "Location" : null } }
```

The difference between the queries is that the first searched for where the `tweet_text` field value was exactly equal to `FIFA`, and the second searched for where the field value contained `FIFA`.

We can append `.count()` to the command to count the number of results:

```
> db.users.find({tweet_text: /FIFA/}).count()
3697
```

Step 7. **Search using text index.** A text index can be created to speed up searches and allows advanced searches with `$text`. Let's create the index using `createIndex()`:

```
> db.users.createIndex({"tweet_text" : "text"})
{
  "createdCollectionAutomatically" : false,
  "numIndexesBefore" : 2,
  "numIndexesAfter" : 2,
  "note" : "all indexes already exist",
  "ok" : 1
}
```

The argument *tweet_text* specifies the field on which to create the index.

Next, we can use the *\$text* operator to search the collection. We can perform the previous query to find the documents containing *FIFA*:

```
> db.users.find({$text : {$search : "FIFA"}}).count()
4031
```

We can also search for documents not containing a specific value. For example, let's search for documents containing *FIFA*, but not *Texas*:

```
> db.users.find({$text : {$search : "FIFA -Texas"}}).count()
4022
```

Step 8. **Search using operators.** MongoDB can also search for field values matching a specific criteria. For example, we can find where the *tweet_mentioned_count* is greater than six:

```
> db.users.find({tweet_mentioned_count: {$gt : 6}})
{ "_id" : ObjectId("57966e26c3815920e1131b03"), "user name" : "marshallrupe",
  : "<a href=\"http://twitter.com/download/iphone\" rel=\"nofollow\">Twitter f
  : 7, "tweet_ID" : "757665013817409536", "tweet_text" : "RT @BrianBorrison: h
  lrupe @da_carlos30 @TrissyTim @BrockHiltonb @ZachZippe @ro...", "user" : { "Cre
  : 326, "FollowersCount" : 215, "FriendsCount" : 165, "UserId" : -2073286695,
  { "_id" : ObjectId("57966ecfc3815920e1132053"), "user name" : "marvheys", "re
  "<a href=\"http://twitter.com/download/android\" rel=\"nofollow\">Twitter for
  : 7, "tweet_ID" : "757665717948977152", "tweet_text" : "RT @philhayton11: Ple
  1882 @marvheys @Matlallor https://t.co/y0s8MxjA5d", "user" : { "CreatedAt" :
  ollowersCount" : 1215, "FriendsCount" : 850, "UserId" : 477884041, "Location"
  { "_id" : ObjectId("5796706bc38159226b4c8af1"), "user name" : "HearAllAbtIt",
  "<a href=\"http://twitter.com\" rel=\"nofollow\">Twitter Web Client</a>", "c
```

The *\$gt* operator search for values greater than a specific value. We can use the *\$where* command to compare between fields in the same document. For example, the following searches for *tweet_mentioned_count* is greater than *tweet_followers_count*:

```
> db.users.find({$where : "this.tweet_mentioned_count > this.tweet_followers_count"}).count()
18
```

Note that the field names for *\$where* are required to be prefixed with *this*, which represent the document.

We can combine multiple searches by using *\$and*. For example, let's search for *tweet_text* containing *FIFA* and *tweet_mentioned_count* greater than four:

```
> db.users.find({$and : [ {tweet_text : /FIFA/}, {tweet_mentioned_count: {$gt : 4}}]}).count()
1
```

When you are done querying MongoDB, run *exit* in the MongoDB shell, and *Control-C* in the terminal window running the server.

Mark as completed

