

CHANGING THE BASE OF A CONTAINER: SIX CONSTRUCTIONS, TWO INVARIANTS, ONE COLLAPSE

MACBETH

ABSTRACT. The category of containers is $\mathbf{Cont} = \mathbf{Fam}(\mathbf{Set}^{\text{op}})$; replacing $\mathbf{Set}$ by a category $\mathcal{C}$ along a functor $F: \mathbf{Set} \rightarrow \mathcal{C}$ yields $\mathbf{Fam}(\mathcal{C}^{\text{op}})$, whose objects are containers whose positions are read out in $\mathcal{C}$. This change of base is where effects and directedness enter the theory of polynomial functors: $\mathcal{C} = \mathbf{Kl}(M)$ gives effectful (M -)containers, $\mathcal{C} = \mathbf{Vec}$ gives linear containers, $\mathcal{C} = \mathbf{Cat}$ recovers directed containers. We survey six ways monad and comonad structure is transported through this construction, and then isolate the invariant that decides when the resulting extension into a category of endofunctors is full and faithful. There are three distinct extensions in play, with three different notions of naturality; keeping them apart resolves an apparent paradox (the reader monad has a cartesian closed Kleisli category yet its extension is never full). Our main result is a sharp collapse: over a commutative-monad base, the enriched container extension is full and faithful for the identity monad and for no other effect. Closedness of the base makes the enriched extension *exist*; connectedness of the monoidal unit makes it *full*; these axes are independent, and over $\mathbf{Kl}(M)$ they meet only at $M = \text{Id}$.

Author: MacBeth (Kodamai). *Date:* 15 September 2026.

Corresponds to `scotmacbeth/work-in-progress commit` PENDING.

Draft — work in progress; Kodamai grant deliverable. A report on the monad/comonad constructions on containers, organised around change of base and enrichment; the new contribution is the enriched-extension collapse of §4 (Theorem 4.2). The per-instance results of §3 are proved in the cited companion papers and are not reproduced.

1. INTRODUCTION

A *container* (S, P) is a set S of shapes together with, for each shape $s \in S$, a set P_s of positions; it presents the polynomial endofunctor

$$\llbracket S, P \rrbracket(X) = \sum_{s \in S} X^{P_s} = \sum_{s \in S} \mathbf{Set}(P_s, X),$$

the interpretation of a strictly-positive datatype whose values are “a shape together with a payload at each position” [1]. The container category $\mathbf{Cont}$ is equivalent to $\mathbf{Fam}(\mathbf{Set}^{\text{op}})$: an object is a family of sets indexed by a

Date: 15 September 2026.

set, a morphism $(S, P) \rightarrow (T, Q)$ is a shape map $S \rightarrow T$ together with, contravariantly, a position map back [10]. The extension $\llbracket - \rrbracket: \mathbf{Cont} \rightarrow [\mathbf{Set}, \mathbf{Set}]$ is full and faithful onto the polynomial functors: containers *are* polynomial functors, presented.

Changing the base. The formula $\llbracket S, P \rrbracket(X) = \sum_s \mathbf{Set}(P_s, X)$ has one degree of freedom that the datatype reading hides: the hom-set $\mathbf{Set}(P_s, X)$. What if positions are read out not in $\mathbf{Set}$ but in some other category $\mathcal{C}$ — so that observing a position may fail, branch, consult a context, cost a resource, or return a distribution? Formally, fix a functor $F: \mathbf{Set} \rightarrow \mathcal{C}$ and consider

$$\mathbf{Fam}(\mathcal{C}^{\text{op}}), \quad \llbracket S, P \rrbracket_{\mathcal{C}}(X) = \sum_{s \in S} \mathcal{C}(P_s, X) \quad (X \in \mathcal{C}).$$

This *change of base* is not cosmetic. It is the single construction under which the main variations of the polynomial-functor calculus are instances of one theory:

- $\mathcal{C} = \mathbf{Set}$: ordinary containers.
- $\mathcal{C} = \mathbf{Kl}(M)$ for a monad M on $\mathbf{Set}$: *M-containers*, whose positions are read in the Kleisli category, so that $\llbracket S, P \rrbracket_M(X) = \sum_s \mathbf{Set}(P_s, MX)$ is the effectful reading.
- $\mathcal{C} = \mathbf{Vec}$: linear containers / the $\mathbf{Vec}$ -valued theory.
- $\mathcal{C} = \mathbf{Cat}$: directed containers, recovering categories [2].

The point Neil Ghani has pressed is that change of base is the *frame*, and the per-instance results are details of transport: a functor $F: \mathbf{Set} \rightarrow \mathcal{C}$ that carries structure, not merely a relabelling of the base. This report is organised around that frame.

Two questions per construction. For each way of putting monad or comonad structure on containers, two questions recur:

- (a) **Availability.** Does the construction exist over this base at all?
- (b) **Faithfulness.** Is the extension into endofunctors full and faithful — i.e. does the combinatorial category of containers embed into the semantic category of functors, so that “container morphism” and “natural transformation” coincide?

Full-and-faithfulness is a *diagnostic*, not the headline: it is the sharpest available test of whether the syntactic category $\mathbf{Fam}(\mathcal{C}^{\text{op}})$ faithfully models its intended semantics. We lead with the structure of the container category over each base (§3), and then use the diagnostic to expose what actually controls it (§4).

Results. The survey (§3) collects the transport constructions Ghani enumerated, each proved elsewhere in this programme: the position-op monad-to-comonad transfer; the $\forall/\exists$ predicate liftings; the identification of *M*-containers with $\mathbf{Fam}(\mathbf{Kl}(M)^{\text{op}})$ and its codensity criterion for fullness; algebraic effects as polynomial functors, with the free monad on a container

as their carrier; and the composition-versus-representability dividing line for monads on **Cont**.

The new contribution (§4) is a clean anatomy of *why* fullness holds or fails, and a sharp collapse. There are three extensions of an M -container into endofunctors, with three different notions of naturality:

- (A) the *ordinary* extension $\llbracket - \rrbracket_M : \mathbf{Fam}(\mathbf{Kl}(M)^{\mathrm{op}}) \rightarrow [\mathbf{Set}, \mathbf{Set}]$, whose morphisms are ordinary (pure) natural transformations;
- (B) the *Kleisli-presheaf* extension $\llbracket - \rrbracket^{\mathbf{Kl}} : \mathbf{Fam}(\mathbf{Kl}(M)^{\mathrm{op}}) \rightarrow [\mathbf{Kl}(M), \mathbf{Set}]$, whose morphisms are Kleisli-natural, and which is *always* full and faithful (co-Yoneda);
- (C) the *self-enriched* extension $\llbracket S, P \rrbracket = \sum_s [P_s, -] : \mathcal{C} \rightarrow \mathcal{C}$ using the internal hom of a closed base, which realises Ghani’s enriched-Yoneda desideratum $\mathbf{Nat}(\sum_s [P_s, -], F) \cong \prod_s F(P_s)$.

Two invariants govern (C), and they are independent:

$$\mathcal{CL} = \{ M : \mathbf{Kl}(M) \text{ is monoidal closed} \} \quad \mathcal{UN} = \{ M : \text{the monoidal unit of } \mathbf{Kl}(M) \text{ is connected} \}.$$

Closedness ($\mathcal{CL}$) makes the enriched extension *exist*; connectedness of the monoidal unit ($\mathcal{UN}$) makes it *full*. Our main theorem is that over a Kleisli base these two conditions meet in exactly one monad.

Theorem 1.1 (Enriched collapse; §4). *Let M be a commutative strong monad on **Set**. The self-enriched M -container extension $\sum_s [P_s, -] : \mathbf{Kl}(M) \rightarrow \mathbf{Kl}(M)$ is full and faithful if and only if M is the identity monad. Equivalently, $\mathcal{CL} \cap \mathcal{UN} = \{\mathrm{Id}\}$: no nontrivial effect — not even an idempotent (localization) monad — carries a uniform enriched full-and-faithful semantics.*

The reader monad $\mathbf{Reader}_S = (-)^S$ is the instructive pivot. Its Kleisli category is *cartesian closed*, so construction (C) is available; nonetheless the extension is not full, because the monoidal unit 1 has global-points functor $(-)^S$, which fails to preserve coproducts for $|S| \geq 2$. The same failure appears in extension (A) as the non-codensity of $\mathbf{Reader}_S$. Closedness and fullness are orthogonal; enrichment relocates the obstruction but does not remove it. The one place fullness is automatic is the Kleisli-presheaf extension (B), at the price that its morphisms are Kleisli-natural rather than pure. The factorisation $\llbracket - \rrbracket_M = R \circ \llbracket - \rrbracket^{\mathbf{Kl}}$, with R restriction along $F : \mathbf{Set} \rightarrow \mathbf{Kl}(M)$ and defect measured by the codensity monad $\mathbf{Ran}_M M$, is the single picture carrying both messages.

Outline. Section 2 sets up the change-of-base spine and fixes notation. Section 3 is the census of the six transport constructions, each stated with its provenance. Section 4 proves the anatomy and the collapse of Theorem 1.1. Section 5 records what the diagnostic teaches, separates composition from the (lossy) distributive-law question, and states the design consequence for effectful and agentic container calculi.

2. THE CHANGE-OF-BASE SPINE

We recall only what the later sections use.

Definition 2.1 (Containers over a base). Let $\mathcal{C}$ be a category. The category $\mathbf{Fam}(\mathcal{C}^{\mathrm{op}})$ of $\mathcal{C}$ -containers has objects (S, P) with $S \in \mathbf{Set}$ and $P: S \rightarrow \mathcal{C}_0$ a family of $\mathcal{C}$ -objects $(P_s)_{s \in S}$; a morphism $(S, P) \rightarrow (T, Q)$ is a function $f: S \rightarrow T$ on shapes together with, for each $s \in S$, a $\mathcal{C}$ -morphism $Q_{f(s)} \rightarrow P_s$ (contravariant in positions). For $\mathcal{C} = \mathbf{Set}$ this is **Cont**.

Remark 2.2 (The bifibration viewpoint). The assignment $\mathcal{C} \mapsto \mathbf{Fam}(\mathcal{C}^{\mathrm{op}})$ is functorial: a functor $F: \mathcal{C} \rightarrow \mathcal{D}$ induces $\mathbf{Fam}(F^{\mathrm{op}}): \mathbf{Fam}(\mathcal{C}^{\mathrm{op}}) \rightarrow \mathbf{Fam}(\mathcal{D}^{\mathrm{op}})$, acting as F on positions and identically on shapes. The total category $\int_{\mathbf{Set}} \mathbf{Cont}(\mathrm{cod})$ assembling all bases is a bifibration over **Set**; contravariance in positions is exactly the fibrewise opposite. Change of base along $F: \mathbf{Set} \rightarrow \mathcal{C}$ is the instance transporting the standard container theory into $\mathcal{C}$; when F is (co)monoidal it transports (co)monoidal structure, which is what the constructions of §3 exploit.

Definition 2.3 (Extension). When $\mathcal{C}$ is locally small the *co-Yoneda (presheaf) extension* is

$$\llbracket - \rrbracket_{\mathcal{C}}: \mathbf{Fam}(\mathcal{C}^{\mathrm{op}}) \longrightarrow [\mathcal{C}, \mathbf{Set}], \quad \llbracket S, P \rrbracket_{\mathcal{C}}(X) = \sum_{s \in S} \mathcal{C}(P_s, X),$$

the coproduct of representables. When moreover a functor $M: \mathbf{Set} \rightarrow \mathbf{Set}$ makes $\mathcal{C}(P_s, X) = \mathbf{Set}(P_s, MX)$ (as for $\mathcal{C} = \mathbf{Kl}(M)$), one also has the *ordinary* extension $\llbracket - \rrbracket_M: \mathbf{Fam}(\mathbf{Kl}(M)^{\mathrm{op}}) \rightarrow [\mathbf{Set}, \mathbf{Set}]$, $\llbracket S, P \rrbracket_M(X) = \sum_s \mathbf{Set}(P_s, MX)$.

Remark 2.4 (Effectful reading). For $\mathcal{C} = \mathbf{Kl}(M)$ the summand $\mathbf{Set}(P_s, MX)$ is the set of ways of assigning to each position an M -effectful observation of X : $M = \mathbf{Maybe}$ makes positions optional, $M = \mathcal{P}$ (powerset) makes them nondeterministic, $M = \mathbf{Dist}$ probabilistic, $M = \mathbf{Reader}_S = (-)^S$ context-dependent. This is the sense in which change of base to $\mathbf{Kl}(M)$ is “the same datatype, read effectfully”.

3. A CENSUS OF MONAD AND COMONAD CONSTRUCTIONS

We now collect the six ways monad/comonad structure has been transported through the container construction. Each subsection states the result and its provenance; the proofs are in the cited sources and are not reproduced. Throughout, M is a monad on **Set** unless stated otherwise.

Two of the constructions (§3.1, §3.2) act *fibrewise*: they change the position family and leave the shape set alone, so they are transports of endostructure on **Set** through the fibration **Cont** $\rightarrow$ **Set** of Remark 2.2. Two more (§3.3, §3.5) genuinely change the base or ask for structure *on* **Cont**. The fifth (§3.4) is the free construction that turns a single container into a monad.

3.1. Position-op transfer: monads become comonads. The simplest transport reads a monad on positions. Because positions are contravariant, a monad on **Set** becomes a *comonad* on **Cont**.

Construction 3.1 (Position transfer). For a monad $M = (M, \eta, \mu)$ on **Set**, define $G: \mathbf{Cont} \rightarrow \mathbf{Cont}$ by

$$G(S, P) = (S, M \circ P), \quad G(u, f) = (u, \{Mf_s\}_s),$$

with counit $\varepsilon_{(S, P)} = (\text{id}_S, \eta_{P_s})$ (backward $P_s \rightarrow MP_s$) and comultiplication $\delta_{(S, P)} = (\text{id}_S, \mu_{P_s})$ (backward $MMP_s \rightarrow MP_s$).

Proposition 3.2 ([8], transfer). *(G, ε, δ) is a comonad on **Cont**, and this is a biconditional: the three comonad laws for G hold if and only if the three monad laws for M hold (the single-shape containers $(1, A)$ realise every set A as a fibre, so no law is lost). Dually, a comonad W on **Set** yields a monad $H(S, P) = (S, W \circ P)$ on **Cont**. Fibrewise, G is postcomposition by M in the fibre $(\mathbf{Set}^{\text{op}})^S$; globally it is the left Kan extension*

$$G(S, P) = \sum_{s \in S} y^{M(P_s)} = \text{Lan}_{(S, P)} M, \quad \mathbf{Cont}(G(S, P), r) \cong [\mathbf{Set}, \mathbf{Set}](\llbracket S, P \rrbracket, r \circ M),$$

naturally in r , and descends to $\llbracket G(S, P) \rrbracket(A) = \sum_s \mathbf{Set}(MP_s, A)$ on extensions.

The mechanism is exactly the slogan of the whole report in miniature: a monad on the base is a comonad on the fibrewise opposite, and **Cont** carries that opposite in its position variable (Remark 2.2).

3.2. Predicate liftings: the $\forall/\exists$ constructions. A container $X = (S_X, P_X)$ and a “predicate” container Y can be combined by quantifying the predicate over positions. There are two ways, and they are the two halves of the composition monoidal structure.

Construction 3.3 ($\forall$ and $\exists$ liftings). For $(s, g) \in \llbracket X \rrbracket(S_Y)$ (so $s \in S_X$, $g: P_X s \rightarrow S_Y$), set

$$\text{All } X Y (s, g) = \prod_{p \in P_X s} P_Y(gp), \quad \text{Exists } X Y (s, g) = \sum_{p \in P_X s} P_Y(gp),$$

giving bifunctors $A X Y = (\llbracket X \rrbracket S_Y, \text{All } X P_Y)$ and $E X Y = (\llbracket X \rrbracket S_Y, \text{Exists } X P_Y)$ on shapes $\sum_s S_Y^{P_X s}$.

Proposition 3.4 ([8], A/E liftings). *The $\exists$ -lifting is exactly composition: $E = \triangleleft$, a bifunctor on all of **Cont**, with $E X (E Y C) = E (X \triangleleft Y) C$ the associativity of $\triangleleft$ and unit $E y C = C$. The $\forall$ -lifting A is a bifunctor only on cartesian morphisms in its first argument: a natural pushforward along $\alpha = (u, \varphi)$ is indexed by set-sections of the backward map φ , and the section-count is 0, ≥ 2 , or exactly 1 according as each φ_s is non-surjective, surjective-but-not-injective, or bijective. Hence A extends canonically to $\mathbf{Cont}_{\text{cart}} \times \mathbf{Cont} \rightarrow \mathbf{Cont}$ only. On this domain A is a left module of the $\triangleleft$ -monoidal category $(\mathbf{Cont}, \triangleleft, y)$:*

$$A X (A Y C) = A (X \triangleleft Y) C = A (E X Y) C, \quad A y C = C.$$

The mixed comparison $AX(EYC) \rightarrow E(AXY)C$ is an isomorphism iff X is linear ($|P_X s| = 1$ for every s).

The cartesian restriction is precisely the phenomenon “ A lifts through α iff α is cartesian”, which for $\alpha = \mu_M$ is the classical criterion that M lifts to containers iff M is cartesian, seen one categorical level down. In the language of §2, $E = \Sigma$ is the free (co-Yoneda) direction and $A = \Pi$ its right adjoint on the cartesian sublattice.

Remark 3.5 (Lift / CoLift / BiLift). Orestis’ AGDA development of the container effect library organises the same data as a trichotomy *Lift*, *CoLift*, *BiLift* of a monad through a container (Kodamai `agda-containers`, `Containers/Effects`; personal communication). Proposition 3.4 is the semantic content of that trichotomy: $E = \Sigma$ is the covariant (Lift) direction, $A = \Pi$ the contravariant (CoLift) one, and their agreement is exactly the linear case.

3.3. M -containers as $\text{Fam}(\text{Kl}(M)^{\text{op}})$, and codensity. The change of base to the Kleisli category is the central instance, and the one where the faithfulness diagnostic first bites.

Proposition 3.6 ([8], Thm 1–2). *Let M be a monad on **Set**. There is an identity-on-data equivalence $M\text{-}\mathbf{Cont} \simeq \text{Fam}(\text{Kl}(M)^{\text{op}})$, and the effectful extension factors through the ordinary one:*

$$\llbracket S, P \rrbracket_M = \llbracket S, P \rrbracket_{\circ M}, \quad \llbracket S, P \rrbracket_M(X) = \sum_{s \in S} \mathbf{Set}(P_s, MX) = \sum_{s \in S} \text{Kl}(M)(P_s, X),$$

naturally in (S, P) . The extension $\llbracket - \rrbracket_M : M\text{-}\mathbf{Cont} \rightarrow [\mathbf{Set}, \mathbf{Set}]$ is always faithful, and

$$\llbracket - \rrbracket_M \text{ is full} \iff \underbrace{M \text{ is codense}}_{M \Rightarrow \text{Ran}_M M \text{ iso}} \wedge \underbrace{\text{each } \mathbf{Set}(A, M-) \text{ is connected.}}_{\text{Ran}_M \text{ preserves shape-coproducts}}$$

If M is affine ($M1 \cong 1$) the connectedness clause holds automatically, so *affine + codense $\Rightarrow$ full*. Among polynomial effects *Id* is full while *Maybe*, *exceptions* $X + E$, *writer* $E \times X$ and *reader* X^S ($|S| \geq 2$) are not; the *finite-distribution monad* *Dist*, being affine and codense, is full.

Two points deserve emphasis because they correct a natural but wrong guess. First, the criterion is *not* “ M preserves coproducts”: that is the criterion for the coarser Kleisli-enriched target of §4, and the right invariant for the target $[\mathbf{Set}, \mathbf{Set}]$ is codensity. Second, the verdict is genuinely selective: probabilistic positions keep fullness, while error, reader, writer and nondeterministic positions destroy it. The codensity monad $\text{Ran}_M M$ is the exact measure of the defect, a fact we use again in §4.

3.4. The free monad on a container. Algebraic effects are presented by a signature, and a signature is a container: a set of operations with an arity (a set of positions) each. The free monad on the signature functor is the

type of effect trees, and it is a monad *on* **Cont** built from a single container by iterated composition. We record the linear instance, where the answer is cleanest and connects to a familiar algebraic object.

Proposition 3.7 ([9], free $\triangleleft$ -monoid). *Let $C = (\star, A)$ be a one-shape linear container over a monoidal base $(\mathcal{V}, \otimes, k)$ (e.g. $\mathcal{V} = \mathbf{Vec}$, A finite-dimensional), so $\llbracket C \rrbracket(W) = A \otimes W$. The free $\triangleleft$ -monoid on C is*

$$C^* = (\mathbb{N}, (A^{\otimes n})_{n \in \mathbb{N}}), \quad \llbracket C^* \rrbracket(W) = \bigoplus_{n \geq 0} A^{\otimes n} \otimes W = T(A) \otimes W,$$

with $T(A)$ the tensor algebra, and it carries the free-monad structure on $\llbracket C \rrbracket$: unit the degree-0 injection and multiplication induced by concatenation $A^{\otimes m} \otimes A^{\otimes n} \rightarrow A^{\otimes(m+n)}$. Thus the free monad on a linear container is the free monoid $T(A)$ acting by $T(A) \otimes (-)$; over **Vec** this is exactly O’Neill’s free monad, realised functorially.

Remark 3.8 (The chain that computes it). The free monad is the colimit of the Adámek chain of *partial sums* $Y_n = \bigoplus_{k < n} A^{\otimes k} \otimes W$, not of the bare powers $\llbracket C \rrbracket^n$: the endofunctor $A \otimes (-)$ is pointable but never well-pointed, so the naive ω -chain does not converge to the monad. The pointing that repairs it is the two-shape container $(\{\text{stop}, \text{layer}\}, P_{\text{stop}} = 0, P_{\text{layer}} = A)$ whose empty-position “stop” shape supplies the degree-0 summand — the residual/skip connection, read container-theoretically.

More generally, the free monad on an arbitrary signature container is again a monad on **Cont** obtained by the same iterated-composition recipe: this is the standard reading of an algebraic signature as a polynomial functor and its effect trees as the free monad, whose handler semantics has a complete categorical account [3]. Our $\triangleleft$ -monoid description is the presentation-level shadow of that account.

3.5. When does a monad on Set give a monad on Cont? The last construction is the subtlest, and it is where polynomiality — *representability* of the effect — enters. We ask when the essential image of $\llbracket - \rrbracket_M$ is closed under functor composition, so that composing two effectful datatypes lands on another effectful datatype.

The obstruction is visible in one identity. For any M -containers p, q ,

$$\llbracket p \rrbracket_M \circ \llbracket q \rrbracket_M = (\llbracket p \rrbracket \circ M \circ \llbracket q \rrbracket) \circ M = G \circ M, \quad G := \llbracket p \rrbracket \circ M \circ \llbracket q \rrbracket,$$

using the factorisation of Proposition 3.6 twice. So *every* composite of two M -extensions already has the shape $G \circ M$; to land back in the essential image one must rewrite the *middle* $M \circ \llbracket q \rrbracket$ as (the extension of) a container. That is possible exactly when M itself is a container — i.e. when $M \cong \sum_{i \in I} \mathbf{Set}(B_i, -)$ is *polynomial* (representable) in the sense of [4]. This is the operational form of the composition question: *closure under composition is a representability condition on the middle effect*, no more and no less.

Proposition 3.9 ([8], composition). *If M is polynomial, with $[M]$ the container presenting it, then splicing $[M]$ in the middle,*

$$p \triangleleft_M q := p \triangleleft [M] \triangleleft q, \quad \llbracket p \triangleleft_M q \rrbracket_M \cong \llbracket p \rrbracket_M \circ \llbracket q \rrbracket_M \quad \text{naturally in } X,$$

exhibits the essential image of $\llbracket - \rrbracket_M$ as closed under composition. The operation $\triangleleft_M$ is associative but has no unit up to container isomorphism unless $M = \text{Id}$ (it is semigroupal, not monoidal). Conversely, closure forces a cardinality growth law $|M(N(MX))| = R_N(|MX|)$ for a fixed polynomial R_N ; already at $p = q = \text{Id}$ this excludes powerset $\mathcal{P}$, nonempty powerset $\mathcal{P}^+$ and Dist , none of which is polynomial.

The full converse — closure $\Rightarrow M$ polynomial — is proved for the analytic monads of non-flat symmetric operads in [8], where the dividing line is a sharp representability/rigidity condition on the middle effect; we do not reproduce that combinatorial analysis here.

Corollary 3.10 (Two independent invariants). *Composability and fullness are logically independent. The writer monad $E \times (-)$ is polynomial (so its M -containers compose) yet is not codense (so $\llbracket - \rrbracket_M$ is not full); the distribution monad Dist is affine and codense (so $\llbracket - \rrbracket_M$ is full) yet is not polynomial (so its M -containers do not compose). In particular the heuristic “composes $\iff$ commutative and affine” is false: $\mathcal{P}, \mathcal{P}^+, \text{Dist}$ are commutative but fail composition, while non-affine Maybe and writer compose.*

This is the first invariant of the effect: *polynomiality governs composition*. The second, *codensity governs fullness*, is the theme of §4, where we show that passing to an enriched base does not rescue it.

4. ENRICHMENT: THREE EXTENSIONS AND THE COLLAPSE OF FULLNESS

The faithfulness diagnostic of §3.3 was run against the target $[\mathbf{Set}, \mathbf{Set}]$. But Ghani observed that when the base $\mathcal{C}$ is monoidal closed one can form a container extension valued in $\mathcal{C}$ itself, using $\mathcal{C}$ ’s internal hom, and asked whether this *enriched* extension enjoys a uniform full-and-faithfulness theorem — and, if so, whether it is available over the effectful bases $\mathcal{C} = \text{Kl}(M)$. The reader monad appears to make this urgent: its Kleisli category is cartesian closed (so the enriched extension exists), yet §3.3 said reader fails fullness. Is there a contradiction?

There is not. The resolution is that *three* distinct functors are in play, with three notions of naturality; once separated, the reader is not full in any of them, consistently. We name them, prove the availability criterion (Kock), tabulate the bases, and then prove the collapse.

4.1. The three extensions. Fix a monad M on $\mathbf{Set}$ and write $\mathcal{C} = \text{Kl}(M)$.

- (A) The **ordinary** extension $\llbracket - \rrbracket_M : \text{Fam}(\text{Kl}(M)^{\text{op}}) \rightarrow [\mathbf{Set}, \mathbf{Set}]$, $\llbracket S, P \rrbracket_M(X) = \sum_s \mathbf{Set}(P_s, MX)$. Morphisms of the target are *pure* natural transformations. Faithful always; full iff M codense and each $\mathbf{Set}(A, M-)$ connected (Proposition 3.6).

- (B) The **Kleisli-presheaf** extension $\llbracket - \rrbracket^{\text{Kl}}: \text{Fam}(\text{Kl}(M)^{\text{op}}) \rightarrow [\text{Kl}(M), \mathbf{Set}]$, $\llbracket S, P \rrbracket^{\text{Kl}} = \sum_s \text{Kl}(M)(P_s, -)$. This is the free-coproduct completion of $\text{Kl}(M)^{\text{op}}$: a coproduct of representables. Morphisms of the target are *Kleisli*-natural. By ordinary co-Yoneda it is *always* full and faithful, with no hypothesis on M .
- (C) Ghani’s **self-enriched** extension. When $\mathcal{C}$ is symmetric monoidal closed with internal hom $[-, -]$, set

$$\llbracket S, P \rrbracket = \sum_{s \in S} [P_s, -]: \mathcal{C} \longrightarrow \mathcal{C},$$

valued in $\mathcal{C}$ -enriched endofunctors. Enriched co-Yoneda [5] gives Ghani’s desideratum $\text{Nat}(\sum_s [P_s, -], F) \cong \prod_s F(P_s)$ at the level of enriched hom-objects.

The three are related by a single factorisation, proved in [8]:

$$\llbracket - \rrbracket_M = R \circ \llbracket - \rrbracket^{\text{Kl}}, \quad R = (-) \circ F: [\text{Kl}(M), \mathbf{Set}] \rightarrow [\mathbf{Set}, \mathbf{Set}],$$

where $F: \mathbf{Set} \rightarrow \text{Kl}(M)$ is the free functor. On objects (A) and (B) agree; R forgets Kleisli-naturality, keeping only pure-naturality. *All* loss of ordinary fullness lives in R , and its size is measured exactly by the codensity monad $\text{Ran}_M M$: pure-natural transformations strictly contain the Kleisli-natural (equivalently, container) ones unless M is codense.

4.2. Availability: when is the base closed? (Kock). Extension (C) requires $\mathcal{C} = \text{Kl}(M)$ to be closed, so we recall the criterion.

Proposition 4.1 (Kock [6, 7]). *Let M be a strong monad on $\mathbf{Set}$.*

- (1) $\text{Kl}(M)$ is symmetric monoidal (tensor $A \times B$ on objects, unit 1 , F strict monoidal) iff M is commutative.
- (2) $\text{Kl}(M)$ is monoidal closed iff the free algebras form an exponential ideal, i.e. each $(MB)^A \cong M[A, B]$ is free.
- (3) $\text{Kl}(M)$ is cartesian closed iff additionally M preserves finite products.

Consequently a genuinely effectful monad whose Kleisli category has biproducts (hence a zero object) is never cartesian closed — a CCC with a zero object is trivial — so the best such an effect can reach is monoidal closure.

Write $\mathcal{CL} = \{M \text{ commutative} : \text{Kl}(M) \text{ monoidal closed}\}$ for the availability class of (C). Table 1 runs the change-of-base bases against these conditions; the “monoidal closed” column is exactly where (C) is available.

4.3. Fullness: connectedness of the unit. Availability is not fullness. By the flagship criterion of [9] (there written for a general closed base), the self-enriched extension (C) is full and faithful iff the monoidal unit I of $\mathcal{C}$ is *connected*, i.e. $\mathcal{C}(I, -)$ preserves small coproducts — this is what matches the transformation set to the shape-coproduct $\sum_s$ in $\prod_s F(P_s)$. Write $\mathcal{UN} = \{M : \text{the unit } 1 \text{ of } \text{Kl}(M) \text{ is connected}\}$. Since $\text{Kl}(M)(1, X) = \mathbf{Set}(1, MX) = MX$, membership $M \in \mathcal{UN}$ says precisely that M preserves small coproducts.

Base $\mathcal{C}$	monoidal?	mon. closed?	cart. closed?
$\text{Kl}(\text{Maybe}) = \mathbf{Par}$	yes	yes	no
$\text{Kl}(\text{Writer}_E)$	iff E comm.	no (over $\mathbf{Set}$)	no
$\text{Kl}(\text{Reader}_S) = \text{coKl}(- \times S)$	yes	yes	yes
$\text{Kl}(\mathcal{P}) = \mathbf{Rel}$	yes	yes	no
$\text{Kl}(\text{Dist}) = \mathbf{Stoch}$	yes	no	no
$\text{Kl}(\beta)$, $\text{Kl}(\text{Cont})$, $\text{Kl}(\text{List})$	no	no	no
$\mathbf{Vec}$ (<i>non-Kleisli</i>)	yes	yes	no
$\mathbf{Cat}$, $\mathbf{Set}$ (<i>non-Kleisli</i>)	yes	yes	yes

TABLE 1. Availability of the self-enriched extension across the change-of-base bases. “Monoidal” needs commutativity; β (ultrafilter), continuation and list fail it, so are only premonoidal. **Stoch** is monoidal but not closed ($(\text{Dist}B)^A$ is a product of simplices, not a simplex). **Rel**, **Vec** are compact closed; **Par** is closed but not cartesian; only **Set**, **Cat**, $\text{Kl}(\text{Reader})$ are cartesian closed.

	connected ($\mathcal{UN}$)	disconnected
closed ($\mathcal{CL}$)	Id (target)	$\text{Reader}_S (S \geq 2)$; Maybe ; $\mathcal{P}$
not closed	Writer_E (E nontrivial)	Dist ; List

TABLE 2. The two axes are independent. Each cell holds a commutative strong monad. The self-enriched extension is available in the top row and full in the left column; only Id is in both.

The two conditions are logically independent (Table 2), and this is the crux: closedness and connectedness are orthogonal axes. Ghani’s cartesian-closed reader sits in $\mathcal{CL}$ but not $\mathcal{UN}$; the writer monad sits in $\mathcal{UN}$ but not $\mathcal{CL}$.

4.4. The collapse. We now prove that over a Kleisli base the two conditions meet only at the identity.

Theorem 4.2 ($\mathcal{CL} \cap \mathcal{UN} = \{\text{Id}\}$). *Let M be a commutative strong monad on $\mathbf{Set}$. The self-enriched M -container extension $\sum_s [P_s, -]: \text{Kl}(M) \rightarrow \text{Kl}(M)$ is full and faithful if and only if $M \cong \text{Id}$ as a monad.*

Proof. By §4.3, fullness $\iff M \in \mathcal{CL} \cap \mathcal{UN}$. We show this intersection is $\{\text{Id}\}$.

Step 1: $\mathcal{UN}$ forces the writer form. Let $M \in \mathcal{UN}$, so M preserves small coproducts. Put $E := M1$. For a set T , the assembly of the injections

$M(\iota_t): M1 \rightarrow MT$ over $t \in T$ (where $\iota_t: 1 \rightarrow T$ picks out t) is the copower-comparison map

$$\theta_T: T \times E \longrightarrow MT, \quad \theta_T(t, e) = M(\iota_t)(e),$$

which connectedness makes a bijection, naturally in T , with $\theta_1 = \text{id}_{M1}$. Hence $M \cong (-) \times E$ as a functor. The monad structure on $(-) \times E$ is forced to be the writer monad of a monoid structure (E, m, e_0) (the monad laws are the monoid laws), commutative since M is. Thus $\mathcal{UN} = \{\text{writer monads on commutative monoids}\}$, with $E = M1$; conversely every writer monad preserves small coproducts because $\times$ distributes over $\coprod$ in **Set**.

Step 2: $\mathcal{CL}$ forces $E \cong 1$. Let $M \in \mathcal{CL} \cap \mathcal{UN}$, so $MX \cong X \times E$. Monoidal closure requires $(-) \times A$ to have a right adjoint for every object A , in particular for $A = \emptyset$. For all C ,

$$\text{Kl}(M)(C \times \emptyset, B) = \text{Kl}(M)(\emptyset, B) = \mathbf{Set}(\emptyset, MB) = 1,$$

so the representing object $[\emptyset, B]$ is terminal in $\text{Kl}(M)$; call it $\top$. A terminal object satisfies $\mathbf{Set}(C, M\top) = \text{Kl}(M)(C, \top) \cong 1$ for all C , forcing $M\top \cong 1$. Using the writer form, $\top \times E \cong M\top \cong 1$, whence $|\top| \cdot |E| = 1$ and $E \cong 1$. Therefore $MX \cong X \times 1 \cong X$, and the only monad structure on Id is the identity monad: $M \cong \text{Id}$.

Step 3: Id qualifies. $\text{Kl}(\text{Id}) = \mathbf{Set}$ is cartesian closed, so $\text{Id} \in \mathcal{CL}$; and $\mathbf{Set}(1, -) = \text{Id}$ preserves all coproducts, so $\text{Id} \in \mathcal{UN}$. Its self-enriched extension $\sum_s (-)^{P_s}$ is the classical container extension, which is full and faithful. Hence $\mathcal{CL} \cap \mathcal{UN} = \{\text{Id}\}$. $\square$

Corollary 4.3 (No idempotent escape). *No nontrivial idempotent (localization) monad on $\mathbf{Set}$ lies in $\mathcal{CL} \cap \mathcal{UN}$. Indeed by Step 1 membership in $\mathcal{UN}$ forces the writer form, and a writer monad is idempotent only when $E \cong 1$; the terminal monad $LX = 1$ already fails connectedness, since $L(1 + 1) = 1 \neq 2 = L1 + L1$.*

Remark 4.4 (The two open gaps of the underlying criterion do not affect the collapse). The flagship criterion of [9] proves necessity of unit-connectedness via the *copower* test, and whether that upgrades to preservation of *all* small coproducts in every closed base is left open there. It is irrelevant here: Step 1 uses only copower-preservation $(T \cdot 1)$, which already forces the writer form, so every non- Id member of $\mathcal{CL}$ fails even the copower test. Likewise, weakening $\mathcal{UN}$ to finite-coproduct preservation would still give $M1 \cong 1$ and $Mn \cong n$ on finite sets; whether a commutative closed monad differing from Id only on infinite sets could then exist is the one question a weaker definition would leave open, and we conjecture not. Under the definition used here the classification is complete.

4.5. The reconciliation. Theorem 4.2 dissolves the apparent paradox. Ghani's claim is that the *base* $\text{Kl}(\text{Reader}_S)$ is cartesian closed — so construction (C)

is *available*. It is not a claim that any container extension is full. And in fact fullness fails in every picture, for one reason seen through three lenses:

- **(A) ordinary:** $\mathbf{Reader}_S$ is affine but not codense, so $\llbracket - \rrbracket_M$ is not full (Proposition 3.6).
- **(C) self-enriched over $\mathbf{Kl}(\mathbf{Reader}_S)$:** the base is closed, so (C) exists; but its unit 1 has global-points functor $\mathbf{Kl}(\mathbf{Reader}_S)(1, -) = \mathbf{Set}(S, -) = (-)^S$, which fails to preserve coproducts for $|S| \geq 2$. Disconnected unit $\Rightarrow$ (C) not full, by §4.3.
- **(B) Kleisli-presheaf:** always full and faithful — but its morphisms are the Kleisli-natural ones, not the pure-natural transformations (A) asks about.

So cartesian closedness buys the *availability* of an internal-hom extension, not its *fullness*. The reader’s failure is enrichment-invariant: it is non-codensity in (A) and a disconnected unit in (C), one obstruction wearing two masks. The dictionary is:

extension	available	full and faithful $\iff$
(C) self-enriched $\sum_s [P_s, -]$	$\mathcal{C}$ closed	unit of $\mathcal{C}$ connected
(B) Kleisli-presheaf $\llbracket - \rrbracket^{\mathbf{Kl}}$	always	always
(A) ordinary $\llbracket - \rrbracket_M$	always	M codense and each $\mathbf{Set}(A, M-)$ connected

bridged by $\llbracket - \rrbracket_M = R \circ \llbracket - \rrbracket^{\mathbf{Kl}}$, whose defect is the codensity monad $\mathbf{Ran}_M M$ — the exact gap between the always-faithful enriched picture and the codensity-gated ordinary one.

5. WHAT THE DIAGNOSTIC TEACHES

Read as a whole, the census and the collapse say something about the change-of-base programme that no single instance says on its own.

The frame is the content. Six ostensibly different constructions — position transfer, $\forall/\exists$ liftings, Kleisli containers, free monads on signatures, and the composition of effectful datatypes — are one construction, $\mathbf{Fam}((-)^{\mathbf{op}})$, applied to different bases or read in different variances. The position transfer (§3.1) and the $\forall/\exists$ liftings (§3.2) are fibrewise transports; the Kleisli identification (§3.3) is the genuine change of base; the free-monoid (§3.4) and composition (§3.5) results are about structure carried *along* that change. Naming the frame turns a list of theorems into a single diagram.

Full-and-faithfulness is a diagnostic, not a goal, and it exposes two invariants of an effect. Polynomiality (representability) governs *composition*: the essential image of $\llbracket - \rrbracket_M$ is closed under composition iff the middle effect is a container (§3.5). Codensity governs *fullness* into $[\mathbf{Set}, \mathbf{Set}]$ (§3.3), and the same invariant reappears, under the name unit-connectedness, as fullness of the enriched extension (§4.3). The two invariants are independent (Corollary 3.10): distributions compose no datatypes yet are full, writers compose datatypes yet are not full.

Enrichment relocates the obstruction; it does not remove it. This is the sharp lesson of Theorem 4.2: passing to a closed base to gain Ghani’s enriched-Yoneda formula does buy the *availability* of the self-enriched extension, but full-and-faithfulness then demands a connected unit, and over a Kleisli base “closed and connected” pins the effect to the identity. There is no effect monad over which one builds change-of-base containers $\text{Fam}(\text{Kl}(M)^{\text{op}})$ with a uniform full-and-faithful *self-enriched* semantics. Any nontrivial effect must therefore be carried either by the always-faithful Kleisli-presheaf extension (B) — paying the price that its transformations are Kleisli-natural rather than pure — or by the ordinary $[\mathbf{Set}, \mathbf{Set}]$ extension (A), with the codensity monad $\text{Ran}_M M$ measuring the fullness defect. For a calculus of effectful or agentic containers, where morphisms of containers are meant to be exactly the definable transformations of the datatype, (B) is the honest target and codensity is the number to watch.

A different, lossier question. Composition (§3.5) asks when $\llbracket p \rrbracket_M \circ \llbracket q \rrbracket_M$ is again an M -extension. A *distinct* question — when a distributive law $MM \Rightarrow M$ merges two layers of effect into one — is lossy: it collapses information that composition preserves, and its answer is governed by different data. We flag the systematic comparison of the two as the natural next step, but it is not the composition theorem of §3.5 in disguise.

Open questions and formalisation status.

- (1) The full converse of Proposition 3.9 (closure $\Rightarrow M$ polynomial) is proved for the analytic monads of non-flat symmetric operads and open in general; the residual case is a representability question about the trailing effect, reduced to familial representability [8].
- (2) The two definitional gaps in the underlying fullness criterion (copower versus all coproducts; finite versus small coproduct connectedness) do not affect Theorem 4.2, but closing them would make the enriched criterion of [9] unconditional.
- (3) The position transfer of §3.1 is verified in Lean (the coordinate proof of the comonad laws, `[Quot.sound]`-only); the free $\triangleleft$ -monoid unit laws of §3.4 are likewise machine-checked [9]. The collapse of Theorem 4.2 is not yet formalised; its two elementary steps (writer form, terminal-object argument) are natural candidates.

REFERENCES

- [1] M. Abbott, T. Altenkirch, N. Ghani, *Containers: constructing strictly positive types*, Theoret. Comput. Sci. **342** (2005), 3–27.
- [2] D. Ahman and T. Uustalu, *Directed containers as categories*, Electron. Proc. Theor. Comput. Sci. **207** (2016), 89–98. arXiv:1604.01187.
- [3] S. Kura, *On complete categorical semantics for effect handlers*, preprint, 2026. arXiv:2602.03275.
- [4] N. Gambino and J. Kock, *Polynomial functors and polynomial monads*, Math. Proc. Cambridge Philos. Soc. **154** (2013), 153–192. arXiv:0906.4931.

- [5] G. M. Kelly, *Basic Concepts of Enriched Category Theory*, London Math. Soc. Lecture Note Ser. **64**, Cambridge Univ. Press, 1982.
- [6] A. Kock, *Monads on symmetric monoidal closed categories*, Arch. Math. (Basel) **21** (1970), 1–10.
- [7] A. Kock, *Closed categories generated by commutative monads*, J. Austral. Math. Soc. **12** (1971), 405–424.
- [8] MacBeth, *Two invariants of an effect monad: codensity governs fullness, polynomiality governs composition*, Kodamai preprint, 2026.
- [9] MacBeth, *Containers over a base*, Kodamai working paper, 2026.
- [10] N. Niu and D. I. Spivak, *Polynomial Functors: A Mathematical Theory of Interaction*, book draft, 2023. arXiv:2312.00990.

KODAMAI