PROPERTY CONDITION ASSESSMENT

Zephyr Office Center | Louisville, KY

Property	Zephyr Office Center
Address	1475 Cherry Drive, Louisville, KY 59274
Site Visit Date	September 11, 2021
Client	Granite Lane Realty
Immediate Repairs	$105,000

Improvements Description

The building is served by redundant elevators, a backup generator and a high-efficiency chiller plant. Exterior finishes comprise brick veneer, fiber-cement siding and aluminum storefront glazing in good condition. Weighted average lease term remaining is 8 years and in-place rents average $30 per square foot, full service gross. The building features a renovated lobby, structured parking at a ratio of 13 per 1,000 square feet, and a tenant lounge with fitness center. Zephyr Office Center was originally constructed in 1994 and consists of 188,992 SF in a building of 40 stories.

The roof is a 23-year membrane system with an estimated remaining useful life of 4 years. Floor plates are efficient and column-spacing supports open and private-office layouts. The building is served by redundant elevators, a backup generator and a high-efficiency chiller plant. The building features a renovated lobby, structured parking at a ratio of 41 per 1,000 square feet, and a tenant lounge with fitness center.

Deferred Maintenance

Domestic water piping is copper and PVC with no evidence of widespread leakage. Elevators were last modernized 9 years ago and are operating without deficiency. ADA observations include non-compliant slopes at two accessible routes and signage at parking; cost to cure is estimated at $449,000. The roofing system exhibits localized ponding and sealant deterioration; spot repairs are recommended within 12 months.

The roofing system exhibits localized ponding and sealant deterioration; spot repairs are recommended within 12 months. Windows and exterior doors are in fair condition; sealant replacement is recommended at selected locations. Electrical service is adequate for current demand; select panels are nearing the end of their useful life. Elevators were last modernized 9 years ago and are operating without deficiency. ADA observations include non-compliant slopes at two accessible routes and signage at parking; cost to cure is estimated at $363,000.

Construction Details

Exterior finishes comprise brick veneer, fiber-cement siding and aluminum storefront glazing in good condition. Mechanical systems include rooftop package units and central plant equipment of varying age. The building is served by redundant elevators, a backup generator and a high-efficiency chiller plant. Common area interiors have been refreshed within the last 6 years and are in average to good condition.

Common area interiors have been refreshed within the last 10 years and are in average to good condition. The building features a renovated lobby, structured parking at a ratio of 48 per 1,000 square feet, and a tenant lounge with fitness center. Zephyr Office Center was originally constructed in 1994 and consists of 188,992 SF in a building of 24 stories. Floor plates are efficient and column-spacing supports open and private-office layouts.

Observed Conditions

Asphalt paving shows alligator cracking and should be sealcoated and restriped during the next 47 months. Windows and exterior doors are in fair condition; sealant replacement is recommended at selected locations. Electrical service is adequate for current demand; select panels are nearing the end of their useful life. ADA observations include non-compliant slopes at two accessible routes and signage at parking; cost to cure is estimated at $378,000.

ADA observations include non-compliant slopes at two accessible routes and signage at parking; cost to cure is estimated at $269,000. Elevators were last modernized 11 years ago and are operating without deficiency. The roofing system exhibits localized ponding and sealant deterioration; spot repairs are recommended within 12 months. Windows and exterior doors are in fair condition; sealant replacement is recommended at selected locations.

Building Systems

FICTITIOUS SAMPLE DOCUMENT — all names, figures and entities are invented for classroom training use only

Construction Details

The roof is a 40-year membrane system with an estimated remaining useful life of 12 years. Zephyr Office Center was originally constructed in 1994 and consists of 188,992 SF in a building of 32 stories. The structure is of wood-frame, masonry and steel-frame construction on a slab-on-grade foundation. The building features a renovated lobby, structured parking at a ratio of 13 per 1,000 square feet, and a tenant lounge with fitness center. Life-safety systems include a fully sprinklered building, addressable fire alarm panel and emergency lighting.

Mechanical systems include rooftop package units and central plant equipment of varying age. Floor plates are efficient and column-spacing supports open and private-office layouts. The building is served by redundant elevators, a backup generator and a high-efficiency chiller plant. Exterior finishes comprise brick veneer, fiber-cement siding and aluminum storefront glazing in good condition. Weighted average lease term remaining is 5 years and in-place rents average $30 per square foot, full service gross.

Deferred Maintenance

Electrical service is adequate for current demand; select panels are nearing the end of their useful life. Asphalt paving shows alligator cracking and should be sealcoated and restriped during the next 33 months. The roofing system exhibits localized ponding and sealant deterioration; spot repairs are recommended within 12 months. Elevators were last modernized 5 years ago and are operating without deficiency.

Elevators were last modernized 4 years ago and are operating without deficiency. ADA observations include non-compliant slopes at two accessible routes and signage at parking; cost to cure is estimated at $165,000. Electrical service is adequate for current demand; select panels are nearing the end of their useful life. Asphalt paving shows alligator cracking and should be sealcoated and restriped during the next 21 months. Windows and exterior doors are in fair condition; sealant replacement is recommended at selected locations.

Building Systems

Common area interiors have been refreshed within the last 8 years and are in average to good condition. Weighted average lease term remaining is 8 years and in-place rents average $30 per square foot, full service gross. The roof is a 38-year membrane system with an estimated remaining useful life of 6 years. Life-safety systems include a fully sprinklered building, addressable fire alarm panel and emergency lighting. Zephyr Office Center was originally constructed in 1994 and consists of 188,992 SF in a building of 34 stories.

Life-safety systems include a fully sprinklered building, addressable fire alarm panel and emergency lighting. Floor plates are efficient and column-spacing supports open and private-office layouts. The roof is a 37-year membrane system with an estimated remaining useful life of 7 years. Common area interiors have been refreshed within the last 7 years and are in average to good condition. The structure is of wood-frame, masonry and steel-frame construction on a slab-on-grade foundation.

Deferred Maintenance

Electrical service is adequate for current demand; select panels are nearing the end of their useful life. Windows and exterior doors are in fair condition; sealant replacement is recommended at selected locations. Asphalt paving shows alligator cracking and should be sealcoated and restriped during the next 40 months. Domestic water piping is copper and PVC with no evidence of widespread leakage.

The roofing system exhibits localized ponding and sealant deterioration; spot repairs are recommended within 12 months. Domestic water piping is copper and PVC with no evidence of widespread leakage. Asphalt paving shows alligator cracking and should be sealcoated and restriped during the next 28 months. Electrical service is adequate for current demand; select panels are nearing the end of their useful life. ADA observations include non-compliant slopes at two accessible routes and signage at parking; cost to cure is estimated at $20,000. Elevators were last modernized 11 years ago and are operating without deficiency.

Improvements Description

The building is served by redundant elevators, a backup generator and a high-efficiency chiller plant. Zephyr Office Center was originally constructed in 1994 and consists of 188,992 SF in a building of 14 stories. Mechanical systems include rooftop package units and central plant equipment of varying age. The structure is of wood-frame, masonry and steel-frame construction on a slab-on-grade foundation. The building features a renovated lobby, structured parking at a ratio of 5 per 1,000 square feet, and a tenant lounge with fitness center.

FICTITIOUS SAMPLE DOCUMENT — all names, figures and entities are invented for classroom training use only

Immediate Repairs and Replacement Reserve Schedule

System	Age (yrs)	EUL	RUL	Condition	Immediate	Reserve (10-yr)
Roof	10	10	0	Fair	$2,000	$116,000
Paving	16	40	24	Fair	$1,000	$161,000
HVAC	12	14	2	Fair	$28,000	$114,000
Plumbing	11	38	27	Poor	$5,000	$106,000
Electrical	3	16	13	Poor	$1,000	$228,000
Elevators	30	36	6	Fair	$10,000	$258,000
Fire/Life Safety	3	17	14	Poor	$26,000	$142,000
Windows	11	23	12	Poor	$32,000	$224,000
Siding/Facade	26	37	11	Poor	$20,000	$179,000
Flooring	2	30	28	Poor	$39,000	$162,000
Appliances	30	36	6	Fair	$36,000	$242,000
Landscaping	14	18	4	Fair	$19,000	$91,000
Pool/Amenity	1	35	34	Fair	$10,000	$272,000
Signage	13	13	0	Good	$39,000	$126,000
Fencing	25	39	14	Poor	$3,000	$245,000
Roof (2)	5	22	17	Poor	$23,000	$10,000
Paving (2)	5	13	8	Fair	$8,000	$236,000
HVAC (2)	14	23	9	Good	$20,000	$175,000
Plumbing (2)	9	10	1	Good	$26,000	$80,000
Electrical (2)	8	28	20	Fair	$40,000	$116,000
Elevators (2)	1	31	30	Good	$36,000	$160,000
Fire/Life Safety (2)	20	32	12	Poor	$38,000	$248,000
Windows (2)	12	15	3	Poor	$13,000	$229,000
Siding/Facade (2)	9	12	3	Fair	$20,000	$182,000
Flooring (2)	21	21	0	Fair	$8,000	$139,000
Appliances (2)	14	28	14	Fair	$10,000	$141,000
Landscaping (2)	14	18	4	Good	$32,000	$151,000
Pool/Amenity (2)	5	24	19	Fair	$4,000	$2,000
Signage (2)	27	36	9	Fair	$20,000	$198,000
Fencing (2)	11	14	3	Good	$34,000	$136,000

Report generated 09/11/2021. Figures are unaudited and subject to change.

FICTITIOUS SAMPLE DOCUMENT — all names, figures and entities are invented for classroom training use only

Findings and Opinions of Cost

Item	Location	Observed Condition	Recommended Action	Priority	Est. Cost
Asphalt paving	Common	Alligator cracking	Mill and overlay	Reserve	$13,500
HVAC unit	Bldg A	Beyond useful life	Replace RTU	Year 1	$46,500
Window sealant	Common	Failed	Re-caulk	Reserve	$59,500
Fire extinguishers	Mechanical	Expired tags	Service	Year 2-5	$2,500
Sprinkler heads	Roof	Painted heads	Replace	Immediate	$24,500
Asphalt paving	Mechanical	Alligator cracking	Mill and overlay	Year 2-5	$63,500
Asphalt paving	Site	Alligator cracking	Mill and overlay	Reserve	$2,000
Asphalt paving	Roof	Alligator cracking	Mill and overlay	Immediate	$6,000
Window sealant	Common	Failed	Re-caulk	Reserve	$71,500
Handrail	Roof	Loose	Secure	Year 2-5	$4,500
Window sealant	Mechanical	Failed	Re-caulk	Year 1	$46,500
Sidewalk	Bldg B	Trip hazards	Grind / replace	Year 1	$20,500
Fire extinguishers	Bldg A	Expired tags	Service	Immediate	$40,500
Asphalt paving	Roof	Alligator cracking	Mill and overlay	Year 2-5	$50,000
Sidewalk	Mechanical	Trip hazards	Grind / replace	Reserve	$43,000
Asphalt paving	Bldg A	Alligator cracking	Mill and overlay	Immediate	$6,000
Asphalt paving	Mechanical	Alligator cracking	Mill and overlay	Immediate	$30,000
Window sealant	Roof	Failed	Re-caulk	Year 2-5	$4,500
Stair treads	Bldg A	Worn / loose	Replace treads	Year 1	$49,500
Dumpster enclosure	Roof	Damaged gate	Repair	Reserve	$59,000
Stair treads	Roof	Worn / loose	Replace treads	Immediate	$34,500
Dumpster enclosure	Bldg A	Damaged gate	Repair	Year 2-5	$23,500
Dumpster enclosure	Common	Damaged gate	Repair	Immediate	$66,000
Sprinkler heads	Bldg A	Painted heads	Replace	Reserve	$70,500
Stair treads	Bldg A	Worn / loose	Replace treads	Year 1	$81,500
Asphalt paving	Bldg B	Alligator cracking	Mill and overlay	Year 1	$41,000
Asphalt paving	Mechanical	Alligator cracking	Mill and overlay	Year 2-5	$79,500
Roof membrane	Bldg B	Ponding / seams	Re-seal and repair	Immediate	$1,000
Handrail	Bldg A	Loose	Secure	Year 2-5	$49,000
Fire extinguishers	Site	Expired tags	Service	Reserve	$33,000
Dumpster enclosure	Mechanical	Damaged gate	Repair	Year 1	$7,500
Sidewalk	Bldg B	Trip hazards	Grind / replace	Reserve	$18,000
Dumpster enclosure	Bldg B	Damaged gate	Repair	Immediate	$69,000
Dumpster enclosure	Bldg B	Damaged gate	Repair	Year 2-5	$52,500
Fire extinguishers	Bldg A	Expired tags	Service	Reserve	$53,500
Handrail	Bldg A	Loose	Secure	Year 1	$14,000
Roof membrane	Site	Ponding / seams	Re-seal and repair	Reserve	$54,500
Roof membrane	Site	Ponding / seams	Re-seal and repair	Immediate	$84,500
Fire extinguishers	Roof	Expired tags	Service	Reserve	$54,500
Sprinkler heads	Roof	Painted heads	Replace	Reserve	$45,000
Window sealant	Common	Failed	Re-caulk	Year 2-5	$33,500

Report generated 09/11/2021. Figures are unaudited and subject to change.

FICTITIOUS SAMPLE DOCUMENT — all names, figures and entities are invented for classroom training use only

Observed Conditions

Asphalt paving shows alligator cracking and should be sealcoated and restriped during the next 12 months. Windows and exterior doors are in fair condition; sealant replacement is recommended at selected locations. Domestic water piping is copper and PVC with no evidence of widespread leakage. The roofing system exhibits localized ponding and sealant deterioration; spot repairs are recommended within 12 months. ADA observations include non-compliant slopes at two accessible routes and signage at parking; cost to cure is estimated at $309,000. Elevators were last modernized 6 years ago and are operating without deficiency.

The roofing system exhibits localized ponding and sealant deterioration; spot repairs are recommended within 12 months. Elevators were last modernized 3 years ago and are operating without deficiency. ADA observations include non-compliant slopes at two accessible routes and signage at parking; cost to cure is estimated at $229,000. Asphalt paving shows alligator cracking and should be sealcoated and restriped during the next 12 months. Windows and exterior doors are in fair condition; sealant replacement is recommended at selected locations.

Recommendations

Asphalt paving shows alligator cracking and should be sealcoated and restriped during the next 39 months. ADA observations include non-compliant slopes at two accessible routes and signage at parking; cost to cure is estimated at $96,000. Elevators were last modernized 7 years ago and are operating without deficiency. Electrical service is adequate for current demand; select panels are nearing the end of their useful life. Windows and exterior doors are in fair condition; sealant replacement is recommended at selected locations. Domestic water piping is copper and PVC with no evidence of widespread leakage.

The roofing system exhibits localized ponding and sealant deterioration; spot repairs are recommended within 12 months. Electrical service is adequate for current demand; select panels are nearing the end of their useful life. Elevators were last modernized 5 years ago and are operating without deficiency. Domestic water piping is copper and PVC with no evidence of widespread leakage. ADA observations include non-compliant slopes at two accessible routes and signage at parking; cost to cure is estimated at $60,000. Windows and exterior doors are in fair condition; sealant replacement is recommended at selected locations.

Observed Conditions

ADA observations include non-compliant slopes at two accessible routes and signage at parking; cost to cure is estimated at $423,000. Domestic water piping is copper and PVC with no evidence of widespread leakage. Windows and exterior doors are in fair condition; sealant replacement is recommended at selected locations. Elevators were last modernized 5 years ago and are operating without deficiency.

Asphalt paving shows alligator cracking and should be sealcoated and restriped during the next 3 months. Domestic water piping is copper and PVC with no evidence of widespread leakage. Electrical service is adequate for current demand; select panels are nearing the end of their useful life. Windows and exterior doors are in fair condition; sealant replacement is recommended at selected locations.

FICTITIOUS SAMPLE DOCUMENT — all names, figures and entities are invented for classroom training use only

Improvements Description

Mechanical systems include rooftop package units and central plant equipment of varying age. Weighted average lease term remaining is 3 years and in-place rents average $30 per square foot, full service gross. The roof is a 26-year membrane system with an estimated remaining useful life of 11 years. Life-safety systems include a fully sprinklered building, addressable fire alarm panel and emergency lighting. The building is served by redundant elevators, a backup generator and a high-efficiency chiller plant. Floor plates are efficient and column-spacing supports open and private-office layouts.

The structure is of wood-frame, masonry and steel-frame construction on a slab-on-grade foundation. Mechanical systems include rooftop package units and central plant equipment of varying age. The building is served by redundant elevators, a backup generator and a high-efficiency chiller plant. Weighted average lease term remaining is 3 years and in-place rents average $30 per square foot, full service gross. The roof is a 37-year membrane system with an estimated remaining useful life of 5 years. Life-safety systems include a fully sprinklered building, addressable fire alarm panel and emergency lighting.

Recommendations

Elevators were last modernized 8 years ago and are operating without deficiency. Asphalt paving shows alligator cracking and should be sealcoated and restriped during the next 46 months. ADA observations include non-compliant slopes at two accessible routes and signage at parking; cost to cure is estimated at $279,000. The roofing system exhibits localized ponding and sealant deterioration; spot repairs are recommended within 12 months. Electrical service is adequate for current demand; select panels are nearing the end of their useful life. Windows and exterior doors are in fair condition; sealant replacement is recommended at selected locations.

ADA observations include non-compliant slopes at two accessible routes and signage at parking; cost to cure is estimated at $171,000. Domestic water piping is copper and PVC with no evidence of widespread leakage. Electrical service is adequate for current demand; select panels are nearing the end of their useful life. Asphalt paving shows alligator cracking and should be sealcoated and restriped during the next 14 months.

Building Systems

Exterior finishes comprise brick veneer, fiber-cement siding and aluminum storefront glazing in good condition. Common area interiors have been refreshed within the last 6 years and are in average to good condition. Mechanical systems include rooftop package units and central plant equipment of varying age. The roof is a 10-year membrane system with an estimated remaining useful life of 7 years. Weighted average lease term remaining is 9 years and in-place rents average $30 per square foot, full service gross. Life-safety systems include a fully sprinklered building, addressable fire alarm panel and emergency lighting.

Weighted average lease term remaining is 7 years and in-place rents average $30 per square foot, full service gross. Exterior finishes comprise brick veneer, fiber-cement siding and aluminum storefront glazing in good condition. The structure is of wood-frame, masonry and steel-frame construction on a slab-on-grade foundation. The building features a renovated lobby, structured parking at a ratio of 4 per 1,000 square feet, and a tenant lounge with fitness center. Mechanical systems include rooftop package units and central plant equipment of varying age. Zephyr Office Center was originally constructed in 1994 and consists of 188,992 SF in a building of 40 stories.

Observed Conditions

Elevators were last modernized 7 years ago and are operating without deficiency. Windows and exterior doors are in fair condition; sealant replacement is recommended at selected locations. ADA observations include non-compliant slopes at two accessible routes and signage at parking; cost to cure is estimated at $238,000. Electrical service is adequate for current demand; select panels are nearing the end of their useful life. The roofing system exhibits localized ponding and sealant deterioration; spot repairs are recommended within 12 months. Domestic water piping is copper and PVC with no evidence of widespread leakage.

The roofing system exhibits localized ponding and sealant deterioration; spot repairs are recommended within 12 months. Elevators were last modernized 11 years ago and are operating without deficiency. ADA observations include non-compliant slopes at two accessible routes and signage at parking; cost to cure is estimated at $172,000. Windows and exterior doors are in fair condition; sealant replacement is recommended at selected locations.

Building Systems

FICTITIOUS SAMPLE DOCUMENT — all names, figures and entities are invented for classroom training use only

Immediate Repairs and Replacement Reserve Schedule

System	Age (yrs)	EUL	RUL	Condition	Immediate	Reserve (10-yr)
Roof	29	38	9	Fair	$27,000	$277,000
Paving	9	13	4	Poor	$16,000	$179,000
HVAC	16	38	22	Fair	$11,000	$23,000
Plumbing	13	16	3	Fair	$14,000	$169,000
Electrical	9	35	26	Fair	$21,000	$159,000
Elevators	7	14	7	Fair	$1,000	$65,000
Fire/Life Safety	18	25	7	Fair	$12,000	$254,000
Windows	15	25	10	Fair	$2,000	$13,000
Siding/Facade	2	22	20	Fair	$20,000	$237,000
Flooring	5	13	8	Fair	$32,000	$195,000
Appliances	10	23	13	Fair	$8,000	$202,000
Landscaping	11	11	0	Poor	$0	$123,000
Pool/Amenity	2	12	10	Fair	$28,000	$224,000
Signage	13	29	16	Good	$2,000	$99,000
Fencing	9	16	7	Fair	$32,000	$83,000
Roof (2)	7	10	3	Fair	$33,000	$229,000
Paving (2)	5	25	20	Fair	$0	$247,000
HVAC (2)	20	29	9	Poor	$29,000	$142,000
Plumbing (2)	9	14	5	Good	$24,000	$222,000
Electrical (2)	8	17	9	Fair	$32,000	$101,000
Elevators (2)	11	36	25	Good	$33,000	$128,000
Fire/Life Safety (2)	1	16	15	Good	$23,000	$13,000
Windows (2)	19	40	21	Good	$33,000	$226,000
Siding/Facade (2)	1	32	31	Fair	$13,000	$173,000
Flooring (2)	6	15	9	Fair	$6,000	$8,000
Appliances (2)	10	12	2	Fair	$23,000	$183,000
Landscaping (2)	10	30	20	Good	$24,000	$198,000
Pool/Amenity (2)	1	18	17	Poor	$8,000	$240,000
Signage (2)	19	35	16	Good	$37,000	$236,000
Fencing (2)	9	17	8	Good	$7,000	$19,000

Report generated 09/11/2021. Figures are unaudited and subject to change.

FICTITIOUS SAMPLE DOCUMENT — all names, figures and entities are invented for classroom training use only

Findings and Opinions of Cost

Item	Location	Observed Condition	Recommended Action	Priority	Est. Cost
Window sealant	Common	Failed	Re-caulk	Year 1	$60,000
Sprinkler heads	Common	Painted heads	Replace	Immediate	$34,500
Sprinkler heads	Common	Painted heads	Replace	Year 2-5	$13,500
Roof membrane	Roof	Ponding / seams	Re-seal and repair	Reserve	$15,500
HVAC unit	Bldg B	Beyond useful life	Replace RTU	Year 1	$90,000
Fire extinguishers	Mechanical	Expired tags	Service	Year 1	$32,000
Dumpster enclosure	Mechanical	Damaged gate	Repair	Year 1	$69,500
Sprinkler heads	Bldg B	Painted heads	Replace	Year 2-5	$27,500
HVAC unit	Common	Beyond useful life	Replace RTU	Immediate	$19,500
Dumpster enclosure	Common	Damaged gate	Repair	Year 2-5	$42,000
Handrail	Site	Loose	Secure	Reserve	$20,500
Water heater	Roof	Corrosion	Replace	Immediate	$42,500
Sidewalk	Common	Trip hazards	Grind / replace	Immediate	$28,000
Handrail	Common	Loose	Secure	Immediate	$46,500
Water heater	Bldg B	Corrosion	Replace	Immediate	$40,000
Handrail	Common	Loose	Secure	Reserve	$74,500
Handrail	Common	Loose	Secure	Year 1	$26,000
Handrail	Common	Loose	Secure	Year 1	$41,000
Handrail	Bldg A	Loose	Secure	Reserve	$10,500
Sidewalk	Bldg A	Trip hazards	Grind / replace	Year 1	$56,500
Fire extinguishers	Mechanical	Expired tags	Service	Year 1	$54,500
HVAC unit	Site	Beyond useful life	Replace RTU	Immediate	$58,000
HVAC unit	Bldg B	Beyond useful life	Replace RTU	Immediate	$27,000
Asphalt paving	Bldg B	Alligator cracking	Mill and overlay	Reserve	$66,000
Handrail	Common	Loose	Secure	Immediate	$87,500
Dumpster enclosure	Bldg A	Damaged gate	Repair	Reserve	$14,000
Roof membrane	Roof	Ponding / seams	Re-seal and repair	Year 1	$37,500
Fire extinguishers	Common	Expired tags	Service	Year 2-5	$16,500
HVAC unit	Bldg A	Beyond useful life	Replace RTU	Immediate	$11,000
Window sealant	Bldg B	Failed	Re-caulk	Reserve	$18,500
Asphalt paving	Common	Alligator cracking	Mill and overlay	Year 1	$87,000
Dumpster enclosure	Roof	Damaged gate	Repair	Year 1	$7,500
Stair treads	Mechanical	Worn / loose	Replace treads	Year 2-5	$72,000
Fire extinguishers	Bldg A	Expired tags	Service	Immediate	$42,500
Water heater	Site	Corrosion	Replace	Reserve	$26,000
Water heater	Roof	Corrosion	Replace	Immediate	$56,500
Fire extinguishers	Roof	Expired tags	Service	Year 2-5	$5,000
HVAC unit	Bldg A	Beyond useful life	Replace RTU	Immediate	$70,500
Dumpster enclosure	Mechanical	Damaged gate	Repair	Immediate	$30,000
Water heater	Common	Corrosion	Replace	Year 2-5	$14,000

Report generated 09/11/2021. Figures are unaudited and subject to change.

FICTITIOUS SAMPLE DOCUMENT — all names, figures and entities are invented for classroom training use only

Deferred Maintenance

Windows and exterior doors are in fair condition; sealant replacement is recommended at selected locations. Electrical service is adequate for current demand; select panels are nearing the end of their useful life. Elevators were last modernized 9 years ago and are operating without deficiency. The roofing system exhibits localized ponding and sealant deterioration; spot repairs are recommended within 12 months.

Electrical service is adequate for current demand; select panels are nearing the end of their useful life. Domestic water piping is copper and PVC with no evidence of widespread leakage. The roofing system exhibits localized ponding and sealant deterioration; spot repairs are recommended within 12 months. Windows and exterior doors are in fair condition; sealant replacement is recommended at selected locations. ADA observations include non-compliant slopes at two accessible routes and signage at parking; cost to cure is estimated at $116,000.

Observed Conditions

The roofing system exhibits localized ponding and sealant deterioration; spot repairs are recommended within 12 months. ADA observations include non-compliant slopes at two accessible routes and signage at parking; cost to cure is estimated at $137,000. Elevators were last modernized 8 years ago and are operating without deficiency. Domestic water piping is copper and PVC with no evidence of widespread leakage. Asphalt paving shows alligator cracking and should be sealcoated and restriped during the next 24 months. Electrical service is adequate for current demand; select panels are nearing the end of their useful life.

Electrical service is adequate for current demand; select panels are nearing the end of their useful life. The roofing system exhibits localized ponding and sealant deterioration; spot repairs are recommended within 12 months. Elevators were last modernized 7 years ago and are operating without deficiency. Windows and exterior doors are in fair condition; sealant replacement is recommended at selected locations. Domestic water piping is copper and PVC with no evidence of widespread leakage. Asphalt paving shows alligator cracking and should be sealcoated and restriped during the next 38 months.

Recommendations

Elevators were last modernized 4 years ago and are operating without deficiency. Windows and exterior doors are in fair condition; sealant replacement is recommended at selected locations. ADA observations include non-compliant slopes at two accessible routes and signage at parking; cost to cure is estimated at $294,000. Asphalt paving shows alligator cracking and should be sealcoated and restriped during the next 14 months.

Elevators were last modernized 5 years ago and are operating without deficiency. ADA observations include non-compliant slopes at two accessible routes and signage at parking; cost to cure is estimated at $189,000. Asphalt paving shows alligator cracking and should be sealcoated and restriped during the next 28 months. Electrical service is adequate for current demand; select panels are nearing the end of their useful life. Windows and exterior doors are in fair condition; sealant replacement is recommended at selected locations.

FICTITIOUS SAMPLE DOCUMENT — all names, figures and entities are invented for classroom training use only

Building Systems

The roof is a 16-year membrane system with an estimated remaining useful life of 3 years. Exterior finishes comprise brick veneer, fiber-cement siding and aluminum storefront glazing in good condition. The building is served by redundant elevators, a backup generator and a high-efficiency chiller plant. Mechanical systems include rooftop package units and central plant equipment of varying age. Zephyr Office Center was originally constructed in 1994 and consists of 188,992 SF in a building of 5 stories.

Floor plates are efficient and column-spacing supports open and private-office layouts. Zephyr Office Center was originally constructed in 1994 and consists of 188,992 SF in a building of 12 stories. Life-safety systems include a fully sprinklered building, addressable fire alarm panel and emergency lighting. The roof is a 35-year membrane system with an estimated remaining useful life of 6 years. The building is served by redundant elevators, a backup generator and a high-efficiency chiller plant.

Observed Conditions

Elevators were last modernized 8 years ago and are operating without deficiency. Domestic water piping is copper and PVC with no evidence of widespread leakage. ADA observations include non-compliant slopes at two accessible routes and signage at parking; cost to cure is estimated at $475,000. Asphalt paving shows alligator cracking and should be sealcoated and restriped during the next 4 months.

Asphalt paving shows alligator cracking and should be sealcoated and restriped during the next 38 months. Domestic water piping is copper and PVC with no evidence of widespread leakage. Elevators were last modernized 10 years ago and are operating without deficiency. Windows and exterior doors are in fair condition; sealant replacement is recommended at selected locations.

Improvements Description

Floor plates are efficient and column-spacing supports open and private-office layouts. Common area interiors have been refreshed within the last 6 years and are in average to good condition. The roof is a 24-year membrane system with an estimated remaining useful life of 12 years. The structure is of wood-frame, masonry and steel-frame construction on a slab-on-grade foundation. The building is served by redundant elevators, a backup generator and a high-efficiency chiller plant.

Weighted average lease term remaining is 6 years and in-place rents average $30 per square foot, full service gross. Exterior finishes comprise brick veneer, fiber-cement siding and aluminum storefront glazing in good condition. The roof is a 42-year membrane system with an estimated remaining useful life of 7 years. Floor plates are efficient and column-spacing supports open and private-office layouts.

Deferred Maintenance

Elevators were last modernized 3 years ago and are operating without deficiency. The roofing system exhibits localized ponding and sealant deterioration; spot repairs are recommended within 12 months. Electrical service is adequate for current demand; select panels are nearing the end of their useful life. Domestic water piping is copper and PVC with no evidence of widespread leakage.

Asphalt paving shows alligator cracking and should be sealcoated and restriped during the next 14 months. Windows and exterior doors are in fair condition; sealant replacement is recommended at selected locations. Elevators were last modernized 5 years ago and are operating without deficiency. Domestic water piping is copper and PVC with no evidence of widespread leakage.

Construction Details

Life-safety systems include a fully sprinklered building, addressable fire alarm panel and emergency lighting. The roof is a 31-year membrane system with an estimated remaining useful life of 6 years. The structure is of wood-frame, masonry and steel-frame construction on a slab-on-grade foundation. Floor plates are efficient and column-spacing supports open and private-office layouts. The building features a renovated lobby, structured parking at a ratio of 26 per 1,000 square feet, and a tenant lounge with fitness center. Weighted average lease term remaining is 9 years and in-place rents average $30 per square foot, full service gross.

The structure is of wood-frame, masonry and steel-frame construction on a slab-on-grade foundation. Mechanical systems include rooftop package units and central plant equipment of varying age. Common area interiors have been refreshed within the last 8 years and are in average to good condition. The building is served by redundant elevators, a backup generator and a high-efficiency chiller plant. The roof is a 48-year membrane system with an estimated remaining useful life of 6 years. Zephyr Office Center was originally constructed in 1994 and consists of 188,992 SF in a building of 40 stories.

FICTITIOUS SAMPLE DOCUMENT — all names, figures and entities are invented for classroom training use only

Immediate Repairs and Replacement Reserve Schedule

System	Age (yrs)	EUL	RUL	Condition	Immediate	Reserve (10-yr)
Roof	18	22	4	Fair	$40,000	$262,000
Paving	14	14	0	Poor	$17,000	$120,000
HVAC	22	23	1	Fair	$31,000	$257,000
Plumbing	19	21	2	Good	$9,000	$146,000
Electrical	16	28	12	Fair	$8,000	$126,000
Elevators	5	26	21	Fair	$14,000	$123,000
Fire/Life Safety	10	13	3	Fair	$23,000	$28,000
Windows	4	29	25	Fair	$32,000	$211,000
Siding/Facade	6	20	14	Fair	$24,000	$219,000
Flooring	36	40	4	Fair	$9,000	$8,000
Appliances	6	28	22	Poor	$32,000	$107,000
Landscaping	3	11	8	Fair	$6,000	$21,000
Pool/Amenity	16	28	12	Fair	$11,000	$175,000
Signage	1	25	24	Fair	$7,000	$190,000
Fencing	18	32	14	Poor	$26,000	$120,000
Roof (2)	7	32	25	Good	$12,000	$242,000
Paving (2)	15	34	19	Good	$21,000	$130,000
HVAC (2)	2	11	9	Fair	$20,000	$19,000
Plumbing (2)	4	18	14	Poor	$31,000	$38,000
Electrical (2)	4	17	13	Fair	$30,000	$182,000
Elevators (2)	8	18	10	Fair	$39,000	$12,000
Fire/Life Safety (2)	6	11	5	Poor	$14,000	$60,000
Windows (2)	17	20	3	Fair	$13,000	$45,000
Siding/Facade (2)	27	28	1	Good	$14,000	$251,000
Flooring (2)	6	33	27	Poor	$31,000	$38,000
Appliances (2)	14	17	3	Good	$21,000	$18,000
Landscaping (2)	11	12	1	Good	$15,000	$41,000
Pool/Amenity (2)	4	17	13	Poor	$2,000	$134,000
Signage (2)	29	31	2	Good	$7,000	$56,000
Fencing (2)	8	20	12	Poor	$8,000	$62,000

Report generated 09/11/2021. Figures are unaudited and subject to change.

FICTITIOUS SAMPLE DOCUMENT — all names, figures and entities are invented for classroom training use only

Findings and Opinions of Cost

Item	Location	Observed Condition	Recommended Action	Priority	Est. Cost
Handrail	Bldg B	Loose	Secure	Immediate	$39,500
Roof membrane	Common	Ponding / seams	Re-seal and repair	Year 1	$79,000
HVAC unit	Site	Beyond useful life	Replace RTU	Immediate	$9,000
Sidewalk	Mechanical	Trip hazards	Grind / replace	Year 1	$63,500
Handrail	Common	Loose	Secure	Year 1	$53,500
Stair treads	Bldg A	Worn / loose	Replace treads	Immediate	$33,500
Roof membrane	Bldg A	Ponding / seams	Re-seal and repair	Year 1	$38,500
Water heater	Bldg B	Corrosion	Replace	Year 1	$52,500
Sprinkler heads	Mechanical	Painted heads	Replace	Reserve	$42,000
Dumpster enclosure	Mechanical	Damaged gate	Repair	Year 1	$8,500
Asphalt paving	Site	Alligator cracking	Mill and overlay	Year 2-5	$2,000
Water heater	Site	Corrosion	Replace	Reserve	$16,000
Water heater	Common	Corrosion	Replace	Year 2-5	$57,000
Stair treads	Bldg A	Worn / loose	Replace treads	Immediate	$9,500
Sprinkler heads	Bldg B	Painted heads	Replace	Year 1	$16,000
Window sealant	Bldg B	Failed	Re-caulk	Year 1	$50,500
Fire extinguishers	Site	Expired tags	Service	Reserve	$31,500
Window sealant	Common	Failed	Re-caulk	Year 2-5	$5,000
Window sealant	Bldg A	Failed	Re-caulk	Immediate	$86,500
Window sealant	Mechanical	Failed	Re-caulk	Immediate	$89,000
Dumpster enclosure	Roof	Damaged gate	Repair	Year 2-5	$90,000
Asphalt paving	Site	Alligator cracking	Mill and overlay	Year 1	$44,500
Asphalt paving	Mechanical	Alligator cracking	Mill and overlay	Year 2-5	$42,000
Roof membrane	Bldg B	Ponding / seams	Re-seal and repair	Year 1	$50,500
HVAC unit	Bldg B	Beyond useful life	Replace RTU	Immediate	$41,000
Fire extinguishers	Roof	Expired tags	Service	Immediate	$1,500
Fire extinguishers	Common	Expired tags	Service	Year 2-5	$39,500
Handrail	Site	Loose	Secure	Reserve	$82,000
Fire extinguishers	Common	Expired tags	Service	Year 1	$40,500
HVAC unit	Mechanical	Beyond useful life	Replace RTU	Reserve	$50,000
Handrail	Bldg B	Loose	Secure	Immediate	$4,000
Fire extinguishers	Bldg B	Expired tags	Service	Immediate	$56,000
Stair treads	Roof	Worn / loose	Replace treads	Year 2-5	$40,000
HVAC unit	Bldg A	Beyond useful life	Replace RTU	Year 1	$34,000
Stair treads	Bldg A	Worn / loose	Replace treads	Year 2-5	$59,500
Water heater	Site	Corrosion	Replace	Immediate	$37,500
Sidewalk	Bldg B	Trip hazards	Grind / replace	Year 2-5	$77,000
Fire extinguishers	Bldg B	Expired tags	Service	Year 2-5	$11,500
Water heater	Roof	Corrosion	Replace	Year 2-5	$1,000
Handrail	Common	Loose	Secure	Immediate	$44,500

Report generated 09/11/2021. Figures are unaudited and subject to change.

FICTITIOUS SAMPLE DOCUMENT — all names, figures and entities are invented for classroom training use only

Observed Conditions

Windows and exterior doors are in fair condition; sealant replacement is recommended at selected locations. Asphalt paving shows alligator cracking and should be sealcoated and restriped during the next 47 months. The roofing system exhibits localized ponding and sealant deterioration; spot repairs are recommended within 12 months. Elevators were last modernized 7 years ago and are operating without deficiency.

Asphalt paving shows alligator cracking and should be sealcoated and restriped during the next 35 months. Windows and exterior doors are in fair condition; sealant replacement is recommended at selected locations. Domestic water piping is copper and PVC with no evidence of widespread leakage. Elevators were last modernized 6 years ago and are operating without deficiency. The roofing system exhibits localized ponding and sealant deterioration; spot repairs are recommended within 12 months. Electrical service is adequate for current demand; select panels are nearing the end of their useful life.

Observed Conditions

Electrical service is adequate for current demand; select panels are nearing the end of their useful life. Elevators were last modernized 8 years ago and are operating without deficiency. Windows and exterior doors are in fair condition; sealant replacement is recommended at selected locations. Domestic water piping is copper and PVC with no evidence of widespread leakage.

Electrical service is adequate for current demand; select panels are nearing the end of their useful life. The roofing system exhibits localized ponding and sealant deterioration; spot repairs are recommended within 12 months. Elevators were last modernized 11 years ago and are operating without deficiency. ADA observations include non-compliant slopes at two accessible routes and signage at parking; cost to cure is estimated at $442,000. Asphalt paving shows alligator cracking and should be sealcoated and restriped during the next 44 months.

Deferred Maintenance

Elevators were last modernized 3 years ago and are operating without deficiency. ADA observations include non-compliant slopes at two accessible routes and signage at parking; cost to cure is estimated at $457,000. Electrical service is adequate for current demand; select panels are nearing the end of their useful life. The roofing system exhibits localized ponding and sealant deterioration; spot repairs are recommended within 12 months. Domestic water piping is copper and PVC with no evidence of widespread leakage.

The roofing system exhibits localized ponding and sealant deterioration; spot repairs are recommended within 12 months. Asphalt paving shows alligator cracking and should be sealcoated and restriped during the next 13 months. Electrical service is adequate for current demand; select panels are nearing the end of their useful life. Domestic water piping is copper and PVC with no evidence of widespread leakage. ADA observations include non-compliant slopes at two accessible routes and signage at parking; cost to cure is estimated at $233,000. Windows and exterior doors are in fair condition; sealant replacement is recommended at selected locations.

FICTITIOUS SAMPLE DOCUMENT — all names, figures and entities are invented for classroom training use only

Construction Details

Weighted average lease term remaining is 10 years and in-place rents average $30 per square foot, full service gross. The building features a renovated lobby, structured parking at a ratio of 16 per 1,000 square feet, and a tenant lounge with fitness center. The roof is a 22-year membrane system with an estimated remaining useful life of 11 years. Exterior finishes comprise brick veneer, fiber-cement siding and aluminum storefront glazing in good condition. Common area interiors have been refreshed within the last 7 years and are in average to good condition. Zephyr Office Center was originally constructed in 1994 and consists of 188,992 SF in a building of 9 stories.

Common area interiors have been refreshed within the last 8 years and are in average to good condition. The roof is a 32-year membrane system with an estimated remaining useful life of 10 years. The building is served by redundant elevators, a backup generator and a high-efficiency chiller plant. Mechanical systems include rooftop package units and central plant equipment of varying age.

Observed Conditions

The roofing system exhibits localized ponding and sealant deterioration; spot repairs are recommended within 12 months. Asphalt paving shows alligator cracking and should be sealcoated and restriped during the next 44 months. Windows and exterior doors are in fair condition; sealant replacement is recommended at selected locations. ADA observations include non-compliant slopes at two accessible routes and signage at parking; cost to cure is estimated at $430,000.

ADA observations include non-compliant slopes at two accessible routes and signage at parking; cost to cure is estimated at $391,000. Elevators were last modernized 3 years ago and are operating without deficiency. Windows and exterior doors are in fair condition; sealant replacement is recommended at selected locations. Electrical service is adequate for current demand; select panels are nearing the end of their useful life. The roofing system exhibits localized ponding and sealant deterioration; spot repairs are recommended within 12 months. Domestic water piping is copper and PVC with no evidence of widespread leakage.

Improvements Description

Life-safety systems include a fully sprinklered building, addressable fire alarm panel and emergency lighting. The structure is of wood-frame, masonry and steel-frame construction on a slab-on-grade foundation. Zephyr Office Center was originally constructed in 1994 and consists of 188,992 SF in a building of 13 stories. Common area interiors have been refreshed within the last 6 years and are in average to good condition. Floor plates are efficient and column-spacing supports open and private-office layouts.

Zephyr Office Center was originally constructed in 1994 and consists of 188,992 SF in a building of 36 stories. The roof is a 46-year membrane system with an estimated remaining useful life of 7 years. Mechanical systems include rooftop package units and central plant equipment of varying age. The building is served by redundant elevators, a backup generator and a high-efficiency chiller plant. The building features a renovated lobby, structured parking at a ratio of 11 per 1,000 square feet, and a tenant lounge with fitness center. Floor plates are efficient and column-spacing supports open and private-office layouts.

Observed Conditions

Elevators were last modernized 12 years ago and are operating without deficiency. The roofing system exhibits localized ponding and sealant deterioration; spot repairs are recommended within 12 months. Electrical service is adequate for current demand; select panels are nearing the end of their useful life. Domestic water piping is copper and PVC with no evidence of widespread leakage.

Electrical service is adequate for current demand; select panels are nearing the end of their useful life. Asphalt paving shows alligator cracking and should be sealcoated and restriped during the next 20 months. Domestic water piping is copper and PVC with no evidence of widespread leakage. Elevators were last modernized 11 years ago and are operating without deficiency. The roofing system exhibits localized ponding and sealant deterioration; spot repairs are recommended within 12 months. Windows and exterior doors are in fair condition; sealant replacement is recommended at selected locations.

Improvements Description

Life-safety systems include a fully sprinklered building, addressable fire alarm panel and emergency lighting. Exterior finishes comprise brick veneer, fiber-cement siding and aluminum storefront glazing in good condition. The roof is a 11-year membrane system with an estimated remaining useful life of 8 years. The structure is of wood-frame, masonry and steel-frame construction on a slab-on-grade foundation. Common area interiors have been refreshed within the last 8 years and are in average to good condition.

FICTITIOUS SAMPLE DOCUMENT — all names, figures and entities are invented for classroom training use only