Rush Crane S047	**RCS (Fassi F165AZ) Q-3**
	in. Wheelbase
, United States	**Quote 3,**
Phone: (210) 901-7204	**Phone:**
Fax:	**Fax:**
Email:	**Contact Email:**
	Prepared for: Default Contact

Vehicle Summary

Unit

Model:	Model 348
Type:	Full Truck
Description:	Pete 348 WB for Railroad Cont'r

Application

Intended Serv.:	Construction/Block
Commodity:	Construction Materials

Body

Type:	Winch or Crane
Length (ft):	24
Height (ft):	8.5
Max Laden Weight (lbs):	15000

Trailer

No. of Trailer Axles:	0
Type:	
Length (ft):	0
Height (ft):	0.0
Kingpin Inset (in):	0
Corner Radius (in):	0

Restrictions

Length (ft):	65
Width (in):	102
Height (ft):	13.5

Chassis

Fr Axle Load (lbs):	18740
Rr Axle Load (lbs)	40000
G.C.W. (lbs):	58500
Road Conditions:	
Class A (Highway)	96
Class B (Hwy/Mtn)	0
Class C (Off-Hwy)	4
Class D (Off-Road)	0
Maximum Grade:	6
Wheelbase (in):	265
Overhang (in):	125
Fr Axle to BOC (in):	69.8
Cab to Axle (in):	195.2
Cab to EOF (in):	320.2
Overall Comb. Length (in):	454

Special Req.

United States Registry

Approved by: _____ **Date:** _____

Note: All sales are F.O.B. designated plant of manufacture.

PACCAR FINANCIAL

Ask your dealer for a quote today, or visit our website @ www.paccarfinancial.com.

PACCAR Financial offers innovative finance, lease and insurance programs customized to meet your needs.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	1/6/2017 4:25:52 PM	***Complete***	Model Number:	Model 348
Effective Date:	Jan 1, 2017		Quote/DTPO/CO:	Q02204204
Prepared by:	Administrator		Version Number:	34.01

Rush Crane S047	**RCS (Fassi F165AZ) Q-3**
	in. Wheelbase
, United States	**Quote 3,**
Phone: (210) 901-7204	**Phone:**
Fax:	**Fax:**
Email:	**Contact Email:**
	Prepared for: Default Contact

	Description	Weight
Base Model		
	Model 348	10,610
	Construction Materials	0
	Construction/Block Truck or tractor used in the construction industry. Use typically involves operating on the job site, delivering construction materials, or to position equipment (crane) for its intended use at the construction site. Includes such activities as water tanker and delivery of precast concrete, bricks, blocks, and bag cement.	0
	Winch or Crane	0
	United States Registry	0
Configuration		
	Other	0
Frame & Equipment		
	10-3/4in Steel Rails 445-480in 10.75x3.5x.375 Dimension, 2,136,000 RBM; Yield Strength: 120,000 psi. Section Modulus: 17.8 cubic inches. Weight: 1.74 lbs/inch pair	914
	Full Steel Inner Liner	811
	Custom Wheelbase or Overhang Engineering approval may be required.	0
	Three-Piece Crossmembers	0
	27.8in Bumper Extension without Adapter Includes Stationary Grille. Requires FEPTO Bumper.	0
	EOF Square without Xmbr For use with body builder installed crossmember.	0
	Omit Rear Mudflaps and Hangers	0
Front Axle & Equipment		

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	1/6/2017 4:25:52 PM	***Complete***	Model Number:	Model 348
Effective Date:	Jan 1, 2017		Quote/DTPO/CO:	Q02204204
Prepared by:	Administrator		Version Number:	34.01

Description	Weight
Dana Spicer D2000F 20,000 lb, 3.5in Drop Factory front axle alignment to improve handling & reduce tire wear. Zerk fittings on tie rod ends, king pins, & draglink ball joints for ease of maintenance & help extend service life of components. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	143
Taper Leaf Springs, Shocks 20,000 lb Standard with Heavy Resistance Shocks.	0
Power Steering Sheppard HD94 Dual For use with 16,000 to 20,000 lb. axle ratings.	0
Power Steering Reservoir Frame Mounted w/Cooler	2
PHP10 Iron LMS Hubs 11-1/4" bolt circle. Includes a supplier extended coverage up to 3 years / 350,000 miles for bearings & seals.	78
Bendix Air Cam Front Drum Brakes 16.5x7 For use with 16,000 lbs to 22,000 lbs steer axles or front drive axles. Includes automatic slack adjusters & outboard mounted brake drums.	0
Long Stroke Brakes, Front Axle	0
Gusseted Cam Brackets, Steer Axle	0
Heavy Duty CAM Bushings, Steer Axle	0

Rear Axle & Equipment

Meritor MT40-14X 40,000 lb Interaxle diff lock air rocker occupies space of one gauge. Laser factory axle alignment to improve handling & reduce tire wear. Magnetic rear axle oil drain plug captures & holds any metal fragments in drive axle lube to extend service life. Parking brakes on all drive axles for optimal performance. Cognis EMGARD® FE 75W-90 synthetic axle lube provides over 1% fuel economy improvement. Reduces wear & extends maintenance intervals, resulting in increased uptime. Provides improved fluid flow to protect components in extreme cold conditions & withstand the stress from high temperatures, extending component life.	620
PHP10 Iron LMS Hubs 11-1/4" bolt circle. Includes a supplier extended coverage up to 3 years / 350,000 miles for bearings & seals.	0
Long Stroke Parking Brakes, Drive Axle(s)	20
Diff Lock Both Axles (Air Rocker Switch occupies the space of one gauge)	60
X30 Brake Drums IPO STD, Drive Axle(s)	-79
Rear Brake Camshaft Reinforcement	9
Heavy Wall, Drive Axle(s)	88
Lube Pump, Drive Axle(s)	36

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	1/6/2017 4:25:52 PM	***Complete***	Model Number:	Model 348
Effective Date:	Jan 1, 2017		Quote/DTPO/CO:	Q02204204
Prepared by:	Administrator		Version Number:	34.01

Description	Weight
Gusseted Cam Brackets, Drive Axle(s)	2
SBM Valve Full trucks require a spring brake modulation (SBM) system for emergency braking application. This system requires an SBM valve and a relay valve with spring brakes on the rear axles. The SBM valve allows the foot valve to operate the rear axle spring brakes if a failure exists in the rear air system.	0
Stability System Not Selected or Not Available	0
Anti-Lock Braking System (ABS) 6S6M ABS-6. Includes air braking system.	35
Synthetic Axle Lubricant All Axles Peterbilt heavy duty models include Fuel Efficient Cognis EMGARD FE75W-90 which provides customers performance advantages over current synthetic lubricants with reduced gear wear and extended maintenance intervals, resulting in increased uptime. In addition, the lubricant provides improved fluid flow to protect gears in extreme cold conditions and withstand the stress from high temperatures, extending component life.	0
Bendix Air Cam Rear Drum Brakes 16.5x7 Includes Automatic Slack Adjusters & Outboard Mounted Brake Drums.	0
Tandem Drive Axle (Model 348)	0
Ratio 5.29 Rear Axle	0
Hendrickson Haulmaax HMX400 40,000 lb, 54in Axle Spacing, 55K Creep Rating	582
Shock Absorbers For HMX Suspension	30

Engine & Equipment

PACCAR PX-9 350@2000 GOV@2200 1150@1400 Productivity (2017 Emissions) Includes alum flywheel housing, cruise control, and J1939 provisions (provides an interface point for the Electronic Service Analysis-ESA and other PACCAR approved diagnostic tools). Chevron Delo LE SAE 10W30 engine oil is specially formulated for new low emissions engines. Magnetic engine oil drain plug captures and holds any metal fragments in engine oil to extend service life. N21320 N205 120..Standard Maximum Speed Limit [LSL] N21330 N207 0....Expiration Distance N21340 P005 120..Hard Maximum Speed Limit N21350 P001 74...Maximum Accelerator Pedal Vehicle Speed N21360 P110 0....Accelerator Lower Droop N21370 P059 74...Maximum Cruise Speed N21380 P111 0....Cruise Control Lower Droop N21400 N203 252..Reserve Speed Function Reset Distance N21410 N202 0....Maximum Cycle Distance N21420 N206 10...Maximum Active Distance N21430 N201 0....Reserve Speed Limit Offset N21440 P015 NO...Engine Protection Shutdown N21450 P026 NO...Gear Down Protection N21460 P046 1400.Max PTO Speed	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	1/6/2017 4:25:52 PM	***Complete***	Model Number:	Model 348
Effective Date:	Jan 1, 2017		Quote/DTPO/CO:	Q02204204
Prepared by:	Administrator		Version Number:	34.01

Description	Weight
N21470 P062 NO...Cruise Control Auto Resume N21480 P068 NO...Auto Engine Brake in Cruise N21500 N209 0....Expiration Distance N21510 P520 YES..Enable Idle Shutdown Park Brake Set N21520 P030 5....Timer Setting N21530 P233 YES..Enable Impending Shutdown Warning N21540 P234 60...Timer For Impending Shutdown Warning N21550 P516 35...Engine Load Threshold N21570 P031 NO...Idle Shutdown Manual Overrule N21590 P230 YES..Enable Hot Ambient Automatic Overrule N21610 P172 40...Low Ambient Temperature Threshold N21620 P173 60...Intermediate Ambient Temperature Threshold N21630 P171 80...High Ambient Temperature Threshold	
Engine Idle Shutdown Timer Disabled	0
Enable EIST Ambient Temp Overrule	0
Eff EIST NA Expiration Miles	0
Effective VSL Setting NA	0
Belly Pan	35
Remote PTO And Throttle Provision	0
CARB Engine Idling Compliance PACCAR PX-7, PX-9 and MX, Cummins ISL, ISM and ISX diesel engines will include the required factory installed serialized sticker on the drivers door to identify them as meeting the NOx idling standard.	0
PACCAR 160 Amp Alternator, Brushed	0
Immersion Type Block Heater 110-120V Standard location is center left hand under cab and includes a weather-proof cover that protects the receptacle. This pre-heater keeps the coolant in the engine block from freezing when the engine is not running.	2
PACCAR 12V Starter	0
3 Optima DT31T Batteries 2700 CCA Threaded Stud type terminal. AGM (Absorbent Glass Material). Stranded copper battery cables are double aught (00) or larger to reduce resistance.	55
Battery Disconnect Switches (2) Mounted in Cab LH Side of Driver Seat	9
Battery Jumper Terminal Mounted Under Hood LH Frame Rail. Not available with PX-7 engines.	4
2-Speed Fan Clutch For Frequent Start/Stops	0
18.7 CFM Air Compressor N/A X15. Furnished on engine. Teflon lined stainless steel braided compressor discharge line.	0
VGT Exhaust Brake (Variable Geometry Turbo). Provides approximately 90-100 HP of retardation and is part of the turbocharger.	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	1/6/2017 4:25:52 PM	***Complete***	Model Number:	Model 348
Effective Date:	Jan 1, 2017		Quote/DTPO/CO:	Q02204204
Prepared by:	Administrator		Version Number:	34.01

Description	Weight
Spin-On Fuel Filter/Water Separator, 12V Heated Frame Mounted. In addition to the fuel filter supplied with the engine. Includes fuel water separator on Models 330, 337, and 348.	0
High Efficiency Cooling System Cooling module is a combination of steel and aluminum components, with aluminum connections to maximize performance and cooling capability. Silicone radiator & heater hoses enhance value, durability, & reliability. Constant tension band clamps reduce leaks. ClimaTech extended life coolant extends maintenance intervals which reduces maintenance costs. Anti-freeze effective to -30 degrees F helps protect the engine. Low coolant level sensor warns of low coolant condition to prevent engine damage. Radiator Size by Model: 587: 1330 sq in, 579/367 FEPTO 1325 sq in, 567/365/367: 1440 sq in, 384/386: 1301 sq in, 365 FEPTO: 1184 sq in, 389/367 HH: 1669 sq in, 348: 1000 sq in, 320: 1242 sq in.	0
Radial Seal, Dry Type Air Cleaner, Frontal Air Intake. Molded rubber air intake connections with lined stainless steel clamps seal to prevent contaminants in air intake.	0
Exhaust Single RH Side Of Cab DPF/SCR RH Under Cab (2017).	29
Curved Tip Standpipe(s)	0
24in Ht, 5in Dia Chrome, Clear Coat Standpipe(s)	0

Transmission & Equipment

Allison 3000 RDS-P Transmission, Gen 5 Rugged Duty Series. Includes Rear Transmission Support except on MX engines, TranSynd Automatic Transmission Fluid, and Water Oil Heat Exchange. Also includes features that monitor the transmission fluid, filter and clutch condition. Will display percent life remaining for the transmission fluid, filter and clutches on the shift selector. This information may be displayed using the Mode and Up and Down buttons. A wrench icon will also be included to indicate when the transmission fluid, filter or clutches need servicing. (Suited for vehicles operating on/off highway and/or requiring PTO operation) Forward Ratios: 1st-3.49, 2nd-1.86, 3rd-1.41, 4th-1.00, 5th-0.75, 6th-0.65 / Reverse Ratios: DR-(5.03)	110
1710 HD Driveline, 2 Midship Bearings	100
(2) Dash Mounted Single Acting Air PTO Controls Standard with PTO engaged indicator light on Class 8 units. (occupies the space of two gauges) Specing PTO switch does not ensure the PTO will fit.	2
Park Brake Interlock For use with transmission mounted PTO.	2
ALLISON 5TH GEN RDS, PKG 223	0
LH PTO Access Dipstick Tube Routing,Allison Trans	0
Allison FuelSense Not Desired	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	1/6/2017 4:25:52 PM	***Complete***	Model Number:	Model 348
Effective Date:	Jan 1, 2017		Quote/DTPO/CO:	Q02204204
Prepared by:	Administrator		Version Number:	34.01

Description	Weight
Allison 6-Speed Configuration, Close Ratio Gears 3000 Series Transmissions	0
Dash Mounted Push Button Shifter	0

Air & Trailer Equipment

Bendix AD-IS Air Dryer W/Heater And Coalescing Filter	0
Berg Pull Cord Drain Valve(s) - All Air Tanks	0
Nylon Chassis Hose	0
Steel Painted Air Tanks All air tanks are steel with painted finish except when Code 4543330 Polish Aluminum Air Tanks is also selected (then exposed air tanks outside the frame rails will be polished aluminum). Peterbilt will determine the optimal size and location of required air tanks. Narratives requesting a specific air tank size or location will not be accepted for factory installation. See ECAT to determine number or location of air tanks installed.	0

Tires & Wheels

FF: BR 18ply 385/65R22.5 M854 Diameter = 42.9 inches; SLR = 19.8 inches	110
RR: BR 16ply 11R22.5 M799 Diameter = 42.0 inches; SLR = 19.5 inches	72
Code-rear Tire Qty 08	0
FF: Alcoa 823627 LVL1 Plt 22.5X12.25 Alm Whl	-16
RR: Alcoa 883677 LvL1 22.5x8.25 Alm Whl	-200
Code-rear Rim Qty 08	0

Fuel Tanks

26in Aluminum 90 Gallon Fuel Tank LH U/C Includes steps for cab access. Paddle handle filler cap with threadless filler neck. Top draw fuel plumbing reduces chance of introducing air into the fuel system during low fuel level conditions due to the central placement of fuel pickup tube. Wire braid fuel lines increase durability & reduce potential for leaks.	14
Location LH U/C 90 Gallon	0
DEF Tank Mounted RH BOC You have selected a Diesel Exhaust Fluid (DEF) tank mounted on the right-hand (passenger) side of the vehicle. Note, some retail fuel distributors have chosen to standardize on DEF dispensing pumps oriented to the left-hand (driver) side of the vehicle. Please verify your selection for DEF tank mounting.	0
Standard DEF To Fuel Ratio 2:1 Or Greater	0
DEF Tank Small	0

Battery Box & Bumper

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	1/6/2017 4:25:52 PM	***Complete***	Model Number:	Model 348
Effective Date:	Jan 1, 2017		Quote/DTPO/CO:	Q02204204
Prepared by:	Administrator		Version Number:	34.01

	Description	Weight
	Omit Standard Battery Box (For use with passenger seat/in-cab battery box codes only)	-45
	Aftertreatment RH U/C Alum Non-Slip Cab Entry Step. DPF/SCR for diesel engines, catalyst for natural gas engines. On Models 579 specifying chassis fairings, the box will be aerodynamic.	0
	Steel Bumper Swept Back Painted Black, FEPTO only With two tow pin holes and step plates on top of bumper.	90
Cab & Equipment		
	Alum Cab 108in BBC Metton Hood w/Bright Crown Includes view window RH door and convex mirror over RH door.	0
	Severe Service Cab Package #1 Includes Aluminum side skins, aluminum rear skin, steel windshield mask, steel firewall, and steel front floor sheet on all cabs, and additional reinforcement structure on the back wall of the day cab.	39
	Thermal Insulation Package in Cab Includes thick, closed-cell foam in floor, special mylar-faced foam in walls and roof structure.	2
	Rubber Fender Lips 2 Inch Wide	8
	Peterbilt UltraRide Driver Seat	0
	Peterbilt UltraRide Passenger Seat	0
	Drivers Armrest - RH Only Required in Model 587 with Evolution LX seats. Optional with Evolution ST and Rolltek Seats.	2
	Passenger Armrest - LH only Required with Evolution LX seats, optional with Evolution ST Seats.	2
	Mounted On In-Cab Battery Box For use with non-air passenger seats only. Includes battery quick disconnect located under driver side door.	39
	Air Ride Driver	0
	High Back Driver	0
	Mordura Driver	0
	Low Back Passenger	0
	Vinyl Passenger	0
	Manifest Pouch on Rear Cab Wall	0
	Adjustable Steering Column - Tilt/Telescope	11
	Steering Wheel with Peterbilt Logo Steering Wheel with embossed Peterbilt logo over horn button.	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	1/6/2017 4:25:52 PM	***Complete***	Model Number:	Model 348
Effective Date:	Jan 1, 2017		Quote/DTPO/CO:	Q02204204
Prepared by:	Administrator		Version Number:	34.01

Description	Weight
Interior Grey/Black Includes rugged charcoal instrument panels, glare-resistant gray dash, black bezels on gauges, (2) power ports, monochromatic molded door pads with durable in-mold color, gray molded back wall, 18 inch 4-spoke soft-touch steering wheel, soft-touch steering column cover, power lift passenger window, extruded rubber floor covering, header-mounted dome light, foot well lighting, integrated "dead pedal", (4) inside entry grab handles, (2) inside sunvisors, (2) coat hooks, (2) cup holders and map bin in dash.	0
Dark Window Tint ipo STD Tint - Day Cab	0
Extended Rear Window ipo Std Window-Day Cab The extended rear window protrudes two inches more than the standard conventional rear cab window. Take this into consideration when determining your loadspace.	0
Day Cab Rear Window	0
One Piece Curved Windshield	0
Combo Fresh Air Heater/Air Conditioner With radiator mounted condenser, dedicated side window defrosters, Bi-Level Heater/Defroster Controls, 54,500 BTU/HR, and silicone heater hoses.	0
Cup Holder (Floor Mounted) Includes two standard-size drink holders and one extra-large jugholder, coin tray, and clipboard-size storage area.	4
Peterbilt Comfort Control - Cab	6
Outside Sunvisor - Stainless Steel Not available with 2.1M high roof sleeper.	4
Stainless Steel Mirrors 7x16 with Heat Element Right Click on Option to see Picture in Product Portfolio.	2
(2) Convex 8 Inch SS Mirror Center mounted under mirror bracket. If rear view mirrors are heated, the convex mirrors will be heated. Option includes dual door stops.	4
Power Package Includes power door locks and power windows.	0
Polished Lower Mirror Bracket Covers	0
(1) Air Horn 24.5in Chrome - Round w/Horn Shield	8
Mount Air Horn Logger Style - RH	2
Standard Speaker Package For Cab (2) Speakers	4
ConcertClass Without CD, Includes BT Phone and Audio, AM/FM, WB, USB and MP3.	10
Radio Antenna Mounted Logger Style Antenna Mounted LH on BOC In Place of Center Roof position on Conventional Models. Models 579 and 567 Antenna Mounted LH Roof In Place Of Center Roof position.	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	1/6/2017 4:25:52 PM	***Complete***	Model Number:	Model 348
Effective Date:	Jan 1, 2017		Quote/DTPO/CO:	Q02204204
Prepared by:	Administrator		Version Number:	34.01

	Description	Weight
	Plug-In Auto Reset Circuit Breaker in place of fuses in junction box.	0
	Peterbilt Electric Windshield Wipers With Intermittent Feature.	0
	CabMate Cab Air Suspension Mfg by Link. The class 8 conventionals (except Model 348) includes (2) airbags, (2) shock absorbers, (1) leveling valve, radius rod, and height limiter. The Models 330, 337, and 348 includes (1) airbag and (1) shock absorber.	15
	Triangle Reflector Kit Shipped Loose	13
	5 lb 3A:40BC Fire Extinguisher Cab Mounted	8
	Backup Alarm (107dB)	3
	Main Transmission Oil Temperature Gauge Located in Driver Information Display	0
	Air Restriction Indicator Mounted on air cleaner or intake piping.	0
	Bright Bezel Gauges	0
	(2) Additional Electric Switches Without Wiring	0
	Main Instrumentation Panel, Graphics Display Includes speedometer with tripodometer, tachometer with hourmeter and outside air temperature display, voltmeter, engine oil pressure, engine coolant temperature, fuel level, primary and secondary air pressure gauges. Includes standard warning light package: high water temperature, low oil pressure, and low air pressure warning lights w/audible alarms, high beam, turn signal, low fuel, parking brake, and ice warning indicators; seat belt reminder; rocker switches with long-life LED indicators; multi-function turn stalk with flash-to-pass feature (night mode flashes headlights and marker lights; day mode flashes headlights only), intermittent windshield wiper and headlamp beam control. Hydraulic braked trucks do not include air pressure gauges.	0
	Headlights Composite Fender Mounted Integral Park, Turn, and Side Marker	0
	(5) Marker Lights, Aero LED Light Emitting Diodes	0
	(2) Beacon Lights Rotating Amber One each side cab roof stainless steel bracket mounted.	4
	(2) Addl Dome/Reading Lights, Ceiling Mounted	0
	(2) Load Lights, Bracket Mounted Inboard Loc K DayCab	6
Paint		
	Standard Paint Color Selection	0
	(1) Color Axalta Two Stage - Cab/Hood Base Coat/Clear Coat N85020 A - L0006EY WHITE - Stand N85400 HOOD TOP L0006EY WHITE - Stand	0

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	1/6/2017 4:25:52 PM	***Complete***	Model Number:	Model 348
Effective Date:	Jan 1, 2017		Quote/DTPO/CO:	Q02204204
Prepared by:	Administrator		Version Number:	34.01

Description	Weight
N85500 CAB ROOF L0006EY WHITE - Stand	
N85200 FRAME N0001EA BLACK	
N85700 BUMPER N0001EA BLACK	
N85300 FENDER L0006EY WHITE - Stand	

Shipping Destination

Shipping Destination (Specify by narrative attached to option code). In Presentation Information screen add "See Instructions" for the Shipping Destination instead of	0

Options Not Subject To Discount

MEDIUM DUTY EMISSIONS SURCHARGE	0
PDI At Excellence Peterbilt Location	0
Vehicle Layout Option is not subject to discount. Fleets will be split prior to build so that the charge is applied to only one unit. Quotes will not reflect this.	0

Miscellaneous

2017 EPA Emissions Engine Warranty Only	0

Total Weight	14530

Prices and Specifications Subject to Change Without Notice.

Unpublished options may require review/approval.
Dimensional and performance data for unpublished options may vary from that displayed in PROSPECTOR.

Printed:	1/6/2017 4:25:52 PM	***Complete***	Model Number:	Model 348
Effective Date:	Jan 1, 2017		Quote/DTPO/CO:	Q02204204
Prepared by:	Administrator		Version Number:	34.01