Build-day checklist

Tick each box in the booklet chapter named in its heading. Tape readings in cm, caliper and drill sizes in mm. Datum: top A's back-left corner (0, 0).

Chapter B · Measure before anything is cut, printed or drilled

- [ ] Both EKBACKEN tops 28 mm thick (calipers). At 27 mm nothing changes; under 27 mm, stop and ask. Never deeper than 21 mm into a top. **MEASURE ON HARDWARE**
- [ ] Feet pad diameter 50 mm (calipers) before printing the 52 mm bore rings. **MEASURE ON HARDWARE**
- [ ] ALEX height 70.0 cm (with and without its stock feet). ALEX bottom panel thickness, only if you fit the optional ALEX feet. **MEASURE ON HARDWARE**
- [ ] Delivered rail lengths (bought as 84 in, 213.4 cm; layout 213 cm) and angle thickness 4.8 mm. **MEASURE ON HARDWARE**
- [ ] VIVO lower clamp: maximum opening 31 mm or more (28 mm top + 3 mm plate); top arm reach (about 89 mm). **MEASURE ON HARDWARE**
- [ ] Room: 252 × 317 cm of floor cleared, including the 3 cm wall gaps; wall to wall 252.0 cm and 317.0 cm; baseboard thickness. **MEASURE ON HARDWARE**
- [ ] Feet load rating (design wants 50 kg or more each). **ASSUMPTION / FIELD CHECK**

Chapters B and C · Parts and tools on hand

- [ ] Six OLOV legs, 105 mm plate with five 5.5 mm holes on an 85 mm circle; 30 × M4 × 16 mm screws (H01), five per leg.
- [ ] Eight of the twelve 4 in feet: 59.5 mm plate with four 5.2 mm holes 46.8 mm apart; 32 × #8 × 5/8 in pan head (H02).
- [ ] Eight printed rings (52 mm bore, 3 mm wall, 10 mm ring on a 75 × 2.5 mm flange), PETG or ABS, flange-down; 24 × #6 × 5/8 in flat head (H06).
- [ ] Two rails, 2 × 2 × 3/16 in angle, ends deburred; 19 × #10 × 1 in pan head Robertson (H03).
- [ ] Four 10 × 3 in mending plates (two joining, two clamp pads); 8 × #10 × 5/8 in (H04) with #10 washers (H05).
- [ ] Two gusseted 90° strut fittings; 6 × 3/8-16 × 1-1/2 in grade 5 bolts (H08), 12 × 3/8 washers (H09), 6 nylon-insert nuts (H10).
- [ ] Printed tools: edge T-square, leg jig, feet corner jig, ALEX corner template, rail marking gauge, rail drill jig, two fitting plugs, drill guide (tower + 5 pucks), foot height gauge (102 mm), wall gauge (6.5 cm and 3 cm legs).
- [ ] Automatic centre punch, cutting oil; 5/64, 1/8, 7/32 and 7/16 in bits (7/16 cobalt); Robertson #2 bit on a 3 in extension.

Verify before: chapter by chapter

Chapter D · Marking both tops, face down

- [ ] Unfinished edge to the wall (y = 0 on top A, x = 0 on top B); top A's side-wall end taped and measured from.
- [ ] A mark off by more than 2 mm: redraw it.

Chapter E · Steel on the bench

- [ ] Rail A stations 3.5, 28.0, 54.0, 80.0, 106.0, 132.0, 158.0, 184.0, 210.5 cm from the wall end (the first at 3.5 cm, not 2.5 cm); rail B 2.5, 7.5, 28.0, 54.0, 80.0, 106.0, 132.0, 158.0, 184.0, 210.5 cm from the corner end; all on the 19 mm line.
- [ ] Fitting as template: rail A heel on the 52.0 cm mark legs toward the far end, and on the 51.5 cm mark legs toward the wall end; rail B heel on the corner end. Bolt holes on the 29 mm line, 7/16 in.

Chapter F · Legs, feet, rails, cabinets

- [ ] Every OLOV pre-set to 80.2 cm, or the ALEX-feet table's number (decided before this chapter).
- [ ] Every foot set with the 102 mm gauge: slides over from the side with no rock.
- [ ] Rail A 12 cm from the front edge to the vertical leg's outer face at both ends and in the middle before drilling; end screws first, re-check, then the rest. Rail pilots 25 mm from the flat leg's top face.
- [ ] Rails screwed to the tops before the tops stand: nine screws in rail A, eight in rail B (holes 3 to 10; holes 1 and 2 wait for chapter H).
- [ ] ALEX units placed by the walls: ALEX 1 back 6.5 cm off the back wall, near side 212.5 cm from the side wall; ALEX 2 side 6.5 cm off the side wall, near end staged at 292.5 cm from the back wall (pushed home to 277.5 cm in chapter G).
- [ ] No rings yet: the rings go on in chapter G.

Chapter G · Standing the tops, rings by tracing

- [ ] Each top stood on its bare ALEX, 3.5 cm of top showing all round (the wall gauge's 6.5 cm leg at the wall); pencil traced round each pad; top lifted off.
- [ ] Each ring set on its circle, pencil line visible all round through the open bottom; pilots 3–4 mm through the ring's own holes, finished with the 12 ALEX puck; three #6 × 5/8 in screws.
- [ ] Top stood back up: all four pads drop into their rings. Top A 3 cm off both walls, level along x and y.
- [ ] Top B's OLOV legs wound to 79.9–80.0 cm before rail B slides under top A, then up to 80.2 cm once home. ALEX 2 pushed home with top B on it: push the ALEX, never the top alone.

Chapter H · The joint

- [ ] Before the plates: rail B's end touches rail A's vertical leg with no gap, and its outer face lines up with the 52.0 cm mark.
- [ ] Surfaces flush by the feet, never by packing under the joining plates.
- [ ] Rail B's screws 1 and 2 driven before the fittings go on.
- [ ] Before the bolts: surfaces flush and rail B touching rail A; inside fitting gusset-down. Six bolts 25 N·m.

Chapter I · Monitor mount

- [ ] Pad plates on their outlines (x 20.0–45.4 cm, y 0.5–8.1 cm; y 20.0–45.4 cm, x 0.5–8.1 cm); clamps finger-tight at x = 40.0 cm and y = 40.0 cm on the Option 1 holes until the crossbar is on.
- [ ] G5 top edge 66.9 cm above the top, under the 67.3 cm limit; if the mount will not reach, lower the G5 (a bottom edge down to 12 cm above the top still clears the ELLOVEN).

Chapter J · Wall-gap trim

- [ ] Screens, PC and everything loose taken off the desk first.
- [ ] Gap measured at five or six points along each wall. Find the smallest reading in the table and print with the gap value beside it; under 27 mm or over 33 mm, measure again and ask.

Smallest reading (mm)	27	28	29	30	31	32	33
Gap value to print	26	27	28	29	30	31	32

- [ ] Desk slid back until the wall gauge's 6.5 cm leg just fits at each ALEX.

Chapter K · Final checks

- [ ] 1 · Surface 83.0 cm ± 0.3 cm at corners 1–6 (85.0 / 87.0 / 89.0 cm with 2 / 4 / 6 cm ALEX feet), then the inside corner (65, 65) last.
- [ ] 2 · Level across the joint reads flat both ways; a fingertip finds no step.
- [ ] 3 · 20 kg (case of water + books) on top B's inside corner, 10 cm in from both edges: drop ≤ 2 mm on a straightedge from L1's line; returns, no creak, nothing moved. Never stand or sit on the desk.
- [ ] 4 · All eight pads bear: rocked sideways by hand (never turned), none rocks or lifts.
- [ ] 5 · Straightedge across the joint at the inside corner: step written down: _____ mm.
- [ ] 6 · Sideways push along each wall: no sway beyond a few mm, no top moving on its ALEX.
- [ ] 7 · No screw tip visible or felt on either laminate face.
- [ ] 8 · Knees clear; rail lower edge 75.1 cm from the floor, 12 cm back from the edge.
- [ ] 9 · Both ALEX fronts open fully without touching a foot or a leg.

Two weeks · date _____ (chapter L)

- [ ] Retighten every screw.
- [ ] Straightedge at the joint: _____ mm. Settled? Retighten the six fitting bolts to 25 N·m (18 ft·lb).
- [ ] Each printed ring and its three screws: no crack (reprint in PETG or ABS if cracked), screws tight.

One month · date _____

- [ ] Straightedge at the joint: _____ mm. Settled? Retighten the six fitting bolts.