

# Effect typing

Sam Lindley

The University of Edinburgh

SPLV 2024

## Effect polymorphism

To support flexible composition of effectful programs we need\* **effect polymorphism**.

## Effect polymorphism

To support flexible composition of effectful programs we need\* **effect polymorphism**.

Example: choice and failure

$$\text{maybeFail} : \forall e. A!(e \uplus \{\text{fail} : a.1 \twoheadrightarrow a\}) \Rightarrow \text{Maybe } A!e$$
$$\text{allChoices} : \forall e. A!(e \uplus \{\text{choose} : 1 \twoheadrightarrow \text{Bool}\}) \Rightarrow \text{List } A!e$$

## Effect polymorphism

To support flexible composition of effectful programs we need\* **effect polymorphism**.

Example: choice and failure

$$\begin{aligned}\text{maybeFail} &: \forall e. A!(e \uplus \{\text{fail} : a.1 \rightarrow a\}) \Rightarrow \text{Maybe } A!e \\ \text{allChoices} &: \forall e. A!(e \uplus \{\text{choose} : 1 \rightarrow \text{Bool}\}) \Rightarrow \text{List } A!e\end{aligned}$$

With explicit type applications we may write:

**handle** (**handle** drunkTosses 2 **with** maybeFail {choose : 1 → Bool}) **with** allChoices ∅

or

**handle** (**handle** drunkTosses 2 **with** allChoices {fail : a.1 → a}) **with** maybeFail ∅

## Effect polymorphism via row polymorphism

Intuitively, a row type is a type-level map from labels to value types  $\ell_1 : A_1, \dots, \ell : A_n$

## Effect polymorphism via row polymorphism

Intuitively, a row type is a type-level map from labels to value types  $\ell_1 : A_1, \dots, \ell : A_n$

Row polymorphism supports abstracting over *the rest* of a row type:  $\ell : A_1, \dots, \ell : A_n; \rho$

There can be at most one row variable in a row type

## Effect polymorphism via row polymorphism

Intuitively, a row type is a type-level map from labels to value types  $\ell_1 : A_1, \dots, \ell : A_n$

Row polymorphism supports abstracting over *the rest* of a row type:  $\ell : A_1, \dots, \ell : A_n; \rho$

There can be at most one row variable in a row type

Originally row polymorphism was designed for polymorphic record typing

[\[Wand, LICS 1989\]](#)

Row polymorphism also works nicely for polymorphic variants and **effect polymorphism**

## Effect polymorphism via row polymorphism

Intuitively, a row type is a type-level map from labels to value types  $\ell_1 : A_1, \dots, \ell : A_n$

Row polymorphism supports abstracting over *the rest* of a row type:  $\ell : A_1, \dots, \ell : A_n; \rho$

There can be at most one row variable in a row type

Originally row polymorphism was designed for polymorphic record typing

[\[Wand, LICS 1989\]](#)

Row polymorphism also works nicely for polymorphic variants and **effect polymorphism**

For effect handlers labels are either operation names or effect names



## Rémy-style row polymorphism

Rows as maps from labels to type-level maybes — each label is either present with type  $A$  ( $\text{Pre}(A)$ ) or absent ( $\text{Abs}$ )

Duplicate labels disallowed

## Rémy-style row polymorphism

Rows as maps from labels to type-level maybes — each label is either present with type  $A$  ( $\text{Pre}(A)$ ) or absent ( $\text{Abs}$ )

Duplicate labels disallowed

Example:

$\text{maybeFail} : \forall (e : \text{Row}_{\{\text{fail}\}}).$

$A!(\{\text{fail} : (a : \text{Type}).1 \rightarrow a; e\}) \Rightarrow \forall (p : \text{Presence}). \text{Maybe } A!\{\text{fail} : p; e\}$

$\text{allChoices} : \forall (e : \text{Row}_{\{\text{choose}\}}).$

$A!(e \uplus \{\text{choose} : 1 \rightarrow \text{Bool}; e\}) \Rightarrow \forall (p : \text{Presence}). \text{List } A!\{\text{choose} : p; e\}$

## Leijen-style row polymorphism

Rows as maps from labels to type-level lists — each label may be present multiple times at different types

Duplicate labels allowed; order of duplicates matters

## Leijen-style row polymorphism

Rows as maps from labels to type-level lists — each label may be present multiple times at different types

Duplicate labels allowed; order of duplicates matters

Example:

$$\begin{aligned} \text{maybeFail} &: \forall (e : \text{Row}). \\ &\quad A!({\color{blue}\text{fail}} : (a : \text{Type}). 1 \twoheadrightarrow a; e) \Rightarrow \text{Maybe } A!{\{; e\}} \\ \text{allChoices} &: \forall (e : \text{Row}). \\ &\quad A!(e \uplus {\color{blue}\text{choose}} : 1 \twoheadrightarrow \text{Bool}; e) \Rightarrow \text{List } A!{\{; e\}} \end{aligned}$$

## Handler composition with row polymorphism

Instantiating an effect variable supports handler composition

## Handler composition with row polymorphism

Instantiating an effect variable supports handler composition

Rémy style (explicit instantiation):

```
handle (handle drunkTosses 2 with maybeFail {choose : 1  $\rightarrow$  Bool} Abs)  
with allChoices  $\emptyset$  Abs
```

## Handler composition with row polymorphism

Instantiating an effect variable supports handler composition

Rémy style (explicit instantiation):

```
handle (handle drunkTosses 2 with maybeFail {choose : 1  $\rightarrow$  Bool} Abs)  
with allChoices  $\emptyset$  Abs
```

Leijen style (explicit instantiation):

```
handle (handle drunkTosses 2 with maybeFail {choose : 1  $\rightarrow$  Bool})  
with allChoices  $\emptyset$ 
```

## Example: abstracting over an exception handler

Rémy style:

$$\text{catch} : (1 \rightarrow b!\{\text{fail} : a.1 \twoheadrightarrow a; e\}) \rightarrow (1 \rightarrow b!\{\text{fail} : p; e\}) \rightarrow b!\{\text{fail} : p; e\}$$

$\text{catch } m \ h = \mathbf{handle} \ m() \ \mathbf{with}$

$$\begin{array}{l} \mathbf{return} \ x \mapsto x \\ \langle \text{fail } () \rangle \mapsto h () \end{array}$$



## Example: abstracting over an exception handler

Rémy style:

$$\text{catch} : (1 \rightarrow b!\{\text{fail} : a.1 \twoheadrightarrow a; e\}) \rightarrow (1 \rightarrow b!\{\text{fail} : p; e\}) \rightarrow b!\{\text{fail} : p; e\}$$
$$\text{catch } m \ h = \mathbf{handle} \ m() \ \mathbf{with}$$
$$\quad \mathbf{return} \ x \mapsto x$$
$$\quad \langle \text{fail } () \rangle \mapsto h \ ()$$

If  $h$  can itself fail then  $p$  is instantiated to  $\text{Pre}(a.1 \twoheadrightarrow a)$

## Example: abstracting over an exception handler

Rémy style:

$$\begin{aligned} \text{catch} &: (1 \rightarrow b!\{\text{fail} : a.1 \twoheadrightarrow a; e\}) \rightarrow (1 \rightarrow b!\{\text{fail} : p; e\}) \rightarrow b!\{\text{fail} : p; e\} \\ \text{catch } m \ h &= \mathbf{handle} \ m() \ \mathbf{with} \\ &\quad \mathbf{return} \ x \mapsto x \\ &\quad \langle \text{fail } () \rangle \mapsto h \end{aligned}$$

If  $h$  can itself fail then  $p$  is instantiated to  $\text{Pre}(a.1 \twoheadrightarrow a)$

Leijen style:

$$\begin{aligned} \text{catch} &: (1 \rightarrow b!\{\text{fail} : a.1 \twoheadrightarrow a; e\}) \rightarrow (1 \rightarrow b!\{; e\}) \rightarrow b!\{; e\} \\ \text{catch } m \ h &= \mathbf{handle} \ m() \ \mathbf{with} \\ &\quad \mathbf{return} \ x \mapsto x \\ &\quad \langle \text{fail } () \rangle \mapsto h \end{aligned}$$

## Example: abstracting over an exception handler

Rémy style:

$$\begin{aligned} \text{catch} &: (1 \rightarrow b!\{\text{fail} : a.1 \twoheadrightarrow a; e\}) \rightarrow (1 \rightarrow b!\{\text{fail} : p; e\}) \rightarrow b!\{\text{fail} : p; e\} \\ \text{catch } m \ h &= \mathbf{handle} \ m() \ \mathbf{with} \\ &\quad \mathbf{return} \ x \mapsto x \\ &\quad \langle \text{fail } () \rangle \mapsto h \end{aligned}$$

If  $h$  can itself fail then  $p$  is instantiated to  $\text{Pre}(a.1 \twoheadrightarrow a)$

Leijen style:

$$\begin{aligned} \text{catch} &: (1 \rightarrow b!\{\text{fail} : a.1 \twoheadrightarrow a; e\}) \rightarrow (1 \rightarrow b!\{; e\}) \rightarrow b!\{; e\} \\ \text{catch } m \ h &= \mathbf{handle} \ m() \ \mathbf{with} \\ &\quad \mathbf{return} \ x \mapsto x \\ &\quad \langle \text{fail } () \rangle \mapsto h \end{aligned}$$

If  $h$  can itself fail then  $e$  is instantiated to  $(\text{fail} : a.1 \twoheadrightarrow a; e')$  for some  $e'$ , which means the type of  $m$  is  $(1 \rightarrow b!\{\text{fail} : a.1 \twoheadrightarrow a, \text{fail} : a.1 \twoheadrightarrow a; e'\})$

## Invisible effect polymorphism

Key observation: for higher-order functions the effect variables almost always match up because we typically *use* the function arguments

## Invisible effect polymorphism

Key observation: for higher-order functions the effect variables almost always match up because we typically *use* the function arguments

Example (Leijen style):

$$\text{catch} : (1 \rightarrow b!\{\text{fail} : a.1 \twoheadrightarrow a; e\}) \rightarrow (1 \rightarrow b!\{; e\}) \rightarrow b!\{; e\}$$
$$\text{map} : (a \rightarrow b!\{; e\}) \rightarrow \text{List } a \rightarrow \text{List } b!\{; e\}$$

## Invisible effect polymorphism

Key observation: for higher-order functions the effect variables almost always match up because we typically *use* the function arguments

Example (Leijen style):

$$\text{catch} : (1 \rightarrow b!\{\text{fail} : a.1 \twoheadrightarrow a; e\}) \rightarrow (1 \rightarrow b!\{; e\}) \rightarrow b!\{; e\}$$
$$\text{map} : (a \rightarrow b!\{; e\}) \rightarrow \text{List } a \rightarrow \text{List } b!\{; e\}$$

We adopt a convention that omitted effect variables are all the same

$$\text{catch} : (1 \rightarrow b!\{\text{fail} : a.1 \twoheadrightarrow a\}) \rightarrow (1 \rightarrow b!\{\}) \rightarrow b!\{\}$$
$$\text{map} : (a \rightarrow b!\{\}) \rightarrow \text{List } a \rightarrow \text{List } b!\{\}$$

## Invisible effect polymorphism

Key observation: for higher-order functions the effect variables almost always match up because we typically *use* the function arguments

Example (Leijen style):

$$\begin{aligned}\text{catch} &: (1 \rightarrow b!\{\text{fail} : a.1 \twoheadrightarrow a; e\}) \rightarrow (1 \rightarrow b!\{; e\}) \rightarrow b!\{; e\} \\ \text{map} &: (a \rightarrow b!\{; e\}) \rightarrow \text{List } a \rightarrow \text{List } b!\{; e\}\end{aligned}$$

We adopt a convention that omitted effect variables are all the same

$$\begin{aligned}\text{catch} &: (1 \rightarrow b!\{\text{fail} : a.1 \twoheadrightarrow a\}) \rightarrow (1 \rightarrow b!\{\}) \rightarrow b!\{\} \\ \text{map} &: (a \rightarrow b!\{\}) \rightarrow \text{List } a \rightarrow \text{List } b!\{\}\end{aligned}$$

And further that empty polymorphic effects need not be written at all:

$$\begin{aligned}\text{catch} &: (1 \rightarrow b!\{\text{fail} : a.1 \twoheadrightarrow a\}) \rightarrow (1 \rightarrow b) \rightarrow b \\ \text{map} &: (a \rightarrow b) \rightarrow \text{List } a \rightarrow \text{List } b\end{aligned}$$

## Invisible effect polymorphism

Key observation: for higher-order functions the effect variables almost always match up because we typically *use* the function arguments

Example (Leijen style):

$$\begin{aligned}\text{catch} &: (1 \rightarrow b!\{\text{fail} : a.1 \twoheadrightarrow a; e\}) \rightarrow (1 \rightarrow b!\{; e\}) \rightarrow b!\{; e\} \\ \text{map} &: (a \rightarrow b!\{; e\}) \rightarrow \text{List } a \rightarrow \text{List } b!\{; e\}\end{aligned}$$

We adopt a convention that omitted effect variables are all the same

$$\begin{aligned}\text{catch} &: (1 \rightarrow b!\{\text{fail} : a.1 \twoheadrightarrow a\}) \rightarrow (1 \rightarrow b!\{\}) \rightarrow b!\{\} \\ \text{map} &: (a \rightarrow b!\{\}) \rightarrow \text{List } a \rightarrow \text{List } b!\{\}\end{aligned}$$

And further that empty polymorphic effects need not be written at all:

$$\begin{aligned}\text{catch} &: (1 \rightarrow b!\{\text{fail} : a.1 \twoheadrightarrow a\}) \rightarrow (1 \rightarrow b) \rightarrow b \\ \text{map} &: (a \rightarrow b) \rightarrow \text{List } a \rightarrow \text{List } b\end{aligned}$$

We do now need to use explicit syntax to denote a closed row ( $\emptyset$ ), but with row-based effect typing closed rows are uncommon



# Effect pollution example

## Handlers

$\text{reads} : \text{List Nat} \rightarrow a! \{ \text{get} : 1 \twoheadrightarrow \text{Nat} \} \Rightarrow a! \{ \text{fail} : a.1 \twoheadrightarrow a \}$

$\text{reads} ([]) = \text{return } x \quad \mapsto x$   
 $\quad \langle \text{get} () \rightarrow r \rangle \mapsto \text{fail} ()$

$\text{reads} (n :: ns) = \text{return } x \quad \mapsto x$   
 $\quad \langle \text{get} () \rightarrow r \rangle \mapsto r \text{ ns } n$

$\text{maybeFail} : b! \{ \text{fail} : a.1 \twoheadrightarrow a \} \Rightarrow \text{Maybe } b$

$\text{maybeFail} = \text{return } x \quad \mapsto \text{Just } x$   
 $\quad \langle \text{fail} () \rightarrow r \rangle \mapsto \text{Nothing}$

## Effect pollution example

$\text{bad} : \text{List } b \rightarrow (1 \rightarrow b! \{ \text{get} : 1 \twoheadrightarrow \text{Nat}, \text{fail} : a.1 \twoheadrightarrow a \}) \rightarrow \text{Maybe } b$   
 $\text{bad } ns \ t = \mathbf{handle} \ (\mathbf{handle} \ t \ ()) \ \mathbf{with} \ \text{reads } ns) \ \mathbf{with} \ \text{maybeFail}$

## Effect pollution example

$\text{bad} : \text{List } b \rightarrow (1 \rightarrow b! \{ \text{get} : 1 \twoheadrightarrow \text{Nat}, \text{fail} : a.1 \twoheadrightarrow a \}) \rightarrow \text{Maybe } b$   
 $\text{bad } ns \ t = \mathbf{handle} \ (\mathbf{handle} \ t \ () \ \mathbf{with} \ \text{reads } ns) \ \mathbf{with} \ \text{maybeFail}$

$\text{bad } [1, 2] \ (\lambda(). \text{get} \ () + \text{fail} \ ()) : \text{Maybe Nat} \Longrightarrow \text{Nothing}$

## Effect pollution example

$\text{bad} : \text{List } b \rightarrow (1 \rightarrow b! \{ \text{get} : 1 \twoheadrightarrow \text{Nat}, \text{fail} : a.1 \twoheadrightarrow a \}) \rightarrow \text{Maybe } b$   
 $\text{bad } ns \ t = \mathbf{handle} \ (\mathbf{handle} \ t \ () \ \mathbf{with} \ \text{reads } ns) \ \mathbf{with} \ \text{maybeFail}$

$\text{bad } [1, 2] \ (\lambda(). \text{get} () + \text{fail} ()) : \text{Maybe Nat} \Longrightarrow \text{Nothing}$

How can we encapsulate the use of `fail` as an intermediate effect?

## Effect pollution example

$\text{bad} : \text{List } b \rightarrow (1 \rightarrow b! \{ \text{get} : 1 \twoheadrightarrow \text{Nat}, \text{fail} : a.1 \twoheadrightarrow a \}) \rightarrow \text{Maybe } b$   
 $\text{bad } ns \ t = \mathbf{handle} \ (\mathbf{handle} \ t \ () \ \mathbf{with} \ \text{reads } ns) \ \mathbf{with} \ \text{maybeFail}$

$\text{bad } [1, 2] \ (\lambda().\text{get} \ () + \text{fail} \ ()) : \text{Maybe Nat} \Longrightarrow \text{Nothing}$

How can we encapsulate the use of `fail` as an intermediate effect?

The aim is to define

$\text{good} : \text{List } b \rightarrow (1 \rightarrow b! \{ \text{get} : 1 \twoheadrightarrow \text{Nat} \}) \rightarrow \text{Maybe } b$

by composing `reads` and `maybeFail` such that

$\text{good } [1, 2] \ (\lambda().\text{get} \ () + \text{fail} \ ()) : \text{Maybe Nat!} \{ \text{fail} : a.1 \twoheadrightarrow a \}$

performs the `fail` operation.

# Effect encapsulation

Two solutions to the effect pollution problem:

- Mask the intermediate effect (only works for Leijen-style row-typing)

$$\text{good} : \text{List } b \rightarrow (1 \rightarrow b!\{\text{get} : 1 \twoheadrightarrow \text{Nat}\}) \rightarrow \text{Maybe } b$$
$$\text{good } ns \ t = \mathbf{handle} (\mathbf{handle} (\langle \text{fail} \rangle (t ())) \mathbf{with} \text{ reads } ns) \mathbf{with} \text{ maybeFail}$$

Frank, Koka, and Helium support this approach.

[Biernacki, Piróg, Polesiuk, Sieczkowski, POPL 2018, “Handle with care”]

[Convent, Lindley, McBride, McLaughlin, JFP 2019, “Doo bee doo bee doo”]

- Add support for fresh effects

Helium and Links support this approach.

[Biernacki, Piróg, Polesiuk, Sieczkowski, POPL 2019, “Abstracting algebraic effects”]

## Effect masking

$$\frac{\Delta; \Gamma \vdash M : A! \{R\}}{\Delta; \Gamma \vdash \langle \text{op} \rangle M : A! \{\text{op} : B \twoheadrightarrow C; R\}}$$

Akin to weakening for effects

Doo bee doo bee doo

*Shall I be pure or impure?*

—Philip Wadler



*A value is. A computation does.*

—Paul Blain Levy



*'To be is to do'—Socrates.*

*'To do is to be'—Sartre.*

*'Do be do be do'—Sinatra.*

—anonymous graffiti, via Kurt Vonnegut





# Frank

[Lindley, McBride, McLaughlin, POPL 2017, “Do be do be do”]

[Convent, Lindley, McBride, McLaughlin, JFP 2019, “Doo bee doo bee doo”]

Frank is an unequivocally effect handler oriented research programming language

Key features include:

- ▶ invisible effect polymorphism
- ▶ call-by-handling
- ▶ multihandlers
- ▶ adjustments
- ▶ adaptors (a generalisation of mask)

Probably a misfeature: unusual syntax

# Links

<http://www.links-lang.org>

Linking theory to practice  
for the web



## DATABASE INTEGRATION



Query  
Shredding

Relational  
Lenses

Language-  
Integrated  
Query

Provenance

Typed  
HTML +  
antiquotes

Formlets

Model-  
View-  
Update

## WEB DEVELOPMENT



## CONCURRENCY & DISTRIBUTION



RPC  
Calculus

Distributed  
Session  
Types

Session  
Exceptions

## INTERACTIVE PROGRAMMING



TryLinks

Notebook  
Programming

## EFFECT HANDLERS




CEK  
Machine  
(Server)

CPS  
Translation  
(Client)

Row-based  
Effects

With thanks to Simon Fowler



# Handlers in Links and Frank (demo)

Demos

# Effect typing scalability challenges

Effect encapsulation

Linearity

Generativity

Indexed effects

Equations