

Inverse Adding-Doubling

(Version 3-14-5)

	Section	Page
iad program	1	1
Simple command-line shell program	32	27
IAD Types	37	29
IAD Public	44	33
Inverse RT	47	34
Validation	51	36
Searching Method	59	39
EZ Inverse RT	69	44
IAD Input Output	94	53
Reading the file header	96	54
Reading just one line of a data file	101	56
Formatting the header information	109	58
IAD Calculation	117	62
Initialization	119	65
Gain	120	66
Grid Routines	131	70
Calculating R and T	171	84
IAD Find	210	95
Fixed Anisotropy	212	96
Fixed Absorption and Anisotropy	221	100
Fixed Absorption and Scattering	223	101
Fixed Optical Depth and Anisotropy	225	102
Fixed Optical Depth and Albedo	227	103
Fixed Anisotropy and Albedo	229	104
Fixed Optical Depth	232	105
Fixed Albedo	237	108
Fixed Scattering	243	111
Fixed Absorption	248	113
IAD Utilities	253	115
Finding optical thickness	255	116
Estimating R and T	261	118
Transforming properties	266	120
Guessing an inverse	287	125
Some debugging stuff	304	130
Index	313	132

Copyright © 1993–2024 Scott Prahl

Permission is granted to make and distribute verbatim copies of this document provided that the copyright notice and this permission notice are preserved on all copies.

Permission is granted to copy and distribute modified versions of this document under the conditions for verbatim copying, provided that the entire resulting derived work is given a different name and distributed under the terms of a permission notice identical to this one.

1. iad program.

Here is a relatively robust command-line utility that shows how the iad and ad subroutines might be called. It suffers because it is written in CWEB and I used the macro expansion feature instead of creating separate functions. Oh well.

I create an empty file `iad_main.h` to simplify the Makefile

`<iad_main.h 1> ≡`

2. All the actual output for this web file goes into `iad_main.c`

`<iad_main.c 2> ≡`

```

<Include files for main 3>
<print version function 20>
<print usage function 21>
<stringdup together function 27>
<mystrtod function 28>
<seconds elapsed function 29>
<print error legend function 26>
<print dot function 31>
<calculate coefficients function 22>
<parse string into array function 30>
<print results header function 24>
<Print results function 25>
int main(int argc, char **argv)
{
    <Declare variables for main 4>
    <Handle options 5>
    Initialize_Measure(&m);
    <Command-line changes to m 18>
    Initialize_Result(m, &r);
    <Command-line changes to r 13>
    if (cl_forward_calc ≠ UNINITIALIZED) {
        <Calculate and Print the Forward Calculation 6>
        exit(EXIT_SUCCESS);
    }
    <prepare file for reading 10>
    if (process_command_line) {
        <Count command-line measurements 19>
        <Calculate and write optical properties 11>
        exit(EXIT_SUCCESS);
    }
    if (Read_Header(stdin, &m, &params) ≡ 0) {
        start_time = clock();
        while (Read_Data_Line(stdin, &m, params) ≡ 0) {
            <Command-line changes to m 18>
            <Calculate and write optical properties 11>
        }
    }
    if (cl_verbosity > 0) fprintf(stderr, "\n\n");
    if (any_error ∧ cl_verbosity > 1) print_error_legend();
    exit(EXIT_SUCCESS);
}

```

3. The first two defines are to stop Visual C++ from silly complaints

```

< Include files for main 3 > ≡
#define _CRT_SECURE_NO_WARNINGS
#define _CRT_NONSTDC_NO_WARNINGS
#define NO_SLIDES 0
#define ONE_SLIDE_ON_TOP 1
#define TWO_IDENTICAL_SLIDES 2
#define ONE_SLIDE_ON_BOTTOM 3
#define ONE_SLIDE_NEAR_SPHERE 4
#define ONE_SLIDE_NOT_NEAR_SPHERE 5
#define MR_IS_ONLY_RD 1
#define MT_IS_ONLY_TD 2
#define NO_UNSCATTERED_LIGHT 3
#include <stdio.h>
#include <string.h>
#include <stdlib.h>
#include <unistd.h>
#include <time.h>
#include <math.h>
#include <ctype.h>
#include <errno.h>
#include "ad_globl.h"
#include "ad_prime.h"
#include "iad_type.h"
#include "iad_pub.h"
#include "iad_io.h"
#include "iad_calc.h"
#include "iad_util.h"
#include "version.h"
#include "mc_lost.h"
#include "ad_frsl.h"

```

See also section 33.

This code is used in sections 2 and 32.

4. \langle Declare variables for *main* 4 $\rangle \equiv$

```

struct measure_type m;
struct invert_type r;
char *g_out_name =  $\Lambda$ ;
int c;
long n_photons = 100000;
int MC_iterations = 19;
int any_error = 0;
int process_command_line = 0;
int params = 0;
int cl_quadrature_points = UNINITIALIZED;
int cl_verbosity = 2;
double cl_forward_calc = UNINITIALIZED;
double cl_default_a = UNINITIALIZED;
double cl_default_g = UNINITIALIZED;
double cl_default_b = UNINITIALIZED;
double cl_default_mua = UNINITIALIZED;
double cl_default_mus = UNINITIALIZED;
double cl_tolerance = UNINITIALIZED;
double cl_slide_OD = UNINITIALIZED;
double cl_cos_angle = UNINITIALIZED;
double cl_beam_d = UNINITIALIZED;
double cl_sample_d = UNINITIALIZED;
double cl_sample_n = UNINITIALIZED;
double cl_slide_d = UNINITIALIZED;
double cl_slide_n = UNINITIALIZED;
double cl_slides = UNINITIALIZED;
double cl_default_fr = UNINITIALIZED;
double cl_rstd_t = UNINITIALIZED;
double cl_rstd_r = UNINITIALIZED;
double cl_rc_fraction = UNINITIALIZED;
double cl_tc_fraction = UNINITIALIZED;
double cl_search = UNINITIALIZED;
double cl_mus0 = UNINITIALIZED;
double cl_musp0 = UNINITIALIZED;
double cl_mus0_pwr = UNINITIALIZED;
double cl_mus0_lambda = UNINITIALIZED;
double cl_UR1 = UNINITIALIZED;
double cl_UT1 = UNINITIALIZED;
double cl_Tc = UNINITIALIZED;
double cl_method = UNINITIALIZED;
int cl_num_spheres = UNINITIALIZED;
double cl_sphere_one[5] = {UNINITIALIZED, UNINITIALIZED, UNINITIALIZED, UNINITIALIZED,
    UNINITIALIZED};
double cl_sphere_two[5] = {UNINITIALIZED, UNINITIALIZED, UNINITIALIZED, UNINITIALIZED,
    UNINITIALIZED};
clock_t start_time = clock();
char command_line_options[] = "1:2:a:A:b:B:c:C:d:D:e:E:f:F:g:G:hi:n:N:M:o:p:q:r:R:s:S:t:T:\
    u:vV:x:Xz";

```

See also section 34.

This code is used in sections 2 and 32.

5. use the `getopt()` to process options.

⟨Handle options 5⟩ ≡

```
while ((c = getopt(argc, argv, command_line_options)) ≠ EOF) {
    int n;
    char cc;
    switch (c) {
    case '1': parse_string_into_array(optarg, cl_sphere_one, 5);
              break;
    case '2': parse_string_into_array(optarg, cl_sphere_two, 5);
              break;
    case 'a': cl_default_a = my_strtod(optarg);
              if (cl_default_a < 0 ∨ cl_default_a > 1) {
                  fprintf(stderr, "Error_in_command-line\n");
                  fprintf(stderr, "albedo -a%s\n", optarg);
                  exit(EXIT_FAILURE);
              }
              break;
    case 'A': cl_default_mua = my_strtod(optarg);
              if (cl_default_mua < 0) {
                  fprintf(stderr, "Error_in_command-line\n");
                  fprintf(stderr, "absorption -A%s\n", optarg);
                  exit(EXIT_FAILURE);
              }
              break;
    case 'b': cl_default_b = my_strtod(optarg);
              if (cl_default_b < 0) {
                  fprintf(stderr, "Error_in_command-line\n");
                  fprintf(stderr, "optical_thickness -b%s\n", optarg);
                  exit(EXIT_FAILURE);
              }
              break;
    case 'B': cl_beam_d = my_strtod(optarg);
              if (cl_beam_d < 0) {
                  fprintf(stderr, "Error_in_command-line\n");
                  fprintf(stderr, "beam_diameter -B%s\n", optarg);
                  exit(EXIT_FAILURE);
              }
              break;
    case 'c': cl_rc_fraction = my_strtod(optarg);
              if (cl_rc_fraction < 0.0 ∨ cl_rc_fraction > 1.0) {
                  fprintf(stderr, "Error_in_command-line\n");
                  fprintf(stderr, "unscattered_refl_fraction -c%s\n", optarg);
                  fprintf(stderr, "must be between 0 and 1\n");
                  exit(EXIT_SUCCESS);
              }
              break;
    case 'C': cl_tc_fraction = my_strtod(optarg);
              if (cl_tc_fraction < 0.0 ∨ cl_tc_fraction > 1.0) {
                  fprintf(stderr, "Error_in_command-line\n");
                  fprintf(stderr, "unscattered_trans_fraction -C%s\n", optarg);
                  fprintf(stderr, "must be between 0 and 1\n");
                  exit(EXIT_SUCCESS);
              }
    }
```

```

    }
    break;
case 'd': cl_sample_d = my_strtod(optarg);
    if (cl_sample_d < 0) {
        fprintf(stderr, "Error_in_command-line\n");
        fprintf(stderr, "sample_thickness'-d%s'\n", optarg);
        exit(EXIT_FAILURE);
    }
    break;
case 'D': cl_slide_d = my_strtod(optarg);
    if (cl_slide_d < 0) {
        fprintf(stderr, "Error_in_command-line\n");
        fprintf(stderr, "slide_thickness'-D%s'\n", optarg);
        exit(EXIT_FAILURE);
    }
    break;
case 'e': cl_tolerance = my_strtod(optarg);
    if (cl_tolerance < 0) {
        fprintf(stderr, "Error_in_command-line\n");
        fprintf(stderr, "error_tolerance'-e%s'\n", optarg);
        exit(EXIT_FAILURE);
    }
    break;
case 'E': cl_slide_OD = my_strtod(optarg);
    if (cl_slide_OD < 0) {
        fprintf(stderr, "Error_in_command-line\n");
        fprintf(stderr, "slide_optical_depth'-E%s'\n", optarg);
        exit(EXIT_FAILURE);
    }
    break;
case 'f': cl_default_fr = my_strtod(optarg);
    if (cl_default_fr < 0.0 ∨ cl_default_fr > 1.0) {
        fprintf(stderr, "Error_in_command-line\n");
        fprintf(stderr, "fraction_hitting_wall'-f%s'\n", optarg);
        fprintf(stderr, "must_be_between_0_and_1\n");
        exit(EXIT_SUCCESS);
    }
    break;
case 'F': /* initial digit means this is mus is constant */
    if (isdigit(optarg[0])) {
        cl_default_mus = my_strtod(optarg);
        if (cl_default_mus < 0) {
            fprintf(stderr, "Error_in_command-line\n");
            fprintf(stderr, "mus'-F%s'\n", optarg);
            exit(EXIT_FAILURE);
        }
        break;
    }
    /* should be a string like 'R 1000 1.2 -1.8' */
    n = sscanf(optarg, "%c%lf%lf%lf", &cc, &cl_mus0_lambda, &cl_mus0, &cl_mus0_pwr);
    if (n ≠ 4 ∨ (cc ≠ 'P' ∧ cc ≠ 'R')) {
        fprintf(stderr, "Error_in_command-line\n");
        fprintf(stderr, "bad_F_option.'-F%s'\n", optarg);
    }

```

```

    fprintf(stderr, "UUUU-F1.0UUUUUUUUUUUUUUUUUUfor_mus=1.0\n");
    fprintf(stderr, "UUUU-F'P5001.0-1.3'for_mus=1.0*(lambda/500)^(-1.3)\n");
    fprintf(stderr, "UUUU-F'R5001.0-1.3'for_mus'=1.0*(lambda/500)^(-1.3)\n");
    exit(EXIT_FAILURE);
}
if (cc == 'R' ∨ cc == 'r') {
    cl_musp0 = cl_mus0;
    cl_mus0 = UNINITIALIZED;
}
break;
case 'g': cl_default_g = my_strtod(optarg);
if (cl_default_g < -1 ∨ cl_default_g > 1) {
    fprintf(stderr, "Error_in_command-line\n");
    fprintf(stderr, "UUUUanisotropy'-g%s'\n", optarg);
    exit(EXIT_FAILURE);
}
break;
case 'G':
if (optarg[0] == '0') cl_slides = NO_SLIDES;
else if (optarg[0] == '2') cl_slides = TWO_IDENTICAL_SLIDES;
else if (optarg[0] == 't' ∨ optarg[0] == 'T') cl_slides = ONE_SLIDE_ON_TOP;
else if (optarg[0] == 'b' ∨ optarg[0] == 'B') cl_slides = ONE_SLIDE_ON_BOTTOM;
else if (optarg[0] == 'n' ∨ optarg[0] == 'N') cl_slides = ONE_SLIDE_NEAR_SPHERE;
else if (optarg[0] == 'f' ∨ optarg[0] == 'F') cl_slides = ONE_SLIDE_NOT_NEAR_SPHERE;
else {
    fprintf(stderr, "Error_in_command-line\n");
    fprintf(stderr, "UUUUArgument_for'-G%s'must_be\n", optarg);
    fprintf(stderr, "UUUU't'---light_always_hits_top_slide_first\n");
    fprintf(stderr, "UUUU'b'---light_always_hits_bottom_slide_first\n");
    fprintf(stderr, "UUUU'n'---slide_always_closest_to_sphere\n");
    fprintf(stderr, "UUUU'f'---slide_always_farthest_from_sphere\n");
    exit(EXIT_FAILURE);
}
break;
case 'i': cl_cos_angle = my_strtod(optarg);
if (cl_cos_angle < 0 ∨ cl_cos_angle > 90) {
    fprintf(stderr, "Error_in_command-line\n");
    fprintf(stderr, "UUUUincident_angle'-i%s'\n", optarg);
    fprintf(stderr, "UUUUmust_be_between_0_and_90_degrees\n");
    exit(EXIT_FAILURE);
}
cl_cos_angle = cos(cl_cos_angle * M_PI/180.0);
break;
case 'M': MC_iterations = (int) my_strtod(optarg);
if (MC_iterations < 0 ∨ MC_iterations > 50) {
    fprintf(stderr, "Error_in_command-line\n");
    fprintf(stderr, "UUUUMC_iterations'-M%s'\n", optarg);
    exit(EXIT_FAILURE);
}
break;
case 'n': cl_sample_n = my_strtod(optarg);
if (cl_sample_n < 0.1 ∨ cl_sample_n > 10) {

```

```

    fprintf(stderr, "Error_in_command-line\n");
    fprintf(stderr, "slab_index'-n%s'\n", optarg);
    exit(EXIT_FAILURE);
}
break;
case 'N': cl_slide_n = my_strtod(optarg);
    if (cl_slide_n < 0.1 ∨ cl_slide_n > 10) {
        fprintf(stderr, "Error_in_command-line\n");
        fprintf(stderr, "slide_index'-N%s'\n", optarg);
        exit(EXIT_FAILURE);
    }
    break;
case 'o': g_out_name = strdup(optarg);
    break;
case 'p': n_photons = (long) my_strtod(optarg);
    break;
case 'q': cl_quadrature_points = (int) my_strtod(optarg);
    if (cl_quadrature_points % 4 ≠ 0) {
        fprintf(stderr, "Error_in_command-line\n");
        fprintf(stderr, "q%s'\n", optarg);
        fprintf(stderr, "Quadrature_points_must_be_a_multiple_of_4\n");
        exit(EXIT_FAILURE);
    }
    if ((cl_cos_angle ≠ UNINITIALIZED) ∧ (cl_quadrature_points % 12 ≠ 0)) {
        fprintf(stderr, "Error_in_command-line\n");
        fprintf(stderr, "q%s'\n", optarg);
        fprintf(stderr,
            "Quadrature_points_must_be_multiple_of_12_for_oblique_incidence\n");
        exit(EXIT_FAILURE);
    }
    break;
case 'r': cl_UR1 = my_strtod(optarg);
    process_command_line = 1;
    if (cl_UR1 < 0 ∨ cl_UR1 > 1) {
        fprintf(stderr, "Error_in_command-line\n");
        fprintf(stderr, "UR1_value'-r%s'\n", optarg);
        fprintf(stderr, "must_be_between_0_and_1\n");
        exit(EXIT_FAILURE);
    }
    break;
case 'R': cl_rstd_r = my_strtod(optarg);
    if (cl_rstd_r < 0 ∨ cl_rstd_r > 1) {
        fprintf(stderr, "Error_in_command-line\n");
        fprintf(stderr, "Rstd_value'-R%s'\n", optarg);
        fprintf(stderr, "must_be_between_0_and_1\n");
        exit(EXIT_FAILURE);
    }
    break;
case 's': cl_search = (int) my_strtod(optarg);
    break;
case 'S': cl_num_spheres = (int) my_strtod(optarg);
    if (cl_num_spheres ≠ 0 ∧ cl_num_spheres ≠ 1 ∧ cl_num_spheres ≠ 2) {

```



```

    fprintf(stderr, "Error_in_command-line\n");
    fprintf(stderr, "sphere_number'-S%s'\n", optarg);
    fprintf(stderr, "must_be_0,1,or_2\n");
    exit(EXIT_FAILURE);
}
break;
case 't': cl_UT1 = my_strtod(optarg);
    if (cl_UT1 < 0 ∨ cl_UT1 > 1) {
        fprintf(stderr, "Error_in_command-line\n");
        fprintf(stderr, "UT1_value'-t%s'\n", optarg);
        fprintf(stderr, "must_be_between_0_and_1\n");
        exit(EXIT_FAILURE);
    }
    process_command_line = 1;
    break;
case 'T': cl_rstd_t = my_strtod(optarg);
    if (cl_rstd_t < 0 ∨ cl_rstd_t > 1) {
        fprintf(stderr, "Error_in_command-line\n");
        fprintf(stderr, "transmission_standard'-T%s'\n", optarg);
        fprintf(stderr, "must_be_between_0_and_1\n");
        exit(EXIT_FAILURE);
    }
    break;
case 'u': cl_Tc = my_strtod(optarg);
    if (cl_Tc < 0 ∨ cl_Tc > 1) {
        fprintf(stderr, "Error_in_command-line\n");
        fprintf(stderr, "unscattered_transmission'-u%s'\n", optarg);
        fprintf(stderr, "must_be_between_0_and_1\n");
        exit(EXIT_FAILURE);
    }
    process_command_line = 1;
    break;
case 'v': print_version(cl_verbosity);
    exit(EXIT_SUCCESS);
    break;
case 'V': cl_verbosity = my_strtod(optarg);
    break;
case 'x': Set_Debugging((int) my_strtod(optarg));
    break;
case 'X': cl_method = COMPARISON;
    break;
case 'z': cl_forward_calc = 1;
    process_command_line = 1;
    break;
default: fprintf(stderr, "unknown_option'%c'\n", c); /* fall through */
case 'h': print_usage();
    exit(EXIT_SUCCESS);
}
}
argc -= optind;
argv += optind;

```

This code is used in section 2.

6. We are doing a forward calculation. We still need to set the albedo and optical depth appropriately. Obviously when the -a switch is used then the albedo should be fixed as a constant equal to *cl_default_a*. The other cases are less clear. If scattering and absorption are both specified, then calculate the albedo using these values. If the scattering is not specified, then we assume that the sample is an unscattering sample and therefore the albedo is zero. On the other hand, if the scattering is specified and the absorption is not, then the albedo is set to one.

```

⟨ Calculate and Print the Forward Calculation 6 ⟩ ≡
  if (cl_default_a ≡ UNINITIALIZED) {
    if (cl_default_mus ≡ UNINITIALIZED) r.a = 0;
    else if (cl_default_mua ≡ UNINITIALIZED) r.a = 1;
    else r.a = cl_default_mus / (cl_default_mua + cl_default_mus);
  }
  else r.a = cl_default_a;

```

See also sections 7, 8, and 9.

This code is used in section 2.

7. This is slightly more tricky because there are four things that can affect the optical thickness — *cl_default_b*, the default mua, default mus and the thickness. If the sample thickness is unspecified, then the only reasonable thing to do is to assume that the sample is very thick. Otherwise, we use the sample thickness to calculate the optical thickness.

```

⟨ Calculate and Print the Forward Calculation 6 ⟩ +≡
  if (cl_default_b ≡ UNINITIALIZED) {
    if (cl_sample_d ≡ UNINITIALIZED) r.b = HUGE_VAL;
    else if (r.a ≡ 0) {
      if (cl_default_mua ≡ UNINITIALIZED) r.b = HUGE_VAL;
      else r.b = cl_default_mua * cl_sample_d;
    }
    else {
      if (cl_default_mus ≡ UNINITIALIZED) r.b = HUGE_VAL;
      else r.b = cl_default_mus / r.a * cl_sample_d;
    }
  }
  else r.b = cl_default_b;

```

8. The easiest case, use the default value or set it to zero

```

⟨ Calculate and Print the Forward Calculation 6 ⟩ +≡
  if (cl_default_g ≡ UNINITIALIZED) r.g = 0;
  else r.g = cl_default_g;

```

9. \langle Calculate and Print the Forward Calculation 6 $\rangle + \equiv$

```

r.slab.a = r.a;
r.slab.b = r.b;
r.slab.g = r.g;
{
    double mu_sp, mu_a, m_r, m_t;
    Calculate_MR_MT(m, r, MC_iterations, &m_r, &m_t);
    Calculate_Mua_Musp(m, r, &mu_sp, &mu_a);
    if (cl_verbosity > 0) {
        Write_Header(m, r, -1);
        print_results_header(stdout);
    }
    print_optical_property_result(stdout, m, r, m_r, m_t, mu_a, mu_sp, 0, 0);
}

```

10. Make sure that the file is not named '-' and warn about too many files

\langle prepare file for reading 10 $\rangle \equiv$

```

if (argc > 1) {
    fprintf(stderr, "Only a single file can be processed at a time\n");
    fprintf(stderr, "try 'applyiad file1 file2 ... fileN'\n");
    exit(EXIT_FAILURE);
}
if (argc == 1 ^ strcmp(argv[0], "-") != 0) { /* filename exists and != "-" */
    int n;
    char *base_name, *rt_name;
    base_name = strdup(argv[0]);
    n = (int)(strlen(base_name) - strlen(".rxt"));
    if (n > 0 ^ strstr(base_name + n, ".rxt") != 0) base_name[n] = '\0';
    rt_name = strdup_together(base_name, ".rxt");
    if (freopen(argv[0], "r", stdin) == 0 ^ freopen(rt_name, "r", stdin) == 0) {
        fprintf(stderr, "Could not open either '%s' or '%s'\n", argv[0], rt_name);
        exit(EXIT_FAILURE);
    }
    if (g_out_name == 0) g_out_name = strdup_together(base_name, ".txt");
    free(rt_name);
    free(base_name);
    process_command_line = 0;
}
if (g_out_name != 0) {
    if (freopen(g_out_name, "w", stdout) == 0) {
        fprintf(stderr, "Could not open file '%s' for output\n", g_out_name);
        exit(EXIT_FAILURE);
    }
}
}

```

This code is used in section 2.

11. Need to explicitly reset *r.search* each time through the loop, because it will get altered by the calculation process. We want to be able to let different lines have different constraints. In particular consider the file *newton.tst*. In that file the first two rows contain three real measurements and the last two have the collimated transmission explicitly set to zero — in other words there are really only two measurements.

⟨ Calculate and write optical properties 11 ⟩ ≡

```
{
  ⟨ Local Variables for Calculation 12 ⟩
  if (Debug(DEBUG_ANY)) {
    fprintf(stderr, "\n-----NEXT_DATA_POINT-----\n");
    if (m.lambda ≠ 0) fprintf(stderr, "lambda=%6.1f", m.lambda);
    fprintf(stderr, "MR=%8.5f MT=%8.5f\n\n", m.m_r, m.m_t);
  }
  Initialize_Result(m, &r);
  ⟨ Command-line changes to r 13 ⟩
  if (cl_method ≡ COMPARISON ∧ m.d_sphere_r ≠ 0 ∧ m.as_r ≡ 0) {
    fprintf(stderr, "A dual-beam measurement is specified, but no port sizes.\n");
    fprintf(stderr, "You might forsake the -X option and use zero spheres (which gives\n");
    fprintf(stderr, "the same result except lost light is not taken into account).\n");
    fprintf(stderr, "Alternatively, bite the bullet and enter your sphere parameters,\n");
    fprintf(stderr, "with the knowledge that only the beam diameter and sample port\n");
    fprintf(stderr, "diameter will be used to estimate lost light from the edges.\n");
    exit(EXIT_SUCCESS);
  }
  if (cl_method ≡ COMPARISON ∧ m.num_spheres ≡ 2) {
    fprintf(stderr, "A dual-beam measurement is specified, but a two sphere experiment\n");
    fprintf(stderr, "is specified. Since this seems impossible, I will make it\n");
    fprintf(stderr, "impossible for you unless you specify 0 or 1 sphere.\n");
    exit(EXIT_SUCCESS);
  }
  ⟨ Write Header 14 ⟩
  Inverse_RT(m, &r);
  if (r.error ≡ IAD_NO_ERROR) {
    calculate_coefficients(m, r, &LR, &LT, &mu_sp, &mu_a);
    ⟨ Improve result using Monte Carlo 15 ⟩
  }
  print_optical_property_result(stdout, m, r, LR, LT, mu_a, mu_sp, mc_iter, rt_total);
  if (Debug(DEBUG_LOST_LIGHT)) fprintf(stderr, "\n");
  else print_dot(start_time, r.error, mc_total, rt_total, 99, cl_verbosity, &any_error);
}
```

See also section 36.

This code is used in sections 2 and 32.

12.

⟨Local Variables for Calculation 12⟩ ≡

```

static int rt_total = 0;
static int mc_total = 0;
int mc_iter = 0;
double ur1 = 0;
double ut1 = 0;
double uru = 0;
double utu = 0;
double mu_a = 0;
double mu_sp = 0;
double LR = 0;
double LT = 0;

rt_total++;

```

This code is used in section 11.

13. ⟨Command-line changes to *r* 13⟩ ≡

```

if (cl_quadrature_points ≠ UNINITIALIZED) r.method.quad_pts = cl_quadrature_points;
else r.method.quad_pts = 8;
if (cl_default_a ≠ UNINITIALIZED) r.default_a = cl_default_a;
if (cl_default_mua ≠ UNINITIALIZED) {
    r.default_mua = cl_default_mua;
    if (cl_sample_d ≠ UNINITIALIZED) r.default_ba = cl_default_mua * cl_sample_d;
    else r.default_ba = cl_default_mua * m.slabs.thickness;
}
if (cl_default_b ≠ UNINITIALIZED) r.default_b = cl_default_b;
if (cl_default_g ≠ UNINITIALIZED) r.default_g = cl_default_g;
if (cl_tolerance ≠ UNINITIALIZED) {
    r.tolerance = cl_tolerance;
    r.MC_tolerance = cl_tolerance;
}
if (cl_musp0 ≠ UNINITIALIZED)
    cl_mus0 = (r.default_g ≠ UNINITIALIZED) ? cl_musp0 / (1 - r.default_g) : cl_musp0;
if (cl_mus0 ≠ UNINITIALIZED ∧ m.lambda ≠ 0)
    cl_default_mus = cl_mus0 * pow(m.lambda / cl_mus0_lambda, cl_mus0_pwr);
if (cl_default_mus ≠ UNINITIALIZED) {
    r.default_mus = cl_default_mus;
    if (cl_sample_d ≠ UNINITIALIZED) r.default_bs = cl_default_mus * cl_sample_d;
    else r.default_bs = cl_default_mus * m.slabs.thickness;
}
if (cl_search ≠ UNINITIALIZED) r.search = cl_search;

```

This code is used in sections 2 and 11.

```

14.  $\langle \text{Write Header 14} \rangle \equiv$ 
  if ( $rt\_total \equiv 1 \wedge cl\_verbosity > 0$ ) {
    Write_Header( $m, r, params$ );
    if ( $MC\_iterations > 0$ ) {
      if ( $n\_photons \geq 0$ )
        fprintf(stdout, "#_Photons_used_to_estimate_lost_light=_%ld\n",  $n\_photons$ );
      else fprintf(stdout, "#_Time_used_to_estimate_lost_light=_%ld_ms\n",  $-n\_photons$ );
    }
    else fprintf(stdout, "#_Photons_used_to_estimate_lost_light=_0\n");
    fprintf(stdout, "#\n");
    print_results_header(stdout);
  }

```

This code is used in section 11.

15. Use Monte Carlo to figure out how much light leaks out. We use the sphere corrected values as the starting values and only do try Monte Carlo when spheres are used, the albedo unknown or non-zero, and there has been no error. The sphere parameters must be known because otherwise the beam size and the port size are unknown.

```

 $\langle \text{Improve result using Monte Carlo 15} \rangle \equiv$ 
  if ( $m.as\_r \neq 0 \wedge r.default\_a \neq 0 \wedge m.num\_spheres > 0$ ) {
    double  $mu\_sp\_last = mu\_sp$ ;
    double  $mu\_a\_last = mu\_a$ ;
    if ( $Debug(DEBUG\_LOST\_LIGHT)$ ) {
      print_results_header(stderr);
      print_optical_property_result(stderr,  $m, r, LR, LT, mu\_a, mu\_sp, mc\_iter, rt\_total$ );
    }
    while ( $mc\_iter < MC\_iterations$ ) {
      MC_Lost( $m, r, n\_photons, \&ur1, \&ut1, \&uru, \&utu, \&m.ur1\_lost, \&m.ut1\_lost, \&m.uru\_lost,$ 
         $\&m.utu\_lost$ );
       $mc\_total++$ ;
       $mc\_iter++$ ;
      Inverse_RT( $m, \&r$ );
      calculate_coefficients( $m, r, \&LR, \&LT, \&mu\_sp, \&mu\_a$ );
      if ( $fabs(mu\_a\_last - mu\_a) / (mu\_a + 0.0001) < r.MC\_tolerance \wedge fabs(mu\_sp\_last - mu\_sp) / (mu\_sp +$ 
         $0.0001) < r.MC\_tolerance$ ) break;
       $mu\_a\_last = mu\_a$ ;
       $mu\_sp\_last = mu\_sp$ ;
      if ( $Debug(DEBUG\_LOST\_LIGHT)$ )
        print_optical_property_result(stderr,  $m, r, LR, LT, mu\_a, mu\_sp, mc\_iter, rt\_total$ );
      else print_dot( $start\_time, r.error, mc\_total, rt\_total, mc\_iter, cl\_verbosity, \&any\_error$ );
      if ( $r.error \neq IAD\_NO\_ERROR$ ) break;
    }
  }

```

This code is used in section 11.

```

16.  ⟨ Testing MC code 16 ⟩ ≡
    {
        struct AD_slab_type s;
        double ur1, ut1, uru, utu;
        double adur1, adut1, aduru, adutu;

        s.a = 0.0;
        s.b = 0.5;
        s.g = 0.0;
        s.phase_function = HENYEY_GREENSTEIN;
        s.n_slab = 1.0;
        s.n_top_slide = 1.0;
        s.n_bottom_slide = 1.0;
        s.b_top_slide = 0;
        s.b_bottom_slide = 0;
        MC_RT(s, &ur1, &ut1, &uru, &utu);
        RT(32, &s, &adur1, &adut1, &aduru, &adutu);
        fprintf(stderr, "\na=%5.4f_b=%5.4f_g=%5.4f_n=%5.4f_ns=%5.4f\n", s.a, s.b, s.g, s.n_slab,
            s.n_top_slide);
        fprintf(stderr, "UUUR1UUUUUUUUUUUUUT1UUUUUUUUUUUUURUUUUUUUUUUUUUUTU\n");
        fprintf(stderr, "UUADUUUUUUUUUUADUUUUUUUUUUADUUUUUUUUUUADUUUUUUUUUUADUUUUUUUUUU\n");
        fprintf(stderr, "%5.4f_%5.4f_%5.4f_%5.4f", adur1, ur1, adut1, ut1);
        fprintf(stderr, "%5.4f_%5.4f_%5.4f_%5.4f\n_u", aduru, uru, adutu, utu);
        s.b = 100.0;
        s.n_slab = 1.5;
        fprintf(stderr, "\na=%5.4f_b=%5.4f_g=%5.4f_n=%5.4f_ns=%5.4f\n", s.a, s.b, s.g, s.n_slab,
            s.n_top_slide);
        MC_RT(s, &ur1, &ut1, &uru, &utu);
        RT(32, &s, &adur1, &adut1, &aduru, &adutu);
        fprintf(stderr, "%5.4f_%5.4f_%5.4f_%5.4f", adur1, ur1, adut1, ut1);
        fprintf(stderr, "%5.4f_%5.4f_%5.4f_%5.4f\n_u", aduru, uru, adutu, utu);
        s.n_slab = 2.0;
        fprintf(stderr, "\na=%5.4f_b=%5.4f_g=%5.4f_n=%5.4f_ns=%5.4f\n", s.a, s.b, s.g, s.n_slab,
            s.n_top_slide);
        MC_RT(s, &ur1, &ut1, &uru, &utu);
        RT(32, &s, &adur1, &adut1, &aduru, &adutu);
        fprintf(stderr, "%5.4f_%5.4f_%5.4f_%5.4f", adur1, ur1, adut1, ut1);
        fprintf(stderr, "%5.4f_%5.4f_%5.4f_%5.4f\n_u", aduru, uru, adutu, utu);
        s.n_slab = 1.5;
        s.n_top_slide = 1.5;
        s.n_bottom_slide = 1.5;
        fprintf(stderr, "\na=%5.4f_b=%5.4f_g=%5.4f_n=%5.4f_ns=%5.4f\n", s.a, s.b, s.g, s.n_slab,
            s.n_top_slide);
        MC_RT(s, &ur1, &ut1, &uru, &utu);
        RT(32, &s, &adur1, &adut1, &aduru, &adutu);
        fprintf(stderr, "%5.4f_%5.4f_%5.4f_%5.4f", adur1, ur1, adut1, ut1);
        fprintf(stderr, "%5.4f_%5.4f_%5.4f_%5.4f\n_u", aduru, uru, adutu, utu);
        s.n_slab = 1.3;
        s.n_top_slide = 1.5;
        s.n_bottom_slide = 1.5;
        fprintf(stderr, "\na=%5.4f_b=%5.4f_g=%5.4f_n=%5.4f_ns=%5.4f\n", s.a, s.b, s.g, s.n_slab,
            s.n_top_slide);
        MC_RT(s, &ur1, &ut1, &uru, &utu);
    }

```

```

17.  ⟨old formatting 17⟩ ≡
    if (cl_verbosity > 0 ∧ count % 100 ≡ 0) fprintf(stderr, "\n");
    if (cl_verbosity > 0) printf(format2, m.m_r, m.m_t, m.m_u, r.a, r.b, r.g, r.final_distance);
    else printf("%9.5f\t%9.5f\t%9.5f\t%9.5f\n", r.a, r.b, r.g, r.final_distance);

```


18. Stuff the command line arguments that should be constant over the entire inversion process into the measurement record and set up the result record to handle the arguments properly so that the optical properties can be determined.

⟨ Command-line changes to *m* 18 ⟩ ≡

```

if (cl.cos_angle ≠ UNINITIALIZED) {
    m.slabs.cos_angle = cl.cos_angle;
    if (cl.quadrature_points ≡ UNINITIALIZED) cl.quadrature_points = 12;
    if (cl.quadrature_points ≠ 12 * (cl.quadrature_points/12)) {
        fprintf(stderr,
            "If you use the -i option to specify an oblique incidence angle, then\n");
        fprintf(stderr, "the number of quadrature points must be a multiple of 12\n");
        exit(EXIT_SUCCESS);
    }
}
if (cl.sample_n ≠ UNINITIALIZED) m.slabs.index = cl.sample_n;
if (cl.slide_n ≠ UNINITIALIZED) {
    m.slabs.bottom.slide_index = cl.slide_n;
    m.slabs.top.slide_index = cl.slide_n;
}
if (cl.slide_OD ≠ UNINITIALIZED) {
    m.slabs.bottom.slide_b = cl.slide_OD;
    m.slabs.top.slide_b = cl.slide_OD;
}
if (cl.sample_d ≠ UNINITIALIZED) m.slabs.thickness = cl.sample_d;
if (cl.beam_d ≠ UNINITIALIZED) m.d.beam = cl.beam_d;
if (cl.slide_d ≠ UNINITIALIZED) {
    m.slabs.bottom.slide_thickness = cl.slide_d;
    m.slabs.top.slide_thickness = cl.slide_d;
}
if (cl.slides ≡ NO_SLIDES) {
    m.slabs.bottom.slide_index = 1.0;
    m.slabs.bottom.slide_thickness = 0.0;
    m.slabs.top.slide_index = 1.0;
    m.slabs.top.slide_thickness = 0.0;
}
if (cl.slides ≡ ONE_SLIDE_ON_TOP ∨ cl.slides ≡ ONE_SLIDE_NEAR_SPHERE) {
    m.slabs.bottom.slide_index = 1.0;
    m.slabs.bottom.slide_thickness = 0.0;
}
if (cl.slides ≡ ONE_SLIDE_ON_BOTTOM ∨ cl.slides ≡ ONE_SLIDE_NOT_NEAR_SPHERE) {
    m.slabs.top.slide_index = 1.0;
    m.slabs.top.slide_thickness = 0.0;
}
if (cl.slides ≡ ONE_SLIDE_NEAR_SPHERE ∨ cl.slides ≡ ONE_SLIDE_NOT_NEAR_SPHERE) m.flip_sample = 1;
else m.flip_sample = 0;
if (cl.method ≠ UNINITIALIZED) m.method = (int) cl.method;
if (cl.rstd_t ≠ UNINITIALIZED) m.rstd_t = cl.rstd_t;
if (cl.rstd_r ≠ UNINITIALIZED) m.rstd_r = cl.rstd_r;
if (cl.sphere.one[4] ≠ UNINITIALIZED) {
    double d_sample_r, d_entrance_r, d_detector_r;
    m.d.sphere_r = cl.sphere.one[0];
    d_sample_r = cl.sphere.one[1];

```

```

    d_entrance_r = cl_sphere_one[2];
    d_detector_r = cl_sphere_one[3];
    m.rw_r = cl_sphere_one[4];
    m.as_r = (d_sample_r/m.d_sphere_r/2) * (d_sample_r/m.d_sphere_r/2);
    m.ae_r = (d_entrance_r/m.d_sphere_r/2) * (d_entrance_r/m.d_sphere_r/2);
    m.ad_r = (d_detector_r/m.d_sphere_r/2) * (d_detector_r/m.d_sphere_r/2);
    m.aw_r = 1.0 - m.as_r - m.ae_r - m.ad_r;
    m.d_sphere_t = m.d_sphere_r;
    m.as_t = m.as_r;
    m.ae_t = m.ae_r;
    m.ad_t = m.ad_r;
    m.aw_t = m.aw_r;
    m.rw_t = m.rw_r;
    if (cl_num_spheres == UNINITIALIZED) m.num_spheres = 1;
}
if (cl_sphere_two[4] != UNINITIALIZED) {
    double d_sample_t, d_entrance_t, d_detector_t;
    m.d_sphere_t = cl_sphere_two[0];
    d_sample_t = cl_sphere_two[1];
    d_entrance_t = cl_sphere_two[2];
    d_detector_t = cl_sphere_two[3];
    m.rw_t = cl_sphere_two[4];
    m.as_t = (d_sample_t/m.d_sphere_t/2) * (d_sample_t/m.d_sphere_t/2);
    m.ae_t = (d_entrance_t/m.d_sphere_t/2) * (d_entrance_t/m.d_sphere_t/2);
    m.ad_t = (d_detector_t/m.d_sphere_t/2) * (d_detector_t/m.d_sphere_t/2);
    m.aw_t = 1.0 - m.as_t - m.ae_t - m.ad_t;
    if (cl_num_spheres == UNINITIALIZED) m.num_spheres = 2;
}
if (cl_num_spheres != UNINITIALIZED) {
    m.num_spheres = (int) cl_num_spheres;
    if (m.num_spheres > 0 & m.method == UNKNOWN) m.method = SUBSTITUTION;
}
if (cl_rc_fraction != UNINITIALIZED) m.fraction_of_rc_in_mr = cl_rc_fraction;
if (cl_tc_fraction != UNINITIALIZED) m.fraction_of_tc_in_mt = cl_tc_fraction;
if (cl_UR1 != UNINITIALIZED) m.m_r = cl_UR1;
if (cl_UT1 != UNINITIALIZED) m.m_t = cl_UT1;
if (cl_Tc != UNINITIALIZED) m.m_u = cl_Tc;
if (cl_default_fr != UNINITIALIZED) m.f_r = cl_default_fr;

```

This code is used in section 2.

19. put the values for command line reflection and transmission into the measurement record.

⟨ Count command-line measurements 19 ⟩ ≡

```

    m.num_measures = 3;
    if (m.m_t == 0) m.num_measures--;
    if (m.m_u == 0) m.num_measures--;
    params = m.num_measures;
    if (m.num_measures == 3) { /* need to fill slab entries to calculate the optical thickness */
        struct AD_slab_type s;
        s.n_slab = m.slabs_index;
        s.n_top_slide = m.slabs_top_slide_index;
        s.n_bottom_slide = m.slabs_bottom_slide_index;
        s.b_top_slide = m.slabs_top_slide_b;
        s.b_bottom_slide = m.slabs_bottom_slide_b;
        s.cos_angle = m.slabs_cos_angle;
        cl.default_b = What_Is_B(s, m.m_u);
    }

```

This code is used in section 2.

20. ⟨ print version function 20 ⟩ ≡

```

static void print_version(int verbosity)
{
    if (verbosity == 0) {
        fprintf(stdout, "%s", VersionShort);
    }
    else {
        fprintf(stdout, "iad_%s\n", Version);
        fprintf(stdout, "Copyright 1993-2024 Scott Pahl, scott.pahl@oit.edu\n");
        fprintf(stdout, "see Applied Optics, 32:559-568, 1993)\n\n");
        fprintf(stdout, "This is free software; see the source for copying conditions.\n");
        fprintf(stdout, "There is no warranty; not even for MERCHANTABILITY or FITNESS.\n");
        fprintf(stdout, "FOR A PARTICULAR PURPOSE.\n");
    }
}

```

This code is used in section 2.

```
static void print_usage(void)
```

```

fprintf(stdout, "iad%s\n\n", Version);
fprintf(stdout, "iad_finds_optical_properties_from_measurements\n\n");
fprintf(stdout, "Usage: iad [options] input\n\n");
fprintf(stdout, "Options:\n");
fprintf(stdout, "  -l '#.#.#.#' reflection sphere parameters\n");
fprintf(stdout, "  -2 '#.#.#.#' transmission sphere parameters\n");
fprintf(stdout, "  -s 'sphere_d, sample_d, entrance_d, detector_d, wall_r'\n");
fprintf(stdout, "  -a # use this albedo\n");
fprintf(stdout, "  -A # use this absorption coefficient\n");
fprintf(stdout, "  -b # use this optical thickness\n");
fprintf(stdout, "  -B # beam diameter\n");
fprintf(stdout, "  -c # fraction of unscattered refl in MR\n");
fprintf(stdout, "  -C # fraction of unscattered trans in MT\n");
fprintf(stdout, "  -d # thickness of sample\n");
fprintf(stdout, "  -D # thickness of slide\n");
fprintf(stdout, "  -e # error tolerance (default 0.0001)\n");
fprintf(stdout, "  -E # optical depth (=mu*D) for slides\n");
fprintf(stdout, "  -f # allow a fraction 0.0-1.0 of light to hit sphere wall first\n");
fprintf(stdout, "  -F # use this scattering coefficient\n");
fprintf(stdout, "  -F 'P_lambda0 mus0 gamma' mus=mus0*(lambda/lambda0)^gamma\n");
fprintf(stdout, "  -F 'R_lambda0 musp0 gamma' musp=musp0*(lambda/lambda0)^gamma\n");
fprintf(stdout, "  -g # scattering anisotropy (default 0)\n");
fprintf(stdout, "  -G # type of boundary '0', '2', 't', 'b', 'n', 'f'\n");
fprintf(stdout, "  -O '0' or '2' --- number of slides\n");
fprintf(stdout, "  -t 't' (top) or 'b' (bottom) --- one slide\n");
fprintf(stdout, "  -n 'n' (near) or 'f' (far) --- one slide\n");
fprintf(stdout, "  -p position relative to sphere\n");
fprintf(stdout, "  -h display help\n");
fprintf(stdout, "  -i # light is incident at this angle in degrees\n");
fprintf(stdout, "  -M # number of Monte Carlo iterations\n");
fprintf(stdout, "  -n # specify index of refraction of slab\n");
fprintf(stdout, "  -N # specify index of refraction of slides\n");
fprintf(stdout, "  -o filename explicitly specify filename for output\n");
fprintf(stdout, "  -p # of Monte Carlo photons (default 100000)\n");
fprintf(stdout, "  -a negative number is max MC time in milliseconds\n");
fprintf(stdout, "  -q # number of quadrature points (default=8)\n");
fprintf(stdout, "  -r # total reflection measurement\n");
fprintf(stdout, "  -R # actual reflectance for 100% measurement\n");
fprintf(stdout, "  -S # number of spheres used\n");
fprintf(stdout, "  -t # total transmission measurement\n");
fprintf(stdout, "  -T # actual transmission for 100% measurement\n");
fprintf(stdout, "  -u # unscattered transmission measurement\n");
fprintf(stdout, "  -v version information\n");
fprintf(stdout, "  -V0 verbosity low --- no output to stdout\n");
fprintf(stdout, "  -V1 verbosity moderate\n");
fprintf(stdout, "  -V2 verbosity high\n");
fprintf(stdout, "  -x # set debugging level\n");

```

```
fprintf(stdout,"_X_xxxxxxxxxxxxxxxxxxxxxx_dual_beam_configuration\n");
fprintf(stdout,"_Z_zxxxxxxxxxxxxxxxxxxxxxx_forward_calculation\n");
fprintf(stdout,"Examples:\n");
fprintf(stdout,"_I_iad_file.rxt_yyyyyyyyyyyyyyyy_Results_will_be_put_in_file.txt\n");
fprintf(stdout,"_I_iad_file_yyyyyyyyyyyyyyyyyyy_Same_as_above\n");
fprintf(stdout,"_I_iad_c0.9_file.rxt_yyyyyy_Assume_M_R_includes_90%_of_uns\ncattered_reflectance\n");
fprintf(stdout,"_I_iad_C0.8_file.rxt_yyyyyy_Assume_M_T_includes_80%_of_uns\ncattered_transmittance\n");
fprintf(stdout,"_I_iad_e0.0001_file.rxt_yyyy_Better_convergence_to_R_&_T_values\n");
fprintf(stdout,"_I_iad_f1.0_file.rxt_yyyyyy_All_light_hits_reflectance_sphere_wall_first\n");
fprintf(stdout,"_I_iad_o_out_file.rxt_yyyyyyy_Calculated_values_in_out\n");
fprintf(stdout,"_I_iad_r0.3_yyyyyyyyyyyyyyyyyy_R_total=0.3,b=inf,_find_albedo\n");
fprintf(stdout,"_I_iad_r0.3_t0.4_yyyyyyyyyyy_R_total=0.3,T_total=0.4,_find_a,b,g\n");
fprintf(stdout,"_I_iad_r0.3_t0.4_n1.5_yyy_R_total=0.3,T_total=0.4,n=1.5,_find_a,b\n");
fprintf(stdout,"_I_iad_r0.3_t0.4_yyyyyyy_R_total=0.3,T_total=0.4,_find_a,b\n");
fprintf(stdout,"_I_iad_p1000_file.rxt_yyyyyy_Only_1000_photons\n");
fprintf(stdout,"_I_iad_p-100_file.rxt_yyyyyy_Allow_only_100ms_per_iteration\n");
fprintf(stdout,"_I_iad_q4_file.rxt_yyyyyyy_Four_quadrature_points\n");
fprintf(stdout,"_I_iad_M0_file.rxt_yyyyyyy_No_MC_yyyy_(iad)\n");
fprintf(stdout,"_I_iad-M1_file.rxt_yyyyyyy_MC_once_(iad->MC->iad)\n");
fprintf(stdout,"_I_iad-M2_file.rxt_yyyyyyy_MC_twice_(iad->MC->iad->MC->iad)\n");
fprintf(stdout,"_I_iad-M0-q4_file.rxt_yyyy_Fast_and_crude_conversion\n");
fprintf(stdout,"_I_iad-Gt_file.rxt_yyyyyyyyyy_One_top_slide_with_properties_from_file.rxt\n");
fprintf(stdout,"_I_iad-Gb-N1.5-D1_file_Use_1_bottom_slide_with_n=1.5_and_thickness=1\n");
fprintf(stdout,"_I_iad-x_yyy1_file.rxt_yyyyyyy_Show_sphere_and_MC_effects\n");
fprintf(stdout,"_I_iad-x_yyy2_file.rxt_yyyyyyy_DEBUG_GRID\n");
fprintf(stdout,"_I_iad-x_yyy4_file.rxt_yyyyyyy_DEBUG_ITERATIONS\n");
fprintf(stdout,"_I_iad-x_yyy8_file.rxt_yyyyyyy_DEBUG_LOST_LIGHT\n");
fprintf(stdout,"_I_iad-x_yy16_file.rxt_yyyyyyy_DEBUG_SPHERE_EFFECTS\n");
fprintf(stdout,"_I_iad-x_yy32_file.rxt_yyyyyyy_DEBUG_BEST_GUESS\n");
fprintf(stdout,"_I_iad-x_yy64_file.rxt_yyyyyyy_DEBUG_EVERY_CALC\n");
fprintf(stdout,"_I_iad-x_y128_file.rxt_yyyyyyy_DEBUG_SEARCH\n");
fprintf(stdout,"_I_iad-x_y255_file.rxt_yyyyyyy_All_debugging_output\n");
fprintf(stdout,"_I_iad-X-i8_file.rxt_yyyyyyy_Dual_beam_spectrometer_with_8_degree_incidence\n\n");
fprintf(stdout,"_I_iad-z-a0.9-b1-i45_Forward_calc_assuming_45_degree_incidence\n\n");
fprintf(stdout,"_apply_iadx.rtx.y.rxt_yyyy_Process_multiple_files\n\n");
fprintf(stdout,"Report_bugs_to_scott.prahl@oit.edu\n\n");
```

22. Just figure out the damn scattering and absorption

⟨calculate coefficients function 22⟩ ≡

```
static void Calculate_Mua_Musp(struct measure_type m, struct invert_type r, double
    *musp, double *mua)
{
    if (r.b ≡ HUGE_VAL) {
        if (r.a ≤ 1 · 10-5) {
            *musp = 0.0;
            *mua = 1.0;
            return;
        }
        if (r.default_mus ≠ UNINITIALIZED) {
            *musp = r.default_mus * (1 - r.g);
            *mua = r.default_mus / r.a - r.default_mus;
            return;
        }
        if (r.default_mua ≠ UNINITIALIZED) {
            *musp = (r.default_mua / (1 - r.a) - r.default_mua) * (1 - r.g);
            *mua = r.default_mua;
            return;
        }
        *musp = 1.0 - r.g;
        *mua = (1.0 - r.a) / r.a;
        return;
    }
    *musp = r.a * r.b / m.slab_thickness * (1.0 - r.g);
    *mua = (1 - r.a) * r.b / m.slab_thickness;
}
```

See also section 23.

This code is used in section 2.

23. This can only be called immediately after *Inverse_RT* You have been warned! Notice that *Calculate_Distance* does not pass any slab properties.

⟨calculate coefficients function 22⟩ +≡

```
static void calculate_coefficients(struct measure_type m, struct invert_type r, double *LR, double
    *LT, double *musp, double *mua)
{
    double delta;
    *LR = 0;
    *LT = 0;
    Calculate_Distance(LR, LT, &delta);
    Calculate_Mua_Musp(m, r, musp, mua);
}
```

This code is used in section 2.

$$\langle \text{Print results function } 25 \rangle \equiv$$

This code is used in section 2.

26. \langle print error legend function 26 $\rangle \equiv$

```
static void print_error_legend(void)
{
    fprintf(stderr, "-----Sorry, but... errors encountered-----\n");
    fprintf(stderr, "****=>Success*****");
    fprintf(stderr, "0-9=>Monte Carlo Iteration\n");
    fprintf(stderr, "R=>M_R_is_too_big");
    fprintf(stderr, "r=>M_R_is_too_small\n");
    fprintf(stderr, "T=>M_T_is_too_big");
    fprintf(stderr, "t=>M_T_is_too_small\n");
    fprintf(stderr, "U=>M_U_is_too_big");
    fprintf(stderr, "u=>M_U_is_too_small\n");
    fprintf(stderr, "!=>M_R+M_T>1");
    fprintf(stderr, "+=>Did not converge\n\n");
}
```

This code is used in section 2.

27. returns a new string consisting of s+t

\langle stringdup together function 27 $\rangle \equiv$

```
static char *strdup_together(char *s, char *t)
{
    char *both;
    if (s == 0) {
        if (t == 0) return 0;
        return strdup(t);
    }
    if (t == 0) return strdup(s);
    both = malloc(strlen(s) + strlen(t) + 1);
    if (both == 0) fprintf(stderr, "Could not allocate memory for both strings.\n");
    strcpy(both, s);
    strcat(both, t);
    return both;
}
```

This code is used in section 2.

28. catch parsing errors in strtod

⟨mystrtod function 28⟩ ≡

```
static double my_strtod(const char *str)
{
    char *endptr;
    errno = 0;
    double val = strtod(str, &endptr);
    if (endptr == str) { /* No digits were found */
        fprintf(stderr, "Error in command-line\n");
        fprintf(stderr, "No conversion could be performed for '%s'.\n", str);
        exit(EXIT_FAILURE);
    }
    if (*endptr != '\0') { /* String contains extra characters after the number */
        fprintf(stderr, "Error in command-line\n");
        fprintf(stderr, "Partial conversion of string = '%s'\n", str);
        exit(EXIT_FAILURE);
    }
    if (errno == ERANGE) {
        /* The converted value is out of range of representable values by a double */
        fprintf(stderr, "Error in command-line\n");
        printf("The value '%s' is out of range of double.\n", str);
        exit(EXIT_FAILURE);
    }
    return val;
}
```

This code is used in section 2.

29. assume that start time has already been set

⟨seconds elapsed function 29⟩ ≡

```
static double seconds_elapsed(clock_t start_time)
{
    clock_t finish_time = clock();
    return (double)(finish_time - start_time)/CLOCKS_PER_SEC;
}
```

This code is used in section 2.

30. given a string and an array, this fills the array with numbers from the string. The numbers should be separated by spaces.

Returns 0 upon successfully filling n entries, returns 1 for any error.

⟨parse string into array function 30⟩ ≡

```
static int parse_string_into_array(char *s, double *a, int n)
{
    char *t, *last, *r;
    int i = 0;

    t = s;
    last = s + strlen(s);
    while (t < last) { /* a space should mark the end of number */
        r = t;
        while (*r ≠ ' ' ∧ *r ≠ '\0') r++;
        *r = '\0'; /* parse the number and save it */
        if (sscanf(t, "%lf", &(a[i])) ≡ 0) return 1;
        i++; /* are we done ? */
        if (i ≡ n) {
            if (a[i - 1] ≤ 0 ∨ a[i - 1] > 1) {
                fprintf(stderr,
                    "Sphere_wall_reflectivity(r_w=%g) must be a fraction less than one.\n",
                    a[i - 1]);
                exit(EXIT_FAILURE);
            }
            return 0;
        } /* move pointer just after last number */
        t = r + 1;
    }
    return 1;
}
```

This code is used in section 2.

31. $\langle \text{print dot function 31} \rangle \equiv$

```
static char what_char(int err)
{
    if (err == IAD_NO_ERROR) return '*';
    if (err == IAD_TOO_MANY_ITERATIONS) return '+';
    if (err == IAD_MR_TOO_BIG) return 'R';
    if (err == IAD_MR_TOO_SMALL) return 'r';
    if (err == IAD_MT_TOO_BIG) return 'T';
    if (err == IAD_MT_TOO_SMALL) return 't';
    if (err == IAD_MU_TOO_BIG) return 'U';
    if (err == IAD_MU_TOO_SMALL) return 'u';
    if (err == IAD_TOO_MUCH_LIGHT) return '!';
    return '?';
}

static void print_dot(clock_t start_time, int err, int count, int points, int final, int verbosity, int
                    *any_error)
{
    static int counter = 0;
    (void) count;
    counter++;
    if (err != IAD_NO_ERROR) *any_error = err;
    if (verbosity == 0) return;
    if (final == 99) fprintf(stderr, "%c", what_char(err));
    else {
        counter--;
        fprintf(stderr, "%1d\b", final % 10);
    }
    if (final == 99) {
        if (counter % 50 == 0) {
            double rate = (seconds_elapsed(start_time)/points);
            fprintf(stderr, "\u003d\u003done\u003d(%5.2f\u003ds/pt)\n", points, rate);
        }
        else if (counter % 10 == 0) fprintf(stderr, "\u003d");
    }
    fflush(stderr);
}
```

This code is used in section 2.

32. Simple command-line shell program.

Here is a quick skeleton that I put together to show how the inverse adding-doubling code works. I have only cursorily tested this. If you find obvious bugs, they are probably real but should not extend beyond this code snippet.

All the output for this web file goes into `iad_main.c`

```
<iad_main_mus.c 32> ≡
<Include files for main 3>
int main(int argc, char **argv)
{
    <Declare variables for main 4>
    if (Read_Header(&m, &r) ≡ TRUE) {
        <Process the header 35>
        m.num_measures = 2;
        m.m_r = 0.0;
        m.slab_thickness = 0.1;
        while (fp ≠ EOF) {
            fp = scanf("%lf%lf%lf%lf", &lambda, &r.mu_a, &m.default_g, &m.m_t);
            fp = readln(&line);
            <Calculate and write optical properties 11>
        }
    }
    exit(EXIT_SUCCESS);
}
```

33. <Include files for main 3> +≡

```
#include <stdio.h>
#include <string.h>
#include <stdlib.h>
#include "ad_globl.h"
#include "iad_type.h"
#include "iad_pub.h"
#include "iad_io.h"
```

34. <Declare variables for main 4> +≡

```
struct measure_type m;
struct invert_type r;
int lines;
char *format1 = "R\tT\tTc\ta\tb\t\ng\t!/?\n";
char *format2 = "%9.5f\t%9.5f\t%9.5f\t%9.5f\t%9.5f\t%9.5f\t%9c\n";
char found = '?';
int fp;
double lambda;
int line = 1;
```

35. <Process the header 35> ≡

```
m.slab_thickness = 1;
Initialize_Result(m, &r);
Write_Header(m, r);
lines = 1;
printf(format1, m.m_r, m.m_t, m.m_u, r.a, r.b, r.g);
```

This code is used in section 32.

36. \langle Calculate and write optical properties 11 $\rangle + \equiv$

```
{  
  r.search = FIND_mus;  
  Inverse_RT(m, &r);  
  if (r.found  $\equiv$  TRUE) found = '!' ;  
  else found = '?';  
  printf(format2, m.m_r, m.m_t, m.m_u, r.a, r.b, r.g, found);  
  fflush(stdout);  
}
```

37. IAD Types. This file has no routines. It is responsible for creating the header file `iad_type.h` and nothing else. Altered 3/3/95 to change the version number below. Change June 95 to improve cross referencing using CTwill. Change August 97 to add root finding with known absorption

38. These are the various optical properties that can be found with this program. `FIND_AUTO` allows one to let the computer figure out what it should be looking for.

These determine what metric is used in the minimization process.

These give the two different types of illumination allowed.

Finally, for convenience I create a Boolean type.

```
<iad_type.h 38> ≡
#undef FALSE
#undef TRUE
  <Preprocessor definitions>
  <Structs to export from IAD Types 41>
```

39.

```
#define FIND_A 0
#define FIND_B 1
#define FIND_AB 2
#define FIND_AG 3
#define FIND_AUTO 4
#define FIND_BG 5
#define FIND_BaG 6
#define FIND_BsG 7
#define FIND_Ba 8
#define FIND_Bs 9
#define FIND_G 10
#define FIND_B_WITH_NO_ABSORPTION 11
#define FIND_B_WITH_NO_SCATTERING 12
#define RELATIVE 0
#define ABSOLUTE 1
#define COLLIMATED 0
#define DIFFUSE 1
#define FALSE 0
#define TRUE 1
#define IAD_MAX_ITERATIONS 500
```

40. Need error codes for this silly program

```
#define IAD_NO_ERROR 0
#define IAD_TOO_MANY_ITERATIONS 1
#define IAD_AS_NOT_VALID 16
#define IAD_AE_NOT_VALID 17
#define IAD_AD_NOT_VALID 18
#define IAD_RW_NOT_VALID 19
#define IAD_RD_NOT_VALID 20
#define IAD_RSTD_NOT_VALID 21
#define IAD_GAMMA_NOT_VALID 22
#define IAD_F_NOT_VALID 23
#define IAD_BAD_PHASE_FUNCTION 24
#define IAD_QUAD_PTS_NOT_VALID 25
#define IAD_BAD_G_VALUE 26
#define IAD_TOO_MANY_LAYERS 27
#define IAD_MEMORY_ERROR 28
#define IAD_FILE_ERROR 29
#define IAD_EXCESSIVE_LIGHT_LOSS 30
#define IAD_RT_LT_MINIMUM 31
#define IAD_MR_TOO_SMALL 32
#define IAD_MR_TOO_BIG 33
#define IAD_MT_TOO_SMALL 34
#define IAD_MT_TOO_BIG 35
#define IAD_MU_TOO_SMALL 36
#define IAD_MU_TOO_BIG 37
#define IAD_TOO_MUCH_LIGHT 38
#define IAD_TSTD_NOT_VALID 39
#define UNINITIALIZED -99
#define DEBUG_A_LITTLE 1
#define DEBUG_GRID 2
#define DEBUG_ITERATIONS 4
#define DEBUG_LOST_LIGHT 8
#define DEBUG_SPHERE_EFFECTS 16
#define DEBUG_BEST_GUESS 32
#define DEBUG_EVERY_CALC 64
#define DEBUG_SEARCH 128
#define DEBUG_RD_ONLY 256
#define DEBUG_GRID_CALC 512
#define DEBUG_ANY #FFFFFFF
#define UNKNOWN 0
#define COMPARISON 1
#define SUBSTITUTION 2
```

41. The idea of the structure **measure_type** is collect all the information regarding a single measurement together in one spot. No information regarding how the inversion procedure is supposed to be done is contained in this structure, unlike in previous incarnations of this program.

⟨Structs to export from IAD Types 41⟩ =

```
typedef struct measure_type {
    double slab_index;
    double slab_thickness;
    double slab_top_slide_index;
    double slab_top_slide_b;
    double slab_top_slide_thickness;
    double slab_bottom_slide_index;
    double slab_bottom_slide_b;
    double slab_bottom_slide_thickness;
    double slab_cos_angle;
    int num_spheres;
    int num_measures;
    int method;
    int flip_sample;
    double d_beam;
    double fraction_of_rc_in_mr;
    double fraction_of_tc_in_mt;
    double m_r, m_t, m_u;
    double lambda;
    double as_r, ad_r, ae_r, aw_r, rd_r, rw_r, rstd_r, f_r;
    double as_t, ad_t, ae_t, aw_t, rd_t, rw_t, rstd_t, f_t;
    double ur1_lost, uru_lost, ut1_lost, utu_lost;
    double d_sphere_r, d_sphere_t;
} IAD_measure_type;
```

See also sections 42 and 43.

This code is used in section 38.

42. This describes how the inversion process should proceed and also contains the results of that inversion process.

⟨Structs to export from IAD Types 41⟩ +≡

```
typedef struct invert_type {
    double a;      /* the calculated albedo */
    double b;      /* the calculated optical depth */
    double g;      /* the calculated anisotropy */
    int found;
    int search;
    int metric;
    double tolerance;
    double MC_tolerance;
    double final_distance;
    int iterations;
    int error;
    struct AD_slab_type slab;
    struct AD_method_type method;
    double default_a;
    double default_b;
    double default_g;
    double default_ba;
    double default_bs;
    double default_mua;
    double default_mus;
} IAD_invert_type;
```

43. A few types that used to be enum's are now int's.

⟨Structs to export from IAD Types 41⟩ +≡

```
typedef int search_type;
typedef int boolean_type;
typedef int illumination_type;
typedef struct guess_t {
    double distance;
    double a;
    double b;
    double g;
} guess_type;
extern double FRACTION;
```

44. IAD Public.

This contains the routine *Inverse_RT* that should generally be the basic entry point into this whole mess. Call this routine with the proper values and true happiness is bound to be yours.

Altered accuracy of the standard method of root finding from 0.001 to 0.00001. Note, it really doesn't help to change the method from ABSOLUTE to RELATIVE, but I did anyway. (3/3/95)

```
<iad_pub.c 44> ≡
#include <stdio.h>
#include <math.h>
#include "nr_util.h"
#include "ad_globl.h"
#include "ad_frsnl.h"
#include "iad_type.h"
#include "iad_util.h"
#include "iad_calc.h"
#include "iad_find.h"
#include "iad_pub.h"
#include "iad_io.h"
#include "stdlib.h"
#include "mc_lost.h"
  <Definition for Inverse_RT 48>
  <Definition for measure_OK 53>
  <Definition for determine_search 60>
  <Definition for Initialize_Result 64>
  <Definition for Initialize_Measure 72>
  <Definition for ez_Inverse_RT 70>
  <Definition for Spheres_Inverse_RT 74>
  <Definition for Spheres_Inverse_RT2 87>
  <Definition for Calculate_MR_MT 81>
  <Definition for MinMax_MR_MT 85>
  <Definition for Calculate_Minimum_MR 83>
```

45. All the information that needs to be written to the header file *iad_pub.h*. This eliminates the need to maintain a set of header files as well.

```
<iad_pub.h 45> ≡
  <Prototype for Inverse_RT 47>;
  <Prototype for measure_OK 52>;
  <Prototype for determine_search 59>;
  <Prototype for Initialize_Result 63>;
  <Prototype for ez_Inverse_RT 69>;
  <Prototype for Initialize_Measure 71>;
  <Prototype for Calculate_MR_MT 80>;
  <Prototype for MinMax_MR_MT 84>;
  <Prototype for Calculate_Minimum_MR 82>;
  <Prototype for Spheres_Inverse_RT2 86>;
```

46. Here is the header file needed to access one interesting routine in the *libiad.so* library.

```
<lib_iad.h 46> ≡
  <Prototype for ez_Inverse_RT 69>;
  <Prototype for Spheres_Inverse_RT 73>;
  <Prototype for Spheres_Inverse_RT2 86>;
```

47. Inverse RT. *Inverse_RT* is the main function in this whole package. You pass the variable *m* containing your experimentally measured values to the function *Inverse_RT*. It hopefully returns the optical properties in *r* that are appropriate for your experiment.

⟨Prototype for *Inverse_RT* 47⟩ ≡

```
void Inverse_RT(struct measure_type m, struct invert_type *r)
```

This code is used in sections 45 and 48.

48. ⟨Definition for *Inverse_RT* 48⟩ ≡

⟨Prototype for *Inverse_RT* 47⟩

```
{
  if (0 ^ Debug(DEBUG_LOST_LIGHT)) {
    fprintf(stderr, "**_Inverse_RT_(%d_spheres)_**\n", m.num_spheres);
    fprintf(stderr, "M_R=%%8.5f, MT=%%8.5f\n", m.m_r, m.m_t);
    fprintf(stderr, "UR1_lost=%%8.5f, UT1_lost=%%8.5f\n", m.ur1_lost, m.ut1_lost);
  }
  r→found = FALSE;
  if (r→search ≡ FIND_AUTO) r→search = determine_search(m, *r);
  if (r→search ≡ FIND_B_WITH_NO_ABSORPTION) {
    r→default_a = 1;
    r→search = FIND_B;
  }
  if (r→search ≡ FIND_B_WITH_NO_SCATTERING) {
    r→default_a = 0;
    r→search = FIND_B;
  }
  ⟨Exit with bad input data 49⟩
  ⟨Find the optical properties 50⟩
  if (r→final_distance ≤ r→tolerance) r→found = TRUE;
}
```

This code is used in section 44.

49. There is no sense going to all the trouble to try a multivariable minimization if the input data is bogus. So I wrote a single routine *measure_OK* to do just this.

⟨Exit with bad input data 49⟩ ≡

```
r→error = measure_OK(m, *r);
if (r→method.quad_pts < 4) r→error = IAD_QUAD_PTS_NOT_VALID;
if (r→error ≠ IAD_NO_ERROR) return;
```

This code is used in section 48.

50. Now I fob the real work off to the unconstrained minimization routines. Ultimately, I would like to replace all these by constrained minimization routines. Actually the first five already are constrained. The real work will be improving the last five because these are 2-D minimization routines.

⟨Find the optical properties 50⟩ ≡

```

switch (r-search) {
  case FIND_A: U_Find_A(m, r);
    break;
  case FIND_B: U_Find_B(m, r);
    break;
  case FIND_G: U_Find_G(m, r);
    break;
  case FIND_Ba: U_Find_Ba(m, r);
    break;
  case FIND_Bs: U_Find_Bs(m, r);
    break;
  case FIND_AB: U_Find_AB(m, r);
    break;
  case FIND_AG: U_Find_AG(m, r);
    break;
  case FIND_BG: U_Find_BG(m, r);
    break;
  case FIND_BsG: U_Find_BsG(m, r);
    break;
  case FIND_BaG: U_Find_BaG(m, r);
    break;
}
if (r-iterations ≡ IAD_MAX_ITERATIONS) r-error = IAD_TOO_MANY_ITERATIONS;

```

This code is used in section 48.

51. Validation.

52. Now the question is — just what is bad data? Here's the prototype.

⟨Prototype for *measure_OK* 52⟩ ≡

```
int measure_OK(struct measure_type m, struct invert_type r)
```

This code is used in sections 45 and 53.

53. It would just be nice to stop computing with bad data. This does not work in practice because it turns out that there is often bogus data in a full wavelength scan. Often the reflectance is too low for short wavelengths and at long wavelengths the detector (photomultiplier tube) does not work worth a damn.

The two sphere checks are more complicated. For example, we can no longer categorically state that the transmittance is less than one or that the sum of the reflectance and transmittance is less than one. Instead we use the transmittance to bound the values for the reflectance — see the routine *MinMax_MR_MT* below.

⟨Definition for *measure_OK* 53⟩ ≡

⟨Prototype for *measure_OK* 52⟩

```
{
  double ru, tu;
  if (m.num_spheres ≠ 2) {
    ⟨Check MT for zero or one spheres 55⟩
    ⟨Check MR for zero or one spheres 54⟩
  }
  else {
    int error = MinMax_MR_MT(m, r);
    if (error ≠ IAD_NO_ERROR) return error;
  }
  ⟨Check MU 56⟩
  if (m.num_spheres ≠ 0) {
    ⟨Check sphere parameters 57⟩
  }
  return IAD_NO_ERROR;
}
```

This code is used in section 44.

54. The reflectance is constrained by the index of refraction of the material and the transmission. The upper bound for the reflectance is just one minus the transmittance. The specular (unscattered) reflectance from the boundaries imposes minimum for the reflectance. Obviously, the reflected light cannot be less than that from the first boundary. This might be calculated by assuming an infinite layer thickness. But we can do better.

There is a definite bound on the minimum reflectance from a sample. If you have a sample with a given transmittance m_t , the minimum reflectance possible is found by assuming that the sample does not scatter any light.

Knowledge of the indices of refraction makes it a relatively simple matter to determine the optical thickness $b = \mu_a * d$ of the slab. The minimum reflection is obtained by including all the specular reflectances from all the surfaces.

If the default albedo has been specified as zero, then there is really no need to check MR because it is ignored.

⟨ Check MR for zero or one spheres 54 ⟩ ≡

```
{
  double mr, mt;
  Calculate_Minimum_MR(m, r, &mr, &mt);
  /* one parameter search only needs one good measurement */
  if (r.search ≡ FIND_A ∨ r.search ≡ FIND_G ∨ r.search ≡ FIND_B ∨ r.search ≡ FIND_Bs ∨ r.search ≡
      FIND_Ba) {
    if (m.m_r < mr ∧ m.m_t ≤ 0) return IAD_MR_TOO_SMALL;
  }
  else {
    if (r.default_a ≡ UNINITIALIZED ∨ r.default_a > 0) {
      if (m.m_r < mr) return IAD_MR_TOO_SMALL;
    }
  }
}
```

This code is used in section 53.

55. The transmittance is also constrained by the index of refraction of the material. The minimum transmittance is zero, but the maximum transmittance cannot exceed the total light passing through the sample when there is no scattering or absorption. This is calculated by assuming an infinitely thin (to eliminate any scattering or absorption effects).

There is a problem when spheres are present. The estimated values for the transmittance using Sp_mu_RT are not actually limiting cases. This will require a bit of fixing, but for now that test is omitted if the number of spheres is more than zero.

⟨ Check MT for zero or one spheres 55 ⟩ ≡

```
if (m.m_t < 0) return IAD_MT_TOO_SMALL;
Sp_mu_RT_Flip(m.flip_sample, r.slabs.n_top_slide, r.slabs.n_slab, r.slabs.n_bottom_slide, r.slabs.b_top_slide, 0,
  r.slabs.b_bottom_slide, r.slabs.cos_angle, &ru, &tu);
if (m.num_spheres ≡ 0 ∧ m.m_t > tu) {
  fprintf(stderr, "ntop=%7.5f, nslab=%7.5f, nbottom=%7.5f\n", r.slabs.n_top_slide, r.slabs.n_slab,
    r.slabs.n_bottom_slide);
  fprintf(stderr, "tu_max=%7.5f, m_t=%7.5f, t_std=%7.5f\n", tu, m.m_t, m.rstd_t);
  return IAD_MT_TOO_BIG;
}
```

This code is used in section 53.

56. The unscattered transmission is now always included in the total transmittance. Therefore the unscattered transmittance must fall between zero and M_T

⟨ Check MU 56 ⟩ \equiv

```
if ( $m_{m_u} < 0$ ) return IAD_MU_TOO_SMALL;
if ( $m_{m_u} > m_{m_t}$ ) return IAD_MU_TOO_BIG;
```

This code is used in section 53.

57. Make sure that reflection sphere parameters are reasonable

⟨ Check sphere parameters 57 ⟩ \equiv

```
if ( $m_{as_r} < 0 \vee m_{as_r} \geq 0.2$ ) return IAD_AS_NOT_VALID;
if ( $m_{ad_r} < 0 \vee m_{ad_r} \geq 0.2$ ) return IAD_AD_NOT_VALID;
if ( $m_{ae_r} < 0 \vee m_{ae_r} \geq 0.2$ ) return IAD_AE_NOT_VALID;
if ( $m_{rw_r} < 0 \vee m_{rw_r} > 1.0$ ) return IAD_RW_NOT_VALID;
if ( $m_{rd_r} < 0 \vee m_{rd_r} > 1.0$ ) return IAD_RD_NOT_VALID;
if ( $m_{rstd_r} < 0 \vee m_{rstd_r} > 1.0$ ) return IAD_RSTD_NOT_VALID;
if ( $m_{rstd_t} < 0 \vee m_{rstd_t} > 1.0$ ) return IAD_TSTD_NOT_VALID;
if ( $m_{f_r} < 0 \vee m_{f_r} > 1$ ) return IAD_F_NOT_VALID;
```

See also section 58.

This code is used in section 53.

58. Make sure that transmission sphere parameters are reasonable

⟨ Check sphere parameters 57 ⟩ $+ \equiv$

```
if ( $m_{as_t} < 0 \vee m_{as_t} \geq 0.2$ ) return IAD_AS_NOT_VALID;
if ( $m_{ad_t} < 0 \vee m_{ad_t} \geq 0.2$ ) return IAD_AD_NOT_VALID;
if ( $m_{ae_t} < 0 \vee m_{ae_t} \geq 0.2$ ) return IAD_AE_NOT_VALID;
if ( $m_{rw_t} < 0 \vee m_{rw_t} > 1.0$ ) return IAD_RW_NOT_VALID;
if ( $m_{rd_t} < 0 \vee m_{rd_t} > 1.0$ ) return IAD_RD_NOT_VALID;
if ( $m_{rstd_t} < 0 \vee m_{rstd_t} > 1.0$ ) return IAD_TSTD_NOT_VALID;
if ( $m_{f_t} < 0 \vee m_{f_t} > 1$ ) return IAD_F_NOT_VALID;
```

59. Searching Method.

The original idea was that this routine would automatically determine what optical parameters could be figured out from the input data. This worked fine for a long while, but I discovered that often it was convenient to constrain the optical properties in various ways. Consequently, this routine got more and more complicated.

What should be done is to figure out whether the search will be 1D or 2D and split this routine into two parts.

It would be nice to enable the user to constrain two parameters, but the infrastructure is missing at this point.

⟨Prototype for *determine_search* 59⟩ ≡

search_type *determine_search*(**struct measure_type** *m*, **struct invert_type** *r*)

This code is used in sections 45 and 60.

60. This routine is responsible for selecting the appropriate optical properties to determine.

⟨Definition for *determine_search* 60⟩ ≡

⟨Prototype for *determine_search* 59⟩

```
{
    double rt, tt, rd, td, tc, rc;
    int search = 0;
    int independent = m.num_measures;
    if (Debug(DEBUG_SEARCH)) {
        fprintf(stderr, "\n***_Determine_Search()\n");
        fprintf(stderr, "starting with %d measurement(s)\n", m.num_measures);
        fprintf(stderr, "m_r=%.5f\n", m.m_r);
        fprintf(stderr, "m_t=%.5f\n", m.m_t);
    }
    Estimate_RT(m, r, &rt, &tt, &rd, &rc, &td, &tc);
    if (m.m_u == 0 ∧ independent == 3) {
        if (Debug(DEBUG_SEARCH)) fprintf(stderr, "no information in tc\n");
        independent--;
    }
    if (rd == 0 ∧ independent == 2) {
        if (Debug(DEBUG_SEARCH)) fprintf(stderr, "no information in rd\n");
        independent--;
    }
    if (td == 0 ∧ independent == 2) {
        if (Debug(DEBUG_SEARCH)) fprintf(stderr, "no information in td\n");
        independent--;
    }
    if (independent == 1 ∨ independent == -1) {
        ⟨One parameter search 61⟩
    }
    else if (independent == 2) {
        ⟨Two parameter search 62⟩
    }
    /* three real parameters with information! */
    else {
        search = FIND_AG;
    }
    if (Debug(DEBUG_SEARCH)) {
        fprintf(stderr, "independent measurements = %3d\n", independent);
        fprintf(stderr, "m_r=%.5f m_t=%.5f (rd=%.5f td=%.5f)\n", m.m_r, m.m_t, rd, td);
        if (search == FIND_A) fprintf(stderr, "search = FIND_A\n");
        if (search == FIND_B) fprintf(stderr, "search = FIND_B\n");
        if (search == FIND_AB) fprintf(stderr, "search = FIND_AB\n");
        if (search == FIND_AG) fprintf(stderr, "search = FIND_AG\n");
        if (search == FIND_AUTO) fprintf(stderr, "search = FIND_AUTO\n");
        if (search == FIND_BG) fprintf(stderr, "search = FIND_BG\n");
        if (search == FIND_BaG) fprintf(stderr, "search = FIND_BaG\n");
        if (search == FIND_BsG) fprintf(stderr, "search = FIND_BsG\n");
        if (search == FIND_Ba) fprintf(stderr, "search = FIND_Ba\n");
        if (search == FIND_Bs) fprintf(stderr, "search = FIND_Bs\n");
        if (search == FIND_G) fprintf(stderr, "search = FIND_G\n");
        if (search == FIND_B_WITH_NO_ABSORPTION)
            fprintf(stderr, "search = FIND_B_WITH_NO_ABSORPTION\n");
    }
}
```

```

    if (search == FIND_B_WITH_NO_SCATTERING)
        fprintf(stderr, "search=FIND_B_WITH_NO_SCATTERING\n");
    }
    return search;
}

```

This code is used in section 44.

61. The fastest inverse problems are those in which just one measurement is known. This corresponds to a simple one-dimensional minimization problem. The only complexity is deciding exactly what should be allowed to vary. The basic assumption is that the anisotropy has been specified or will be assumed to be zero.

If the anisotropy is assumed known, then one other assumption will allow us to figure out the last parameter to solve for.

Ultimately, if no default values are given, then we look at the value of the total transmittance. If this is zero, then we assume that the optical thickness is infinite and solve for the albedo. Otherwise we will just make a stab at solving for the optical thickness assuming the albedo is one.

⟨ One parameter search 61 ⟩ ≡

```

    if (r.default_a != UNINITIALIZED) {
        if (r.default_a == 0) search = FIND_B_WITH_NO_SCATTERING;
        else if (r.default_a == 1) search = FIND_B_WITH_NO_ABSORPTION;
        else if (tt == 0) search = FIND_G;
        else search = FIND_B;
    }
    else if (r.default_b != UNINITIALIZED) search = FIND_A;
    else if (r.default_bs != UNINITIALIZED) search = FIND_Ba;
    else if (r.default_ba != UNINITIALIZED) search = FIND_Bs;
    else if (td == 0) search = FIND_A;
    else if (rd == 0) search = FIND_B_WITH_NO_SCATTERING;
    else search = FIND_B_WITH_NO_ABSORPTION;

```

This code is used in section 60.

62. If the absorption depth $\mu_a d$ is constrained return *FIND_BsG*. Recall that I use the bizarre mnemonic $bs = \mu_s d$ here and so this means that the program will search over various values of $\mu_s d$ and g .

If there are just two measurements then I assume that the anisotropy is not of interest and the only thing to calculate is the reduced albedo and optical thickness based on an assumed anisotropy.

```

⟨Two parameter search 62⟩ ≡
  if (r.default_a ≠ UNINITIALIZED) {
    if (r.default_a ≡ 0) search = FIND_B;
    else if (r.default_g ≠ UNINITIALIZED) search = FIND_B;
    else search = FIND_BG;
  }
  else if (r.default_b ≠ UNINITIALIZED) {
    if (r.default_g ≠ UNINITIALIZED) search = FIND_A;
    else search = FIND_AG;
  }
  else if (r.default_ba ≠ UNINITIALIZED) {
    if (r.default_g ≠ UNINITIALIZED) search = FIND_Bs;
    else search = FIND_BsG;
  }
  else if (r.default_bs ≠ UNINITIALIZED) {
    if (r.default_g ≠ UNINITIALIZED) search = FIND_Ba;
    else search = FIND_BaG;
  }
  else if (rt + tt > 1 ∧ 0 ∧ m.num_spheres ≠ 2) search = FIND_B_WITH_NO_ABSORPTION;
  else search = FIND_AB;

```

This code is used in section 60.

63. This little routine just stuffs reasonable values into the structure we use to return the solution. This does not replace the values for *r.default_g* nor for *r.method.quad_pts*. Presumably these have been set correctly elsewhere.

```

⟨Prototype for Initialize_Result 63⟩ ≡
  void Initialize_Result(struct measure_type m, struct invert_type *r)

```

This code is used in sections 45 and 64.

```

64.  ⟨Definition for Initialize_Result 64⟩ ≡
  ⟨Prototype for Initialize_Result 63⟩
  {
    ⟨Fill r with reasonable values 65⟩
  }

```

This code is used in section 44.

65. Start with the optical properties.

```

⟨Fill r with reasonable values 65⟩ ≡
  r→a = 0.0;
  r→b = 0.0;
  r→g = 0.0;

```

See also sections 66, 67, and 68.

This code is used in section 64.

66. Continue with other useful stuff.

```
⟨ Fill r with reasonable values 65 ⟩ +=
  r→found = FALSE;
  r→tolerance = 0.0001;
  r→MC_tolerance = 0.01;    /* percent */
  r→search = FIND_AUTO;
  r→metric = RELATIVE;
  r→final_distance = 10;
  r→iterations = 0;
  r→error = IAD_NO_ERROR;
```

67. The defaults might be handy

```
⟨ Fill r with reasonable values 65 ⟩ +=
  r→default_a = UNINITIALIZED;
  r→default_b = UNINITIALIZED;
  r→default_g = UNINITIALIZED;
  r→default_ba = UNINITIALIZED;
  r→default_bs = UNINITIALIZED;
  r→default_mua = UNINITIALIZED;
  r→default_mus = UNINITIALIZED;
```

68. It is necessary to set up the slab correctly so, I stuff reasonable values into this record as well.

```
⟨ Fill r with reasonable values 65 ⟩ +=
  r→slab.a = 0.5;
  r→slab.b = 1.0;
  r→slab.g = 0;
  r→slab.phase_function = HENYEY_GREENSTEIN;
  r→slab.n_slab = m.slab_index;
  r→slab.n_top_slide = m.slab_top_slide_index;
  r→slab.n_bottom_slide = m.slab_bottom_slide_index;
  r→slab.b_top_slide = m.slab_top_slide_b;
  r→slab.b_bottom_slide = m.slab_bottom_slide_b;
  r→slab.cos_angle = m.slab_cos_angle;
  r→method.a_calc = 0.5;
  r→method.b_calc = 1;
  r→method.g_calc = 0.5;
  r→method.quad_pts = 8;
  r→method.b_thinnest = 1.0/32.0;
```

69. EZ Inverse RT. *ez_Inverse_RT* is a simple interface to the main function *Inverse_RT* in this package. It eliminates the need for complicated data structures so that the command line interface (as well as those to Perl and Mathematica) will be simpler. This function assumes that the reflection and transmission include specular reflection and that the transmission also include unscattered transmission.

Other assumptions are that the top and bottom slides have the same index of refraction, that the illumination is collimated. Of course no sphere parameters are included.

⟨Prototype for *ez_Inverse_RT* 69⟩ ≡

```
void ez_Inverse_RT(double n,double nslide,double UR1,double UT1,double Tc,double *a,double
    *b,double *g,int *error)
```

This code is used in sections 45, 46, and 70.

70. ⟨Definition for *ez_Inverse_RT* 70⟩ ≡

⟨Prototype for *ez_Inverse_RT* 69⟩

```
{
    struct measure_type m;
    struct invert_type r;

    *a = 0;
    *b = HUGE_VAL;
    *g = 0;
    Initialize_Measure(&m);
    m.slab_index = n;
    m.slab_top_slide_index = nslide;
    m.slab_bottom_slide_index = nslide;
    m.slab_cos_angle = 1.0;
    m.num_measures = 3;
    if (UT1 ≡ 0) m.num_measures —;
    if (Tc ≡ 0) m.num_measures —;
    m.m_r = UR1;
    m.m_t = UT1;
    m.m_u = Tc;
    Initialize_Result(m, &r);
    r.method.quad_pts = 8;
    Inverse_RT(m, &r);
    *error = r.error;
    if (r.error ≡ IAD_NO_ERROR) {
        *a = r.a;
        *b = r.b;
        *g = r.g;
    }
}
```

This code is used in section 44.

71. ⟨Prototype for *Initialize_Measure* 71⟩ ≡

```
void Initialize_Measure(struct measure_type *m)
```

This code is used in sections 45 and 72.

72. \langle Definition for *Initialize_Measure* 72 $\rangle \equiv$

\langle Prototype for *Initialize_Measure* 71 \rangle

```
{
  double default_sphere_d = 8.0 * 25.4;
  double default_sample_d = 0.0 * 25.4;
  double default_detector_d = 0.1 * 25.4;
  double default_entrance_d = 0.5 * 25.4;
  double sphere_area = M_PI * default_sphere_d * default_sphere_d;
  m_slab_index = 1.0;
  m_slab_top_slide_index = 1.0;
  m_slab_top_slide_b = 0.0;
  m_slab_top_slide_thickness = 0.0;
  m_slab_bottom_slide_index = 1.0;
  m_slab_bottom_slide_b = 0.0;
  m_slab_bottom_slide_thickness = 0.0;
  m_slab_thickness = 1.0;
  m_slab_cos_angle = 1.0;
  m_num_spheres = 0;
  m_num_measures = 1;
  m_method = UNKNOWN;
  m_fraction_of_rc_in_mr = 1.0;
  m_fraction_of_tc_in_mt = 1.0;
  m_flip_sample = 0;
  m_m_r = 0.0;
  m_m_t = 0.0;
  m_m_u = 0.0;
  m_d_sphere_r = default_sphere_d;
  m_as_r = (M_PI * default_sample_d * default_sample_d / 4.0) / sphere_area;
  m_ad_r = (M_PI * default_detector_d * default_detector_d / 4.0) / sphere_area;
  m_ae_r = (M_PI * default_entrance_d * default_entrance_d / 4.0) / sphere_area;
  m_aw_r = 1.0 - m_as_r - m_ad_r - m_ae_r;
  m_rd_r = 0.0;
  m_rw_r = 1.0;
  m_rstd_r = 1.0;
  m_f_r = 0.0;
  m_d_sphere_t = default_sphere_d;
  m_as_t = m_as_r;
  m_ad_t = m_ad_r;
  m_ae_t = m_ae_r;
  m_aw_t = m_aw_r;
  m_rd_t = 0.0;
  m_rw_t = 1.0;
  m_rstd_t = 1.0;
  m_f_t = 0.0;
  m_lambda = 0.0;
  m_d_beam = 0.0;
  m_ur1_lost = 0;
  m_u ru_lost = 0;
  m_ut1_lost = 0;
  m_utu_lost = 0;
}
```

This code is used in section 44.

73. To avoid interfacing with C-structures it is necessary to pass the information as arrays. Here I have divided the experiment into (1) setup, (2) reflection sphere coefficients, (3) transmission sphere coefficients, (4) measurements, and (5) results.

⟨Prototype for *Spheres_Inverse_RT* 73⟩ ≡

```
void Spheres_Inverse_RT(double *setup, double *analysis, double *sphere_r, double *sphere_t, double
    *measurements, double *results)
```

This code is used in sections 46 and 74.

74. ⟨Definition for *Spheres_Inverse_RT* 74⟩ ≡

⟨Prototype for *Spheres_Inverse_RT* 73⟩

```
{
    struct measure_type m;
    struct invert_type r;
    long num_photons;
    double ur1, ut1, uru, utu;
    int i, mc_runs = 1;
    Initialize_Measure(&m);
    ⟨handle setup 75⟩
    ⟨handle reflection sphere 78⟩
    ⟨handle transmission sphere 79⟩
    ⟨handle measurement 77⟩
    Initialize_Result(m, &r);
    results[0] = 0;
    results[1] = 0;
    results[2] = 0;
    ⟨handle analysis 76⟩
    Inverse_RT(m, &r);
    for (i = 0; i < mc_runs; i++) {
        MC_Lost(m, r, num_photons, &ur1, &ut1, &uru, &utu, &m.ur1_lost, &m.ut1_lost, &m.uru_lost,
            &m.utu_lost);
        Inverse_RT(m, &r);
    }
    if (r.error ≡ IAD_NO_ERROR) {
        results[0] = (1 - r.a) * r.b / m.slab_thickness;
        results[1] = (r.a) * r.b / m.slab_thickness;
        results[2] = r.g;
    }
    results[3] = r.error;
}
```

This code is used in section 44.

75. These are in exactly the same order as the parameters in the .rxt header

⟨handle setup 75⟩ ≡

```
{
  double d_sample_r, d_entrance_r, d_detector_r;
  double d_sample_t, d_entrance_t, d_detector_t;

  m.slab_index = setup[0];
  m.slab_top_slide_index = setup[1];
  m.slab_thickness = setup[2];
  m.slab_top_slide_thickness = setup[3];
  m.d_beam = setup[4];
  m.rstd_r = setup[5];
  m.num_spheres = (int) setup[6];
  m.d_sphere_r = setup[7];
  d_sample_r = setup[8];
  d_entrance_r = setup[9];
  d_detector_r = setup[10];
  m.rw_r = setup[11];
  m.d_sphere_t = setup[12];
  d_sample_t = setup[13];
  d_entrance_t = setup[14];
  d_detector_t = setup[15];
  m.rw_t = setup[16];
  r.default_g = setup[17];
  num_photons = (long) setup[18];
  m.as_r = (d_sample_r/m.d_sphere_r/2.0) * (d_sample_r/m.d_sphere_r/2.0);
  m.ae_r = (d_entrance_r/m.d_sphere_r/2.0) * (d_entrance_r/m.d_sphere_r/2.0);
  m.ad_r = (d_detector_r/m.d_sphere_r/2.0) * (d_detector_r/m.d_sphere_r/2.0);
  m.aw_r = 1.0 - m.as_r - m.ae_r - m.ad_r;
  m.as_t = (d_sample_t/m.d_sphere_t/2.0) * (d_sample_t/m.d_sphere_t/2.0);
  m.ae_t = (d_entrance_t/m.d_sphere_t/2.0) * (d_entrance_t/m.d_sphere_t/2.0);
  m.ad_t = (d_detector_t/m.d_sphere_t/2.0) * (d_detector_t/m.d_sphere_t/2.0);
  m.aw_t = 1.0 - m.as_t - m.ae_t - m.ad_t;
  m.slab_bottom_slide_index = m.slab_top_slide_index;
  m.slab_bottom_slide_thickness = m.slab_top_slide_thickness;
  fprintf(stderr, "****_executing_FIXME_****/n");
  m.slab_cos_angle = 1.0; /* FIXME */
}
```

This code is used in section 74.

76. ⟨handle analysis 76⟩ ≡

```
r.method.quad_pts = (int) analysis[0];
mc_runs = (int) analysis[1];
```

This code is used in section 74.

77.

```

⟨ handle measurement 77 ⟩ ≡
    m.m_r = measurements[0];
    m.m_t = measurements[1];
    m.m_u = measurements[2];
    m.num_measures = 3;
    if (m.m_t ≡ 0) m.num_measures--;
    if (m.m_u ≡ 0) m.num_measures--;

```

This code is used in section 74.

78.

```

⟨ handle reflection sphere 78 ⟩ ≡
    m.as_r = sphere_r[0];
    m.ae_r = sphere_r[1];
    m.ad_r = sphere_r[2];
    m.rw_r = sphere_r[3];
    m.rd_r = sphere_r[4];
    m.rstd_r = sphere_r[5];
    m.f_r = sphere_r[7];

```

This code is used in section 74.

79.

```

⟨ handle transmission sphere 79 ⟩ ≡
    m.as_t = sphere_t[0];
    m.ae_t = sphere_t[1];
    m.ad_t = sphere_t[2];
    m.rw_t = sphere_t[3];
    m.rd_t = sphere_t[4];
    m.rstd_t = sphere_t[5];
    m.f_t = sphere_t[7];

```

This code is used in section 74.

80. I needed a routine that would calculate the values of M_R and M_T without doing the whole inversion process. It seems odd that this does not exist yet.

The values for the lost light *m.uru_lost* etc., should be calculated before calling this routine.

⟨ Prototype for *Calculate_MR_MT* 80 ⟩ ≡

```

    void Calculate_MR_MT(struct measure_type m, struct invert_type r, int include_MC, double
        *M_R, double *M_T)

```

This code is used in sections 45 and 81.

81. \langle Definition for *Calculate_MR_MT* 81 $\rangle \equiv$
 \langle Prototype for *Calculate_MR_MT* 80 \rangle
 {
 double *distance, ur1, ut1, uru, utu*;
 struct measure_type *old_mm*;
 struct invert_type *old_rr*;
 if (*include_MC* \wedge *m.num_spheres* $>$ 0) *MC_Lost*(*m, r, -2000, &ur1, &ut1, &uru, &utu, &(m.ur1_lost),*
 &(m.ut1_lost), &(m.uru_lost), &(m.utu_lost));
 Get_Calc_State(&*old_mm, &old_rr*);
 Set_Calc_State(*m, r*);
 Calculate_Distance(**M_R**, **M_T**, &*distance*);
 Set_Calc_State(*old_mm, old_rr*);
 }

This code is used in section 44.

82. So, it turns out that the minimum measured **M_R** can be less than four percent for black glass! This is because the sphere efficiency is much worse for the glass than for the white standard.

\langle Prototype for *Calculate_Minimum_MR* 82 $\rangle \equiv$
void *Calculate_Minimum_MR*(**struct measure_type** *m, struct invert_type r, double *mr, double *mt*)

This code is used in sections 45 and 83.

83. \langle Definition for *Calculate_Minimum_MR* 83 $\rangle \equiv$
 \langle Prototype for *Calculate_Minimum_MR* 82 \rangle
 {
 if (*r.default_b* \equiv UNINITIALIZED)
 if (*r.slabs.n_slabs* $>$ 1.0) *r.slabs.b* = HUGE_VAL;
 else *r.slabs.b* = $1 \cdot 10^{-5}$;
 else *r.slabs.b* = *r.default_b*;
 if (*r.default_a* \equiv UNINITIALIZED) *r.slabs.a* = 0;
 else *r.slabs.a* = *r.default_a*;
 if (*r.default_g* \equiv UNINITIALIZED) *r.slabs.g* = 0.0;
 else *r.slabs.g* = *r.default_g*;
 if (*r.search* \equiv FIND_G) *r.slabs.a* = 0;
 r.a = *r.slabs.a*;
 r.b = *r.slabs.b*;
 r.g = *r.slabs.g*;
 Calculate_MR_MT(*m, r, 0, mr, mt*);
 **mt* = 0;
 }

This code is used in section 44.

84. The minimum possible value of MR for a given MT will be when the albedo is zero and the maximum value will be when the albedo is one. In the first case there will be no light loss and in the second we will assume that any light loss is negligible (to maximize MR).

The second case is perhaps over-simplified. Obviously for a fixed thickness as the albedo increases, the reflectance will increase. So how does *U_Find_B()* work when the albedo is set to 1?

The problem is that to calculate these values one must know the optical thickness. Fortunately with the recent addition of constrained minimization, we can do exactly this.

The only thing that remains is to sort out the light lost effect.

⟨Prototype for *MinMax_MR_MT* 84⟩ ≡

```
int MinMax_MR_MT(struct measure_type m, struct invert_type r)
```

This code is used in sections 45 and 85.

85. ⟨Definition for *MinMax_MR_MT* 85⟩ ≡

⟨Prototype for *MinMax_MR_MT* 84⟩

```
{
    double distance, measured_m_r, min_possible_m_r, max_possible_m_r, temp_m_t;
    if (m.m_r < 0) return IAD_MR_TOO_SMALL;
    if (m.m_r * m.rstd_r > 1) return IAD_MR_TOO_BIG;
    if (m.m_t < 0) return IAD_MT_TOO_SMALL;
    if (m.m_t ≡ 0) return IAD_NO_ERROR;
    measured_m_r = m.m_r;
    m.m_r = 0;
    r.search = FIND_B;
    r.default_a = 0;
    U_Find_B(m, &r);
    Calculate_Distance(&min_possible_m_r, &temp_m_t, &distance);
    if (measured_m_r < min_possible_m_r) return IAD_MR_TOO_SMALL;
    r.default_a = 1.0;
    U_Find_B(m, &r);
    Calculate_Distance(&max_possible_m_r, &temp_m_t, &distance);
    if (measured_m_r > max_possible_m_r) return IAD_MR_TOO_BIG;
    return IAD_NO_ERROR;
}
```

This code is used in section 44.

86. ⟨Prototype for *Spheres_Inverse_RT2* 86⟩ ≡

```
void Spheres_Inverse_RT2(double *sample, double *illumination, double *sphere_r, double
    *sphere_t, double *analysis, double *measurement, double *a, double *b, double *g)
```

This code is used in sections 45, 46, and 87.

87. \langle Definition for *Spheres_Inverse_RT2* 87 $\rangle \equiv$
 \langle Prototype for *Spheres_Inverse_RT2* 86 \rangle
{
 struct **measure_type** *m*;
 struct **invert_type** *r*;
 long *num_photons*;
 double *ur1*, *ut1*, *uru*, *utu*;
 int *i*, *mc_runs* = 1;
 Initialize_Measure(&*m*);
 \langle handle2 sample 88 \rangle
 \langle handle2 illumination 89 \rangle
 \langle handle2 reflection sphere 90 \rangle
 \langle handle2 transmission sphere 91 \rangle
 \langle handle2 analysis 92 \rangle
 \langle handle2 measurement 93 \rangle
 Initialize_Result(*m*, &*r*);
 Inverse_RT(*m*, &*r*);
 for (*i* = 0; *i* < *mc_runs*; *i*++) {
 MC_Lost(*m*, *r*, *num_photons*, &*ur1*, &*ut1*, &*uru*, &*utu*, &*m.ur1_lost*, &*m.ut1_lost*, &*m.uru_lost*,
 &*m.utu_lost*);
 Inverse_RT(*m*, &*r*);
 }
 if (*r.error* \equiv IAD_NO_ERROR) {
 a = *r.a*;
 b = *r.b*;
 g = *r.g*;
 }
}

This code is used in section 44.

88. Just move the values from the sample array into the right places

\langle handle2 sample 88 $\rangle \equiv$
 m.slab_index = *sample*[0];
 m.slab_top_slide_index = *sample*[1];
 m.slab_bottom_slide_index = *sample*[2];
 m.slab_thickness = *sample*[3];
 m.slab_top_slide_thickness = *sample*[4];
 m.slab_bottom_slide_thickness = *sample*[5];
 m.slab_top_slide_thickness = 0;
 m.slab_bottom_slide_thickness = 0;

This code is used in section 87.

89. Just move the values from the illumination array into the right places. Need to spend time to figure out how to integrate items 2, 3, and 4

\langle handle2 illumination 89 $\rangle \equiv$
 m.d.beam = *illumination*[0]; /* *m.lambda* = *illumination*[1]; */
 /* *m.specular-reflection-excluded* = *illumination*[2]; */ /* *m.direct-transmission-excluded* =
 illumination[3]; */ /* *m.diffuse-illumination* = *illumination*[4]; */
 m.num_spheres = *illumination*[5];

This code is used in section 87.

90.

```

⟨ handle2 reflection sphere 90 ⟩ ≡
{
    double d_sample_r, d_entrance_r, d_detector_r;
    m.d_sphere_r = sphere_r[0];
    d_sample_r = sphere_r[1];
    d_entrance_r = sphere_r[2];
    d_detector_r = sphere_r[3];
    m.rw_r = sphere_r[4];
    m.rd_r = sphere_r[5];
    m.as_r = (d_sample_r/m.d_sphere_r/2.0) * (d_sample_r/m.d_sphere_r/2.0);
    m.ae_r = (d_entrance_r/m.d_sphere_r/2.0) * (d_entrance_r/m.d_sphere_r/2.0);
    m.ad_r = (d_detector_r/m.d_sphere_r/2.0) * (d_detector_r/m.d_sphere_r/2.0);
    m.aw_r = 1.0 - m.as_r - m.ae_r - m.ad_r;
}

```

This code is used in section 87.

91.

```

⟨ handle2 transmission sphere 91 ⟩ ≡
{
    double d_sample_t, d_entrance_t, d_detector_t;
    m.d_sphere_t = sphere_t[0];
    d_sample_t = sphere_t[1];
    d_entrance_t = sphere_t[2];
    d_detector_t = sphere_t[3];
    m.rw_t = sphere_t[4];
    m.rd_t = sphere_t[5];
    m.as_t = (d_sample_t/m.d_sphere_t/2.0) * (d_sample_t/m.d_sphere_t/2.0);
    m.ae_t = (d_entrance_t/m.d_sphere_t/2.0) * (d_entrance_t/m.d_sphere_t/2.0);
    m.ad_t = (d_detector_t/m.d_sphere_t/2.0) * (d_detector_t/m.d_sphere_t/2.0);
    m.aw_t = 1.0 - m.as_t - m.ae_t - m.ad_t;
}

```

This code is used in section 87.

92.

```

⟨ handle2 analysis 92 ⟩ ≡
    r.method.quad_pts = (int) analysis[0];
    mc_runs = (int) analysis[1];
    num_photons = (long) analysis[2];

```

This code is used in section 87.

93.

```

⟨ handle2 measurement 93 ⟩ ≡
    m.rstd_r = measurement[0];
    m.m_r = measurement[1];
    m.m_t = measurement[2];
    m.m_u = measurement[3];
    m.num_measures = 3;
    if (m.m_t == 0) m.num_measures--;
    if (m.m_u == 0) m.num_measures--;

```

This code is used in section 87.

94. IAD Input Output.

The special define below is to get Visual C to suppress silly warnings.

```

<iad_io.c 94> ≡
#define _CRT_SECURE_NO_WARNINGS
#include <string.h>
#include <stdio.h>
#include <ctype.h>
#include <math.h>
#include "ad_globl.h"
#include "iad_type.h"
#include "iad_io.h"
#include "iad_pub.h"
#include "version.h"
  <Definition for skip_white 104>
  <Definition for read_number 106>
  <Definition for check_magic 108>
  <Definition for Read_Header 98>
  <Definition for Write_Header 110>
  <Definition for Read_Data_Line 102>

```

```

95. <iad_io.h 95> ≡
  <Prototype for Read_Header 97>;
  <Prototype for Write_Header 109>;
  <Prototype for Read_Data_Line 101>;

```

96. Reading the file header.

97. \langle Prototype for *Read_Header* 97 $\rangle \equiv$

```
int Read_Header(FILE *fp, struct measure_type *m, int *params)
```

This code is used in sections 95 and 98.

98. Pretty straightforward stuff. The only thing that needs to be commented on is that only one slide thickness/index is specified in the file. This must be applied to both the top and bottom slides. Finally, to specify no slide, then either setting the slide index to 1.0 or the thickness to 0.0 should do the trick.

\langle Definition for *Read_Header* 98 $\rangle \equiv$

\langle Prototype for *Read_Header* 97 \rangle

```
{
    double x;
    Initialize_Measure(m);
    if (check_magic(fp)) return 1;
    if (read_number(fp, &m->slab_index)) return 1;
    if (read_number(fp, &m->slab_top_slide_index)) return 1;
    if (read_number(fp, &m->slab_thickness)) return 1;
    if (read_number(fp, &m->slab_top_slide_thickness)) return 1;
    if (read_number(fp, &m->d_beam)) return 1;
    if (m->slab_top_slide_thickness  $\equiv$  0.0) m->slab_top_slide_index = 1.0;
    if (m->slab_top_slide_index  $\equiv$  1.0) m->slab_top_slide_thickness = 0.0;
    if (m->slab_top_slide_index  $\equiv$  0.0) {
        m->slab_top_slide_thickness = 0.0;
        m->slab_top_slide_index = 1.0;
    }
    m->slab_bottom_slide_index = m->slab_top_slide_index;
    m->slab_bottom_slide_thickness = m->slab_top_slide_thickness;
    if (read_number(fp, &m->rstd_r)) return 1;
    if (read_number(fp, &x)) return 1;
    m->num_spheres = (int) x;
    m->method = SUBSTITUTION;
     $\langle$ Read coefficients for reflection sphere 99 $\rangle$ 
     $\langle$ Read coefficients for transmission sphere 100 $\rangle$ 
    if (read_number(fp, &x)) return 1;
    *params = (int) x;
    m->num_measures = (*params  $\geq$  3) ? 3 : *params;
    return 0;
}
```

This code is used in section 94.

99. \langle Read coefficients for reflection sphere 99 $\rangle \equiv$

```
{
  double d_sample_r, d_entrance_r, d_detector_r;
  if (read_number(fp, &m-d_sphere_r)) return 1;
  if (read_number(fp, &d_sample_r)) return 1;
  if (read_number(fp, &d_entrance_r)) return 1;
  if (read_number(fp, &d_detector_r)) return 1;
  if (read_number(fp, &m-rw_r)) return 1;
  m-as_r = (d_sample_r/m-d_sphere_r/2.0) * (d_sample_r/m-d_sphere_r/2.0);
  m-ae_r = (d_entrance_r/m-d_sphere_r/2.0) * (d_entrance_r/m-d_sphere_r/2.0);
  m-ad_r = (d_detector_r/m-d_sphere_r/2.0) * (d_detector_r/m-d_sphere_r/2.0);
  m-aw_r = 1.0 - m-as_r - m-ae_r - m-ad_r;
}
```

This code is used in section 98.

100. \langle Read coefficients for transmission sphere 100 $\rangle \equiv$

```
{
  double d_sample_t, d_entrance_t, d_detector_t;
  if (read_number(fp, &m-d_sphere_t)) return 1;
  if (read_number(fp, &d_sample_t)) return 1;
  if (read_number(fp, &d_entrance_t)) return 1;
  if (read_number(fp, &d_detector_t)) return 1;
  if (read_number(fp, &m-rw_t)) return 1;
  m-as_t = (d_sample_t/m-d_sphere_t/2.0) * (d_sample_t/m-d_sphere_t/2.0);
  m-ae_t = (d_entrance_t/m-d_sphere_t/2.0) * (d_entrance_t/m-d_sphere_t/2.0);
  m-ad_t = (d_detector_t/m-d_sphere_t/2.0) * (d_detector_t/m-d_sphere_t/2.0);
  m-aw_t = 1.0 - m-as_t - m-ae_t - m-ad_t;
}
```

This code is used in section 98.

101. Reading just one line of a data file.

This reads a line of data based on the value of *params*.

If the first number is greater than one then it is assumed to be the wavelength and is ignored. test on the first value of the line.

A non-zero value is returned upon a failure.

⟨Prototype for *Read_Data_Line* 101⟩ ≡

```
int Read_Data_Line(FILE *fp, struct measure_type *m, int params)
```

This code is used in sections 95 and 102.

102. ⟨Definition for *Read_Data_Line* 102⟩ ≡

⟨Prototype for *Read_Data_Line* 101⟩

```
{
    if (read_number(fp, &m-m_r)) return 1;
    if (m-m_r > 1) {
        m-lambda = m-m_r;
        if (read_number(fp, &m-m_r)) return 1;
    }
    if (params ≡ -1) {
        m-m_t = m-m_r;
        m-m_r = 0;
        return 0;
    }
    if (params ≡ 1) return 0;
    if (read_number(fp, &m-m_t)) return 1;
    if (params ≡ 2) return 0;
    if (read_number(fp, &m-m_u)) return 1;
    if (params ≡ 3) return 0;
    if (read_number(fp, &m-rw_r)) return 1;
    m-rw_t = m-rw_r;
    if (params ≡ 4) return 0;
    if (read_number(fp, &m-rw_t)) return 1;
    if (params ≡ 5) return 0;
    if (read_number(fp, &m-rstd_r)) return 1;
    if (params ≡ 6) return 0;
    if (read_number(fp, &m-rstd_t)) return 1;
    return 0;
}
```

This code is used in section 94.

103. Skip over white space and comments. It is assumed that # starts all comments and continues to the end of a line. This routine should work on files with nearly any line ending CR, LF, CRLF.

Failure is indicated by a non-zero return value.

⟨Prototype for *skip_white* 103⟩ ≡

```
int skip_white(FILE *fp)
```

This code is used in section 104.

104. \langle Definition for *skip_white* 104 $\rangle \equiv$
 \langle Prototype for *skip_white* 103 \rangle

```

{
    int c = fgetc(fp);
    while (!feof(fp)) {
        if (isspace(c)) c = fgetc(fp);
        else if (c == '#') do c = fgetc(fp); while (!feof(fp) & c != '\n' & c != '\r');
        else break;
    }
    if (feof(fp)) return 1;
    ungetc(c, fp);
    return 0;
}

```

This code is used in section 94.

105. Read a single number. Return 0 if there are no problems, otherwise return 1.

\langle Prototype for *read_number* 105 $\rangle \equiv$

```

int read_number(FILE *fp, double *x)

```

This code is used in section 106.

106. \langle Definition for *read_number* 106 $\rangle \equiv$
 \langle Prototype for *read_number* 105 \rangle

```

{
    if (skip_white(fp)) return 1;
    if (fscanf(fp, "%lf", x)) return 0;
    else return 1;
}

```

This code is used in section 94.

107. Ensure that the data file is actually in the right form. Return 0 if the file has the right starting characters. Return 1 if on a failure.

\langle Prototype for *check_magic* 107 $\rangle \equiv$

```

int check_magic(FILE *fp)

```

This code is used in section 108.

108. \langle Definition for *check_magic* 108 $\rangle \equiv$
 \langle Prototype for *check_magic* 107 \rangle

```

{
    char magic[] = "IAD1";
    int i, c;
    for (i = 0; i < 4; i++) {
        c = fgetc(fp);
        if (feof(fp) || c != magic[i]) {
            fprintf(stderr, "Sorry, but iad_input_files must begin with IAD1\n");
            fprintf(stderr, "as the first four characters of the file.\n");
            fprintf(stderr, "Perhaps you are using an old iad format?\n");
            return 1;
        }
    }
    return 0;
}

```

This code is used in section 94.

109. Formatting the header information.

⟨Prototype for *Write_Header* 109⟩ ≡

```
void Write_Header(struct measure_type m, struct invert_type r, int params)
```

This code is used in sections 95 and 110.

110. ⟨Definition for *Write_Header* 110⟩ ≡

⟨Prototype for *Write_Header* 109⟩

```
{
  ⟨Write slab info 111⟩
  ⟨Write irradiation info 112⟩
  ⟨Write general sphere info 113⟩
  ⟨Write first sphere info 114⟩
  ⟨Write second sphere info 115⟩
  ⟨Write measure and inversion info 116⟩
}
```

This code is used in section 94.

111. ⟨Write slab info 111⟩ ≡

```
double xx;
```

```
printf("#_Inverse_Adding-Doubling_%s_\n", Version);
printf("#_\n");
printf("#_Beam_diameter_=%7.1f_mm\n", m.d_beam);
printf("#_Sample_thickness_=%7.3f_mm\n", m.slab_thickness);
printf("#_Top_slide_thickness_=%7.3f_mm\n", m.slab_top_slide_thickness);
printf("#_Bottom_slide_thickness_=%7.3f_mm\n", m.slab_bottom_slide_thickness);
printf("#_Sample_index_of_refraction_=%7.4f\n", m.slab_index);
printf("#_Top_slide_index_of_refraction_=%7.4f\n", m.slab_top_slide_index);
printf("#_Bottom_slide_index_of_refraction_=%7.4f\n", m.slab_bottom_slide_index);
```

This code is used in section 110.

112. ⟨Write irradiation info 112⟩ ≡

```
printf("#_\n");
```

This code is used in section 110.

113. ⟨Write general sphere info 113⟩ ≡

```
printf("#_Fraction_unscattered_refl._in_M_R_=%7.1f%%\n", m.fraction_of_rc_in_mr * 100);
printf("#_Fraction_unscattered_trans._in_M_T_=%7.1f%%\n", m.fraction_of_tc_in_mt * 100);
printf("#_\n");
```

This code is used in section 110.

114. ⟨Write first sphere info 114⟩ ≡

```
printf("#_Reflection_sphere\n");
printf("#_sphere_diameter_=%7.1f_mm\n", m.d_sphere_r);
printf("#_sample_port_diameter_=%7.1f_mm\n", 2 * m.d_sphere_r * sqrt(m.as_r));
printf("#_entrance_port_diameter_=%7.1f_mm\n", 2 * m.d_sphere_r * sqrt(m.ae_r));
printf("#_detector_port_diameter_=%7.1f_mm\n", 2 * m.d_sphere_r * sqrt(m.ad_r));
printf("#_wall_reflectance_=%7.1f%%\n", m.rw_r * 100);
printf("#_standard_reflectance_=%7.1f%%\n", m.rstd_r * 100);
printf("#_detector_reflectance_=%7.1f%%\n", m.rd_r * 100);
printf("#_\n");
```

This code is used in section 110.

115. \langle Write second sphere info 115 $\rangle \equiv$

```
printf("#_Transmission_sphere\n");
printf("#_sphere_diameter=_%7.1f_mm\n", m.d_sphere_t);
printf("#_sample_port_diameter=_%7.1f_mm\n", 2 * m.d_sphere_r * sqrt(m.as_t));
printf("#_entrance_port_diameter=_%7.1f_mm\n", 2 * m.d_sphere_r * sqrt(m.ae_t));
printf("#_detector_port_diameter=_%7.1f_mm\n", 2 * m.d_sphere_r * sqrt(m.ad_t));
printf("#_wall_reflectance=_%7.1f_%\n", m.rw_t * 100);
printf("#_standard_transmittance=_%7.1f_%\n", m.rstd_t * 100);
printf("#_detector_reflectance=_%7.1f_%\n", m.rd_t * 100);
```

This code is used in section 110.

```

116.  < Write measure and inversion info 116 > ≡
    printf("#\n");
    switch (params) {
    case -1: printf("#_No_M_R_or_M_T--_forward_calculation.\n");
        break;
    case 1: printf("#_Just_M_R_was_measured");
        break;
    case 2: printf("#_M_R_and_M_T_were_measured");
        break;
    case 3: printf("#_M_R,_M_T,_and_M_U_were_measured");
        break;
    case 4: printf("#_M_R,_M_T,_M_U,_and_r_w_were_measured");
        break;
    case 5: printf("#_M_R,_M_T,_M_U,_r_w,_and_t_w_were_measured");
        break;
    case 6: printf("#_M_R,_M_T,_M_U,_r_w,_t_w,_and_r_std_were_measured");
        break;
    case 7: printf("#_M_R,_M_T,_M_U,_r_w,_t_w,_r_std_and_t_std_were_measured");
        break;
    default: printf("#_Something_went_wrong..._measures_should_be_1_to_5!\n");
        break;
    }
    if (1 ≤ params ∧ params ≤ 7) {
        if (m.flip_sample) printf("_sample_flipped");
        switch (m.method) {
        case UNKNOWN: printf("_using_an_unknown_method.\n");
            break;
        case SUBSTITUTION: printf("_using_the_substitution_(single-beam)_method.\n");
            break;
        case COMPARISON: printf("_using_the_comparison_(dual-beam)_method.\n");
        }
    }
    switch (m.num_spheres) {
    case 0: printf("#_No_sphere_corrections_were_used");
        break;
    case 1:
        if (m.method ≡ COMPARISON) printf("#_No_sphere_corrections_were_needed");
        else printf("#_Single_sphere_corrections_were_used");
        break;
    case 2: printf("#_Double_sphere_corrections_were_used");
        break;
    }
    printf("_and_light_was_incident_at_%d_degrees_from_the_normal",
        (int)(acos(m.slab_cos_angle) * 57.2958));
    printf(".\n");
    switch (r.search) {
    case FIND_AB: printf("#_The_inverse_routine_varied_the_albedo_and_optical_depth.\n");
        printf("#\n");
        xx = (r.default_g ≠ UNINITIALIZED) ? r.default_g : 0;
        printf("#_Default_single_scattering_anisotropy_=%7.3f\n", xx);
        break;
    case FIND_AG: printf("#_The_inverse_routine_varied_the_albedo_and_anisotropy.\n");

```

```

    printf("#_\n");
    if (r.default_b ≠ UNINITIALIZED)
        printf("#_Default_(mu_t*d)=_%7.3g\n", r.default_b);
    else printf("#_\n");
    break;
case FIND_AUTO: printf("#_The_inverse_routine_adapted_to_the_input_data.\n");
    printf("#_\n");
    printf("#_\n");
    break;
case FIND_A: printf("#_The_inverse_routine_varied_only_the_albedo.\n");
    printf("#_\n");
    xx = (r.default_g ≠ UNINITIALIZED) ? r.default_g : 0;
    printf("#_Default_single_scattering_anisotropy_is_%7.3f", xx);
    xx = (r.default_b ≠ UNINITIALIZED) ? r.default_b : HUGE_VAL;
    printf("_and_(mu_t*d)=_%7.3g\n", xx);
    break;
case FIND_B: printf("#_The_inverse_routine_varied_only_the_optical_depth.\n");
    printf("#_\n");
    xx = (r.default_g ≠ UNINITIALIZED) ? r.default_g : 0;
    printf("#_Default_single_scattering_anisotropy_is_%7.3f", xx);
    if (r.default_a ≠ UNINITIALIZED) printf("and_default_albedo=_%7.3g\n", r.default_a);
    else printf("\n");
    break;
case FIND_Ba: printf("#_The_inverse_routine_varied_only_the_absorption.\n");
    printf("#_\n");
    xx = (r.default_bs ≠ UNINITIALIZED) ? r.default_bs : 0;
    printf("#_Default_(mu_s*d)=_%7.3g\n", xx);
    break;
case FIND_Bs: printf("#_The_inverse_routine_varied_only_the_scattering.\n");
    printf("#_\n");
    xx = (r.default_ba ≠ UNINITIALIZED) ? r.default_ba : 0;
    printf("#_Default_(mu_a*d)=_%7.3g\n", xx);
    break;
default: printf("#_\n");
    printf("#_\n");
    printf("#_\n");
    break;
}
printf("#_AD_quadrature_points=_%3d\n", r.method.quad_pts);
printf("#_AD_tolerance_for_success=_%9.5f\n", r.tolerance);
printf("#_MC_tolerance_for_mu_a_and_mu_s' =_%7.3f%%\n", r.MC_tolerance);

```

This code is used in section 110.

117. IAD Calculation.

```

<iad_calc.c 117> ≡
#include <math.h>
#include <string.h>
#include <stdio.h>
#include <stdlib.h>
#include "nr_util.h"
#include "nr_zbrent.h"
#include "ad_globl.h"
#include "ad_frsnl.h"
#include "ad_prime.h"
#include "iad_type.h"
#include "iad_util.h"
#include "iad_calc.h"
#define ABIT 1·10-6
#define A_COLUMN 1
#define B_COLUMN 2
#define G_COLUMN 3
#define URU_COLUMN 4
#define UTU_COLUMN 5
#define UR1_COLUMN 6
#define UT1_COLUMN 7
#define REFLECTION_SPHERE 1
#define TRANSMISSION_SPHERE 0
#define GRID_SIZE 101
#define T_TRUST_FACTOR 1
static int CALCULATING_GRID = 1;
static struct measure_type MM;
static struct invert_type RR;
static struct measure_type MGRID;
static struct invert_type RGRID;
static double **The_Grid = Λ;
static double GG_a;
static double GG_b;
static double GG_g;
static double GG_bs;
static double GG_ba;
static boolean_type The_Grid_Initialized = FALSE;
static boolean_type The_Grid_Search = -1;

<Definition for Set_Calc_State 133>
<Definition for Get_Calc_State 135>
<Definition for Same_Calc_State 137>
<Prototype for Fill_AB_Grid 155>;
<Prototype for Fill_AG_Grid 160>;
<Definition for RT_Flip 153>
<Definition for Allocate_Grid 139>
<Definition for Valid_Grid 143>
<Definition for fill_grid_entry 154>
<Definition for Fill_Grid 170>
<Definition for Near_Grid_Points 151>
<Definition for Fill_AB_Grid 156>
<Definition for Fill_AG_Grid 161>

```

- ⟨ Definition for *Fill_BG_Grid* 164 ⟩
- ⟨ Definition for *Fill_BaG_Grid* 166 ⟩
- ⟨ Definition for *Fill_BsG_Grid* 168 ⟩
- ⟨ Definition for *Grid_ABG* 141 ⟩
- ⟨ Definition for *Gain* 122 ⟩
- ⟨ Definition for *Gain_11* 124 ⟩
- ⟨ Definition for *Gain_22* 126 ⟩
- ⟨ Definition for *Two_Sphere_R* 128 ⟩
- ⟨ Definition for *Two_Sphere_T* 130 ⟩
- ⟨ Definition for *Calculate_Distance_With_Corrections* 176 ⟩
- ⟨ Definition for *Calculate_Grid_Distance* 174 ⟩
- ⟨ Definition for *Calculate_Distance* 172 ⟩
- ⟨ Definition for *abg_distance* 149 ⟩
- ⟨ Definition for *Find_AG_fn* 186 ⟩
- ⟨ Definition for *Find_AB_fn* 188 ⟩
- ⟨ Definition for *Find_Ba_fn* 190 ⟩
- ⟨ Definition for *Find_Bs_fn* 192 ⟩
- ⟨ Definition for *Find_A_fn* 194 ⟩
- ⟨ Definition for *Find_B_fn* 196 ⟩
- ⟨ Definition for *Find_G_fn* 198 ⟩
- ⟨ Definition for *Find_BG_fn* 200 ⟩
- ⟨ Definition for *Find_BaG_fn* 202 ⟩
- ⟨ Definition for *Find_BsG_fn* 204 ⟩
- ⟨ Definition for *maxloss* 206 ⟩
- ⟨ Definition for *Max_Light_Loss* 208 ⟩

118.

```

< iad_calc.h 118 > ≡
  < Prototype for Gain 121 >;
  < Prototype for Gain_11 123 >;
  < Prototype for Gain_22 125 >;
  < Prototype for Two_Sphere_R 127 >;
  < Prototype for Two_Sphere_T 129 >;
  < Prototype for Set_Calc_State 132 >;
  < Prototype for Get_Calc_State 134 >;
  < Prototype for Same_Calc_State 136 >;
  < Prototype for Valid_Grid 142 >;
  < Prototype for Allocate_Grid 138 >;
  < Prototype for Fill_Grid 169 >;
  < Prototype for Near_Grid_Points 150 >;
  < Prototype for Grid_ABG 140 >;
  < Prototype for Find_AG_fn 185 >;
  < Prototype for Find_AB_fn 187 >;
  < Prototype for Find_Ba_fn 189 >;
  < Prototype for Find_Bs_fn 191 >;
  < Prototype for Find_A_fn 193 >;
  < Prototype for Find_B_fn 195 >;
  < Prototype for Find_G_fn 197 >;
  < Prototype for Find_BG_fn 199 >;
  < Prototype for Find_BsG_fn 203 >;
  < Prototype for Find_BaG_fn 201 >;
  < Prototype for Fill_BG_Grid 163 >;
  < Prototype for Fill_BsG_Grid 167 >;
  < Prototype for Fill_BaG_Grid 165 >;
  < Prototype for Calculate_Distance_With_Corrections 175 >;
  < Prototype for Calculate_Distance 171 >;
  < Prototype for Calculate_Grid_Distance 173 >;
  < Prototype for abg_distance 148 >;
  < Prototype for maxloss 205 >;
  < Prototype for Max_Light_Loss 207 >;

```

119. Initialization.

The functions in this file assume that the local variables **MM** and **RR** have been initialized appropriately. The variable **MM** contains all the information about how a particular experiment was done. The structure **RR** contains the data structure that is passed to the adding-doubling routines as well as the number of quadrature points.

history 6/8/94 changed error output to *stderr*.

120. Gain.

Assume that a sphere is illuminated with diffuse light having a power P . This light can reach all parts of sphere — specifically, light from this source is not blocked by a baffle. Multiple reflections in the sphere will increase the power falling on non-white areas in the sphere (e.g., the sample, detector, and entrance) To find the total we need to sum all the total of all incident light at a point. The first incidence is

$$P_w^{(1)} = a_w P, \quad P_s^{(1)} = a_s P, \quad P_d^{(1)} = a_d P$$

The light from the detector and sample is multiplied by $(1 - a_e)$ and not by a_w because the light from the detector (and sample) is not allowed to hit either the detector or sample. The second incidence on the wall is

$$P_w^{(2)} = a_w r_w P_w^{(1)} + (1 - a_e) r_d P_d^{(1)} + (1 - a_e) r_s P_s^{(1)}$$

The light that hits the walls after k bounces has the same form as above

$$P_w^{(k)} = a_w r_w P_w^{(k-1)} + (1 - a_e) r_d P_d^{(k-1)} + (1 - a_e) r_s P_s^{(k-1)}$$

Since the light falling on the sample and detector must come from the wall

$$P_s^{(k)} = a_s r_w P_w^{(k-1)} \quad \text{and} \quad P_d^{(k)} = a_d r_w P_w^{(k-1)},$$

Therefore,

$$P_w^{(k)} = a_w r_w P_w^{(k-1)} + (1 - a_e) r_w (a_d r_d + a_s r_s) P_w^{(k-2)}$$

The total power falling on the walls is just

$$P_w = \sum_{k=1}^{\infty} P_w^{(k)} = \frac{a_w + (1 - a_e)(a_d r_d + a_s r_s)}{1 - a_w r_w - (1 - a_e) r_w (a_d r_d + a_s r_s)} P$$

The total power falling the detector is

$$P_d = a_d P + \sum_{k=2}^{\infty} a_d r_w P_w^{(k-1)} = a_d P + a_d r_w P_w$$

The gain $G(r_s)$ on the irradiance on the detector (relative to a black sphere),

$$G(r_s) \equiv \frac{P_d/A_d}{P/A}$$

in terms of the sphere parameters

$$G(r_s) = 1 + \frac{1}{a_w} \cdot \frac{a_w r_w + (1 - a_e) r_w (a_d r_d + a_s r_s)}{1 - a_w r_w - (1 - a_e) r_w (a_d r_d + a_s r_s)}$$

The gain for a detector in a transmission sphere is similar, but with primed parameters to designate a second potential sphere that is used. For a black sphere the gain $G(0) = 1$, which is easily verified by setting $r_w = 0$, $r_s = 0$, and $r_d = 0$. Conversely, when the sphere walls and sample are perfectly white, the irradiance at the entrance port, the sample port, and the detector port must increase so that the total power leaving via these ports is equal to the incident diffuse power P . Thus the gain should be the ratio of the sphere wall area over the area of the ports through which light leaves or $G(1) = A/(A_e + A_d)$ which follows immediately from the gain formula with $r_w = 1$, $r_s = 1$, and $r_d = 0$.

121. The gain $G(r_s)$ on the irradiance on the detector (relative to a black sphere),

$$G(r_s) \equiv \frac{P_d/A_d}{P/A}$$

in terms of the sphere parameters

$$G(r_s) = 1 + \frac{a_w r_w + (1 - a_e) r_w (a_d r_d + a_s r_s)}{1 - a_w r_w - (1 - a_e) r_w (a_d r_d + a_s r_s)}$$

⟨Prototype for *Gain* 121⟩ ≡

double *Gain*(**int** *sphere*, **struct** *measure_type* *m*, **double** URU)

This code is used in sections 118 and 122.

122. ⟨Definition for *Gain* 122⟩ ≡

⟨Prototype for *Gain* 121⟩

```
{
  double G, tmp;
  if (sphere == REFLECTION_SPHERE) {
    tmp = m.rw_r * (m.aw_r + (1 - m.ae_r) * (m.ad_r * m.rd_r + m.as_r * URU));
    if (tmp == 1.0) G = 1;
    else G = 1.0 + tmp / (1.0 - tmp);
  }
  else {
    tmp = m.rw_t * (m.aw_t + (1 - m.ae_t) * (m.ad_t * m.rd_t + m.as_t * URU));
    if (tmp == 1.0) G = 1;
    else G = 1.0 + tmp / (1.0 - tmp);
  }
  return G;
}
```

This code is used in section 117.

123. The gain for light on the detector in the first sphere for diffuse light starting in that same sphere is defined as

$$G_{1 \rightarrow 1}(r_s, t_s) \equiv \frac{P_{1 \rightarrow 1}(r_s, t_s)/A_d}{P/A}$$

then the full expression for the gain is

$$G_{1 \rightarrow 1}(r_s, t_s) = \frac{G(r_s)}{1 - a_s a'_s r_w r'_w (1 - a_e)(1 - a'_e) G(r_s) G'(r_s) t_s^2}$$

⟨Prototype for *Gain_11* 123⟩ ≡

double *Gain_11*(**struct** *measure_type* *m*, **double** URU, **double** *tdiffuse*)

This code is used in sections 118 and 124.

124. $\langle \text{Definition for } \textit{Gain_11} \text{ 124} \rangle \equiv$

$\langle \text{Prototype for } \textit{Gain_11} \text{ 123} \rangle$

```
{
  double G, GP, G11;
  G = Gain(REFLECTION_SPHERE, m, URU);
  GP = Gain(TRANSMISSION_SPHERE, m, URU);
  G11 = G/(1-m.as_r*m.as_t*m.aw_r*m.aw_t*(1-m.ae_r)*(1-m.ae_t)*G*GP*tdiffuse*tdiffuse);
  return G11;
}
```

This code is used in section 117.

125. Similarly, when the light starts in the second sphere, the gain for light on the detector in the second sphere $G_{2 \rightarrow 2}$ is found by switching all primed variables to unprimed. Thus $G_{2 \rightarrow 1}(r_s, t_s)$ is

$$G_{2 \rightarrow 2}(r_s, t_s) = \frac{G'(r_s)}{1 - a_s a'_s r_w r'_w (1 - a_e)(1 - a'_e) G(r_s) G'(r_s) t_s^2}$$

$\langle \text{Prototype for } \textit{Gain_22} \text{ 125} \rangle \equiv$

double *Gain_22*(**struct measure_type** m, **double** URU, **double** *tdiffuse*)

This code is used in sections 118 and 126.

126. $\langle \text{Definition for } \textit{Gain_22} \text{ 126} \rangle \equiv$

$\langle \text{Prototype for } \textit{Gain_22} \text{ 125} \rangle$

```
{
  double G, GP, G22;
  G = Gain(REFLECTION_SPHERE, m, URU);
  GP = Gain(TRANSMISSION_SPHERE, m, URU);
  G22 = GP/(1-m.as_r*m.as_t*m.aw_r*m.aw_t*(1-m.ae_r)*(1-m.ae_t)*G*GP*tdiffuse*tdiffuse);
  return G22;
}
```

This code is used in section 117.

127. The reflected power for two spheres makes use of the formulas for *Gain_11* above.

The light on the detector in the reflection (first) sphere arises from three sources: the fraction of light directly reflected off the sphere wall $f r_w^2 (1 - a_e) P$, the fraction of light reflected by the sample $(1 - f) r_s^{\text{direct}} r_w^2 (1 - a_e) P$, and the light transmitted through the sample $(1 - f) t_s^{\text{direct}} r'_w (1 - a'_e) P$,

$$\begin{aligned} R(r_s^{\text{direct}}, r_s, t_s^{\text{direct}}, t_s) &= G_{1 \rightarrow 1}(r_s, t_s) \cdot a_d (1 - a_e) r_w^2 f P \\ &\quad + G_{1 \rightarrow 1}(r_s, t_s) \cdot a_d (1 - a_e) r_w (1 - f) r_s^{\text{direct}} P \\ &\quad + G_{2 \rightarrow 1}(r_s, t_s) \cdot a_d (1 - a'_e) r'_w (1 - f) t_s^{\text{direct}} P \end{aligned}$$

which simplifies slightly to

$$\begin{aligned} R(r_s^{\text{direct}}, r_s, t_s^{\text{direct}}, t_s) &= a_d (1 - a_e) r_w P \cdot G_{1 \rightarrow 1}(r_s, t_s) \\ &\quad \times \left[(1 - f) r_s^{\text{direct}} + f r_w + (1 - f) a'_s (1 - a'_e) r'_w t_s^{\text{direct}} t_s G'(r_s) \right] \end{aligned}$$

$\langle \text{Prototype for } \textit{Two_Sphere_R} \text{ 127} \rangle \equiv$

double *Two_Sphere_R*(**struct measure_type** m, **double** UR1, **double** URU, **double** UT1, **double** UTU)

This code is used in sections 118 and 128.

128. $\langle \text{Definition for } Two_Sphere_R \text{ 128} \rangle \equiv$

$\langle \text{Prototype for } Two_Sphere_R \text{ 127} \rangle$

```
{
  double x, GP;
  GP = Gain(TRANSMISSION_SPHERE, m, URU);
  x = m.ad_r * (1 - m.ae_r) * m.rw_r * Gain_11(m, URU, UTU);
  x *= (1 - m.f_r) * UR1 + m.rw_r * m.f_r + (1 - m.f_r) * m.as_t * (1 - m.ae_t) * m.rw_t * UT1 * UTU * GP;
  return x;
}
```

This code is used in section 117.

129. For the power on the detector in the transmission (second) sphere we have the same three sources. The only difference is that the subscripts on the gain terms now indicate that the light ends up in the second sphere

$$\begin{aligned} T(r_s^{\text{direct}}, r_s, t_s^{\text{direct}}, t_s) &= G_{1 \rightarrow 2}(r_s, t_s) \cdot a'_d(1 - a_e)r_w^2 f P \\ &\quad + G_{1 \rightarrow 2}(r_s, t_s) \cdot a'_d(1 - a_e)r_w(1 - f)r_s^{\text{direct}} P \\ &\quad + G_{2 \rightarrow 2}(r_s, t_s) \cdot a'_d(1 - a'_e)r'_w(1 - f)t_s^{\text{direct}} P \end{aligned}$$

or

$$\begin{aligned} T(r_s^{\text{direct}}, r_s, t_s^{\text{direct}}, t_s) &= a'_d(1 - a'_e)r'_w P \cdot G_{2 \rightarrow 2}(r_s, t_s) \\ &\quad \times \left[(1 - f)t_s^{\text{direct}} + (1 - a_e)r_w a_s t_s (f r_w + (1 - f)r_s^{\text{direct}}) G(r_s) \right] \end{aligned}$$

$\langle \text{Prototype for } Two_Sphere_T \text{ 129} \rangle \equiv$

double *Two_Sphere_T*(**struct** *measure_type* *m*, **double** UR1, **double** URU, **double** UT1, **double** UTU)

This code is used in sections 118 and 130.

130. $\langle \text{Definition for } Two_Sphere_T \text{ 130} \rangle \equiv$

$\langle \text{Prototype for } Two_Sphere_T \text{ 129} \rangle$

```
{
  double x, G;
  G = Gain(REFLECTION_SPHERE, m, URU);
  x = m.ad_t * (1 - m.ae_t) * m.rw_t * Gain_22(m, URU, UTU);
  x *= (1 - m.f_r) * UT1 + (1 - m.ae_r) * m.rw_r * m.as_r * UTU * (m.f_r * m.rw_r + (1 - m.f_r) * UR1) * G;
  return x;
}
```

This code is used in section 117.

131. Grid Routines. There is a long story associated with these routines. I spent a lot of time trying to find an empirical function to allow a guess at a starting value for the inversion routine. Basically nothing worked very well. There were too many special cases and what not. So I decided to calculate a whole bunch of reflection and transmission values and keep their associated optical properties linked nearby.

I did the very simplest thing. I just allocate a matrix that is five columns wide. Then I fill every row with a calculated set of optical properties and observables. The distribution of values that I use could certainly use some work, but they currently work.

SO... how does this thing work anyway? There are two possible grids one for calculations requiring the program to find the albedo and the optical depth (a and b) and one to find the albedo and anisotropy (a and g). These grids must be allocated and initialized before use.

132. This is a pretty important routine that should have some explanation. The reason that it exists, is that we need some ‘out-of-band’ information during the minimization process. Since the light transport calculation depends on all sorts of stuff (e.g., the sphere parameters) and the minimization routines just vary one or two parameters this information needs to be put somewhere.

I chose the global variables MM and RR to save things in.

The bottom line is that you cannot do a light transport calculation without calling this routine first.

⟨Prototype for *Set_Calc_State* 132⟩ ≡

```
void Set_Calc_State(struct measure_type m, struct invert_type r)
```

This code is used in sections 118 and 133.

133. ⟨Definition for *Set_Calc_State* 133⟩ ≡

⟨Prototype for *Set_Calc_State* 132⟩

```
{
    memcpy(&MM, &m, sizeof(struct measure_type));
    memcpy(&RR, &r, sizeof(struct invert_type));
    if (Debug(DEBUG_ITERATIONS) ^ !CALCULATING_GRID) {
        fprintf(stderr, "MC Loss (UR1=%7.5f, UT1=%7.5f, ", m.ur1_lost, m.ut1_lost);
        fprintf(stderr, "URU=%7.5f, UTU=%7.5f)\n", m.uru_lost, m.utu_lost);
    }
}
```

This code is used in section 117.

134. The inverse of the previous routine. Note that you must have space for the parameters m and r already allocated.

⟨Prototype for *Get_Calc_State* 134⟩ ≡

```
void Get_Calc_State(struct measure_type *m, struct invert_type *r)
```

This code is used in sections 118 and 135.

135. ⟨Definition for *Get_Calc_State* 135⟩ ≡

⟨Prototype for *Get_Calc_State* 134⟩

```
{
    memcpy(m, &MM, sizeof(struct measure_type));
    memcpy(r, &RR, sizeof(struct invert_type));
}
```

This code is used in section 117.

136. The inverse of the previous routine. Note that you must have space for the parameters m and r already allocated.

⟨Prototype for *Same_Calc_State* 136⟩ ≡

boolean_type *Same_Calc_State*(**struct** *measure_type* m , **struct** *invert_type* r)

This code is used in sections 118 and 137.

137. ⟨Definition for *Same_Calc_State* 137⟩ ≡

⟨Prototype for *Same_Calc_State* 136⟩

```
{
    if (The_Grid ≡  $\Lambda$ ) return FALSE;
    if ( $\neg$ The_Grid_Initialized) return FALSE;
    if (r.search ≠ RR.search) return FALSE;
    if (r.method.quad_pts ≠ RR.method.quad_pts) return FALSE;
    if (r.slab.a ≠ RR.slab.a) return FALSE;
    if (r.slab.b ≠ RR.slab.b) return FALSE;
    if (r.slab.g ≠ RR.slab.g) return FALSE;
    if (r.slab.phase_function ≠ RR.slab.phase_function) return FALSE;
    if (r.slab.n_slab ≠ RR.slab.n_slab) return FALSE;
    if (r.slab.n_top_slide ≠ RR.slab.n_top_slide) return FALSE;
    if (r.slab.n_bottom_slide ≠ RR.slab.n_bottom_slide) return FALSE;
    if (r.slab.b_top_slide ≠ RR.slab.b_top_slide) return FALSE;
    if (r.slab.b_bottom_slide ≠ RR.slab.b_bottom_slide) return FALSE;
    if (r.slab.cos_angle ≠ RR.slab.cos_angle) return FALSE;
    if (m.num_measures ≡ 3) ∧ (m.m_u ≠ MGRID.m_u) return (FALSE);
    return TRUE;
}
```

This code is used in section 117.

138. ⟨Prototype for *Allocate_Grid* 138⟩ ≡

void *Allocate_Grid*(**search_type** s)

This code is used in sections 118 and 139.

139. ⟨Definition for *Allocate_Grid* 139⟩ ≡

⟨Prototype for *Allocate_Grid* 138⟩

```
{
    (void)  $s$ ;
    The_Grid = dmatrix(0, GRID_SIZE * GRID_SIZE, 1, 7);
    if (The_Grid ≡  $\Lambda$ ) AD_error("unable to allocate the grid matrix");
    The_Grid_Initialized = FALSE;
}
```

This code is used in section 117.

140. This routine will return the a , b , and g values for a particular row in the grid.

⟨Prototype for *Grid_ABG* 140⟩ ≡

void *Grid_ABG*(**int** i , **int** j , **guess_type** $*guess$)

This code is used in sections 118 and 141.

141. $\langle \text{Definition for } Grid_ABG \text{ 141} \rangle \equiv$
 $\langle \text{Prototype for } Grid_ABG \text{ 140} \rangle$

```

{
  if (0 ≤ i ∧ i < GRID_SIZE ∧ 0 ≤ j ∧ j < GRID_SIZE) {
    guess-a = The_Grid[GRID_SIZE * i + j][A_COLUMN];
    guess-b = The_Grid[GRID_SIZE * i + j][B_COLUMN];
    guess-g = The_Grid[GRID_SIZE * i + j][G_COLUMN];
    guess-distance = Calculate_Grid_Distance(i, j);
  }
  else {
    guess-a = 0.5;
    guess-b = 0.5;
    guess-g = 0.5;
    guess-distance = 999;
  }
}

```

This code is used in section 117.

142. This routine is used to figure out if the current grid is valid. This can fail for several reasons. First the grid may not have been allocated. Or it may not have been initialized. The boundary conditions may have changed. The number or values of the sphere parameters may have changed. It is tedious, but straightforward to check these cases out.

If this routine returns true, then it is a pretty good bet that the values in the current grid can be used to guess the next starting set of values.

$\langle \text{Prototype for } Valid_Grid \text{ 142} \rangle \equiv$
boolean_type *Valid_Grid*(**struct measure_type** *m*, **search_type** *s*)

This code is used in sections 118 and 143.

143. $\langle \text{Definition for } Valid_Grid \text{ 143} \rangle \equiv$
 $\langle \text{Prototype for } Valid_Grid \text{ 142} \rangle$

```

{
   $\langle \text{Tests for invalid grid 144} \rangle$ 
  return (TRUE);
}

```

This code is used in section 117.

144. First check are to test if the grid has ever been filled

$\langle \text{Tests for invalid grid 144} \rangle \equiv$

```

if (The_Grid ≡ Λ) {
  if (Debug(DEBUG_GRID)) fprintf(stderr, "GRID: Fill because NULL\n");
  return (FALSE);
}
if (¬The_Grid_Initialized) {
  if (Debug(DEBUG_GRID)) fprintf(stderr, "GRID: Fill because not initialized\n");
  return (FALSE);
}

```

See also sections 145, 146, and 147.

This code is used in section 143.

145. If the type of search has changed then report the grid as invalid

⟨ Tests for invalid grid 144 ⟩ +≡

```

if (The_Grid_Search ≠ s) {
    if (Debug(DEBUG_GRID)) fprintf(stderr, "GRID: Fill because search type changed\n");
    return (FALSE);
}

```

146. Compare the *m.m_u* value only if there are three measurements

⟨ Tests for invalid grid 144 ⟩ +≡

```

if ((m.num_measures ≡ 3) ∧ (m.m_u ≠ MGRID.m_u)) {
    if (Debug(DEBUG_GRID)) fprintf(stderr, "GRID: Fill because unscattered light changed\n");
    return (FALSE);
}

```

147. Make sure that the boundary conditions have not changed.

⟨ Tests for invalid grid 144 ⟩ +≡

```

if (m.slab_index ≠ MGRID.slab_index) {
    if (Debug(DEBUG_GRID))
        fprintf(stderr, "GRID: Fill because slab refractive index changed\n");
    return (FALSE);
}
if (m.slab_cos_angle ≠ MGRID.slab_cos_angle) {
    if (Debug(DEBUG_GRID)) fprintf(stderr, "GRID: Fill because light angle changed\n");
    return (FALSE);
}
if (m.slab_top_slide_index ≠ MGRID.slab_top_slide_index) {
    if (Debug(DEBUG_GRID)) fprintf(stderr, "GRID: Fill because top slide index changed\n");
    return (FALSE);
}
if (m.slab_bottom_slide_index ≠ MGRID.slab_bottom_slide_index) {
    if (Debug(DEBUG_GRID)) fprintf(stderr, "GRID: Fill because bottom slide index changed\n");
    return (FALSE);
}

```

148. Routine to just figure out the distance to a particular a, b, g point

⟨ Prototype for *abg_distance* 148 ⟩ ≡

```

void abg_distance(double a, double b, double g, guess_type *guess)

```

This code is used in sections 118 and 149.

149. \langle Definition for *abg_distance* 149 $\rangle \equiv$
 \langle Prototype for *abg_distance* 148 \rangle
{
 double *m_r, m_t, distance*;
 struct measure_type *old_mm*;
 struct invert_type *old_rr*;
 Get_Calc_State(&*old_mm*, &*old_rr*);
 RR.slab.a = *a*;
 RR.slab.b = *b*;
 RR.slab.g = *g*;
 Calculate_Distance(&*m_r*, &*m_t*, &*distance*);
 Set_Calc_State(*old_mm*, *old_rr*);
 guess-a = *a*;
 guess-b = *b*;
 guess-g = *g*;
 guess-distance = *distance*;
}

This code is used in section 117.

150. This just searches through the grid to find the minimum entry and returns the optical properties of that entry. The smallest, the next smallest, and the third smallest values are returned.

This has been rewritten to use *Calculate_Distance_With_Corrections* so that changes in sphere parameters won't necessitate recalculating the grid.

\langle Prototype for *Near_Grid_Points* 150 $\rangle \equiv$
void *Near_Grid_Points*(**double** *r*, **double** *t*, **search_type** *s*, **int** **i_min*, **int** **j_min*)

This code is used in sections 118 and 151.

151. \langle Definition for *Near_Grid_Points* 151 $\rangle \equiv$
 \langle Prototype for *Near_Grid_Points* 150 \rangle

```

{
  int i, j;
  double fval;
  double smallest = 10.0;
  struct measure_type old_mm;
  struct invert_type old_rr;

  (void) r;
  (void) t;
  (void) s;
  Get_Calc_State(&old_mm, &old_rr);
  *i_min = 0;
  *j_min = 0;
  for (i = 0; i < GRID_SIZE; i++) {
    for (j = 0; j < GRID_SIZE; j++) {
      CALCULATING_GRID = 1;
      fval = Calculate_Grid_Distance(i, j);
      CALCULATING_GRID = 0;
      if (fval < smallest) {
        *i_min = i;
        *j_min = j;
        smallest = fval;
      }
    }
  }
  Set_Calc_State(old_mm, old_rr);
}

```

This code is used in section 117.

152. Routine to incorporate flipping of sample if needed. This is pretty simple. The assumption is that flipping is handled relative to the reflection side of the sphere. Thus even when flipping is needed, the usual call to `RT()` will result in the correct values for the reflectances. The transmission values can then be calculated by swapping the top and bottom slides.

Technically, the value of `slab` should be `const` but it is not so that we don't pay a copying overhead whenever `flip` is false (the usual case).

\langle Prototype for *RT_Flip* 152 $\rangle \equiv$

```

void RT_Flip(int flip, int n, struct AD_slab_type *slab, double *UR1, double *UT1, double
             *URU, double *UTU)

```

This code is used in section 153.

153. $\langle \text{Definition for } RT_Flip \text{ 153} \rangle \equiv$
 $\langle \text{Prototype for } RT_Flip \text{ 152} \rangle$
 $\{$
 double *swap*, *correct_UR1*, *correct_URU*;
 RT(*n*, *slab*, UR1, UT1, URU, UTU);
 if (*flip*) $\{$
 correct_UR1 = *UR1;
 correct_URU = *URU;
 swap = *slab-n_top_slide*;
 slab-n_top_slide = *slab-n_bottom_slide*;
 slab-n_bottom_slide = *swap*;
 swap = *slab-b_top_slide*;
 slab-b_top_slide = *slab-b_bottom_slide*;
 slab-b_bottom_slide = *swap*;
 RT(*n*, *slab*, UR1, UT1, URU, UTU);
 swap = *slab-n_top_slide*;
 slab-n_top_slide = *slab-n_bottom_slide*;
 slab-n_bottom_slide = *swap*;
 swap = *slab-b_top_slide*;
 slab-b_top_slide = *slab-b_bottom_slide*;
 slab-b_bottom_slide = *swap*;
 *UR1 = *correct_UR1*;
 *URU = *correct_URU*;
 $\}$
 $\}$

This code is used in section 117.

154. Simple routine to put values into the grid

Presumes that *RR.slab* is properly set up.

⟨Definition for *fill_grid_entry* 154⟩ ≡

```
static void fill_grid_entry(int i, int j)
{
    double ur1, ut1, uru, utu;
    if (RR.slab.b ≤ 1 · 10-6) RR.slab.b = 1 · 10-6;
    if (Debug(DEBUG_EVERY_CALC)) {
        if (¬CALCULATING_GRID)
            fprintf(stderr, "a=%8.5f b=%10.5f g=%8.5f", RR.slab.a, RR.slab.b, RR.slab.g);
        else {
            if (j ≡ 0) fprintf(stderr, ".");
            if (i + 1 ≡ GRID_SIZE ∧ j ≡ 0) fprintf(stderr, "\n");
        }
    }
    RT_Flip(MM.flip_sample, RR.method.quad_pts, &RR.slab, &ur1, &ut1, &uru, &utu);
    if (Debug(DEBUG_EVERY_CALC) ∧ ¬CALCULATING_GRID)
        fprintf(stderr, "ur1=%8.5f ut1=%8.5f\n", ur1, ut1);
    The_Grid[GRID_SIZE * i + j][A_COLUMN] = RR.slab.a;
    The_Grid[GRID_SIZE * i + j][B_COLUMN] = RR.slab.b;
    The_Grid[GRID_SIZE * i + j][G_COLUMN] = RR.slab.g;
    The_Grid[GRID_SIZE * i + j][UR1_COLUMN] = ur1;
    The_Grid[GRID_SIZE * i + j][UT1_COLUMN] = ut1;
    The_Grid[GRID_SIZE * i + j][URU_COLUMN] = uru;
    The_Grid[GRID_SIZE * i + j][UTU_COLUMN] = utu;
    if (Debug(DEBUG_GRID_CALC)) {
        fprintf(stderr, "+_2d_2d", i, j);
        fprintf(stderr, "%10.5f%10.5f%10.5f", RR.slab.a, RR.slab.b, RR.slab.g);
        fprintf(stderr, "%10.5f%10.5f", MM.m_r, uru);
        fprintf(stderr, "%10.5f%10.5f\n", MM.m_t, utu);
    }
}
```

This code is used in section 117.

155. This routine fills the grid with a proper set of values. With a little work, this routine could be made much faster by (1) only generating the phase function matrix once, (2) Making only one pass through the array for each albedo value, i.e., using the matrix left over from $b = 1$ to generate the solution for $b = 2$. Unfortunately this would require a complete revision of the *Calculate_Distance* routine. Fortunately, this routine should only need to be calculated once at the beginning of each run.

⟨Prototype for *Fill_AB_Grid* 155⟩ ≡

```
void Fill_AB_Grid(struct measure_type m, struct invert_type r)
```

This code is used in sections 117 and 156.

156. \langle Definition for *Fill_AB_Grid* 156 $\rangle \equiv$
 \langle Prototype for *Fill_AB_Grid* 155 \rangle

```

{
  int i, j;
  double a;
  double min_b = -8;    /* exp(-10) is smallest thickness */
  double max_b = +8;    /* exp(+8) is greatest thickness */
  if (Debug(DEBUG_GRID)) fprintf(stderr, "Filling AB grid\n");
  if (The_Grid  $\equiv$   $\Lambda$ ) Allocate_Grid(r.search);
   $\langle$  Zero GG 162  $\rangle$ 
  Set_Calc_State(m, r);
  GG_g = RR.slab.g;
  for (i = 0; i < GRID_SIZE; i++) {
    double x = (double) i / (GRID_SIZE - 1.0);
    RR.slab.b = exp(min_b + (max_b - min_b) * x);
    for (j = 0; j < GRID_SIZE; j++) {
       $\langle$  Generate next albedo using j 158  $\rangle$ 
      fill_grid_entry(i, j);
    }
  }
  The_Grid_Initialized = TRUE;
  The_Grid_Search = FIND_AB;
}

```

This code is used in section 117.

157. Now it seems that I must be a bit more subtle in choosing the range of albedos to use in the grid. Originally I just spaced them according to

$$a = 1 - \left[\frac{j-1}{n-1} \right]^3$$

where $1 \leq j \leq n$. Long ago it seems that I based things only on the square of the bracketed term, but I seem to remember that I was forced to change it from a square to a cube to get more global convergence.

So why am I rewriting this? Well, because it works very poorly for samples with small albedos. For example, when $n = 11$ then the values chosen for a are (1, .999, .992, .973, .936, .875, .784, .657, .488, .271, 0). Clearly very skewed towards high albedos.

I am considering a two part division. I'm not too sure how it should go. Let the first half be uniformly divided and the last half follow the cubic scheme given above. The list of values should then be (1, .996, .968, .892, 0.744, .5, .4, .3, .2, .1, 0).

Maybe it would be best if I just went back to a quadratic term. Who knows?

In the if statement below, note that it could read $j \geq k$ and still generate the same results.

\langle Nonworking code 157 $\rangle \equiv$

```

k = floor((GRID_SIZE - 1)/2);
if (j > k) {
  a = 0.5 * (1 - (j - k - 1)/(GRID_SIZE - k - 1));
  RR.slab.a = a;
}
else {
  a = (j - 1.0)/(GRID_SIZE - k - 1);
  RR.slab.a = 1.0 - a * a * a/2;
}

```

158. Well, the above code did not work well. So I futzed around and sort of empirically ended up using the very simple method below. The only real difference from the previous method what that the method is now quadratic and not cubic.

```

⟨Generate next albedo using j 158⟩ ≡
  a = (double) j / (GRID_SIZE - 1.0);
  if (a < 0.25) RR.slabs.a = 1.0 - a * a;
  else if (a > 0.75) RR.slabs.a = (1.0 - a) * (1.0 - a);
  else RR.slabs.a = 1 - a;

```

See also section 159.

This code is used in sections 156 and 161.

159. Well, the above code has gaps. Here is an attempt to eliminate the gaps

```

⟨Generate next albedo using j 158⟩ +≡
  a = (double) j / (GRID_SIZE - 1.0);
  RR.slabs.a = (1.0 - a * a) * (1.0 - a) + (1.0 - a) * (1.0 - a) * a;

```

160. This is quite similar to *Fill_AB_Grid*, with the exception of the little shuffle I do at the beginning to figure out the optical thickness to use. The problem is that the optical thickness may not be known. If it is known then the only way that we could have gotten here is if the user dictated *FIND_AG* and specified *b* and only provided two measurements. Otherwise, the user must have made three measurements and the optical depth can be figured out from *m.m.u*.

This routine could also be improved by not recalculating the anisotropy matrix for every point. But this would only end up being a minor performance enhancement if it were fixed.

```

⟨Prototype for Fill_AG_Grid 160⟩ ≡
  void Fill_AG_Grid(struct measure_type m, struct invert_type r)

```

This code is used in sections 117 and 161.

```

161.  ⟨Definition for Fill_AG_Grid 161⟩ ≡
  ⟨Prototype for Fill_AG_Grid 160⟩
  {
    int i, j;
    double a;
    if (Debug(DEBUG_GRID)) fprintf(stderr, "Filling AG grid\n");
    if (The_Grid == Λ) Allocate_Grid(r.search);
    ⟨Zero GG 162⟩
    Set_Calc_State(m, r);
    GG_b = r.slabs.b;
    for (i = 0; i < GRID_SIZE; i++) {
      RR.slabs.g = 0.9999 * (2.0 * i / (GRID_SIZE - 1.0) - 1.0);
      for (j = 0; j < GRID_SIZE; j++) {
        ⟨Generate next albedo using j 158⟩
        fill_grid_entry(i, j);
      }
    }
    The_Grid_Initialized = TRUE;
    The_Grid_Search = FIND_AG;
  }

```

This code is used in section 117.

162.

```

⟨Zero GG 162⟩ ≡
    GG_a = 0.0;
    GG_b = 0.0;
    GG_g = 0.0;
    GG_bs = 0.0;
    GG_ba = 0.0;

```

This code is used in sections 156, 161, 164, 166, and 168.

163. This is quite similar to *Fill_AB_Grid*, with the exception of the that the albedo is held fixed while *b* and *g* are varied.

This routine could also be improved by not recalculating the anisotropy matrix for every point. But this would only end up being a minor performance enhancement if it were fixed.

```

⟨Prototype for Fill_BG_Grid 163⟩ ≡
    void Fill_BG_Grid(struct measure_type m, struct invert_type r)

```

This code is used in sections 118 and 164.

```

164.  ⟨Definition for Fill_BG_Grid 164⟩ ≡
    ⟨Prototype for Fill_BG_Grid 163⟩
    {
        int i, j;
        if (The_Grid ≡ Λ) Allocate_Grid(r.search);
        ⟨Zero GG 162⟩
        if (Debug(DEBUG_GRID)) fprintf(stderr, "Filling_BG_grid\n");
        Set_Calc_State(m, r);
        RR.slab.b = 1.0/32.0;
        RR.slab.a = RR.default_a;
        GG_a = RR.slab.a;
        for (i = 0; i < GRID_SIZE; i++) {
            RR.slab.b *= 2;
            for (j = 0; j < GRID_SIZE; j++) {
                RR.slab.g = 0.9999 * (2.0 * j / (GRID_SIZE - 1.0) - 1.0);
                fill_grid_entry(i, j);
            }
        }
        The_Grid_Initialized = TRUE;
        The_Grid_Search = FIND_BG;
    }

```

This code is used in section 117.

165. This is quite similar to *Fill_BG_Grid*, with the exception of the that the $b_s = \mu_s d$ is held fixed. Here *b* and *g* are varied on the usual grid, but the albedo is forced to take whatever value is needed to ensure that the scattering constant remains fixed.

```

⟨Prototype for Fill_BaG_Grid 165⟩ ≡
    void Fill_BaG_Grid(struct measure_type m, struct invert_type r)

```

This code is used in sections 118 and 166.

166. \langle Definition for *Fill_BaG_Grid* 166 $\rangle \equiv$
 \langle Prototype for *Fill_BaG_Grid* 165 \rangle
{
 int *i, j*;
 double *bs, ba*;
 if (*The_Grid* $\equiv \Lambda$) *Allocate_Grid*(*r.search*);
 \langle Zero *GG* 162 \rangle
 if (*Debug*(DEBUG_GRID)) *fprintf*(*stderr*, "Filling \sqcup BaG \sqcup grid\n");
 Set_Calc_State(*m, r*);
 ba = 1.0/32.0;
 bs = *RR.default_bs*;
 GG_bs = *bs*;
 for (*i* = 0; *i* < GRID_SIZE; *i*++) {
 ba *= 2;
 ba = *exp*((**double**) *i*/(GRID_SIZE - 1.0) * *log*(1024.0))/16.0;
 RR.slab.b = *ba* + *bs*;
 if (*RR.slab.b* > 0) *RR.slab.a* = *bs*/*RR.slab.b*;
 else *RR.slab.a* = 0;
 for (*j* = 0; *j* < GRID_SIZE; *j*++) {
 RR.slab.g = 0.9999 * (2.0 * *j*/(GRID_SIZE - 1.0) - 1.0);
 fill_grid_entry(*i, j*);
 }
 }
 The_Grid_Initialized = TRUE;
 The_Grid_Search = *FIND_BaG*;
}

This code is used in section 117.

167. Very similar to the above routine. The value of $b_a = \mu_a d$ is held constant.

\langle Prototype for *Fill_BsG_Grid* 167 $\rangle \equiv$
 void *Fill_BsG_Grid*(**struct** *measure_type m*, **struct** *invert_type r*)

This code is used in sections 118 and 168.

168. \langle Definition for *Fill_BsG_Grid* 168 $\rangle \equiv$
 \langle Prototype for *Fill_BsG_Grid* 167 \rangle

```
{
  int i, j;
  double bs, ba;
  if (The_Grid  $\equiv \Lambda$ ) Allocate_Grid(r.search);
   $\langle$  Zero GG 162  $\rangle$ 
  Set_Calc_State(m, r);
  bs = 1.0/32.0;
  ba = RR.default_ba;
  GG_ba = ba;
  for (i = 0; i < GRID_SIZE; i++) {
    bs *= 2;
    RR.slab.b = ba + bs;
    if (RR.slab.b > 0) RR.slab.a = bs/RR.slab.b;
    else RR.slab.a = 0;
    for (j = 0; j < GRID_SIZE; j++) {
      RR.slab.g = 0.9999 * (2.0 * j / (GRID_SIZE - 1.0) - 1.0);
      fill_grid_entry(i, j);
    }
  }
  The_Grid_Initialized = TRUE;
  The_Grid_Search = FIND_BsG;
}
```

This code is used in section 117.

169. \langle Prototype for *Fill_Grid* 169 $\rangle \equiv$

void *Fill_Grid*(**struct** measure_type m, **struct** invert_type r, **int** force_new)

This code is used in sections 118 and 170.

170. $\langle \text{Definition for } \textit{Fill_Grid} \text{ 170} \rangle \equiv$
 $\langle \text{Prototype for } \textit{Fill_Grid} \text{ 169} \rangle$
 $\{$
 if $(\textit{force_new} \vee \neg \textit{Same_Calc_State}(m, r)) \{$
 switch $(r.\textit{search}) \{$
 case $\textit{FIND_AB}:$
 if $(\textit{Debug}(\textit{DEBUG_SEARCH})) \textit{fprintf}(\textit{stderr}, "filling_AB_Grid\n");$
 $\textit{Fill_AB_Grid}(m, r);$
 break;
 case $\textit{FIND_AG}:$
 if $(\textit{Debug}(\textit{DEBUG_SEARCH})) \textit{fprintf}(\textit{stderr}, "filling_AG_Grid\n");$
 $\textit{Fill_AG_Grid}(m, r);$
 break;
 case $\textit{FIND_BG}:$
 if $(\textit{Debug}(\textit{DEBUG_SEARCH})) \textit{fprintf}(\textit{stderr}, "filling_BG_Grid\n");$
 $\textit{Fill_BG_Grid}(m, r);$
 break;
 case $\textit{FIND_BaG}:$
 if $(\textit{Debug}(\textit{DEBUG_SEARCH})) \textit{fprintf}(\textit{stderr}, "filling_BaG_Grid\n");$
 $\textit{Fill_BaG_Grid}(m, r);$
 break;
 case $\textit{FIND_BsG}:$
 if $(\textit{Debug}(\textit{DEBUG_SEARCH})) \textit{fprintf}(\textit{stderr}, "filling_BsG_Grid\n");$
 $\textit{Fill_BsG_Grid}(m, r);$
 break;
 default: $\textit{AD_error}("Attempt_to_fill_grid_for_unusual_search_case.");$
 }
 }
 $\textit{Get_Calc_State}(\&\textit{MGRID}, \&\textit{RGRID});$
 $\}$

This code is used in section 117.

171. Calculating R and T.

Calculate_Distance returns the distance between the measured values in MM and the calculated values for the current guess at the optical properties. It assumes that the everything in the local variables MM and RR have been set appropriately.

⟨Prototype for *Calculate_Distance* 171⟩ ≡

```
void Calculate_Distance(double *M_R, double *M_T, double *deviation)
```

This code is used in sections 118 and 172.

172. ⟨Definition for *Calculate_Distance* 172⟩ ≡

⟨Prototype for *Calculate_Distance* 171⟩

```
{
    double Rc, Tc, ur1, ut1, uru, utu;
    if (RR.slab.b ≤ 1 · 10-6) RR.slab.b = 1 · 10-6;
    if (0 ∧ Debug(DEBUG_EVERY_CALC))
        fprintf(stderr, "a=%8.5f_b=%10.5f_g=%8.5f", RR.slab.a, RR.slab.b, RR.slab.g);
    RT_Flip(MM.flip_sample, RR.method.quad_pts, &RR.slab, &ur1, &ut1, &uru, &utu);
    if (0 ∧ Debug(DEBUG_EVERY_CALC))
        fprintf(stderr, "ur1=%8.5f_ut1=%8.5f(not_M_R_and_M_T!)\n", ur1, ut1);
    Sp_mu_RT_Flip(MM.flip_sample, RR.slab.n_top_slide, RR.slab.n_slab, RR.slab.n_bottom_slide,
        RR.slab.b_top_slide, RR.slab.b, RR.slab.b_bottom_slide, RR.slab.cos_angle, &Rc, &Tc);
    if ((¬CALCULATING_GRID ∧ Debug(DEBUG_ITERATIONS)) ∨ (CALCULATING_GRID ∧
        Debug(DEBUG_GRID_CALC))) fprintf(stderr, "UUUUUUUU");
    Calculate_Distance_With_Corrections(ur1, ut1, Rc, Tc, uru, utu, M_R, M_T, deviation);
}
```

This code is used in section 117.

173. ⟨Prototype for *Calculate_Grid_Distance* 173⟩ ≡

```
double Calculate_Grid_Distance(int i, int j)
```

This code is used in sections 118 and 174.

174. ⟨Definition for *Calculate_Grid_Distance* 174⟩ ≡

⟨Prototype for *Calculate_Grid_Distance* 173⟩

```
{
    double ur1, ut1, uru, utu, Rc, Tc, b, dev, LR, LT;
    if (Debug(DEBUG_GRID_CALC)) fprintf(stderr, "g_%2d_%2d", i, j);
    b = The_Grid[GRID_SIZE * i + j][B_COLUMN];
    ur1 = The_Grid[GRID_SIZE * i + j][UR1_COLUMN];
    ut1 = The_Grid[GRID_SIZE * i + j][UT1_COLUMN];
    uru = The_Grid[GRID_SIZE * i + j][URU_COLUMN];
    utu = The_Grid[GRID_SIZE * i + j][UTU_COLUMN];
    RR.slab.a = The_Grid[GRID_SIZE * i + j][A_COLUMN];
    RR.slab.b = The_Grid[GRID_SIZE * i + j][B_COLUMN];
    RR.slab.g = The_Grid[GRID_SIZE * i + j][G_COLUMN];
    Sp_mu_RT_Flip(MM.flip_sample, RR.slab.n_top_slide, RR.slab.n_slab, RR.slab.n_bottom_slide,
        RR.slab.b_top_slide, b, RR.slab.b_bottom_slide, RR.slab.cos_angle, &Rc, &Tc);
    CALCULATING_GRID = 1;
    Calculate_Distance_With_Corrections(ur1, ut1, Rc, Tc, uru, utu, &LR, &LT, &dev);
    CALCULATING_GRID = 0;
    return dev;
}
```

This code is used in section 117.

175. This is the routine that actually finds the distance. I have factored this part out so that it can be used in the *Near_Grid_Points* routine.

Rc and *Tc* refer to the unscattered (collimated) reflection and transmission.

The only tricky part is to remember that the we are trying to match the measured values. The measured values are affected by sphere parameters and light loss. Since the values *UR1* and *UT1* are for an infinite slab sample with no light loss, the light loss out the edges must be subtracted. It is these values that are used with the sphere formulas to convert the modified *UR1* and *UT1* to values for **M_R* and **M_T*.

⟨Prototype for *Calculate_Distance_With_Corrections* 175⟩ ≡

```
void Calculate_Distance_With_Corrections(double UR1,double UT1,double Rc,double Tc,double
    URU,double UTU,double *M_R,double *M_T,double *dev)
```

This code is used in sections 118 and 176.

176. ⟨Definition for *Calculate_Distance_With_Corrections* 176⟩ ≡

⟨Prototype for *Calculate_Distance_With_Corrections* 175⟩

```
{
    double R_direct, T_direct, R_diffuse, T_diffuse;
    R_diffuse = URU - MM.uru_lost;
    T_diffuse = UTU - MM.utu_lost;
    R_direct = UR1 - MM.ur1_lost - (1.0 - MM.fraction_of_rc_in_mr) * Rc;
    T_direct = UT1 - MM.ut1_lost - (1.0 - MM.fraction_of_tc_in_mt) * Tc;
    switch (MM.num_spheres) {
    case 0: ⟨Calc M_R and M_T for no spheres 177⟩
        break;
    case 1:
        if (MM.method ≡ COMPARISON) ⟨Calc M_R and M_T for dual beam sphere 179⟩
            else ⟨Calc M_R and M_T for single beam sphere 178⟩
                break;
    case 2: ⟨Calc M_R and M_T for two spheres 180⟩
        break;
    default: fprintf(stderr, "Bad_number_of_spheres=%d\n", MM.num_spheres);
    }
    ⟨Calculate the deviation 181⟩
    ⟨Print diagnostics 184⟩
}
```

This code is used in section 117.

177. If no spheres were used in the measurement, then presumably the measured values are the reflection and transmission. Consequently, we just ascertain what the irradiance was and whether the specular reflection ports were blocked and proceed accordingly. Note that blocking the ports does not have much meaning unless the light is collimated, and therefore the reflection and transmission is only modified for collimated irradiance.

⟨Calc M_R and M_T for no spheres 177⟩ ≡

```
{
    *M_R = R_direct;
    *M_T = T_direct;
}
```

This code is used in section 176.

178. The direct incident power is $(1 - f)P$. The reflected power will be $(1 - f)r_s^{\text{direct}}P$. Since baffles ensure that the light cannot reach the detector, we must bounce the light off the sphere walls to use to above gain formulas. The contribution will then be $(1 - f)r_s^{\text{direct}}(1 - a_e)r_wP$. The measured power will be

$$P_d = a_d(1 - a_e)r_w[(1 - f)r_s^{\text{direct}} + fr_w]P \cdot G(r_s)$$

Similarly the power falling on the detector measuring transmitted light is

$$P'_d = a'_d t_s^{\text{direct}} r'_w (1 - a'_e)P \cdot G'(r_s)$$

when the ‘entrance’ port in the transmission sphere is closed, $a'_e = 0$.

The normalized sphere measurements are

$$M_R = r_{\text{std}} \cdot \frac{R(r_s^{\text{direct}}, r_s) - R(0, 0)}{R(r_{\text{std}}, r_{\text{std}}) - R(0, 0)}$$

and

$$M_T = t_{\text{std}} \cdot \frac{T(t_s^{\text{direct}}, r_s) - T(0, 0)}{T(t_{\text{std}}, r_{\text{std}}) - T(0, 0)}$$

⟨ Calc M_R and M_T for single beam sphere 178 ⟩ ≡

```
{
  double P_std, P_d, P_0;
  double G, G_0, G_std, GP_std, GP;
  G_0 = Gain(REFLECTION_SPHERE, MM, 0.0);
  G = Gain(REFLECTION_SPHERE, MM, R_diffuse);
  G_std = Gain(REFLECTION_SPHERE, MM, MM.rstd_r);
  P_d = G * (R_direct * (1 - MM.f_r) + MM.f_r * MM.rw_r);
  P_std = G_std * (MM.rstd_r * (1 - MM.f_r) + MM.f_r * MM.rw_r);
  P_0 = G_0 * (MM.f_r * MM.rw_r);
  *M_R = MM.rstd_r * (P_d - P_0) / (P_std - P_0);
  GP = Gain(TRANSMISSION_SPHERE, MM, R_diffuse);
  GP_std = Gain(TRANSMISSION_SPHERE, MM, 0.0);
  *M_T = T_direct * GP / GP_std;
}
```

This code is used in section 176.

179. The dual beam case is different because the sphere efficiency is equivalent for measurement of light hitting the sample first or hitting the reference standard first. The dual beam measurement should report the ratio of these two reflectance measurements, thereby eliminating the need to calculate the gain completely. The same holds when no sample is present.

The normalized reflectance measurement (the difference between dual beam measurement for a port with the sample and with nothing) is

$$M_R = r_{\text{std}} \cdot \frac{(1-f)r_s^{\text{direct}} + fr_w}{(1-f')r_{\text{std}} - f'r_w} - r_{\text{std}} \cdot \frac{(1-f)(0) + fr_w}{(1-f')r_{\text{std}} - f'r_w}$$

or

$$M_R = \frac{(1-f)r_s^{\text{direct}}}{(1-f') - f'r_w/r_{\text{std}}}$$

When $f = f' = 1$, then $M_R = 1$ no matter what the reflectance is. (Leave it in this form to avoid division by zero when $f = 1$.)

The normalized transmittance is simply t_s^{direct} .

When $f = 0$ then this result is essentially the same as the no spheres result (because no sphere corrections are needed). However if the number of spheres is zero, then no lost light calculations are made and therefore that is a potential error.

⟨ Calc M_R and M_T for dual beam sphere 179 ⟩ ≡

```
{
  *M_R = (1 - MM.f_r) * R_direct / ((1 - MM.f_r) + MM.f_r * MM.rw_r / MM.rstd_r);
  *M_T = T_direct;
}
```

This code is used in section 176.

180. When two integrating spheres are present then the double integrating sphere formulas are slightly more complicated.

I am not sure what it means when $rstd_t$ is not unity.

The normalized sphere measurements for two spheres are

$$M_R = \frac{R(r_s^{\text{direct}}, r_s, t_s^{\text{direct}}, t_s) - R(0, 0, 0, 0)}{R(r_{\text{std}}, r_{\text{std}}, 0, 0) - R(0, 0, 0, 0)}$$

and

$$M_T = \frac{T(r_s^{\text{direct}}, r_s, t_s^{\text{direct}}, t_s) - T(0, 0, 0, 0)}{T(0, 0, 1, 1) - T(0, 0, 0, 0)}$$

Note that R_0 and T_0 will be zero unless one has explicitly set the fraction $m.f_r$ or $m.f_t$ to be non-zero.

⟨ Calc M_R and M_T for two spheres 180 ⟩ ≡

```
{
  double R_0, T_0;
  R_0 = TwoSphere_R(MM, 0, 0, 0, 0);
  T_0 = TwoSphere_T(MM, 0, 0, 0, 0);
  *M_R = MM.rstd_r * (TwoSphere_R(MM, R_direct, R_diffuse, T_direct,
    T_diffuse) - R_0) / (TwoSphere_R(MM, MM.rstd_r, MM.rstd_r, 0, 0) - R_0);
  *M_T = (TwoSphere_T(MM, R_direct, R_diffuse, T_direct, T_diffuse) - T_0) / (TwoSphere_T(MM, 0, 0, 1,
    1) - T_0);
}
```

This code is used in section 176.

181. There are at least three things that need to be considered here. First, the number of measurements. Second, is the metric is relative or absolute. And third, is the albedo fixed at zero which means that the transmission measurement should be used instead of the reflection measurement.

```

< Calculate the deviation 181 > ≡
  if (RR.search ≡ FIND_A ∨ RR.search ≡ FIND_G ∨ RR.search ≡ FIND_B ∨ RR.search ≡ FIND_Bs ∨ RR.search ≡
      FIND_Ba) {
    < One parameter deviation 182 >
  }
  else {
    < Two parameter deviation 183 >
  }

```

This code is used in section 176.

182. This part was slightly tricky. The crux of the problem was to decide if the transmission or the reflection was trustworthy. After looking a bunches of measurements, I decided that the transmission measurement was almost always more reliable. So when there is just a single measurement known, then use the total transmission if it exists.

```

< One parameter deviation 182 > ≡
  if (MM.m_t > 0) {
    if (RR.metric ≡ RELATIVE) *dev = fabs(MM.m_t - *M_T)/(MM.m_t + ABIT);
    else *dev = fabs(MM.m_t - *M_T);
  }
  else {
    if (RR.metric ≡ RELATIVE) *dev = fabs(MM.m_r - *M_R)/(MM.m_r + ABIT);
    else *dev = fabs(MM.m_r - *M_R);
  }

```

This code is used in section 181.

183. This stuff happens when we are doing two parameter searches. In these cases there should be information in both R and T. The distance should be calculated using the deviation from both. The albedo stuff might be able to be take out. We'll see.

```

< Two parameter deviation 183 > ≡
  if (RR.metric ≡ RELATIVE) {
    *dev = 0;
    if (MM.m_t > ABIT) *dev = T_TRUST_FACTOR * fabs(MM.m_t - *M_T)/(MM.m_t + ABIT);
    if (RR.default_a ≠ 0) *dev += fabs(MM.m_r - *M_R)/(MM.m_r + ABIT);
  }
  else {
    *dev = T_TRUST_FACTOR * fabs(MM.m_t - *M_T);
    if (RR.default_a ≠ 0) *dev += fabs(MM.m_r - *M_R);
  }

```

This code is used in section 181.

184. This is here so that I can figure out why the program is not converging. This is a little convoluted so that the global constants at the top of this file interact properly.

```

⟨Print diagnostics 184⟩ ≡
  if ((Debug(DEBUG_ITERATIONS) ∧ ¬CALCULATING_GRID) ∨
      (Debug(DEBUG_GRID_CALC) ∧ CALCULATING_GRID)) {
    static int once;
    if (once ≠ MM.lambda) {
      fprintf(stderr, "%10s_□%10s_□%10s_□%7s_□%7s_□%7s_□%7s_□%8s\n", "a", "b", "g", "m_r",
          "fit", "m_t", "fit", "delta");
      once = MM.lambda;
    }
    fprintf(stderr, "%10.5f_□%10.5f_□%10.5f_□", RR.slab.a, RR.slab.b, RR.slab.g);
    fprintf(stderr, "□%7.5f_□%7.5f_□", MM.m_r, *M_R);
    fprintf(stderr, "□%7.5f_□%7.5f_□", MM.m_t, *M_T);
    fprintf(stderr, "%8.5f_□\n", *dev);
  }

```

This code is used in section 176.

185. ⟨Prototype for *Find_AG_fn* 185⟩ ≡
double *Find_AG_fn*(**double** x[])

This code is used in sections 118 and 186.

186. ⟨Definition for *Find_AG_fn* 186⟩ ≡
 ⟨Prototype for *Find_AG_fn* 185⟩
 {
double m_r, m_t, deviation;
 RR.slab.a = *acalc2a*(x[1]);
 RR.slab.g = *gcalc2g*(x[2]);
Calculate_Distance(&m_r, &m_t, &deviation);
return deviation;
 }

This code is used in section 117.

187. ⟨Prototype for *Find_AB_fn* 187⟩ ≡
double *Find_AB_fn*(**double** x[])

This code is used in sections 118 and 188.

188. ⟨Definition for *Find_AB_fn* 188⟩ ≡
 ⟨Prototype for *Find_AB_fn* 187⟩
 {
double m_r, m_t, deviation;
 RR.slab.a = *acalc2a*(x[1]);
 RR.slab.b = *bcalc2b*(x[2]);
Calculate_Distance(&m_r, &m_t, &deviation);
return deviation;
 }

This code is used in section 117.

189. ⟨Prototype for *Find_Ba_fn* 189⟩ ≡
double *Find_Ba_fn*(**double** x)

This code is used in sections 118 and 190.

190. This is tricky only because the value in `RR.slabs.b` is used to hold the value of bs or $d \cdot \mu_s$. It must be switched to the correct value for the optical thickness and then switched back at the end of the routine.

```

⟨Definition for Find_Ba_fn 190⟩ ≡
⟨Prototype for Find_Ba_fn 189⟩
{
    double m_r, m_t, deviation, ba, bs;
    bs = RR.slabs.b;
    ba = bcalc2b(x);
    RR.slabs.b = ba + bs; /* unswindle */
    RR.slabs.a = bs / (ba + bs);
    Calculate_Distance(&m_r, &m_t, &deviation);
    RR.slabs.b = bs; /* swindle */
    return deviation;
}

```

This code is used in section 117.

191. See the comments for the *Find_Ba_fn* routine above. Play the same trick but use ba .

```

⟨Prototype for Find_Bs_fn 191⟩ ≡
    double Find_Bs_fn(double x)

```

This code is used in sections 118 and 192.

```

192. ⟨Definition for Find_Bs_fn 192⟩ ≡
⟨Prototype for Find_Bs_fn 191⟩
{
    double m_r, m_t, deviation, ba, bs;
    ba = RR.slabs.b; /* unswindle */
    bs = bcalc2b(x);
    RR.slabs.b = ba + bs;
    RR.slabs.a = bs / (ba + bs);
    Calculate_Distance(&m_r, &m_t, &deviation);
    RR.slabs.b = ba; /* swindle */
    return deviation;
}

```

This code is used in section 117.

```

193. ⟨Prototype for Find_A_fn 193⟩ ≡
    double Find_A_fn(double x)

```

This code is used in sections 118 and 194.

```

194. ⟨Definition for Find_A_fn 194⟩ ≡
⟨Prototype for Find_A_fn 193⟩
{
    double m_r, m_t, deviation;
    RR.slabs.a = acalc2a(x);
    Calculate_Distance(&m_r, &m_t, &deviation);
    return deviation;
}

```

This code is used in section 117.

195. $\langle \text{Prototype for } Find_B_fn \text{ 195} \rangle \equiv$
double *Find_B_fn*(**double** *x*)

This code is used in sections 118 and 196.

196. $\langle \text{Definition for } Find_B_fn \text{ 196} \rangle \equiv$
 $\langle \text{Prototype for } Find_B_fn \text{ 195} \rangle$
 {
 double *m_r*, *m_t*, *deviation*;
 RR.slab.b = *bcalc2b*(*x*);
 Calculate_Distance(&*m_r*, &*m_t*, &*deviation*);
 return *deviation*;
 }

This code is used in section 117.

197. $\langle \text{Prototype for } Find_G_fn \text{ 197} \rangle \equiv$
double *Find_G_fn*(**double** *x*)

This code is used in sections 118 and 198.

198. $\langle \text{Definition for } Find_G_fn \text{ 198} \rangle \equiv$
 $\langle \text{Prototype for } Find_G_fn \text{ 197} \rangle$
 {
 double *m_r*, *m_t*, *deviation*;
 RR.slab.g = *gcalc2g*(*x*);
 Calculate_Distance(&*m_r*, &*m_t*, &*deviation*);
 return *deviation*;
 }

This code is used in section 117.

199. $\langle \text{Prototype for } Find_BG_fn \text{ 199} \rangle \equiv$
double *Find_BG_fn*(**double** *x*[])

This code is used in sections 118 and 200.

200. $\langle \text{Definition for } Find_BG_fn \text{ 200} \rangle \equiv$
 $\langle \text{Prototype for } Find_BG_fn \text{ 199} \rangle$
 {
 double *m_r*, *m_t*, *deviation*;
 RR.slab.b = *bcalc2b*(*x*[1]);
 RR.slab.g = *gcalc2g*(*x*[2]);
 RR.slab.a = RR.default_a;
 Calculate_Distance(&*m_r*, &*m_t*, &*deviation*);
 return *deviation*;
 }

This code is used in section 117.

201. For this function the first term *x*[1] will contain the value of $\mu_s d$, the second term will contain the anisotropy. Of course the first term is in the bizarre calculation space and needs to be translated back into normal terms before use. We just at the scattering back on and voilà we have a useable value for the optical depth.

$\langle \text{Prototype for } Find_BaG_fn \text{ 201} \rangle \equiv$
double *Find_BaG_fn*(**double** *x*[])

This code is used in sections 118 and 202.

202. $\langle \text{Definition for } Find_BaG_fn \text{ 202} \rangle \equiv$
 $\langle \text{Prototype for } Find_BaG_fn \text{ 201} \rangle$
 {
 double *m_r, m_t, deviation*;
 RR.slab.b = bcalc2b(*x*[1]) + RR.default_bs;
 if (RR.slab.b ≤ 0) RR.slab.a = 0;
 else RR.slab.a = RR.default_bs/RR.slab.b;
 RR.slab.g = gcalc2g(*x*[2]);
 Calculate_Distance(&*m_r*, &*m_t*, &*deviation*);
 return *deviation*;
 }

This code is used in section 117.

203. $\langle \text{Prototype for } Find_BsG_fn \text{ 203} \rangle \equiv$
double *Find_BsG_fn*(**double** *x*[])

This code is used in sections 118 and 204.

204. $\langle \text{Definition for } Find_BsG_fn \text{ 204} \rangle \equiv$
 $\langle \text{Prototype for } Find_BsG_fn \text{ 203} \rangle$
 {
 double *m_r, m_t, deviation*;
 RR.slab.b = bcalc2b(*x*[1]) + RR.default_ba;
 if (RR.slab.b ≤ 0) RR.slab.a = 0;
 else RR.slab.a = 1.0 - RR.default_ba/RR.slab.b;
 RR.slab.g = gcalc2g(*x*[2]);
 Calculate_Distance(&*m_r*, &*m_t*, &*deviation*);
 return *deviation*;
 }

This code is used in section 117.

205. Routine to figure out if the light loss exceeds what is physically possible. Returns the discrepancy between the current values and the maximum possible values for the the measurements *m_r* and *m_t*.

$\langle \text{Prototype for } maxloss \text{ 205} \rangle \equiv$
double *maxloss*(**double** *f*)

This code is used in sections 118 and 206.

206. \langle Definition for *maxloss* 206 $\rangle \equiv$
 \langle Prototype for *maxloss* 205 \rangle
{
 struct **measure_type** *m_old*;
 struct **invert_type** *r_old*;
 double *m_r*, *m_t*, *deviation*;
 Get_Calc_State(&*m_old*, &*r_old*);
 RR.slab.a = 1.0;
 MM.ur1_lost *= *f*;
 MM.ut1_lost *= *f*;
 Calculate_Distance(&*m_r*, &*m_t*, &*deviation*);
 Set_Calc_State(*m_old*, *r_old*);
 deviation = ((MM.*m_r* + MM.*m_t*) - (*m_r* + *m_t*));
 return *deviation*;
}

This code is used in section 117.

207. This checks the two light loss values *ur1_loss* and *ut1_loss* to see if they exceed what is physically possible. If they do, then these values are replaced by a couple that are the maximum possible for the current values in *m* and *r*.

\langle Prototype for *Max_Light_Loss* 207 $\rangle \equiv$
void *Max_Light_Loss*(**struct** **measure_type** *m*, **struct** **invert_type** *r*, **double** **ur1_loss*, **double** **ut1_loss*)

This code is used in sections 118 and 208.

208. \langle Definition for *Max_Light_Loss* 208 $\rangle \equiv$
 \langle Prototype for *Max_Light_Loss* 207 \rangle
{
 struct **measure_type** *m_old*;
 struct **invert_type** *r_old*;
 **ur1_loss* = *m.ur1_lost*;
 **ut1_loss* = *m.ut1_lost*;
 if (*Debug*(DEBUG_LOST_LIGHT))
 fprintf(*stderr*, "\nlost before ur1=%7.5f, ut1=%7.5f\n", **ur1_loss*, **ut1_loss*);
 Get_Calc_State(&*m_old*, &*r_old*);
 Set_Calc_State(*m*, *r*);
 if (*maxloss*(1.0) * *maxloss*(0.0) < 0) {
 double *frac*;
 frac = *zbrent*(*maxloss*, 0.00, 1.0, 0.001);
 **ur1_loss* = *m.ur1_lost* * *frac*;
 **ut1_loss* = *m.ut1_lost* * *frac*;
 }
 Set_Calc_State(*m_old*, *r_old*);
 if (*Debug*(DEBUG_LOST_LIGHT))
 fprintf(*stderr*, "lost after ur1=%7.5f, ut1=%7.5f\n", **ur1_loss*, **ut1_loss*);
}

This code is used in section 117.

209. this is currently unused

⟨ Unused diffusion fragment 209 ⟩ ≡

```

typedef struct {
    double f;
    double aprime;
    double bprime;
    double gprime;
    double boundary_method;
    double n_top;
    double n_bottom;
    double slide_top;
    double slide_bottom;
    double F0;
    double depth;
    double Exact_coll_flag;
} slabtype;

static void DE_RT(int nfluxes, AD_slab_type slab, double *UR1, double *UT1, double *URU, double
    *UTU)
{
    slabtype s;
    double rp, tp, rs, ts;
    s.f = slab.g * slab.g;
    s.gprime = slab.g / (1 + slab.g);
    s.aprime = (1 - s.f) * slab.a / (1 - slab.a * s.f);
    s.bprime = (1 - slab.a * s.f) * slab.b;
    s.boundary_method = Egan;
    s.n_top = slab.n_slab;
    s.n_bottom = slab.n_slab;
    s.slide_top = slab.n_top_slide;
    s.slide_bottom = slab.n_bottom_slide;
    s.F0 = 1/M_PI;
    s.depth = 0.0;
    s.Exact_coll_flag = FALSE;
    if (MM.illumination ≡ collimated) {
        compute_R_and_T(&s, 1.0, &rp, &rs, &tp, &ts);
        *UR1 = rp + rs;
        *UT1 = tp + ts;
        *URU = 0.0;
        *UTU = 0.0;
        return;
    }
    quad_Dif_Calc_R_and_T(&s, &rp, &rs, &tp, &ts);
    *URU = rp + rs;
    *UTU = tp + ts;
    *UR1 = 0.0;
    *UT1 = 0.0;
}

```

210. IAD Find. March 1995. Incorporated the *quick_guess* algorithm for low albedos.

```

<iad_find.c 210> ≡
#include <math.h>
#include <stdio.h>
#include <stdlib.h>
#include "ad_globl.h"
#include "nr_util.h"
#include "nr_mnbrk.h"
#include "nr_brent.h"
#include "nr_amoeb.h"
#include "iad_type.h"
#include "iad_util.h"
#include "iad_calc.h"
#include "iad_find.h"
#define NUMBER_OF_GUESSES 10
guess_type guess[NUMBER_OF_GUESSES];
int compare_guesses(const void *p1, const void *p2)
{
    guess_type *g1 = (guess_type *) p1;
    guess_type *g2 = (guess_type *) p2;
    if (g1->distance < g2->distance) return -1;
    else if (g1->distance == g2->distance) return 0;
    else return 1;
}
<Definition for U_Find_Ba 224>
<Definition for U_Find_Bs 222>
<Definition for U_Find_A 226>
<Definition for U_Find_B 230>
<Definition for U_Find_G 228>
<Definition for U_Find_AG 233>
<Definition for U_Find_AB 213>
<Definition for U_Find_BG 238>
<Definition for U_Find_BaG 244>
<Definition for U_Find_BsG 249>

```

211. All the information that needs to be written to the header file `iad_find.h`. This eliminates the need to maintain a set of header files as well.

```

<iad_find.h 211> ≡
<Prototype for U_Find_Ba 223>;
<Prototype for U_Find_Bs 221>;
<Prototype for U_Find_A 225>;
<Prototype for U_Find_B 229>;
<Prototype for U_Find_G 227>;
<Prototype for U_Find_AG 232>;
<Prototype for U_Find_AB 212>;
<Prototype for U_Find_BG 237>;
<Prototype for U_Find_BaG 243>;
<Prototype for U_Find_BsG 248>;

```


212. Fixed Anisotropy.

This is the most common case.

⟨Prototype for *U_Find_AB* 212⟩ ≡

```
void U_Find_AB(struct measure_type m, struct invert_type *r)
```

This code is used in sections 211 and 213.

213. ⟨Definition for *U_Find_AB* 213⟩ ≡

⟨Prototype for *U_Find_AB* 212⟩

```
{
  ⟨Allocate local simplex variables 214⟩
  if (Debug(DEBUG_SEARCH)) {
    fprintf(stderr, "In U_Find_AB");
    fprintf(stderr, " (mu=%6.4f)", r→slab.cos_angle);
    if (r→default_g ≠ UNINITIALIZED) fprintf(stderr, " default_g=%8.5f", r→default_g);
    fprintf(stderr, "\n");
  }
  r→slab.g = (r→default_g ≡ UNINITIALIZED) ? 0 : r→default_g;
  Set_Calc.State(m, *r);
  ⟨Get the initial a, b, and g 215⟩
  ⟨Initialize the nodes of the a and b simplex 216⟩
  ⟨Evaluate the a and b simplex at the nodes 217⟩
  amoeba(p, y, 2, r→tolerance, Find_AB_fn, &r→iterations);
  ⟨Choose the best node of the a and b simplex 218⟩
  ⟨Free simplex data structures 220⟩
  ⟨Put final values in result 219⟩
}
```

This code is used in section 210.

214. To use the simplex algorithm, we need to vectors and a matrix.

⟨Allocate local simplex variables 214⟩ ≡

```
int i, i_best, j_best;
double *x, *y, **p;

x = dvector(1, 2);
y = dvector(1, 3);
p = dmatrix(1, 3, 1, 2);
```

This code is used in sections 213, 233, 238, 244, and 249.

215. Just get the optimal optical properties to start the search process.

I had to add the line that tests to make sure the albedo is greater than 0.2 because the grid just does not work so well in this case. The problem is that for low albedos there is really very little information about the anisotropy available. This change was also made in the analagous code for a and b .

⟨ Get the initial a , b , and g 215 ⟩ ≡

```
{
    /* double a3,b3,g3; */
    size_t count = NUMBER_OF_GUESSES; /* distance to last result */
    abg_distance(r→slab.a, r→slab.b, r→slab.g, &(guess[0]));
    if (¬Valid_Grid(m, r→search)) Fill_Grid(m, *r, 1); /* distance to nearest grid point */
    Near_Grid_Points(m.m_r, m.m_t, r→search, &i_best, &j_best);
    Grid_ABG(i_best, j_best, &(guess[1]));
    Grid_ABG(i_best + 1, j_best, &(guess[2]));
    Grid_ABG(i_best - 1, j_best, &(guess[3]));
    Grid_ABG(i_best, j_best + 1, &(guess[4]));
    Grid_ABG(i_best, j_best - 1, &(guess[5]));
    Grid_ABG(i_best + 1, j_best + 1, &(guess[6]));
    Grid_ABG(i_best - 1, j_best - 1, &(guess[7]));
    Grid_ABG(i_best + 1, j_best - 1, &(guess[8]));
    Grid_ABG(i_best - 1, j_best + 1, &(guess[9]));
    qsort((void *) guess, count, sizeof(guess_type), compare_guesses);
    if (Debug(DEBUG_BEST_GUESS)) {
        int k;
        fprintf(stderr, "Best_Grid_Guesses\n");
        fprintf(stderr, "k albedo b g distance\n");
        for (k = 0; k ≤ 6; k++) {
            fprintf(stderr, "%3d", k);
            fprintf(stderr, "%10.5f", guess[k].a);
            fprintf(stderr, "%10.5f", guess[k].b);
            fprintf(stderr, "%10.5f", guess[k].g);
            fprintf(stderr, "%10.5f\n", guess[k].distance);
        }
    }
}
```

This code is used in sections 213, 233, 238, 244, and 249.

216. \langle Initialize the nodes of the a and b simplex 216 $\rangle \equiv$

```

{
  int k, kk;
  p[1][1] = a2acalc(guess[0].a);
  p[1][2] = b2bcalc(guess[0].b);
  for (k = 1; k < 7; k++) {
    if (guess[0].a  $\neq$  guess[k].a) break;
  }
  p[2][1] = a2acalc(guess[k].a);
  p[2][2] = b2bcalc(guess[k].b);
  for (kk = 1; kk < 7; kk++) {
    if (k  $\equiv$  kk) continue;
    if (guess[0].b  $\neq$  guess[kk].b  $\vee$  guess[k].b  $\neq$  guess[kk].b) break;
  }
  p[3][1] = a2acalc(guess[kk].a);
  p[3][2] = b2bcalc(guess[kk].b);
  if (Debug(DEBUG_BEST_GUESS)) {
    fprintf(stderr, "-----\n");
    fprintf(stderr, "□<1>□");
    fprintf(stderr, "%10.5f□", guess[0].a);
    fprintf(stderr, "%10.5f□", guess[0].b);
    fprintf(stderr, "%10.5f□", guess[0].g);
    fprintf(stderr, "%10.5f\n", guess[0].distance);
    fprintf(stderr, "□<2>□");
    fprintf(stderr, "%10.5f□", guess[k].a);
    fprintf(stderr, "%10.5f□", guess[k].b);
    fprintf(stderr, "%10.5f□", guess[k].g);
    fprintf(stderr, "%10.5f\n", guess[k].distance);
    fprintf(stderr, "□<3>□");
    fprintf(stderr, "%10.5f□", guess[kk].a);
    fprintf(stderr, "%10.5f□", guess[kk].b);
    fprintf(stderr, "%10.5f□", guess[kk].g);
    fprintf(stderr, "%10.5f\n\n", guess[kk].distance);
  }
}

```

This code is used in section 213.

217. \langle Evaluate the a and b simplex at the nodes 217 $\rangle \equiv$

```

for (i = 1; i  $\leq$  3; i++) {
  x[1] = p[i][1];
  x[2] = p[i][2];
  y[i] = Find_AB_fn(x);
}

```

This code is used in section 213.

218. \langle Choose the best node of the a and b simplex 218 $\rangle \equiv$
`r-final_distance = 10;`
for ($i = 1$; $i \leq 3$; $i++$) {
 if ($y[i] < r\text{-}final_distance$) {
 $r\text{-}slab.a = a\text{calc}2a(p[i][1]);$
 $r\text{-}slab.b = b\text{calc}2b(p[i][2]);$
 $r\text{-}final_distance = y[i];$
 }
}

This code is used in section 213.

219. \langle Put final values in result 219 $\rangle \equiv$
if ($Debug(DEBUG_ITERATIONS)$) $fprintf(stderr, "amoeba_iterations_=_ \%d\backslash n", r\text{-}iterations);$
 $r\text{-}a = r\text{-}slab.a;$
 $r\text{-}b = r\text{-}slab.b;$
 $r\text{-}g = r\text{-}slab.g;$
 $r\text{-}found = (r\text{-}tolerance \leq r\text{-}final_distance);$
 $Set_Calc_State(m, *r);$

This code is used in sections 213, 222, 224, 226, 228, 230, 233, 238, 244, and 249.

220. Since we allocated these puppies, we got to get rid of them.

\langle Free simplex data structures 220 $\rangle \equiv$
 $free_dvector(x, 1, 2);$
 $free_dvector(y, 1, 3);$
 $free_dmatrix(p, 1, 3, 1, 2);$

This code is used in sections 213, 233, 238, 244, and 249.

221. Fixed Absorption and Anisotropy. Typically, this routine is called when the absorption coefficient is known, the anisotropy is known, and the physical thickness of the sample is known. This routine calculates the varies the scattering coefficient until the measurements are matched.

This was written for Ted Moffitt to analyze some intralipid data. We wanted to know what the scattering coefficient of the Intralipid was and made total transmission measurements through a sample with a fixed physical thickness. We did not make reflection measurements because the light source diverged too much, and we could not make reflection measurements easily.

In retrospect, we could have made URU measurements by illuminating the wall of the integrating sphere. However, these diffuse type of measurements are very difficult to make accurately.

This is tricky only because the value in *slab.b* is used to hold the value of *ba* or $d \cdot \mu_a$ when the *Find_Bs_fn* is used.

⟨Prototype for *U_Find_Bs* 221⟩ ≡

```
void U_Find_Bs(struct measure_type m, struct invert_type *r)
```

This code is used in sections 211 and 222.

222. ⟨Definition for *U_Find_Bs* 222⟩ ≡

⟨Prototype for *U_Find_Bs* 221⟩

```
{
    double ax, bx, cx, fa, fb, fc, bs;
    if (Debug(DEBUG_SEARCH)) {
        fprintf(stderr, "In_U_Find_Bs");
        fprintf(stderr, "\_(\mu=%6.4f)", r→slab.cos_angle);
        if (r→default_ba ≠ UNINITIALIZED) fprintf(stderr, "\_\_default_ba=\_8.5f", r→default_ba);
        if (r→default_g ≠ UNINITIALIZED) fprintf(stderr, "\_\_default_g=\_8.5f", r→default_g);
        fprintf(stderr, "\n");
    }
    if (m.m.t ≡ 0) {
        r→slab.b = HUGE_VAL;
        U_Find_A(m, r);
        return;
    }
    r→slab.a = 0;
    r→slab.g = (r→default_g ≡ UNINITIALIZED) ? 0 : r→default_g;
    r→slab.b = (r→default_ba ≡ UNINITIALIZED) ? HUGE_VAL : r→default_ba;
    Set_Calc_State(m, *r); /* store ba in RR.slab.b */
    ax = b2bcalc(0.1); /* first try for bs */
    bx = b2bcalc(1.0);
    mnbrak(&ax, &bx, &cx, &fa, &fb, &fc, Find_Bs_fn);
    r→final_distance = brent(ax, bx, cx, Find_Bs_fn, r→tolerance, &bs); /* recover true values */
    r→slab.a = bcalc2b(bs)/(bcalc2b(bs) + r→slab.b);
    r→slab.b = bcalc2b(bs) + r→slab.b;
    ⟨Put final values in result 219⟩
}
```

This code is used in section 210.

223. Fixed Absorption and Scattering. Typically, this routine is called when the scattering coefficient is known, the anisotropy is known, and the physical thickness of the sample is known. This routine calculates the varies the absorption coefficient until the measurements are matched.

This is tricky only because the value in *slab.b* is used to hold the value of *bs* or $d \cdot \mu_s$ when the *Find_Ba_fn* is used.

⟨Prototype for *U_Find_Ba* 223⟩ ≡

```
void U_Find_Ba(struct measure_type m, struct invert_type *r)
```

This code is used in sections 211 and 224.

224. ⟨Definition for *U_Find_Ba* 224⟩ ≡

⟨Prototype for *U_Find_Ba* 223⟩

```
{
    double ax, bx, cx, fa, fb, fc, ba;
    if (Debug(DEBUG_SEARCH)) {
        fprintf(stderr, "In_U_Find_Bs");
        fprintf(stderr, "\_(\mu=%6.4f)", r→slab.cos_angle);
        if (r→default_bs ≠ UNINITIALIZED) fprintf(stderr, "\_default_bs=\_8.5f", r→default_bs);
        if (r→default_g ≠ UNINITIALIZED) fprintf(stderr, "\_default_g=\_8.5f", r→default_g);
        fprintf(stderr, "\n");
    }
    r→slab.a = 0;
    r→slab.g = (r→default_g ≡ UNINITIALIZED) ? 0 : r→default_g;
    r→slab.b = (r→default_bs ≡ UNINITIALIZED) ? HUGE_VAL : r→default_bs;
    if (m.m_t ≡ 0) {
        r→slab.b = HUGE_VAL;
        U_Find_A(m, r);
        return;
    }
    Set_Calc_State(m, *r); /* store bs in RR.slab.b */
    ax = b2bcalc(0.1); /* first try for ba */
    bx = b2bcalc(1.0);
    mnbrak(&ax, &bx, &cx, &fa, &fb, &fc, Find_Ba_fn);
    r→final_distance = brent(ax, bx, cx, Find_Ba_fn, r→tolerance, &ba); /* recover true values */
    r→slab.a = (r→slab.b) / (bcalc2b(ba) + r→slab.b);
    r→slab.b = bcalc2b(ba) + r→slab.b; /* actual value of b */
    ⟨Put final values in result 219⟩
}
```

This code is used in section 210.

225. Fixed Optical Depth and Anisotropy. Typically, this routine is called when the optical thickness is assumed infinite. However, it may also be called when the optical thickness is assumed to be fixed at a particular value. Typically the only reasonable situation for this to occur is when the diffuse transmission is non-zero but the collimated transmission is zero. If this is the case then there is no information in the collimated transmission measurement and there is no sense even using it because the slab is not infinitely thick.

⟨Prototype for *U_Find_A* 225⟩ ≡

```
void U_Find_A(struct measure_type m, struct invert_type *r)
```

This code is used in sections 211 and 226.

226. ⟨Definition for *U_Find_A* 226⟩ ≡

⟨Prototype for *U_Find_A* 225⟩

```
{
    double Rt, Tt, Rd, Rc, Td, Tc;
    if (Debug(DEBUG_SEARCH)) {
        fprintf(stderr, "In_U_Find_A");
        fprintf(stderr, "\u(mu=%6.4f)", r→slab.cos_angle);
        if (r→default_b ≠ UNINITIALIZED) fprintf(stderr, "\u\udefault_b\u=%8.5f", r→default_b);
        if (r→default_g ≠ UNINITIALIZED) fprintf(stderr, "\u\udefault_g\u=%8.5f", r→default_g);
        fprintf(stderr, "\n");
    }
    Estimate_RT(m, *r, &Rt, &Tt, &Rd, &Rc, &Td, &Tc);
    r→slab.g = (r→default_g ≡ UNINITIALIZED) ? 0 : r→default_g;
    r→slab.b = (r→default_b ≡ UNINITIALIZED) ? HUGE_VAL : r→default_b;
    r→slab.a = 0.0;
    r→final_distance = 0.0;
    Set_Calc_State(m, *r);
    if (Rt > 0.99999) {
        r→final_distance = Find_A_fn(a2acalc(1.0));
        r→slab.a = 1.0;
    }
    else {
        double x, ax, bx, cx, fa, fb, fc;
        ax = a2acalc(0.3);
        bx = a2acalc(0.5);
        mnbrak(&ax, &bx, &cx, &fa, &fb, &fc, Find_A_fn);
        r→final_distance = brent(ax, bx, cx, Find_A_fn, r→tolerance, &x);
        r→slab.a = acalc2a(x);
    }
    ⟨Put final values in result 219⟩
}
```

This code is used in section 210.

227. Fixed Optical Depth and Albedo.

⟨Prototype for *U_Find_G* 227⟩ ≡

```
void U_Find_G(struct measure_type m, struct invert_type *r)
```

This code is used in sections 211 and 228.

228. ⟨Definition for *U_Find_G* 228⟩ ≡

⟨Prototype for *U_Find_G* 227⟩

```
{
    double Rt, Tt, Rd, Rc, Td, Tc;
    if (Debug(DEBUG_SEARCH)) {
        fprintf(stderr, "In_U_Find_G");
        fprintf(stderr, "_(mu=%6.4f)", r→slab.cos_angle);
        if (r→default_a ≠ UNINITIALIZED) fprintf(stderr, "_(default_a=%8.5f)", r→default_a);
        if (r→default_b ≠ UNINITIALIZED) fprintf(stderr, "_(default_b=%8.5f)", r→default_b);
        fprintf(stderr, "\n");
    }
    Estimate_RT(m, *r, &Rt, &Tt, &Rd, &Rc, &Td, &Tc);
    r→slab.a = (r→default_a ≡ UNINITIALIZED) ? 0.5 : r→default_a;
    r→slab.b = (r→default_b ≡ UNINITIALIZED) ? HUGE_VAL : r→default_b;
    r→slab.g = 0.0;
    r→final_distance = 0.0;
    Set_Calc_State(m, *r);
    if (Rd > 0.0) {
        double x, ax, bx, cx, fa, fb, fc;
        ax = g2gcalc(−0.99);
        bx = g2gcalc(0.99);
        mnbrak(&ax, &bx, &cx, &fa, &fb, &fc, Find_G_fn);
        r→final_distance = brent(ax, bx, cx, Find_G_fn, r→tolerance, &x);
        r→slab.g = gcalc2g(x);
        Set_Calc_State(m, *r);
    }
    ⟨Put final values in result 219⟩
}
```

This code is used in section 210.

229. Fixed Anisotropy and Albedo. This routine can be called in three different situations: (1) the albedo is zero, (2) the albedo is one, or (3) the albedo is fixed at a default value. I calculate the individual reflections and transmissions to establish which of these cases we happen to have.

⟨Prototype for *U_Find_B* 229⟩ ≡

```
void U_Find_B(struct measure_type m, struct invert_type *r)
```

This code is used in sections 211 and 230.

230. ⟨Definition for *U_Find_B* 230⟩ ≡

⟨Prototype for *U_Find_B* 229⟩

```
{
    double Rt, Tt, Rd, Rc, Td, Tc;
    if (Debug(DEBUG_SEARCH)) {
        fprintf(stderr, "In_U_Find_B");
        fprintf(stderr, "\u(mu=%6.4f)", r→slab.cos_angle);
        if (r→default_a ≠ UNINITIALIZED) fprintf(stderr, "\u\udefault_a=\u%8.5f", r→default_a);
        if (r→default_g ≠ UNINITIALIZED) fprintf(stderr, "\u\udefault_g=\u%8.5f", r→default_g);
        fprintf(stderr, "\n");
    }
    Estimate_RT(m, *r, &Rt, &Tt, &Rd, &Rc, &Td, &Tc);
    r→slab.g = (r→default_g ≡ UNINITIALIZED) ? 0 : r→default_g;
    r→slab.a = (r→default_a ≡ UNINITIALIZED) ? 0 : r→default_a;
    r→slab.b = 0.5;
    r→final_distance = 0.0;
    Set_Calc_State(m, *r);
    ⟨Iteratively solve for b 231⟩
    ⟨Put final values in result 219⟩
    if (Debug(DEBUG_SEARCH)) {
        fprintf(stderr, "In_U_Find_B\ufinal\u(a,b,g)\u=\u");
        fprintf(stderr, "(\u%8.5f,\u%8.5f,\u%8.5f)\n", r→a, r→b, r→g);
    }
}
```

This code is used in section 210.

231. This could be improved tremendously. I just don't want to mess with it at the moment.

⟨Iteratively solve for *b* 231⟩ ≡

```
{
    double x, ax, bx, cx, fa, fb, fc;
    ax = b2bcalc(0.1);
    bx = b2bcalc(10);
    mnbrak(&ax, &bx, &cx, &fa, &fb, &fc, Find_B_fn);
    r→final_distance = brent(ax, bx, cx, Find_B_fn, r→tolerance, &x);
    r→slab.b = bcalc2b(x);
    Set_Calc_State(m, *r);
}
```

This code is used in section 230.

232. Fixed Optical Depth.

We can get here a couple of different ways.

First there can be three real measurements, i.e., t_c is not zero, in this case we want to fix b based on the t_c measurement.

Second, we can get here if a default value for b has been set.

Otherwise, we really should not be here. Just set $b = 1$ and calculate away.

⟨Prototype for *U_Find_AG* 232⟩ ≡

```
void U_Find_AG(struct measure_type m, struct invert_type *r)
```

This code is used in sections 211 and 233.

233. ⟨Definition for *U_Find_AG* 233⟩ ≡

⟨Prototype for *U_Find_AG* 232⟩

```
{
  ⟨Allocate local simplex variables 214⟩
  if (Debug(DEBUG_SEARCH)) {
    fprintf(stderr, "In U_Find_AG");
    fprintf(stderr, " (mu=%6.4f)", r→slab.cos_angle);
    if (r→default_b ≠ UNINITIALIZED) fprintf(stderr, " (default_b=%8.5f", r→default_b);
    fprintf(stderr, "\n");
  }
  if (m.num_measures ≡ 3) r→slab.b = What_Is_B(r→slab, m.m_u);
  else if (r→default_b ≡ UNINITIALIZED) r→slab.b = 1;
  else r→slab.b = r→default_b;
  Set_Calc_State(m, *r);
  ⟨Get the initial a, b, and g 215⟩
  ⟨Initialize the nodes of the a and g simplex 234⟩
  ⟨Evaluate the a and g simplex at the nodes 235⟩
  amoeba(p, y, 2, r→tolerance, Find_AG_fn, &r→iterations);
  ⟨Choose the best node of the a and g simplex 236⟩
  ⟨Free simplex data structures 220⟩
  ⟨Put final values in result 219⟩
}
```

This code is used in section 210.

234. \langle Initialize the nodes of the a and g simplex 234 $\rangle \equiv$

```

{
  int k, kk;
  p[1][1] = a2acalc(guess[0].a);
  p[1][2] = g2gcalc(guess[0].g);
  for (k = 1; k < 7; k++) {
    if (guess[0].a  $\neq$  guess[k].a) break;
  }
  p[2][1] = a2acalc(guess[k].a);
  p[2][2] = g2gcalc(guess[k].g);
  for (kk = 1; kk < 7; kk++) {
    if (kk  $\equiv$  k) continue;
    if (guess[0].g  $\neq$  guess[kk].g  $\vee$  guess[k].g  $\neq$  guess[kk].g) break;
  }
  p[3][1] = a2acalc(guess[kk].a);
  p[3][2] = g2gcalc(guess[kk].g);
  if (Debug(DEBUG_BEST_GUESS)) {
    fprintf(stderr, "guess_1");
    fprintf(stderr, "%10.5f_", guess[0].a);
    fprintf(stderr, "%10.5f_", guess[0].b);
    fprintf(stderr, "%10.5f_", guess[0].g);
    fprintf(stderr, "%10.5f\n", guess[0].distance);
    fprintf(stderr, "guess_2");
    fprintf(stderr, "%10.5f_", guess[k].a);
    fprintf(stderr, "%10.5f_", guess[k].b);
    fprintf(stderr, "%10.5f_", guess[k].g);
    fprintf(stderr, "%10.5f\n", guess[k].distance);
    fprintf(stderr, "guess_3");
    fprintf(stderr, "%10.5f_", guess[kk].a);
    fprintf(stderr, "%10.5f_", guess[kk].b);
    fprintf(stderr, "%10.5f_", guess[kk].g);
    fprintf(stderr, "%10.5f\n", guess[kk].distance);
  }
}

```

This code is used in section 233.

235. \langle Evaluate the a and g simplex at the nodes 235 $\rangle \equiv$

```

for (i = 1; i  $\leq$  3; i++) {
  x[1] = p[i][1];
  x[2] = p[i][2];
  y[i] = Find_AG_fn(x);
}

```

This code is used in section 233.

236. Here we find the node of the simplex that gave the best result and save that one. At the same time we save the whole simplex for later use if needed.

⟨ Choose the best node of the a and g simplex 236 ⟩ \equiv

```

     $r\text{-final\_distance} = 10;$ 
    for ( $i = 1; i \leq 3; i++$ ) {
        if ( $y[i] < r\text{-final\_distance}$ ) {
             $r\text{-slab}.a = a\text{calc}2a(p[i][1]);$ 
             $r\text{-slab}.g = g\text{calc}2g(p[i][2]);$ 
             $r\text{-final\_distance} = y[i];$ 
        }
    }

```

This code is used in section 233.

237. Fixed Albedo. Here the optical depth and the anisotropy are varied (for a fixed albedo).

⟨Prototype for *U_Find_BG* 237⟩ ≡

```
void U_Find_BG(struct measure_type m, struct invert_type *r)
```

This code is used in sections 211 and 238.

238. ⟨Definition for *U_Find_BG* 238⟩ ≡

⟨Prototype for *U_Find_BG* 237⟩

```
{
  ⟨Allocate local simplex variables 214⟩
  if (Debug(DEBUG_SEARCH)) {
    fprintf(stderr, "In U_Find_BG");
    fprintf(stderr, "\n(mu=%6.4f)", r_slab.cos_angle);
    if (r_default_a ≠ UNINITIALIZED) fprintf(stderr, "\n\ndefault_a=%8.5f", r_default_a);
    fprintf(stderr, "\n");
  }
  r_slab.a = (r_default_a ≡ UNINITIALIZED) ? 0 : r_default_a;
  Set_Calc_State(m, *r);
  ⟨Get the initial a, b, and g 215⟩
  ⟨Initialize the nodes of the b and g simplex 240⟩
  ⟨Evaluate the bg simplex at the nodes 241⟩
  amoeba(p, y, 2, r_tolerance, Find_BG_fn, &r_iterations);
  ⟨Choose the best node of the b and g simplex 242⟩
  ⟨Free simplex data structures 220⟩
  ⟨Put final values in result 219⟩
}
```

This code is used in section 210.

239. A very simple start for variation of *b* and *g*. This should work fine for the cases in which the absorption or scattering are fixed.

240. $\langle \text{Initialize the nodes of the } b \text{ and } g \text{ simplex } 240 \rangle \equiv$

```

{
  int k, kk;
  p[1][1] = b2bcalc(guess[0].b);
  p[1][2] = g2gcalc(guess[0].g);
  for (k = 1; k < 7; k++) {
    if (guess[0].b ≠ guess[k].b) break;
  }
  p[2][1] = b2bcalc(guess[k].b);
  p[2][2] = g2gcalc(guess[k].g);
  for (kk = 1; kk < 7; kk++) {
    if (kk ≡ k) continue;
    if (guess[0].g ≠ guess[kk].g ∨ guess[k].g ≠ guess[kk].g) break;
  }
  p[3][1] = b2bcalc(guess[kk].b);
  p[3][2] = g2gcalc(guess[kk].g);
  if (Debug(DEBUG_BEST_GUESS)) {
    fprintf(stderr, "guess_1");
    fprintf(stderr, "%10.5f_", guess[0].a);
    fprintf(stderr, "%10.5f_", guess[0].b);
    fprintf(stderr, "%10.5f_", guess[0].g);
    fprintf(stderr, "%10.5f\n", guess[0].distance);
    fprintf(stderr, "guess_2");
    fprintf(stderr, "%10.5f_", guess[k].a);
    fprintf(stderr, "%10.5f_", guess[k].b);
    fprintf(stderr, "%10.5f_", guess[k].g);
    fprintf(stderr, "%10.5f\n", guess[k].distance);
    fprintf(stderr, "guess_3");
    fprintf(stderr, "%10.5f_", guess[kk].a);
    fprintf(stderr, "%10.5f_", guess[kk].b);
    fprintf(stderr, "%10.5f_", guess[kk].g);
    fprintf(stderr, "%10.5f\n", guess[kk].distance);
  }
}

```

This code is used in section 238.

241. $\langle \text{Evaluate the } bg \text{ simplex at the nodes } 241 \rangle \equiv$

```

for (i = 1; i ≤ 3; i++) {
  x[1] = p[i][1];
  x[2] = p[i][2];
  y[i] = Find_BG_fn(x);
}

```

This code is used in section 238.

242. Here we find the node of the simplex that gave the best result and save that one. At the same time we save the whole simplex for later use if needed.

⟨ Choose the best node of the b and g simplex [242](#) ⟩ ≡

```

r-final_distance = 10;
for ( $i = 1; i \leq 3; i++$ ) {
  if ( $y[i] < r\text{-}final\_distance$ ) {
    r-slab.b = bcalc2b( $p[i][1]$ );
    r-slab.g = gcalc2g( $p[i][2]$ );
    r-final_distance =  $y[i]$ ;
  }
}
```

This code is used in section [238](#).

243. Fixed Scattering. Here I assume that a constant b_s ,

$$b_s = \mu_s d$$

where d is the physical thickness of the sample and μ_s is of course the absorption coefficient. This is just like *U_Find_BaG* except that $b_a = \mu_a d$ is varied instead of b .

⟨Prototype for *U_Find_BaG* 243⟩ ≡

```
void U_Find_BaG(struct measure_type m, struct invert_type *r)
```

This code is used in sections 211 and 244.

244. ⟨Definition for *U_Find_BaG* 244⟩ ≡

```
⟨Prototype for U_Find_BaG 243⟩
{
  ⟨Allocate local simplex variables 214⟩
  Set_Calc_State(m, *r);
  ⟨Get the initial a, b, and g 215⟩
  ⟨Initialize the nodes of the ba and g simplex 245⟩
  ⟨Evaluate the BaG simplex at the nodes 246⟩
  amoeba(p, y, 2, r-tolerance, Find_BaG_fn, &r-iterations);
  ⟨Choose the best node of the ba and g simplex 247⟩
  ⟨Free simplex data structures 220⟩
  ⟨Put final values in result 219⟩
}
```

This code is used in section 210.

245. ⟨Initialize the nodes of the *ba* and *g* simplex 245⟩ ≡

```
if (guess[0].b > r-default-bs) {
  p[1][1] = b2bcalc(guess[0].b - r-default-bs);
  p[2][1] = b2bcalc(2 * (guess[0].b - r-default-bs));
  p[3][1] = p[1][1];
}
else {
  p[1][1] = b2bcalc(0.0001);
  p[2][1] = b2bcalc(0.001);
  p[3][1] = p[1][1];
}
p[1][2] = g2gcalc(guess[0].g);
p[2][2] = p[1][2];
p[3][2] = g2gcalc(0.9 * guess[0].g + 0.05);
```

This code is used in section 244.

246. ⟨Evaluate the *BaG* simplex at the nodes 246⟩ ≡

```
for (i = 1; i ≤ 3; i++) {
  x[1] = p[i][1];
  x[2] = p[i][2];
  y[i] = Find_BaG_fn(x);
}
```

This code is used in section 244.

247. Here we find the node of the simplex that gave the best result and save that one. At the same time we save the whole simplex for later use if needed.

⟨ Choose the best node of the *ba* and *g* simplex 247 ⟩ ≡

```

    r→final_distance = 10;
    for (i = 1; i ≤ 3; i++) {
        if (y[i] < r→final_distance) {
            r→slab.b = bcalc2b(p[i][1]) + r→default_bs;
            r→slab.a = r→default_bs / r→slab.b;
            r→slab.g = gcalc2g(p[i][2]);
            r→final_distance = y[i];
        }
    }

```

This code is used in section 244.

248. Fixed Absorption. Here I assume that a constant b_a ,

$$b_a = \mu_a d$$

where d is the physical thickness of the sample and μ_a is of course the absorption coefficient. This is just like *U_Find_BG* except that $b_s = \mu_s d$ is varied instead of b .

⟨Prototype for *U_Find_BsG* 248⟩ ≡

```
void U_Find_BsG(struct measure_type m, struct invert_type *r)
```

This code is used in sections 211 and 249.

249. ⟨Definition for *U_Find_BsG* 249⟩ ≡

⟨Prototype for *U_Find_BsG* 248⟩

```
{
  ⟨Allocate local simplex variables 214⟩
  if (Debug(DEBUG_SEARCH)) {
    fprintf(stderr, "In_U_Find_BsG");
    fprintf(stderr, "\u(mu=%6.4f)", r→slab.cos_angle);
    if (r→default_ba ≠ UNINITIALIZED) fprintf(stderr, "\u\udefault_ba=\u%8.5f", r→default_ba);
    fprintf(stderr, "\n");
  }
  Set_Calc_State(m, *r);
  ⟨Get the initial a, b, and g 215⟩
  ⟨Initialize the nodes of the bs and g simplex 250⟩
  ⟨Evaluate the BsG simplex at the nodes 251⟩
  amoeba(p, y, 2, r→tolerance, Find_BsG_fn, &r→iterations);
  ⟨Choose the best node of the bs and g simplex 252⟩
  ⟨Free simplex data structures 220⟩
  ⟨Put final values in result 219⟩
}
```

This code is used in section 210.

250. ⟨Initialize the nodes of the *bs* and *g* simplex 250⟩ ≡

```
p[1][1] = b2bcalc(guess[0].b - r→default_ba);
p[1][2] = g2gcalc(guess[0].g);
p[2][1] = b2bcalc(2 * guess[0].b - 2 * r→default_ba);
p[2][2] = p[1][2];
p[3][1] = p[1][1];
p[3][2] = g2gcalc(0.9 * guess[0].g + 0.05);
```

This code is used in section 249.

251. ⟨Evaluate the *BsG* simplex at the nodes 251⟩ ≡

```
for (i = 1; i ≤ 3; i++) {
  x[1] = p[i][1];
  x[2] = p[i][2];
  y[i] = Find_BsG_fn(x);
}
```

This code is used in section 249.

252. \langle Choose the best node of the *bs* and *g* simplex [252](#) $\rangle \equiv$
 $r\text{-final_distance} = 10;$
for ($i = 1; i \leq 3; i++$) {
 if ($y[i] < r\text{-final_distance}$) {
 $r\text{-slab}.b = bcalc2b(p[i][1]) + r\text{-default_ba};$
 $r\text{-slab}.a = 1 - r\text{-default_ba}/r\text{-slab}.b;$
 $r\text{-slab}.g = gcalc2g(p[i][2]);$
 $r\text{-final_distance} = y[i];$
 }
}

This code is used in section [249](#).

253. IAD Utilities.

March 1995. Reincluded *quick_guess* code.

```

<iad_util.c 253> ≡
#include <math.h>
#include <float.h>
#include <stdio.h>
#include "nr_util.h"
#include "ad_globl.h"
#include "ad_frsnl.h"
#include "ad_bound.h"
#include "iad_type.h"
#include "iad_calc.h"
#include "iad_pub.h"
#include "iad_util.h"
    unsigned long g_util_debugging = 0;
    <Preprocessor definitions>
    <Definition for What_Is_B 256>
    <Definition for Estimate_RT 262>
    <Definition for a2acalc 268>
    <Definition for acalc2a 270>
    <Definition for g2gcalc 272>
    <Definition for gcalc2g 274>
    <Definition for b2bcalc 276>
    <Definition for bcalc2b 278>
    <Definition for twoprime 280>
    <Definition for twounprime 282>
    <Definition for abgg2ab 284>
    <Definition for abgb2ag 286>
    <Definition for quick_guess 293>
    <Definition for Set_Debugging 306>
    <Definition for Debug 308>
    <Definition for Print_Invert_Type 310>
    <Definition for Print_Measure_Type 312>

```

254. <iad_util.h 254> ≡

```

    <Prototype for What_Is_B 255>;
    <Prototype for Estimate_RT 261>;
    <Prototype for a2acalc 267>;
    <Prototype for acalc2a 269>;
    <Prototype for g2gcalc 271>;
    <Prototype for gcalc2g 273>;
    <Prototype for b2bcalc 275>;
    <Prototype for bcalc2b 277>;
    <Prototype for twoprime 279>;
    <Prototype for twounprime 281>;
    <Prototype for abgg2ab 283>;
    <Prototype for abgb2ag 285>;
    <Prototype for quick_guess 292>;
    <Prototype for Set_Debugging 305>;
    <Prototype for Debug 307>;
    <Prototype for Print_Invert_Type 309>;
    <Prototype for Print_Measure_Type 311>;

```

255. Finding optical thickness.

This routine figures out what the optical thickness of a slab based on the index of refraction of the slab and the amount of collimated light that gets through it.

It should be pointed out right here in the front that this routine does not work for diffuse irradiance, but then the whole concept of estimating the optical depth for diffuse irradiance is bogus anyway.

In version 1.3 changed all error output to *stderr*. Version 1.4 included cases involving absorption in the boundaries.

```
#define BIG_A_VALUE 999999.0
#define SMALL_A_VALUE 0.000001
⟨Prototype for What_Is_B 255⟩ ≡
    double What_Is_B(struct AD_slab_type slab, double Tc)
```

This code is used in sections 254 and 256.

```
256. ⟨Definition for What_Is_B 256⟩ ≡
    ⟨Prototype for What_Is_B 255⟩
    {
        double r1, r2, t1, t2, mu_in_slab;
        ⟨Calculate specular reflection and transmission 257⟩
        ⟨Check for bad values of Tc 258⟩
        ⟨Solve if multiple internal reflections are not present 259⟩
        ⟨Find thickness when multiple internal reflections are present 260⟩
    }
```

This code is used in section 253.

257. The first thing to do is to find the specular reflection for light interacting with the top and bottom air-glass-sample interfaces. I make a simple check to ensure that the the indices are different before calculating the bottom reflection. Most of the time the $r1 \equiv r2$, but there are always those annoying special cases.

```
⟨Calculate specular reflection and transmission 257⟩ ≡
    Absorbing_Glass_RT(1.0, slab.n_top_slide, slab.n_slab, slab.cos_angle, slab.b_top_slide, &r1, &t1);
    mu_in_slab = Cos_Snell(1.0, slab.cos_angle, slab.n_slab);
    Absorbing_Glass_RT(slab.n_slab, slab.n_bottom_slide, 1.0, mu_in_slab, slab.b_bottom_slide, &r2, &t2);
```

This code is used in section 256.

258. Bad values for the unscattered transmission are those that are non-positive, those greater than one, and those greater than are possible in a non-absorbing medium, i.e.,

$$T_c > \frac{t_1 t_2}{1 - r_1 r_2}$$

Since this routine has no way to report errors, I just set the optical thickness to the natural values in these cases.

```
⟨Check for bad values of Tc 258⟩ ≡
    if (Tc ≤ 0) return (HUGE_VAL);
    if (Tc ≥ t1 * t2 / (1 - r1 * r2)) return (0.001);
```

This code is used in section 256.

259. If either $r1$ or $r2 \equiv 0$ then things are very simple because the sample does not sustain multiple internal reflections and the unscattered transmission is

$$T_c = t_1 t_2 \exp(-b/\nu)$$

where b is the optical thickness and ν is `slab.cos_angle`. Clearly,

$$b = -\nu \ln \left(\frac{T_c}{t_1 t_2} \right)$$

⟨Solve if multiple internal reflections are not present 259⟩ ≡

if ($r1 \equiv 0 \vee r2 \equiv 0$) **return** ($-slab.cos_angle * \log(Tc/t1/t2)$);

This code is used in section 256.

260. Well I kept putting it off, but now comes the time to solve the following equation for b

$$T_c = \frac{t_1 t_2 \exp(-b)}{1 - r_1 r_2 \exp(-2b)}$$

We note immediately that this is a quadratic equation in $x = \exp(-b)$.

$$r_1 r_2 T_c x^2 + t_1 t_2 x - T_c = 0$$

Sufficient tests have been made above to ensure that none of the coefficients are exactly zero. However, it is clear that the leading quadratic term has a much smaller coefficient than the other two. Since r_1 and r_2 are typically about four percent the product is roughly 10^{-3} . The collimated transmission can be very small and this makes things even worse. A further complication is that we need to choose the only positive root.

Now the roots of $ax^2 + bx + c = 0$ can be found using the standard quadratic formula,

$$x = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$$

This is very bad for small values of a . Instead I use

$$q = -\frac{1}{2} \left[b + \text{sgn}(b) \sqrt{b^2 - 4ac} \right]$$

with the two roots

$$x = \frac{q}{a} \quad \text{and} \quad x = \frac{c}{q}$$

Substituting our coefficients

$$q = -\frac{1}{2} \left[t_1 t_2 + \sqrt{t_1^2 t_2^2 + 4r_1 r_2 T_c^2} \right]$$

With some algebra, this can be shown to be

$$q = -t_1 t_2 \left[1 + \frac{r_1 r_2 T_c^2}{t_1^2 t_2^2} + \dots \right]$$

The only positive root is $x = -T_c/q$. Therefore

$$x = \frac{2T_c}{t_1 t_2 + \sqrt{t_1^2 t_2^2 + 4r_1 r_2 T_c^2}}$$

(Not very pretty, but straightforward enough.)

⟨Find thickness when multiple internal reflections are present 260⟩ ≡

```
{
  double B;
  B = t1 * t2;
  return (-slab.cos_angle * log(2 * Tc / (B + sqrt(B * B + 4 * Tc * Tc * r1 * r2))));
}
```

This code is used in section 256.

261. Estimating R and T.

In several places, it is useful to know an *estimate* for the values of the reflection and transmission of the sample based on the measurements. This routine provides such an estimate, but it currently ignores anything corrections that might be made for the integrating spheres.

Good values are only really obtainable when *num_measures* \equiv 3, otherwise we need to make pretty strong assumptions about the reflection and transmission values. If *num_measures* < 3, then we will assume that no collimated light makes it all the way through the sample. The specular reflection is then just that for a semi-infinite sample and *Tc* = 0. If *num_measures* \equiv 1, then *Td* is also set to zero.

rt total reflection
rc primary or specular reflection
rd diffuse or scattered reflection
tt total transmission
tp primary or unscattered transmission
td diffuse or scattered transmission

⟨Prototype for *Estimate_RT* 261⟩ \equiv

```
void Estimate_RT(struct measure_type m, struct invert_type r, double *rt, double *tt, double
                 *rd, double *rc, double *td, double *tc)
```

This code is used in sections 254 and 262.

262. ⟨Definition for *Estimate_RT* 262⟩ \equiv

⟨Prototype for *Estimate_RT* 261⟩

```
{
    ⟨Calculate the unscattered transmission and reflection 263⟩
    ⟨Estimate the backscattered reflection 264⟩
    ⟨Estimate the scattered transmission 265⟩
}
```

This code is used in section 253.

263. If there are three measurements then the specular reflection can be calculated pretty well. If there are fewer then the unscattered transmission is assumed to be zero. This is not necessarily the case, but after all, this routine only makes estimates of the various reflection and transmission quantities.

If there are three measurements, the optical thickness of the sample is required. Of course if there are three measurements then the illumination must be collimated and we can call *What_Is_B* to find out the optical thickness. We pass this value to a routine in the **fresnel.h** unit and sit back and wait.

All the above is true if sphere corrections are not needed. Now, we just fob this off on another function.

⟨Calculate the unscattered transmission and reflection 263⟩ \equiv

```
Calculate_Minimum_MR(m, r, rc, tc);
```

This code is used in section 262.

264. Finding the diffuse reflection is now just a matter of checking whether V1% contains the specular reflection from the sample or not and then just adding or subtracting the specular reflection as appropriate.

⟨ Estimate the backscattered reflection 264 ⟩ ≡

```

if (m.fraction_of_rc_in_mr) {
    *rt = m.m_r;
    *rd = *rt - m.fraction_of_rc_in_mr * (*rc);
    if (*rd < 0) {
        *rd = 0;
        *rc = *rt;
    }
}
else {
    *rd = m.m_r;
    *rt = *rd + *rc;
}
if (Debug(DEBUG_SEARCH)) {
    fprintf(stderr, "uuuuuuuuuurt=%.5f\n", *rt);
    fprintf(stderr, "uuuuestrd=%.5f\n", *rd);
}

```

This code is used in section 262.

265. The transmission values follow in much the same way as the diffuse reflection values — just subtract the specular transmission from the total transmission.

⟨ Estimate the scattered transmission 265 ⟩ ≡

```

if (m.num_measures == 1) {
    *tt = 0.0;
    *td = 0.0;
}
else if (m.fraction_of_tc_in_mt) {
    *tt = m.m_t;
    *td = *tt - *tc;
    if (*td < 0) {
        *tc = *tt;
        *td = 0;
    }
}
else {
    *td = m.m_t;
    *tt = *td + *tc;
}
if (Debug(DEBUG_SEARCH)) {
    fprintf(stderr, "uuuuuuuuuutt=%.5f\n", *tt);
    fprintf(stderr, "uuuuesttd=%.5f\n", *td);
}

```

This code is used in section 262.

266. Transforming properties. Routines to convert optical properties to calculation space and back.

267. *a2acalc* is used for the albedo transformations according to

$$a_{calc} = \frac{2a - 1}{a(1 - a)}$$

Care is taken to avoid division by zero. Why was this function chosen? Well mostly because it maps the region between $[0, 1] \rightarrow (-\infty, +\infty)$.

⟨Prototype for *a2acalc* 267⟩ \equiv
double a2acalc(double a)

This code is used in sections 254 and 268.

268. ⟨Definition for *a2acalc* 268⟩ \equiv
 ⟨Prototype for *a2acalc* 267⟩
 {
 if ($a \leq 0$) **return** `-BIG_A_VALUE`;
 if ($a \geq 1$) **return** `BIG_A_VALUE`;
 return $((2 * a - 1) / a / (1 - a))$;
 }

This code is used in section 253.

269. *acalc2a* is used for the albedo transformations Now when we solve

$$a_{calc} = \frac{2a - 1}{a(1 - a)}$$

we obtain the quadratic equation

$$a_{calc}a^2 + (2 - a_{calc})a - 1 = 0$$

The only root of this equation between zero and one is

$$a = \frac{-2 + a_{calc} + \sqrt{a_{calc}^2 + 4}}{2a_{calc}}$$

I suppose that I should spend the time to recast this using the more appropriate numerical solutions of the quadratic equation, but this worked and I will leave it as it is for now.

⟨Prototype for *acalc2a* 269⟩ \equiv
double acalc2a(double acalc)

This code is used in sections 254 and 270.

270. ⟨Definition for *acalc2a* 270⟩ \equiv
 ⟨Prototype for *acalc2a* 269⟩
 {
 if ($acalc \equiv \text{BIG_A_VALUE}$) **return** 1.0;
 else if ($acalc \equiv -\text{BIG_A_VALUE}$) **return** 0.0;
 else if ($fabs(acalc) < \text{SMALL_A_VALUE}$) **return** 0.5;
 else return $((-2 + a_{calc} + \text{sqrt}(acalc * a_{calc} + 4)) / (2 * a_{calc}))$;
 }

This code is used in section 253.

271. *g2gcalc* is used for the anisotropy transformations according to

$$g_{calc} = \frac{g}{1 + |g|}$$

which maps $(-1, 1) \rightarrow (-\infty, +\infty)$.

⟨Prototype for *g2gcalc* 271⟩ ≡

double g2gcalc(double g)

This code is used in sections 254 and 272.

272. ⟨Definition for *g2gcalc* 272⟩ ≡

⟨Prototype for *g2gcalc* 271⟩

```
{
    if (g ≤ -1) return (-HUGE_VAL);
    if (g ≥ 1) return (HUGE_VAL);
    return (g/(1 - fabs(g)));
}
```

This code is used in section 253.

273. *gcalc2g* is used for the anisotropy transformations it is the inverse of *g2gcalc*. The relation is

$$g = \frac{g_{calc}}{1 + |g_{calc}|}$$

⟨Prototype for *gcalc2g* 273⟩ ≡

double gcalc2g(double gcalc)

This code is used in sections 254 and 274.

274. ⟨Definition for *gcalc2g* 274⟩ ≡

⟨Prototype for *gcalc2g* 273⟩

```
{
    if (gcalc ≡ -HUGE_VAL) return -1.0;
    if (gcalc ≡ HUGE_VAL) return 1.0;
    return (gcalc/(1 + fabs(gcalc)));
}
```

This code is used in section 253.

275. *b2bcalc* is used for the optical depth transformations it is the inverse of *bcalc2b*. The relation is

$$b_{calc} = \ln(b)$$

The only caveats are to ensure that I don't take the logarithm of something big or non-positive.

⟨Prototype for *b2bcalc* 275⟩ ≡

double b2bcalc(double b)

This code is used in sections 254 and 276.

276. $\langle \text{Definition for } b2bcalc \text{ 276} \rangle \equiv$
 $\langle \text{Prototype for } b2bcalc \text{ 275} \rangle$

```
{
    if (b  $\equiv$  HUGE_VAL) return HUGE_VAL;
    if (b  $\leq$  0) return 0.0;
    return (log(b));
}
```

This code is used in section 253.

277. *bcalc2b* is used for the anisotropy transformations it is the inverse of *b2bcalc*. The relation is

$$b = \exp(b_{calc})$$

The only tricky part is to ensure that I don't exponentiate something big and get an overflow error. In ANSI C the maximum value for x such that 10^x is in the range of representable finite floating point numbers (for doubles) is given by DBL_MAX_10_EXP. Thus if we want to know if

$$e^{b_{calc}} > 10^x$$

or

$$b_{calc} > x \ln(10) \approx 2.3x$$

and this is the criterion that I use.

$\langle \text{Prototype for } bcalc2b \text{ 277} \rangle \equiv$
double *bcalc2b*(**double** *bcalc*)

This code is used in sections 254 and 278.

278. $\langle \text{Definition for } bcalc2b \text{ 278} \rangle \equiv$
 $\langle \text{Prototype for } bcalc2b \text{ 277} \rangle$

```
{
    if (bcalc  $\equiv$  HUGE_VAL) return HUGE_VAL;
    if (bcalc > 2.3 * DBL_MAX_10_EXP) return HUGE_VAL;
    return (exp(bcalc));
}
```

This code is used in section 253.

279. *twoprime* converts the true albedo a , optical depth b to the reduced albedo ap and reduced optical depth bp that correspond to $g = 0$.

$\langle \text{Prototype for } twoprime \text{ 279} \rangle \equiv$
void *twoprime*(**double** a , **double** b , **double** g , **double** $*ap$, **double** $*bp$)

This code is used in sections 254 and 280.

280. $\langle \text{Definition for } twoprime \text{ 280} \rangle \equiv$
 $\langle \text{Prototype for } twoprime \text{ 279} \rangle$

```
{
    if ( $a \equiv 1 \wedge g \equiv 1$ ) *ap = 0.0;
    else *ap = (1 - g) * a / (1 - a * g);
    if (b  $\equiv$  HUGE_VAL) *bp = HUGE_VAL;
    else *bp = (1 - a * g) * b;
}
```

This code is used in section 253.

281. *twounprime* converts the reduced albedo *ap* and reduced optical depth *bp* (for $g = 0$) to the true albedo *a* and optical depth *b* for an anisotropy *g*.

⟨Prototype for *twounprime* 281⟩ \equiv

```
void twounprime(double ap, double bp, double g, double *a, double *b)
```

This code is used in sections 254 and 282.

282. ⟨Definition for *twounprime* 282⟩ \equiv

⟨Prototype for *twounprime* 281⟩

```
{
    *a = ap / (1 - g + ap * g);
    if (bp  $\equiv$  HUGE_VAL) *b = HUGE_VAL;
    else *b = (1 + ap * g / (1 - g)) * bp;
}
```

This code is used in section 253.

283. *abgg2ab* assume *a*, *b*, *g*, and *g1* are given this does the similarity translation that you would expect it should by converting it to the reduced optical properties and then transforming back using the new value of *g*

⟨Prototype for *abgg2ab* 283⟩ \equiv

```
void abgg2ab(double a1, double b1, double g1, double g2, double *a2, double *b2)
```

This code is used in sections 254 and 284.

284. ⟨Definition for *abgg2ab* 284⟩ \equiv

⟨Prototype for *abgg2ab* 283⟩

```
{
    double a, b;
    twoprime(a1, b1, g1, &a, &b);
    twounprime(a, b, g2, a2, b2);
}
```

This code is used in section 253.

285. *abgb2ag* translates reduced optical properties to unreduced values assuming that the new optical thickness is given i.e., *a1* and *b1* are *a'* and *b'* for $g = 0$. This routine then finds the appropriate anisotropy and albedo which correspond to an optical thickness *b2*.

If both *b1* and *b2* are zero then just assume $g = 0$ for the unreduced values.

⟨Prototype for *abgb2ag* 285⟩ \equiv

```
void abgb2ag(double a1, double b1, double b2, double *a2, double *g2)
```

This code is used in sections 254 and 286.

286. $\langle \text{Definition for } abgb2ag \text{ } 286 \rangle \equiv$
 $\langle \text{Prototype for } abgb2ag \text{ } 285 \rangle$
 {
 if ($b1 \equiv 0 \vee b2 \equiv 0$) {
 $*a2 = a1$;
 $*g2 = 0$;
 }
 if ($b2 < b1$) $b2 = b1$;
 if ($a1 \equiv 0$) $*a2 = 0.0$;
 else {
 if ($a1 \equiv 1$) $*a2 = 1.0$;
 else {
 if ($b1 \equiv 0 \vee b2 \equiv \text{HUGE_VAL}$) $*a2 = a1$;
 else $*a2 = 1 + b1/b2 * (a1 - 1)$;
 }
 }
 if ($*a2 \equiv 0 \vee b2 \equiv 0 \vee b2 \equiv \text{HUGE_VAL}$) $*g2 = 0.5$;
 else $*g2 = (1 - b1/b2)/(a2)$;
 }

This code is used in section 253.

287. Guessing an inverse.

This routine is not used anymore.

⟨Prototype for *slow_guess* 287⟩ ≡

```
void slow_guess(struct measure_type m, struct invert_type *r, double *a, double *b, double *g)
```

This code is used in section 288.

288. ⟨Definition for *slow_guess* 288⟩ ≡

⟨Prototype for *slow_guess* 287⟩

```
{
  double fmin = 10.0;
  double fval;
  double *x;
  x = dvector(1, 2);
  switch (r→search) {
  case FIND_A: ⟨Slow guess for a alone 289⟩
    break;
  case FIND_B: ⟨Slow guess for b alone 290⟩
    break;
  case FIND_AB: case FIND_AG: ⟨Slow guess for a and b or a and g 291⟩
    break;
  }
  *a = r→slab.a;
  *b = r→slab.b;
  *g = r→slab.g;
  free_dvector(x, 1, 2);
}
```

289. ⟨Slow guess for *a* alone 289⟩ ≡

```
r→slab.b = HUGE_VAL;
r→slab.g = r→default_g;
Set_Calc_State(m, *r);
for (r→slab.a = 0.0; r→slab.a ≤ 1.0; r→slab.a += 0.1) {
  fval = Find_A_fn(a2acalc(r→slab.a));
  if (fval < fmin) {
    r→a = r→slab.a;
    fmin = fval;
  }
}
r→slab.a = r→a;
```

This code is used in section 288.

290. Presumably the only time that this will need to be called is when the albedo is fixed or is one. For now, I'll just assume that it is one.

```

⟨ Slow guess for b alone 290 ⟩ ≡
  r→slab.a = 1;
  r→slab.g = r→default_g;
  Set_Calc_State(m, *r);
  for (r→slab.b = 1/32.0; r→slab.b ≤ 32; r→slab.b *= 2) {
    fval = Find_B_fn(b2bcalc(r→slab.b));
    if (fval < fmin) {
      r→b = r→slab.b;
      fmin = fval;
    }
  }
  r→slab.b = r→b;

```

This code is used in section 288.

```

291. ⟨ Slow guess for a and b or a and g 291 ⟩ ≡
{
  double min_a, min_b, min_g;
  if (¬ Valid_Grid(m, r→search)) Fill_Grid(m, *r);
  Near_Grid_Points(m.m_r, m.m_t, r→search, &min_a, &min_b, &min_g);
  r→slab.a = min_a;
  r→slab.b = min_b;
  r→slab.g = min_g;
}

```

This code is used in section 288.

```

292. ⟨ Prototype for quick_guess 292 ⟩ ≡
  void quick_guess(struct measure_type m, struct invert_type r, double *a, double *b, double *g)

```

This code is used in sections 254 and 293.

```

293. ⟨ Definition for quick_guess 293 ⟩ ≡
⟨ Prototype for quick_guess 292 ⟩
{
  double UR1, UT1, rd, td, tc, rc, bprime, aprime, alpha, beta, logr;
  Estimate_RT(m, r, &UR1, &UT1, &rd, &rc, &td, &tc);
  ⟨ Estimate aprime 294 ⟩
  switch (m.num_measures) {
  case 1: ⟨ Guess when only reflection is known 296 ⟩
    break;
  case 2: ⟨ Guess when reflection and transmission are known 297 ⟩
    break;
  case 3: ⟨ Guess when all three measurements are known 298 ⟩
    break;
  }
  ⟨ Clean up guesses 303 ⟩
}

```

This code is used in section 253.

294. $\langle \text{Estimate } a_{\text{prime}} \text{ 294} \rangle \equiv$
 if (UT1 \equiv 1) $a_{\text{prime}} = 1.0$;
 else if ($rd/(1 - UT1) \geq 0.1$) {
 double $tmp = (1 - rd - UT1)/(1 - UT1)$;
 $a_{\text{prime}} = 1 - 4.0/9.0 * tmp * tmp$;
 }
 else if ($rd < 0.05 \wedge UT1 < 0.4$) $a_{\text{prime}} = 1 - (1 - 10 * rd) * (1 - 10 * rd)$;
 else if ($rd < 0.1 \wedge UT1 < 0.4$) $a_{\text{prime}} = 0.5 + (rd - 0.05) * 4$;
 else {
 double $tmp = (1 - 4 * rd - UT1)/(1 - UT1)$;
 $a_{\text{prime}} = 1 - tmp * tmp$;
 }

This code is used in section 293.

295. $\langle \text{Estimate } b_{\text{prime}} \text{ 295} \rangle \equiv$
 if ($rd < 0.01$) {
 $b_{\text{prime}} = \text{What_Is_B}(r.\text{slab}, UT1)$;
 $fprintf(stderr, "low_rd<0.01!_ut1=\%f_a_{\text{prime}}=\%f_b_{\text{prime}}=\%f\n", UT1, a_{\text{prime}}, b_{\text{prime}})$;
 }
 else if ($UT1 \leq 0$) $b_{\text{prime}} = \text{HUGE_VAL}$;
 else if ($UT1 > 0.1$) $b_{\text{prime}} = 2 * \exp(5 * (rd - UT1) * \log(2.0))$;
 else {
 $alpha = 1/\log(0.05/1.0)$;
 $beta = \log(1.0)/\log(0.05/1.0)$;
 $logr = \log(UR1)$;
 $b_{\text{prime}} = \log(UT1) - beta * \log(0.05) + beta * logr$;
 $b_{\text{prime}} /= alpha * \log(0.05) - alpha * logr - 1$;
 }

This code is used in sections 297, 301, and 302.

296.

$\langle \text{Guess when only reflection is known 296} \rangle \equiv$
 $*g = r.\text{default_g}$;
 $*a = a_{\text{prime}}/(1 - *g + a_{\text{prime}} * (*g))$;
 $*b = \text{HUGE_VAL}$;

This code is used in section 293.

297. $\langle \text{Guess when reflection and transmission are known 297} \rangle \equiv$
 $\langle \text{Estimate } b_{\text{prime}} \text{ 295} \rangle$
 $*g = r.\text{default_g}$;
 $*a = a_{\text{prime}}/(1 - *g + a_{\text{prime}} * *g)$;
 $*b = b_{\text{prime}}/(1 - *a * *g)$;

This code is used in section 293.

298. $\langle \text{Guess when all three measurements are known } 298 \rangle \equiv$
`switch (r.search) {`
`case FIND_A: $\langle \text{Guess when finding albedo } 299 \rangle$`
`break;`
`case FIND_B: $\langle \text{Guess when finding optical depth } 300 \rangle$`
`break;`
`case FIND_AB: $\langle \text{Guess when finding the albedo and optical depth } 301 \rangle$`
`break;`
`case FIND_AG: $\langle \text{Guess when finding anisotropy and albedo } 302 \rangle$`
`break;`
`}`

This code is used in section 293.

299.

$\langle \text{Guess when finding albedo } 299 \rangle \equiv$
`*g = r.default_g;`
`*a = aprime / (1 - *g + aprime * *g);`
`*b = What_Is_B(r.slabs, m.m_u);`

This code is used in section 298.

300.

$\langle \text{Guess when finding optical depth } 300 \rangle \equiv$
`*g = r.default_g;`
`*a = 0.0;`
`*b = What_Is_B(r.slabs, m.m_u);`

This code is used in section 298.

301.

$\langle \text{Guess when finding the albedo and optical depth } 301 \rangle \equiv$
`*g = r.default_g;`
`if (*g \equiv 1) *a = 0.0;`
`else *a = aprime / (1 - *g + aprime * *g);`
 $\langle \text{Estimate } b_{\text{prime}} 295 \rangle$
`if (bprime \equiv HUGE_VAL \vee *a * *g \equiv 1) *b = HUGE_VAL;`
`else *b = bprime / (1 - *a * *g);`

This code is used in section 298.

302.

$\langle \text{Guess when finding anisotropy and albedo } 302 \rangle \equiv$
`*b = What_Is_B(r.slabs, m.m_u);`
`if (*b \equiv HUGE_VAL \vee *b \equiv 0) {`
`*a = aprime;`
`*g = r.default_g;`
`}`
`else {`
 $\langle \text{Estimate } b_{\text{prime}} 295 \rangle$
`*a = 1 + bprime * (aprime - 1) / (*b);`
`if (*a < 0.1) *g = 0.0;`
`else *g = (1 - bprime / (*b)) / (*a);`
`}`

This code is used in section 298.

303.

```
⟨ Clean up guesses 303 ⟩ ≡  
  if (*a < 0) *a = 0.0;  
  if (*g < 0) *g = 0.0;  
  else if (*g ≥ 1) *g = 0.5;
```

This code is used in section 293.

304. Some debugging stuff.

305. \langle Prototype for *Set_Debugging* 305 $\rangle \equiv$
void *Set_Debugging*(**unsigned long** *debug_level*)

This code is used in sections 254 and 306.

306.

\langle Definition for *Set_Debugging* 306 $\rangle \equiv$
 \langle Prototype for *Set_Debugging* 305 \rangle
{
 g_util_debugging = *debug_level*;
}

This code is used in section 253.

307.

\langle Prototype for *Debug* 307 $\rangle \equiv$
int *Debug*(**unsigned long** *mask*)

This code is used in sections 254 and 308.

308.

\langle Definition for *Debug* 308 $\rangle \equiv$
 \langle Prototype for *Debug* 307 \rangle
{
 if (*g_util_debugging* & *mask*) **return** 1;
 else return 0;
}

This code is used in section 253.

309.

\langle Prototype for *Print_Invert_Type* 309 $\rangle \equiv$
void *Print_Invert_Type*(**struct invert_type** *r*)

This code is used in sections 254 and 310.

310.

\langle Definition for *Print_Invert_Type* 310 $\rangle \equiv$
 \langle Prototype for *Print_Invert_Type* 309 \rangle
{
 fprintf(*stderr*, "\n");
 fprintf(*stderr*, "default_ua=%10.5fubb=%10.5fuuug=%10.5f\n", *r.default_a*, *r.default_b*, *r.default_g*);
 fprintf(*stderr*, "slabuuua=%10.5fubb=%10.5fuuug=%10.5f\n", *r.slab.a*, *r.slab.b*, *r.slab.g*);
 fprintf(*stderr*, "n_uuuuutop=%10.5f_uuid=%10.5f_uubot=%10.5f\n", *r.slab.n_top_slide*, *r.slab.n_slab*,
 r.slab.n_bottom_slide);
 fprintf(*stderr*, "thick_uutop=%10.5f_ucos=%10.5f_uubot=%10.5f\n", *r.slab.b_top_slide*, *r.slab.cos_angle*,
 r.slab.b_bottom_slide);
 fprintf(*stderr*, "search_u=%d_uquadrature_upts_u=%d\n", *r.search*, *r.method.quad_pts*);
}

This code is used in section 253.

311.

⟨Prototype for *Print_Measure_Type* 311⟩ ≡

```
void Print_Measure_Type(struct measure_type m)
```

This code is used in sections 254 and 312.

312.

⟨Definition for *Print_Measure_Type* 312⟩ ≡

⟨Prototype for *Print_Measure_Type* 311⟩

```
{
    fprintf(stderr, "\n");
    fprintf(stderr, "#Beam_diameter=%7.1f_mm\n", m.d_beam);
    fprintf(stderr, "#Sample_thickness=%7.1f_mm\n", m.slab_thickness);
    fprintf(stderr, "#Top_slide_thickness=%7.1f_mm\n",
        m.slab_top_slide_thickness);
    fprintf(stderr, "#Bottom_slide_thickness=%7.1f_mm\n",
        m.slab_bottom_slide_thickness);
    fprintf(stderr, "#Sample_index_of_refraction=%7.3f\n", m.slab_index);
    fprintf(stderr, "#Top_slide_index_of_refraction=%7.3f\n", m.slab_top_slide_index);
    fprintf(stderr, "#Bottom_slide_index_of_refraction=%7.3f\n", m.slab_bottom_slide_index);
    fprintf(stderr, "#Fraction_unscattered_light_in_M_R=%7.1f%%\n",
        m.fraction_of_rc_in_mr * 100);
    fprintf(stderr, "#Fraction_unscattered_light_in_M_T=%7.1f%%\n",
        m.fraction_of_tc_in_mt * 100);
    fprintf(stderr, "#\n");
    fprintf(stderr, "#Reflection_sphere\n");
    fprintf(stderr, "#sphere_diameter=%7.1f_mm\n", m.d_sphere_r);
    fprintf(stderr, "#sample_port_diameter=%7.1f_mm\n",
        2 * m.d_sphere_r * sqrt(m.as_r));
    fprintf(stderr, "#entrance_port_diameter=%7.1f_mm\n",
        2 * m.d_sphere_r * sqrt(m.ae_r));
    fprintf(stderr, "#detector_port_diameter=%7.1f_mm\n",
        2 * m.d_sphere_r * sqrt(m.ad_r));
    fprintf(stderr, "#wall_reflectance=%7.1f%%\n", m.rw_r * 100);
    fprintf(stderr, "#standard_reflectance=%7.1f%%\n", m.rstd_r * 100);
    fprintf(stderr, "#detector_reflectance=%7.1f%%\n", m.rd_r * 100);
    fprintf(stderr, "#spheres=%7d\n", m.num_spheres);
    fprintf(stderr, "#measures=%7d\n", m.num_measures);
    fprintf(stderr, "#method=%7d\n", m.method);
    fprintf(stderr, "area_r_as=%10.5f_ad=%10.5f_ae=%10.5f_aw=%10.5f\n", m.as_r, m.ad_r,
        m.ae_r, m.aw_r);
    fprintf(stderr, "refls_rd=%10.5f_rw=%10.5f_rstd=%10.5f_rf=%10.5f\n", m.rd_r, m.rw_r,
        m.rstd_r, m.f_r);
    fprintf(stderr, "area_t_as=%10.5f_ad=%10.5f_ae=%10.5f_aw=%10.5f\n", m.as_t, m.ad_t,
        m.ae_t, m.aw_t);
    fprintf(stderr, "refls_td=%10.5f_rw=%10.5f_rstd=%10.5f_rf=%10.5f\n", m.rd_t, m.rw_t,
        m.rstd_t, m.f_t);
    fprintf(stderr, "lost_ur1=%10.5f_ut1=%10.5f_uuru=%10.5f_uutu=%10.5f\n", m.ur1_lost,
        m.ut1_lost, m.utu_lost, m.utu_lost);
}
```

This code is used in section 253.

313. Index. Here is a cross-reference table for the inverse adding-doubling program. All sections in which an identifier is used are listed with that identifier, except that reserved words are indexed only when they appear in format definitions, and the appearances of identifiers in section names are not indexed. Underlined entries correspond to where the identifier was declared. Error messages and a few other things like “ASCII code dependencies” are indexed here too.

`_CRT_NONSTDC_NO_WARNINGS`: [3](#).
`_CRT_SECURE_NO_WARNINGS`: [3](#), [94](#).
`a`: [30](#), [42](#), [43](#), [69](#), [86](#), [148](#), [156](#), [161](#), [267](#), [279](#),
[281](#), [284](#), [287](#), [292](#).
`a_calc`: [68](#).
`A_COLUMN`: [117](#), [141](#), [154](#), [174](#).
`abg_distance`: [148](#), [215](#).
`abgb2ag`: [285](#).
`abgg2ab`: [283](#).
`ABIT`: [117](#), [182](#), [183](#).
`ABSOLUTE`: [39](#), [44](#).
`Absorbing_Glass_RT`: [257](#).
`acalc`: [269](#), [270](#).
`acalc2a`: [186](#), [188](#), [194](#), [218](#), [226](#), [236](#), [269](#).
`acos`: [116](#).
`AD_error`: [139](#), [170](#).
`AD_method_type`: [42](#).
`ad_r`: [18](#), [41](#), [57](#), [72](#), [75](#), [78](#), [90](#), [99](#), [114](#), [122](#),
[128](#), [312](#).
`AD_slab_type`: [16](#), [19](#), [42](#), [152](#), [209](#), [255](#).
`ad_t`: [18](#), [41](#), [58](#), [72](#), [75](#), [79](#), [91](#), [100](#), [115](#), [122](#),
[130](#), [312](#).
`aduru`: [16](#).
`adur1`: [16](#).
`adutu`: [16](#).
`adut1`: [16](#).
`ae_r`: [18](#), [41](#), [57](#), [72](#), [75](#), [78](#), [90](#), [99](#), [114](#), [122](#),
[124](#), [126](#), [128](#), [130](#), [312](#).
`ae_t`: [18](#), [41](#), [58](#), [72](#), [75](#), [79](#), [91](#), [100](#), [115](#), [122](#),
[124](#), [126](#), [128](#), [130](#), [312](#).
`Allocate_Grid`: [138](#), [156](#), [161](#), [164](#), [166](#), [168](#).
`alpha`: [293](#), [295](#).
`amoeba`: [213](#), [233](#), [238](#), [244](#), [249](#).
`analysis`: [73](#), [76](#), [86](#), [92](#).
`any_error`: [2](#), [4](#), [11](#), [15](#), [31](#).
`ap`: [279](#), [280](#), [281](#), [282](#).
`aprime`: [209](#), [293](#), [294](#), [295](#), [296](#), [297](#), [299](#), [301](#), [302](#).
`argc`: [2](#), [5](#), [10](#), [32](#).
`argv`: [2](#), [5](#), [10](#), [32](#).
`as_r`: [11](#), [15](#), [18](#), [41](#), [57](#), [72](#), [75](#), [78](#), [90](#), [99](#), [114](#),
[122](#), [124](#), [126](#), [130](#), [312](#).
`as_t`: [18](#), [41](#), [58](#), [72](#), [75](#), [79](#), [91](#), [100](#), [115](#), [122](#),
[124](#), [126](#), [128](#), [312](#).
`aw_r`: [18](#), [41](#), [72](#), [75](#), [90](#), [99](#), [122](#), [124](#), [126](#), [312](#).
`aw_t`: [18](#), [41](#), [72](#), [75](#), [91](#), [100](#), [122](#), [124](#), [126](#), [312](#).
`ax`: [222](#), [224](#), [226](#), [228](#), [231](#).
`a1`: [283](#), [284](#), [285](#), [286](#).
`a2`: [283](#), [284](#), [285](#), [286](#).
`a2acalc`: [216](#), [226](#), [234](#), [267](#), [289](#).
`B`: [260](#).
`b`: [42](#), [43](#), [69](#), [86](#), [148](#), [174](#), [275](#), [279](#), [281](#),
[284](#), [287](#), [292](#).
`b.bottom_slide`: [16](#), [19](#), [55](#), [68](#), [137](#), [153](#), [172](#),
[174](#), [257](#), [310](#).
`b_calc`: [68](#).
`B_COLUMN`: [117](#), [141](#), [154](#), [174](#).
`b.thinnest`: [68](#).
`b.top_slide`: [16](#), [19](#), [55](#), [68](#), [137](#), [153](#), [172](#), [174](#),
[257](#), [310](#).
`ba`: [166](#), [168](#), [190](#), [191](#), [192](#), [221](#), [224](#).
`base_name`: [10](#).
`bcalc`: [277](#), [278](#).
`bcalc2b`: [188](#), [190](#), [192](#), [196](#), [200](#), [202](#), [204](#), [218](#),
[222](#), [224](#), [231](#), [242](#), [247](#), [252](#), [275](#), [277](#).
`beta`: [293](#), [295](#).
`BIG_A_VALUE`: [255](#), [268](#), [270](#).
`boolean_type`: [43](#), [117](#), [136](#), [142](#).
`both`: [27](#).
`boundary_method`: [209](#).
`bp`: [279](#), [280](#), [281](#), [282](#).
`bprime`: [209](#), [293](#), [295](#), [297](#), [301](#), [302](#).
`brent`: [222](#), [224](#), [226](#), [228](#), [231](#).
`bs`: [166](#), [168](#), [190](#), [192](#), [222](#), [223](#).
`bx`: [222](#), [224](#), [226](#), [228](#), [231](#).
`b1`: [283](#), [284](#), [285](#), [286](#).
`b2`: [283](#), [284](#), [285](#), [286](#).
`b2bcalc`: [216](#), [222](#), [224](#), [231](#), [240](#), [245](#), [250](#),
[275](#), [277](#), [290](#).
`c`: [4](#), [104](#), [108](#).
`calculate_coefficients`: [11](#), [15](#), [23](#).
`Calculate_Distance`: [23](#), [81](#), [85](#), [149](#), [155](#), [171](#), [186](#),
[188](#), [190](#), [192](#), [194](#), [196](#), [198](#), [200](#), [202](#), [204](#), [206](#).
`Calculate_Distance_With_Corrections`: [150](#), [172](#),
[174](#), [175](#).
`Calculate_Grid_Distance`: [141](#), [151](#), [173](#).
`Calculate_Minimum_MR`: [54](#), [82](#), [263](#).
`Calculate_MR_MT`: [9](#), [80](#), [83](#).
`Calculate_Mua_Musp`: [9](#), [22](#), [23](#).
`CALCULATING_GRID`: [117](#), [133](#), [151](#), [154](#), [172](#),
[174](#), [184](#).
`cc`: [5](#).
`check_magic`: [98](#), [107](#).
`cl_beam_d`: [4](#), [5](#), [18](#).
`cl_cos_angle`: [4](#), [5](#), [18](#).

- cl_default_a*: [4](#), [5](#), [6](#), [13](#).
- cl_default_b*: [4](#), [5](#), [7](#), [13](#), [19](#).
- cl_default_fr*: [4](#), [5](#), [18](#).
- cl_default_g*: [4](#), [5](#), [8](#), [13](#).
- cl_default_mua*: [4](#), [5](#), [6](#), [7](#), [13](#).
- cl_default_mus*: [4](#), [5](#), [6](#), [7](#), [13](#).
- cl_forward_calc*: [2](#), [4](#), [5](#).
- cl_method*: [4](#), [5](#), [11](#), [18](#).
- cl_musp0*: [4](#), [5](#), [13](#).
- cl_mus0*: [4](#), [5](#), [13](#).
- cl_mus0_lambda*: [4](#), [5](#), [13](#).
- cl_mus0_pwr*: [4](#), [5](#), [13](#).
- cl_num_spheres*: [4](#), [5](#), [18](#).
- cl_quadrature_points*: [4](#), [5](#), [13](#), [18](#).
- cl_rc_fraction*: [4](#), [5](#), [18](#).
- cl_rstd_r*: [4](#), [5](#), [18](#).
- cl_rstd_t*: [4](#), [5](#), [18](#).
- cl_sample_d*: [4](#), [5](#), [7](#), [13](#), [18](#).
- cl_sample_n*: [4](#), [5](#), [18](#).
- cl_search*: [4](#), [5](#), [13](#).
- cl_slide_d*: [4](#), [5](#), [18](#).
- cl_slide_n*: [4](#), [5](#), [18](#).
- cl_slide_OD*: [4](#), [5](#), [18](#).
- cl_slides*: [4](#), [5](#), [18](#).
- cl_sphere_one*: [4](#), [5](#), [18](#).
- cl_sphere_two*: [4](#), [5](#), [18](#).
- cl_Tc*: [4](#), [5](#), [18](#).
- cl_tc_fraction*: [4](#), [5](#), [18](#).
- cl_tolerance*: [4](#), [5](#), [13](#).
- cl_UR1*: [4](#), [5](#), [18](#).
- cl_UT1*: [4](#), [5](#), [18](#).
- cl_verbosity*: [2](#), [4](#), [5](#), [9](#), [11](#), [14](#), [15](#), [17](#).
- clock*: [2](#), [4](#), [29](#).
- CLOCKS_PER_SEC: [29](#).
- COLLIMATED: [39](#).
- collimated*: [209](#).
- command_line_options*: [4](#), [5](#).
- compare_guesses*: [210](#), [215](#).
- COMPARISON: [5](#), [11](#), [40](#), [116](#), [176](#).
- compute_R_and_T*: [209](#).
- correct_URU*: [153](#).
- correct_UR1*: [153](#).
- cos*: [5](#).
- cos_angle*: [19](#), [55](#), [68](#), [137](#), [172](#), [174](#), [213](#), [222](#), [224](#), [226](#), [228](#), [230](#), [233](#), [238](#), [249](#), [257](#), [259](#), [260](#), [310](#).
- Cos_Snell*: [257](#).
- count*: [17](#), [31](#), [215](#).
- counter*: [31](#).
- cx*: [222](#), [224](#), [226](#), [228](#), [231](#).
- d_beam*: [18](#), [41](#), [72](#), [75](#), [89](#), [98](#), [111](#), [312](#).
- d_detector_r*: [18](#), [75](#), [90](#), [99](#).
- d_detector_t*: [18](#), [75](#), [91](#), [100](#).
- d_entrance_r*: [18](#), [75](#), [90](#), [99](#).
- d_entrance_t*: [18](#), [75](#), [91](#), [100](#).
- d_sample_r*: [18](#), [75](#), [90](#), [99](#).
- d_sample_t*: [18](#), [75](#), [91](#), [100](#).
- d_sphere_r*: [11](#), [18](#), [41](#), [72](#), [75](#), [90](#), [99](#), [114](#), [115](#), [312](#).
- d_sphere_t*: [18](#), [41](#), [72](#), [75](#), [91](#), [100](#), [115](#).
- DBL_MAX_10_EXP: [277](#), [278](#).
- DE_RT: [209](#).
- Debug*: [11](#), [15](#), [24](#), [25](#), [48](#), [60](#), [133](#), [144](#), [145](#), [146](#), [147](#), [154](#), [156](#), [161](#), [164](#), [166](#), [170](#), [172](#), [174](#), [184](#), [208](#), [213](#), [215](#), [216](#), [219](#), [222](#), [224](#), [226](#), [228](#), [230](#), [233](#), [234](#), [238](#), [240](#), [249](#), [264](#), [265](#), [307](#).
- DEBUG_A_LITTLE: [40](#).
- DEBUG_ANY: [11](#), [40](#).
- DEBUG_BEST_GUESS: [40](#), [215](#), [216](#), [234](#), [240](#).
- DEBUG_EVERY_CALC: [40](#), [154](#), [172](#).
- DEBUG_GRID: [40](#), [144](#), [145](#), [146](#), [147](#), [156](#), [161](#), [164](#), [166](#).
- DEBUG_GRID_CALC: [40](#), [154](#), [172](#), [174](#), [184](#).
- DEBUG_ITERATIONS: [40](#), [133](#), [172](#), [184](#), [219](#).
- debug_level*: [305](#), [306](#).
- DEBUG_LOST_LIGHT: [11](#), [15](#), [24](#), [25](#), [40](#), [48](#), [208](#).
- DEBUG_RD_ONLY: [40](#).
- DEBUG_SEARCH: [40](#), [60](#), [170](#), [213](#), [222](#), [224](#), [226](#), [228](#), [230](#), [233](#), [238](#), [249](#), [264](#), [265](#).
- DEBUG_SPHERE_EFFECTS: [40](#).
- default_a*: [13](#), [15](#), [42](#), [48](#), [54](#), [61](#), [62](#), [67](#), [83](#), [85](#), [116](#), [164](#), [183](#), [200](#), [228](#), [230](#), [238](#), [310](#).
- default_b*: [13](#), [42](#), [61](#), [62](#), [67](#), [83](#), [116](#), [226](#), [228](#), [233](#), [310](#).
- default_ba*: [13](#), [42](#), [61](#), [62](#), [67](#), [116](#), [168](#), [204](#), [222](#), [249](#), [250](#), [252](#).
- default_bs*: [13](#), [42](#), [61](#), [62](#), [67](#), [116](#), [166](#), [202](#), [224](#), [245](#), [247](#).
- default_detector_d*: [72](#).
- default_entrance_d*: [72](#).
- default_g*: [13](#), [32](#), [42](#), [62](#), [63](#), [67](#), [75](#), [83](#), [116](#), [213](#), [222](#), [224](#), [226](#), [230](#), [289](#), [290](#), [296](#), [297](#), [299](#), [300](#), [301](#), [302](#), [310](#).
- default_mua*: [13](#), [22](#), [42](#), [67](#).
- default_mus*: [13](#), [22](#), [42](#), [67](#).
- default_sample_d*: [72](#).
- default_sphere_d*: [72](#).
- delta*: [23](#).
- depth*: [209](#).
- determine_search*: [48](#), [59](#).
- dev*: [174](#), [175](#), [182](#), [183](#), [184](#).
- deviation*: [171](#), [172](#), [186](#), [188](#), [190](#), [192](#), [194](#), [196](#), [198](#), [200](#), [202](#), [204](#), [206](#).
- DIFFUSE: [39](#).
- distance*: [43](#), [81](#), [85](#), [141](#), [149](#), [210](#), [215](#), [216](#), [234](#), [240](#).

- dmatrix*: [139](#), [214](#).
dvector: [214](#), [288](#).
Egan: [209](#).
endptr: [28](#).
EOF: [5](#), [32](#).
ERANGE: [28](#).
err: [31](#).
errno: [28](#).
error: [42](#), [53](#), [66](#), [69](#), [70](#), [74](#), [87](#).
Estimate_RT: [60](#), [226](#), [228](#), [230](#), [261](#), [293](#).
Exact_coll_flag: [209](#).
exit: [2](#), [5](#), [10](#), [11](#), [18](#), [28](#), [30](#), [32](#).
EXIT_FAILURE: [5](#), [10](#), [28](#), [30](#).
EXIT_SUCCESS: [2](#), [5](#), [11](#), [18](#), [32](#).
exp: [156](#), [166](#), [278](#), [295](#).
ez_Inverse_RT: [69](#).
f: [205](#), [209](#).
f_r: [18](#), [41](#), [57](#), [72](#), [78](#), [128](#), [130](#), [178](#), [179](#), [180](#), [312](#).
f_t: [41](#), [58](#), [72](#), [79](#), [180](#), [312](#).
fa: [222](#), [224](#), [226](#), [228](#), [231](#).
fabs: [15](#), [182](#), [183](#), [270](#), [272](#), [274](#).
FALSE: [38](#), [39](#), [48](#), [66](#), [117](#), [137](#), [139](#), [144](#), [145](#), [146](#), [147](#), [209](#).
fb: [222](#), [224](#), [226](#), [228](#), [231](#).
fc: [222](#), [224](#), [226](#), [228](#), [231](#).
feof: [104](#), [108](#).
fflush: [25](#), [31](#), [36](#).
fgetc: [104](#), [108](#).
Fill_AB_Grid: [155](#), [160](#), [163](#), [170](#).
Fill_AG_Grid: [160](#), [170](#).
Fill_BaG_Grid: [165](#), [170](#).
Fill_BG_Grid: [163](#), [165](#), [170](#).
Fill_BsG_Grid: [167](#), [170](#).
Fill_Grid: [169](#), [215](#), [291](#).
fill_grid_entry: [154](#), [156](#), [161](#), [164](#), [166](#), [168](#).
final: [31](#).
final_distance: [17](#), [42](#), [48](#), [66](#), [218](#), [219](#), [222](#), [224](#), [226](#), [228](#), [230](#), [231](#), [236](#), [242](#), [247](#), [252](#).
FIND_A: [39](#), [50](#), [54](#), [60](#), [61](#), [62](#), [116](#), [181](#), [288](#), [298](#).
Find_A_fn: [193](#), [226](#), [289](#).
FIND_AB: [39](#), [50](#), [60](#), [62](#), [116](#), [156](#), [170](#), [288](#), [298](#).
Find_AB_fn: [187](#), [213](#), [217](#).
FIND_AG: [39](#), [50](#), [60](#), [62](#), [116](#), [160](#), [161](#), [170](#), [288](#), [298](#).
Find_AG_fn: [185](#), [233](#), [235](#).
FIND_AUTO: [38](#), [39](#), [48](#), [60](#), [66](#), [116](#).
FIND_B: [39](#), [48](#), [50](#), [54](#), [60](#), [61](#), [62](#), [85](#), [116](#), [181](#), [288](#), [298](#).
Find_B_fn: [195](#), [231](#), [290](#).
FIND_B_WITH_NO_ABSORPTION: [39](#), [48](#), [60](#), [61](#), [62](#).
FIND_B_WITH_NO_SCATTERING: [39](#), [48](#), [60](#), [61](#).
FIND_Ba: [39](#), [50](#), [54](#), [60](#), [61](#), [62](#), [116](#), [181](#).
Find_Ba_fn: [189](#), [191](#), [223](#), [224](#).
FIND_BaG: [39](#), [50](#), [60](#), [62](#), [166](#), [170](#).
Find_BaG_fn: [201](#), [244](#), [246](#).
FIND_BG: [39](#), [50](#), [60](#), [62](#), [164](#), [170](#).
Find_BG_fn: [199](#), [238](#), [241](#).
FIND_Bs: [39](#), [50](#), [54](#), [60](#), [61](#), [62](#), [116](#), [181](#).
Find_Bs_fn: [191](#), [221](#), [222](#).
FIND_BsG: [39](#), [50](#), [60](#), [62](#), [168](#), [170](#).
Find_BsG_fn: [203](#), [249](#), [251](#).
FIND_G: [39](#), [50](#), [54](#), [60](#), [61](#), [83](#), [181](#).
Find_G_fn: [197](#), [228](#).
FIND_mus: [36](#).
finish_time: [29](#).
flip: [152](#), [153](#).
flip_sample: [18](#), [41](#), [55](#), [72](#), [116](#), [154](#), [172](#), [174](#).
floor: [157](#).
fmin: [288](#), [289](#), [290](#).
force_new: [169](#), [170](#).
format1: [34](#), [35](#).
format2: [17](#), [34](#), [36](#).
found: [34](#), [36](#), [42](#), [48](#), [66](#), [219](#).
fp: [24](#), [25](#), [32](#), [34](#), [97](#), [98](#), [99](#), [100](#), [101](#), [102](#), [103](#), [104](#), [105](#), [106](#), [107](#), [108](#).
fprintf: [2](#), [5](#), [10](#), [11](#), [14](#), [16](#), [17](#), [18](#), [20](#), [21](#), [24](#), [25](#), [26](#), [27](#), [28](#), [30](#), [31](#), [48](#), [55](#), [60](#), [75](#), [108](#), [133](#), [144](#), [145](#), [146](#), [147](#), [154](#), [156](#), [161](#), [164](#), [166](#), [170](#), [172](#), [174](#), [176](#), [184](#), [208](#), [213](#), [215](#), [216](#), [219](#), [222](#), [224](#), [226](#), [228](#), [230](#), [233](#), [234](#), [238](#), [240](#), [249](#), [264](#), [265](#), [295](#), [310](#), [312](#).
frac: [208](#).
FRACTION: [43](#).
fraction_of_rc_in_mr: [18](#), [41](#), [72](#), [113](#), [176](#), [264](#), [312](#).
fraction_of_tc_in_mt: [18](#), [41](#), [72](#), [113](#), [176](#), [265](#), [312](#).
free: [10](#).
free_dmatrix: [220](#).
free_dvector: [220](#), [288](#).
freopen: [10](#).
fscanf: [106](#).
fval: [151](#), [288](#), [289](#), [290](#).
FO: [209](#).
G: [122](#), [124](#), [126](#), [130](#), [178](#).
g: [42](#), [43](#), [69](#), [86](#), [148](#), [271](#), [279](#), [281](#), [287](#), [292](#).
g_calc: [68](#).
G_COLUMN: [117](#), [141](#), [154](#), [174](#).
g_out_name: [4](#), [5](#), [10](#).
G_std: [178](#).
g_util_debugging: [253](#), [306](#), [308](#).
G_0: [178](#).
Gain: [121](#), [124](#), [126](#), [128](#), [130](#), [178](#).
Gain_11: [123](#), [127](#), [128](#).
Gain_22: [125](#), [130](#).
gcalc: [273](#), [274](#).

- gcalc2g*: [186](#), [198](#), [200](#), [202](#), [204](#), [228](#), [236](#), [242](#), [247](#), [252](#), [273](#).
Get_Calc_State: [81](#), [134](#), [149](#), [151](#), [170](#), [206](#), [208](#).
getopt: [5](#).
GG_a: [117](#), [162](#), [164](#).
GG_b: [117](#), [161](#), [162](#).
GG_ba: [117](#), [162](#), [168](#).
GG_bs: [117](#), [162](#), [166](#).
GG_g: [117](#), [156](#), [162](#).
GP: [124](#), [126](#), [128](#), [178](#).
GP_std: [178](#).
gprime: [209](#).
Grid_ABG: [140](#), [215](#).
GRID_SIZE: [117](#), [139](#), [141](#), [151](#), [154](#), [156](#), [157](#), [158](#), [159](#), [161](#), [164](#), [166](#), [168](#), [174](#).
guess: [140](#), [141](#), [148](#), [149](#), [210](#), [215](#), [216](#), [234](#), [240](#), [245](#), [250](#).
guess_t: [43](#).
guess_type: [43](#), [140](#), [148](#), [210](#), [215](#).
g1: [210](#), [283](#), [284](#).
G11: [124](#).
g2: [210](#), [283](#), [284](#), [285](#), [286](#).
g2gcalc: [228](#), [234](#), [240](#), [245](#), [250](#), [271](#), [273](#).
G22: [126](#).
HENYEE_GREENSTEIN: [16](#), [68](#).
HUGE_VAL: [7](#), [22](#), [70](#), [83](#), [116](#), [222](#), [224](#), [226](#), [228](#), [258](#), [272](#), [274](#), [276](#), [278](#), [280](#), [282](#), [286](#), [289](#), [295](#), [296](#), [301](#), [302](#).
i: [30](#), [74](#), [87](#), [108](#), [140](#), [151](#), [154](#), [156](#), [161](#), [164](#), [166](#), [168](#), [173](#), [214](#).
i_best: [214](#), [215](#).
i_min: [150](#), [151](#).
IAD_AD_NOT_VALID: [40](#), [57](#), [58](#).
IAD_AE_NOT_VALID: [40](#), [57](#), [58](#).
IAD_AS_NOT_VALID: [40](#), [57](#), [58](#).
IAD_BAD_G_VALUE: [40](#).
IAD_BAD_PHASE_FUNCTION: [40](#).
IAD_EXCESSIVE_LIGHT_LOSS: [40](#).
IAD_F_NOT_VALID: [40](#), [57](#), [58](#).
IAD_FILE_ERROR: [40](#).
IAD_GAMMA_NOT_VALID: [40](#).
IAD_invert_type: [42](#).
IAD_MAX_ITERATIONS: [39](#), [50](#).
IAD_measure_type: [41](#).
IAD_MEMORY_ERROR: [40](#).
IAD_MR_TOO_BIG: [31](#), [40](#), [85](#).
IAD_MR_TOO_SMALL: [31](#), [40](#), [54](#), [85](#).
IAD_MT_TOO_BIG: [31](#), [40](#), [55](#).
IAD_MT_TOO_SMALL: [31](#), [40](#), [55](#), [85](#).
IAD_MU_TOO_BIG: [31](#), [40](#), [56](#).
IAD_MU_TOO_SMALL: [31](#), [40](#), [56](#).
IAD_NO_ERROR: [11](#), [15](#), [31](#), [40](#), [49](#), [53](#), [66](#), [70](#), [74](#), [85](#), [87](#).
IAD_QUAD_PTS_NOT_VALID: [40](#), [49](#).
IAD_RD_NOT_VALID: [40](#), [57](#), [58](#).
IAD_RSTD_NOT_VALID: [40](#), [57](#).
IAD_RT_LT_MINIMUM: [40](#).
IAD_RW_NOT_VALID: [40](#), [57](#), [58](#).
IAD_TOO_MANY_ITERATIONS: [31](#), [40](#), [50](#).
IAD_TOO_MANY_LAYERS: [40](#).
IAD_TOO_MUCH_LIGHT: [31](#), [40](#).
IAD_TSTD_NOT_VALID: [40](#), [57](#), [58](#).
illumination: [86](#), [89](#), [209](#).
illumination_type: [43](#).
include_MC: [80](#), [81](#).
independent: [60](#).
Initialize_Measure: [2](#), [70](#), [71](#), [74](#), [87](#), [98](#).
Initialize_Result: [2](#), [11](#), [35](#), [63](#), [70](#), [74](#), [87](#).
Inverse_RT: [11](#), [15](#), [23](#), [36](#), [44](#), [47](#), [69](#), [70](#), [74](#), [87](#).
invert_type: [4](#), [22](#), [23](#), [25](#), [34](#), [42](#), [47](#), [52](#), [59](#), [63](#), [70](#), [74](#), [80](#), [81](#), [82](#), [84](#), [87](#), [109](#), [117](#), [132](#), [133](#), [134](#), [135](#), [136](#), [149](#), [151](#), [155](#), [160](#), [163](#), [165](#), [167](#), [169](#), [206](#), [207](#), [208](#), [212](#), [221](#), [223](#), [225](#), [227](#), [229](#), [232](#), [237](#), [243](#), [248](#), [261](#), [287](#), [292](#), [309](#).
isdigit: [5](#).
isspace: [104](#).
iterations: [25](#), [42](#), [50](#), [66](#), [213](#), [219](#), [233](#), [238](#), [244](#), [249](#).
j: [140](#), [151](#), [154](#), [156](#), [161](#), [164](#), [166](#), [168](#), [173](#).
j_best: [214](#), [215](#).
j_min: [150](#), [151](#).
k: [215](#), [216](#), [234](#), [240](#).
kk: [216](#), [234](#), [240](#).
lambda: [11](#), [13](#), [25](#), [32](#), [34](#), [41](#), [72](#), [102](#), [184](#).
last: [30](#).
line: [25](#), [32](#), [34](#).
lines: [34](#), [35](#).
log: [166](#), [259](#), [260](#), [276](#), [295](#).
logr: [293](#), [295](#).
LR: [11](#), [12](#), [15](#), [23](#), [25](#), [174](#).
LT: [11](#), [12](#), [15](#), [23](#), [25](#), [174](#).
m: [4](#), [22](#), [23](#), [25](#), [34](#), [47](#), [52](#), [59](#), [63](#), [70](#), [71](#), [74](#), [80](#), [82](#), [84](#), [87](#), [97](#), [101](#), [109](#), [121](#), [123](#), [125](#), [127](#), [129](#), [132](#), [134](#), [136](#), [142](#), [155](#), [160](#), [163](#), [165](#), [167](#), [169](#), [207](#), [212](#), [221](#), [223](#), [225](#), [227](#), [229](#), [232](#), [237](#), [243](#), [248](#), [261](#), [287](#), [292](#), [311](#).
m_old: [206](#), [208](#).
M_PI: [5](#), [72](#), [209](#).
M_R: [80](#), [81](#), [82](#), [171](#), [172](#), [175](#), [177](#), [178](#), [179](#), [180](#), [182](#), [183](#), [184](#).
m_r: [9](#), [11](#), [17](#), [18](#), [25](#), [32](#), [35](#), [36](#), [41](#), [48](#), [54](#), [60](#), [70](#), [72](#), [77](#), [85](#), [93](#), [102](#), [149](#), [154](#), [182](#), [183](#), [184](#),

- [186](#), [188](#), [190](#), [192](#), [194](#), [196](#), [198](#), [200](#), [202](#), [204](#), [205](#), [206](#), [215](#), [264](#), [291](#).
- M_T**: [56](#), [80](#), [81](#), [171](#), [172](#), [175](#), [177](#), [178](#), [179](#), [180](#), [182](#), [183](#), [184](#).
- m_t**: [9](#), [11](#), [17](#), [18](#), [19](#), [25](#), [32](#), [35](#), [36](#), [41](#), [48](#), [54](#), [55](#), [56](#), [60](#), [70](#), [72](#), [77](#), [85](#), [93](#), [102](#), [149](#), [154](#), [182](#), [183](#), [184](#), [186](#), [188](#), [190](#), [192](#), [194](#), [196](#), [198](#), [200](#), [202](#), [204](#), [205](#), [206](#), [215](#), [222](#), [224](#), [265](#), [291](#).
- m_u**: [17](#), [18](#), [19](#), [35](#), [36](#), [41](#), [56](#), [60](#), [70](#), [72](#), [77](#), [93](#), [102](#), [137](#), [146](#), [160](#), [233](#), [299](#), [300](#), [302](#).
- magic**: [108](#).
- main**: [2](#), [32](#).
- malloc**: [27](#).
- mask**: [307](#), [308](#).
- max_b**: [156](#).
- Max_Light_Loss**: [207](#).
- max_possible_m_r**: [85](#).
- maxloss**: [205](#), [208](#).
- mc_iter**: [11](#), [12](#), [15](#), [25](#).
- MC_iterations**: [4](#), [5](#), [9](#), [14](#), [15](#).
- MC_Lost**: [15](#), [74](#), [81](#), [87](#).
- MC_RT**: [16](#).
- mc_runs**: [74](#), [76](#), [87](#), [92](#).
- MC_tolerance**: [13](#), [15](#), [42](#), [66](#), [116](#).
- mc_total**: [11](#), [12](#), [15](#).
- measure_OK**: [49](#), [52](#).
- measure_type**: [4](#), [22](#), [23](#), [25](#), [34](#), [41](#), [47](#), [52](#), [59](#), [63](#), [70](#), [71](#), [74](#), [80](#), [81](#), [82](#), [84](#), [87](#), [97](#), [101](#), [109](#), [117](#), [121](#), [123](#), [125](#), [127](#), [129](#), [132](#), [133](#), [134](#), [135](#), [136](#), [142](#), [149](#), [151](#), [155](#), [160](#), [163](#), [165](#), [167](#), [169](#), [206](#), [207](#), [208](#), [212](#), [221](#), [223](#), [225](#), [227](#), [229](#), [232](#), [237](#), [243](#), [248](#), [261](#), [287](#), [292](#), [311](#).
- measured_m_r**: [85](#).
- measurement**: [86](#), [93](#).
- measurements**: [73](#), [77](#).
- memcpy**: [133](#), [135](#).
- method**: [13](#), [18](#), [41](#), [42](#), [49](#), [63](#), [68](#), [70](#), [72](#), [76](#), [92](#), [98](#), [116](#), [137](#), [154](#), [172](#), [176](#), [310](#), [312](#).
- metric**: [42](#), [66](#), [182](#), [183](#).
- MGRID**: [117](#), [137](#), [146](#), [147](#), [170](#).
- min_a**: [291](#).
- min_b**: [156](#), [291](#).
- min_g**: [291](#).
- min_possible_m_r**: [85](#).
- MinMax_MR_MT**: [53](#), [84](#).
- MM**: [117](#), [119](#), [132](#), [133](#), [135](#), [154](#), [171](#), [172](#), [174](#), [176](#), [178](#), [179](#), [180](#), [182](#), [183](#), [184](#), [206](#), [209](#).
- mnbrak**: [222](#), [224](#), [226](#), [228](#), [231](#).
- mr**: [54](#), [82](#), [83](#).
- MR_IS_ONLY_RD**: [3](#).
- mt**: [54](#), [82](#), [83](#).
- MT_IS_ONLY_TD**: [3](#).
- mu_a**: [9](#), [11](#), [12](#), [15](#), [25](#), [32](#), [54](#).
- mu_a_last**: [15](#).
- mu_in_slab**: [256](#), [257](#).
- mu_sp**: [9](#), [11](#), [12](#), [15](#), [25](#).
- mu_sp_last**: [15](#).
- mua**: [22](#), [23](#).
- musp**: [22](#), [23](#).
- my_strtod**: [5](#), [28](#).
- n**: [5](#), [10](#), [30](#), [69](#), [152](#).
- n_bottom**: [209](#).
- n_bottom_slide**: [16](#), [19](#), [55](#), [68](#), [137](#), [153](#), [172](#), [174](#), [209](#), [257](#), [310](#).
- n_photons**: [4](#), [5](#), [14](#), [15](#).
- n_slab**: [16](#), [19](#), [55](#), [68](#), [83](#), [137](#), [172](#), [174](#), [209](#), [257](#), [310](#).
- n_top**: [209](#).
- n_top_slide**: [16](#), [19](#), [55](#), [68](#), [137](#), [153](#), [172](#), [174](#), [209](#), [257](#), [310](#).
- Near_Grid_Points**: [150](#), [175](#), [215](#), [291](#).
- nfluxes**: [209](#).
- NO_SLIDES**: [3](#), [5](#), [18](#).
- NO_UNSCATTERED_LIGHT**: [3](#).
- nslide**: [69](#), [70](#).
- num_measures**: [19](#), [32](#), [41](#), [60](#), [70](#), [72](#), [77](#), [93](#), [98](#), [137](#), [146](#), [233](#), [261](#), [265](#), [293](#), [312](#).
- num_photons**: [74](#), [75](#), [87](#), [92](#).
- num_spheres**: [11](#), [15](#), [18](#), [41](#), [48](#), [53](#), [55](#), [62](#), [72](#), [75](#), [81](#), [89](#), [98](#), [116](#), [176](#), [312](#).
- NUMBER_OF_GUESSES**: [210](#), [215](#).
- old_mm**: [81](#), [149](#), [151](#).
- old_rr**: [81](#), [149](#), [151](#).
- once**: [184](#).
- ONE_SLIDE_NEAR_SPHERE**: [3](#), [5](#), [18](#).
- ONE_SLIDE_NOT_NEAR_SPHERE**: [3](#), [5](#), [18](#).
- ONE_SLIDE_ON_BOTTOM**: [3](#), [5](#), [18](#).
- ONE_SLIDE_ON_TOP**: [3](#), [5](#), [18](#).
- optarg**: [5](#).
- optind**: [5](#).
- p**: [214](#).
- P_d**: [178](#).
- P_std**: [178](#).
- P_0**: [178](#).
- params**: [2](#), [4](#), [14](#), [19](#), [97](#), [98](#), [101](#), [102](#), [109](#), [116](#).
- parse_string_into_array**: [5](#), [30](#).
- phase_function**: [16](#), [68](#), [137](#).
- points**: [31](#).
- pow**: [13](#).
- print_dot**: [11](#), [15](#), [31](#).
- print_error_legend**: [2](#), [26](#).
- Print_Invert_Type**: [309](#).
- Print_Measure_Type**: [311](#).
- print_optical_property_result**: [9](#), [11](#), [15](#), [25](#).

- print_results_header*: 9, 14, 15, [24](#).
print_usage: 5, [21](#).
print_version: 5, [20](#).
printf: 17, 28, 35, 36, [111](#), [112](#), [113](#), [114](#), [115](#), [116](#).
process_command_line: 2, [4](#), 5, 10.
p1: [210](#).
p2: [210](#).
qsort: [215](#).
quad_Dif_Calc_R_and_T: [209](#).
quad_pts: 13, 49, 63, 68, 70, 76, 92, [116](#), [137](#),
[154](#), [172](#), [310](#).
quick_guess: [210](#), [253](#), [292](#).
r: [4](#), [22](#), [23](#), [25](#), [30](#), [34](#), [47](#), [52](#), [59](#), [63](#), [70](#), [74](#), [80](#),
[82](#), [84](#), [87](#), [109](#), [132](#), [134](#), [136](#), [150](#), [155](#), [160](#),
[163](#), [165](#), [167](#), [169](#), [207](#), [212](#), [221](#), [223](#), [225](#), [227](#),
[229](#), [232](#), [237](#), [243](#), [248](#), [261](#), [287](#), [292](#), [309](#).
R_diffuse: [176](#), [178](#), [180](#).
R_direct: [176](#), [177](#), [178](#), [179](#), [180](#).
r_old: [206](#), [208](#).
R_O: [180](#).
rate: [31](#).
rc: [60](#), [261](#), [263](#), [264](#), [293](#).
Rc: [172](#), [174](#), [175](#), [176](#), [226](#), [228](#), [230](#).
rd: [60](#), [61](#), [261](#), [264](#), [293](#), [294](#), [295](#).
Rd: [226](#), [228](#), [230](#).
rd_r: [41](#), 57, 72, 78, 90, 114, 122, [312](#).
rd_t: [41](#), 58, 72, 79, 91, 115, 122, [312](#).
Read_Data_Line: 2, [101](#).
Read_Header: 2, 32, [97](#).
read_number: 98, 99, 100, 102, [105](#).
readln: 32.
REFLECTION_SPHERE: [117](#), [122](#), [124](#), [126](#), [130](#), [178](#).
RELATIVE: [39](#), [44](#), 66, [182](#), [183](#).
results: [73](#), [74](#).
RGRID: [117](#), [170](#).
rp: [209](#).
RR: [117](#), [119](#), [132](#), [133](#), [135](#), [137](#), [149](#), [154](#), [156](#),
[157](#), [158](#), [159](#), [161](#), [164](#), [166](#), [168](#), [171](#), [172](#),
[174](#), [181](#), [182](#), [183](#), [184](#), [186](#), [188](#), [190](#), [192](#),
[194](#), [196](#), [198](#), [200](#), [202](#), [204](#), [206](#).
rs: [209](#).
rstd_r: 18, [41](#), 57, 72, 75, 78, 85, 93, 98, 102,
[114](#), [178](#), [179](#), [180](#), [312](#).
rstd_t: 18, [41](#), 55, 57, 58, 72, 79, 102, [115](#), [180](#), [312](#).
rt: [60](#), 62, [261](#), [264](#).
Rt: [226](#), [228](#), [230](#).
RT: 16, [152](#), [153](#).
RT_Flip: [152](#), [154](#), [172](#).
rt_name: [10](#).
rt_total: 11, [12](#), 14, 15.
ru: [53](#), 55.
rw_r: 18, [41](#), 57, 58, 72, 75, 78, 90, 99, 102, [114](#),
[122](#), [128](#), [130](#), [178](#), [179](#), [312](#).
rw_t: 18, [41](#), 58, 72, 75, 79, 91, 100, 102, [115](#),
[122](#), [128](#), [130](#), [312](#).
r1: [256](#), [257](#), [258](#), [259](#), [260](#).
r2: [256](#), [257](#), [258](#), [259](#), [260](#).
s: [16](#), [19](#), [27](#), [30](#), [138](#), [142](#), [150](#), [209](#).
Same_Calc_State: [136](#), [170](#).
sample: [86](#), 88.
scanf: 32.
search: 11, 13, 36, [42](#), 48, 50, 54, [60](#), 61, 62, 66,
83, 85, 116, 137, 156, 161, 164, 166, 168, 170,
181, 215, 288, 291, 298, 310.
search_type: [43](#), 59, 138, 142, 150.
seconds_elapsed: [29](#), 31.
Set_Calc_State: 81, [132](#), 149, 151, 156, 161, 164,
166, 168, 206, 208, 213, 219, 222, 224, 226, 228,
230, 231, 233, 238, 244, 249, 289, 290.
Set_Debugging: 5, [305](#).
setup: [73](#), 75.
skip_white: [103](#), 106.
slab: 9, [42](#), 55, 68, 83, 137, 149, [152](#), 153, 154,
156, 157, 158, 159, 161, 164, 166, 168, 172, 174,
184, 186, 188, 190, 192, 194, 196, 198, 200, 202,
204, 206, [209](#), 213, 215, 218, 219, 221, 222, 223,
224, 226, 228, 230, 231, 233, 236, 238, 242,
247, 249, 252, [255](#), 257, 259, 260, 288, 289,
290, 291, 295, 299, 300, 302, 310.
slab.bottom_slide_b: 18, 19, [41](#), 68, 72.
slab.bottom_slide_index: 18, 19, [41](#), 68, 70, 72,
75, 88, 98, 111, 147, 312.
slab.bottom_slide_thickness: 18, [41](#), 72, 75, 88,
98, 111, 312.
slab.cos_angle: 18, 19, [41](#), 68, 70, 72, 75, 116, 147.
slab.index: 18, 19, [41](#), 68, 70, 72, 75, 88, 98,
111, 147, 312.
slab.thickness: 13, 18, 22, 32, 35, [41](#), 72, 74,
75, 88, 98, 111, 312.
slab.top_slide_b: 18, 19, [41](#), 68, 72.
slab.top_slide_index: 18, 19, [41](#), 68, 70, 72, 75,
88, 98, 111, 147, 312.
slab.top_slide_thickness: 18, [41](#), 72, 75, 88, 98,
111, 312.
slabtype: [209](#).
slide_bottom: [209](#).
slide_top: [209](#).
slow_guess: [287](#).
SMALL_A_VALUE: [255](#), 270.
smallest: [151](#).
Sp_mu_RT: 55.
Sp_mu_RT_Flip: 55, 172, 174.
sphere: [121](#), [122](#).

- sphere_area*: [72](#).
sphere_r: [73](#), [78](#), [86](#), [90](#).
sphere_t: [73](#), [79](#), [86](#), [91](#).
Spheres_Inverse_RT: [73](#).
Spheres_Inverse_RT2: [86](#).
sqrt: [114](#), [115](#), [260](#), [270](#), [312](#).
sscanf: [5](#), [30](#).
start_time: [2](#), [4](#), [11](#), [15](#), [29](#), [31](#).
stderr: [2](#), [5](#), [10](#), [11](#), [15](#), [16](#), [17](#), [18](#), [26](#), [27](#), [28](#),
[30](#), [31](#), [48](#), [55](#), [60](#), [75](#), [108](#), [119](#), [133](#), [144](#), [145](#),
[146](#), [147](#), [154](#), [156](#), [161](#), [164](#), [166](#), [170](#), [172](#),
[174](#), [176](#), [184](#), [208](#), [213](#), [215](#), [216](#), [219](#), [222](#),
[224](#), [226](#), [228](#), [230](#), [233](#), [234](#), [238](#), [240](#), [249](#),
[255](#), [264](#), [265](#), [295](#), [310](#), [312](#).
stdin: [2](#), [10](#).
stdout: [9](#), [10](#), [11](#), [14](#), [20](#), [21](#), [36](#).
str: [28](#).
strcat: [27](#).
strcmp: [10](#).
strcpy: [27](#).
strdup: [5](#), [10](#), [27](#).
strdup_together: [10](#), [27](#).
strlen: [10](#), [27](#), [30](#).
strstr: [10](#).
strtod: [28](#).
SUBSTITUTION: [18](#), [40](#), [98](#), [116](#).
swap: [153](#).
t: [27](#), [30](#), [150](#).
T_diffuse: [176](#), [180](#).
T_direct: [176](#), [177](#), [178](#), [179](#), [180](#).
T_TRUST_FACTOR: [117](#), [183](#).
T_0: [180](#).
tc: [60](#), [261](#), [263](#), [265](#), [293](#).
Tc: [69](#), [70](#), [172](#), [174](#), [175](#), [176](#), [226](#), [228](#), [230](#),
[255](#), [258](#), [259](#), [260](#).
td: [60](#), [61](#), [261](#), [265](#), [293](#).
Td: [226](#), [228](#), [230](#), [261](#).
tdiffuse: [123](#), [124](#), [125](#), [126](#).
temp_m_t: [85](#).
The_Grid: [117](#), [137](#), [139](#), [141](#), [144](#), [154](#), [156](#), [161](#),
[164](#), [166](#), [168](#), [174](#).
The_Grid_Initialized: [117](#), [137](#), [139](#), [144](#), [156](#),
[161](#), [164](#), [166](#), [168](#).
The_Grid_Search: [117](#), [145](#), [156](#), [161](#), [164](#), [166](#),
[168](#).
tmp: [122](#), [294](#).
tolerance: [13](#), [42](#), [48](#), [66](#), [116](#), [213](#), [219](#), [222](#), [224](#),
[226](#), [228](#), [231](#), [233](#), [238](#), [244](#), [249](#).
tp: [209](#), [261](#).
TRANSMISSION_SPHERE: [117](#), [124](#), [126](#), [128](#), [178](#).
TRUE: [32](#), [36](#), [38](#), [39](#), [48](#), [137](#), [143](#), [156](#), [161](#),
[164](#), [166](#), [168](#).
ts: [209](#).
tt: [60](#), [61](#), [62](#), [261](#), [265](#).
Tt: [226](#), [228](#), [230](#).
tu: [53](#), [55](#).
TWO_IDENTICAL_SLIDES: [3](#), [5](#).
Two_Sphere_R: [127](#), [180](#).
Two_Sphere_T: [129](#), [180](#).
twoprime: [279](#), [284](#).
twounprime: [281](#), [284](#).
t1: [256](#), [257](#), [258](#), [259](#), [260](#).
t2: [256](#), [257](#), [258](#), [259](#), [260](#).
U_Find_A: [50](#), [222](#), [224](#), [225](#).
U_Find_AB: [50](#), [212](#).
U_Find_AG: [50](#), [232](#).
U_Find_B: [50](#), [84](#), [85](#), [229](#).
U_Find_Ba: [50](#), [223](#).
U_Find_BaG: [50](#), [243](#).
U_Find_BG: [50](#), [237](#), [243](#), [248](#).
U_Find_Bs: [50](#), [221](#).
U_Find_BsG: [50](#), [248](#).
U_Find_G: [50](#), [227](#).
ungetc: [104](#).
UNINITIALIZED: [2](#), [4](#), [5](#), [6](#), [7](#), [8](#), [13](#), [18](#), [22](#), [40](#),
[54](#), [61](#), [62](#), [67](#), [83](#), [116](#), [213](#), [222](#), [224](#), [226](#),
[228](#), [230](#), [233](#), [238](#), [249](#).
UNKNOWN: [18](#), [40](#), [72](#), [116](#).
URU: [121](#), [122](#), [123](#), [124](#), [125](#), [126](#), [127](#), [128](#), [129](#),
[130](#), [152](#), [153](#), [175](#), [176](#), [209](#).
uru: [12](#), [15](#), [16](#), [74](#), [81](#), [87](#), [154](#), [172](#), [174](#).
URU_COLUMN: [117](#), [154](#), [174](#).
uru_lost: [15](#), [25](#), [41](#), [72](#), [74](#), [80](#), [81](#), [87](#), [133](#), [176](#).
UR1: [69](#), [70](#), [127](#), [128](#), [129](#), [130](#), [152](#), [153](#), [175](#),
[176](#), [209](#), [293](#), [295](#).
ur1: [12](#), [15](#), [16](#), [74](#), [81](#), [87](#), [154](#), [172](#), [174](#).
UR1_COLUMN: [117](#), [154](#), [174](#).
ur1_loss: [207](#), [208](#).
ur1_lost: [15](#), [25](#), [41](#), [48](#), [72](#), [74](#), [81](#), [87](#), [133](#),
[176](#), [206](#), [208](#), [312](#).
UTU: [127](#), [128](#), [129](#), [130](#), [152](#), [153](#), [175](#), [176](#), [209](#).
utu: [12](#), [15](#), [16](#), [74](#), [81](#), [87](#), [154](#), [172](#), [174](#).
UTU_COLUMN: [117](#), [154](#), [174](#).
utu_lost: [15](#), [25](#), [41](#), [72](#), [74](#), [81](#), [87](#), [133](#), [176](#), [312](#).
UT1: [69](#), [70](#), [127](#), [128](#), [129](#), [130](#), [152](#), [153](#), [175](#),
[176](#), [209](#), [293](#), [294](#), [295](#).
ut1: [12](#), [15](#), [16](#), [74](#), [81](#), [87](#), [154](#), [172](#), [174](#).
UT1_COLUMN: [117](#), [154](#), [174](#).
ut1_loss: [207](#), [208](#).
ut1_lost: [15](#), [25](#), [41](#), [48](#), [72](#), [74](#), [81](#), [87](#), [133](#),
[176](#), [206](#), [208](#), [312](#).
val: [28](#).
Valid_Grid: [142](#), [215](#), [291](#).
verbosity: [20](#), [31](#).

Version: [20](#), [21](#), [111](#).

VersionShort: [20](#).

what_char: [25](#), [31](#).

What_Is_B: [19](#), [233](#), [255](#), [263](#), [295](#), [299](#), [300](#), [302](#).

Write_Header: [9](#), [14](#), [35](#), [109](#).

x: [98](#), [105](#), [128](#), [130](#), [156](#), [185](#), [187](#), [189](#), [191](#), [193](#),
[195](#), [197](#), [199](#), [201](#), [203](#), [214](#), [226](#), [228](#), [231](#), [288](#).

xx: [111](#), [116](#).

y: [214](#).

zbrent: [208](#).

- ⟨ Allocate local simplex variables 214 ⟩ Used in sections 213, 233, 238, 244, and 249.
- ⟨ Calc M_R and M_T for dual beam sphere 179 ⟩ Used in section 176.
- ⟨ Calc M_R and M_T for no spheres 177 ⟩ Used in section 176.
- ⟨ Calc M_R and M_T for single beam sphere 178 ⟩ Used in section 176.
- ⟨ Calc M_R and M_T for two spheres 180 ⟩ Used in section 176.
- ⟨ Calculate and Print the Forward Calculation 6, 7, 8, 9 ⟩ Used in section 2.
- ⟨ Calculate and write optical properties 11, 36 ⟩ Used in sections 2 and 32.
- ⟨ Calculate specular reflection and transmission 257 ⟩ Used in section 256.
- ⟨ Calculate the deviation 181 ⟩ Used in section 176.
- ⟨ Calculate the unscattered transmission and reflection 263 ⟩ Used in section 262.
- ⟨ Check MU 56 ⟩ Used in section 53.
- ⟨ Check MR for zero or one spheres 54 ⟩ Used in section 53.
- ⟨ Check MT for zero or one spheres 55 ⟩ Used in section 53.
- ⟨ Check for bad values of Tc 258 ⟩ Used in section 256.
- ⟨ Check sphere parameters 57, 58 ⟩ Used in section 53.
- ⟨ Choose the best node of the a and b simplex 218 ⟩ Used in section 213.
- ⟨ Choose the best node of the a and g simplex 236 ⟩ Used in section 233.
- ⟨ Choose the best node of the ba and g simplex 247 ⟩ Used in section 244.
- ⟨ Choose the best node of the bs and g simplex 252 ⟩ Used in section 249.
- ⟨ Choose the best node of the b and g simplex 242 ⟩ Used in section 238.
- ⟨ Clean up guesses 303 ⟩ Used in section 293.
- ⟨ Command-line changes to m 18 ⟩ Used in section 2.
- ⟨ Command-line changes to r 13 ⟩ Used in sections 2 and 11.
- ⟨ Count command-line measurements 19 ⟩ Used in section 2.
- ⟨ Declare variables for *main* 4, 34 ⟩ Used in sections 2 and 32.
- ⟨ Definition for *Allocate_Grid* 139 ⟩ Used in section 117.
- ⟨ Definition for *Calculate_Distance_With_Corrections* 176 ⟩ Used in section 117.
- ⟨ Definition for *Calculate_Distance* 172 ⟩ Used in section 117.
- ⟨ Definition for *Calculate_Grid_Distance* 174 ⟩ Used in section 117.
- ⟨ Definition for *Calculate_MR_MT* 81 ⟩ Used in section 44.
- ⟨ Definition for *Calculate_Minimum_MR* 83 ⟩ Used in section 44.
- ⟨ Definition for *Debug* 308 ⟩ Used in section 253.
- ⟨ Definition for *Estimate_RT* 262 ⟩ Used in section 253.
- ⟨ Definition for *Fill_AB_Grid* 156 ⟩ Used in section 117.
- ⟨ Definition for *Fill_AG_Grid* 161 ⟩ Used in section 117.
- ⟨ Definition for *Fill_BG_Grid* 164 ⟩ Used in section 117.
- ⟨ Definition for *Fill_BaG_Grid* 166 ⟩ Used in section 117.
- ⟨ Definition for *Fill_BsG_Grid* 168 ⟩ Used in section 117.
- ⟨ Definition for *Fill_Grid* 170 ⟩ Used in section 117.
- ⟨ Definition for *Find_AB_fn* 188 ⟩ Used in section 117.
- ⟨ Definition for *Find_AG_fn* 186 ⟩ Used in section 117.
- ⟨ Definition for *Find_A_fn* 194 ⟩ Used in section 117.
- ⟨ Definition for *Find_BG_fn* 200 ⟩ Used in section 117.
- ⟨ Definition for *Find_B_fn* 196 ⟩ Used in section 117.
- ⟨ Definition for *Find_BaG_fn* 202 ⟩ Used in section 117.
- ⟨ Definition for *Find_Ba_fn* 190 ⟩ Used in section 117.
- ⟨ Definition for *Find_BsG_fn* 204 ⟩ Used in section 117.
- ⟨ Definition for *Find_Bs_fn* 192 ⟩ Used in section 117.
- ⟨ Definition for *Find_G_fn* 198 ⟩ Used in section 117.
- ⟨ Definition for *Gain_11* 124 ⟩ Used in section 117.
- ⟨ Definition for *Gain_22* 126 ⟩ Used in section 117.
- ⟨ Definition for *Gain* 122 ⟩ Used in section 117.

〈Definition for *Get_Calc_State* 135〉 Used in section 117.
 〈Definition for *Grid_ABG* 141〉 Used in section 117.
 〈Definition for *Initialize_Measure* 72〉 Used in section 44.
 〈Definition for *Initialize_Result* 64〉 Used in section 44.
 〈Definition for *Inverse_RT* 48〉 Used in section 44.
 〈Definition for *Max_Light_Loss* 208〉 Used in section 117.
 〈Definition for *MinMax_MR_MT* 85〉 Used in section 44.
 〈Definition for *Near_Grid_Points* 151〉 Used in section 117.
 〈Definition for *Print_Invert_Type* 310〉 Used in section 253.
 〈Definition for *Print_Measure_Type* 312〉 Used in section 253.
 〈Definition for *RT_Flip* 153〉 Used in section 117.
 〈Definition for *Read_Data_Line* 102〉 Used in section 94.
 〈Definition for *Read_Header* 98〉 Used in section 94.
 〈Definition for *Same_Calc_State* 137〉 Used in section 117.
 〈Definition for *Set_Calc_State* 133〉 Used in section 117.
 〈Definition for *Set_Debugging* 306〉 Used in section 253.
 〈Definition for *Spheres_Inverse_RT2* 87〉 Used in section 44.
 〈Definition for *Spheres_Inverse_RT* 74〉 Used in section 44.
 〈Definition for *Two_Sphere_R* 128〉 Used in section 117.
 〈Definition for *Two_Sphere_T* 130〉 Used in section 117.
 〈Definition for *U_Find_AB* 213〉 Used in section 210.
 〈Definition for *U_Find_AG* 233〉 Used in section 210.
 〈Definition for *U_Find_A* 226〉 Used in section 210.
 〈Definition for *U_Find_BG* 238〉 Used in section 210.
 〈Definition for *U_Find_BaG* 244〉 Used in section 210.
 〈Definition for *U_Find_Ba* 224〉 Used in section 210.
 〈Definition for *U_Find_BsG* 249〉 Used in section 210.
 〈Definition for *U_Find_Bs* 222〉 Used in section 210.
 〈Definition for *U_Find_B* 230〉 Used in section 210.
 〈Definition for *U_Find_G* 228〉 Used in section 210.
 〈Definition for *Valid_Grid* 143〉 Used in section 117.
 〈Definition for *What_Is_B* 256〉 Used in section 253.
 〈Definition for *Write_Header* 110〉 Used in section 94.
 〈Definition for *a2acalc* 268〉 Used in section 253.
 〈Definition for *abg_distance* 149〉 Used in section 117.
 〈Definition for *abgb2ag* 286〉 Used in section 253.
 〈Definition for *abgg2ab* 284〉 Used in section 253.
 〈Definition for *acalc2a* 270〉 Used in section 253.
 〈Definition for *b2bcalc* 276〉 Used in section 253.
 〈Definition for *bcalc2b* 278〉 Used in section 253.
 〈Definition for *check_magic* 108〉 Used in section 94.
 〈Definition for *determine_search* 60〉 Used in section 44.
 〈Definition for *ez_Inverse_RT* 70〉 Used in section 44.
 〈Definition for *fill_grid_entry* 154〉 Used in section 117.
 〈Definition for *g2gcalc* 272〉 Used in section 253.
 〈Definition for *gcalc2g* 274〉 Used in section 253.
 〈Definition for *maxloss* 206〉 Used in section 117.
 〈Definition for *measure_OK* 53〉 Used in section 44.
 〈Definition for *quick_guess* 293〉 Used in section 253.
 〈Definition for *read_number* 106〉 Used in section 94.
 〈Definition for *skip_white* 104〉 Used in section 94.
 〈Definition for *slow_guess* 288〉

- ⟨Definition for *twoprime* 280⟩ Used in section 253.
- ⟨Definition for *twounprime* 282⟩ Used in section 253.
- ⟨Estimate the backscattered reflection 264⟩ Used in section 262.
- ⟨Estimate the scattered transmission 265⟩ Used in section 262.
- ⟨Estimate *aprime* 294⟩ Used in section 293.
- ⟨Estimate *bprime* 295⟩ Used in sections 297, 301, and 302.
- ⟨Evaluate the *BaG* simplex at the nodes 246⟩ Used in section 244.
- ⟨Evaluate the *BsG* simplex at the nodes 251⟩ Used in section 249.
- ⟨Evaluate the *bg* simplex at the nodes 241⟩ Used in section 238.
- ⟨Evaluate the *a* and *b* simplex at the nodes 217⟩ Used in section 213.
- ⟨Evaluate the *a* and *g* simplex at the nodes 235⟩ Used in section 233.
- ⟨Exit with bad input data 49⟩ Used in section 48.
- ⟨Fill *r* with reasonable values 65, 66, 67, 68⟩ Used in section 64.
- ⟨Find the optical properties 50⟩ Used in section 48.
- ⟨Find thickness when multiple internal reflections are present 260⟩ Used in section 256.
- ⟨Free simplex data structures 220⟩ Used in sections 213, 233, 238, 244, and 249.
- ⟨Generate next albedo using *j* 158, 159⟩ Used in sections 156 and 161.
- ⟨Get the initial *a*, *b*, and *g* 215⟩ Used in sections 213, 233, 238, 244, and 249.
- ⟨Guess when all three measurements are known 298⟩ Used in section 293.
- ⟨Guess when finding albedo 299⟩ Used in section 298.
- ⟨Guess when finding anisotropy and albedo 302⟩ Used in section 298.
- ⟨Guess when finding optical depth 300⟩ Used in section 298.
- ⟨Guess when finding the albedo and optical depth 301⟩ Used in section 298.
- ⟨Guess when only reflection is known 296⟩ Used in section 293.
- ⟨Guess when reflection and transmission are known 297⟩ Used in section 293.
- ⟨Handle options 5⟩ Used in section 2.
- ⟨Improve result using Monte Carlo 15⟩ Used in section 11.
- ⟨Include files for *main* 3, 33⟩ Used in sections 2 and 32.
- ⟨Initialize the nodes of the *a* and *b* simplex 216⟩ Used in section 213.
- ⟨Initialize the nodes of the *a* and *g* simplex 234⟩ Used in section 233.
- ⟨Initialize the nodes of the *ba* and *g* simplex 245⟩ Used in section 244.
- ⟨Initialize the nodes of the *bs* and *g* simplex 250⟩ Used in section 249.
- ⟨Initialize the nodes of the *b* and *g* simplex 240⟩ Used in section 238.
- ⟨Iteratively solve for *b* 231⟩ Used in section 230.
- ⟨Local Variables for Calculation 12⟩ Used in section 11.
- ⟨Nonworking code 157⟩
- ⟨One parameter deviation 182⟩ Used in section 181.
- ⟨One parameter search 61⟩ Used in section 60.
- ⟨Print diagnostics 184⟩ Used in section 176.
- ⟨Print results function 25⟩ Used in section 2.
- ⟨Process the header 35⟩ Used in section 32.
- ⟨Prototype for *Allocate_Grid* 138⟩ Used in sections 118 and 139.
- ⟨Prototype for *Calculate_Distance_With_Corrections* 175⟩ Used in sections 118 and 176.
- ⟨Prototype for *Calculate_Distance* 171⟩ Used in sections 118 and 172.
- ⟨Prototype for *Calculate_Grid_Distance* 173⟩ Used in sections 118 and 174.
- ⟨Prototype for *Calculate_MR_MT* 80⟩ Used in sections 45 and 81.
- ⟨Prototype for *Calculate_Minimum_MR* 82⟩ Used in sections 45 and 83.
- ⟨Prototype for *Debug* 307⟩ Used in sections 254 and 308.
- ⟨Prototype for *Estimate_RT* 261⟩ Used in sections 254 and 262.
- ⟨Prototype for *Fill_AB_Grid* 155⟩ Used in sections 117 and 156.
- ⟨Prototype for *Fill_AG_Grid* 160⟩ Used in sections 117 and 161.
- ⟨Prototype for *Fill_BG_Grid* 163⟩ Used in sections 118 and 164.

- ⟨Prototype for *Fill_BaG_Grid* 165⟩ Used in sections 118 and 166.
- ⟨Prototype for *Fill_BsG_Grid* 167⟩ Used in sections 118 and 168.
- ⟨Prototype for *Fill_Grid* 169⟩ Used in sections 118 and 170.
- ⟨Prototype for *Find_AB_fn* 187⟩ Used in sections 118 and 188.
- ⟨Prototype for *Find_AG_fn* 185⟩ Used in sections 118 and 186.
- ⟨Prototype for *Find_A_fn* 193⟩ Used in sections 118 and 194.
- ⟨Prototype for *Find_BG_fn* 199⟩ Used in sections 118 and 200.
- ⟨Prototype for *Find_B_fn* 195⟩ Used in sections 118 and 196.
- ⟨Prototype for *Find_BaG_fn* 201⟩ Used in sections 118 and 202.
- ⟨Prototype for *Find_Ba_fn* 189⟩ Used in sections 118 and 190.
- ⟨Prototype for *Find_BsG_fn* 203⟩ Used in sections 118 and 204.
- ⟨Prototype for *Find_Bs_fn* 191⟩ Used in sections 118 and 192.
- ⟨Prototype for *Find_G_fn* 197⟩ Used in sections 118 and 198.
- ⟨Prototype for *Gain_11* 123⟩ Used in sections 118 and 124.
- ⟨Prototype for *Gain_22* 125⟩ Used in sections 118 and 126.
- ⟨Prototype for *Gain* 121⟩ Used in sections 118 and 122.
- ⟨Prototype for *Get_Calc_State* 134⟩ Used in sections 118 and 135.
- ⟨Prototype for *Grid_ABG* 140⟩ Used in sections 118 and 141.
- ⟨Prototype for *Initialize_Measure* 71⟩ Used in sections 45 and 72.
- ⟨Prototype for *Initialize_Result* 63⟩ Used in sections 45 and 64.
- ⟨Prototype for *Inverse_RT* 47⟩ Used in sections 45 and 48.
- ⟨Prototype for *Max_Light_Loss* 207⟩ Used in sections 118 and 208.
- ⟨Prototype for *MinMax_MR_MT* 84⟩ Used in sections 45 and 85.
- ⟨Prototype for *Near_Grid_Points* 150⟩ Used in sections 118 and 151.
- ⟨Prototype for *Print_Invert_Type* 309⟩ Used in sections 254 and 310.
- ⟨Prototype for *Print_Measure_Type* 311⟩ Used in sections 254 and 312.
- ⟨Prototype for *RT_Flip* 152⟩ Used in section 153.
- ⟨Prototype for *Read_Data_Line* 101⟩ Used in sections 95 and 102.
- ⟨Prototype for *Read_Header* 97⟩ Used in sections 95 and 98.
- ⟨Prototype for *Same_Calc_State* 136⟩ Used in sections 118 and 137.
- ⟨Prototype for *Set_Calc_State* 132⟩ Used in sections 118 and 133.
- ⟨Prototype for *Set_Debugging* 305⟩ Used in sections 254 and 306.
- ⟨Prototype for *Spheres_Inverse_RT2* 86⟩ Used in sections 45, 46, and 87.
- ⟨Prototype for *Spheres_Inverse_RT* 73⟩ Used in sections 46 and 74.
- ⟨Prototype for *Two_Sphere_R* 127⟩ Used in sections 118 and 128.
- ⟨Prototype for *Two_Sphere_T* 129⟩ Used in sections 118 and 130.
- ⟨Prototype for *U_Find_AB* 212⟩ Used in sections 211 and 213.
- ⟨Prototype for *U_Find_AG* 232⟩ Used in sections 211 and 233.
- ⟨Prototype for *U_Find_A* 225⟩ Used in sections 211 and 226.
- ⟨Prototype for *U_Find_BG* 237⟩ Used in sections 211 and 238.
- ⟨Prototype for *U_Find_BaG* 243⟩ Used in sections 211 and 244.
- ⟨Prototype for *U_Find_Ba* 223⟩ Used in sections 211 and 224.
- ⟨Prototype for *U_Find_BsG* 248⟩ Used in sections 211 and 249.
- ⟨Prototype for *U_Find_Bs* 221⟩ Used in sections 211 and 222.
- ⟨Prototype for *U_Find_B* 229⟩ Used in sections 211 and 230.
- ⟨Prototype for *U_Find_G* 227⟩ Used in sections 211 and 228.
- ⟨Prototype for *Valid_Grid* 142⟩ Used in sections 118 and 143.
- ⟨Prototype for *What_Is_B* 255⟩ Used in sections 254 and 256.
- ⟨Prototype for *Write_Header* 109⟩ Used in sections 95 and 110.
- ⟨Prototype for *a2acalc* 267⟩ Used in sections 254 and 268.
- ⟨Prototype for *abg_distance* 148⟩ Used in sections 118 and 149.
- ⟨Prototype for *abgb2ag* 285⟩ Used in sections 254 and 286.

<Prototype for *abgg2ab* 283> Used in sections 254 and 284.
 <Prototype for *acalc2a* 269> Used in sections 254 and 270.
 <Prototype for *b2bcalc* 275> Used in sections 254 and 276.
 <Prototype for *bcalc2b* 277> Used in sections 254 and 278.
 <Prototype for *check_magic* 107> Used in section 108.
 <Prototype for *determine_search* 59> Used in sections 45 and 60.
 <Prototype for *ez_Inverse_RT* 69> Used in sections 45, 46, and 70.
 <Prototype for *g2gcalc* 271> Used in sections 254 and 272.
 <Prototype for *gcalc2g* 273> Used in sections 254 and 274.
 <Prototype for *maxloss* 205> Used in sections 118 and 206.
 <Prototype for *measure_OK* 52> Used in sections 45 and 53.
 <Prototype for *quick_guess* 292> Used in sections 254 and 293.
 <Prototype for *read_number* 105> Used in section 106.
 <Prototype for *skip_white* 103> Used in section 104.
 <Prototype for *slow_guess* 287> Used in section 288.
 <Prototype for *twoprime* 279> Used in sections 254 and 280.
 <Prototype for *twounprime* 281> Used in sections 254 and 282.
 <Put final values in result 219> Used in sections 213, 222, 224, 226, 228, 230, 233, 238, 244, and 249.
 <Read coefficients for reflection sphere 99> Used in section 98.
 <Read coefficients for transmission sphere 100> Used in section 98.
 <Slow guess for *a* alone 289> Used in section 288.
 <Slow guess for *a* and *b* or *a* and *g* 291> Used in section 288.
 <Slow guess for *b* alone 290> Used in section 288.
 <Solve if multiple internal reflections are not present 259> Used in section 256.
 <Structs to export from IAD Types 41, 42, 43> Used in section 38.
 <Testing MC code 16>
 <Tests for invalid grid 144, 145, 146, 147> Used in section 143.
 <Two parameter deviation 183> Used in section 181.
 <Two parameter search 62> Used in section 60.
 <Unused diffusion fragment 209>
 <Write Header 14> Used in section 11.
 <Write first sphere info 114> Used in section 110.
 <Write general sphere info 113> Used in section 110.
 <Write irradiation info 112> Used in section 110.
 <Write measure and inversion info 116> Used in section 110.
 <Write second sphere info 115> Used in section 110.
 <Write slab info 111> Used in section 110.
 <Zero *GG* 162> Used in sections 156, 161, 164, 166, and 168.
 <calculate coefficients function 22, 23> Used in section 2.
 <handle analysis 76> Used in section 74.
 <handle measurement 77> Used in section 74.
 <handle reflection sphere 78> Used in section 74.
 <handle setup 75> Used in section 74.
 <handle transmission sphere 79> Used in section 74.
 <handle2 analysis 92> Used in section 87.
 <handle2 illumination 89> Used in section 87.
 <handle2 measurement 93> Used in section 87.
 <handle2 reflection sphere 90> Used in section 87.
 <handle2 sample 88> Used in section 87.
 <handle2 transmission sphere 91> Used in section 87.
 <iad_calc.c 117>
 <iad_calc.h 118>

[〈iad_find.c 210〉](#)
[〈iad_find.h 211〉](#)
[〈iad_io.c 94〉](#)
[〈iad_io.h 95〉](#)
[〈iad_main.c 2〉](#)
[〈iad_main.h 1〉](#)
[〈iad_main_mus.c 32〉](#)
[〈iad_pub.c 44〉](#)
[〈iad_pub.h 45〉](#)
[〈iad_type.h 38〉](#)
[〈iad_util.c 253〉](#)
[〈iad_util.h 254〉](#)
[〈lib_iad.h 46〉](#)
[〈mystrtod function 28〉](#) Used in section [2](#).
[〈old formatting 17〉](#)
[〈parse string into array function 30〉](#) Used in section [2](#).
[〈prepare file for reading 10〉](#) Used in section [2](#).
[〈print dot function 31〉](#) Used in section [2](#).
[〈print error legend function 26〉](#) Used in section [2](#).
[〈print results header function 24〉](#) Used in section [2](#).
[〈print usage function 21〉](#) Used in section [2](#).
[〈print version function 20〉](#) Used in section [2](#).
[〈seconds elapsed function 29〉](#) Used in section [2](#).
[〈stringdup together function 27〉](#) Used in section [2](#).