Inverse Adding-Doubling

(Version 3-16-1)

1. `iad` program.

Here is a relatively robust command-line utility that shows how the iad and ad subroutines might be called. It suffers because it is written in `CWEB` and I used the macro expansion feature instead of creating separate functions. Oh well.

I create an empty file `iad_main.h` to simplify the Makefile

⟨ `iad_main.h` 1 ⟩ ≡

2. All the actual output for this web file goes into `iad_main.c`

```
⟨ iad_main.c 2 ⟩ ≡
  ⟨ Include files for main 3 ⟩
  ⟨ print version function 20 ⟩
  ⟨ print usage function 21 ⟩
  ⟨ stringdup together function 27 ⟩
  ⟨ mystrtod function 28 ⟩
  ⟨ seconds elapsed function 29 ⟩
  ⟨ print error legend function 26 ⟩
  ⟨ what_char function 31 ⟩
  ⟨ print long error function 32 ⟩
  ⟨ print dot function 33 ⟩
  ⟨ calculate coefficients function 22 ⟩
  ⟨ parse string into array function 30 ⟩
  ⟨ print results header function 24 ⟩
  ⟨ Print results function 25 ⟩
  int main(int argc, char **argv)
  {
    ⟨ Declare variables for main 4 ⟩
    ⟨ Save command-line for use later 5 ⟩
    ⟨ Handle options 6 ⟩
    Initialize_Measure(&m);
    ⟨ Command-line changes to m 17 ⟩
    Initialize_Result(m, &r, TRUE);
    ⟨ Command-line changes to r 14 ⟩
    if (cl_forward_calc ≠ UNINITIALIZED) {
      ⟨ Calculate and Print the Forward Calculation 7 ⟩
      exit(EXIT_SUCCESS);
    }
    ⟨ prepare file for reading 11 ⟩
    if (process_command_line) {
      ⟨ Count command-line measurements 19 ⟩
      ⟨ Calculate and write optical properties 12 ⟩
      exit(EXIT_SUCCESS);
    }
    if (Read_Header(stdin, &m, &params) ≡ 0) {
      start_time = clock( );
      while (Read_Data_Line(stdin, &m, &r, params) ≡ 0) {
        ⟨ Command-line changes to m 17 ⟩
        ⟨ Calculate and write optical properties 12 ⟩
      }
    }
    if (cl_verbosity > 0) fprintf(stderr, "\n\n");
    if (any_error ∧ cl_verbosity > 1) print_error_legend( );
    exit(EXIT_SUCCESS);
  }
```

3. The first two defines are to stop Visual C++ from silly complaints

⟨ Include files for *main* 3 ⟩ ≡

```
#define _CRT_SECURE_NO_WARNINGS
#define _CRT_NONSTDC_NO_WARNINGS
#define NO_SLIDES 0
#define ONE_SLIDE_ON_TOP 1
#define TWO_IDENTICAL_SLIDES 2
#define ONE_SLIDE_ON_BOTTOM 3
#define ONE_SLIDE_NEAR_SPHERE 4
#define ONE_SLIDE_NOT_NEAR_SPHERE 5
#define MR_IS_ONLY_RD 1
#define MT_IS_ONLY_TD 2
#define NO_UNSCATTERED_LIGHT 3
#include <stdio.h>
#include <string.h>
#include <stdlib.h>
#include <unistd.h>
#include <time.h>
#include <math.h>
#include <ctype.h>
#include <errno.h>
#include "ad_globl.h"
#include "ad_prime.h"
#include "iad_type.h"
#include "iad_pub.h"
#include "iad_io.h"
#include "iad_calc.h"
#include "iad_util.h"
#include "version.h"
#include "mc_lost.h"
#include "ad_frsnl.h"
```

See also section 35.

This code is used in sections 2 and 34.

4. ⟨ Declare variables for *main* 4 ⟩ ≡

```
struct measure_type m;
struct invert_type r;
char *g_out_name = Λ;
int c;
long n_photons = 100000;
int MAX_MC_iterations = 19;
int any_error = 0;
int process_command_line = 0;
int params = 0;
int cl_quadrature_points = UNINITIALIZED;
int cl_verbosity = 2;
double cl_forward_calc = UNINITIALIZED;
double cl_default_a = UNINITIALIZED;
double cl_default_g = UNINITIALIZED;
double cl_default_b = UNINITIALIZED;
double cl_default_mua = UNINITIALIZED;
double cl_default_mus = UNINITIALIZED;
double cl_tolerance = UNINITIALIZED;
double cl_slide_OD = UNINITIALIZED;
double cl_cos_angle = UNINITIALIZED;
double cl_beam_d = UNINITIALIZED;
double cl_sample_d = UNINITIALIZED;
double cl_sample_n = UNINITIALIZED;
double cl_slide_d = UNINITIALIZED;
double cl_slide_n = UNINITIALIZED;
double cl_slides = UNINITIALIZED;
double cl_default_fr = UNINITIALIZED;
double cl_rstd_t = UNINITIALIZED;
double cl_rstd_r = UNINITIALIZED;
double cl_baffle_r = UNINITIALIZED;
double cl_baffle_t = UNINITIALIZED;
double cl_rc_fraction = UNINITIALIZED;
double cl_tc_fraction = UNINITIALIZED;
double cl_lambda = UNINITIALIZED;
double cl_rwall_r = UNINITIALIZED;
double cl_rwall_t = UNINITIALIZED;
double cl_search = UNINITIALIZED;
double cl_mus0 = UNINITIALIZED;
double cl_musp0 = UNINITIALIZED;
double cl_mus0_pwr = UNINITIALIZED;
double cl_mus0_lambda = UNINITIALIZED;
double cl_UR1 = UNINITIALIZED;
double cl_UT1 = UNINITIALIZED;
double cl_Tc = UNINITIALIZED;
double cl_method = UNINITIALIZED;
int cl_num_spheres = UNINITIALIZED;
double cl_sphere_one[5] = {UNINITIALIZED, UNINITIALIZED, UNINITIALIZED, UNINITIALIZED,
    UNINITIALIZED};
double cl_sphere_two[5] = {UNINITIALIZED, UNINITIALIZED, UNINITIALIZED, UNINITIALIZED,
    UNINITIALIZED};
clock_t start_time = clock( );
```

```
char command_line_options[] = "1:2:a:A:b:B:c:C:d:D:e:E:f:F:g:G:hH:i:L:M:n:N:o:p:q:r:R:s:S:\
    t:T:u:vV:w:W:x:Xz";
char *command_line = Λ;
```

See also section 36.

This code is used in sections 2 and 34.

5. I want to add the command line to the output file. To do this, we need to save the entire thing before the options get processed. The extra +1 in the total length calculation is for the space character between options. Finally, we need to reset *optind* to 1 to start *getopt*( ) processing from the beginning. It should be noted that this strips any quotes from the command-line.

```
⟨ Save command-line for use later 5 ⟩ ≡
{
  size_t command_line_length = 0;
  for (int i = 0; i < argc; ++i) {
    command_line_length += strlen(argv[i]) + 3;
  }
  command_line = (char *) malloc(command_line_length);
  if (command_line ≡ Λ) {
    fprintf(stderr, "Memory␣allocation␣failed\n");
    return 1;
  }
  strcpy(command_line, "");
  for (int i = 0; i < argc; ++i) {
    if (strchr(argv[i], '␣') ≠ Λ) {
      strcat(command_line, "'");
      strcat(command_line, argv[i]);
      strcat(command_line, "'␣");
    }
    else {
      strcat(command_line, argv[i]);
      strcat(command_line, "␣");
    }
  }
  optind = 1;
}
```

This code is used in section 2.

6. use the *getopt*( ) to process options.

```
⟨ Handle options 6 ⟩ ≡
  while ((c = getopt(argc, argv, command_line_options)) ≠ EOF) {
    int n;
    char cc;
    char *tmp_str = Λ;
    switch (c) {
    case '1': tmp_str = strdup(optarg);
      parse_string_into_array(optarg, cl_sphere_one, 5);
      if (cl_sphere_one[4] ≡ UNINITIALIZED) {
        fprintf(stderr, "Error␣in␣command-line␣argument␣for␣-1\n");
        fprintf(stderr, "␣␣␣␣␣the␣current␣argument␣is␣'%s'␣but␣it␣must␣have␣5␣terms:␣", tmp_str);
        fprintf(stderr, "'d_sphere␣d_sample␣d_empty␣d_detector␣r_wall'\n");
        exit(EXIT_FAILURE);
      }
      break;
    case '2': tmp_str = strdup(optarg);
      parse_string_into_array(optarg, cl_sphere_two, 5);
      if (cl_sphere_two[4] ≡ UNINITIALIZED) {
        fprintf(stderr, "Error␣in␣command-line␣argument␣for␣-2\n");
        fprintf(stderr, "␣␣␣␣␣the␣current␣argument␣is␣'%s'␣but␣it␣must␣have␣5␣terms:␣", tmp_str);
        fprintf(stderr, "'d_sphere␣d_sample␣d_empty␣d_detector␣r_wall'\n");
        exit(EXIT_FAILURE);
      }
      break;
    case 'a': cl_default_a = my_strtod(optarg);
      if (cl_default_a < 0 ∨ cl_default_a > 1) {
        fprintf(stderr, "Error␣in␣command-line\n");
        fprintf(stderr, "␣␣␣␣␣albedo␣'-a␣%s'\n", optarg);
        exit(EXIT_FAILURE);
      }
      break;
    case 'A': cl_default_mua = my_strtod(optarg);
      if (cl_default_mua < 0) {
        fprintf(stderr, "Error␣in␣command-line\n");
        fprintf(stderr, "␣␣␣␣␣absorption␣'-A␣%s'\n", optarg);
        exit(EXIT_FAILURE);
      }
      break;
    case 'b': cl_default_b = my_strtod(optarg);
      if (cl_default_b < 0) {
        fprintf(stderr, "Error␣in␣command-line\n");
        fprintf(stderr, "␣␣␣␣␣optical␣thickness␣'-b␣%s'\n", optarg);
        exit(EXIT_FAILURE);
      }
      break;
    case 'B': cl_beam_d = my_strtod(optarg);
      if (cl_beam_d < 0) {
        fprintf(stderr, "Error␣in␣command-line\n");
        fprintf(stderr, "␣␣␣␣␣beam␣diameter␣'-B␣%s'\n", optarg);
        exit(EXIT_FAILURE);
      }
```

```
    break;
  case 'c': cl_rc_fraction = my_strtod(optarg);
    if (cl_rc_fraction < 0.0 ∨ cl_rc_fraction > 1.0) {
      fprintf(stderr, "Error␣in␣command-line\n");
      fprintf(stderr, "␣␣␣␣unscattered␣refl␣fraction␣'-c␣%s'\n", optarg);
      fprintf(stderr, "␣␣␣␣must␣be␣between␣0␣and␣1\n");
      exit(EXIT_SUCCESS);
    }
    break;
  case 'C': cl_tc_fraction = my_strtod(optarg);
    if (cl_tc_fraction < 0.0 ∨ cl_tc_fraction > 1.0) {
      fprintf(stderr, "Error␣in␣command-line\n");
      fprintf(stderr, "␣␣␣␣unscattered␣trans␣fraction␣'-C␣%s'\n", optarg);
      fprintf(stderr, "␣␣␣␣must␣be␣between␣0␣and␣1\n");
      exit(EXIT_SUCCESS);
    }
    break;
  case 'd': cl_sample_d = my_strtod(optarg);
    if (cl_sample_d < 0) {
      fprintf(stderr, "Error␣in␣command-line\n");
      fprintf(stderr, "␣␣␣␣sample␣thickness␣'-d␣%s'\n", optarg);
      exit(EXIT_FAILURE);
    }
    break;
  case 'D': cl_slide_d = my_strtod(optarg);
    if (cl_slide_d < 0) {
      fprintf(stderr, "Error␣in␣command-line\n");
      fprintf(stderr, "␣␣␣␣slide␣thickness␣'-D␣%s'\n", optarg);
      exit(EXIT_FAILURE);
    }
    break;
  case 'e': cl_tolerance = my_strtod(optarg);
    if (cl_tolerance < 0) {
      fprintf(stderr, "Error␣in␣command-line\n");
      fprintf(stderr, "␣␣␣␣error␣tolerance␣'-e␣%s'\n", optarg);
      exit(EXIT_FAILURE);
    }
    break;
  case 'E': cl_slide_OD = my_strtod(optarg);
    if (cl_slide_OD < 0) {
      fprintf(stderr, "Error␣in␣command-line\n");
      fprintf(stderr, "␣␣␣␣slide␣optical␣depth␣'-E␣%s'\n", optarg);
      exit(EXIT_FAILURE);
    }
    break;
  case 'f': cl_default_fr = my_strtod(optarg);
    if (cl_default_fr < 0.0 ∨ cl_default_fr > 1.0) {
      fprintf(stderr, "Error␣in␣command-line␣argument:␣");
      fprintf(stderr, "'-f␣%s'␣The␣argument␣must␣be␣between␣0␣and␣1.\n", optarg);
      exit(EXIT_SUCCESS);
    }
    break;
```

```
case 'F':      /* initial digit means this is mus is constant */
  if (isdigit(optarg[0])) {
    cl_default_mus = my_strtod(optarg);
    if (cl_default_mus < 0) {
      fprintf(stderr, "Error in command-line\n");
      fprintf(stderr, "    mus '-F %s'\n", optarg);
      exit(EXIT_FAILURE);
    }
    break;
  }     /* should be a string like 'R 1000 1.2 -1.8' */
  n = sscanf(optarg, "%c %lf %lf %lf", &cc, &cl_mus0_lambda, &cl_mus0, &cl_mus0_pwr);
  if (n ≠ 4 ∨ (cc ≠ 'P' ∧ cc ≠ 'R')) {
    fprintf(stderr, "Error in command-line\n");
    fprintf(stderr, "    bad -F option. '-F %s'\n", optarg);
    fprintf(stderr, "    -F 1.0                for mus=1.0\n");
    fprintf(stderr, "    -F 'P 500 1.0 -1.3' for mus=1.0*(lambda/500)^(-1.3)\n");
    fprintf(stderr, "    -F 'R 500 1.0 -1.3' for mus'=1.0*(lambda/500)^(-1.3)\n");
    exit(EXIT_FAILURE);
  }
  if (cc ≡ 'R' ∨ cc ≡ 'r') {
    cl_musp0 = cl_mus0;
    cl_mus0 = UNINITIALIZED;
  }
  break;
case 'g': cl_default_g = my_strtod(optarg);
  if (cl_default_g < -1 ∨ cl_default_g > 1) {
    fprintf(stderr, "Error in command-line\n");
    fprintf(stderr, "    anisotropy '-g %s'\n", optarg);
    exit(EXIT_FAILURE);
  }
  break;
case 'G':
  if (optarg[0] ≡ '0') cl_slides = NO_SLIDES;
  else if (optarg[0] ≡ '2') cl_slides = TWO_IDENTICAL_SLIDES;
  else if (optarg[0] ≡ 't' ∨ optarg[0] ≡ 'T') cl_slides = ONE_SLIDE_ON_TOP;
  else if (optarg[0] ≡ 'b' ∨ optarg[0] ≡ 'B') cl_slides = ONE_SLIDE_ON_BOTTOM;
  else if (optarg[0] ≡ 'n' ∨ optarg[0] ≡ 'N') cl_slides = ONE_SLIDE_NEAR_SPHERE;
  else if (optarg[0] ≡ 'f' ∨ optarg[0] ≡ 'F') cl_slides = ONE_SLIDE_NOT_NEAR_SPHERE;
  else {
    fprintf(stderr, "Error in command-line\n");
    fprintf(stderr, "    Argument for '-G %s' must be \n", optarg);
    fprintf(stderr, "    't' --- light always hits top slide first\n");
    fprintf(stderr, "    'b' --- light always hits bottom slide first\n");
    fprintf(stderr, "    'n' --- slide always closest to sphere\n");
    fprintf(stderr, "    'f' --- slide always farthest from sphere\n");
    exit(EXIT_FAILURE);
  }
  break;
case 'H':
  if (optarg[0] ≡ '0') {
    cl_baffle_r = 0;
    cl_baffle_t = 0;
```

```
    }
    else if (optarg[0] ≡ '1') {
      cl_baffle_r = 1;
      cl_baffle_t = 0;
    }
    else if (optarg[0] ≡ '2') {
      cl_baffle_r = 0;
      cl_baffle_t = 1;
    }
    else if (optarg[0] ≡ '3') {
      cl_baffle_r = 1;
      cl_baffle_t = 1;
    }
    else {
      fprintf(stderr, "Error␣in␣command-line␣-H␣argument\n");
      fprintf(stderr, "␣␣␣␣argument␣is␣'%s',␣but␣", optarg);
      fprintf(stderr, "must␣be␣0,␣1,␣2,␣or␣3\n");
      exit(EXIT_FAILURE);
    }
  case 'i': cl_cos_angle = my_strtod(optarg);
    if (cl_cos_angle < 0 ∨ cl_cos_angle > 90) {
      fprintf(stderr, "Error␣in␣command-line\n");
      fprintf(stderr, "␣␣␣␣incident␣angle␣'-i␣%s'\n", optarg);
      fprintf(stderr, "␣␣␣␣must␣be␣between␣0␣and␣90␣degrees\n");
      exit(EXIT_FAILURE);
    }
    cl_cos_angle = cos(cl_cos_angle * M_PI/180.0);
    break;
  case 'L': cl_lambda = my_strtod(optarg);
    break;
  case 'M': MAX_MC_iterations = (int) my_strtod(optarg);
    if (MAX_MC_iterations < 0 ∨ MAX_MC_iterations > 50) {
      fprintf(stderr, "Error␣in␣command-line\n");
      fprintf(stderr, "␣␣␣␣MC␣iterations␣'-M␣%s'\n", optarg);
      exit(EXIT_FAILURE);
    }
    break;
  case 'n': cl_sample_n = my_strtod(optarg);
    if (cl_sample_n < 0.1 ∨ cl_sample_n > 10) {
      fprintf(stderr, "Error␣in␣command-line\n");
      fprintf(stderr, "␣␣␣␣slab␣index␣'-n␣%s'\n", optarg);
      exit(EXIT_FAILURE);
    }
    break;
  case 'N': cl_slide_n = my_strtod(optarg);
    if (cl_slide_n < 0.1 ∨ cl_slide_n > 10) {
      fprintf(stderr, "Error␣in␣command-line\n");
      fprintf(stderr, "␣␣␣␣slide␣index␣'-N␣%s'\n", optarg);
      exit(EXIT_FAILURE);
    }
    break;
  case 'o': g_out_name = strdup(optarg);
```

```
    break;
  case 'p': n_photons = (long) my_strtod(optarg);
    break;
  case 'q': cl_quadrature_points = (int) my_strtod(optarg);
    if (cl_quadrature_points % 4 ≠ 0) {
      fprintf(stderr, "Error in command-line\n");
      fprintf(stderr, "    '-q %s'\n", optarg);
      fprintf(stderr, "    Quadrature points must be a multiple of 4\n");
      exit(EXIT_FAILURE);
    }
    if ((cl_cos_angle ≠ UNINITIALIZED) ∧ (cl_quadrature_points % 12 ≠ 0)) {
      fprintf(stderr, "Error in command-line\n");
      fprintf(stderr, "    '-q %s'\n", optarg);
      fprintf(stderr,
          "    Quadrature points must be multiple of 12 for oblique incidence\n");
      exit(EXIT_FAILURE);
    }
    break;
  case 'r': cl_UR1 = my_strtod(optarg);
    process_command_line = 1;
    if (cl_UR1 < 0 ∨ cl_UR1 > 1) {
      fprintf(stderr, "Error in command-line\n");
      fprintf(stderr, "    UR1 value '-r %s'\n", optarg);
      fprintf(stderr, "    must be between 0 and 1\n");
      exit(EXIT_FAILURE);
    }
    break;
  case 'R': cl_rstd_r = my_strtod(optarg);
    if (cl_rstd_r < 0 ∨ cl_rstd_r > 1) {
      fprintf(stderr, "Error in command-line\n");
      fprintf(stderr, "    Rstd value '-R %s'\n", optarg);
      fprintf(stderr, "    must be between 0 and 1\n");
      exit(EXIT_FAILURE);
    }
    break;
  case 's': cl_search = (int) my_strtod(optarg);
    break;
  case 'S': cl_num_spheres = (int) my_strtod(optarg);
    if (cl_num_spheres ≠ 0 ∧ cl_num_spheres ≠ 1 ∧ cl_num_spheres ≠ 2) {
      fprintf(stderr, "Error in command-line\n");
      fprintf(stderr, "    sphere number '-S %s'\n", optarg);
      fprintf(stderr, "    must be 0, 1, or 2\n");
      exit(EXIT_FAILURE);
    }
    break;
  case 't': cl_UT1 = my_strtod(optarg);
    if (cl_UT1 < 0 ∨ cl_UT1 > 1) {
      fprintf(stderr, "Error in command-line\n");
      fprintf(stderr, "    UT1 value '-t %s'\n", optarg);
      fprintf(stderr, "    must be between 0 and 1\n");
      exit(EXIT_FAILURE);
    }
```

```
    process_command_line = 1;
    break;
  case 'T': cl_rstd_t = my_strtod(optarg);
    if (cl_rstd_t < 0 ∨ cl_rstd_t > 1) {
      fprintf(stderr, "Error in command-line\n");
      fprintf(stderr, "     transmission standard '-T %s'\n", optarg);
      fprintf(stderr, "     must be between 0 and 1\n");
      exit(EXIT_FAILURE);
    }
    break;
  case 'u': cl_Tc = my_strtod(optarg);
    if (cl_Tc < 0 ∨ cl_Tc > 1) {
      fprintf(stderr, "Error in command-line\n");
      fprintf(stderr, "     unscattered transmission '-u %s'\n", optarg);
      fprintf(stderr, "     must be between 0 and 1\n");
      exit(EXIT_FAILURE);
    }
    process_command_line = 1;
    break;
  case 'v': print_version(cl_verbosity);
    exit(EXIT_SUCCESS);
    break;
  case 'V': cl_verbosity = my_strtod(optarg);
    break;
  case 'w': cl_rwall_r = my_strtod(optarg);
    if (cl_rwall_r < 0 ∨ cl_rwall_r > 1) {
      fprintf(stderr, "Error in command-line\n");
      fprintf(stderr, "     refl sphere wall '-w %s'\n", optarg);
      fprintf(stderr, "     must be between 0 and 1\n");
      exit(EXIT_FAILURE);
    }
    break;
  case 'W': cl_rwall_t = my_strtod(optarg);
    if (cl_rwall_t < 0 ∨ cl_rwall_r > 1) {
      fprintf(stderr, "Error in command-line\n");
      fprintf(stderr, "     trans sphere wall '-w %s'\n", optarg);
      fprintf(stderr, "     must be between 0 and 1\n");
      exit(EXIT_FAILURE);
    }
    break;
  case 'x': Set_Debugging((int) my_strtod(optarg));
    break;
  case 'X': cl_method = COMPARISON;
    break;
  case 'z': cl_forward_calc = 1;
    process_command_line = 1;
    break;
  default: fprintf(stderr, "unknown option '%c'\n", c);      /* fall through */
  case 'h': print_usage( );
    exit(EXIT_SUCCESS);
  }
}
```

```
argc -= optind;
argv += optind;
```

This code is used in section 2.

7. We are doing a forward calculation. We still need to set the albedo and optical depth appropriately. Obviously when the -a switch is used then the albedo should be fixed as a constant equal to *cl_default_a*. The other cases are less clear. If scattering and absorption are both specified, then calculate the albedo using these values. If the scattering is not specified, then we assume that the sample is an unscattering sample and therefore the albedo is zero. On the other hand, if the scattering is specified and the absorption is not, then the albedo is set to one.

```
⟨ Calculate and Print the Forward Calculation 7 ⟩ ≡
  if (cl_default_a ≡ UNINITIALIZED) {
    if (cl_default_mus ≡ UNINITIALIZED) r.a = 0;
    else if (cl_default_mua ≡ UNINITIALIZED) r.a = 1;
    else r.a = cl_default_mus/(cl_default_mua + cl_default_mus);
  }
  else r.a = cl_default_a;
```

See also sections 8, 9, and 10.

This code is used in section 2.

8. This is slightly more tricky because there are four things that can affect the optical thickness — *cl_default_b*, the default mua, default mus and the thickness. If the sample thickness is unspecified, then the only reasonable thing to do is to assume that the sample is very thick. Otherwise, we use the sample thickness to calculate the optical thickness.

```
⟨ Calculate and Print the Forward Calculation 7 ⟩ +≡
  if (cl_default_b ≡ UNINITIALIZED) {
    if (cl_sample_d ≡ UNINITIALIZED) r.b = HUGE_VAL;
    else if (r.a ≡ 0) {
      if (cl_default_mua ≡ UNINITIALIZED) r.b = HUGE_VAL;
      else r.b = cl_default_mua * cl_sample_d;
    }
    else {
      if (cl_default_mus ≡ UNINITIALIZED) r.b = HUGE_VAL;
      else r.b = cl_default_mus/r.a * cl_sample_d;
    }
  }
  else r.b = cl_default_b;
```

9. The easiest case, use the default value or set it to zero

```
⟨ Calculate and Print the Forward Calculation 7 ⟩ +≡
  if (cl_default_g ≡ UNINITIALIZED) r.g = 0;
  else r.g = cl_default_g;
```

10. ⟨ Calculate and Print the Forward Calculation 7 ⟩ +≡

```
r.slab.a = r.a;
r.slab.b = r.b;
r.slab.g = r.g;
{
  double mu_sp, mu_a, m_r, m_t;
  Calculate_MR_MT(m, r, TRUE, TRUE, &m_r, &m_t);
  Calculate_Mua_Musp(m, r, &mu_sp, &mu_a);
  if (cl_verbosity > 0) {
    Write_Header(m, r, -1, command_line);
    print_results_header(stdout);
  }
  if (m.as_r ≠ 0 ∧ r.default_a ≠ 0 ∧ MAX_MC_iterations > 0) {
    double ur1, ut1, uru, utu;
    MC_Lost(m, r, n_photons, &ur1, &ut1, &uru, &utu, &m.ur1_lost, &m.ut1_lost, &m.uru_lost,
        &m.utu_lost);
    m_r -= m.ur1_lost;
    m_t -= m.ut1_lost;
  }
  print_optical_property_result(stdout, m, r, m_r, m_t, mu_a, mu_sp, 0);
}
```

11. Make sure that the file is not named '-' and warn about too many files

```
⟨ prepare file for reading 11 ⟩ ≡
  if (argc > 1) {
    fprintf(stderr, "Only␣a␣single␣file␣can␣be␣processed␣at␣a␣time\n");
    fprintf(stderr, "try␣'apply␣iad␣file1␣file2␣...␣fileN'\n");
    exit(EXIT_FAILURE);
  }
  if (argc ≡ 1 ∧ strcmp(argv[0], "-") ≠ 0) {      /* filename exists and != "-" */
    int n;
    char *base_name, *rt_name;
    base_name = strdup(argv[0]);
    n = (int)(strlen(base_name) − strlen(".rxt"));
    if (n > 0 ∧ strstr(base_name + n, ".rxt") ≠ Λ) base_name[n] = '\0';
    rt_name = strdup_together(base_name, ".rxt");
    if (freopen(argv[0], "r", stdin) ≡ Λ ∧ freopen(rt_name, "r", stdin) ≡ Λ) {
      fprintf(stderr, "Could␣not␣open␣either␣'%s'␣or␣'%s'\n", argv[0], rt_name);
      exit(EXIT_FAILURE);
    }
    if (g_out_name ≡ Λ) g_out_name = strdup_together(base_name, ".txt");
    free(rt_name);
    free(base_name);
    process_command_line = 0;
  }
  if (g_out_name ≠ Λ) {
    if (freopen(g_out_name, "w", stdout) ≡ Λ) {
      fprintf(stderr, "Could␣not␣open␣file␣'%s'␣for␣output\n", g_out_name);
      exit(EXIT_FAILURE);
    }
  }
```

This code is used in section 2.

12. Need to explicitly reset *r.search* each time through the loop, because it will get altered by the calculation process. This also allows the command line to overwrite the reflection or transmission value from the command-line with something like `-r 0` or `-t 0`.

We also want to be able to let different lines have different constraints. In particular consider the file `newton.tst`. In that file the first two rows contain three real measurements and the last two have the collimated transmission explicitly set to zero — in other words there are really only two measurements.

```
⟨ Calculate and write optical properties 12 ⟩ ≡
  {
    ⟨ Local Variables for Calculation 13 ⟩
    if (Debug(DEBUG_ANY)) {
      fprintf(stderr, "\n--------------------NEXT␣DATA␣POINT----------------------\n");
      if (m.lambda ≠ 0) fprintf(stderr, "lambda=%6.1f␣", m.lambda);
      fprintf(stderr, "MR=%8.5f␣MT=%8.5f\n\n", m.m_r, m.m_t);
    }
    Initialize_Result(m, &r, FALSE);
    ⟨ Command-line changes to r 14 ⟩
    ⟨ Warn and quit for bad options 18 ⟩
    ⟨ Write Header 15 ⟩
    m.ur1_lost = 0;
    m.uru_lost = 0;
    m.ut1_lost = 0;
    m.utu_lost = 0;
    Inverse_RT(m, &r);
    ⟨ Improve result using Monte Carlo 16 ⟩
    calculate_coefficients(m, r, &LR, &LT, &mu_sp, &mu_a);
    print_optical_property_result(stdout, m, r, LR, LT, mu_a, mu_sp, rt_total);
    if (r.error ≠ IAD_NO_ERROR) any_error = 1;
    if (Debug(DEBUG_ANY)) print_long_error(r.error);
    else print_dot(start_time, r.error, mc_total, TRUE, cl_verbosity);
  }
```

See also section 38.

This code is used in sections 2 and 34.

13.

```
⟨ Local Variables for Calculation 13 ⟩ ≡
  static int rt_total = 0;
  static int mc_total = 0;
  double ur1 = 0;
  double ut1 = 0;
  double uru = 0;
  double utu = 0;
  double mu_a = 0;
  double mu_sp = 0;
  double LR = 0;
  double LT = 0;
  rt_total++;
```

This code is used in section 12.

14. ⟨ Command-line changes to r 14 ⟩ ≡

```
if (cl_quadrature_points ≠ UNINITIALIZED) r.method.quad_pts = cl_quadrature_points;
else r.method.quad_pts = 8;
if (cl_default_a ≠ UNINITIALIZED) r.default_a = cl_default_a;
if (cl_default_mua ≠ UNINITIALIZED ∧ r.default_mua ≠ UNINITIALIZED) {
  r.default_mua = cl_default_mua;
  if (cl_sample_d ≠ UNINITIALIZED) r.default_ba = cl_default_mua * cl_sample_d;
  else r.default_ba = cl_default_mua * m.slab_thickness;
}
if (cl_default_b ≠ UNINITIALIZED) r.default_b = cl_default_b;
if (cl_default_g ≠ UNINITIALIZED) r.default_g = cl_default_g;
if (cl_tolerance ≠ UNINITIALIZED) {
  r.tolerance = cl_tolerance;
  r.MC_tolerance = cl_tolerance;
}
if (cl_musp0 ≠ UNINITIALIZED)
  cl_mus0 = (r.default_g ≠ UNINITIALIZED) ? cl_musp0/(1 − r.default_g) : cl_musp0;
if (cl_mus0 ≠ UNINITIALIZED ∧ m.lambda ≠ 0)
  cl_default_mus = cl_mus0 * pow(m.lambda/cl_mus0_lambda, cl_mus0_pwr);
if (cl_default_mus ≠ UNINITIALIZED) {
  r.default_mus = cl_default_mus;
  if (cl_sample_d ≠ UNINITIALIZED) r.default_bs = cl_default_mus * cl_sample_d;
  else r.default_bs = cl_default_mus * m.slab_thickness;
}
if (cl_search ≠ UNINITIALIZED) r.search = cl_search;
```

This code is used in sections 2 and 12.

15. ⟨ Write Header 15 ⟩ ≡

```
if (rt_total ≡ 1 ∧ cl_verbosity > 0) {
  Write_Header(m, r, params, command_line);
  if (MAX_MC_iterations > 0) {
    if (n_photons ≥ 0)
      fprintf(stdout, "#␣␣Photons␣used␣to␣estimate␣lost␣light␣=␣␣␣%ld\n", n_photons);
    else fprintf(stdout, "#␣␣␣␣␣␣Time␣used␣to␣estimate␣lost␣light␣=␣␣␣%ld␣ms\n", −n_photons);
  }
  else fprintf(stdout, "#␣␣Photons␣used␣to␣estimate␣lost␣light␣=␣␣␣0\n");
  fprintf(stdout, "#\n");
  print_results_header(stdout);
}
```

This code is used in section 12.

16. Use Monte Carlo to figure out how much light leaks out. We use the sphere corrected values as the starting values and only do try Monte Carlo when spheres are used, the albedo unknown or non-zero, and there has been no error. The sphere parameters must be known because otherwise the beam size and the port size are unknown.

```
⟨ Improve result using Monte Carlo 16 ⟩ ≡
  if (r.error ≡ IAD_NO_ERROR ∧ m.num_spheres > 0 ∧ r.default_a ≠ 0) {
    double mu_sp_last = mu_sp;
    double mu_a_last = mu_a;
    if (Debug(DEBUG_LOST_LIGHT)) {
      print_results_header(stderr);
      print_optical_property_result(stderr, m, r, LR, LT, mu_a, mu_sp, rt_total);
    }
    while (r.MC_iterations < MAX_MC_iterations) {
      if (Debug(DEBUG_ITERATIONS))
        fprintf(stderr, "\n-------------␣Monte␣Carlo␣Iteration␣%d␣-----------------\n",
            r.MC_iterations + 1);
      MC_Lost(m, r, n_photons, &ur1, &ut1, &uru, &utu, &m.ur1_lost, &m.ut1_lost, &m.uru_lost,
          &m.utu_lost);
      mc_total++;
      r.MC_iterations++;
      Inverse_RT(m, &r);
      calculate_coefficients(m, r, &LR, &LT, &mu_sp, &mu_a);
      if (fabs(mu_a_last − mu_a)/(mu_a + 0.0001) < r.MC_tolerance ∧ fabs(mu_sp_last − mu_sp)/(mu_sp +
          0.0001) < r.MC_tolerance) break;
      mu_a_last = mu_a;
      mu_sp_last = mu_sp;
      if (Debug(DEBUG_LOST_LIGHT))
        print_optical_property_result(stderr, m, r, LR, LT, mu_a, mu_sp, rt_total);
      else print_dot(start_time, r.error, mc_total, FALSE, cl_verbosity);
      if (r.error ≠ IAD_NO_ERROR) break;
    }
  }
```

This code is used in section 12.

17. Stuff the command line arguments that should be constant over the entire inversion process into the measurement record and set up the result record to handle the arguments properly so that the optical properties can be determined.

```
⟨ Command-line changes to m 17 ⟩ ≡
  if (cl_cos_angle ≠ UNINITIALIZED) {
    m.slab_cos_angle = cl_cos_angle;
    if (cl_quadrature_points ≡ UNINITIALIZED) cl_quadrature_points = 12;
    if (cl_quadrature_points ≠ 12 * (cl_quadrature_points/12)) {
      fprintf(stderr,
          "If you use the -i option to specify an oblique incidence angle, then\n");
      fprintf(stderr, "the number of quadrature points must be a multiple of 12\n");
      exit(EXIT_SUCCESS);
    }
  }
  if (cl_sample_n ≠ UNINITIALIZED) m.slab_index = cl_sample_n;
  if (cl_slide_n ≠ UNINITIALIZED) {
    m.slab_bottom_slide_index = cl_slide_n;
    m.slab_top_slide_index = cl_slide_n;
  }
  if (cl_slide_OD ≠ UNINITIALIZED) {
    m.slab_bottom_slide_b = cl_slide_OD;
    m.slab_top_slide_b = cl_slide_OD;
  }
  if (cl_sample_d ≠ UNINITIALIZED) m.slab_thickness = cl_sample_d;
  if (cl_beam_d ≠ UNINITIALIZED) m.d_beam = cl_beam_d;
  if (cl_slide_d ≠ UNINITIALIZED) {
    m.slab_bottom_slide_thickness = cl_slide_d;
    m.slab_top_slide_thickness = cl_slide_d;
  }
  if (cl_slides ≡ NO_SLIDES) {
    m.slab_bottom_slide_index = 1.0;
    m.slab_bottom_slide_thickness = 0.0;
    m.slab_top_slide_index = 1.0;
    m.slab_top_slide_thickness = 0.0;
  }
  if (cl_slides ≡ ONE_SLIDE_ON_TOP ∨ cl_slides ≡ ONE_SLIDE_NEAR_SPHERE) {
    m.slab_bottom_slide_index = 1.0;
    m.slab_bottom_slide_thickness = 0.0;
  }
  if (cl_slides ≡ ONE_SLIDE_ON_BOTTOM ∨ cl_slides ≡ ONE_SLIDE_NOT_NEAR_SPHERE) {
    m.slab_top_slide_index = 1.0;
    m.slab_top_slide_thickness = 0.0;
  }
  if (cl_slides ≡ ONE_SLIDE_NEAR_SPHERE ∨ cl_slides ≡ ONE_SLIDE_NOT_NEAR_SPHERE) m.flip_sample = 1;
  else m.flip_sample = 0;
  if (cl_method ≠ UNINITIALIZED) m.method = (int) cl_method;
  if (cl_rstd_t ≠ UNINITIALIZED) m.rstd_t = cl_rstd_t;
  if (cl_rstd_r ≠ UNINITIALIZED) m.rstd_r = cl_rstd_r;
  if (cl_rwall_r ≠ UNINITIALIZED) m.rw_r = cl_rwall_r;
  if (cl_rwall_t ≠ UNINITIALIZED) m.rw_t = cl_rwall_t;
  if (cl_sphere_one[0] ≠ UNINITIALIZED) {
    double d_sample_r, d_empty_r, d_detector_r;
```

```
    m.d_sphere_r = cl_sphere_one[0];
    d_sample_r = cl_sphere_one[1];
    d_empty_r = cl_sphere_one[2];
    d_detector_r = cl_sphere_one[3];
    m.rw_r = cl_sphere_one[4];
    m.as_r = (d_sample_r/m.d_sphere_r/2) * (d_sample_r/m.d_sphere_r/2);
    m.ae_r = (d_empty_r/m.d_sphere_r/2) * (d_empty_r/m.d_sphere_r/2);
    m.ad_r = (d_detector_r/m.d_sphere_r/2) * (d_detector_r/m.d_sphere_r/2);
    m.aw_r = 1.0 - m.as_r - m.ae_r - m.ad_r;
    m.d_sphere_t = m.d_sphere_r;
    m.as_t = m.as_r;
    m.ae_t = m.ae_r;
    m.ad_t = m.ad_r;
    m.aw_t = m.aw_r;
    m.rw_t = m.rw_r;
    if (cl_num_spheres ≡ UNINITIALIZED) m.num_spheres = 1;
  }
  if (cl_sphere_two[0] ≠ UNINITIALIZED) {
    double d_sample_t, d_empty_t, d_detector_t;
    m.d_sphere_t = cl_sphere_two[0];
    d_sample_t = cl_sphere_two[1];
    d_empty_t = cl_sphere_two[2];
    d_detector_t = cl_sphere_two[3];
    m.rw_t = cl_sphere_two[4];
    m.as_t = (d_sample_t/m.d_sphere_t/2) * (d_sample_t/m.d_sphere_t/2);
    m.ae_t = (d_empty_t/m.d_sphere_t/2) * (d_empty_t/m.d_sphere_t/2);
    m.ad_t = (d_detector_t/m.d_sphere_t/2) * (d_detector_t/m.d_sphere_t/2);
    m.aw_t = 1.0 - m.as_t - m.ae_t - m.ad_t;
    if (cl_num_spheres ≡ UNINITIALIZED) m.num_spheres = 2;
  }
  if (cl_num_spheres ≠ UNINITIALIZED) {
    m.num_spheres = (int) cl_num_spheres;
    if (m.num_spheres > 0 ∧ m.method ≡ UNKNOWN) m.method = SUBSTITUTION;
  }
  if (cl_rc_fraction ≠ UNINITIALIZED) m.fraction_of_rc_in_mr = cl_rc_fraction;
  if (cl_tc_fraction ≠ UNINITIALIZED) m.fraction_of_tc_in_mt = cl_tc_fraction;
  if (cl_UR1 ≠ UNINITIALIZED) m.m_r = cl_UR1;
  if (cl_UT1 ≠ UNINITIALIZED) m.m_t = cl_UT1;
  if (cl_Tc ≠ UNINITIALIZED) m.m_u = cl_Tc;
  if (cl_default_fr ≠ UNINITIALIZED) m.f_r = cl_default_fr;
  if (cl_baffle_r ≠ UNINITIALIZED) m.baffle_r = cl_baffle_r;
  if (cl_baffle_t ≠ UNINITIALIZED) m.baffle_t = cl_baffle_t;
  if (cl_lambda ≠ UNINITIALIZED) m.lambda = cl_lambda;
```

This code is used in section 2.

18. ⟨ Warn and quit for bad options 18 ⟩ ≡

```
if (cl_method ≡ COMPARISON ∧ m.d_sphere_r ≠ 0 ∧ m.as_r ≡ 0) {
  fprintf(stderr, "A␣dual-beam␣measurement␣is␣specified,␣but␣no␣port␣sizes.\n");
  fprintf(stderr, "You␣might␣forsake␣the␣-X␣option␣and␣use␣zero␣spheres␣(which␣gives\n");
  fprintf(stderr, "the␣same␣result␣except␣lost␣light␣is␣not␣taken␣into␣account).\n");
  fprintf(stderr, "Alternatively,␣bite␣the␣bullet␣and␣enter␣your␣sphere␣parameters,\n");
  fprintf(stderr, "with␣the␣knowledge␣that␣only␣the␣beam␣diameter␣and␣sample␣port\n");
  fprintf(stderr, "diameter␣will␣be␣used␣to␣estimate␣lost␣light␣from␣the␣edges.\n");
  exit(EXIT_SUCCESS);
}
if (cl_method ≡ COMPARISON ∧ m.num_spheres ≡ 2) {
  fprintf(stderr, "A␣dual-beam␣measurement␣is␣specified,␣but␣a␣two␣sphere␣experiment\n");
  fprintf(stderr, "is␣specified.␣Since␣this␣seems␣impossible,␣I␣will␣make␣it\n");
  fprintf(stderr, "impossible␣for␣you␣unless␣you␣specify␣0␣or␣1␣sphere.\n");
  exit(EXIT_SUCCESS);
}
if (cl_method ≡ COMPARISON ∧ m.f_r ≠ 0) {
  fprintf(stderr, "A␣dual-beam␣measurement␣is␣specified,␣but␣a␣fraction␣of␣light\n");
  fprintf(stderr, "is␣specified␣to␣hit␣the␣sphere␣wall␣first.␣␣This␣situation\n");
  fprintf(stderr, "is␣not␣supported␣by␣iad.␣␣Sorry.\n");
  exit(EXIT_SUCCESS);
}
```

This code is used in section 12.

19. put the values for command line reflection and transmission into the measurement record.

⟨ Count command-line measurements 19 ⟩ ≡

```
m.num_measures = 3;
if (m.m_r ≡ 0) m.num_measures−−;
if (m.m_t ≡ 0) m.num_measures−−;
if (m.m_u ≡ 0) m.num_measures−−;
params = m.num_measures;
if (m.num_measures ≡ 3) {      /* need to fill slab entries to calculate the optical thickness */
  struct AD_slab_type s;
  s.n_slab = m.slab_index;
  s.n_top_slide = m.slab_top_slide_index;
  s.n_bottom_slide = m.slab_bottom_slide_index;
  s.b_top_slide = m.slab_top_slide_b;
  s.b_bottom_slide = m.slab_bottom_slide_b;
  s.cos_angle = m.slab_cos_angle;
  cl_default_b = What_Is_B(s, m.m_u);
}
```

This code is used in section 2.

20. ⟨ print version function 20 ⟩ ≡

```
static void print_version(int verbosity)
{
  if (verbosity ≡ 0) {
    fprintf(stdout, "%s", VersionShort);
  }
  else {
    fprintf(stdout, "iad␣%s\n", Version);
    fprintf(stdout, "Copyright␣1993-2024␣Scott␣Prahl,␣scott.prahl@oit.edu\n");
    fprintf(stdout, "␣␣␣␣␣␣␣␣␣␣(see␣Applied␣Optics,␣32:559-568,␣1993)\n\n");
    fprintf(stdout, "This␣is␣free␣software;␣see␣the␣source␣for␣copying␣conditions.\n");
    fprintf(stdout, "There␣is␣no␣warranty;␣not␣even␣for␣MERCHANTABILITY␣or␣FITNESS.\n");
    fprintf(stdout, "FOR␣A␣PARTICULAR␣PURPOSE.\n");
  }
}
```

This code is used in section 2.

21. ⟨ print usage function 21 ⟩ ≡

```
static void print_usage(void)
{
  fprintf(stdout, "iad %s\n\n", Version);
  fprintf(stdout, "iad finds optical properties from measurements\n\n");
  fprintf(stdout, "Usage:  iad [options] input\n\n");
  fprintf(stdout, "Options:\n");
  fprintf(stdout, "  -1 '# # # # #'   reflection sphere parameters \n");
  fprintf(stdout, "                   'd_sphere d d_sample_port d_empty_port d\
      _detector_port r_wall'\n");
  fprintf(stdout, "  -2 '# # # # #'   transmission sphere parameters \n");
  fprintf(stdout, "                   'd_sphere d d_sample_port d_empty_port d\
      _detector_port r_wall'\n");
  fprintf(stdout, "  -a #             use this albedo \n");
  fprintf(stdout, "  -A #             use this absorption coefficient \n");
  fprintf(stdout, "  -b #             use this optical thickness \n");
  fprintf(stdout, "  -B #             beam diameter \n");
  fprintf(stdout, "  -c #             fraction of unscattered refl in MR\n");
  fprintf(stdout, "  -C #             fraction of unscattered trans in MT\n");
  fprintf(stdout, "  -d #             thickness of sample \n");
  fprintf(stdout, "  -D #             thickness of slide \n");
  fprintf(stdout, "  -e #             error tolerance (default 0.0001) \n");
  fprintf(stdout, "  -E #             optical depth (=mua*D) for slides\n");
  fprintf(stdout,
      "  -f #             allow a fraction 0.0-1.0 of light to hit sphere wall first\n");
  fprintf(stdout, "  -F #             constrain scattering coefficient \n");
  fprintf(stdout, "                   # = constant: use constant scattering coefficient \n");
  fprintf(stdout, "                   # = 'P lambda0 mus0 gamma' then mus=mus0\
      *(lambda/lambda0)^gamma\n");
  fprintf(stdout, "                   # = 'R lambda0 musp0 gamma'  musp=musp0*\
      (lambda/lambda0)^gamma\n");
  fprintf(stdout, "  -g #             scattering anisotropy (default 0) \n");
  fprintf(stdout, "  -G #             type of boundary '0', '2', 't', 'b', 'n', 'f' \n");
  fprintf(stdout, "                   '0' or '2'             ---  number of slides\n");
  fprintf(stdout, "                   't' (top) or 'b' (bottom)  ---  one slide \
      that is hit by light first\n");
  fprintf(stdout, "                   'n' (near) or 'f' (far)    ---  one slide \
      position relative to sphere\n");
  fprintf(stdout, "  -h               display help\n");
  fprintf(stdout, "  -H #             # = 0, no baffles for R or T spheres\n");
  fprintf(stdout, "                   # = 1, baffle for R but not for T sphere\n");
  fprintf(stdout, "                   # = 2, baffle for T but not for R sphere\n");
  fprintf(stdout, "                   # = 3, baffle for both R and T spheres (default)\n");
  fprintf(stdout, "  -L #             specify the wavelength lambda\n");
  fprintf(stdout, "  -M #             number of Monte Carlo iterations\n");
  fprintf(stdout, "  -n #             specify index of refraction of slab\n");
  fprintf(stdout, "  -N #             specify index of refraction of slides\n");
  fprintf(stdout, "  -o filename      explicitly specify filename for output\n");
  fprintf(stdout, "  -p #             # of Monte Carlo photons (default 100000)\n");
  fprintf(stdout, "                   a negative number is max MC time in milliseconds\n");
  fprintf(stdout, "  -q #             number of quadrature points (default=8)\n");
  fprintf(stdout, "  -r #             total reflection measurement\n");
```

```
fprintf(stdout,"␣␣-R␣#␣␣␣␣␣␣␣␣␣␣␣␣␣actual␣reflectance␣for␣100%%␣measurement␣\n");
fprintf(stdout,"␣␣-S␣#␣␣␣␣␣␣␣␣␣␣␣␣␣number␣of␣spheres␣used\n");
fprintf(stdout,"␣␣-t␣#␣␣␣␣␣␣␣␣␣␣␣␣␣total␣transmission␣measurement\n");
fprintf(stdout,"␣␣-T␣#␣␣␣␣␣␣␣␣␣␣␣␣␣actual␣transmission␣for␣100%%␣measurement␣\n");
fprintf(stdout,"␣␣-u␣#␣␣␣␣␣␣␣␣␣␣␣␣␣unscattered␣transmission␣measurement\n");
fprintf(stdout,"␣␣-v␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣version␣information\n");
fprintf(stdout,"␣␣-V␣0␣␣␣␣␣␣␣␣␣␣␣␣␣verbosity␣low␣---␣no␣output␣to␣stdout\n");
fprintf(stdout,"␣␣-V␣1␣␣␣␣␣␣␣␣␣␣␣␣␣verbosity␣moderate␣\n");
fprintf(stdout,"␣␣-V␣2␣␣␣␣␣␣␣␣␣␣␣␣␣verbosity␣high\n");
fprintf(stdout,"␣␣-w␣#␣␣␣␣␣␣␣␣␣␣␣␣␣wall␣reflectivity␣for␣reflection␣sphere\n");
fprintf(stdout,"␣␣-W␣#␣␣␣␣␣␣␣␣␣␣␣␣␣wall␣reflectivity␣for␣transmission␣sphere\n");
fprintf(stdout,"␣␣-x␣#␣␣␣␣␣␣␣␣␣␣␣␣␣set␣debugging␣level\n");
fprintf(stdout,"␣␣-X␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣dual␣beam␣configuration\n");
fprintf(stdout,"␣␣-z␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣do␣forward␣calculation\n");
fprintf(stdout,"Examples:\n");
fprintf(stdout,"␣␣iad␣file.rxt␣␣␣␣␣␣␣␣␣␣␣␣␣␣Results␣will␣be␣put␣in␣file.txt\n");
fprintf(stdout,"␣␣iad␣file␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣Same␣as␣above\n");
fprintf(stdout,"␣␣iad␣-c␣0.9␣file.rxt␣␣␣␣␣␣␣Assume␣M_R␣includes␣90%%␣of␣uns\
    cattered␣reflectance\n");
fprintf(stdout,"␣␣iad␣-C␣0.8␣file.rxt␣␣␣␣␣␣␣Assume␣M_T␣includes␣80%%␣of␣uns\
    cattered␣transmittance\n");
fprintf(stdout,"␣␣iad␣-e␣0.0001␣file.rxt␣␣␣␣Better␣convergence␣to␣R␣&␣T␣values\n");
fprintf(stdout,
    "␣␣iad␣-f␣1.0␣file.rxt␣␣␣␣␣␣␣All␣light␣hits␣reflectance␣sphere␣wall␣first\n");
fprintf(stdout,"␣␣iad␣-o␣out␣file.rxt␣␣␣␣␣␣␣Calculated␣values␣in␣out\n");
fprintf(stdout,"␣␣iad␣-r␣0.3␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣R_total=0.3,␣b=inf,␣find␣albedo\n");
fprintf(stdout,"␣␣iad␣-r␣0.3␣-t␣0.4␣␣␣␣␣␣␣␣␣R_total=0.3,␣T_total=0.4,␣find␣a,b,g\n");
fprintf(stdout,"␣␣iad␣-r␣0.3␣-t␣0.4␣-n␣1.5␣␣R_total=0.3,␣T_total=0.4,␣n=1.5,␣find␣a,b\n");
fprintf(stdout,"␣␣iad␣-r␣0.3␣-t␣0.4␣␣␣␣␣␣␣␣␣R_total=0.3,␣T_total=0.4,␣find␣a,b\n");
fprintf(stdout,"␣␣iad␣-p␣1000␣file.rxt␣␣␣␣␣␣Only␣1000␣photons\n");
fprintf(stdout,"␣␣iad␣-p␣-100␣file.rxt␣␣␣␣␣␣Allow␣only␣100ms␣per␣iteration\n");
fprintf(stdout,"␣␣iad␣-q␣4␣file.rxt␣␣␣␣␣␣␣␣␣Four␣quadrature␣points\n");
fprintf(stdout,"␣␣iad␣-M␣0␣file.rxt␣␣␣␣␣␣␣␣␣No␣MC␣␣␣␣(iad)\n");
fprintf(stdout,"␣␣iad␣-M␣1␣file.rxt␣␣␣␣␣␣␣␣␣MC␣once␣␣(iad␣->␣MC␣->␣iad)\n");
fprintf(stdout,"␣␣iad␣-M␣2␣file.rxt␣␣␣␣␣␣␣␣␣MC␣twice␣(iad␣->␣MC␣->␣iad␣->␣MC␣->␣iad)\n");
fprintf(stdout,"␣␣iad␣-M␣0␣-q␣4␣file.rxt␣␣␣␣Fast␣and␣crude␣conversion\n");
fprintf(stdout,
    "␣␣iad␣-G␣t␣file.rxt␣␣␣␣␣␣␣␣␣One␣top␣slide␣with␣properties␣from␣file.rxt\n");
fprintf(stdout,
    "␣␣iad␣-G␣b␣-N␣1.5␣-D␣1␣file␣Use␣1␣bottom␣slide␣with␣n=1.5␣and␣thickness=1\n");
fprintf(stdout,"␣␣iad␣-x␣␣␣1␣file.rxt␣␣␣␣␣␣␣Show␣sphere␣and␣MC␣effects\n");
fprintf(stdout,"␣␣iad␣-x␣␣␣2␣file.rxt␣␣␣␣␣␣␣Show␣grid␣decisions\n");
fprintf(stdout,"␣␣iad␣-x␣␣␣4␣file.rxt␣␣␣␣␣␣␣Show␣interations\n");
fprintf(stdout,"␣␣iad␣-x␣␣␣8␣file.rxt␣␣␣␣␣␣␣Show␣lost␣light␣effects\n");
fprintf(stdout,"␣␣iad␣-x␣␣16␣file.rxt␣␣␣␣␣␣␣Show␣best␣grid␣points\n");
fprintf(stdout,"␣␣iad␣-x␣␣32␣file.rxt␣␣␣␣␣␣␣Show␣decisions␣for␣type␣of␣search\n");
fprintf(stdout,"␣␣iad␣-x␣␣64␣file.rxt␣␣␣␣␣␣␣Show␣all␣grid␣calculations\n");
fprintf(stdout,"␣␣iad␣-x␣128␣file.rxt␣␣␣␣␣␣␣Show␣sphere␣calculations\n");
fprintf(stdout,"␣␣iad␣-x␣256␣file.rxt␣␣␣␣␣␣␣DEBUG_EVERY_CALC\n");
fprintf(stdout,"␣␣iad␣-x␣511␣file.rxt␣␣␣␣␣␣␣Show␣all␣debugging␣output\n");
fprintf(stdout,
    "␣␣iad␣-X␣-i␣8␣file.rxt␣␣␣␣␣␣Dual␣beam␣spectrometer␣with␣8␣degree␣incidence\n\n");
```

```
  fprintf(stdout,
      "␣␣iad␣-z␣-a␣0.9␣-b␣1␣-i␣45␣␣Forward␣calc␣assuming␣45␣degree␣incidence\n\n");
  fprintf(stdout, "␣␣apply␣iad␣x.rxt␣y.rxt␣␣␣␣␣Process␣multiple␣files\n\n");
  fprintf(stdout, "Report␣bugs␣to␣<scott.prahl@oit.edu>\n\n");
}
```

This code is used in section 2.

22. Just figure out the damn scattering and absorption

```
⟨ calculate coefficients function 22 ⟩ ≡
static void Calculate_Mua_Musp(struct measure_type m, struct invert_type r, double
        *musp, double *mua)
{
  if (r.b ≡ HUGE_VAL) {
    if (r.a ≤ 1 · 10^−5) {
      *musp = 0.0;
      *mua = 1.0;
      return;
    }
    if (r.default_mus ≠ UNINITIALIZED) {
      *musp = r.default_mus * (1 − r.g);
      *mua = r.default_mus/r.a − r.default_mus;
      return;
    }
    if (r.default_mua ≠ UNINITIALIZED) {
      *musp = (r.default_mua/(1 − r.a) − r.default_mua) * (1 − r.g);
      *mua = r.default_mua;
      return;
    }
    *musp = 1.0 − r.g;
    *mua = (1.0 − r.a)/r.a;
    return;
  }
  *musp = r.a * r.b/m.slab_thickness * (1.0 − r.g);
  *mua = (1 − r.a) * r.b/m.slab_thickness;
}
```

See also section 23.

This code is used in section 2.

23. This can only be called immediately after *Inverse_RT* You have been warned! Notice that *Calculate_Distance* does not pass any slab properties.

```
⟨ calculate coefficients function 22 ⟩ +≡
static void calculate_coefficients(struct measure_type m, struct invert_type r, double *LR, double
        *LT, double *musp, double *mua)
{
  double delta;
  *LR = 0;
  *LT = 0;
  Calculate_Distance(LR, LT, &delta);
  Calculate_Mua_Musp(m, r, musp, mua);
}
```

24. ⟨ print results header function 24 ⟩ ≡

```
static void print_results_header(FILE *fp)
{
  if (Debug(DEBUG_LOST_LIGHT)) {
    fprintf(fp, "#␣␣␣␣␣␣|␣Meas␣␣␣␣␣␣M_R␣␣|␣Meas␣␣␣␣␣␣M_T␣␣|␣␣calc␣␣␣calc␣␣␣calc␣␣|");
    fprintf(fp, "␣␣Lost␣␣␣Lost␣␣␣Lost␣␣␣Lost␣␣|␣MC␣␣␣IAD␣␣Error\n");
    fprintf(fp, "#␣wave␣|␣␣M_R␣␣␣␣␣␣fit␣␣|␣␣M_T␣␣␣␣␣␣fit␣␣|␣␣mu_a␣␣␣mu_s'␣␣␣g␣␣␣␣|␣␣");
    fprintf(fp, "␣UR1␣␣␣␣URU␣␣␣␣UT1␣␣␣␣UTU␣␣|␣␣#␣␣␣␣#␣␣␣Type\n");
    fprintf(fp, "#␣␣nm␣␣|␣␣---␣␣␣␣␣␣---␣␣|␣␣---␣␣␣␣␣␣---␣␣|␣␣1/mm␣␣␣1/mm␣␣␣␣---␣␣|");
    fprintf(fp, "␣␣␣---␣␣␣␣---␣␣␣␣---␣␣␣␣---␣␣|␣---␣␣---␣␣---\n");
    fprintf(fp, "#------------------------------------------------------------");
    fprintf(fp, "------------------------------------------------------------\n");
  }
  else {
    fprintf(fp, "#␣␣␣␣␣\tMeasured␣\t␣␣␣M_R␣␣␣\tMeasured␣\t␣␣␣M_T␣␣␣\tEstimat\
ed\tEstimated\tEstimated");
    if (Debug(DEBUG_LOST_LIGHT)) fprintf(fp, "\t␣␣Lost␣␣␣\t␣␣Lost␣␣␣\t␣␣Lost␣␣␣\t␣␣Lo\
st␣␣␣\t␣␣␣MC␣␣␣␣\t␣␣␣IAD␣␣␣\t␣␣Error␣␣");
    fprintf(fp, "\n");
    fprintf(fp, "##wave\t␣␣␣M_R␣␣␣\t␣␣␣fit␣␣␣\t␣␣␣M_T␣␣␣\t␣␣␣fit␣␣␣\t␣␣mu_a␣\
␣␣\t␣␣mu_s'␣␣\t␣␣␣␣g␣␣␣␣");
    if (Debug(DEBUG_LOST_LIGHT)) fprintf(fp, "\t␣␣␣UR1␣␣␣\t␣␣␣URU␣␣␣\t␣␣␣UT1␣␣␣\t␣␣␣U\
TU␣␣␣\t␣␣␣␣#␣␣␣␣\t␣␣␣␣#␣␣␣␣\t␣␣State␣␣");
    fprintf(fp, "\n");
    fprintf(fp, "#␣[nm]\t␣␣[---]␣␣\t␣␣[---]␣␣\t␣␣[---]␣␣\t␣␣[---]␣␣\t␣␣1/mm␣\
␣␣\t␣␣1/mm␣␣␣\t␣␣[---]␣␣");
    if (Debug(DEBUG_LOST_LIGHT)) fprintf(fp, "\t␣␣[---]␣␣\t␣␣[---]␣␣\t␣␣[---]␣␣\t␣␣[-\
--]␣␣\t␣␣[---]␣␣\t␣␣[---]␣␣\t␣␣[---]␣␣");
    fprintf(fp, "\n");
  }
}
```

This code is used in section 2.

25. When debugging lost light, it is handy to see how each iteration changes the calculated values for the optical properties. We do that here if we are debugging, otherwise we just print a number or something to keep the user from wondering what is going on.

⟨ Print results function 25 ⟩ ≡

```
void print_optical_property_result(FILE *fp, struct measure_type m, struct invert_type r, double
        LR, double LT, double mu_a, double mu_sp, int line)
{
  if (Debug(DEBUG_LOST_LIGHT)) {
    if (m.lambda ≠ 0) fprintf(fp, "%6.1f␣␣␣", m.lambda);
    else fprintf(fp, "%6d␣␣␣", line);
    if (mu_a ≥ 200) mu_a = 199.9999;
    if (mu_sp ≥ 1000) mu_sp = 999.9999;
    fprintf(fp, "%6.4f␣%␣6.4f␣|␣", m.m_r, LR);
    fprintf(fp, "%6.4f␣%␣6.4f␣|␣", m.m_t, LT);
    fprintf(fp, "%6.3f␣", mu_a);
    fprintf(fp, "%6.3f␣", mu_sp);
    fprintf(fp, "%6.3f␣|", r.g);
    fprintf(fp, "␣%6.4f␣%6.4f␣", m.ur1_lost, m.uru_lost);
    fprintf(fp, "%6.4f␣%6.4f␣|␣", m.ut1_lost, m.utu_lost);
    fprintf(fp, "%2d␣␣", r.MC_iterations);
    fprintf(fp, "%3d", r.AD_iterations);
    fprintf(fp, "␣␣␣␣%c␣\n", what_char(r.error));
  }
  else {
    if (m.lambda ≠ 0) fprintf(fp, "%6.1f\t", m.lambda);
    else fprintf(fp, "%6d\t", line);
    if (mu_a ≥ 200) mu_a = 199.9999;
    if (mu_sp ≥ 1000) mu_sp = 999.9999;
    fprintf(fp, "%␣9.4f\t%␣9.4f\t", m.m_r, LR);
    fprintf(fp, "%␣9.4f\t%␣9.4f\t", m.m_t, LT);
    fprintf(fp, "%␣9.4f\t", mu_a);
    fprintf(fp, "%␣9.4f\t", mu_sp);
    fprintf(fp, "%␣9.4f\t", r.g);
    fprintf(fp, "␣%c␣\n", what_char(r.error));
  }
  fflush(fp);
}
```

This code is used in section 2.

26. ⟨ print error legend function 26 ⟩ ≡

```
static void print_error_legend(void)
{
  if (Debug(DEBUG_ANY)) return;
  fprintf(stderr, "-----------------␣Sorry,␣but␣...␣errors␣encountered␣---------------\n");
  fprintf(stderr, "␣␣␣*␣␣==>␣Success␣␣␣␣␣␣␣␣␣␣");
  fprintf(stderr, "␣␣0-9␣==>␣Monte␣Carlo␣Iteration\n");
  fprintf(stderr, "␣␣␣R␣␣==>␣M_R␣is␣too␣big␣␣␣");
  fprintf(stderr, "␣␣␣r␣␣==>␣M_R␣is␣too␣small\n");
  fprintf(stderr, "␣␣␣T␣␣==>␣M_T␣is␣too␣big␣␣␣");
  fprintf(stderr, "␣␣␣t␣␣==>␣M_T␣is␣too␣small\n");
  fprintf(stderr, "␣␣␣U␣␣==>␣M_U␣is␣too␣big␣␣␣");
  fprintf(stderr, "␣␣␣u␣␣==>␣M_U␣is␣too␣small\n");
  fprintf(stderr, "␣␣␣!␣␣==>␣M_R␣+␣M_T␣>␣1␣␣␣␣");
  fprintf(stderr, "␣␣␣+␣␣==>␣Did␣not␣converge\n\n");
}
```

This code is used in section 2.

27. returns a new string consisting of s+t

⟨ stringdup together function 27 ⟩ ≡

```
static char *strdup_together(char *s, char *t)
{
  char *both;
  if (s ≡ Λ) {
    if (t ≡ Λ) return Λ;
    return strdup(t);
  }
  if (t ≡ Λ) return strdup(s);
  both = malloc(strlen(s) + strlen(t) + 1);
  if (both ≡ Λ) fprintf(stderr, "Could␣not␣allocate␣memory␣for␣both␣strings.\n");
  strcpy(both, s);
  strcat(both, t);
  return both;
}
```

This code is used in section 2.

28. catch parsing errors in strtod

```
⟨ mystrtod function 28 ⟩ ≡
  static double my_strtod(const char *str)
  {
    char *endptr;
    errno = 0;
    double val = strtod(str, &endptr);
    if (endptr ≡ str) {      /* No digits were found */
      fprintf(stderr, "Error␣in␣command-line\n");
      fprintf(stderr, "␣␣␣␣No␣conversion␣could␣be␣performed␣for␣‘%s‘.\n", str);
      exit(EXIT_FAILURE);
    }
    if (*endptr ≠ '\0') {      /* String contains extra characters after the number */
      fprintf(stderr, "Error␣in␣command-line\n");
      fprintf(stderr, "␣␣␣␣Partial␣conversion␣of␣string␣=␣'%s'\n", str);
      exit(EXIT_FAILURE);
    }
    if (errno ≡ ERANGE) {
      /* The converted value is out of range of representable values by a double */
      fprintf(stderr, "Error␣in␣command-line\n");
      printf("␣␣␣␣The␣value␣'%s'␣is␣out␣of␣range␣of␣double.\n", str);
      exit(EXIT_FAILURE);
    }
    return val;
  }
```

This code is used in section 2.

29. assume that start time has already been set

```
⟨ seconds elapsed function 29 ⟩ ≡
  static double seconds_elapsed(clock_t start_time)
  {
    clock_t finish_time = clock( );
    return (double)(finish_time − start_time)/CLOCKS_PER_SEC;
  }
```

This code is used in section 2.

30. given a string and an array, this fills the array with numbers from the string. The numbers should be separated by spaces.

Returns 0 upon successfully filling n entries, returns 1 for any error.

```
⟨ parse string into array function 30 ⟩ ≡
  static int parse_string_into_array(char *s, double *a, int n)
  {
    char *t, *last, *r;
    int i = 0;
    t = s;
    last = s + strlen(s);
    while (t < last) {      /* a space should mark the end of number */
      r = t;
      while (*r ≠ ' ' ∧ *r ≠ '\0') r++;
      *r = '\0';      /* parse the number and save it */
      if (sscanf(t, "%lf", &(a[i])) ≡ 0) return 1;
      i++;      /* are we done ? */
      if (i ≡ n) {
        if (a[i − 1] ≤ 0 ∨ a[i − 1] > 1) {
          fprintf(stderr,
              "Sphere wall reflectivity (r_w=%g) must be a fraction less than one.\n",
              a[i − 1]);
          exit(EXIT_FAILURE);
        }
        return 0;
      }      /* move pointer just after last number */
      t = r + 1;
    }
    return 1;
  }
```

This code is used in section 2.

31.

```
⟨ what_char function 31 ⟩ ≡
  static char what_char(int err)
  {
    if (err ≡ IAD_NO_ERROR) return '*';
    if (err ≡ IAD_TOO_MANY_ITERATIONS) return '+';
    if (err ≡ IAD_MR_TOO_BIG) return 'R';
    if (err ≡ IAD_MR_TOO_SMALL) return 'r';
    if (err ≡ IAD_MT_TOO_BIG) return 'T';
    if (err ≡ IAD_MT_TOO_SMALL) return 't';
    if (err ≡ IAD_MU_TOO_BIG) return 'U';
    if (err ≡ IAD_MU_TOO_SMALL) return 'u';
    if (err ≡ IAD_TOO_MUCH_LIGHT) return '!';
    return '?';
  }
```

This code is used in section 2.

32. ⟨ print long error function 32 ⟩ ≡

```
static void print_long_error(int err)
{
  if (err ≡ IAD_TOO_MANY_ITERATIONS) fprintf(stderr, "Failed␣Search,␣too␣many␣iterations\n");
  if (err ≡ IAD_MR_TOO_BIG) fprintf(stderr, "Failed␣Search,␣M_R␣is␣too␣big\n");
  if (err ≡ IAD_MR_TOO_SMALL) fprintf(stderr, "Failed␣Search,␣M_R␣is␣too␣small\n");
  if (err ≡ IAD_MT_TOO_BIG) fprintf(stderr, "Failed␣Search,␣M_T␣is␣too␣big\n");
  if (err ≡ IAD_MT_TOO_SMALL) fprintf(stderr, "Failed␣Search,␣M_T␣is␣too␣small\n");
  if (err ≡ IAD_MU_TOO_BIG) fprintf(stderr, "Failed␣Search,␣M_U␣is␣too␣big\n");
  if (err ≡ IAD_MU_TOO_SMALL) fprintf(stderr, "Failed␣Search,␣M_U␣is␣too␣snall\n");
  if (err ≡ IAD_TOO_MUCH_LIGHT) fprintf(stderr, "Failed␣Search,␣Total␣light␣bigger␣than␣1\n");
  fprintf(stderr, "\n");
}
```

This code is used in section 2.

33. The idea here is to show some intermediate output while a file is being processed.

⟨ print dot function 33 ⟩ ≡

```
static void print_dot(clock_t start_time, int err, int points, int final, int verbosity)
{
  static int counter = 0;
  counter++;
  if (verbosity ≡ 0 ∨ Debug(DEBUG_ANY)) return;
  if (final) fprintf(stderr, "%c", what_char(err));
  else {
    counter--;
    fprintf(stderr, "%1d\b", points % 10);
  }
  if (final) {
    if (counter % 50 ≡ 0) {
      double rate = (seconds_elapsed(start_time)/counter);
      fprintf(stderr, "␣␣%3d␣done␣(%5.2f␣s/pt)\n", counter, rate);
    }
    else if (counter % 10 ≡ 0) fprintf(stderr, "␣");
  }
  fflush(stderr);
}
```

This code is used in section 2.

34. Simple command-line shell program.

Here is a quick skeleton that I put together to show how the inverse adding-doubling code works. I have only cursorily tested this. If you find obvious bugs, they are probably real but should not extend beyond this code snippet.

All the output for this web file goes into `iad_main.c`

```
⟨ iad_main_mus.c 34 ⟩ ≡
  ⟨ Include files for main 3 ⟩
  int main(int argc, char **argv)
  {
    ⟨ Declare variables for main 4 ⟩
    if (Read_Header(&m, &r) ≡ TRUE) {
      ⟨ Process the header 37 ⟩
      m.num_measures = 2;
      m.m_r = 0.0;
      m.slab_thickness = 0.1;
      while (fp ≠ EOF) {
        fp = scanf("%lf␣%lf␣%lf␣%lf", &lambda, &r.mu_a, &m.default_g, &m.m_t);
        fp = readln(&line);
        ⟨ Calculate and write optical properties 12 ⟩
      }
    }
    exit(EXIT_SUCCESS);
  }
```

35. ⟨ Include files for *main* 3 ⟩ +≡

```
#include <stdio.h>
#include <string.h>
#include <stdlib.h>
#include "ad_globl.h"
#include "iad_type.h"
#include "iad_pub.h"
#include "iad_io.h"
```

36. ⟨ Declare variables for *main* 4 ⟩ +≡

```
  struct measure_type m;
  struct invert_type r;
  int lines;
  char *format1 = "␣␣␣␣R␣␣␣␣\t␣␣␣␣T␣␣␣␣\t␣␣␣␣Tc␣␣␣␣\t␣␣␣␣␣a␣␣␣␣\t␣␣␣␣␣b␣␣␣␣\t␣\
      ␣␣␣␣g␣␣␣␣\t␣␣␣␣!/?\n";
  char *format2 = "␣%9.5f\t␣%9.5f\t␣%9.5f\t␣%9.5f\t␣%9.5f\t␣%9.5f\t␣%9c\n";
  char found = '?';
  int fp;
  double lambda;
  int line = 1;
```

37. ⟨ Process the header 37 ⟩ ≡

```
  m.slab_thickness = 1;
  Initialize_Result(m, &r);
  Write_Header(m, r);
  lines = 1;
  printf(format1, m.m_r, m.m_t, m.m_u, r.a, r.b, r.g);
```

This code is used in section 34.

38. ⟨ Calculate and write optical properties 12 ⟩ +≡

```
{
  r.search = FIND_mus;
  Inverse_RT(m, &r);
  if (r.found ≡ TRUE) found = '!';
  else found = '?';
  printf(format2, m.m_r, m.m_t, m.m_u, r.a, r.b, r.g, found);
  fflush(stdout);
}
```

39. IAD Types. This file has no routines. It is responsible for creating the header file `iad_type.h` and nothing else.

⟨ `iad_type.h` 39 ⟩ ≡
```
#undef FALSE
#undef TRUE
  ⟨ Preprocessor definitions ⟩
  ⟨ Structs to export from IAD Types 42 ⟩
```

40.
```
#define FIND_A 0
#define FIND_B 1
#define FIND_AB 2
#define FIND_AG 3
#define FIND_AUTO 4
#define FIND_BG 5
#define FIND_BaG 6
#define FIND_BsG 7
#define FIND_Ba 8
#define FIND_Bs 9
#define FIND_G 10
#define FIND_B_WITH_NO_ABSORPTION 11
#define FIND_B_WITH_NO_SCATTERING 12
#define RELATIVE 0
#define ABSOLUTE 1
#define COLLIMATED 0
#define DIFFUSE 1
#define FALSE 0
#define TRUE 1
#define IAD_MAX_ITERATIONS 500
```

41. Need error codes for this silly program

```
#define IAD_NO_ERROR 0
#define IAD_TOO_MANY_ITERATIONS 1
#define IAD_AS_NOT_VALID 16
#define IAD_AE_NOT_VALID 17
#define IAD_AD_NOT_VALID 18
#define IAD_RW_NOT_VALID 19
#define IAD_RD_NOT_VALID 20
#define IAD_RSTD_NOT_VALID 21
#define IAD_GAMMA_NOT_VALID 22
#define IAD_F_NOT_VALID 23
#define IAD_BAD_PHASE_FUNCTION 24
#define IAD_QUAD_PTS_NOT_VALID 25
#define IAD_BAD_G_VALUE 26
#define IAD_TOO_MANY_LAYERS 27
#define IAD_MEMORY_ERROR 28
#define IAD_FILE_ERROR 29
#define IAD_EXCESSIVE_LIGHT_LOSS 30
#define IAD_RT_LT_MINIMUM 31
#define IAD_MR_TOO_SMALL 32
#define IAD_MR_TOO_BIG 33
#define IAD_MT_TOO_SMALL 34
#define IAD_MT_TOO_BIG 35
#define IAD_MU_TOO_SMALL 36
#define IAD_MU_TOO_BIG 37
#define IAD_TOO_MUCH_LIGHT 38
#define IAD_TSTD_NOT_VALID 39
#define UNINITIALIZED -99
#define DEBUG_A_LITTLE 1
#define DEBUG_GRID 2
#define DEBUG_ITERATIONS 4
#define DEBUG_LOST_LIGHT 8
#define DEBUG_BEST_GUESS 16
#define DEBUG_SEARCH 32
#define DEBUG_GRID_CALC 64
#define DEBUG_SPHERE_GAIN 128
#define DEBUG_EVERY_CALC 256
#define DEBUG_ANY #FFFFFFFF
#define UNKNOWN 0
#define COMPARISON 1
#define SUBSTITUTION 2
```

42. The idea of the structure **measure_type** is collect all the information regarding a single measurement together in one spot. No information regarding how the inversion procedure is supposed to be done is contained in this structure, unlike in previous incarnations of this program.

⟨ Structs to export from IAD Types 42 ⟩ ≡

```
typedef struct measure_type {
  double slab_index;
  double slab_thickness;
  double slab_top_slide_index;
  double slab_top_slide_b;
  double slab_top_slide_thickness;
  double slab_bottom_slide_index;
  double slab_bottom_slide_b;
  double slab_bottom_slide_thickness;
  double slab_cos_angle;
  int num_spheres;
  int num_measures;
  int method;
  int flip_sample;
  int baffle_r, baffle_t;
  double d_beam;
  double fraction_of_rc_in_mr;
  double fraction_of_tc_in_mt;
  double m_r, m_t, m_u;
  double lambda;
  double as_r, ad_r, ae_r, aw_r, rd_r, rw_r, rstd_r, f_r;
  double as_t, ad_t, ae_t, aw_t, rd_t, rw_t, rstd_t;
  double ur1_lost, uru_lost, ut1_lost, utu_lost;
  double d_sphere_r, d_sphere_t;
} IAD_measure_type;
```

See also sections 43 and 44.

This code is used in section 39.

43. This describes how the inversion process should proceed and also contains the results of that inversion process.

```
⟨ Structs to export from IAD Types 42 ⟩ +≡
  typedef struct invert_type {
    double a;      /* the calculated albedo */
    double b;      /* the calculated optical depth */
    double g;      /* the calculated anisotropy */
    int found;
    int search;
    int metric;
    double tolerance;
    double MC_tolerance;
    double final_distance;
    int error;
    struct AD_slab_type slab;
    struct AD_method_type method;
    int AD_iterations;
    int MC_iterations;
    double default_a;
    double default_b;
    double default_g;
    double default_ba;
    double default_bs;
    double default_mua;
    double default_mus;
  } IAD_invert_type;
```

44. A few types that used to be enum's are now int's.

```
⟨ Structs to export from IAD Types 42 ⟩ +≡
  typedef int search_type;
  typedef int boolean_type;
  typedef int illumination_type;
  typedef struct guess_t {
    double distance;
    double a;
    double b;
    double g;
  } guess_type;
  extern double FRACTION;
```

45. IAD Public.

This contains the routine *Inverse_RT* that should generally be the basic entry point into this whole mess. Call this routine with the proper values and true happiness is bound to be yours.

Altered accuracy of the standard method of root finding from 0.001 to 0.00001. Note, it really doesn't help to change the method from `ABSOLUTE` to `RELATIVE`, but I did anyway. (3/3/95)

⟨ `iad_pub.c` 45 ⟩ ≡

```
#include <stdio.h>
#include <math.h>
#include "nr_util.h"
#include "ad_globl.h"
#include "ad_frsnl.h"
#include "iad_type.h"
#include "iad_util.h"
#include "iad_calc.h"
#include "iad_find.h"
#include "iad_pub.h"
#include "iad_io.h"
#include "stdlib.h"
#include "mc_lost.h"
```

⟨ Definition for *Inverse_RT* 49 ⟩
⟨ Definition for *measure_OK* 55 ⟩
⟨ Definition for *determine_search* 62 ⟩
⟨ Definition for *Initialize_Result* 66 ⟩
⟨ Definition for *Initialize_Measure* 74 ⟩
⟨ Definition for *ez_Inverse_RT* 72 ⟩
⟨ Definition for *Spheres_Inverse_RT* 76 ⟩
⟨ Definition for *Spheres_Inverse_RT2* 89 ⟩
⟨ Definition for *Calculate_MR_MT* 83 ⟩
⟨ Definition for *MinMax_MR_MT* 87 ⟩
⟨ Definition for *Calculate_Minimum_MR* 85 ⟩

46. All the information that needs to be written to the header file `iad_pub.h`. This eliminates the need to maintain a set of header files as well.

⟨ `iad_pub.h` 46 ⟩ ≡

⟨ Prototype for *Inverse_RT* 48 ⟩;
⟨ Prototype for *measure_OK* 54 ⟩;
⟨ Prototype for *determine_search* 61 ⟩;
⟨ Prototype for *Initialize_Result* 65 ⟩;
⟨ Prototype for *ez_Inverse_RT* 71 ⟩;
⟨ Prototype for *Initialize_Measure* 73 ⟩;
⟨ Prototype for *Calculate_MR_MT* 82 ⟩;
⟨ Prototype for *MinMax_MR_MT* 86 ⟩;
⟨ Prototype for *Calculate_Minimum_MR* 84 ⟩;
⟨ Prototype for *Spheres_Inverse_RT2* 88 ⟩;

47. Here is the header file needed to access one interesting routine in the `libiad.so` library.

⟨ `lib_iad.h` 47 ⟩ ≡

⟨ Prototype for *ez_Inverse_RT* 71 ⟩;
⟨ Prototype for *Spheres_Inverse_RT* 75 ⟩;
⟨ Prototype for *Spheres_Inverse_RT2* 88 ⟩;

48. Inverse RT. *Inverse_RT* is the main function in this whole package. You pass the variable m containing your experimentally measured values to the function *Inverse_RT*. It hopefully returns the optical properties in r that are appropriate for your experiment.

```
⟨ Prototype for Inverse_RT 48 ⟩ ≡
  void Inverse_RT(struct measure_type m, struct invert_type *r)
```

This code is used in sections 46 and 49.

49.
```
⟨ Definition for Inverse_RT 49 ⟩ ≡
  ⟨ Prototype for Inverse_RT 48 ⟩
  {
    r→found = FALSE;
    if (r→search ≡ FIND_AUTO) r→search = determine_search(m, *r);
    if (r→search ≡ FIND_B_WITH_NO_ABSORPTION) {
      r→default_a = 1;
      r→search = FIND_B;
    }
    if (r→search ≡ FIND_B_WITH_NO_SCATTERING) {
      r→default_a = 0;
      r→search = FIND_B;
    }
    ⟨ Exit with bad input data 50 ⟩
    ⟨ Find the optical properties 51 ⟩
    ⟨ Print basic sphere and MC effects 52 ⟩
    if (r→final_distance ≤ r→tolerance) r→found = TRUE;
  }
```

This code is used in section 45.

50. There is no sense going to all the trouble to try a multivariable minimization if the input data is bogus. So I wrote a single routine *measure_OK* to do just this.

```
⟨ Exit with bad input data 50 ⟩ ≡
  r→error = measure_OK(m, *r);
  if (r→method.quad_pts < 4) r→error = IAD_QUAD_PTS_NOT_VALID;
  if (r→error ≠ IAD_NO_ERROR) return;
```

This code is used in section 49.

51. Now I fob the real work off to the unconstrained minimization routines. Ultimately, I would like to replace all these by constrained minimization routines. Actually the first five already are constrained. The real work will be improving the last five because these are 2-D minimization routines.

```
⟨ Find the optical properties 51 ⟩ ≡
  if (Debug(DEBUG_ITERATIONS)) {
    fprintf(stderr, "----------␣Beginning␣New␣Search␣----------\n");
    fprintf(stderr, "␣␣␣␣␣␣␣␣␣␣");
    fprintf(stderr, "␣␣␣␣␣␣a␣␣␣␣␣␣␣␣␣␣b␣␣␣␣␣␣␣␣␣␣␣g␣␣␣|");
    fprintf(stderr, "␣␣␣␣␣M_R␣␣␣␣␣␣␣␣␣calc␣␣␣|");
    fprintf(stderr, "␣␣␣␣␣M_T␣␣␣␣␣␣␣␣␣calc␣␣␣|");
    if (r→metric ≡ RELATIVE) fprintf(stderr, "␣relative␣distance\n");
    else fprintf(stderr, "␣absolute␣distance\n");
  }
  switch (r→search) {
  case FIND_A: U_Find_A(m, r);
    break;
  case FIND_B: U_Find_B(m, r);
    break;
  case FIND_G: U_Find_G(m, r);
    break;
  case FIND_Ba: U_Find_Ba(m, r);
    break;
  case FIND_Bs: U_Find_Bs(m, r);
    break;
  case FIND_AB: U_Find_AB(m, r);
    break;
  case FIND_AG: U_Find_AG(m, r);
    break;
  case FIND_BG: U_Find_BG(m, r);
    break;
  case FIND_BsG: U_Find_BsG(m, r);
    break;
  case FIND_BaG: U_Find_BaG(m, r);
    break;
  }
  if (Debug(DEBUG_ITERATIONS))
    fprintf(stderr, "Final␣amoeba␣result␣after␣AD_iterations␣=␣%d\n", r→AD_iterations);
  if (r→AD_iterations ≥ IAD_MAX_ITERATIONS) r→error = IAD_TOO_MANY_ITERATIONS;
```

This code is used in section 49.

52. This is to support -x 1

```
⟨ Print basic sphere and MC effects 52 ⟩ ≡
  if (Debug(DEBUG_A_LITTLE)) {
    double M_R, M_T;
    fprintf(stderr, "AD␣iterations=␣%3d␣␣␣MC␣iterations=%3d", r→AD_iterations, r→MC_iterations);
    fprintf(stderr, "␣␣␣␣␣␣␣␣␣␣␣␣␣␣a=%6.4f␣b=%8.4f␣g=%6.4f\n", r→slab.a, r→slab.b, r→slab.g);
    fprintf(stderr, "␣␣␣␣␣M_R␣loss␣␣␣␣␣%8.5f␣␣␣M_T␣loss␣␣␣␣␣%8.5f", m.ur1_lost, m.ut1_lost);
    if (r→MC_iterations ≡ 0) fprintf(stderr, "␣(␣no␣MC␣calculation␣yet)\n");
    else fprintf(stderr, "␣(␣MC␣loss␣calculation)\n");
    Calculate_MR_MT(m, *r, FALSE, FALSE, &M_R, &M_T);
    fprintf(stderr, "␣␣␣␣␣M_R␣bare␣␣␣␣␣%8.5f␣␣␣M_T␣bare␣␣␣␣␣%8.5f", M_R, M_T);
    fprintf(stderr, "␣(␣---␣MC␣loss,␣---␣sphere␣effects)\n");
    Calculate_MR_MT(m, *r, FALSE, TRUE, &M_R, &M_T);
    fprintf(stderr, "␣␣␣␣␣M_R␣sphere␣␣␣%8.5f␣␣␣M_T␣sphere␣␣␣%8.5f", M_R, M_T);
    fprintf(stderr, "␣(␣---␣MC␣loss,␣+++␣sphere␣effects)\n");
    Calculate_MR_MT(m, *r, TRUE, FALSE, &M_R, &M_T);
    fprintf(stderr, "␣␣␣␣␣M_R␣mc␣␣␣␣␣␣␣%8.5f␣␣␣M_T␣mc␣␣␣␣␣␣␣%8.5f", M_R, M_T);
    fprintf(stderr, "␣(␣+++␣MC␣loss,␣---␣sphere␣effects)\n");
    Calculate_MR_MT(m, *r, TRUE, TRUE, &M_R, &M_T);
    fprintf(stderr, "␣␣␣␣␣M_R␣both␣␣␣␣␣%8.5f␣␣␣M_T␣both␣␣␣␣␣%8.5f", M_R, M_T);
    fprintf(stderr, "␣(␣+++␣MC␣loss,␣+++␣sphere␣effects)\n");
    fprintf(stderr, "␣␣␣␣␣M_R␣measured␣%8.5f␣␣␣M_T␣measured␣%8.5f", m.m_r, m.m_t);
    fprintf(stderr, "␣(␣␣target␣values)\n");
    fprintf(stderr, "Final␣distance␣%8.5f\n\n", r→final_distance);
  }
```

This code is used in section 49.

53. Validation.

54. Now the question is — just what is bad data? Here's the prototype.

```
⟨ Prototype for measure_OK 54 ⟩ ≡
  int measure_OK(struct measure_type m, struct invert_type r)
```

This code is used in sections 46 and 55.

55. It would just be nice to stop computing with bad data. This does not work in practice because it turns out that there is often bogus data in a full wavelength scan. Often the reflectance is too low for short wavelengths and at long wavelengths the detector (photomultiplier tube) does not work worth a damn.

The two sphere checks are more complicated. For example, we can no longer categorically state that the transmittance is less than one or that the sum of the reflectance and transmittance is less than one. Instead we use the transmittance to bound the values for the reflectance — see the routine *MinMax_MR_MT* below.

```
⟨ Definition for measure_OK 55 ⟩ ≡
  ⟨ Prototype for measure_OK 54 ⟩
  {
    double ru, tu;
    if (m.num_spheres ≠ 2) {
      ⟨ Check MT for zero or one spheres 57 ⟩
      ⟨ Check MR for zero or one spheres 56 ⟩
    }
    else {
      int error = MinMax_MR_MT(m, r);
      if (error ≠ IAD_NO_ERROR) return error;
    }
    ⟨ Check MU 58 ⟩
    if (m.num_spheres ≠ 0) {
      ⟨ Check sphere parameters 59 ⟩
    }
    return IAD_NO_ERROR;
  }
```

This code is used in section 45.

56. The reflectance is constrained by the index of refraction of the material and the transmission. The upper bound for the reflectance is just one minus the transmittance. The specular (unscattered) reflectance from the boundaries imposes minimum for the reflectance. Obviously, the reflected light cannot be less than that from the first boundary. This might be calculated by assuming an infinite layer thickness. But we can do better.

There is a definite bound on the minimum reflectance from a sample. If you have a sample with a given transmittance m_t, the minimum reflectance possible is found by assuming that the sample does not scatter any light.

Knowledge of the indicies of refraction makes it a relatively simple matter to determine the optical thickness $b = mu\_a * d$ of the slab. The minimum reflection is obtained by including all the specular reflectances from all the surfaces.

If the default albedo has been specified as zero, then there is really no need to check `MR` because it is ignored.

⟨ Check `MR` for zero or one spheres 56 ⟩ ≡

```
{
  double mr, mt;
  Calculate_Minimum_MR(m, r, &mr, &mt);
  if (m.m_r < 0) return IAD_MR_TOO_SMALL;
  if (m.m_r > 1) return IAD_MR_TOO_BIG;
      /* one parameter search only needs one good measurement */
  if (r.search ≡ FIND_A ∨ r.search ≡ FIND_G ∨ r.search ≡ FIND_B ∨ r.search ≡ FIND_Bs ∨ r.search ≡
        FIND_Ba) {
    if (m.m_r < mr ∧ m.m_t ≤ 0) return IAD_MR_TOO_SMALL;
  }
  else {
    if (r.default_a ≡ UNINITIALIZED ∨ r.default_a > 0) {
      if (m.m_r < mr) return IAD_MR_TOO_SMALL;
    }
  }
}
```

This code is used in section 55.

57. The transmittance is also constrained by the index of refraction of the material. The minimum transmittance is zero, but the maximum transmittance cannot exceed the total light passing through the sample when there is no scattering or absorption. This is calculated by assuming an infinitely thin (to eliminate any scattering or absorption effects).

There is a problem when spheres are present. The estimated values for the transmittance using *Sp_mu_RT* are not actually limiting cases. This will require a bit of fixing, but for now that test is omitted if the number of spheres is more than zero.

⟨ Check `MT` for zero or one spheres 57 ⟩ ≡

```
if (m.m_t < 0) return IAD_MT_TOO_SMALL;
if (m.m_t > 1) return IAD_MR_TOO_BIG;
Sp_mu_RT_Flip(m.flip_sample, r.slab.n_top_slide, r.slab.n_slab, r.slab.n_bottom_slide, r.slab.b_top_slide, 0,
    r.slab.b_bottom_slide, r.slab.cos_angle, &ru, &tu);
if (m.num_spheres ≡ 0 ∧ m.m_t > tu) {
  fprintf(stderr, "ntop=%7.5f, nslab=%7.5f, nbottom=%7.5f\n", r.slab.n_top_slide, r.slab.n_slab,
      r.slab.n_bottom_slide);
  fprintf(stderr, "tu_max=%7.5f, m_t=%7.5f, t_std=%7.5f\n", tu, m.m_t, m.rstd_t);
  return IAD_MT_TOO_BIG;
}
```

This code is used in section 55.

58. The unscattered transmission is now always included in the total transmittance. Therefore the unscattered transmittance must fall betwee zero and `M_T`

⟨ Check MU 58 ⟩ ≡

```
if (m.m_u < 0) return IAD_MU_TOO_SMALL;
if (m.m_t > 0 ∧ m.m_u > m.m_t) return IAD_MU_TOO_BIG;
```

This code is used in section 55.

59. Make sure that reflection sphere parameters are reasonable

⟨ Check sphere parameters 59 ⟩ ≡

```
if (m.as_r < 0 ∨ m.as_r ≥ 0.2) return IAD_AS_NOT_VALID;
if (m.ad_r < 0 ∨ m.ad_r ≥ 0.2) return IAD_AD_NOT_VALID;
if (m.ae_r < 0 ∨ m.ae_r ≥ 0.2) return IAD_AE_NOT_VALID;
if (m.rw_r < 0 ∨ m.rw_r > 1.0) return IAD_RW_NOT_VALID;
if (m.rd_r < 0 ∨ m.rd_r > 1.0) return IAD_RD_NOT_VALID;
if (m.rstd_r < 0 ∨ m.rstd_r > 1.0) return IAD_RSTD_NOT_VALID;
if (m.rstd_t < 0 ∨ m.rstd_t > 1.0) return IAD_TSTD_NOT_VALID;
if (m.f_r < 0 ∨ m.f_r > 1) return IAD_F_NOT_VALID;
```

See also section 60.

This code is used in section 55.

60. Make sure that transmission sphere parameters are reasonable

⟨ Check sphere parameters 59 ⟩ +≡

```
if (m.as_t < 0 ∨ m.as_t ≥ 0.2) return IAD_AS_NOT_VALID;
if (m.ad_t < 0 ∨ m.ad_t ≥ 0.2) return IAD_AD_NOT_VALID;
if (m.ae_t < 0 ∨ m.ae_t ≥ 0.2) return IAD_AE_NOT_VALID;
if (m.rw_t < 0 ∨ m.rw_r > 1.0) return IAD_RW_NOT_VALID;
if (m.rd_t < 0 ∨ m.rd_t > 1.0) return IAD_RD_NOT_VALID;
if (m.rstd_t < 0 ∨ m.rstd_t > 1.0) return IAD_TSTD_NOT_VALID;
```

61. Searching Method.

The original idea was that this routine would automatically determine what optical parameters could be figured out from the input data. This worked fine for a long while, but I discovered that often it was convenient to constrain the optical properties in various ways. Consequently, this routine got more and more complicated.

What should be done is to figure out whether the search will be 1D or 2D and split this routine into two parts.

It would be nice to enable the user to constrain two parameters, but the infrastructure is missing at this point.

⟨ Prototype for *determine_search* 61 ⟩ ≡

search_type *determine_search*(**struct measure_type** m, **struct invert_type** r)

This code is used in sections 46 and 62.

62. This routine is responsible for selecting the appropriate optical properties to determine.

```
⟨ Definition for determine_search 62 ⟩ ≡
  ⟨ Prototype for determine_search 61 ⟩
  {
    double rt, tt, rd, td, tc, rc;
    int search = 0;
    int independent = 0;
    int constraints = 0;
    if (m.m_r > 0) independent++;
    if (m.m_t > 0) independent++;
    if (m.m_u > 0) independent++;
    if (r.default_a ≠ UNINITIALIZED) constraints++;
    if (r.default_b ≠ UNINITIALIZED) constraints++;
    if (r.default_g ≠ UNINITIALIZED) constraints++;
    if (r.default_mua ≠ UNINITIALIZED) constraints++;
    if (r.default_mus ≠ UNINITIALIZED) constraints++;
    Estimate_RT(m, r, &rt, &tt, &rd, &rc, &td, &tc);
    if (Debug(DEBUG_SEARCH)) {
      fprintf(stderr, "SEARCH: starting with %d measurement(s)\n", independent);
      fprintf(stderr, "SEARCH:       and with %d constraint(s)\n", constraints);
      fprintf(stderr, "SEARCH: m_r = %8.5f ", m.m_r);
      fprintf(stderr, "m_t = %8.5f ", m.m_t);
      fprintf(stderr, "m_u = %8.5f\n", m.m_u);
      fprintf(stderr, "SEARCH:   rt = %8.5f ", rt);
      fprintf(stderr, " rd = %8.5f ", rd);
      fprintf(stderr, " ru = %8.5f\n", rc);
      fprintf(stderr, "SEARCH:   tt = %8.5f ", tt);
      fprintf(stderr, " td = %8.5f ", td);
      fprintf(stderr, " tu = %8.5f\n", tc);
    }
    if (m.m_u ≡ 0 ∧ independent ≡ 3) {
      if (Debug(DEBUG_SEARCH)) fprintf(stderr, "SEARCH: no information in tc\n");
      independent--;
    }
    if (rd ≡ 0 ∧ independent ≥ 2) {
      if (Debug(DEBUG_SEARCH)) fprintf(stderr, "SEARCH: no information in rd\n");
      independent--;
    }
    if (td ≡ 0 ∧ independent ≥ 2) {
      if (Debug(DEBUG_SEARCH)) fprintf(stderr, "SEARCH: no information in td\n");
      independent--;
    }
    if (independent ≡ −1) {
      fprintf(stderr, "Something is wrong, independent should not be -1\n");
    }
    if (constraints + independent > 3) {
      fprintf(stderr, "Too many constraints!\n");
    }
    if (independent ≡ 1 ∨ independent ≡ −1) {
      ⟨ One parameter search 63 ⟩
    }
    else if (independent ≡ 2) {
```

```
    ⟨ Two parameter search 64 ⟩
  }    /* three real parameters with information! */
  else {
    search = FIND_AG;
  }
  if (search ≡ FIND_BG ∧ m.m_u > 0) search = FIND_G;
  if (Debug(DEBUG_SEARCH)) {
    fprintf(stderr, "SEARCH: ending with %d measurement(s)\n", independent);
    fprintf(stderr, "SEARCH:     and with %d constraint(s)\n", constraints);
    fprintf(stderr, "SEARCH: final choice for search = ");
    if (search ≡ FIND_A) fprintf(stderr, "FIND_A\n");
    if (search ≡ FIND_B) fprintf(stderr, "FIND_B\n");
    if (search ≡ FIND_AB) fprintf(stderr, "FIND_AB\n");
    if (search ≡ FIND_AG) fprintf(stderr, "FIND_AG\n");
    if (search ≡ FIND_AUTO) fprintf(stderr, "FIND_AUTO\n");
    if (search ≡ FIND_BG) fprintf(stderr, "FIND_BG\n");
    if (search ≡ FIND_BaG) fprintf(stderr, "FIND_BaG\n");
    if (search ≡ FIND_BsG) fprintf(stderr, "FIND_BsG\n");
    if (search ≡ FIND_Ba) fprintf(stderr, "FIND_Ba\n");
    if (search ≡ FIND_Bs) fprintf(stderr, "FIND_Bs\n");
    if (search ≡ FIND_G) fprintf(stderr, "FIND_G\n");
    if (search ≡ FIND_B_WITH_NO_ABSORPTION) fprintf(stderr, "FIND_B_WITH_NO_ABSORPTION\n");
    if (search ≡ FIND_B_WITH_NO_SCATTERING) fprintf(stderr, "FIND_B_WITH_NO_SCATTERING\n");
  }
  return search;
}
```

This code is used in section 45.

63. The fastest inverse problems are those in which just one measurement is known. This corresponds to a simple one-dimensional minimization problem. The only complexity is deciding exactly what should be allowed to vary. The basic assumption is that the anisotropy has been specified or will be assumed to be zero.

If the anistropy is assumed known, then one other assumption will allow us to figure out the last parameter to solve for.

Ultimately, if no default values are given, then we look at the value of the total transmittance. If this is zero, then we assume that the optical thickness is infinite and solve for the albedo. Otherwise we will just make a stab at solving for the optical thickness assuming the albedo is one.

```
⟨ One parameter search 63 ⟩ ≡
  if (r.default_a ≠ UNINITIALIZED) {
    if (r.default_a ≡ 0) search = FIND_B_WITH_NO_SCATTERING;
    else if (r.default_a ≡ 1) search = FIND_B_WITH_NO_ABSORPTION;
    else if (tt ≡ 0) search = FIND_G;
    else search = FIND_B;
  }
  else if (r.default_b ≠ UNINITIALIZED) search = FIND_A;
  else if (r.default_bs ≠ UNINITIALIZED) search = FIND_Ba;
  else if (r.default_ba ≠ UNINITIALIZED) search = FIND_Bs;
  else if (m.m_t ≡ 0) search = FIND_A;
  else if (rd ≡ 0) search = FIND_B_WITH_NO_SCATTERING;
  else search = FIND_B_WITH_NO_ABSORPTION;
```

This code is used in section 62.

64. If the absorption depth $\mu_a d$ is constrained return *FIND_BsG*. Recall that I use the bizarre mnemonic $bs = \mu_s d$ here and so this means that the program will search over various values of $\mu_s d$ and g.

If there are just two measurements then I assume that the anisotropy is not of interest and the only thing to calculate is the reduced albedo and optical thickness based on an assumed anisotropy.

```
⟨ Two parameter search 64 ⟩ ≡
  if (r.default_a ≠ UNINITIALIZED) {
    if (r.default_a ≡ 0) search = FIND_B;
    else if (r.default_g ≠ UNINITIALIZED) search = FIND_B;
    else if (r.default_b ≠ UNINITIALIZED) search = FIND_G;
    else search = FIND_BG;
  }
  else if (r.default_b ≠ UNINITIALIZED) {
    if (r.default_g ≠ UNINITIALIZED) search = FIND_A;
    else search = FIND_AG;
  }
  else if (r.default_g ≠ UNINITIALIZED) {
    search = FIND_AB;
  }
  else if (r.default_ba ≠ UNINITIALIZED) {
    if (r.default_g ≠ UNINITIALIZED) search = FIND_Bs;
    else search = FIND_BsG;
  }
  else if (r.default_bs ≠ UNINITIALIZED) {
    if (r.default_g ≠ UNINITIALIZED) search = FIND_Ba;
    else search = FIND_BaG;
  }
  else if (rt + tt > 1 ∧ 0 ∧ m.num_spheres ≠ 2) search = FIND_B_WITH_NO_ABSORPTION;
  else search = FIND_AB;
```

This code is used in section 62.

65. This little routine just stuffs reasonable values into the structure we use to return the solution. This does not replace the values for *r.default_g* nor for *r.method.quad_pts*. Presumably these have been set correctly elsewhere.

```
⟨ Prototype for Initialize_Result 65 ⟩ ≡
  void Initialize_Result(struct measure_type m, struct invert_type *r, int overwrite_defaults)
```

This code is used in sections 46 and 66.

66.

```
⟨ Definition for Initialize_Result 66 ⟩ ≡
  ⟨ Prototype for Initialize_Result 65 ⟩
  {
    ⟨ Fill r with reasonable values 67 ⟩
  }
```

This code is used in section 45.

67. Start with the optical properties.

```
⟨ Fill r with reasonable values 67 ⟩ ≡
  r→a = 0.0;
  r→b = 0.0;
  r→g = 0.0;
```

See also sections 68, 69, and 70.

This code is used in section 66.

68. Continue with other useful stuff.

```
⟨ Fill r with reasonable values 67 ⟩ +≡
  r→found = FALSE;
  r→tolerance = 0.0001;
  r→MC_tolerance = 0.01;      /* percent */
  r→search = FIND_AUTO;
  r→metric = RELATIVE;
  r→final_distance = 10;
  r→AD_iterations = 0;
  r→MC_iterations = 0;
  r→error = IAD_NO_ERROR;
```

69. The defaults might be handy

```
⟨ Fill r with reasonable values 67 ⟩ +≡
  if (overwrite_defaults) {
    r→default_a = UNINITIALIZED;
    r→default_b = UNINITIALIZED;
    r→default_g = UNINITIALIZED;
    r→default_ba = UNINITIALIZED;
    r→default_bs = UNINITIALIZED;
    r→default_mua = UNINITIALIZED;
    r→default_mus = UNINITIALIZED;
  }
```

70. It is necessary to set up the slab correctly so, I stuff reasonable values into this record as well.

```
⟨ Fill r with reasonable values 67 ⟩ +≡
  r→slab.a = 0.5;
  r→slab.b = 1.0;
  r→slab.g = 0;
  r→slab.phase_function = HENYEY_GREENSTEIN;
  r→slab.n_slab = m.slab_index;
  r→slab.n_top_slide = m.slab_top_slide_index;
  r→slab.n_bottom_slide = m.slab_bottom_slide_index;
  r→slab.b_top_slide = m.slab_top_slide_b;
  r→slab.b_bottom_slide = m.slab_bottom_slide_b;
  r→slab.cos_angle = m.slab_cos_angle;
  r→method.a_calc = 0.5;
  r→method.b_calc = 1;
  r→method.g_calc = 0.5;
  r→method.quad_pts = 8;
  r→method.b_thinnest = 1.0/32.0;
```

71. EZ Inverse RT. *ez_Inverse_RT* is a simple interface to the main function *Inverse_RT* in this package. It eliminates the need for complicated data structures so that the command line interface (as well as those to Perl and Mathematica) will be simpler. This function assumes that the reflection and transmission include specular reflection and that the transmission also include unscattered transmission.

Other assumptions are that the top and bottom slides have the same index of refraction, that the illumination is collimated. Of course no sphere parameters are included.

```
⟨ Prototype for ez_Inverse_RT 71 ⟩ ≡
  void ez_Inverse_RT(double n, double nslide, double UR1, double UT1, double Tc, double *a, double
      *b, double *g, int *error)
```

This code is used in sections 46, 47, and 72.

72.

```
⟨ Definition for ez_Inverse_RT 72 ⟩ ≡
  ⟨ Prototype for ez_Inverse_RT 71 ⟩
  {
    struct measure_type m;
    struct invert_type r;
    *a = 0;
    *b = HUGE_VAL;
    *g = 0;
    Initialize_Measure(&m);
    m.slab_index = n;
    m.slab_top_slide_index = nslide;
    m.slab_bottom_slide_index = nslide;
    m.slab_cos_angle = 1.0;
    m.num_measures = 3;
    if (UT1 ≡ 0) m.num_measures--;
    if (Tc ≡ 0) m.num_measures--;
    m.m_r = UR1;
    m.m_t = UT1;
    m.m_u = Tc;
    Initialize_Result(m, &r, TRUE);
    r.method.quad_pts = 8;
    Inverse_RT(m, &r);
    *error = r.error;
    if (r.error ≡ IAD_NO_ERROR) {
      *a = r.a;
      *b = r.b;
      *g = r.g;
    }
  }
```

This code is used in section 45.

73.

```
⟨ Prototype for Initialize_Measure 73 ⟩ ≡
  void Initialize_Measure(struct measure_type *m)
```

This code is used in sections 46 and 74.

74. ⟨ Definition for *Initialize_Measure* 74 ⟩ ≡

```
⟨ Prototype for Initialize_Measure 73 ⟩
{
  double default_sphere_d = 8.0 * 25.4;
  double default_sample_d = 0.0 * 25.4;
  double default_detector_d = 0.1 * 25.4;
  double default_entrance_d = 0.5 * 25.4;
  double sphere_area = M_PI * default_sphere_d * default_sphere_d;
  m→slab_index = 1.0;
  m→slab_top_slide_index = 1.0;
  m→slab_top_slide_b = 0.0;
  m→slab_top_slide_thickness = 0.0;
  m→slab_bottom_slide_index = 1.0;
  m→slab_bottom_slide_b = 0.0;
  m→slab_bottom_slide_thickness = 0.0;
  m→slab_thickness = 1.0;
  m→slab_cos_angle = 1.0;
  m→num_spheres = 0;
  m→num_measures = 1;
  m→method = UNKNOWN;
  m→fraction_of_rc_in_mr = 1.0;
  m→fraction_of_tc_in_mt = 1.0;
  m→baffle_r = 1;
  m→baffle_t = 1;
  m→flip_sample = 0;
  m→m_r = 0.0;
  m→m_t = 0.0;
  m→m_u = 0.0;
  m→d_sphere_r = default_sphere_d;
  m→as_r = (M_PI * default_sample_d * default_sample_d/4.0)/sphere_area;
  m→ad_r = (M_PI * default_detector_d * default_detector_d/4.0)/sphere_area;
  m→ae_r = (M_PI * default_entrance_d * default_entrance_d/4.0)/sphere_area;
  m→aw_r = 1.0 − m→as_r − m→ad_r − m→ae_r;
  m→rd_r = 0.0;
  m→rw_r = 1.0;
  m→rstd_r = 1.0;
  m→f_r = 0.0;
  m→d_sphere_t = default_sphere_d;
  m→as_t = m→as_r;
  m→ad_t = m→ad_r;
  m→ae_t = 0;
  m→aw_t = 1.0 − m→as_t − m→ad_t − m→ae_t;
  m→rd_t = 0.0;
  m→rw_t = 1.0;
  m→rstd_t = 1.0;
  m→lambda = 0.0;
  m→d_beam = 0.0;
  m→ur1_lost = 0;
  m→uru_lost = 0;
  m→ut1_lost = 0;
  m→utu_lost = 0;
}
```

This code is used in section 45.

75. To avoid interfacing with C-structures it is necessary to pass the information as arrays. Here I have divided the experiment into (1) setup, (2) reflection sphere coefficients, (3) transmission sphere coefficients, (4) measurements, and (5) results.

```
⟨ Prototype for Spheres_Inverse_RT 75 ⟩ ≡
  void Spheres_Inverse_RT(double *setup, double *analysis, double *sphere_r, double *sphere_t, double
      *measurements, double *results)
```

This code is used in sections 47 and 76.

76.

```
⟨ Definition for Spheres_Inverse_RT 76 ⟩ ≡
  ⟨ Prototype for Spheres_Inverse_RT 75 ⟩
  {
    struct measure_type m;
    struct invert_type r;
    long num_photons;
    double ur1, ut1, uru, utu;
    int i, mc_runs = 1;
    Initialize_Measure(&m);
    ⟨ handle setup 77 ⟩
    ⟨ handle reflection sphere 80 ⟩
    ⟨ handle transmission sphere 81 ⟩
    ⟨ handle measurement 79 ⟩
    Initialize_Result(m, &r, TRUE);
    results[0] = 0;
    results[1] = 0;
    results[2] = 0;
    ⟨ handle analysis 78 ⟩
    Inverse_RT(m, &r);
    for (i = 0; i < mc_runs; i++) {
      MC_Lost(m, r, num_photons, &ur1, &ut1, &uru, &utu, &m.ur1_lost, &m.ut1_lost, &m.uru_lost,
          &m.utu_lost);
      Inverse_RT(m, &r);
    }
    if (r.error ≡ IAD_NO_ERROR) {
      results[0] = (1 − r.a) * r.b/m.slab_thickness;
      results[1] = (r.a) * r.b/m.slab_thickness;
      results[2] = r.g;
    }
    results[3] = r.error;
  }
```

This code is used in section 45.

77. These are in exactly the same order as the parameters in the .rxt header

```
⟨ handle setup 77 ⟩ ≡
  {
    double d_sample_r, d_entrance_r, d_detector_r;
    double d_sample_t, d_entrance_t, d_detector_t;
    m.slab_index = setup[0];
    m.slab_top_slide_index = setup[1];
    m.slab_thickness = setup[2];
    m.slab_top_slide_thickness = setup[3];
    m.d_beam = setup[4];
    m.rstd_r = setup[5];
    m.num_spheres = (int) setup[6];
    m.d_sphere_r = setup[7];
    d_sample_r = setup[8];
    d_entrance_r = setup[9];
    d_detector_r = setup[10];
    m.rw_r = setup[11];
    m.d_sphere_t = setup[12];
    d_sample_t = setup[13];
    d_entrance_t = setup[14];
    d_detector_t = setup[15];
    m.rw_t = setup[16];
    r.default_g = setup[17];
    num_photons = (long) setup[18];
    m.as_r = (d_sample_r/m.d_sphere_r/2.0) * (d_sample_r/m.d_sphere_r/2.0);
    m.ae_r = (d_entrance_r/m.d_sphere_r/2.0) * (d_entrance_r/m.d_sphere_r/2.0);
    m.ad_r = (d_detector_r/m.d_sphere_r/2.0) * (d_detector_r/m.d_sphere_r/2.0);
    m.aw_r = 1.0 - m.as_r - m.ae_r - m.ad_r;
    m.as_t = (d_sample_t/m.d_sphere_t/2.0) * (d_sample_t/m.d_sphere_t/2.0);
    m.ae_t = (d_entrance_t/m.d_sphere_t/2.0) * (d_entrance_t/m.d_sphere_t/2.0);
    m.ad_t = (d_detector_t/m.d_sphere_t/2.0) * (d_detector_t/m.d_sphere_t/2.0);
    m.aw_t = 1.0 - m.as_t - m.ae_t - m.ad_t;
    m.slab_bottom_slide_index = m.slab_top_slide_index;
    m.slab_bottom_slide_thickness = m.slab_top_slide_thickness;
    fprintf(stderr, "**** executing FIXME ****/n");
    m.slab_cos_angle = 1.0;      /* FIXME */
  }
```

This code is used in section 76.

78.

```
⟨ handle analysis 78 ⟩ ≡
  r.method.quad_pts = (int) analysis[0];
  mc_runs = (int) analysis[1];
```

This code is used in section 76.

79.

⟨ handle measurement 79 ⟩ ≡
```
m.m_r = measurements[0];
m.m_t = measurements[1];
m.m_u = measurements[2];
m.num_measures = 3;
if (m.m_t ≡ 0) m.num_measures −−;
if (m.m_u ≡ 0) m.num_measures −−;
```
This code is used in section 76.

80.

⟨ handle reflection sphere 80 ⟩ ≡
```
m.as_r = sphere_r[0];
m.ae_r = sphere_r[1];
m.ad_r = sphere_r[2];
m.rw_r = sphere_r[3];
m.rd_r = sphere_r[4];
m.rstd_r = sphere_r[5];
m.f_r = sphere_r[7];
```
This code is used in section 76.

81.

⟨ handle transmission sphere 81 ⟩ ≡
```
m.as_t = sphere_t[0];
m.ae_t = sphere_t[1];
m.ad_t = sphere_t[2];
m.rw_t = sphere_t[3];
m.rd_t = sphere_t[4];
m.rstd_t = sphere_t[5];
```
This code is used in section 76.

82. I needed a routine that would calculate the values of `M_R` and `M_T` without doing the whole inversion process. It seems odd that this does not exist yet.

The values for the lost light *m.uru_lost* etc., should be calculated before calling this routine.

⟨ Prototype for *Calculate_MR_MT* 82 ⟩ ≡
```
void Calculate_MR_MT(struct measure_type m, struct invert_type r, int include_MC, int
    include_spheres, double *M_R, double *M_T)
```
This code is used in sections 46 and 83.

83. ⟨ Definition for *Calculate_MR_MT* 83 ⟩ ≡

```
⟨ Prototype for Calculate_MR_MT 82 ⟩
{
  double distance;
  struct measure_type old_mm;
  struct invert_type old_rr;
  if (¬include_MC) {
    m.ur1_lost = 0;
    m.ut1_lost = 0;
    m.uru_lost = 0;
    m.utu_lost = 0;
  }
  if (¬include_spheres) {
    m.num_spheres = 0;
  }
  Get_Calc_State(&old_mm, &old_rr);
  Set_Calc_State(m, r);
  Calculate_Distance(M_R, M_T, &distance);
  Set_Calc_State(old_mm, old_rr);
}
```

This code is used in section 45.

84. So, it turns out that the minimum measured `M_R` can be less than four percent for black glass! This is because the sphere efficiency is much worse for the glass than for the white standard.

```
⟨ Prototype for Calculate_Minimum_MR 84 ⟩ ≡
  void Calculate_Minimum_MR(struct measure_type m, struct invert_type r, double *mr, double
      *mt)
```

This code is used in sections 46 and 85.

85. ⟨ Definition for *Calculate_Minimum_MR* 85 ⟩ ≡

```
⟨ Prototype for Calculate_Minimum_MR 84 ⟩
{
  if (m.m_u > 0) r.slab.b = What_Is_B(r.slab, m.m_u);
  else if (r.default_b ≠ UNINITIALIZED) r.slab.b = r.default_b;
  else r.slab.b = HUGE_VAL;
  r.slab.a = 0;
  if (r.default_g ≡ UNINITIALIZED) r.slab.g = 0.0;
  else r.slab.g = r.default_g;
  r.a = r.slab.a;
  r.b = r.slab.b;
  r.g = r.slab.g;
  Calculate_MR_MT(m, r, FALSE, TRUE, mr, mt);
}
```

This code is used in section 45.

86. The minimum possible value of MR for a given MT will be when the albedo is zero and the maximum value will be when the albedo is one. In the first case there will be no light loss and in the second we will assume that any light loss is neglible (to maximize MR).

The second case is perhaps over-simplified. Obviously for a fixed thickness as the albedo increases, the reflectance will increase. So how does *U_Find_B*( ) work when the albedo is set to 1?

The problem is that to calculate these values one must know the optical thickness. Fortunately with the recent addition of constrained minimization, we can do exactly this.

The only thing that remains is to sort out the light lost effect.

⟨ Prototype for *MinMax_MR_MT* 86 ⟩ ≡

```
int MinMax_MR_MT(struct measure_type m, struct invert_type r)
```

This code is used in sections 46 and 87.

87. ⟨ Definition for *MinMax_MR_MT* 87 ⟩ ≡

```
⟨ Prototype for MinMax_MR_MT 86 ⟩
{
  double distance, measured_m_r, min_possible_m_r, max_possible_m_r, temp_m_t;
  if (m.m_r < 0) return IAD_MR_TOO_SMALL;
  if (m.m_r * m.rstd_r > 1) return IAD_MR_TOO_BIG;
  if (m.m_t < 0) return IAD_MT_TOO_SMALL;
  if (m.m_t ≡ 0) return IAD_NO_ERROR;
  measured_m_r = m.m_r;
  m.m_r = 0;
  r.search = FIND_B;
  if (Debug(DEBUG_ITERATIONS))
    fprintf(stderr, "Determining␣minimum␣possible␣M_R␣for␣given␣M_T\n");
  r.default_a = 0;
  U_Find_B(m, &r);
  Calculate_Distance(&min_possible_m_r, &temp_m_t, &distance);
  if (measured_m_r < min_possible_m_r) return IAD_MR_TOO_SMALL;
  if (Debug(DEBUG_ITERATIONS))
    fprintf(stderr, "Determining␣maximum␣possible␣M_R␣for␣given␣M_T\n");
  r.default_a = 1.0;
  U_Find_B(m, &r);
  Calculate_Distance(&max_possible_m_r, &temp_m_t, &distance);
  if (measured_m_r > max_possible_m_r) return IAD_MR_TOO_BIG;
  return IAD_NO_ERROR;
}
```

This code is used in section 45.

88. ⟨ Prototype for *Spheres_Inverse_RT2* 88 ⟩ ≡

```
void Spheres_Inverse_RT2(double *sample, double *illumination, double *sphere_r, double
    *sphere_t, double *analysis, double *measurement, double *a, double *b, double *g)
```

This code is used in sections 46, 47, and 89.

89. ⟨ Definition for *Spheres_Inverse_RT2* 89 ⟩ ≡

```
⟨ Prototype for Spheres_Inverse_RT2 88 ⟩
{
  struct measure_type m;
  struct invert_type r;
  long num_photons;
  double ur1, ut1, uru, utu;
  int i, mc_runs = 1;
  Initialize_Measure(&m);
  ⟨ handle2 sample 90 ⟩
  ⟨ handle2 illumination 91 ⟩
  ⟨ handle2 reflection sphere 92 ⟩
  ⟨ handle2 transmission sphere 93 ⟩
  ⟨ handle2 analysis 94 ⟩
  ⟨ handle2 measurement 95 ⟩
  Initialize_Result(m, &r, TRUE);
  Inverse_RT(m, &r);
  for (i = 0; i < mc_runs; i++) {
    MC_Lost(m, r, num_photons, &ur1, &ut1, &uru, &utu, &m.ur1_lost, &m.ut1_lost, &m.uru_lost,
        &m.utu_lost);
    Inverse_RT(m, &r);
  }
  if (r.error ≡ IAD_NO_ERROR) {
    *a = r.a;
    *b = r.b;
    *g = r.g;
  }
}
```

This code is used in section 45.

90. Just move the values from the sample array into the right places

⟨ handle2 sample 90 ⟩ ≡

```
m.slab_index = sample[0];
m.slab_top_slide_index = sample[1];
m.slab_bottom_slide_index = sample[2];
m.slab_thickness = sample[3];
m.slab_top_slide_thickness = sample[4];
m.slab_bottom_slide_thickness = sample[5];
m.slab_top_slide_thickness = 0;
m.slab_bottom_slide_thickness = 0;
```

This code is used in section 89.

91. Just move the values from the illumination array into the right places. Need to spend time to figure out how to integrate items 2, 3, and 4

⟨ handle2 illumination 91 ⟩ ≡

```
m.d_beam = illumination[0];      /* m.lambda = illumination[1]; */
  /* m.specular-reflection-excluded = illumination[2]; */      /* m.direct-transmission-excluded =
    illumination[3]; */      /* m.diffuse-illumination = illumination[4]; */
m.num_spheres = illumination[5];
```

This code is used in section 89.

92.

⟨ handle2 reflection sphere 92 ⟩ ≡

```
{
  double d_sample_r, d_entrance_r, d_detector_r;
  m.d_sphere_r = sphere_r[0];
  d_sample_r = sphere_r[1];
  d_entrance_r = sphere_r[2];
  d_detector_r = sphere_r[3];
  m.rw_r = sphere_r[4];
  m.rd_r = sphere_r[5];
  m.as_r = (d_sample_r/m.d_sphere_r/2.0) * (d_sample_r/m.d_sphere_r/2.0);
  m.ae_r = (d_entrance_r/m.d_sphere_r/2.0) * (d_entrance_r/m.d_sphere_r/2.0);
  m.ad_r = (d_detector_r/m.d_sphere_r/2.0) * (d_detector_r/m.d_sphere_r/2.0);
  m.aw_r = 1.0 - m.as_r - m.ae_r - m.ad_r;
}
```

This code is used in section 89.

93.

⟨ handle2 transmission sphere 93 ⟩ ≡

```
{
  double d_sample_t, d_entrance_t, d_detector_t;
  m.d_sphere_t = sphere_t[0];
  d_sample_t = sphere_t[1];
  d_entrance_t = sphere_t[2];
  d_detector_t = sphere_t[3];
  m.rw_t = sphere_t[4];
  m.rd_t = sphere_t[5];
  m.as_t = (d_sample_t/m.d_sphere_t/2.0) * (d_sample_t/m.d_sphere_t/2.0);
  m.ae_t = (d_entrance_t/m.d_sphere_t/2.0) * (d_entrance_t/m.d_sphere_t/2.0);
  m.ad_t = (d_detector_t/m.d_sphere_t/2.0) * (d_detector_t/m.d_sphere_t/2.0);
  m.aw_t = 1.0 - m.as_t - m.ae_t - m.ad_t;
}
```

This code is used in section 89.

94.

⟨ handle2 analysis 94 ⟩ ≡

```
r.method.quad_pts = (int) analysis[0];
mc_runs = (int) analysis[1];
num_photons = (long) analysis[2];
```

This code is used in section 89.

95.

⟨ handle2 measurement 95 ⟩ ≡

```
m.rstd_r = measurement[0];
m.m_r = measurement[1];
m.m_t = measurement[2];
m.m_u = measurement[3];
m.num_measures = 3;
if (m.m_t ≡ 0) m.num_measures--;
if (m.m_u ≡ 0) m.num_measures--;
```

This code is used in section 89.

96. IAD Input Output.
The special define below is to get Visual C to suppress silly warnings.

⟨ iad_io.c 96 ⟩ ≡
```
#define _CRT_SECURE_NO_WARNINGS
#define MAX_COLUMNS 256
  char COLUMN_LABELS[MAX_COLUMNS] = "";
#include <string.h>
#include <stdio.h>
#include <stdlib.h>
#include <ctype.h>
#include <math.h>
#include "ad_globl.h"
#include "iad_type.h"
#include "iad_io.h"
#include "iad_pub.h"
#include "version.h"
```
⟨ Definition for *skip_white* 108 ⟩
⟨ Definition for *read_number* 110 ⟩
⟨ Definition for *check_magic* 112 ⟩
⟨ Definition for *remove_whitespace* 121 ⟩
⟨ Definition for *remove_comment* 122 ⟩
⟨ Definition for *remove_first_char* 123 ⟩
⟨ Definition for *print_maybe* 124 ⟩
⟨ Definition for *Read_Data_Legend* 126 ⟩
⟨ Definition for *Read_Data_Line_Per_Labels* 106 ⟩
⟨ Definition for *Read_Header* 100 ⟩
⟨ Definition for *Write_Header* 114 ⟩
⟨ Definition for *Read_Data_Line* 105 ⟩

97. ⟨ iad_io.h 97 ⟩ ≡
⟨ Prototype for *Read_Header* 99 ⟩;
⟨ Prototype for *Write_Header* 113 ⟩;
⟨ Prototype for *Read_Data_Line* 104 ⟩;

98. Reading the file header.

99. ⟨ Prototype for *Read_Header* 99 ⟩ ≡

```
int Read_Header(FILE *fp, struct measure_type *m, int *params)
```

This code is used in sections 97 and 100.

100. Pretty straightforward stuff. The only thing that needs to be commented on is that only one slide thickness/index is specified in the file. This must be applied to both the top and bottom slides. Finally, to specify no slide, then either setting the slide index to 1.0 or the thickness to 0.0 should do the trick.

⟨ Definition for *Read_Header* 100 ⟩ ≡

```
⟨ Prototype for Read_Header 99 ⟩
{
  double x;
  Initialize_Measure(m);
  if (check_magic(fp)) return 1;
  if (read_number(fp, &m→slab_index)) return 1;
  if (read_number(fp, &m→slab_top_slide_index)) return 1;
  if (read_number(fp, &m→slab_thickness)) return 1;
  if (read_number(fp, &m→slab_top_slide_thickness)) return 1;
  if (read_number(fp, &m→d_beam)) return 1;
  if (m→slab_top_slide_thickness ≡ 0.0) m→slab_top_slide_index = 1.0;
  if (m→slab_top_slide_index ≡ 1.0) m→slab_top_slide_thickness = 0.0;
  if (m→slab_top_slide_index ≡ 0.0) {
    m→slab_top_slide_thickness = 0.0;
    m→slab_top_slide_index = 1.0;
  }
  m→slab_bottom_slide_index = m→slab_top_slide_index;
  m→slab_bottom_slide_thickness = m→slab_top_slide_thickness;
  if (read_number(fp, &m→rstd_r)) return 1;
  if (read_number(fp, &x)) return 1;
  m→num_spheres = (int) x;
  m→method = SUBSTITUTION;
  ⟨ Read coefficients for reflection sphere 101 ⟩
  ⟨ Read coefficients for transmission sphere 102 ⟩
  ⟨ Read info about measurements 103 ⟩
  return 0;
}
```

This code is used in section 96.

101. ⟨ Read coefficients for reflection sphere 101 ⟩ ≡

```
{
  double d_sample_r, d_empty_r, d_detector_r;
  if (read_number(fp, &m→d_sphere_r)) return 1;
  if (read_number(fp, &d_sample_r)) return 1;
  if (read_number(fp, &d_empty_r)) return 1;
  if (read_number(fp, &d_detector_r)) return 1;
  if (read_number(fp, &m→rw_r)) return 1;
  m→as_r = (d_sample_r/m→d_sphere_r/2.0) * (d_sample_r/m→d_sphere_r/2.0);
  m→ae_r = (d_empty_r/m→d_sphere_r/2.0) * (d_empty_r/m→d_sphere_r/2.0);
  m→ad_r = (d_detector_r/m→d_sphere_r/2.0) * (d_detector_r/m→d_sphere_r/2.0);
  m→aw_r = 1.0 - m→as_r - m→ae_r - m→ad_r;
}
```

This code is used in section 100.

102. ⟨ Read coefficients for transmission sphere 102 ⟩ ≡

```
{
  double d_sample_t, d_empty_t, d_detector_t;
  if (read_number(fp, &m→d_sphere_t)) return 1;
  if (read_number(fp, &d_sample_t)) return 1;
  if (read_number(fp, &d_empty_t)) return 1;
  if (read_number(fp, &d_detector_t)) return 1;
  if (read_number(fp, &m→rw_t)) return 1;
  m→as_t = (d_sample_t/m→d_sphere_t/2.0) * (d_sample_t/m→d_sphere_t/2.0);
  m→ae_t = (d_empty_t/m→d_sphere_t/2.0) * (d_empty_t/m→d_sphere_t/2.0);
  m→ad_t = (d_detector_t/m→d_sphere_t/2.0) * (d_detector_t/m→d_sphere_t/2.0);
  m→aw_t = 1.0 - m→as_t - m→ae_t - m→ad_t;
}
```

This code is used in section 100.

103. ⟨ Read info about measurements 103 ⟩ ≡

```
*params = Read_Data_Legend(fp);
if (COLUMN_LABELS[0] ≠ '\0') {
  m→num_measures = 0;
  if (strchr(COLUMN_LABELS, 'r')) m→num_measures++;
  if (strchr(COLUMN_LABELS, 't')) m→num_measures++;
  if (strchr(COLUMN_LABELS, 'u')) m→num_measures++;
  if (m→num_measures ≡ 0) {
    fprintf(stderr, "Column␣labels␣must␣have␣at␣least␣one␣'r',␣'t',␣or␣'u'\n");
    fprintf(stderr, "Column␣labels␣=␣'%s'\n", COLUMN_LABELS);
    exit(EXIT_FAILURE);
  }
}
else m→num_measures = (*params ≥ 3) ? 3 : *params;
```

This code is used in section 100.

104. Reading just one line of a data file.

This reads a line of data based on the value of *params*.

If the first number is greater than one then it is assumed to be the wavelength and is ignored. test on the first value of the line.

A non-zero value is returned upon a failure.

⟨ Prototype for *Read_Data_Line* 104 ⟩ ≡

```
int Read_Data_Line(FILE *fp, struct measure_type *m, struct invert_type *r, int params)
```

This code is used in sections 97 and 105.

105. ⟨ Definition for *Read_Data_Line* 105 ⟩ ≡

```
⟨ Prototype for Read_Data_Line 104 ⟩
{
  if (strlen(COLUMN_LABELS) > 0) return Read_Data_Line_Per_Labels(fp, m, r, params);
  if (read_number(fp, &m→m_r)) return 1;
  if (m→m_r > 1) {
    m→lambda = m→m_r;
    if (read_number(fp, &m→m_r)) return 1;
  }
  if (params ≡ 1) return 0;
  if (read_number(fp, &m→m_t)) return 1;
  if (params ≡ 2) return 0;
  if (read_number(fp, &m→m_u)) return 1;
  if (params ≡ 3) return 0;
  if (read_number(fp, &m→rw_r)) return 1;
  m→rw_t = m→rw_r;
  if (params ≡ 4) return 0;
  if (read_number(fp, &m→rw_t)) return 1;
  if (params ≡ 5) return 0;
  if (read_number(fp, &m→rstd_r)) return 1;
  if (params ≡ 6) return 0;
  if (read_number(fp, &m→rstd_t)) return 1;
  return 0;
}
```

This code is used in section 96.

106. ⟨ Definition for *Read_Data_Line_Per_Labels* 106 ⟩ ≡

```
int Read_Data_Line_Per_Labels(FILE *fp, struct measure_type *m, struct invert_type *r, int
        params)
{
  int count = 0;
  double x;
  while (count < params) {
    if (read_number(fp, &x)) return 1;
    char c = COLUMN_LABELS[count];
    if (FALSE) fprintf(stderr, "count = %2d, option = %c, value = %10.5f\n", count, c, x);
    switch (c) {
    case 'a': r→default_a = x;
      break;
    case 'A': r→default_mua = x;
      r→default_ba = x * m→slab_thickness;
      break;
    case 'b': r→default_b = x;
      break;
    case 'B': m→d_beam = x;
      break;
    case 'c': m→fraction_of_rc_in_mr = x;
      break;
    case 'C': m→fraction_of_tc_in_mt = x;
      break;
    case 'd': m→slab_thickness = x;
      break;
    case 'D': m→slab_top_slide_thickness = x;
      m→slab_bottom_slide_thickness = x;
      break;
    case 'e': r→tolerance = x;
      r→MC_tolerance = x;
      break;
    case 'E': m→slab_bottom_slide_b = x;
      m→slab_top_slide_b = x;
      break;
    case 'F': r→default_mus = x;
      r→default_bs = x * m→slab_thickness;
      break;
    case 'g': r→default_g = x;
      break;
    case 'L': m→lambda = x;
      break;
    case 'M': m→num_spheres = (int) x;
      break;
    case 'n': m→slab_index = x;
      break;
    case 'N': m→slab_top_slide_index = x;
      m→slab_bottom_slide_index = x;
      break;
    case 'q': r→method.quad_pts = (int) x;
      break;
```

```
      case 'r': m→m_r = x;
        break;
      case 'R': m→rstd_r = x;
        break;
      case 't': m→m_t = x;
        break;
      case 'S': m→num_spheres = (int) x;
        break;
      case 'T': m→rstd_t = x;
        break;
      case 'u': m→m_u = x;
        break;
      case 'w': m→rw_r = x;
        break;
      case 'W': m→rw_t = x;
        break;
      default: fprintf(stderr, "legend␣variable␣'%c'␣unimplemented", c);
        return 1;
      }
      count++;
    }
    return 0;
  }
```

This code is used in section 96.

107. Skip over white space and comments. It is assumed that # starts all comments and continues to the end of a line. This routine should work on files with nearly any line ending CR, LF, CRLF.

Failure is indicated by a non-zero return value.

```
⟨ Prototype for skip_white 107 ⟩ ≡
  int skip_white(FILE *fp)
```

This code is used in section 108.

108.

```
⟨ Definition for skip_white 108 ⟩ ≡
  ⟨ Prototype for skip_white 107 ⟩
  {
    int c = fgetc(fp);
    while (¬feof(fp)) {
      if (isspace(c)) c = fgetc(fp);
      else if (c ≡ '#') do c = fgetc(fp); while (¬feof(fp) ∧ c ≠ '\n' ∧ c ≠ '\r');
      else break;
    }
    if (feof(fp)) return 1;
    ungetc(c, fp);
    return 0;
  }
```

This code is used in section 96.

109. Read a single number. Return 0 if there are no problems, otherwise return 1.

```
⟨ Prototype for read_number 109 ⟩ ≡
  int read_number(FILE *fp, double *x)
```

This code is used in section 110.

110. ⟨ Definition for *read_number* 110 ⟩ ≡

```
⟨ Prototype for read_number 109 ⟩
{
  if (skip_white(fp)) return 1;
  if (fscanf(fp, "%lf", x)) return 0;
  else return 1;
}
```

This code is used in section 96.

111. Ensure that the data file is actually in the right form. Return 0 if the file has the right starting characters. Return 1 if on a failure.

⟨ Prototype for *check_magic* 111 ⟩ ≡

```
int check_magic(FILE *fp)
```

This code is used in section 112.

112. ⟨ Definition for *check_magic* 112 ⟩ ≡

```
⟨ Prototype for check_magic 111 ⟩
{
  char magic[] = "IAD1";
  int i, c;
  for (i = 0; i < 4; i++) {
    c = fgetc(fp);
    if (feof(fp) ∨ c ≠ magic[i]) {
      fprintf(stderr, "Sorry, but iad input files must begin with IAD1\n");
      fprintf(stderr, "␣␣␣␣␣␣␣␣as the first four characters of the file.\n");
      fprintf(stderr, "␣␣␣␣␣␣␣␣Perhaps you are using an old iad format?\n");
      return 1;
    }
  }
  return 0;
}
```

This code is used in section 96.

113. Formatting the header information.

⟨ Prototype for *Write_Header* 113 ⟩ ≡
void *Write_Header*(**struct measure_type** *m*, **struct invert_type** *r*, **int** *params*, **char** ∗*cmd*)

This code is used in sections 97 and 114.

114. ⟨ Definition for *Write_Header* 114 ⟩ ≡
⟨ Prototype for *Write_Header* 113 ⟩
{
⟨ Write slab info 115 ⟩
⟨ Write irradiation info 116 ⟩
⟨ Write general sphere info 117 ⟩
⟨ Write first sphere info 118 ⟩
⟨ Write second sphere info 119 ⟩
⟨ Write measure and inversion info 120 ⟩
}

This code is used in section 96.

115. ⟨ Write slab info 115 ⟩ ≡
double *xx*;
printf("# Inverse Adding-Doubling %s \n", *Version*);
printf("# %s\n", *cmd*);
printf("# Beam diameter = ");
print_maybe('B', "%7.1f mm\n", *m.d_beam*);
printf("# Sample thickness = ");
print_maybe('d', "%7.3f mm\n", *m.slab_thickness*);
printf("# Top slide thickness = ");
print_maybe('D', "%7.3f mm\n", *m.slab_top_slide_thickness*);
printf("# Bottom slide thickness = ");
print_maybe('D', "%7.3f mm\n", *m.slab_bottom_slide_thickness*);
printf("# Sample index of refraction = ");
print_maybe('n', "%7.4f mm\n", *m.slab_index*);
printf("# Top slide index of refraction = ");
print_maybe('N', "%7.4f mm\n", *m.slab_top_slide_index*);
printf("# Bottom slide index of refraction = ");
print_maybe('N', "%7.4f mm\n", *m.slab_bottom_slide_index*);

This code is used in section 114.

116. ⟨ Write irradiation info 116 ⟩ ≡
printf("# \n");

This code is used in section 114.

117. ⟨ Write general sphere info 117 ⟩ ≡
printf("# Percentage unscattered refl. in M_R = ");
print_maybe('c', "%7.1f %%\n", *m.fraction_of_rc_in_mr* ∗ 100);
printf("# Percentage unscattered trans. in M_T = ");
print_maybe('C', "%7.1f %%\n", *m.fraction_of_tc_in_mt* ∗ 100);
printf("# \n");

This code is used in section 114.

118. ⟨ Write first sphere info 118 ⟩ ≡

```
printf("# Reflection sphere");
if (m.baffle_r) printf(" has a baffle between sample and detector");
else printf(" has no baffle between sample and detector");
if (m.num_spheres > 0) printf("\n");
else printf(" (ignored since no spheres used)\n");
printf("#                    sphere diameter = %7.1f mm\n", m.d_sphere_r);
printf("#                  sample port diameter = %7.1f mm\n", 2 * m.d_sphere_r * sqrt(m.as_r));
printf("#                   empty port diameter = %7.1f mm\n", 2 * m.d_sphere_r * sqrt(m.ae_r));
printf("#                detector port diameter = %7.1f mm\n", 2 * m.d_sphere_r * sqrt(m.ad_r));
printf("#              detector reflectance = %7.1f %%\n", m.rd_r * 100);
printf("#                      wall reflectance = ");
print_maybe('w', "%7.1f %%\n", m.rw_r * 100);
printf("#              calibration standard = ");
print_maybe('R', "%7.1f %%\n", m.rstd_r * 100);
printf("#\n");
```

This code is used in section 114.

119. ⟨ Write second sphere info 119 ⟩ ≡

```
printf("# Transmission sphere");
if (m.baffle_t) printf(" has a baffle between sample and detector");
else printf(" has no baffle between sample and detector");
if (m.num_spheres > 0) printf("\n");
else printf(" (ignored since no spheres used)\n");
printf("#                    sphere diameter = %7.1f mm\n", m.d_sphere_t);
printf("#                  sample port diameter = %7.1f mm\n", 2 * m.d_sphere_r * sqrt(m.as_t));
printf("#                   empty port diameter = %7.1f mm\n", 2 * m.d_sphere_r * sqrt(m.ae_t));
printf("#                detector port diameter = %7.1f mm\n", 2 * m.d_sphere_r * sqrt(m.ad_t));
printf("#              detector reflectance = %7.1f %%\n", m.rd_t * 100);
if (m.ae_t ≡ 0) printf("#    wall reflectance and cal standard = ");
else printf("#                      wall reflectance = ");
print_maybe('w', "%7.1f %%\n", m.rw_t * 100);
printf("#              calibration standard = %7.1f %%", m.rstd_t * 100);
if (m.ae_t ≡ 0) printf(" (ignored)");
printf("\n");
```

This code is used in section 114.

120. ⟨ Write measure and inversion info 120 ⟩ ≡

```
printf("#\n");
if (COLUMN_LABELS[0] ≡ '\0') {
  switch (params) {
  case −1: printf("# No M_R or M_T -- forward calculation.\n");
    break;
  case 1: printf("# Just M_R was measured");
    break;
  case 2: printf("# M_R and M_T were measured");
    break;
  case 3: printf("# M_R, M_T, and M_U were measured");
    break;
  case 4: printf("# M_R, M_T, M_U, and r_w were measured");
    break;
  case 5: printf("# M_R, M_T, M_U, r_w, and t_w were measured");
    break;
  case 6: printf("# M_R, M_T, M_U, r_w, t_w, and r_std were measured");
    break;
  case 7: printf("# M_R, M_T, M_U, r_w, t_w, r_std and t_std were measured");
    break;
  default: printf("# Something went wrong ... measures should be 1 to 7!\n");
    break;
  }
}
else {
  int i;
  printf("# %d input columns with LABELS:", params);
  for (i = 0; i < params; i++) {
    printf(" %c ", COLUMN_LABELS[i]);
  }
}
if (m.flip_sample) printf(" (sample flipped) ");
switch (m.method) {
case UNKNOWN: printf(" using an unknown method.\n");
  break;
case SUBSTITUTION: printf(" using the substitution (single-beam) method.\n");
  break;
case COMPARISON: printf(" using the comparison (dual-beam) method.\n");
}
switch (m.num_spheres) {
case 0: printf("# No sphere corrections were used");
  break;
case 1:
  if (m.method ≡ COMPARISON) printf("# No sphere corrections were needed");
  else printf("# Single sphere corrections were used");
  break;
case 2: printf("# Double sphere corrections were used");
  break;
}
printf(" and light was incident at %d degrees from the normal",
    (int)(acos(m.slab_cos_angle) * 57.2958));
printf(".\n");
```

```
switch (r.search) {
case FIND_AB: printf("# The inverse routine varied the albedo and optical depth.\n");
  printf("# \n");
  xx = (r.default_g ≠ UNINITIALIZED) ? r.default_g : 0;
  printf("# Default single scattering anisotropy = %7.3f \n", xx);
  break;
case FIND_AG: printf("# The inverse routine varied the albedo and anisotropy.\n");
  printf("# \n");
  if (r.default_b ≠ UNINITIALIZED)
    printf("#                        Default (mu_t*d) = %7.3g\n", r.default_b);
  else printf("# \n");
  break;
case FIND_AUTO: printf("# The inverse routine adapted to the input data.\n");
  printf("# \n");
  printf("# \n");
  break;
case FIND_A: printf("# The inverse routine varied only the albedo.\n");
  printf("# \n");
  xx = (r.default_g ≠ UNINITIALIZED) ? r.default_g : 0;
  printf("# Default single scattering anisotropy is %7.3f ", xx);
  xx = (r.default_b ≠ UNINITIALIZED) ? r.default_b : HUGE_VAL;
  printf(" and (mu_t*d) = %7.3g\n", xx);
  break;
case FIND_B: printf("# The inverse routine varied only the optical depth.\n");
  printf("# \n");
  xx = (r.default_g ≠ UNINITIALIZED) ? r.default_g : 0;
  printf("# Default single scattering anisotropy is %7.3f ", xx);
  if (r.default_a ≠ UNINITIALIZED) printf("and default albedo = %7.3g\n", r.default_a);
  else printf("\n");
  break;
case FIND_Ba: printf("# The inverse routine varied only the absorption.\n");
  printf("# \n");
  xx = (r.default_bs ≠ UNINITIALIZED) ? r.default_bs : 0;
  printf("#                        Default (mu_s*d) = %7.3g\n", xx);
  break;
case FIND_Bs: printf("# The inverse routine varied only the scattering.\n");
  printf("# \n");
  xx = (r.default_ba ≠ UNINITIALIZED) ? r.default_ba : 0;
  printf("#                        Default (mu_a*d) = %7.3g\n", xx);
  break;
default: printf("# \n");
  printf("# \n");
  printf("# \n");
  break;
}
printf("#                    AD quadrature points = %3d\n", r.method.quad_pts);
printf("#                AD tolerance for success = %9.5f\n", r.tolerance);
printf("#                MC tolerance for mu_a and mu_s' = %7.3f %%\n", r.MC_tolerance);
```

This code is used in section 114.

121. Discard white space and dashes in the legend string

```
⟨ Definition for remove_whitespace 121 ⟩ ≡
  void remove_whitespace(char *str)
  {
    int i, j = 0;
    for (i = 0; str[i] ≠ '\0'; i++) {
      if (¬isspace(str[i]) ∧ str[i] ≠ '-') {
        str[j++] = str[i];
      }
    }
    str[j] = '\0';
  }
```

This code is used in section 96.

122.

```
⟨ Definition for remove_comment 122 ⟩ ≡
  void remove_comment(char *str)
  {
    int i;
    for (i = 0; str[i] ≠ '\0'; i++) {
      if (str[i] ≡ '#') {
        str[i] = '\0';
        break;
      }
    }
  }
```

This code is used in section 96.

123.

```
⟨ Definition for remove_first_char 123 ⟩ ≡
  void remove_first_char(char *str)
  {
    int len = strlen(str);
    if (len > 0) {
      for (int i = 0; i < len; i++) {
        str[i] = str[i + 1];
      }
    }
  }
```

This code is used in section 96.

124.

```
⟨ Definition for print_maybe 124 ⟩ ≡
  void print_maybe(char c, char *format, double x)
  {
    char *result = strchr(COLUMN_LABELS, c);
    if (result ≡ Λ) printf(format, x);
    else printf("␣(varies␣with␣input␣row)\n");
  }
```

This code is used in section 96.

125.

```
⟨ Prototype for Read_Data_Legend 125 ⟩ ≡
  int Read_Data_Legend(FILE *fp)
```

This code is used in section 126.

126. ⟨ Definition for *Read_Data_Legend* 126 ⟩ ≡

```
⟨ Prototype for Read_Data_Legend 125 ⟩
{
  int n = 0;
  char c;
  skip_white(fp);
  if (fgets(COLUMN_LABELS, MAX_COLUMNS, fp) ≡ Λ) {
    fprintf(stderr, "could␣not␣read␣Data␣Legend␣String␣in␣file\n");
    exit(EXIT_FAILURE);
  }
  remove_whitespace(COLUMN_LABELS);
  remove_comment(COLUMN_LABELS);
  c = COLUMN_LABELS[0];
  if (c ≡ '1' ∨ c ≡ '2' ∨ c ≡ '3' ∨ c ≡ '4' ∨ c ≡ '5' ∨ c ≡ '6' ∨ c ≡ '7') {
    n = COLUMN_LABELS[0] − '0';
    COLUMN_LABELS[0] = '\0';
  }
  else {
    n = strlen(COLUMN_LABELS);
  }
  return n;
}
```

This code is used in section 96.

127. IAD Calculation.

⟨ iad_calc.c 127 ⟩ ≡
```
#include <math.h>
#include <string.h>
#include <stdio.h>
#include <stdlib.h>
#include "nr_util.h"
#include "nr_zbrent.h"
#include "ad_globl.h"
#include "ad_frsnl.h"
#include "ad_prime.h"
#include "iad_type.h"
#include "iad_util.h"
#include "iad_calc.h"
#define ABIT 1.0e-6
#define A_COLUMN 1
#define B_COLUMN 2
#define G_COLUMN 3
#define URU_COLUMN 4
#define UTU_COLUMN 5
#define UR1_COLUMN 6
#define UT1_COLUMN 7
#define REFLECTION_SPHERE 1
#define TRANSMISSION_SPHERE 0
#define GRID_SIZE 201
#define T_TRUST_FACTOR 1
#define MAX_ABS_G 0.999999
#define SWAP(a,b)
  {
    double swap = (a);
    (a) = (b);
    (b) = swap;
  }
  static int CALCULATING_GRID = 0;
  static struct measure_type MM;
  static struct invert_type RR;
  static struct measure_type MGRID;
  static struct invert_type RGRID;
  static double **The_Grid = Λ;
  static double GG_a;
  static double GG_b;
  static double GG_g;
  static double GG_bs;
  static double GG_ba;
  static boolean_type The_Grid_Initialized = FALSE;
  static boolean_type The_Grid_Search = -1;
  ⟨ Definition for Set_Calc_State 143 ⟩
  ⟨ Definition for Get_Calc_State 145 ⟩
  ⟨ Definition for Same_Calc_State 147 ⟩
  ⟨ Prototype for Fill_AB_Grid 165 ⟩;
  ⟨ Prototype for Fill_AG_Grid 169 ⟩;
```

⟨ Definition for *RT_Flip* 163 ⟩
⟨ Definition for *Allocate_Grid* 149 ⟩
⟨ Definition for *Valid_Grid* 153 ⟩
⟨ Definition for *fill_grid_entry* 164 ⟩
⟨ Definition for *Fill_Grid* 179 ⟩
⟨ Definition for *Near_Grid_Points* 161 ⟩
⟨ Definition for *Fill_AB_Grid* 166 ⟩
⟨ Definition for *Fill_AG_Grid* 170 ⟩
⟨ Definition for *Fill_BG_Grid* 173 ⟩
⟨ Definition for *Fill_BaG_Grid* 175 ⟩
⟨ Definition for *Fill_BsG_Grid* 177 ⟩
⟨ Definition for *Grid_ABG* 151 ⟩
⟨ Definition for *Gain* 132 ⟩
⟨ Definition for *Gain_11* 134 ⟩
⟨ Definition for *Gain_22* 136 ⟩
⟨ Definition for *Two_Sphere_R* 138 ⟩
⟨ Definition for *Two_Sphere_T* 140 ⟩
⟨ Definition for *Calculate_Distance_With_Corrections* 185 ⟩
⟨ Definition for *Calculate_Grid_Distance* 183 ⟩
⟨ Definition for *Calculate_Distance* 181 ⟩
⟨ Definition for *abg_distance* 159 ⟩
⟨ Definition for *Find_AG_fn* 199 ⟩
⟨ Definition for *Find_AB_fn* 201 ⟩
⟨ Definition for *Find_Ba_fn* 203 ⟩
⟨ Definition for *Find_Bs_fn* 205 ⟩
⟨ Definition for *Find_A_fn* 207 ⟩
⟨ Definition for *Find_B_fn* 209 ⟩
⟨ Definition for *Find_G_fn* 211 ⟩
⟨ Definition for *Find_BG_fn* 213 ⟩
⟨ Definition for *Find_BaG_fn* 215 ⟩
⟨ Definition for *Find_BsG_fn* 217 ⟩
⟨ Definition for *maxloss* 219 ⟩
⟨ Definition for *Max_Light_Loss* 221 ⟩

128.

⟨ iad_calc.h 128 ⟩ ≡
⟨ Prototype for *Gain* 131 ⟩;
⟨ Prototype for *Gain_11* 133 ⟩;
⟨ Prototype for *Gain_22* 135 ⟩;
⟨ Prototype for *Two_Sphere_R* 137 ⟩;
⟨ Prototype for *Two_Sphere_T* 139 ⟩;
⟨ Prototype for *Set_Calc_State* 142 ⟩;
⟨ Prototype for *Get_Calc_State* 144 ⟩;
⟨ Prototype for *Same_Calc_State* 146 ⟩;
⟨ Prototype for *Valid_Grid* 152 ⟩;
⟨ Prototype for *Allocate_Grid* 148 ⟩;
⟨ Prototype for *Fill_Grid* 178 ⟩;
⟨ Prototype for *Near_Grid_Points* 160 ⟩;
⟨ Prototype for *Grid_ABG* 150 ⟩;
⟨ Prototype for *Find_AG_fn* 198 ⟩;
⟨ Prototype for *Find_AB_fn* 200 ⟩;
⟨ Prototype for *Find_Ba_fn* 202 ⟩;
⟨ Prototype for *Find_Bs_fn* 204 ⟩;
⟨ Prototype for *Find_A_fn* 206 ⟩;
⟨ Prototype for *Find_B_fn* 208 ⟩;
⟨ Prototype for *Find_G_fn* 210 ⟩;
⟨ Prototype for *Find_BG_fn* 212 ⟩;
⟨ Prototype for *Find_BsG_fn* 216 ⟩;
⟨ Prototype for *Find_BaG_fn* 214 ⟩;
⟨ Prototype for *Fill_BG_Grid* 172 ⟩;
⟨ Prototype for *Fill_BsG_Grid* 176 ⟩;
⟨ Prototype for *Fill_BaG_Grid* 174 ⟩;
⟨ Prototype for *Calculate_Distance_With_Corrections* 184 ⟩;
⟨ Prototype for *Calculate_Distance* 180 ⟩;
⟨ Prototype for *Calculate_Grid_Distance* 182 ⟩;
⟨ Prototype for *abg_distance* 158 ⟩;
⟨ Prototype for *maxloss* 218 ⟩;
⟨ Prototype for *Max_Light_Loss* 220 ⟩;
⟨ Prototype for *RT_Flip* 162 ⟩;

129. Initialization.

The functions in this file assume that the local variables `MM` and `RR` have been initialized appropriately. The variable `MM` contains all the information about how a particular experiment was done. The structure `RR` contains the data structure that is passed to the adding-doubling routines as well as the number of quadrature points.

130. Gain.

Assume that a sphere is illuminated with diffuse light having a power P. This light will undergo multiple reflections in the sphere walls that will increase the power falling on the detector.

The gain on the detector due to integrating sphere effects varies with the presence of a baffle between the sample and the detector. If a baffle is present then

$$G_{\text{no baffle}}(r_s) = \frac{1}{1 - a_w r_w - a_d r_d - a_s r_s}$$

or with a baffle as

$$G_{\text{baffle}}(r_s) = \frac{1}{1 - a_w r_w - r_w(1 - a_e)(a_d r_d + a_s r_s)}$$

For a black sphere the gain does not depend on the diffuse reflectivity of the sample and is unity. $G(r_s) = 1$, which is easily verified by setting $r_w = 0$.

131. ⟨ Prototype for *Gain* 131 ⟩ ≡

```
double Gain(int sphere, struct measure_type m, double URU)
```

This code is used in sections 128 and 132.

132. ⟨ Definition for *Gain* 132 ⟩ ≡

```
⟨ Prototype for Gain 131 ⟩
{
  double G, denom;
  if (sphere ≡ REFLECTION_SPHERE) {
    if (m.baffle_r) denom = 1.0 − m.rw_r ∗ (m.aw_r + (1 − m.ae_r) ∗ (m.ad_r ∗ m.rd_r + m.as_r ∗ URU));
    else denom = 1.0 − m.aw_r ∗ m.rw_r − m.ad_r ∗ m.rd_r − m.as_r ∗ URU;
  }
  else {
    if (m.baffle_t) denom = 1.0 − m.rw_t ∗ (m.aw_t + (1 − m.ae_t) ∗ (m.ad_t ∗ m.rd_t + m.as_t ∗ URU));
    else denom = 1.0 − m.aw_t ∗ m.rw_t − m.ad_t ∗ m.rd_t − m.as_t ∗ URU;
  }
  G = 1.0/denom;
  return G;
}
```

This code is used in section 127.

133. The gain for light on the detector in the first sphere for diffuse light starting in that same sphere is defined as

$$G_{1\to1}(r_s, t_s) \equiv \frac{P_{1\to1}(r_s, t_s)/A_d}{P/A}$$

then the full expression for the gain is

$$G_{1\to1}(r_s, t_s) = \frac{G(r_s)}{1 - a_s a'_s r_w r'_w (1 - a_e)(1 - a'_e) G(r_s) G'(r_s) t_s^2}$$

⟨ Prototype for *Gain_11* 133 ⟩ ≡

```
double Gain_11(struct measure_type m, double URU, double tdiffuse)
```

This code is used in sections 128 and 134.

134. ⟨ Definition for *Gain_11* 134 ⟩ ≡

```
⟨ Prototype for Gain_11 133 ⟩
{
  double G, GP, G11;
  G = Gain(REFLECTION_SPHERE, m, URU);
  GP = Gain(TRANSMISSION_SPHERE, m, URU);
  G11 = G/(1 - m.as_r * m.as_t * m.aw_r * m.aw_t * (1 - m.ae_r) * (1 - m.ae_t) * G * GP * tdiffuse * tdiffuse);
  return G11;
}
```

This code is used in section 127.

135. Similarly, when the light starts in the second sphere, the gain for light on the detector in the second sphere $G_{2\to2}$ is found by switching all primed variables to unprimed. Thus $G_{2\to1}(r_s, t_s)$ is

$$G_{2\to2}(r_s, t_s) = \frac{G'(r_s)}{1 - a_s a'_s r_w r'_w (1 - a_e)(1 - a'_e) G(r_s) G'(r_s) t_s^2}$$

⟨ Prototype for *Gain_22* 135 ⟩ ≡

```
double Gain_22(struct measure_type m, double URU, double tdiffuse)
```

This code is used in sections 128 and 136.

136. ⟨ Definition for *Gain_22* 136 ⟩ ≡

```
⟨ Prototype for Gain_22 135 ⟩
{
  double G, GP, G22;
  G = Gain(REFLECTION_SPHERE, m, URU);
  GP = Gain(TRANSMISSION_SPHERE, m, URU);
  G22 = GP/(1 - m.as_r * m.as_t * m.aw_r * m.aw_t * (1 - m.ae_r) * (1 - m.ae_t) * G * GP * tdiffuse * tdiffuse);
  return G22;
}
```

This code is used in section 127.

137. The reflected power for two spheres makes use of the formulas for *Gain_11* above.

The light on the detector in the reflection (first) sphere arises from three sources: the fraction of light directly reflected off the sphere wall $f r_w^2 (1 - a_e) P$, the fraction of light reflected by the sample $(1 - f) r_s^{\text{direct}} r_w^2 (1 - a_e) P$, and the light transmitted through the sample $(1 - f) t_s^{\text{direct}} r'_w (1 - a'_e) P$,

$$\begin{aligned} R(r_s^{\text{direct}}, r_s, t_s^{\text{direct}}, t_s) = {} & G_{1\to1}(r_s, t_s) \cdot a_d (1 - a_e) r_w^2 f P \\ & + G_{1\to1}(r_s, t_s) \cdot a_d (1 - a_e) r_w (1 - f) r_s^{\text{direct}} P \\ & + G_{2\to1}(r_s, t_s) \cdot a_d (1 - a'_e) r'_w (1 - f) t_s^{\text{direct}} P \end{aligned}$$

which simplifies slightly to

$$\begin{aligned} R(r_s^{\text{direct}}, r_s, t_s^{\text{direct}}, t_s) = {} & a_d (1 - a_e) r_w P \cdot G_{1\to1}(r_s, t_s) \\ & \times \left[(1 - f) r_s^{\text{direct}} + f r_w + (1 - f) a'_s (1 - a'_e) r'_w t_s^{\text{direct}} t_s G'(r_s) \right] \end{aligned}$$

⟨ Prototype for *Two_Sphere_R* 137 ⟩ ≡

```
double Two_Sphere_R(struct measure_type m, double UR1, double URU, double UT1, double UTU)
```

This code is used in sections 128 and 138.

138. ⟨ Definition for *Two_Sphere_R* 138 ⟩ ≡
⟨ Prototype for *Two_Sphere_R* 137 ⟩
{
double x, GP;
GP = *Gain*(TRANSMISSION_SPHERE, m, URU);
$x = m.ad\_r * (1 - m.ae\_r) * m.rw\_r *$ *Gain_11*(m, URU, UTU);
x *= $(1 - m.f\_r) *$ UR1 $+ m.rw\_r * m.f\_r + (1 - m.f\_r) * m.as\_t * (1 - m.ae\_t) * m.rw\_t *$ UT1 $*$ UTU $*$ GP;
return x;
}
This code is used in section 127.

139. For the power on the detector in the transmission (second) sphere we have the same three sources. The only difference is that the subscripts on the gain terms now indicate that the light ends up in the second sphere

$$\begin{aligned} T(r_s^{\text{direct}}, r_s, t_s^{\text{direct}}, t_s) &= G_{1\to 2}(r_s, t_s) \cdot a'_d(1 - a_e) r_w^2 f P \\ &\quad + G_{1\to 2}(r_s, t_s) \cdot a'_d(1 - a_e) r_w (1 - f) r_s^{\text{direct}} P \\ &\quad + G_{2\to 2}(r_s, t_s) \cdot a'_d(1 - a'_e) r'_w (1 - f) t_s^{\text{direct}} P \end{aligned}$$

or

$$\begin{aligned} T(r_s^{\text{direct}}, r_s, t_s^{\text{direct}}, t_s) &= a'_d(1 - a'_e) r'_w P \cdot G_{2\to 2}(r_s, t_s) \\ &\quad \times \left[(1 - f) t_s^{\text{direct}} + (1 - a_e) r_w a_s t_s (f r_w + (1 - f) r_s^{\text{direct}}) G(r_s) \right] \end{aligned}$$

⟨ Prototype for *Two_Sphere_T* 139 ⟩ ≡
double *Two_Sphere_T*(**struct measure_type** m, **double** UR1, **double** URU, **double** UT1, **double** UTU)
This code is used in sections 128 and 140.

140. ⟨ Definition for *Two_Sphere_T* 140 ⟩ ≡
⟨ Prototype for *Two_Sphere_T* 139 ⟩
{
double x, G;
G = *Gain*(REFLECTION_SPHERE, m, URU);
$x = m.ad\_t * (1 - m.ae\_t) * m.rw\_t *$ *Gain_22*(m, URU, UTU);
x *= $(1 - m.f\_r) *$ UT1 $+ (1 - m.ae\_r) * m.rw\_r * m.as\_r *$ UTU $* (m.f\_r * m.rw\_r + (1 - m.f\_r) *$ UR1$) * G$;
return x;
}
This code is used in section 127.

141. Grid Routines. There is a long story associated with these routines. I spent a lot of time trying to find an empirical function to allow a guess at a starting value for the inversion routine. Basically nothing worked very well. There were too many special cases and what not. So I decided to calculate a whole bunch of reflection and transmission values and keep their associated optical properties linked nearby.

I did the very simplest thing. I just allocate a matrix that is five columns wide. Then I fill every row with a calculated set of optical properties and observables. The distribution of values that I use could certainly use some work, but they currently work.

SO... how does this thing work anyway? There are two possible grids one for calculations requiring the program to find the albedo and the optical depth (a and b) and one to find the albedo and anisotropy (a and g). These grids must be allocated and initialized before use.

142. This is a pretty important routine that should have some explanation. The reason that it exists, is that we need some 'out-of-band' information during the minimization process. Since the light transport calculation depends on all sorts of stuff (e.g., the sphere parameters) and the minimization routines just vary one or two parameters this information needs to be put somewhere.

I chose the global variables `MM` and `RR` to save things in.

The bottom line is that you cannot do a light transport calculation without calling this routine first.

⟨ Prototype for *Set_Calc_State* 142 ⟩ ≡
void *Set_Calc_State*(**struct measure_type** m, **struct invert_type** r)

This code is used in sections 128 and 143.

143. ⟨ Definition for *Set_Calc_State* 143 ⟩ ≡
⟨ Prototype for *Set_Calc_State* 142 ⟩
{
memcpy(&MM, &m, **sizeof**(**struct measure_type**));
memcpy(&RR, &r, **sizeof**(**struct invert_type**));
}

This code is used in section 127.

144. The inverse of the previous routine. Note that you must have space for the parameters m and r already allocated.

⟨ Prototype for *Get_Calc_State* 144 ⟩ ≡
void *Get_Calc_State*(**struct measure_type** $*m$, **struct invert_type** $*r$)

This code is used in sections 128 and 145.

145. ⟨ Definition for *Get_Calc_State* 145 ⟩ ≡
⟨ Prototype for *Get_Calc_State* 144 ⟩
{
memcpy(m, &MM, **sizeof**(**struct measure_type**));
memcpy(r, &RR, **sizeof**(**struct invert_type**));
}

This code is used in section 127.

146. The inverse of the previous routine. Note that you must have space for the parameters m and r already allocated.

⟨ Prototype for *Same_Calc_State* 146 ⟩ ≡
boolean_type *Same_Calc_State*(**struct measure_type** m, **struct invert_type** r)

This code is used in sections 128 and 147.

147. ⟨ Definition for *Same_Calc_State* 147 ⟩ ≡

```
⟨ Prototype for Same_Calc_State 146 ⟩
{
  if (The_Grid ≡ Λ) return FALSE;
  if (¬The_Grid_Initialized) return FALSE;
  if (r.search ≠ RR.search) return FALSE;
  if (r.method.quad_pts ≠ RR.method.quad_pts) return FALSE;
  if (r.slab.a ≠ RR.slab.a) return FALSE;
  if (r.slab.b ≠ RR.slab.b) return FALSE;
  if (r.slab.g ≠ RR.slab.g) return FALSE;
  if (r.slab.phase_function ≠ RR.slab.phase_function) return FALSE;
  if (r.slab.n_slab ≠ RR.slab.n_slab) return FALSE;
  if (r.slab.n_top_slide ≠ RR.slab.n_top_slide) return FALSE;
  if (r.slab.n_bottom_slide ≠ RR.slab.n_bottom_slide) return FALSE;
  if (r.slab.b_top_slide ≠ RR.slab.b_top_slide) return FALSE;
  if (r.slab.b_bottom_slide ≠ RR.slab.b_bottom_slide) return FALSE;
  if (r.slab.cos_angle ≠ RR.slab.cos_angle) return FALSE;
  if ((m.num_measures ≡ 3) ∧ (m.m_u ≠ MGRID.m_u)) return (FALSE);
  return TRUE;
}
```

This code is used in section 127.

148. ⟨ Prototype for *Allocate_Grid* 148 ⟩ ≡

```
void Allocate_Grid(search_type s)
```

This code is used in sections 128 and 149.

149. ⟨ Definition for *Allocate_Grid* 149 ⟩ ≡

```
⟨ Prototype for Allocate_Grid 148 ⟩
{
  (void) s;
  The_Grid = dmatrix(0, GRID_SIZE * GRID_SIZE, 1, 7);
  if (The_Grid ≡ Λ) AD_error("unable␣to␣allocate␣the␣grid␣matrix");
  The_Grid_Initialized = FALSE;
}
```

This code is used in section 127.

150. This routine will return the a, b, and g values for a particular row in the grid.

⟨ Prototype for *Grid_ABG* 150 ⟩ ≡

```
void Grid_ABG(int i, int j, guess_type *guess)
```

This code is used in sections 128 and 151.

151. ⟨ Definition for *Grid_ABG* 151 ⟩ ≡

```
⟨ Prototype for Grid_ABG 150 ⟩
{
  if (0 ≤ i ∧ i < GRID_SIZE ∧ 0 ≤ j ∧ j < GRID_SIZE) {
    guess→a = The_Grid[GRID_SIZE * i + j][A_COLUMN];
    guess→b = The_Grid[GRID_SIZE * i + j][B_COLUMN];
    guess→g = The_Grid[GRID_SIZE * i + j][G_COLUMN];
    guess→distance = Calculate_Grid_Distance(i, j);
  }
  else {
    guess→a = 0.5;
    guess→b = 0.5;
    guess→g = 0.5;
    guess→distance = 999;
  }
}
```

This code is used in section 127.

152. This routine is used to figure out if the current grid is valid. This can fail for several reasons. First the grid may not have been allocated. Or it may not have been initialized. The boundary conditions may have changed. The number or values of the sphere parameters may have changed. It is tedious, but straightforward to check these cases out.

If this routine returns true, then it is a pretty good bet that the values in the current grid can be used to guess the next starting set of values.

⟨ Prototype for *Valid_Grid* 152 ⟩ ≡

```
boolean_type Valid_Grid(struct measure_type m, struct invert_type r)
```

This code is used in sections 128 and 153.

153. ⟨ Definition for *Valid_Grid* 153 ⟩ ≡

```
⟨ Prototype for Valid_Grid 152 ⟩
{
  int s = r.search;
  ⟨ Tests for invalid grid 154 ⟩
  return (TRUE);
}
```

This code is used in section 127.

154. First check are to test if the grid has ever been filled

⟨ Tests for invalid grid 154 ⟩ ≡

```
if (The_Grid ≡ Λ) {
  if (Debug(DEBUG_GRID)) fprintf(stderr, "GRID: Fill because NULL\n");
  return (FALSE);
}
if (¬The_Grid_Initialized) {
  if (Debug(DEBUG_GRID)) fprintf(stderr, "GRID: Fill because not initialized\n");
  return (FALSE);
}
```

See also sections 155, 156, and 157.

This code is used in section 153.

155. If the type of search has changed then report the grid as invalid

```
⟨ Tests for invalid grid 154 ⟩ +≡
  if (The_Grid_Search ≠ s) {
    if (Debug(DEBUG_GRID)) fprintf(stderr, "GRID: Fill because search type changed\n");
    return (FALSE);
  }
```

156. Compare the $m.m\_u$ value only if there are three measurements

```
⟨ Tests for invalid grid 154 ⟩ +≡
  if ((m.num_measures ≡ 3) ∧ (m.m_u ≠ MGRID.m_u)) {
    if (Debug(DEBUG_GRID)) fprintf(stderr, "GRID: Fill because unscattered light changed\n");
    return (FALSE);
  }
```

157. Make sure that the boundary conditions have not changed.

```
⟨ Tests for invalid grid 154 ⟩ +≡
  if (m.slab_index ≠ MGRID.slab_index) {
    if (Debug(DEBUG_GRID))
      fprintf(stderr, "GRID: Fill because slab refractive index changed\n");
    return (FALSE);
  }
  if (m.slab_cos_angle ≠ MGRID.slab_cos_angle) {
    if (Debug(DEBUG_GRID)) fprintf(stderr, "GRID: Fill because light angle changed\n");
    return (FALSE);
  }
  if (m.slab_top_slide_index ≠ MGRID.slab_top_slide_index) {
    if (Debug(DEBUG_GRID)) fprintf(stderr, "GRID: Fill because top slide index changed\n");
    return (FALSE);
  }
  if (m.slab_bottom_slide_index ≠ MGRID.slab_bottom_slide_index) {
    if (Debug(DEBUG_GRID)) fprintf(stderr, "GRID: Fill because bottom slide index changed\n");
    return (FALSE);
  }
  if (s ≡ FIND_AB ∧ r.slab.g ≠ RGRID.slab.g) {
    if (Debug(DEBUG_GRID)) fprintf(stderr, "GRID: Fill because anisotropy changed\n");
    return (FALSE);
  }
  if (s ≡ FIND_BsG ∧ r.default_ba ≠ RGRID.default_ba) {
    if (Debug(DEBUG_GRID)) fprintf(stderr, "GRID: Fill because mu_a changed\n");
    return (FALSE);
  }
```

158. Routine to just figure out the distance to a particular a, b, g point

```
⟨ Prototype for abg_distance 158 ⟩ ≡
  void abg_distance(double a, double b, double g, guess_type *guess)
```

This code is used in sections 128 and 159.

159. ⟨ Definition for *abg_distance* 159 ⟩ ≡

```
⟨ Prototype for abg_distance 158 ⟩
{
  double m_r, m_t, distance;
  struct measure_type old_mm;
  struct invert_type old_rr;
  Get_Calc_State(&old_mm, &old_rr);
  RR.slab.a = a;
  RR.slab.b = b;
  RR.slab.g = g;
  Calculate_Distance(&m_r, &m_t, &distance);
  Set_Calc_State(old_mm, old_rr);
  guess→a = a;
  guess→b = b;
  guess→g = g;
  guess→distance = distance;
}
```

This code is used in section 127.

160. This just searches through the grid to find the minimum entry and returns the optical properties of that entry. The smallest, the next smallest, and the third smallest values are returned.

This has been rewritten to use *Calculate_Distance_With_Corrections* so that changes in sphere parameters won't necessitate recalculating the grid.

⟨ Prototype for *Near_Grid_Points* 160 ⟩ ≡

```
void Near_Grid_Points(double r, double t, search_type s, int *i_min, int *j_min)
```

This code is used in sections 128 and 161.

161. ⟨ Definition for *Near_Grid_Points* 161 ⟩ ≡

```
⟨ Prototype for Near_Grid_Points 160 ⟩
{
  int i, j;
  double fval;
  double smallest = 10.0;
  struct measure_type old_mm;
  struct invert_type old_rr;
  (void) r;
  (void) t;
  (void) s;
  if (Debug(DEBUG_GRID)) fprintf(stderr, "GRID: Finding best grid points\n");
  Get_Calc_State(&old_mm, &old_rr);
  *i_min = 0;
  *j_min = 0;
  for (i = 0; i < GRID_SIZE; i++) {
    for (j = 0; j < GRID_SIZE; j++) {
      CALCULATING_GRID = 1;
      fval = Calculate_Grid_Distance(i, j);
      CALCULATING_GRID = 0;
      if (fval < smallest) {
        *i_min = i;
        *j_min = j;
        smallest = fval;
      }
    }
  }
  Set_Calc_State(old_mm, old_rr);
}
```

This code is used in section 127.

162. Routine to incorporate flipping of sample if needed. This is pretty simple. The assumption is that flipping is handled relative to the reflection side of the sphere. Thus even when flipping is needed, the usual call to `RT()` will result in the correct values for the reflectances. The transmission values can then be calculated by swapping the top and bottom slides.

Technically, the value of slab should be **const** but it is not so that we don't pay a copying overhead whenever *flip* is false (the usual case).

⟨ Prototype for *RT_Flip* 162 ⟩ ≡

```
void RT_Flip(int flip, int n, struct AD_slab_type *slab, double *UR1, double *UT1, double
    *URU, double *UTU)
```

This code is used in sections 128 and 163.

163. ⟨ Definition for *RT_Flip* 163 ⟩ ≡

```
⟨ Prototype for RT_Flip 162 ⟩
{
  double correct_UR1, correct_URU;
  RT(n, slab, UR1, UT1, URU, UTU);
  if (flip) {
    correct_UR1 = *UR1;
    correct_URU = *URU;
    SWAP(slab→n_top_slide, slab→n_bottom_slide)SWAP(slab→b_top_slide, slab→b_bottom_slide)RT(n, slab, UR1,
        UT1, URU, UTU);
    SWAP(slab→n_top_slide, slab→n_bottom_slide)SWAP(slab→b_top_slide,
        slab→b_bottom_slide) * UR1 = correct_UR1;
    *URU = correct_URU;
  }
}
```

This code is used in section 127.

164. Simple routine to put values into the grid
Presumes that RR.*slab* is properly set up.

```
⟨ Definition for fill_grid_entry 164 ⟩ ≡
  static void fill_grid_entry(int i, int j)
  {
    double ur1, ut1, uru, utu;
    if (RR.slab.b ≤ 1 · 10^−6) RR.slab.b = 1 · 10^−6;
    if (Debug(DEBUG_GRID_CALC) ∧ i ≡ 0 ∧ j ≡ 0) {
      fprintf(stderr, "+␣␣␣i␣␣␣j␣");
      fprintf(stderr, "␣␣␣␣␣␣a␣␣␣␣␣␣␣␣␣b␣␣␣␣␣␣␣␣␣␣g␣␣␣␣␣|");
      fprintf(stderr, "␣␣␣␣␣M_R␣␣␣␣␣␣␣␣grid␣␣|");
      fprintf(stderr, "␣␣␣␣␣M_T␣␣␣␣␣␣␣␣grid\n");
    }
    if (Debug(DEBUG_EVERY_CALC)) {
      if (¬CALCULATING_GRID)
        fprintf(stderr, "a=%8.5f␣b=%10.5f␣g=%8.5f␣", RR.slab.a, RR.slab.b, RR.slab.g);
      else {
        if (j ≡ 0) fprintf(stderr, ".");
        if (i + 1 ≡ GRID_SIZE ∧ j ≡ 0) fprintf(stderr, "\n");
      }
    }
    RT_Flip(MM.flip_sample, RR.method.quad_pts, &RR.slab, &ur1, &ut1, &uru, &utu);
    if (Debug(DEBUG_EVERY_CALC) ∧ ¬CALCULATING_GRID)
      fprintf(stderr, "ur1=%8.5f␣ut1=%8.5f\n", ur1, ut1);
    The_Grid[GRID_SIZE * i + j][A_COLUMN] = RR.slab.a;
    The_Grid[GRID_SIZE * i + j][B_COLUMN] = RR.slab.b;
    The_Grid[GRID_SIZE * i + j][G_COLUMN] = RR.slab.g;
    The_Grid[GRID_SIZE * i + j][UR1_COLUMN] = ur1;
    The_Grid[GRID_SIZE * i + j][UT1_COLUMN] = ut1;
    The_Grid[GRID_SIZE * i + j][URU_COLUMN] = uru;
    The_Grid[GRID_SIZE * i + j][UTU_COLUMN] = utu;
    if (Debug(DEBUG_GRID_CALC)) {
      fprintf(stderr, "+␣%3d␣%3d␣", i, j);
      fprintf(stderr, "%10.5f␣%10.5f␣%10.5f␣|", RR.slab.a, RR.slab.b, RR.slab.g);
      fprintf(stderr, "%10.5f␣%10.5f␣|", MM.m_r, uru);
      fprintf(stderr, "%10.5f␣%10.5f␣\n", MM.m_t, utu);
    }
  }
```

This code is used in section 127.

165. This routine fills the grid with a proper set of values. With a little work, this routine could be made much faster by (1) only generating the phase function matrix once, (2) Making only one pass through the array for each albedo value, i.e., using the matrix left over from $b = 1$ to generate the solution for $b = 2$. Unfortunately this would require a complete revision of the *Calculate_Distance* routine. Fortunately, this routine should only need to be calculated once at the beginning of each run.

```
⟨ Prototype for Fill_AB_Grid 165 ⟩ ≡
  void Fill_AB_Grid(struct measure_type m, struct invert_type r)
```

This code is used in sections 127 and 166.

166. ⟨ Definition for *Fill_AB_Grid* 166 ⟩ ≡

```
⟨ Prototype for Fill_AB_Grid 165 ⟩
{
  int i, j;
  double a;
  double min_log_b = −8;      /* exp(-10) is smallest thickness */
  double max_log_b = +8;      /* exp(+8) is greatest thickness */
  if (Debug(DEBUG_GRID)) fprintf(stderr, "GRID: Filling AB grid\n");
  if (The_Grid ≡ Λ) Allocate_Grid(r.search);
  ⟨ Zero GG 171 ⟩
  Set_Calc_State(m, r);
  GG_g = RR.slab.g;
  for (i = 0; i < GRID_SIZE; i++) {
    double x = (double) i/(GRID_SIZE − 1.0);
    RR.slab.b = exp(min_log_b + (max_log_b − min_log_b) * x);
    for (j = 0; j < GRID_SIZE; j++) {
      ⟨ Generate next albedo using j 168 ⟩
      fill_grid_entry(i, j);
    }
  }
  The_Grid_Initialized = TRUE;
  The_Grid_Search = FIND_AB;
}
```

This code is used in section 127.

167. Now it seems that I must be a bit more subtle in choosing the range of albedos to use in the grid. Originally I just spaced them according to

$$a = 1 - \left[\frac{j-1}{n-1}\right]^3$$

where $1 \le j \le n$. Long ago it seems that I based things only on the square of the bracketed term, but I seem to remember that I was forced to change it from a square to a cube to get more global convergence.

So why am I rewriting this? Well, because it works very poorly for samples with small albedos. For example, when $n = 11$ then the values chosen for a are (1, .999, .992, .973, .936, .875, .784, .657, .488, .271, 0). Clearly very skewed towards high albedos.

I am considering a two part division. I'm not too sure how it should go. Let the first half be uniformly divided and the last half follow the cubic scheme given above. The list of values should then be (1, .996, .968, .892, 0.744, .5, .4, .3, .2, .1, 0).

Maybe it would be best if I just went back to a quadratic term. Who knows?

In the **if** statement below, note that it could read $j \ge k$ and still generate the same results.

⟨ Nonworking code 167 ⟩ ≡

```
k = floor((GRID_SIZE − 1)/2);
if (j > k) {
  a = 0.5 * (1 − (j − k − 1)/(GRID_SIZE − k − 1));
  RR.slab.a = a;
}
else {
  a = (j − 1.0)/(GRID_SIZE − k − 1);
  RR.slab.a = 1.0 − a * a * a/2;
}
```

168. Here is heuristic that seems to work well

```
⟨ Generate next albedo using j 168 ⟩ ≡
  a = (double) j/(GRID_SIZE − 1.0);
  RR.slab.a = (1.0 − a ∗ a) ∗ (1.0 − a) + (1.0 − a) ∗ (1.0 − a) ∗ a;
```

This code is used in sections 166 and 170.

169. This is quite similar to *Fill_AB_Grid*, with the exception of the little shuffle I do at the beginning to figure out the optical thickness to use. The problem is that the optical thickness may not be known. If it is known then the only way that we could have gotten here is if the user dictated `FIND_AG` and specified b and only provided two measurements. Otherwise, the user must have made three measurements and the optical depth can be figured out from $m.m\_u$.

This routine could also be improved by not recalculating the anisotropy matrix for every point. But this would only end up being a minor performance enhancement if it were fixed.

```
⟨ Prototype for Fill_AG_Grid 169 ⟩ ≡
  void Fill_AG_Grid(struct measure_type m, struct invert_type r)
```

This code is used in sections 127 and 170.

170.

```
⟨ Definition for Fill_AG_Grid 170 ⟩ ≡
  ⟨ Prototype for Fill_AG_Grid 169 ⟩
  {
    int i, j;
    double max_a = −10;
    double min_a = 10;
    if (Debug(DEBUG_GRID)) fprintf(stderr, "GRID: Filling AG grid\n");
    if (The_Grid ≡ Λ) Allocate_Grid(r.search);
    ⟨ Zero GG 171 ⟩
    Set_Calc_State(m, r);
    GG_b = r.slab.b;
    for (i = 0; i < GRID_SIZE; i++) {
      RR.slab.g = MAX_ABS_G ∗ (2.0 ∗ i/(GRID_SIZE − 1.0) − 1.0);
      for (j = 0; j < GRID_SIZE; j++) {
        double a;
        ⟨ Generate next albedo using j 168 ⟩
        fill_grid_entry(i, j);
        if (a < 0) RR.slab.a = 0;
        if (a < min_a) min_a = a;
        if (a > max_a) max_a = a;
      }
    }
    if (Debug(DEBUG_GRID)) {
      fprintf(stderr, "GRID: a         = %9.7f to %9.7f \n", min_a, max_a);
      fprintf(stderr, "GRID: b         = %9.5f \n", r.slab.b);
      fprintf(stderr, "GRID: g   range = %9.6f to %9.6f \n", −MAX_ABS_G, MAX_ABS_G);
    }
    The_Grid_Initialized = TRUE;
    The_Grid_Search = FIND_AG;
  }
```

This code is used in section 127.

171.

```
⟨ Zero GG 171 ⟩ ≡
  GG_a = 0.0;
  GG_b = 0.0;
  GG_g = 0.0;
  GG_bs = 0.0;
  GG_ba = 0.0;
```

This code is used in sections 166, 170, 173, 175, and 177.

172. This is quite similar to *Fill_AB_Grid*, with the exception of the that the albedo is held fixed while b and g are varied.

This routine could also be improved by not recalculating the anisotropy matrix for every point. But this would only end up being a minor performance enhancement if it were fixed.

```
⟨ Prototype for Fill_BG_Grid 172 ⟩ ≡
  void Fill_BG_Grid(struct measure_type m, struct invert_type r)
```

This code is used in sections 128 and 173.

173. ⟨ Definition for *Fill_BG_Grid* 173 ⟩ ≡

```
⟨ Prototype for Fill_BG_Grid 172 ⟩
{
  int i, j;
  double min_log_b = −8;      /* exp(-10) is smallest thickness */
  double max_log_b = +10;     /* exp(+8) is greatest thickness */
  if (The_Grid ≡ Λ) Allocate_Grid(r.search);
  ⟨ Zero GG 171 ⟩
  if (Debug(DEBUG_GRID)) fprintf(stderr, "GRID: Filling BG grid\n");
  Set_Calc_State(m, r);
  RR.slab.a = RR.default_a;
  GG_a = RR.slab.a;
  for (i = 0; i < GRID_SIZE; i++) {
    double x = (double) i/(GRID_SIZE − 1.0);
    RR.slab.b = exp(min_log_b + (max_log_b − min_log_b) * x);
    for (j = 0; j < GRID_SIZE; j++) {
      RR.slab.g = MAX_ABS_G * (2.0 * j/(GRID_SIZE − 1.0) − 1.0);
      fill_grid_entry(i, j);
    }
  }
  if (Debug(DEBUG_GRID)) {
    fprintf(stderr, "GRID: a        = %9.7f \n", RR.default_a);
    fprintf(stderr, "GRID: b   range = %9.5f to %9.3f \n", exp(min_log_b), exp(max_log_b));
    fprintf(stderr, "GRID: g   range = %9.6f to %9.6f \n", −MAX_ABS_G, MAX_ABS_G);
  }
  The_Grid_Initialized = TRUE;
  The_Grid_Search = FIND_BG;
}
```

This code is used in section 127.

174. This is quite similar to *Fill_BG_Grid*, with the exception of the that the $b_s = \mu_s d$ is held fixed. Here b and g are varied on the usual grid, but the albedo is forced to take whatever value is needed to ensure that the scattering remains fixed.

```
⟨ Prototype for Fill_BaG_Grid 174 ⟩ ≡
  void Fill_BaG_Grid(struct measure_type m, struct invert_type r)
```

This code is used in sections 128 and 175.

175.

```
⟨ Definition for Fill_BaG_Grid 175 ⟩ ≡
  ⟨ Prototype for Fill_BaG_Grid 174 ⟩
  {
    int i, j;
    double max_a = −10;
    double min_a = 10;
    double bs = r.default_bs;
    double log_bs = log(bs);
    double min_log_b = −8;      /* exp(-10) is smallest thickness */
    double max_log_b = +10;     /* exp(+8) is greatest thickness */
    if (min_log_b < log_bs) min_log_b = log_bs;
    if (The_Grid ≡ Λ) Allocate_Grid(r.search);
    ⟨ Zero GG 171 ⟩
    if (Debug(DEBUG_GRID)) {
      fprintf(stderr, "GRID: Filling BaG grid\n");
      fprintf(stderr, "GRID:       bs = %9.5f\n", bs);
      fprintf(stderr, "GRID: ba range = %9.6f to %9.3f \n", exp(min_log_b) − bs, exp(max_log_b) − bs);
    }
    Set_Calc_State(m, r);
    GG_bs = bs;
    for (i = 0; i < GRID_SIZE; i++) {
      double x = (double) i/(GRID_SIZE − 1.0);
      RR.slab.b = exp(min_log_b + (max_log_b − min_log_b) * x);
      if (RR.slab.b > 0) RR.slab.a = bs/RR.slab.b;
      else RR.slab.a = 0;
      if (RR.slab.a < 0) RR.slab.a = 0;
      if (RR.slab.a < min_a) min_a = RR.slab.a;
      if (RR.slab.a > max_a) max_a = RR.slab.a;
      for (j = 0; j < GRID_SIZE; j++) {
        RR.slab.g = MAX_ABS_G * (2.0 * j/(GRID_SIZE − 1.0) − 1.0);
        fill_grid_entry(i, j);
      }
    }
    if (Debug(DEBUG_GRID)) {
      fprintf(stderr, "GRID: a        = %9.7f to %9.7f \n", min_a, max_a);
      fprintf(stderr, "GRID: b   range = %9.5f to %9.3f \n", exp(min_log_b), exp(max_log_b));
      fprintf(stderr, "GRID: g   range = %9.6f to %9.6f \n", −MAX_ABS_G, MAX_ABS_G);
    }
    The_Grid_Initialized = TRUE;
    The_Grid_Search = FIND_BaG;
  }
```

This code is used in section 127.

176. Very similiar to the above routine, but holding $b_a = \mu_a d$ fixed. Here b and g are varied on the usual grid, but the albedo is forced to take whatever value is needed to ensure that the absorption remains fixed.

```
⟨ Prototype for Fill_BsG_Grid 176 ⟩ ≡
  void Fill_BsG_Grid(struct measure_type m, struct invert_type r)
```

This code is used in sections 128 and 177.

177.

```
⟨ Definition for Fill_BsG_Grid 177 ⟩ ≡
  ⟨ Prototype for Fill_BsG_Grid 176 ⟩
  {
    int i, j;
    double max_a = −10;
    double min_a = 10;
    double ba = r.default_ba;
    double log_ba = log(ba);
    double min_log_b = −8;      /* exp(-10) is smallest thickness */
    double max_log_b = +10;     /* exp(+8) is greatest thickness */
    if (min_log_b < log_ba) min_log_b = log_ba;
    if (The_Grid ≡ Λ) Allocate_Grid(r.search);
    ⟨ Zero GG 171 ⟩
    if (Debug(DEBUG_GRID)) {
      fprintf(stderr, "GRID: Filling BsG grid\n");
      fprintf(stderr, "GRID:       ba = %9.5f\n", ba);
      fprintf(stderr, "GRID: bs range = %9.6f to %9.3f \n", exp(min_log_b) − ba, exp(max_log_b) − ba);
    }
    Set_Calc_State(m, r);
    GG_ba = RR.default_ba;
    for (i = 0; i < GRID_SIZE; i++) {
      double x = (double) i/(GRID_SIZE − 1.0);
      RR.slab.b = exp(min_log_b + (max_log_b − min_log_b) * x);
      if (RR.slab.b > 0) RR.slab.a = 1 − RR.default_ba/RR.slab.b;
      else RR.slab.a = 0;
      if (RR.slab.a < 0) RR.slab.a = 0;
      if (RR.slab.a < min_a) min_a = RR.slab.a;
      if (RR.slab.a > max_a) max_a = RR.slab.a;
      for (j = 0; j < GRID_SIZE; j++) {
        RR.slab.g = MAX_ABS_G * (2.0 * j/(GRID_SIZE − 1.0) − 1.0);
        fill_grid_entry(i, j);
      }
    }
    if (Debug(DEBUG_GRID)) {
      fprintf(stderr, "GRID:  a   range = %9.7f to %9.7f \n", min_a, max_a);
      fprintf(stderr, "GRID:  b   range = %9.5f to %9.3f \n", exp(min_log_b), exp(max_log_b));
      fprintf(stderr, "GRID:  g   range = %9.6f to %9.6f \n", −MAX_ABS_G, MAX_ABS_G);
    }
    The_Grid_Initialized = TRUE;
    The_Grid_Search = FIND_BsG;
  }
```

This code is used in section 127.

178. ⟨ Prototype for *Fill_Grid* 178 ⟩ ≡

```
void Fill_Grid(struct measure_type m, struct invert_type r, int force_new)
```

This code is used in sections 128 and 179.

179. ⟨ Definition for *Fill_Grid* 179 ⟩ ≡

```
⟨ Prototype for Fill_Grid 178 ⟩
{
  if (force_new ∨ ¬Same_Calc_State(m, r)) {
    switch (r.search) {
    case FIND_AB: Fill_AB_Grid(m, r);
      break;
    case FIND_AG: Fill_AG_Grid(m, r);
      break;
    case FIND_BG: Fill_BG_Grid(m, r);
      break;
    case FIND_BaG: Fill_BaG_Grid(m, r);
      break;
    case FIND_BsG: Fill_BsG_Grid(m, r);
      break;
    default: AD_error("Attempt to fill grid for unknown search case.");
    }
  }
  Get_Calc_State(&MGRID, &RGRID);
}
```

This code is used in section 127.

180. Calculating R and T.

Calculate_Distance returns the distance between the measured values in `MM` and the calculated values for the current guess at the optical properties. It assumes that the everything in the local variables `MM` and `RR` have been set appropriately.

⟨ Prototype for *Calculate_Distance* 180 ⟩ ≡

```
void Calculate_Distance(double *M_R, double *M_T, double *deviation)
```

This code is used in sections 128 and 181.

181. ⟨ Definition for *Calculate_Distance* 181 ⟩ ≡

```
⟨ Prototype for Calculate_Distance 180 ⟩
{
  double Rc, Tc, ur1, ut1, uru, utu;
  if (RR.slab.b ≤ 1 · 10^−6) RR.slab.b = 1 · 10^−6;
  RT_Flip(MM.flip_sample, RR.method.quad_pts, &RR.slab, &ur1, &ut1, &uru, &utu);
  Sp_mu_RT_Flip(MM.flip_sample, RR.slab.n_top_slide, RR.slab.n_slab, RR.slab.n_bottom_slide,
      RR.slab.b_top_slide, RR.slab.b, RR.slab.b_bottom_slide, RR.slab.cos_angle, &Rc, &Tc);
  if ((¬CALCULATING_GRID ∧ Debug(DEBUG_ITERATIONS)) ∨ (CALCULATING_GRID ∧
      Debug(DEBUG_GRID_CALC))) fprintf(stderr, "␣␣␣␣␣␣␣␣");
  Calculate_Distance_With_Corrections(ur1, ut1, Rc, Tc, uru, utu, M_R, M_T, deviation);
}
```

This code is used in section 127.

182. ⟨ Prototype for *Calculate_Grid_Distance* 182 ⟩ ≡

```
double Calculate_Grid_Distance(int i, int j)
```

This code is used in sections 128 and 183.

183. ⟨ Definition for *Calculate_Grid_Distance* 183 ⟩ ≡

```
⟨ Prototype for Calculate_Grid_Distance 182 ⟩
{
  double ur1, ut1, uru, utu, Rc, Tc, b, dev, LR, LT;
  if (Debug(DEBUG_GRID_CALC) ∧ i ≡ 0 ∧ j ≡ 0) {
    fprintf(stderr, "+␣␣␣i␣␣␣j␣");
    fprintf(stderr, "␣␣␣␣␣␣a␣␣␣␣␣␣␣␣␣b␣␣␣␣␣␣␣␣␣␣g␣␣␣␣␣|");
    fprintf(stderr, "␣␣␣␣␣M_R␣␣␣␣␣␣␣␣grid␣␣␣|");
    fprintf(stderr, "␣␣␣␣␣M_T␣␣␣␣␣␣␣␣grid␣␣␣|␣␣distance\n");
  }
  if (Debug(DEBUG_GRID_CALC)) fprintf(stderr, "g␣%3d␣%3d␣", i, j);
  b = The_Grid[GRID_SIZE * i + j][B_COLUMN];
  ur1 = The_Grid[GRID_SIZE * i + j][UR1_COLUMN];
  ut1 = The_Grid[GRID_SIZE * i + j][UT1_COLUMN];
  uru = The_Grid[GRID_SIZE * i + j][URU_COLUMN];
  utu = The_Grid[GRID_SIZE * i + j][UTU_COLUMN];
  RR.slab.a = The_Grid[GRID_SIZE * i + j][A_COLUMN];
  RR.slab.b = The_Grid[GRID_SIZE * i + j][B_COLUMN];
  RR.slab.g = The_Grid[GRID_SIZE * i + j][G_COLUMN];
  Sp_mu_RT_Flip(MM.flip_sample, RR.slab.n_top_slide, RR.slab.n_slab, RR.slab.n_bottom_slide,
      RR.slab.b_top_slide, b, RR.slab.b_bottom_slide, RR.slab.cos_angle, &Rc, &Tc);
  CALCULATING_GRID = 1;
  Calculate_Distance_With_Corrections(ur1, ut1, Rc, Tc, uru, utu, &LR, &LT, &dev);
  CALCULATING_GRID = 0;
  return dev;
}
```

This code is used in section 127.

184. This is the routine that actually finds the distance. I have factored this part out so that it can be used in the *Near_Grid_Points* routine.

Rc and *Tc* refer to the unscattered (collimated) reflection and transmission.

The only tricky part is to remember that the we are trying to match the measured values. The measured values are affected by sphere parameters and light loss. Since the values UR1 and UT1 are for an infinite slab sample with no light loss, the light loss out the edges must be subtracted. It is these values that are used with the sphere formulas to convert the modified UR1 and UT1 to values for ∗M_R and ∗M_T.

```
⟨ Prototype for Calculate_Distance_With_Corrections 184 ⟩ ≡
  void Calculate_Distance_With_Corrections(double UR1, double UT1, double Rc, double Tc, double
      URU, double UTU, double *M_R, double *M_T, double *dev)
```

This code is used in sections 128 and 185.

185. ⟨ Definition for *Calculate_Distance_With_Corrections* 185 ⟩ ≡

```
⟨ Prototype for Calculate_Distance_With_Corrections 184 ⟩
{
  ⟨ Determine calculated light to be used 186 ⟩
  switch (MM.num_spheres) {
  case 0: ⟨ Calc M_R and M_T for no spheres 188 ⟩
    break;
  case 1:
    if (MM.method ≡ COMPARISON) {
      ⟨ Calc M_R and M_T for dual beam sphere 192 ⟩
    }
    else {
      ⟨ Calc M_R and M_T for single beam sphere 189 ⟩
    }
    break;
  case 2: ⟨ Calc M_R and M_T for two spheres 193 ⟩
    break;
  default: fprintf(stderr, "Bad␣number␣of␣spheres␣=␣%d\n", MM.num_spheres);
    exit(EXIT_FAILURE);
  }
  ⟨ Calculate the deviation 194 ⟩
  ⟨ Print diagnostics 197 ⟩
}
```

This code is used in section 127.

186. The calculated values for `M_R` and `M_T` must be adapted to match the measurements. The diffuse light `URU` and `UTU` are used to determine the gain from the sphere. They're only modified by the lost light calculation. All values can become slightly negative because the Monte Carlo is noisy. Negative values are set to zero.

⟨ Determine calculated light to be used 186 ⟩ ≡

```
double UR1_calc, UT1_calc, URU_calc, UTU_calc;
URU_calc = URU − MM.uru_lost;
if (URU_calc < 0) URU_calc = 0;
UTU_calc = UTU − MM.utu_lost;
if (UTU_calc < 0) UTU_calc = 0;
```

See also section 187.

This code is used in section 185.

187. The measurements for `UR1` and `UT1` need to be modified to accommodate light that misses the detector either because it is intentionally not collected (unscattered light) or it leaks out (lost light). Since none of the light that leaks out could be unscattered light, these two are independent of one another.

The code allows for some of the light to hit the sphere wall first; these effects are accounted for in the sphere code below.

⟨ Determine calculated light to be used 186 ⟩ +≡

```
UR1_calc = UR1 − (1.0 − MM.fraction_of_rc_in_mr) ∗ Rc − MM.ur1_lost;
if (UR1_calc < 0) UR1_calc = 0;
UT1_calc = UT1 − (1.0 − MM.fraction_of_tc_in_mt) ∗ Tc − MM.ut1_lost;
if (UT1_calc < 0) UT1_calc = 0;
```

188. When no spheres are used, then no corrections can or need to be made. The lost light estimates in MM.*ur1_lost* and MM.*ut1_lost* should be zero and so the values for *UR1_calc* and *UT1_calc* properly account for the presence or absence of unscattered light.

```
⟨ Calc M_R and M_T for no spheres 188 ⟩ ≡
  {
    *M_R = UR1_calc;
    *M_T = UT1_calc;
  }
```

This code is used in section 185.

189. In a reflection experiment, some fraction f of the incident light P_i might hit the wall first. Thus the incident power on the sample is $(1-f)P_i$ and the incident power on the sphere wall will be fP_i. The diffuse reflection entering the sphere depends on the presence of a baffle.

If a baffle is present then

$$P_d = [a_d(1-a_e)r_w P_i] \cdot (r_s^{\text{direct}} * (1-f) + r_w f) \cdot G(r_s)$$

and when there is no baffle

$$P_d = [a_d P_i] \cdot (r_s^{\text{direct}} * (1-f) + r_w f) \cdot G(r_s)$$

Since the quantities in square brackets are identical for $R(r_s^{\text{direct}}, r_s)$, $R(0,0)$, and $R(r_{\text{std}}, r_{\text{std}})$. Consequently they cancel out when calculating the normalized reflection measurement

$$M_R = r_{\text{std}} \cdot \frac{R(r_s^{\text{direct}}, r_s) - R(0,0)}{R(r_{\text{std}}, r_{\text{std}}) - R(0,0)}$$

This leads to the following code for M_R

```
⟨ Calc M_R and M_T for single beam sphere 189 ⟩ ≡
  double P_std, P, P_0, G, G_0, G_std;
  int tmp;
  G_0 = Gain(REFLECTION_SPHERE, MM, 0.0);
  G = Gain(REFLECTION_SPHERE, MM, URU_calc);
  G_std = Gain(REFLECTION_SPHERE, MM, MM.rstd_r);
  P = G * (UR1_calc * (1 - MM.f_r) + MM.f_r * MM.rw_r);
  P_std = G_std * (MM.rstd_r * (1 - MM.f_r) + MM.f_r * MM.rw_r);
  P_0 = G_0 * (MM.f_r * MM.rw_r);
  *M_R = MM.rstd_r * (P - P_0)/(P_std - P_0);
  if (Debug(DEBUG_SPHERE_GAIN) ∧ ¬CALCULATING_GRID) {
    fprintf(stderr, "SPHERE: REFLECTION\n");
    fprintf(stderr, "SPHERE:       G0 = %7.3f       G   = %7.3f G_std = %7.3f\n", G_0, G, G_std);
    fprintf(stderr, "SPHERE:       P0 = %7.3f       P   = %7.3f P_std = %7.3f\n", P_0, P, P_std);
    fprintf(stderr, "SPHERE:     UR1 = %7.3f UR1calc = %7.3f   M_R = %7.3f\n", UR1, UR1_calc,
        *M_R);
  }
```

See also section 191.

This code is used in section 185.

190. In a transmission experiment, the calculations are simpler and harder. First, the value of $T(0,0) = 0$ because computationally, there is no dark noise in the detector nor any possible light leakage from the outside into the sphere. This simplifies

$$M_T = r_0 \cdot \frac{T(t_s^{\text{direct}}, r_s) - T(0,0)}{T(t_{\text{std}}, r_{\text{std}}) - T(0,0)}$$

to

$$M_T = r_0 \cdot \frac{T(t_s^{\text{direct}}, r_s)}{T(t_{\text{std}}, r_{\text{std}})}$$

where r_0 might be r_{std} or r_w for the transmission sphere.

We do not need to worry about some fraction of the incident light P_i hitting the sphere wall before interacting with the sample.

Finally, if the transmission sphere has a baffle present for the sample measurement, then it is no longer in the right place and diffuse light entering the sphere is just $[a_d P_i] r_0$

When a baffle is present then the light falling on the detector in a transmission experiment is

$$P_d = T(t_s^{\text{direct}}, r_s) = [a_d P_i](1 - a_e) r_w t_s^{\text{direct}} G(r_s)$$

and with no baffle present

$$P_d = T(t_s^{\text{direct}}, r_s) = [a_d P_i] t_s^{\text{direct}} G(r_s)$$

191. The normalization $T(t_{\rm std}, r_{\rm std})$ can be measured in two ways.

When transmission measurements are made, typically the empty port (the one that let the light into the sphere for the reflection measurement) is filled with a white port cover whose reflectance matches the rest of the sphere. In this case, the natural way to make the standard transmission measurement is to shine the beam through the empty sample port onto the back side of the sphere. If the baffle was properly placed for the transmission experiment (between the sample port and the detector) then the calibration transmission measurement is now made in a sphere without a baffle. In addition, the beam is diffused only after bouncing off the sphere wall. Therefore the power falling on the detector is

$$P_{\rm std} = T(1.0, r_w) = [a_d P_i] r_w G(0)$$

An alternate method is when there is an empty port in the sphere (perhaps to allow the unscattered light to leave). In any case, the calibration measurement is done by removing the sample and placing the calibration standare in what used to be the empty port. In this case, the roles of the sample and empty ports have switched. Consequently, the areas of the sample and empty ports must be swapped before the gain is calculated.

$$P_{\rm std} = T(1.0, r_{\rm std}) = [a_d P_i] r_{\rm std} G(r_{\rm std})$$

Note that r_w or $r_{\rm std}$ in $P_{\rm std}$ term cancel with r_0 when calculating M_T. Further, the quantities $a_d P_i$ also cancel.

```
⟨ Calc M_R and M_T for single beam sphere 189 ⟩ +≡
  G = Gain(TRANSMISSION_SPHERE, MM, URU_calc);
  P = UT1_calc * G;
  if (MM.baffle_t) P *= (1 - MM.ae_t) * MM.rw_t;
  tmp = MM.baffle_t;
  MM.baffle_t = FALSE;
  if (MM.ae_t ≡ 0) {
    G_std = Gain(TRANSMISSION_SPHERE, MM, 0);
  }
  else {
    SWAP(MM.ae_t, MM.as_t);
    G_std = Gain(TRANSMISSION_SPHERE, MM, MM.rstd_t);
    SWAP(MM.ae_t, MM.as_t);
  }
  P_std = G_std;
  MM.baffle_t = tmp;
  *M_T = P/P_std;
  if (Debug(DEBUG_SPHERE_GAIN) ∧ ¬CALCULATING_GRID) {
    fprintf(stderr, "SPHERE: TRANSMISSION\n");
    fprintf(stderr, "SPHERE:                        G  =  %7.3f  G_std  =  %7.3f\n", G, G_std);
    fprintf(stderr, "SPHERE:                        P  =  %7.3f  P_std  =  %7.3f\n", P, P_std);
    fprintf(stderr, "SPHERE:     UT1  =  %7.3f  UT1calc  =  %7.3f    M_T  =  %7.3f\n", UT1, UT1_calc,
        *M_T);
    fprintf(stderr, "\n");
  }
```

192. The dual beam case is different because the sphere efficiency is equivalent for measurement of light hitting the sample first or hitting the reference standard first. The dual beam measurement should report the ratio of these two reflectance measurements, thereby eliminating the need to calculate the sphere gain.

The only correction that needs to be made have already been made, namely subtracting the `UR1` or `UT1` lost light and also accounting for whether or not unscattered light is collected.

Originally, I had a bunch of calculations trying to account for light that hits the sphere wall first. Since the exact details of how a dual beam spectrometer reports its measurements is unknown, it makes no sense to try and account for it.

⟨ Calc `M_R` and `M_T` for dual beam sphere 192 ⟩ ≡

```
{
  *M_R = UR1_calc;
  *M_T = UT1_calc;
}
```

This code is used in section 185.

193. When two integrating spheres are present then the double integrating sphere formulas are slightly more complicated.

The normalized sphere measurements for two spheres are

$$M_R = \frac{R(r_s^{\text{direct}}, r_s, t_s^{\text{direct}}, t_s) - R(0,0,0,0)}{R(r_{\text{std}}, r_{\text{std}}, 0, 0) - R(0,0,0,0)}$$

and

$$M_T = \frac{T(r_s^{\text{direct}}, r_s, t_s^{\text{direct}}, t_s) - T(0,0,0,0)}{T(0,0,1,1) - T(0,0,0,0)}$$

Note that `R_0` and `T_0` will be zero unless one has explicitly set the fraction $m.f\_r$ or $m.f\_t$ to be non-zero.

⟨ Calc `M_R` and `M_T` for two spheres 193 ⟩ ≡

```
{
  double R_0, T_0;
  R_0 = Two_Sphere_R(MM, 0, 0, 0, 0);
  T_0 = Two_Sphere_T(MM, 0, 0, 0, 0);
  *M_R = MM.rstd_r * (Two_Sphere_R(MM, UR1_calc, URU_calc, UT1_calc,
      UTU_calc) - R_0)/(Two_Sphere_R(MM, MM.rstd_r, MM.rstd_r, 0, 0) - R_0);
  *M_T = (Two_Sphere_T(MM, UR1_calc, URU_calc, UT1_calc, UTU_calc) - T_0)/(Two_Sphere_T(MM, 0, 0,
      1, 1) - T_0);
}
```

This code is used in section 185.

194. There are at least three things that need to be considered here. First, the number of measurements. Second, is the metric is relative or absolute. And third, is the albedo fixed at zero which means that the transmission measurement should be used instead of the reflection measurement.

⟨ Calculate the deviation 194 ⟩ ≡

```
if (RR.search ≡ FIND_A ∨ RR.search ≡ FIND_G ∨ RR.search ≡ FIND_B ∨ RR.search ≡ FIND_Bs ∨ RR.search ≡
      FIND_Ba) {
  ⟨ One parameter deviation 195 ⟩
}
else {
  ⟨ Two parameter deviation 196 ⟩
}
```

This code is used in section 185.

195. This part was slightly tricky. The crux of the problem was to decide if the transmission or the reflection was trustworthy. After looking a bunches of measurements, I decided that the transmission measurement was almost always more reliable. So when there is just a single measurement known, then use the total transmission if it exists.

```
⟨ One parameter deviation 195 ⟩ ≡
  if (MM.m_t > 0) {
    if (RR.metric ≡ RELATIVE) *dev = fabs(MM.m_t − *M_T)/(MM.m_t + ABIT);
    else *dev = fabs(MM.m_t − *M_T);
  }
  else {
    if (RR.metric ≡ RELATIVE) *dev = fabs(MM.m_r − *M_R)/(MM.m_r + ABIT);
    else *dev = fabs(MM.m_r − *M_R);
  }
```

This code is used in section 194.

196. This stuff happens when we are doing two parameter searches. In these cases there should be information in both R and T. The distance should be calculated using the deviation from both. The albedo stuff might be able to be take out. We'll see.

```
⟨ Two parameter deviation 196 ⟩ ≡
  if (RR.metric ≡ RELATIVE) {
    if (MM.m_t > ABIT) *dev = T_TRUST_FACTOR * fabs(MM.m_t − *M_T)/(UTU_calc + ABIT);
    if (RR.default_a ≠ 0) {
      *dev += fabs(MM.m_r − *M_R)/(URU_calc + ABIT);
    }
  }
  else {
    *dev = T_TRUST_FACTOR * fabs(MM.m_t − *M_T);
    if (RR.default_a ≠ 0) *dev += fabs(MM.m_r − *M_R);
  }
```

This code is used in section 194.

197. This is here so that I can figure out why the program is not converging. This is a little convoluted so that the global constants at the top of this file interact properly.

```
⟨ Print diagnostics 197 ⟩ ≡
  if ((Debug(DEBUG_ITERATIONS) ∧ ¬CALCULATING_GRID) ∨
        (Debug(DEBUG_GRID_CALC) ∧ CALCULATING_GRID)) {
    fprintf(stderr, "%10.5f␣%10.4f␣%10.5f␣|", RR.slab.a, RR.slab.b, RR.slab.g);
    fprintf(stderr, "␣%10.5f␣%10.5f␣|", MM.m_r, *M_R);
    fprintf(stderr, "␣%10.5f␣%10.5f␣|", MM.m_t, *M_T);
    fprintf(stderr, "%10.3f\n", *dev);
  }
```

This code is used in section 185.

198. ⟨ Prototype for *Find_AG_fn* 198 ⟩ ≡

```
double Find_AG_fn(double x[])
```

This code is used in sections 128 and 199.

199. ⟨ Definition for *Find_AG_fn* 199 ⟩ ≡
```
⟨ Prototype for Find_AG_fn 198 ⟩
{
  double m_r, m_t, deviation;
  RR.slab.a = acalc2a(x[1]);
  RR.slab.g = gcalc2g(x[2]);
  Calculate_Distance(&m_r, &m_t, &deviation);
  return deviation;
}
```
This code is used in section 127.

200. ⟨ Prototype for *Find_AB_fn* 200 ⟩ ≡
```
double Find_AB_fn(double x[])
```
This code is used in sections 128 and 201.

201. ⟨ Definition for *Find_AB_fn* 201 ⟩ ≡
```
⟨ Prototype for Find_AB_fn 200 ⟩
{
  double m_r, m_t, deviation;
  RR.slab.a = acalc2a(x[1]);
  RR.slab.b = bcalc2b(x[2]);
  Calculate_Distance(&m_r, &m_t, &deviation);
  return deviation;
}
```
This code is used in section 127.

202. ⟨ Prototype for *Find_Ba_fn* 202 ⟩ ≡
```
double Find_Ba_fn(double x)
```
This code is used in sections 128 and 203.

203. This is tricky only because the value in RR.*slab.b* is used to hold the value of bs or $d \cdot \mu_s$. It must be switched to the correct value for the optical thickness and then switched back at the end of the routine.

⟨ Definition for *Find_Ba_fn* 203 ⟩ ≡
```
⟨ Prototype for Find_Ba_fn 202 ⟩
{
  double m_r, m_t, deviation, ba, bs;
  bs = RR.slab.b;
  ba = bcalc2b(x);
  RR.slab.b = ba + bs;      /* unswindle */
  RR.slab.a = bs/(ba + bs);
  Calculate_Distance(&m_r, &m_t, &deviation);
  RR.slab.b = bs;      /* swindle */
  return deviation;
}
```
This code is used in section 127.

204. See the comments for the *Find_Ba_fn* routine above. Play the same trick but use ba.

⟨ Prototype for *Find_Bs_fn* 204 ⟩ ≡
```
double Find_Bs_fn(double x)
```
This code is used in sections 128 and 205.

205. ⟨ Definition for *Find_Bs_fn* 205 ⟩ ≡
```
⟨ Prototype for Find_Bs_fn 204 ⟩
{
  double m_r, m_t, deviation, ba, bs;
  ba = RR.slab.b;      /* unswindle */
  bs = bcalc2b(x);
  RR.slab.b = ba + bs;
  RR.slab.a = bs/(ba + bs);
  Calculate_Distance(&m_r, &m_t, &deviation);
  RR.slab.b = ba;      /* swindle */
  return deviation;
}
```
This code is used in section 127.

206. ⟨ Prototype for *Find_A_fn* 206 ⟩ ≡
```
double Find_A_fn(double x)
```
This code is used in sections 128 and 207.

207. ⟨ Definition for *Find_A_fn* 207 ⟩ ≡
```
⟨ Prototype for Find_A_fn 206 ⟩
{
  double m_r, m_t, deviation;
  RR.slab.a = acalc2a(x);
  Calculate_Distance(&m_r, &m_t, &deviation);
  return deviation;
}
```
This code is used in section 127.

208. ⟨ Prototype for *Find_B_fn* 208 ⟩ ≡
```
double Find_B_fn(double x)
```
This code is used in sections 128 and 209.

209. ⟨ Definition for *Find_B_fn* 209 ⟩ ≡
```
⟨ Prototype for Find_B_fn 208 ⟩
{
  double m_r, m_t, deviation;
  RR.slab.b = bcalc2b(x);
  Calculate_Distance(&m_r, &m_t, &deviation);
  return deviation;
}
```
This code is used in section 127.

210. ⟨ Prototype for *Find_G_fn* 210 ⟩ ≡
```
double Find_G_fn(double x)
```
This code is used in sections 128 and 211.

211. ⟨ Definition for *Find_G_fn* 211 ⟩ ≡
```
⟨ Prototype for Find_G_fn 210 ⟩
{
  double m_r, m_t, deviation;
  RR.slab.g = gcalc2g(x);
  Calculate_Distance(&m_r, &m_t, &deviation);
  return deviation;
}
```
This code is used in section 127.

212. ⟨ Prototype for *Find_BG_fn* 212 ⟩ ≡
```
double Find_BG_fn(double x[])
```
This code is used in sections 128 and 213.

213. ⟨ Definition for *Find_BG_fn* 213 ⟩ ≡
```
⟨ Prototype for Find_BG_fn 212 ⟩
{
  double m_r, m_t, deviation;
  RR.slab.b = bcalc2b(x[1]);
  RR.slab.g = gcalc2g(x[2]);
  RR.slab.a = RR.default_a;
  Calculate_Distance(&m_r, &m_t, &deviation);
  return deviation;
}
```
This code is used in section 127.

214. For this function the first term $x[1]$ will contain the value of $\mu_s d$, the second term will contain the anisotropy. Of course the first term is in the bizarre calculation space and needs to be translated back into normal terms before use. We just at the scattering back on and voilá we have a useable value for the optical depth.

⟨ Prototype for *Find_BaG_fn* 214 ⟩ ≡
```
double Find_BaG_fn(double x[])
```
This code is used in sections 128 and 215.

215. ⟨ Definition for *Find_BaG_fn* 215 ⟩ ≡
```
⟨ Prototype for Find_BaG_fn 214 ⟩
{
  double m_r, m_t, deviation;
  RR.slab.b = bcalc2b(x[1]) + RR.default_bs;
  if (RR.slab.b ≤ 0) RR.slab.a = 0;
  else RR.slab.a = RR.default_bs/RR.slab.b;
  RR.slab.g = gcalc2g(x[2]);
  Calculate_Distance(&m_r, &m_t, &deviation);
  return deviation;
}
```
This code is used in section 127.

216. ⟨ Prototype for *Find_BsG_fn* 216 ⟩ ≡
```
double Find_BsG_fn(double x[])
```
This code is used in sections 128 and 217.

217. ⟨ Definition for *Find_BsG_fn* 217 ⟩ ≡

```
⟨ Prototype for Find_BsG_fn 216 ⟩
{
  double m_r, m_t, deviation;
  RR.slab.b = bcalc2b(x[1]) + RR.default_ba;
  if (RR.slab.b ≤ 0) RR.slab.a = 0;
  else RR.slab.a = 1.0 − RR.default_ba/RR.slab.b;
  RR.slab.g = gcalc2g(x[2]);
  Calculate_Distance(&m_r, &m_t, &deviation);
  return deviation;
}
```

This code is used in section 127.

218. Routine to figure out if the light loss exceeds what is physically possible. Returns the descrepancy betweent the current values and the maximum possible values for the the measurements *m_r* and *m_t*.

⟨ Prototype for *maxloss* 218 ⟩ ≡

```
double maxloss(double f)
```

This code is used in sections 128 and 219.

219. ⟨ Definition for *maxloss* 219 ⟩ ≡

```
⟨ Prototype for maxloss 218 ⟩
{
  struct measure_type m_old;
  struct invert_type r_old;
  double m_r, m_t, deviation;
  Get_Calc_State(&m_old, &r_old);
  RR.slab.a = 1.0;
  MM.ur1_lost *= f;
  MM.ut1_lost *= f;
  Calculate_Distance(&m_r, &m_t, &deviation);
  Set_Calc_State(m_old, r_old);
  deviation = ((MM.m_r + MM.m_t) − (m_r + m_t));
  return deviation;
}
```

This code is used in section 127.

220. This checks the two light loss values *ur1_loss* and *ut1_loss* to see if they exceed what is physically possible. If they do, then these values are replaced by a couple that are the maximum possible for the current values in *m* and *r*.

⟨ Prototype for *Max_Light_Loss* 220 ⟩ ≡

```
void Max_Light_Loss(struct measure_type m, struct invert_type r, double *ur1_loss, double
    *ut1_loss)
```

This code is used in sections 128 and 221.

221. ⟨ Definition for *Max_Light_Loss* 221 ⟩ ≡

```
⟨ Prototype for Max_Light_Loss 220 ⟩
{
  struct measure_type m_old;
  struct invert_type r_old;
  *ur1_loss = m.ur1_lost;
  *ut1_loss = m.ut1_lost;
  if (Debug(DEBUG_LOST_LIGHT))
    fprintf(stderr, "\nlost␣before␣ur1=%7.5f,␣ut1=%7.5f\n", *ur1_loss, *ut1_loss);
  Get_Calc_State(&m_old, &r_old);
  Set_Calc_State(m, r);
  if (maxloss(1.0) * maxloss(0.0) < 0) {
    double frac;
    frac = zbrent(maxloss, 0.00, 1.0, 0.001);
    *ur1_loss = m.ur1_lost * frac;
    *ut1_loss = m.ut1_lost * frac;
  }
  Set_Calc_State(m_old, r_old);
  if (Debug(DEBUG_LOST_LIGHT))
    fprintf(stderr, "lost␣after␣␣ur1=%7.5f,␣ut1=%7.5f\n", *ur1_loss, *ut1_loss);
}
```

This code is used in section 127.

222. this is currently unused

```
⟨ Unused diffusion fragment 222 ⟩ ≡
  typedef struct {
    double f;
    double aprime;
    double bprime;
    double gprime;
    double boundary_method;
    double n_top;
    double n_bottom;
    double slide_top;
    double slide_bottom;
    double FO;
    double depth;
    double Exact_coll_flag;
  } slabtype;
  static void DE_RT(int nfluxes, AD_slab_type slab, double *UR1, double *UT1, double *URU, double
          *UTU)
  {
    slabtype s;
    double rp, tp, rs, ts;
    s.f = slab.g * slab.g;
    s.gprime = slab.g/(1 + slab.g);
    s.aprime = (1 - s.f) * slab.a/(1 - slab.a * s.f);
    s.bprime = (1 - slab.a * s.f) * slab.b;
    s.boundary_method = Egan;
    s.n_top = slab.n_slab;
    s.n_bottom = slab.n_slab;
    s.slide_top = slab.n_top_slide;
    s.slide_bottom = slab.n_bottom_slide;
    s.FO = 1/M_PI;
    s.depth = 0.0;
    s.Exact_coll_flag = FALSE;
    if (MM.illumination ≡ collimated) {
      compute_R_and_T(&s, 1.0, &rp, &rs, &tp, &ts);
      *UR1 = rp + rs;
      *UT1 = tp + ts;
      *URU = 0.0;
      *UTU = 0.0;
      return;
    }
    quad_Dif_Calc_R_and_T(&s, &rp, &rs, &tp, &ts);
    *URU = rp + rs;
    *UTU = tp + ts;
    *UR1 = 0.0;
    *UT1 = 0.0;
  }
```

223. IAD Find. March 1995. Incorporated the *quick_guess* algorithm for low albedos.

```
⟨ iad_find.c 223 ⟩ ≡
#include <math.h>
#include <stdio.h>
#include <stdlib.h>
#include "ad_globl.h"
#include "nr_util.h"
#include "nr_mnbrk.h"
#include "nr_brent.h"
#include "nr_amoeb.h"
#include "iad_type.h"
#include "iad_util.h"
#include "iad_calc.h"
#include "iad_find.h"
#define NUMBER_OF_GUESSES 10
  guess_type guess[NUMBER_OF_GUESSES];
  int compare_guesses(const void *p1, const void *p2)
  {
    guess_type *g1 = (guess_type *) p1;
    guess_type *g2 = (guess_type *) p2;
    if (g1→distance < g2→distance) return -1;
    else if (g1→distance ≡ g2→distance) return 0;
    else return 1;
  }
  ⟨ Definition for U_Find_Ba 237 ⟩
  ⟨ Definition for U_Find_Bs 235 ⟩
  ⟨ Definition for U_Find_A 239 ⟩
  ⟨ Definition for U_Find_B 243 ⟩
  ⟨ Definition for U_Find_G 241 ⟩
  ⟨ Definition for U_Find_AG 246 ⟩
  ⟨ Definition for U_Find_AB 226 ⟩
  ⟨ Definition for U_Find_BG 251 ⟩
  ⟨ Definition for U_Find_BaG 257 ⟩
  ⟨ Definition for U_Find_BsG 262 ⟩
```

224. All the information that needs to be written to the header file `iad_find.h`. This eliminates the need to maintain a set of header files as well.

```
⟨ iad_find.h 224 ⟩ ≡
  ⟨ Prototype for U_Find_Ba 236 ⟩;
  ⟨ Prototype for U_Find_Bs 234 ⟩;
  ⟨ Prototype for U_Find_A 238 ⟩;
  ⟨ Prototype for U_Find_B 242 ⟩;
  ⟨ Prototype for U_Find_G 240 ⟩;
  ⟨ Prototype for U_Find_AG 245 ⟩;
  ⟨ Prototype for U_Find_AB 225 ⟩;
  ⟨ Prototype for U_Find_BG 250 ⟩;
  ⟨ Prototype for U_Find_BaG 256 ⟩;
  ⟨ Prototype for U_Find_BsG 261 ⟩;
```

225. Fixed Anisotropy.
This is the most common case.

```
⟨ Prototype for U_Find_AB 225 ⟩ ≡
  void U_Find_AB(struct measure_type m, struct invert_type *r)
```

This code is used in sections 224 and 226.

226. ⟨ Definition for *U_Find_AB* 226 ⟩ ≡

```
⟨ Prototype for U_Find_AB 225 ⟩
{
  ⟨ Allocate local simplex variables 227 ⟩
  if (Debug(DEBUG_SEARCH)) {
    fprintf(stderr, "SEARCH: Using U_Find_AB()");
    fprintf(stderr, " (mu=%6.4f)", r->slab.cos_angle);
    if (r->default_g ≠ UNINITIALIZED) fprintf(stderr, "  default_g = %8.5f", r->default_g);
    fprintf(stderr, "\n");
  }
  r->slab.g = (r->default_g ≡ UNINITIALIZED) ? 0 : r->default_g;
  Set_Calc_State(m, *r);
  ⟨ Get the initial a, b, and g 228 ⟩
  ⟨ Initialize the nodes of the a and b simplex 229 ⟩
  ⟨ Evaluate the a and b simplex at the nodes 230 ⟩
  amoeba(p, y, 2, r->tolerance, Find_AB_fn, &r->AD_iterations);
  ⟨ Choose the best node of the a and b simplex 231 ⟩
  ⟨ Free simplex data structures 233 ⟩
  ⟨ Put final values in result 232 ⟩
}
```

This code is used in section 223.

227. To use the simplex algorithm, we need to vectors and a matrix.

```
⟨ Allocate local simplex variables 227 ⟩ ≡
  int i, i_best, j_best;
  double *x, *y, **p;
  x = dvector(1, 2);
  y = dvector(1, 3);
  p = dmatrix(1, 3, 1, 2);
```

This code is used in sections 226, 246, 251, 257, and 262.

228. Just get the optimal optical properties to start the search process.

I had to add the line that tests to make sure the albedo is greater than 0.2 because the grid just does not work so well in this case. The problem is that for low albedos there is really very little information about the anisotropy available. This change was also made in the analagous code for a and b.

```
⟨ Get the initial a, b, and g 228 ⟩ ≡
  {     /* double a3,b3,g3; */
    size_t count = NUMBER_OF_GUESSES;     /* distance to last result */
    abg_distance(r->slab.a, r->slab.b, r->slab.g, &(guess[0]));
    if (¬Valid_Grid(m, *r)) Fill_Grid(m, *r, 1);     /* distance to nearest grid point */
    Near_Grid_Points(m.m_r, m.m_t, r->search, &i_best, &j_best);
    Grid_ABG(i_best, j_best, &(guess[1]));
    Grid_ABG(i_best + 1, j_best, &(guess[2]));
    Grid_ABG(i_best − 1, j_best, &(guess[3]));
    Grid_ABG(i_best, j_best + 1, &(guess[4]));
    Grid_ABG(i_best, j_best − 1, &(guess[5]));
    Grid_ABG(i_best + 1, j_best + 1, &(guess[6]));
    Grid_ABG(i_best − 1, j_best − 1, &(guess[7]));
    Grid_ABG(i_best + 1, j_best − 1, &(guess[8]));
    Grid_ABG(i_best − 1, j_best + 1, &(guess[9]));
    qsort((void *) guess, count, sizeof(guess_type), compare_guesses);
    if (Debug(DEBUG_BEST_GUESS)) {
      int k;
      fprintf(stderr, "BEST: GRID GUESSES\n");
      fprintf(stderr, "BEST:  k       albedo          b           g    distance\n");
      for (k = 0; k ≤ 6; k++) {
        fprintf(stderr, "BEST:%3d  ", k);
        fprintf(stderr, "%10.5f ", guess[k].a);
        fprintf(stderr, "%10.5f ", guess[k].b);
        fprintf(stderr, "%10.5f ", guess[k].g);
        fprintf(stderr, "%10.5f\n", guess[k].distance);
      }
    }
  }
```

This code is used in sections 226, 246, 251, 257, and 262.

229. ⟨ Initialize the nodes of the a and b simplex 229 ⟩ ≡

```
{
  int k, kk;
  p[1][1] = a2acalc(guess[0].a);
  p[1][2] = b2bcalc(guess[0].b);
  for (k = 1; k < 7; k++) {
    if (guess[0].a ≠ guess[k].a) break;
  }
  p[2][1] = a2acalc(guess[k].a);
  p[2][2] = b2bcalc(guess[k].b);
  for (kk = 1; kk < 7; kk++) {
    if (k ≡ kk) continue;
    if (guess[0].b ≠ guess[kk].b ∨ guess[k].b ≠ guess[kk].b) break;
  }
  p[3][1] = a2acalc(guess[kk].a);
  p[3][2] = b2bcalc(guess[kk].b);
  if (Debug(DEBUG_BEST_GUESS)) {
    fprintf(stderr, "------------------------------------------------------\n");
    fprintf(stderr, "BEST: <1> ");
    fprintf(stderr, "%10.5f ", guess[0].a);
    fprintf(stderr, "%10.5f ", guess[0].b);
    fprintf(stderr, "%10.5f ", guess[0].g);
    fprintf(stderr, "%10.5f\n", guess[0].distance);
    fprintf(stderr, "BEST: <2> ");
    fprintf(stderr, "%10.5f ", guess[k].a);
    fprintf(stderr, "%10.5f ", guess[k].b);
    fprintf(stderr, "%10.5f ", guess[k].g);
    fprintf(stderr, "%10.5f\n", guess[k].distance);
    fprintf(stderr, "BEST: <3> ");
    fprintf(stderr, "%10.5f ", guess[kk].a);
    fprintf(stderr, "%10.5f ", guess[kk].b);
    fprintf(stderr, "%10.5f ", guess[kk].g);
    fprintf(stderr, "%10.5f\n", guess[kk].distance);
    fprintf(stderr, "\n");
  }
}
```

This code is used in section 226.

230. ⟨ Evaluate the a and b simplex at the nodes 230 ⟩ ≡

```
for (i = 1; i ≤ 3; i++) {
  x[1] = p[i][1];
  x[2] = p[i][2];
  y[i] = Find_AB_fn(x);
}
```

This code is used in section 226.

231. ⟨ Choose the best node of the a and b simplex 231 ⟩ ≡

```
r→final_distance = 10;
for (i = 1; i ≤ 3; i++) {
  if (y[i] < r→final_distance) {
    r→slab.a = acalc2a(p[i][1]);
    r→slab.b = bcalc2b(p[i][2]);
    r→final_distance = y[i];
  }
}
```

This code is used in section 226.

232. ⟨ Put final values in result 232 ⟩ ≡

```
r→a = r→slab.a;
r→b = r→slab.b;
r→g = r→slab.g;
r→found = (r→tolerance ≤ r→final_distance);
Set_Calc_State(m, *r);
```

This code is used in sections 226, 235, 237, 239, 241, 243, 246, 251, 257, and 262.

233. Since we allocated these puppies, we got to get rid of them.

⟨ Free simplex data structures 233 ⟩ ≡

```
free_dvector(x, 1, 2);
free_dvector(y, 1, 3);
free_dmatrix(p, 1, 3, 1, 2);
```

This code is used in sections 226, 246, 251, 257, and 262.

234. Fixed Absorption and Anisotropy. Typically, this routine is called when the absorption coefficient is known, the anisotropy is known, and the physical thickness of the sample is known. This routine calculates the varies the scattering coefficient until the measurements are matched.

This was written for Ted Moffitt to analyze some intralipid data. We wanted to know what the scattering coefficient of the Intralipid was and made total transmission measurements through a sample with a fixed physical thickness. We did not make reflection measurements because the light source diverged too much, and we could not make reflection measurements easily.

In retrospect, we could have made URU measurements by illuminating the wall of the integrating sphere. However, these diffuse type of measurements are very difficult to make accurately.

This is tricky only because the value in *slab.b* is used to hold the value of *ba* or $d \cdot \mu_a$ when the *Find_Bs_fn* is used.

⟨ Prototype for *U_Find_Bs* 234 ⟩ ≡

```
void U_Find_Bs(struct measure_type m, struct invert_type *r)
```

This code is used in sections 224 and 235.

235. ⟨ Definition for *U_Find_Bs* 235 ⟩ ≡

```
⟨ Prototype for U_Find_Bs 234 ⟩
{
  double ax, bx, cx, fa, fb, fc, bs;
  if (Debug(DEBUG_SEARCH)) {
    fprintf(stderr, "SEARCH: Using U_Find_Bs()");
    fprintf(stderr, " (mu=%6.4f)", r->slab.cos_angle);
    if (r->default_ba ≠ UNINITIALIZED) fprintf(stderr, "  default_ba = %8.5f", r->default_ba);
    if (r->default_g ≠ UNINITIALIZED) fprintf(stderr, "  default_g = %8.5f", r->default_g);
    fprintf(stderr, "\n");
  }
  if (m.m_t ≡ 0) {
    r->slab.b = HUGE_VAL;
    U_Find_A(m, r);
    return;
  }
  r->slab.a = 0;
  r->slab.g = (r->default_g ≡ UNINITIALIZED) ? 0 : r->default_g;
  r->slab.b = (r->default_ba ≡ UNINITIALIZED) ? HUGE_VAL : r->default_ba;
  Set_Calc_State(m, *r);      /* store ba in RR.slab.b */
  ax = b2bcalc(0.1);      /* first try for bs */
  bx = b2bcalc(1.0);
  mnbrak(&ax, &bx, &cx, &fa, &fb, &fc, Find_Bs_fn);
  r->final_distance = brent(ax, bx, cx, Find_Bs_fn, r->tolerance, &bs);      /* recover true values */
  r->slab.a = bcalc2b(bs)/(bcalc2b(bs) + r->slab.b);
  r->slab.b = bcalc2b(bs) + r->slab.b;
  ⟨ Put final values in result 232 ⟩
}
```

This code is used in section 223.

236. Fixed Absorption and Scattering. Typically, this routine is called when the scattering coefficient is known, the anisotropy is known, and the physical thickness of the sample is known. This routine calculates the varies the absorption coefficient until the measurements are matched.

This is tricky only because the value in *slab.b* is used to hold the value of *bs* or $d \cdot \mu_s$ when the *Find_Ba_fn* is used.

```
⟨ Prototype for U_Find_Ba 236 ⟩ ≡
  void U_Find_Ba(struct measure_type m, struct invert_type *r)
```

This code is used in sections 224 and 237.

237.

```
⟨ Definition for U_Find_Ba 237 ⟩ ≡
  ⟨ Prototype for U_Find_Ba 236 ⟩
  {
    double ax, bx, cx, fa, fb, fc, ba;
    if (Debug(DEBUG_SEARCH)) {
      fprintf(stderr, "SEARCH: Using U_Find_Bs()");
      fprintf(stderr, " (mu=%6.4f)", r→slab.cos_angle);
      if (r→default_bs ≠ UNINITIALIZED) fprintf(stderr, "  default_bs = %8.5f", r→default_bs);
      if (r→default_g ≠ UNINITIALIZED) fprintf(stderr, "  default_g = %8.5f", r→default_g);
      fprintf(stderr, "\n");
    }
    r→slab.a = 0;
    r→slab.g = (r→default_g ≡ UNINITIALIZED) ? 0 : r→default_g;
    r→slab.b = (r→default_bs ≡ UNINITIALIZED) ? HUGE_VAL : r→default_bs;
    if (m.m_t ≡ 0) {
      r→slab.b = HUGE_VAL;
      U_Find_A(m, r);
      return;
    }
    Set_Calc_State(m, *r);      /* store bs in RR.slab.b */
    ax = b2bcalc(0.1);      /* first try for ba */
    bx = b2bcalc(1.0);
    mnbrak(&ax, &bx, &cx, &fa, &fb, &fc, Find_Ba_fn);
    r→final_distance = brent(ax, bx, cx, Find_Ba_fn, r→tolerance, &ba);      /* recover true values */
    r→slab.a = (r→slab.b)/(bcalc2b(ba) + r→slab.b);
    r→slab.b = bcalc2b(ba) + r→slab.b;      /* actual value of b */
    ⟨ Put final values in result 232 ⟩
  }
```

This code is used in section 223.

238. Fixed Optical Depth and Anisotropy. Typically, this routine is called when the optical thickness is assumed infinite. However, it may also be called when the optical thickness is assumed to be fixed at a particular value. Typically the only reasonable situation for this to occur is when the diffuse transmission is non-zero but the collimated transmission is zero. If this is the case then there is no information in the collimated transmission measurement and there is no sense even using it because the slab is not infinitely thick.

```
⟨ Prototype for U_Find_A 238 ⟩ ≡
  void U_Find_A(struct measure_type m, struct invert_type *r)
```

This code is used in sections 224 and 239.

239.

```
⟨ Definition for U_Find_A 239 ⟩ ≡
  ⟨ Prototype for U_Find_A 238 ⟩
  {
    double Rt, Tt, Rd, Rc, Td, Tc;
    if (Debug(DEBUG_SEARCH)) {
      fprintf(stderr, "SEARCH: Using U_Find_A()");
      fprintf(stderr, " (mu=%6.4f)", r->slab.cos_angle);
      if (r->default_b ≠ UNINITIALIZED) fprintf(stderr, "  default_b = %8.5f", r->default_b);
      if (r->default_g ≠ UNINITIALIZED) fprintf(stderr, "  default_g = %8.5f", r->default_g);
      fprintf(stderr, "\n");
    }
    Estimate_RT(m, *r, &Rt, &Tt, &Rd, &Rc, &Td, &Tc);
    r->slab.g = (r->default_g ≡ UNINITIALIZED) ? 0 : r->default_g;
    r->slab.b = (r->default_b ≡ UNINITIALIZED) ? HUGE_VAL : r->default_b;
    r->slab.a = 0.0;
    r->final_distance = 0.0;
    Set_Calc_State(m, *r);
    if (Rt > 0.99999) {
      r->final_distance = Find_A_fn(a2acalc(1.0));
      r->slab.a = 1.0;
    }
    else {
      double x, ax, bx, cx, fa, fb, fc;
      ax = a2acalc(0.3);
      bx = a2acalc(0.5);
      mnbrak(&ax, &bx, &cx, &fa, &fb, &fc, Find_A_fn);
      r->final_distance = brent(ax, bx, cx, Find_A_fn, r->tolerance, &x);
      r->slab.a = acalc2a(x);
    }
    ⟨ Put final values in result 232 ⟩
  }
```

This code is used in section 223.

240. Fixed Optical Depth and Albedo.

⟨ Prototype for *U_Find_G* 240 ⟩ ≡

```
void U_Find_G(struct measure_type m, struct invert_type *r)
```

This code is used in sections 224 and 241.

241. ⟨ Definition for *U_Find_G* 241 ⟩ ≡

```
⟨ Prototype for U_Find_G 240 ⟩
{
  double Rt, Tt, Rd, Rc, Td, Tc;
  double x, ax, bx, cx, fa, fb, fc;
  if (Debug(DEBUG_SEARCH)) {
    fprintf(stderr, "SEARCH: Using U_Find_G()");
    fprintf(stderr, " (mu=%6.4f)", r->slab.cos_angle);
    if (r->default_a ≠ UNINITIALIZED) fprintf(stderr, "  default_a = %8.5f", r->default_a);
    if (r->default_b ≠ UNINITIALIZED) fprintf(stderr, "  default_b = %8.5f", r->default_b);
    fprintf(stderr, "\n");
  }
  Estimate_RT(m, *r, &Rt, &Tt, &Rd, &Rc, &Td, &Tc);
  r->slab.a = (r->default_a ≡ UNINITIALIZED) ? 0.5 : r->default_a;
  if (r->default_b ≠ UNINITIALIZED) r->slab.b = r->default_b;
  else if (m.m_u > 0) r->slab.b = What_Is_B(r->slab, m.m_u);
  else r->slab.b = HUGE_VAL;
  r->slab.g = 0.0;
  r->final_distance = 0.0;
  Set_Calc_State(m, *r);
  ax = g2gcalc(−0.99);
  bx = g2gcalc(0.99);
  mnbrak(&ax, &bx, &cx, &fa, &fb, &fc, Find_G_fn);
  r->final_distance = brent(ax, bx, cx, Find_G_fn, r->tolerance, &x);
  r->slab.g = gcalc2g(x);
  Set_Calc_State(m, *r);
  ⟨ Put final values in result 232 ⟩
}
```

This code is used in section 223.

242. Fixed Anisotropy and Albedo. This routine can be called in three different situations: (1) the albedo is zero, (2) the albedo is one, or (3) the albedo is fixed at a default value. I calculate the individual reflections and transmissions to establish which of these cases we happen to have.

```
⟨ Prototype for U_Find_B 242 ⟩ ≡
  void U_Find_B(struct measure_type m, struct invert_type *r)
```

This code is used in sections 224 and 243.

243.

```
⟨ Definition for U_Find_B 243 ⟩ ≡
  ⟨ Prototype for U_Find_B 242 ⟩
  {
    double Rt, Tt, Rd, Rc, Td, Tc;
    if (Debug(DEBUG_SEARCH)) {
      fprintf(stderr, "SEARCH: Using U_Find_B()");
      fprintf(stderr, " (mu=%6.4f)", r→slab.cos_angle);
      if (r→default_a ≠ UNINITIALIZED) fprintf(stderr, "  default_a = %8.5f", r→default_a);
      if (r→default_g ≠ UNINITIALIZED) fprintf(stderr, "  default_g = %8.5f", r→default_g);
      fprintf(stderr, "\n");
    }
    Estimate_RT(m, *r, &Rt, &Tt, &Rd, &Rc, &Td, &Tc);
    r→slab.g = (r→default_g ≡ UNINITIALIZED) ? 0 : r→default_g;
    r→slab.a = (r→default_a ≡ UNINITIALIZED) ? 0 : r→default_a;
    r→slab.b = 0.5;
    r→final_distance = 0.0;
    Set_Calc_State(m, *r);
    ⟨ Iteratively solve for b 244 ⟩
    ⟨ Put final values in result 232 ⟩
  }
```

This code is used in section 223.

244. This could be improved tremendously. I just don't want to mess with it at the moment.

```
⟨ Iteratively solve for b 244 ⟩ ≡
  {
    double x, ax, bx, cx, fa, fb, fc;
    ax = b2bcalc(0.1);
    bx = b2bcalc(10);
    mnbrak(&ax, &bx, &cx, &fa, &fb, &fc, Find_B_fn);
    r→final_distance = brent(ax, bx, cx, Find_B_fn, r→tolerance, &x);
    r→slab.b = bcalc2b(x);
    Set_Calc_State(m, *r);
  }
```

This code is used in section 243.

245. Fixed Optical Depth.

We can get here a couple of different ways.

First there can be three real measurements, i.e., t_c is not zero, in this case we want to fix b based on the t_c measurement.

Second, we can get here if a default value for b has been set.

Otherwise, we really should not be here. Just set $b = 1$ and calculate away.

```
⟨ Prototype for U_Find_AG 245 ⟩ ≡
  void U_Find_AG(struct measure_type m, struct invert_type *r)
```

This code is used in sections 224 and 246.

246. ⟨ Definition for *U_Find_AG* 246 ⟩ ≡

```
⟨ Prototype for U_Find_AG 245 ⟩
{
  ⟨ Allocate local simplex variables 227 ⟩
  if (Debug(DEBUG_SEARCH)) {
    fprintf(stderr, "SEARCH: Using U_Find_AG()");
    fprintf(stderr, " (mu=%6.4f)", r->slab.cos_angle);
    if (r->default_b ≠ UNINITIALIZED) fprintf(stderr, "  default_b = %8.5f", r->default_b);
    fprintf(stderr, "\n");
  }
  if (m.num_measures ≡ 3) r->slab.b = What_Is_B(r->slab, m.m_u);
  else if (r->default_b ≡ UNINITIALIZED) r->slab.b = 1;
  else r->slab.b = r->default_b;
  Set_Calc_State(m, *r);
  ⟨ Get the initial a, b, and g 228 ⟩
  ⟨ Initialize the nodes of the a and g simplex 247 ⟩
  ⟨ Evaluate the a and g simplex at the nodes 248 ⟩
  amoeba(p, y, 2, r->tolerance, Find_AG_fn, &r->AD_iterations);
  ⟨ Choose the best node of the a and g simplex 249 ⟩
  ⟨ Free simplex data structures 233 ⟩
  ⟨ Put final values in result 232 ⟩
}
```

This code is used in section 223.

247. ⟨ Initialize the nodes of the a and g simplex 247 ⟩ ≡

```
{
  int k, kk;
  p[1][1] = a2acalc(guess[0].a);
  p[1][2] = g2gcalc(guess[0].g);
  for (k = 1; k < 7; k++) {
    if (guess[0].a ≠ guess[k].a) break;
  }
  p[2][1] = a2acalc(guess[k].a);
  p[2][2] = g2gcalc(guess[k].g);
  for (kk = 1; kk < 7; kk++) {
    if (kk ≡ k) continue;
    if (guess[0].g ≠ guess[kk].g ∨ guess[k].g ≠ guess[kk].g) break;
  }
  p[3][1] = a2acalc(guess[kk].a);
  p[3][2] = g2gcalc(guess[kk].g);
  if (Debug(DEBUG_BEST_GUESS)) {
    fprintf(stderr, "------------------------------------------------------\n");
    fprintf(stderr, "BEST: <1> ");
    fprintf(stderr, "%10.5f ", guess[0].a);
    fprintf(stderr, "%10.5f ", guess[0].b);
    fprintf(stderr, "%10.5f ", guess[0].g);
    fprintf(stderr, "%10.5f\n", guess[0].distance);
    fprintf(stderr, "BEST: <2> ");
    fprintf(stderr, "%10.5f ", guess[k].a);
    fprintf(stderr, "%10.5f ", guess[k].b);
    fprintf(stderr, "%10.5f ", guess[k].g);
    fprintf(stderr, "%10.5f\n", guess[k].distance);
    fprintf(stderr, "BEST: <3> ");
    fprintf(stderr, "%10.5f ", guess[kk].a);
    fprintf(stderr, "%10.5f ", guess[kk].b);
    fprintf(stderr, "%10.5f ", guess[kk].g);
    fprintf(stderr, "%10.5f\n", guess[kk].distance);
    fprintf(stderr, "\n");
  }
}
```

This code is used in section 246.

248. ⟨ Evaluate the a and g simplex at the nodes 248 ⟩ ≡

```
for (i = 1; i ≤ 3; i++) {
  x[1] = p[i][1];
  x[2] = p[i][2];
  y[i] = Find_AG_fn(x);
}
```

This code is used in section 246.

249. Here we find the node of the simplex that gave the best result and save that one. At the same time we save the whole simplex for later use if needed.

```
⟨ Choose the best node of the a and g simplex 249 ⟩ ≡
  r→final_distance = 10;
  for (i = 1; i ≤ 3; i++) {
    if (y[i] < r→final_distance) {
      r→slab.a = acalc2a(p[i][1]);
      r→slab.g = gcalc2g(p[i][2]);
      r→final_distance = y[i];
    }
  }
```

This code is used in section 246.

250. Fixed Albedo. Here the optical depth and the anisotropy are varied (for a fixed albedo).

```
⟨ Prototype for U_Find_BG 250 ⟩ ≡
  void U_Find_BG(struct measure_type m, struct invert_type *r)
```

This code is used in sections 224 and 251.

251.

```
⟨ Definition for U_Find_BG 251 ⟩ ≡
  ⟨ Prototype for U_Find_BG 250 ⟩
  {
    ⟨ Allocate local simplex variables 227 ⟩
    if (Debug(DEBUG_SEARCH)) {
      fprintf(stderr, "SEARCH: Using U_Find_BG()");
      fprintf(stderr, " (mu=%6.4f)", r→slab.cos_angle);
      if (r→default_a ≠ UNINITIALIZED) fprintf(stderr, "  default_a = %8.5f", r→default_a);
      fprintf(stderr, "\n");
    }
    r→slab.a = (r→default_a ≡ UNINITIALIZED) ? 0 : r→default_a;
    Set_Calc_State(m, *r);
    ⟨ Get the initial a, b, and g 228 ⟩
    ⟨ Initialize the nodes of the b and g simplex 253 ⟩
    ⟨ Evaluate the bg simplex at the nodes 254 ⟩
    amoeba(p, y, 2, r→tolerance, Find_BG_fn, &r→AD_iterations);
    ⟨ Choose the best node of the b and g simplex 255 ⟩
    ⟨ Free simplex data structures 233 ⟩
    ⟨ Put final values in result 232 ⟩
  }
```

This code is used in section 223.

252. A very simple start for variation of b and g. This should work fine for the cases in which the absorption or scattering are fixed.

253. ⟨ Initialize the nodes of the b and g simplex 253 ⟩ ≡

```
{
  int k, kk;
  p[1][1] = b2bcalc(guess[0].b);
  p[1][2] = g2gcalc(guess[0].g);
  for (k = 1; k < 7; k++) {
    if (guess[0].b ≠ guess[k].b) break;
  }
  p[2][1] = b2bcalc(guess[k].b);
  p[2][2] = g2gcalc(guess[k].g);
  for (kk = 1; kk < 7; kk++) {
    if (kk ≡ k) continue;
    if (guess[0].g ≠ guess[kk].g ∨ guess[k].g ≠ guess[kk].g) break;
  }
  p[3][1] = b2bcalc(guess[kk].b);
  p[3][2] = g2gcalc(guess[kk].g);
  if (Debug(DEBUG_BEST_GUESS)) {
    fprintf(stderr, "------------------------------------------------------\n");
    fprintf(stderr, "BEST: <1> ");
    fprintf(stderr, "%10.5f ", guess[0].a);
    fprintf(stderr, "%10.5f ", guess[0].b);
    fprintf(stderr, "%10.5f ", guess[0].g);
    fprintf(stderr, "%10.5f\n", guess[0].distance);
    fprintf(stderr, "BEST: <2> ");
    fprintf(stderr, "%10.5f ", guess[k].a);
    fprintf(stderr, "%10.5f ", guess[k].b);
    fprintf(stderr, "%10.5f ", guess[k].g);
    fprintf(stderr, "%10.5f\n", guess[k].distance);
    fprintf(stderr, "BEST: <3> ");
    fprintf(stderr, "%10.5f ", guess[kk].a);
    fprintf(stderr, "%10.5f ", guess[kk].b);
    fprintf(stderr, "%10.5f ", guess[kk].g);
    fprintf(stderr, "%10.5f\n", guess[kk].distance);
    fprintf(stderr, "\n");
  }
}
```

This code is used in section 251.

254. ⟨ Evaluate the bg simplex at the nodes 254 ⟩ ≡

```
for (i = 1; i ≤ 3; i++) {
  x[1] = p[i][1];
  x[2] = p[i][2];
  y[i] = Find_BG_fn(x);
}
```

This code is used in section 251.

255. Here we find the node of the simplex that gave the best result and save that one. At the same time we save the whole simplex for later use if needed.

```
⟨ Choose the best node of the b and g simplex 255 ⟩ ≡
  r→final_distance = 10;
  for (i = 1; i ≤ 3; i++) {
    if (y[i] < r→final_distance) {
      r→slab.b = bcalc2b(p[i][1]);
      r→slab.g = gcalc2g(p[i][2]);
      r→final_distance = y[i];
    }
  }
```

This code is used in section 251.

256. Fixed Scattering. Here I assume that a constant b_s,

$$b_s = \mu_s d$$

where d is the physical thickness of the sample and μ_s is of course the absorption coefficient. This is just like *U_Find_BG* except that $b_a = \mu_a d$ is varied instead of b.

```
⟨ Prototype for U_Find_BaG 256 ⟩ ≡
  void U_Find_BaG(struct measure_type m, struct invert_type *r)
```

This code is used in sections 224 and 257.

257.
```
⟨ Definition for U_Find_BaG 257 ⟩ ≡
  ⟨ Prototype for U_Find_BaG 256 ⟩
  {
    ⟨ Allocate local simplex variables 227 ⟩
    Set_Calc_State(m, *r);
    ⟨ Get the initial a, b, and g 228 ⟩
    ⟨ Initialize the nodes of the ba and g simplex 258 ⟩
    ⟨ Evaluate the BaG simplex at the nodes 259 ⟩
    amoeba(p, y, 2, r→tolerance, Find_BaG_fn, &r→AD_iterations);
    ⟨ Choose the best node of the ba and g simplex 260 ⟩
    ⟨ Free simplex data structures 233 ⟩
    ⟨ Put final values in result 232 ⟩
  }
```

This code is used in section 223.

258.
```
⟨ Initialize the nodes of the ba and g simplex 258 ⟩ ≡
  if (guess[0].b > r→default_bs) {
    p[1][1] = b2bcalc(guess[0].b − r→default_bs);
    p[2][1] = b2bcalc(2 * (guess[0].b − r→default_bs));
    p[3][1] = p[1][1];
  }
  else {
    p[1][1] = b2bcalc(0.0001);
    p[2][1] = b2bcalc(0.001);
    p[3][1] = p[1][1];
  }
  p[1][2] = g2gcalc(guess[0].g);
  p[2][2] = p[1][2];
  p[3][2] = g2gcalc(0.9 * guess[0].g + 0.05);
```

This code is used in section 257.

259.
```
⟨ Evaluate the BaG simplex at the nodes 259 ⟩ ≡
  for (i = 1; i ≤ 3; i++) {
    x[1] = p[i][1];
    x[2] = p[i][2];
    y[i] = Find_BaG_fn(x);
  }
```

This code is used in section 257.

260. Here we find the node of the simplex that gave the best result and save that one. At the same time we save the whole simplex for later use if needed.

```
⟨ Choose the best node of the ba and g simplex 260 ⟩ ≡
  r→final_distance = 10;
  for (i = 1; i ≤ 3; i++) {
    if (y[i] < r→final_distance) {
      r→slab.b = bcalc2b(p[i][1]) + r→default_bs;
      r→slab.a = r→default_bs/r→slab.b;
      r→slab.g = gcalc2g(p[i][2]);
      r→final_distance = y[i];
    }
  }
```

This code is used in section 257.

261. Fixed Absorption. Here I assume that we have a constant b_a,

$$b_a = \mu_a d$$

where d is the physical thickness of the sample and μ_a is of course the absorption coefficient. This is just like *U_Find_BG* except that $b_s = \mu_s d$ is varied instead of b.

```
⟨ Prototype for U_Find_BsG 261 ⟩ ≡
  void U_Find_BsG(struct measure_type m, struct invert_type *r)
```

This code is used in sections 224 and 262.

262.

```
⟨ Definition for U_Find_BsG 262 ⟩ ≡
  ⟨ Prototype for U_Find_BsG 261 ⟩
  {
    ⟨ Allocate local simplex variables 227 ⟩
    if (Debug(DEBUG_SEARCH)) {
      fprintf(stderr, "SEARCH: Using U_Find_BsG()");
      fprintf(stderr, " (mu=%6.4f)", r→slab.cos_angle);
      if (r→default_ba ≠ UNINITIALIZED) fprintf(stderr, "  default_ba = %8.5f", r→default_ba);
      fprintf(stderr, "\n");
    }
    Set_Calc_State(m, *r);
    ⟨ Get the initial a, b, and g 228 ⟩
    ⟨ Initialize the nodes of the bs and g simplex 263 ⟩
    ⟨ Evaluate the BsG simplex at the nodes 264 ⟩
    amoeba(p, y, 2, r→tolerance, Find_BsG_fn, &r→AD_iterations);
    ⟨ Choose the best node of the bs and g simplex 265 ⟩
    ⟨ Free simplex data structures 233 ⟩
    ⟨ Put final values in result 232 ⟩
  }
```

This code is used in section 223.

263.

```
⟨ Initialize the nodes of the bs and g simplex 263 ⟩ ≡
  p[1][1] = b2bcalc(guess[0].b − r→default_ba);
  p[1][2] = g2gcalc(guess[0].g);
  p[2][1] = b2bcalc(2 * guess[0].b − 2 * r→default_ba);
  p[2][2] = p[1][2];
  p[3][1] = p[1][1];
  p[3][2] = g2gcalc(0.9 * guess[0].g + 0.05);
```

This code is used in section 262.

264.

```
⟨ Evaluate the BsG simplex at the nodes 264 ⟩ ≡
  for (i = 1; i ≤ 3; i++) {
    x[1] = p[i][1];
    x[2] = p[i][2];
    y[i] = Find_BsG_fn(x);
  }
```

This code is used in section 262.

265. ⟨ Choose the best node of the *bs* and *g* simplex 265 ⟩ ≡

```
r→final_distance = 10;
for (i = 1; i ≤ 3; i++) {
  if (y[i] < r→final_distance) {
    r→slab.b = bcalc2b(p[i][1]) + r→default_ba;
    r→slab.a = 1 − r→default_ba/r→slab.b;
    r→slab.g = gcalc2g(p[i][2]);
    r→final_distance = y[i];
  }
}
```

This code is used in section 262.

266. IAD Utilities.
March 1995. Reincluded *quick_guess* code.

⟨ iad_util.c 266 ⟩ ≡
```
#include <math.h>
#include <float.h>
#include <stdio.h>
#include "nr_util.h"
#include "ad_globl.h"
#include "ad_frsnl.h"
#include "ad_bound.h"
#include "iad_type.h"
#include "iad_calc.h"
#include "iad_pub.h"
#include "iad_util.h"
  unsigned long g_util_debugging = 0;
  ⟨ Preprocessor definitions ⟩
  ⟨ Definition for What_Is_B 269 ⟩
  ⟨ Definition for Estimate_RT 275 ⟩
  ⟨ Definition for a2acalc 282 ⟩
  ⟨ Definition for acalc2a 284 ⟩
  ⟨ Definition for g2gcalc 286 ⟩
  ⟨ Definition for gcalc2g 288 ⟩
  ⟨ Definition for b2bcalc 290 ⟩
  ⟨ Definition for bcalc2b 292 ⟩
  ⟨ Definition for twoprime 294 ⟩
  ⟨ Definition for twounprime 296 ⟩
  ⟨ Definition for abgg2ab 298 ⟩
  ⟨ Definition for abgb2ag 300 ⟩
  ⟨ Definition for quick_guess 307 ⟩
  ⟨ Definition for Set_Debugging 320 ⟩
  ⟨ Definition for Debug 322 ⟩
  ⟨ Definition for Print_Invert_Type 324 ⟩
  ⟨ Definition for Print_Measure_Type 326 ⟩
```

267. ⟨ iad_util.h 267 ⟩ ≡
```
  ⟨ Prototype for What_Is_B 268 ⟩;
  ⟨ Prototype for Estimate_RT 274 ⟩;
  ⟨ Prototype for a2acalc 281 ⟩;
  ⟨ Prototype for acalc2a 283 ⟩;
  ⟨ Prototype for g2gcalc 285 ⟩;
  ⟨ Prototype for gcalc2g 287 ⟩;
  ⟨ Prototype for b2bcalc 289 ⟩;
  ⟨ Prototype for bcalc2b 291 ⟩;
  ⟨ Prototype for twoprime 293 ⟩;
  ⟨ Prototype for twounprime 295 ⟩;
  ⟨ Prototype for abgg2ab 297 ⟩;
  ⟨ Prototype for abgb2ag 299 ⟩;
  ⟨ Prototype for quick_guess 306 ⟩;
  ⟨ Prototype for Set_Debugging 319 ⟩;
  ⟨ Prototype for Debug 321 ⟩;
  ⟨ Prototype for Print_Invert_Type 323 ⟩;
  ⟨ Prototype for Print_Measure_Type 325 ⟩;
```

268. Finding optical thickness.

This routine figures out what the optical thickness of a slab based on the index of refraction of the slab and the amount of collimated light that gets through it.

It should be pointed out right here in the front that this routine does not work for diffuse irradiance, but then the whole concept of estimating the optical depth for diffuse irradiance is bogus anyway.

In version 1.3 changed all error output to *stderr*. Version 1.4 included cases involving absorption in the boundaries.

```
#define BIG_A_VALUE 999999.0
#define SMALL_A_VALUE 0.000001
⟨ Prototype for What_Is_B 268 ⟩ ≡
  double What_Is_B(struct AD_slab_type slab, double Tc)
```

This code is used in sections 267 and 269.

269. ⟨ Definition for *What_Is_B* 269 ⟩ ≡

```
⟨ Prototype for What_Is_B 268 ⟩
{
  double r1, r2, t1, t2, mu_in_slab;
  ⟨ Calculate specular reflection and transmission 270 ⟩
  ⟨ Check for bad values of Tc 271 ⟩
  ⟨ Solve if multiple internal reflections are not present 272 ⟩
  ⟨ Find thickness when multiple internal reflections are present 273 ⟩
}
```

This code is used in section 266.

270. The first thing to do is to find the specular reflection for light interacting with the top and bottom air-glass-sample interfaces. I make a simple check to ensure that the the indices are different before calculating the bottom reflection. Most of the time the $r1 \equiv r2$, but there are always those annoying special cases.

```
⟨ Calculate specular reflection and transmission 270 ⟩ ≡
  Absorbing_Glass_RT(1.0, slab.n_top_slide, slab.n_slab, slab.cos_angle, slab.b_top_slide, &r1, &t1);
  mu_in_slab = Cos_Snell(1.0, slab.cos_angle, slab.n_slab);
  Absorbing_Glass_RT(slab.n_slab, slab.n_bottom_slide, 1.0, mu_in_slab, slab.b_bottom_slide, &r2, &t2);
```

This code is used in section 269.

271. Bad values for the unscattered transmission are those that are non-positive, those greater than one, and those greater than are possible in a non-absorbing medium, i.e.,

$$T_c > \frac{t_1 t_2}{1 - r_1 r_2}$$

Since this routine has no way to report errors, I just set the optical thickness to the natural values in these cases.

```
⟨ Check for bad values of Tc 271 ⟩ ≡
  if (Tc ≤ 0) return (HUGE_VAL);
  if (Tc ≥ t1 * t2/(1 − r1 * r2)) return (0.001);
```

This code is used in section 269.

272. If either *r1* or *r2* $\equiv 0$ then things are very simple because the sample does not sustain multiple internal reflections and the unscattered transmission is

$$T_c = t_1 t_2 \exp(-b/\nu)$$

where b is the optical thickness and ν is *slab.cos_angle*. Clearly,

$$b = -\nu \ln\left(\frac{T_c}{t_1 t_2}\right)$$

⟨ Solve if multiple internal reflections are not present 272 ⟩ ≡
if (*r1* $\equiv 0 \vee$ *r2* $\equiv 0$) **return** (−*slab.cos_angle* ∗ *log*(*Tc*/*t1*/*t2*));
This code is used in section 269.

273. Well I kept putting it off, but now comes the time to solve the following equation for b

$$T_c = \frac{t_1 t_2 \exp(-b)}{1 - r_1 r_2 \exp(-2b)}$$

We note immediately that this is a quadratic equation in $x = \exp(-b)$.

$$r_1 r_2 T_c x^2 + t_1 t_2 x - T_c = 0$$

Sufficient tests have been made above to ensure that none of the coefficients are exactly zero. However, it is clear that the leading quadratic term has a much smaller coefficient than the other two. Since r_1 and r_2 are typically about four percent the product is roughly 10^{-3}. The collimated transmission can be very small and this makes things even worse. A further complication is that we need to choose the only positive root.

Now the roots of $ax^2 + bx + c = 0$ can be found using the standard quadratic formula,

$$x = \frac{-b \pm \sqrt{b^2 - 4ac}}{2a}$$

This is very bad for small values of a. Instead I use

$$q = -\frac{1}{2}\left[b + \mathrm{sgn}(b)\sqrt{b^2 - 4ac}\right]$$

with the two roots

$$x = \frac{q}{a} \qquad \text{and} \qquad x = \frac{c}{q}$$

Substituting our coefficients

$$q = -\frac{1}{2}\left[t_1 t_2 + \sqrt{t_1^2 t_2^2 + 4 r_1 r_2 T_c^2}\right]$$

With some algebra, this can be shown to be

$$q = -t_1 t_2 \left[1 + \frac{r_1 r_2 T_c^2}{t_1^2 t_2^2} + \cdots\right]$$

The only positive root is $x = -T_c/q$. Therefore

$$x = \frac{2T_c}{t_1 t_2 + \sqrt{t_1^2 t_2^2 + 4 r_1 r_2 T_c^2}}$$

(Not very pretty, but straightforward enough.)

⟨ Find thickness when multiple internal reflections are present 273 ⟩ ≡

```
{
  double B;
  B = t1 * t2;
  return (-slab.cos_angle * log(2 * Tc/(B + sqrt(B * B + 4 * Tc * Tc * r1 * r2))));
}
```

This code is used in section 269.

274. Estimating R and T.

In several places, it is useful to know an *estimate* for the values of the reflection and transmission of the sample based on the measurements. This routine provides such an estimate, but it currently ignores anything corrections that might be made for the integrating spheres.

Good values are only really obtainable when $num\_measures \equiv 3$, otherwise we need to make pretty strong assumptions about the reflection and transmission values. If $num\_measures < 3$, then we will assume that no collimated light makes it all the way through the sample. The specular reflection is then just that for a semi-infinite sample and $Tc = 0$. If $num\_measures \equiv 1$, then Td is also set to zero.

rt	total reflection
rc	primary or specular reflection
rd	diffuse or scattered reflection
tt	total transmission
tp	primary or unscattered transmission
td	diffuse or scattered transmission

⟨ Prototype for *Estimate_RT* 274 ⟩ ≡

void *Estimate_RT*(**struct measure_type** *m*, **struct invert_type** *r*, **double** ∗*rt*, **double** ∗*tt*, **double** ∗*rd*, **double** ∗*rc*, **double** ∗*td*, **double** ∗*tc*)

This code is used in sections 267 and 275.

275. ⟨ Definition for *Estimate_RT* 275 ⟩ ≡

```
⟨ Prototype for Estimate_RT 274 ⟩
{
  ⟨ Calculate the unscattered transmission and reflection 276 ⟩
  ⟨ Estimate the backscattered reflection 277 ⟩
  ⟨ Estimate the scattered transmission 278 ⟩
  ⟨ Debug info for estimate RT 279 ⟩
}
```

This code is used in section 266.

276. If there are three measurements then the specular reflection can be calculated pretty well. If there are fewer then the unscattered transmission is assumed to be zero. This is not necessarily the case, but after all, this routine only makes estimates of the various reflection and transmission quantities.

If there are three measurements, the optical thickness of the sample is required. Of course if there are three measurements then the illumination must be collimated and we can call *What_Is_B* to find out the optical thickness. We pass this value to a routine in the `fresnel.h` unit and sit back and wait.

All the above is true if sphere corrections are not needed. Now, we just fob this off on another function.

⟨ Calculate the unscattered transmission and reflection 276 ⟩ ≡

```
Calculate_Minimum_MR(m, r, rc, tc);
```

This code is used in section 275.

277. Finding the diffuse reflection is now just a matter of checking whether V1% contains the specular reflection from the sample or not and then just adding or subtracting the specular reflection as appropriate.

```
⟨ Estimate the backscattered reflection 277 ⟩ ≡
  if (m.fraction_of_rc_in_mr) {
    *rt = m.m_r;
    *rd = *rt − m.fraction_of_rc_in_mr * (*rc);
    if (*rd < 0) {
      *rd = 0;
      *rc = *rt;
    }
  }
  else {
    *rd = m.m_r;
    *rt = *rd + *rc;
  }
```

This code is used in section 275.

278. The transmission values follow in much the same way as the diffuse reflection values — just subtract the specular transmission from the total transmission.

```
⟨ Estimate the scattered transmission 278 ⟩ ≡
  if (m.fraction_of_tc_in_mt) {
    *tt = m.m_t;
    *td = *tt − *tc;
    if (*td < 0) {
      *tc = *tt;
      *td = 0;
    }
  }
  else {
    *td = m.m_t;
    *tt = *td + *tc;
  }
```

This code is used in section 275.

279. Collect debugging info here

```
⟨ Debug info for estimate RT 279 ⟩ ≡
  if (0 ∧ Debug(DEBUG_SEARCH)) {
    fprintf(stderr, "SEARCH: r_t = %8.5f ", *rt);
    fprintf(stderr, "r_d = %8.5f ", *rd);
    fprintf(stderr, "r_u = %8.5f\n", *rc);
    fprintf(stderr, "SEARCH: t_t = %8.5f ", *tt);
    fprintf(stderr, "t_d = %8.5f ", *td);
    fprintf(stderr, "t_u = %8.5f\n", *tc);
  }
```

This code is used in section 275.

280. Transforming properties. Routines to convert optical properties to calculation space and back.

281. *a2acalc* is used for the albedo transformations according to

$$a_{calc} = \frac{2a - 1}{a(1 - a)}$$

Care is taken to avoid division by zero. Why was this function chosen? Well mostly because it maps the region between $[0, 1] \to (-\infty, +\infty)$.

⟨ Prototype for *a2acalc* 281 ⟩ ≡
```
double a2acalc(double a)
```
This code is used in sections 267 and 282.

282. ⟨ Definition for *a2acalc* 282 ⟩ ≡
```
⟨ Prototype for a2acalc 281 ⟩
{
  if (a ≤ 0) return -BIG_A_VALUE;
  if (a ≥ 1) return BIG_A_VALUE;
  return ((2 * a - 1)/a/(1 - a));
}
```
This code is used in section 266.

283. *acalc2a* is used for the albedo transformations Now when we solve

$$a_calc = \frac{2a - 1}{a(1 - a)}$$

we obtain the quadratic equation

$$a_{calc}a^2 + (2 - a_{calc})a - 1 = 0$$

The only root of this equation between zero and one is

$$a = \frac{-2 + a_{calc} + \sqrt{a_{calc}^2 + 4}}{2a_{calc}}$$

I suppose that I should spend the time to recast this using the more appropriate numerical solutions of the quadratic equation, but this worked and I will leave it as it is for now.

⟨ Prototype for *acalc2a* 283 ⟩ ≡
```
double acalc2a(double acalc)
```
This code is used in sections 267 and 284.

284. ⟨ Definition for *acalc2a* 284 ⟩ ≡
```
⟨ Prototype for acalc2a 283 ⟩
{
  if (acalc ≡ BIG_A_VALUE) return 1.0;
  else if (acalc ≡ -BIG_A_VALUE) return 0.0;
  else if (fabs(acalc) < SMALL_A_VALUE) return 0.5;
  else return ((-2 + acalc + sqrt(acalc * acalc + 4))/(2 * acalc));
}
```
This code is used in section 266.

285. *g2gcalc* is used for the anisotropy transformations according to

$$g_{calc} = \frac{g}{1 + |g|}$$

which maps $(-1, 1) \to (-\infty, +\infty)$.

⟨ Prototype for *g2gcalc* 285 ⟩ ≡
```
double g2gcalc(double g)
```
This code is used in sections 267 and 286.

286. ⟨ Definition for *g2gcalc* 286 ⟩ ≡
```
⟨ Prototype for g2gcalc 285 ⟩
{
  if (g ≤ −0.99999) return (−HUGE_VAL);
  if (g ≥ 0.99999) return (HUGE_VAL);
  return (g/(1 − fabs(g)));
}
```
This code is used in section 266.

287. *gcalc2g* is used for the anisotropy transformations it is the inverse of *g2gcalc*. The relation is

$$g = \frac{g_{calc}}{1 + |g_{calc}|}$$

⟨ Prototype for *gcalc2g* 287 ⟩ ≡
```
double gcalc2g(double gcalc)
```
This code is used in sections 267 and 288.

288. ⟨ Definition for *gcalc2g* 288 ⟩ ≡
```
⟨ Prototype for gcalc2g 287 ⟩
{
  if (gcalc ≡ −HUGE_VAL) return −0.99999;
  if (gcalc ≡ HUGE_VAL) return 0.99999;
  return (gcalc/(1 + fabs(gcalc)));
}
```
This code is used in section 266.

289. *b2bcalc* is used for the optical depth transformations it is the inverse of *bcalc2b*. The relation is

$$b_{calc} = \ln(b)$$

The only caveats are to ensure that I don't take the logarithm of something big or non-positive.

⟨ Prototype for *b2bcalc* 289 ⟩ ≡
```
double b2bcalc(double b)
```
This code is used in sections 267 and 290.

290. ⟨ Definition for *b2bcalc* 290 ⟩ ≡
```
⟨ Prototype for b2bcalc 289 ⟩
{
  if (b ≡ HUGE_VAL) return HUGE_VAL;
  if (b ≤ 0) return 0.0;
  return (log(b));
}
```
This code is used in section 266.

291. *bcalc2b* is used for the anisotropy transformations it is the inverse of *b2bcalc*. The relation is

$$b = \exp(b_{calc})$$

The only tricky part is to ensure that I don't exponentiate something big and get an overflow error. In ANSI C the maximum value for x such that 10^x is in the range of representable finite floating point numbers (for doubles) is given by `DBL_MAX_10_EXP`. Thus if we want to know if

$$e^{b_{calc}} > 10^x$$

or

$$b_{calc} > x \ln(10) \approx 2.3x$$

and this is the criterion that I use.

⟨ Prototype for *bcalc2b* 291 ⟩ ≡
```
double bcalc2b(double bcalc)
```
This code is used in sections 267 and 292.

292. ⟨ Definition for *bcalc2b* 292 ⟩ ≡
```
⟨ Prototype for bcalc2b 291 ⟩
{
  if (bcalc ≡ HUGE_VAL) return HUGE_VAL;
  if (bcalc > 2.3 * DBL_MAX_10_EXP) return HUGE_VAL;
  return (exp(bcalc));
}
```
This code is used in section 266.

293. *twoprime* converts the true albedo a, optical depth b to the reduced albedo ap and reduced optical depth bp that correspond to $g = 0$.

⟨ Prototype for *twoprime* 293 ⟩ ≡
```
void twoprime(double a, double b, double g, double *ap, double *bp)
```
This code is used in sections 267 and 294.

294. ⟨ Definition for *twoprime* 294 ⟩ ≡
```
⟨ Prototype for twoprime 293 ⟩
{
  if (a ≡ 1 ∧ g ≡ 1) *ap = 0.0;
  else *ap = (1 − g) * a/(1 − a * g);
  if (b ≡ HUGE_VAL) *bp = HUGE_VAL;
  else *bp = (1 − a * g) * b;
}
```
This code is used in section 266.

295. *twounprime* converts the reduced albedo ap and reduced optical depth bp (for $g = 0$) to the true albedo a and optical depth b for an anisotropy g.

```
⟨ Prototype for twounprime 295 ⟩ ≡
  void twounprime(double ap, double bp, double g, double *a, double *b)
```

This code is used in sections 267 and 296.

296.
```
⟨ Definition for twounprime 296 ⟩ ≡
  ⟨ Prototype for twounprime 295 ⟩
  {
    *a = ap/(1 - g + ap * g);
    if (bp ≡ HUGE_VAL) *b = HUGE_VAL;
    else *b = (1 + ap * g/(1 - g)) * bp;
  }
```

This code is used in section 266.

297. *abgg2ab* assume a, b, g, and *g1* are given this does the similarity translation that you would expect it should by converting it to the reduced optical properties and then transforming back using the new value of g

```
⟨ Prototype for abgg2ab 297 ⟩ ≡
  void abgg2ab(double a1, double b1, double g1, double g2, double *a2, double *b2)
```

This code is used in sections 267 and 298.

298.
```
⟨ Definition for abgg2ab 298 ⟩ ≡
  ⟨ Prototype for abgg2ab 297 ⟩
  {
    double a, b;
    twoprime(a1, b1, g1, &a, &b);
    twounprime(a, b, g2, a2, b2);
  }
```

This code is used in section 266.

299. *abgb2ag* translates reduced optical properties to unreduced values assuming that the new optical thickness is given i.e., *a1* and *b1* are a' and b' for $g = 0$. This routine then finds the appropriate anisotropy and albedo which correspond to an optical thickness *b2*.

If both *b1* and *b2* are zero then just assume $g = 0$ for the unreduced values.

```
⟨ Prototype for abgb2ag 299 ⟩ ≡
  void abgb2ag(double a1, double b1, double b2, double *a2, double *g2)
```

This code is used in sections 267 and 300.

300. ⟨ Definition for *abgb2ag* 300 ⟩ ≡

```
⟨ Prototype for abgb2ag 299 ⟩
{
  if (b1 ≡ 0 ∨ b2 ≡ 0) {
    *a2 = a1;
    *g2 = 0;
  }
  if (b2 < b1) b2 = b1;
  if (a1 ≡ 0) *a2 = 0.0;
  else {
    if (a1 ≡ 1) *a2 = 1.0;
    else {
      if (b1 ≡ 0 ∨ b2 ≡ HUGE_VAL) *a2 = a1;
      else *a2 = 1 + b1/b2 * (a1 − 1);
    }
  }
  if (*a2 ≡ 0 ∨ b2 ≡ 0 ∨ b2 ≡ HUGE_VAL) *g2 = 0.5;
  else *g2 = (1 − b1/b2)/(*a2);
}
```

This code is used in section 266.

301. Guessing an inverse.
This routine is not used anymore.

```
⟨ Prototype for slow_guess 301 ⟩ ≡
  void slow_guess(struct measure_type m, struct invert_type *r, double *a, double *b, double *g)
```

This code is used in section 302.

302.
```
⟨ Definition for slow_guess 302 ⟩ ≡
  ⟨ Prototype for slow_guess 301 ⟩
  {
    double fmin = 10.0;
    double fval;
    double *x;
    x = dvector(1, 2);
    switch (r→search) {
    case FIND_A: ⟨ Slow guess for a alone 303 ⟩
      break;
    case FIND_B: ⟨ Slow guess for b alone 304 ⟩
      break;
    case FIND_AB: case FIND_AG: ⟨ Slow guess for a and b or a and g 305 ⟩
      break;
    }
    *a = r→slab.a;
    *b = r→slab.b;
    *g = r→slab.g;
    free_dvector(x, 1, 2);
  }
```

303.
```
⟨ Slow guess for a alone 303 ⟩ ≡
  r→slab.b = HUGE_VAL;
  r→slab.g = r→default_g;
  Set_Calc_State(m, *r);
  for (r→slab.a = 0.0; r→slab.a ≤ 1.0; r→slab.a += 0.1) {
    fval = Find_A_fn(a2acalc(r→slab.a));
    if (fval < fmin) {
      r→a = r→slab.a;
      fmin = fval;
    }
  }
  r→slab.a = r→a;
```

This code is used in section 302.

304. Presumably the only time that this will need to be called is when the albedo is fixed or is one. For now, I'll just assume that it is one.

```
⟨ Slow guess for b alone 304 ⟩ ≡
  r→slab.a = 1;
  r→slab.g = r→default_g;
  Set_Calc_State(m, *r);
  for (r→slab.b = 1/32.0; r→slab.b ≤ 32; r→slab.b *= 2) {
    fval = Find_B_fn(b2bcalc(r→slab.b));
    if (fval < fmin) {
      r→b = r→slab.b;
      fmin = fval;
    }
  }
  r→slab.b = r→b;
```

This code is used in section 302.

305.

```
⟨ Slow guess for a and b or a and g 305 ⟩ ≡
  {
    double min_a, min_b, min_g;
    if (¬Valid_Grid(m, r→search)) Fill_Grid(m, *r);
    Near_Grid_Points(m.m_r, m.m_t, r→search, &min_a, &min_b, &min_g);
    r→slab.a = min_a;
    r→slab.b = min_b;
    r→slab.g = min_g;
  }
```

This code is used in section 302.

306.

```
⟨ Prototype for quick_guess 306 ⟩ ≡
  void quick_guess(struct measure_type m, struct invert_type r, double *a, double *b, double *g)
```

This code is used in sections 267 and 307.

307.

```
⟨ Definition for quick_guess 307 ⟩ ≡
  ⟨ Prototype for quick_guess 306 ⟩
  {
    double UR1, UT1, rd, td, tc, rc, bprime, aprime, alpha, beta, logr;
    Estimate_RT(m, r, &UR1, &UT1, &rd, &rc, &td, &tc);
    ⟨ Estimate aprime 308 ⟩
    switch (m.num_measures) {
    case 1: ⟨ Guess when only reflection is known 310 ⟩
      break;
    case 2: ⟨ Guess when reflection and transmission are known 311 ⟩
      break;
    case 3: ⟨ Guess when all three measurements are known 312 ⟩
      break;
    }
    ⟨ Clean up guesses 317 ⟩
  }
```

This code is used in section 266.

308. ⟨ Estimate *aprime* 308 ⟩ ≡

```
if (UT1 ≡ 1) aprime = 1.0;
else if (rd/(1 − UT1) ≥ 0.1) {
  double tmp = (1 − rd − UT1)/(1 − UT1);
  aprime = 1 − 4.0/9.0 ∗ tmp ∗ tmp;
}
else if (rd < 0.05 ∧ UT1 < 0.4) aprime = 1 − (1 − 10 ∗ rd) ∗ (1 − 10 ∗ rd);
else if (rd < 0.1 ∧ UT1 < 0.4) aprime = 0.5 + (rd − 0.05) ∗ 4;
else {
  double tmp = (1 − 4 ∗ rd − UT1)/(1 − UT1);
  aprime = 1 − tmp ∗ tmp;
}
```

This code is used in section 307.

309. ⟨ Estimate *bprime* 309 ⟩ ≡

```
if (rd < 0.01) {
  bprime = What_Is_B(r.slab, UT1);
  fprintf(stderr, "low␣rd<0.01!␣ut1=%f␣aprime=%f␣bprime=%f\n", UT1, aprime, bprime);
}
else if (UT1 ≤ 0) bprime = HUGE_VAL;
else if (UT1 > 0.1) bprime = 2 ∗ exp(5 ∗ (rd − UT1) ∗ log(2.0));
else {
  alpha = 1/log(0.05/1.0);
  beta = log(1.0)/log(0.05/1.0);
  logr = log(UR1);
  bprime = log(UT1) − beta ∗ log(0.05) + beta ∗ logr;
  bprime /= alpha ∗ log(0.05) − alpha ∗ logr − 1;
}
```

This code is used in sections 311, 315, and 316.

310.

⟨ Guess when only reflection is known 310 ⟩ ≡

```
∗g = r.default_g;
∗a = aprime/(1 − ∗g + aprime ∗ (∗g));
∗b = HUGE_VAL;
```

This code is used in section 307.

311. ⟨ Guess when reflection and transmission are known 311 ⟩ ≡

```
⟨ Estimate bprime 309 ⟩
∗g = r.default_g;
∗a = aprime/(1 − ∗g + aprime ∗ ∗g);
∗b = bprime/(1 − ∗a ∗ ∗g);
```

This code is used in section 307.

312. ⟨ Guess when all three measurements are known 312 ⟩ ≡
```
switch (r.search) {
case FIND_A: ⟨ Guess when finding albedo 313 ⟩
  break;
case FIND_B: ⟨ Guess when finding optical depth 314 ⟩
  break;
case FIND_AB: ⟨ Guess when finding the albedo and optical depth 315 ⟩
  break;
case FIND_AG: ⟨ Guess when finding anisotropy and albedo 316 ⟩
  break;
}
```
This code is used in section 307.

313.
⟨ Guess when finding albedo 313 ⟩ ≡
```
*g = r.default_g;
*a = aprime/(1 - *g + aprime * *g);
*b = What_Is_B(r.slab, m.m_u);
```
This code is used in section 312.

314.
⟨ Guess when finding optical depth 314 ⟩ ≡
```
*g = r.default_g;
*a = 0.0;
*b = What_Is_B(r.slab, m.m_u);
```
This code is used in section 312.

315.
⟨ Guess when finding the albedo and optical depth 315 ⟩ ≡
```
*g = r.default_g;
if (*g ≡ 1) *a = 0.0;
else *a = aprime/(1 - *g + aprime * *g);
⟨ Estimate bprime 309 ⟩
if (bprime ≡ HUGE_VAL ∨ *a * *g ≡ 1) *b = HUGE_VAL;
else *b = bprime/(1 - *a * *g);
```
This code is used in section 312.

316.
⟨ Guess when finding anisotropy and albedo 316 ⟩ ≡
```
*b = What_Is_B(r.slab, m.m_u);
if (*b ≡ HUGE_VAL ∨ *b ≡ 0) {
  *a = aprime;
  *g = r.default_g;
}
else {
  ⟨ Estimate bprime 309 ⟩
  *a = 1 + bprime * (aprime - 1)/(*b);
  if (*a < 0.1) *g = 0.0;
  else *g = (1 - bprime/(*b))/(*a);
}
```
This code is used in section 312.

317.

⟨ Clean up guesses 317 ⟩ ≡

```
if (*a < 0) *a = 0.0;
if (*g < 0) *g = 0.0;
else if (*g ≥ 1) *g = 0.5;
```

This code is used in section 307.

318. Some debugging stuff.

319. ⟨ Prototype for *Set_Debugging* 319 ⟩ ≡
```
void Set_Debugging(unsigned long debug_level)
```
This code is used in sections 267 and 320.

320.
⟨ Definition for *Set_Debugging* 320 ⟩ ≡
```
⟨ Prototype for Set_Debugging 319 ⟩
{
  g_util_debugging = debug_level;
}
```
This code is used in section 266.

321.
⟨ Prototype for *Debug* 321 ⟩ ≡
```
int Debug(unsigned long mask)
```
This code is used in sections 267 and 322.

322.
⟨ Definition for *Debug* 322 ⟩ ≡
```
⟨ Prototype for Debug 321 ⟩
{
  if (g_util_debugging & mask) return 1;
  else return 0;
}
```
This code is used in section 266.

323.
⟨ Prototype for *Print_Invert_Type* 323 ⟩ ≡
```
void Print_Invert_Type(struct invert_type r)
```
This code is used in sections 267 and 324.

324.

⟨ Definition for *Print_Invert_Type* 324 ⟩ ≡
⟨ Prototype for *Print_Invert_Type* 323 ⟩
{
fprintf(*stderr*, "\n");
fprintf(*stderr*, "default␣␣␣a=%10.5f␣␣␣␣b=%10.5f␣␣␣␣␣g=%10.5f\n", *r.default_a*, *r.default_b*, *r.default_g*);
fprintf(*stderr*, "slab␣␣␣␣␣␣a=%10.5f␣␣␣␣b=%10.5f␣␣␣␣␣g=%10.5f\n", *r.slab.a*, *r.slab.b*, *r.slab.g*);
fprintf(*stderr*, "n␣␣␣␣␣␣␣top=%10.5f␣mid=%10.5f␣␣bot=%10.5f\n", *r.slab.n_top_slide*, *r.slab.n_slab*,
r.slab.n_bottom_slide);
fprintf(*stderr*, "thick␣␣top=%10.5f␣cos=%10.5f␣␣bot=%10.5f\n", *r.slab.b_top_slide*, *r.slab.cos_angle*,
r.slab.b_bottom_slide);
fprintf(*stderr*, "search␣=␣%d␣quadrature␣points␣=␣%d\n", *r.search*, *r.method.quad_pts*);
fprintf(*stderr*, "default_a␣=␣%10.5f\n", *r.default_a*);
fprintf(*stderr*, "default_b␣=␣%10.5f\n", *r.default_b*);
fprintf(*stderr*, "default_g␣=␣%10.5f\n", *r.default_g*);
fprintf(*stderr*, "default_mua␣=␣%10.5f\n", *r.default_mua*);
fprintf(*stderr*, "default_mus␣=␣%10.5f\n", *r.default_mus*);
}
This code is used in section 266.

325.

⟨ Prototype for *Print_Measure_Type* 325 ⟩ ≡
void *Print_Measure_Type*(**struct measure_type** *m*)
This code is used in sections 267 and 326.

326.

```
⟨ Definition for Print_Measure_Type 326 ⟩ ≡
  ⟨ Prototype for Print_Measure_Type 325 ⟩
  {
    fprintf(stderr, "\n");
    fprintf(stderr, "#␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣Beam␣diameter␣=␣%7.1f␣mm\n", m.d_beam);
    fprintf(stderr, "#␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣Sample␣thickness␣=␣%7.1f␣mm\n", m.slab_thickness);
    fprintf(stderr, "#␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣Top␣slide␣thickness␣=␣%7.1f␣mm\n",
        m.slab_top_slide_thickness);
    fprintf(stderr, "#␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣Bottom␣slide␣thickness␣=␣%7.1f␣mm\n",
        m.slab_bottom_slide_thickness);
    fprintf(stderr, "#␣␣␣␣␣␣␣␣␣␣␣Sample␣index␣of␣refraction␣=␣%7.3f\n", m.slab_index);
    fprintf(stderr, "#␣␣␣␣␣␣␣␣␣Top␣slide␣index␣of␣refraction␣=␣%7.3f\n", m.slab_top_slide_index);
    fprintf(stderr, "#␣␣␣␣␣␣Bottom␣slide␣index␣of␣refraction␣=␣%7.3f\n", m.slab_bottom_slide_index);
    fprintf(stderr, "#␣␣␣␣␣Fraction␣unscattered␣light␣in␣M_R␣=␣%7.1f␣%%\n",
        m.fraction_of_rc_in_mr * 100);
    fprintf(stderr, "#␣␣␣␣␣Fraction␣unscattered␣light␣in␣M_T␣=␣%7.1f␣%%\n",
        m.fraction_of_tc_in_mt * 100);
    fprintf(stderr, "#␣\n");
    fprintf(stderr, "#␣Reflection␣sphere\n");
    fprintf(stderr, "#␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣sphere␣diameter␣=␣%7.1f␣mm\n", m.d_sphere_r);
    fprintf(stderr, "#␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣sample␣port␣diameter␣=␣%7.1f␣mm\n",
        2 * m.d_sphere_r * sqrt(m.as_r));
    fprintf(stderr, "#␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣entrance␣port␣diameter␣=␣%7.1f␣mm\n",
        2 * m.d_sphere_r * sqrt(m.ae_r));
    fprintf(stderr, "#␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣detector␣port␣diameter␣=␣%7.1f␣mm\n",
        2 * m.d_sphere_r * sqrt(m.ad_r));
    fprintf(stderr, "#␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣wall␣reflectance␣=␣%7.1f␣%%\n", m.rw_r * 100);
    fprintf(stderr, "#␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣standard␣reflectance␣=␣%7.1f␣%%\n", m.rstd_r * 100);
    fprintf(stderr, "#␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣detector␣reflectance␣=␣%7.1f␣%%\n", m.rd_r * 100);
    fprintf(stderr, "#␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣spheres␣=␣%7d\n", m.num_spheres);
    fprintf(stderr, "#␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣measures␣=␣%7d\n", m.num_measures);
    fprintf(stderr, "#␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣␣method␣=␣%7d\n", m.method);
    fprintf(stderr, "area_r␣as=%10.5f␣␣ad=%10.5f␣␣␣␣ae=%10.5f␣␣aw=%10.5f\n", m.as_r, m.ad_r,
        m.ae_r, m.aw_r);
    fprintf(stderr, "refls␣␣rd=%10.5f␣␣rw=%10.5f␣␣rstd=%10.5f␣␣␣f=%10.5f\n", m.rd_r, m.rw_r,
        m.rstd_r, m.f_r);
    fprintf(stderr, "area_t␣as=%10.5f␣␣ad=%10.5f␣␣␣␣ae=%10.5f␣␣aw=%10.5f\n", m.as_t, m.ad_t,
        m.ae_t, m.aw_t);
    fprintf(stderr, "refls␣␣rd=%10.5f␣␣rw=%10.5f␣␣rstd=%10.5f\n", m.rd_t, m.rw_t, m.rstd_t);
    fprintf(stderr, "lost␣␣ur1=%10.5f␣ut1=%10.5f␣␣␣uru=%10.5f␣␣utu=%10.5f\n", m.ur1_lost,
        m.ut1_lost, m.utu_lost, m.utu_lost);
  }
```

This code is used in section 266.

327. Index. Here is a cross-reference table for the inverse adding-doubling program. All sections in which an identifier is used are listed with that identifier, except that reserved words are indexed only when they appear in format definitions, and the appearances of identifiers in section names are not indexed. Underlined entries correspond to where the identifier was declared. Error messages and a few other things like "ASCII code dependencies" are indexed here too.

⟨ Allocate local simplex variables 227 ⟩ Used in sections 226, 246, 251, 257, and 262.
⟨ Calc M_R and M_T for dual beam sphere 192 ⟩ Used in section 185.
⟨ Calc M_R and M_T for no spheres 188 ⟩ Used in section 185.
⟨ Calc M_R and M_T for single beam sphere 189, 191 ⟩ Used in section 185.
⟨ Calc M_R and M_T for two spheres 193 ⟩ Used in section 185.
⟨ Calculate and Print the Forward Calculation 7, 8, 9, 10 ⟩ Used in section 2.
⟨ Calculate and write optical properties 12, 38 ⟩ Used in sections 2 and 34.
⟨ Calculate specular reflection and transmission 270 ⟩ Used in section 269.
⟨ Calculate the deviation 194 ⟩ Used in section 185.
⟨ Calculate the unscattered transmission and reflection 276 ⟩ Used in section 275.
⟨ Check MU 58 ⟩ Used in section 55.
⟨ Check MR for zero or one spheres 56 ⟩ Used in section 55.
⟨ Check MT for zero or one spheres 57 ⟩ Used in section 55.
⟨ Check for bad values of Tc 271 ⟩ Used in section 269.
⟨ Check sphere parameters 59, 60 ⟩ Used in section 55.
⟨ Choose the best node of the a and b simplex 231 ⟩ Used in section 226.
⟨ Choose the best node of the a and g simplex 249 ⟩ Used in section 246.
⟨ Choose the best node of the ba and g simplex 260 ⟩ Used in section 257.
⟨ Choose the best node of the bs and g simplex 265 ⟩ Used in section 262.
⟨ Choose the best node of the b and g simplex 255 ⟩ Used in section 251.
⟨ Clean up guesses 317 ⟩ Used in section 307.
⟨ Command-line changes to m 17 ⟩ Used in section 2.
⟨ Command-line changes to r 14 ⟩ Used in sections 2 and 12.
⟨ Count command-line measurements 19 ⟩ Used in section 2.
⟨ Debug info for estimate RT 279 ⟩ Used in section 275.
⟨ Declare variables for *main* 4, 36 ⟩ Used in sections 2 and 34.
⟨ Definition for *Allocate_Grid* 149 ⟩ Used in section 127.
⟨ Definition for *Calculate_Distance_With_Corrections* 185 ⟩ Used in section 127.
⟨ Definition for *Calculate_Distance* 181 ⟩ Used in section 127.
⟨ Definition for *Calculate_Grid_Distance* 183 ⟩ Used in section 127.
⟨ Definition for *Calculate_MR_MT* 83 ⟩ Used in section 45.
⟨ Definition for *Calculate_Minimum_MR* 85 ⟩ Used in section 45.
⟨ Definition for *Debug* 322 ⟩ Used in section 266.
⟨ Definition for *Estimate_RT* 275 ⟩ Used in section 266.
⟨ Definition for *Fill_AB_Grid* 166 ⟩ Used in section 127.
⟨ Definition for *Fill_AG_Grid* 170 ⟩ Used in section 127.
⟨ Definition for *Fill_BG_Grid* 173 ⟩ Used in section 127.
⟨ Definition for *Fill_BaG_Grid* 175 ⟩ Used in section 127.
⟨ Definition for *Fill_BsG_Grid* 177 ⟩ Used in section 127.
⟨ Definition for *Fill_Grid* 179 ⟩ Used in section 127.
⟨ Definition for *Find_AB_fn* 201 ⟩ Used in section 127.
⟨ Definition for *Find_AG_fn* 199 ⟩ Used in section 127.
⟨ Definition for *Find_A_fn* 207 ⟩ Used in section 127.
⟨ Definition for *Find_BG_fn* 213 ⟩ Used in section 127.
⟨ Definition for *Find_B_fn* 209 ⟩ Used in section 127.
⟨ Definition for *Find_BaG_fn* 215 ⟩ Used in section 127.
⟨ Definition for *Find_Ba_fn* 203 ⟩ Used in section 127.
⟨ Definition for *Find_BsG_fn* 217 ⟩ Used in section 127.
⟨ Definition for *Find_Bs_fn* 205 ⟩ Used in section 127.
⟨ Definition for *Find_G_fn* 211 ⟩ Used in section 127.
⟨ Definition for *Gain_11* 134 ⟩ Used in section 127.
⟨ Definition for *Gain_22* 136 ⟩ Used in section 127.

⟨ Definition for *Gain* 132 ⟩ Used in section 127.
⟨ Definition for *Get_Calc_State* 145 ⟩ Used in section 127.
⟨ Definition for *Grid_ABG* 151 ⟩ Used in section 127.
⟨ Definition for *Initialize_Measure* 74 ⟩ Used in section 45.
⟨ Definition for *Initialize_Result* 66 ⟩ Used in section 45.
⟨ Definition for *Inverse_RT* 49 ⟩ Used in section 45.
⟨ Definition for *Max_Light_Loss* 221 ⟩ Used in section 127.
⟨ Definition for *MinMax_MR_MT* 87 ⟩ Used in section 45.
⟨ Definition for *Near_Grid_Points* 161 ⟩ Used in section 127.
⟨ Definition for *Print_Invert_Type* 324 ⟩ Used in section 266.
⟨ Definition for *Print_Measure_Type* 326 ⟩ Used in section 266.
⟨ Definition for *RT_Flip* 163 ⟩ Used in section 127.
⟨ Definition for *Read_Data_Legend* 126 ⟩ Used in section 96.
⟨ Definition for *Read_Data_Line_Per_Labels* 106 ⟩ Used in section 96.
⟨ Definition for *Read_Data_Line* 105 ⟩ Used in section 96.
⟨ Definition for *Read_Header* 100 ⟩ Used in section 96.
⟨ Definition for *Same_Calc_State* 147 ⟩ Used in section 127.
⟨ Definition for *Set_Calc_State* 143 ⟩ Used in section 127.
⟨ Definition for *Set_Debugging* 320 ⟩ Used in section 266.
⟨ Definition for *Spheres_Inverse_RT2* 89 ⟩ Used in section 45.
⟨ Definition for *Spheres_Inverse_RT* 76 ⟩ Used in section 45.
⟨ Definition for *Two_Sphere_R* 138 ⟩ Used in section 127.
⟨ Definition for *Two_Sphere_T* 140 ⟩ Used in section 127.
⟨ Definition for *U_Find_AB* 226 ⟩ Used in section 223.
⟨ Definition for *U_Find_AG* 246 ⟩ Used in section 223.
⟨ Definition for *U_Find_A* 239 ⟩ Used in section 223.
⟨ Definition for *U_Find_BG* 251 ⟩ Used in section 223.
⟨ Definition for *U_Find_BaG* 257 ⟩ Used in section 223.
⟨ Definition for *U_Find_Ba* 237 ⟩ Used in section 223.
⟨ Definition for *U_Find_BsG* 262 ⟩ Used in section 223.
⟨ Definition for *U_Find_Bs* 235 ⟩ Used in section 223.
⟨ Definition for *U_Find_B* 243 ⟩ Used in section 223.
⟨ Definition for *U_Find_G* 241 ⟩ Used in section 223.
⟨ Definition for *Valid_Grid* 153 ⟩ Used in section 127.
⟨ Definition for *What_Is_B* 269 ⟩ Used in section 266.
⟨ Definition for *Write_Header* 114 ⟩ Used in section 96.
⟨ Definition for *a2acalc* 282 ⟩ Used in section 266.
⟨ Definition for *abg_distance* 159 ⟩ Used in section 127.
⟨ Definition for *abgb2ag* 300 ⟩ Used in section 266.
⟨ Definition for *abgg2ab* 298 ⟩ Used in section 266.
⟨ Definition for *acalc2a* 284 ⟩ Used in section 266.
⟨ Definition for *b2bcalc* 290 ⟩ Used in section 266.
⟨ Definition for *bcalc2b* 292 ⟩ Used in section 266.
⟨ Definition for *check_magic* 112 ⟩ Used in section 96.
⟨ Definition for *determine_search* 62 ⟩ Used in section 45.
⟨ Definition for *ez_Inverse_RT* 72 ⟩ Used in section 45.
⟨ Definition for *fill_grid_entry* 164 ⟩ Used in section 127.
⟨ Definition for *g2gcalc* 286 ⟩ Used in section 266.
⟨ Definition for *gcalc2g* 288 ⟩ Used in section 266.
⟨ Definition for *maxloss* 219 ⟩ Used in section 127.
⟨ Definition for *measure_OK* 55 ⟩ Used in section 45.
⟨ Definition for *print_maybe* 124 ⟩ Used in section 96.

⟨ Definition for *quick_guess* 307 ⟩ Used in section 266.
⟨ Definition for *read_number* 110 ⟩ Used in section 96.
⟨ Definition for *remove_comment* 122 ⟩ Used in section 96.
⟨ Definition for *remove_first_char* 123 ⟩ Used in section 96.
⟨ Definition for *remove_whitespace* 121 ⟩ Used in section 96.
⟨ Definition for *skip_white* 108 ⟩ Used in section 96.
⟨ Definition for *slow_guess* 302 ⟩
⟨ Definition for *twoprime* 294 ⟩ Used in section 266.
⟨ Definition for *twounprime* 296 ⟩ Used in section 266.
⟨ Determine calculated light to be used 186, 187 ⟩ Used in section 185.
⟨ Estimate the backscattered reflection 277 ⟩ Used in section 275.
⟨ Estimate the scattered transmission 278 ⟩ Used in section 275.
⟨ Estimate *aprime* 308 ⟩ Used in section 307.
⟨ Estimate *bprime* 309 ⟩ Used in sections 311, 315, and 316.
⟨ Evaluate the *BaG* simplex at the nodes 259 ⟩ Used in section 257.
⟨ Evaluate the *BsG* simplex at the nodes 264 ⟩ Used in section 262.
⟨ Evaluate the *bg* simplex at the nodes 254 ⟩ Used in section 251.
⟨ Evaluate the a and b simplex at the nodes 230 ⟩ Used in section 226.
⟨ Evaluate the a and g simplex at the nodes 248 ⟩ Used in section 246.
⟨ Exit with bad input data 50 ⟩ Used in section 49.
⟨ Fill r with reasonable values 67, 68, 69, 70 ⟩ Used in section 66.
⟨ Find the optical properties 51 ⟩ Used in section 49.
⟨ Find thickness when multiple internal reflections are present 273 ⟩ Used in section 269.
⟨ Free simplex data structures 233 ⟩ Used in sections 226, 246, 251, 257, and 262.
⟨ Generate next albedo using j 168 ⟩ Used in sections 166 and 170.
⟨ Get the initial a, b, and g 228 ⟩ Used in sections 226, 246, 251, 257, and 262.
⟨ Guess when all three measurements are known 312 ⟩ Used in section 307.
⟨ Guess when finding albedo 313 ⟩ Used in section 312.
⟨ Guess when finding anisotropy and albedo 316 ⟩ Used in section 312.
⟨ Guess when finding optical depth 314 ⟩ Used in section 312.
⟨ Guess when finding the albedo and optical depth 315 ⟩ Used in section 312.
⟨ Guess when only reflection is known 310 ⟩ Used in section 307.
⟨ Guess when reflection and transmission are known 311 ⟩ Used in section 307.
⟨ Handle options 6 ⟩ Used in section 2.
⟨ Improve result using Monte Carlo 16 ⟩ Used in section 12.
⟨ Include files for *main* 3, 35 ⟩ Used in sections 2 and 34.
⟨ Initialize the nodes of the a and b simplex 229 ⟩ Used in section 226.
⟨ Initialize the nodes of the a and g simplex 247 ⟩ Used in section 246.
⟨ Initialize the nodes of the *ba* and g simplex 258 ⟩ Used in section 257.
⟨ Initialize the nodes of the *bs* and g simplex 263 ⟩ Used in section 262.
⟨ Initialize the nodes of the b and g simplex 253 ⟩ Used in section 251.
⟨ Iteratively solve for b 244 ⟩ Used in section 243.
⟨ Local Variables for Calculation 13 ⟩ Used in section 12.
⟨ Nonworking code 167 ⟩
⟨ One parameter deviation 195 ⟩ Used in section 194.
⟨ One parameter search 63 ⟩ Used in section 62.
⟨ Print basic sphere and MC effects 52 ⟩ Used in section 49.
⟨ Print diagnostics 197 ⟩ Used in section 185.
⟨ Print results function 25 ⟩ Used in section 2.
⟨ Process the header 37 ⟩ Used in section 34.
⟨ Prototype for *Allocate_Grid* 148 ⟩ Used in sections 128 and 149.
⟨ Prototype for *Calculate_Distance_With_Corrections* 184 ⟩ Used in sections 128 and 185.

⟨ Prototype for *Calculate_Distance* 180 ⟩ Used in sections 128 and 181.
⟨ Prototype for *Calculate_Grid_Distance* 182 ⟩ Used in sections 128 and 183.
⟨ Prototype for *Calculate_MR_MT* 82 ⟩ Used in sections 46 and 83.
⟨ Prototype for *Calculate_Minimum_MR* 84 ⟩ Used in sections 46 and 85.
⟨ Prototype for *Debug* 321 ⟩ Used in sections 267 and 322.
⟨ Prototype for *Estimate_RT* 274 ⟩ Used in sections 267 and 275.
⟨ Prototype for *Fill_AB_Grid* 165 ⟩ Used in sections 127 and 166.
⟨ Prototype for *Fill_AG_Grid* 169 ⟩ Used in sections 127 and 170.
⟨ Prototype for *Fill_BG_Grid* 172 ⟩ Used in sections 128 and 173.
⟨ Prototype for *Fill_BaG_Grid* 174 ⟩ Used in sections 128 and 175.
⟨ Prototype for *Fill_BsG_Grid* 176 ⟩ Used in sections 128 and 177.
⟨ Prototype for *Fill_Grid* 178 ⟩ Used in sections 128 and 179.
⟨ Prototype for *Find_AB_fn* 200 ⟩ Used in sections 128 and 201.
⟨ Prototype for *Find_AG_fn* 198 ⟩ Used in sections 128 and 199.
⟨ Prototype for *Find_A_fn* 206 ⟩ Used in sections 128 and 207.
⟨ Prototype for *Find_BG_fn* 212 ⟩ Used in sections 128 and 213.
⟨ Prototype for *Find_B_fn* 208 ⟩ Used in sections 128 and 209.
⟨ Prototype for *Find_BaG_fn* 214 ⟩ Used in sections 128 and 215.
⟨ Prototype for *Find_Ba_fn* 202 ⟩ Used in sections 128 and 203.
⟨ Prototype for *Find_BsG_fn* 216 ⟩ Used in sections 128 and 217.
⟨ Prototype for *Find_Bs_fn* 204 ⟩ Used in sections 128 and 205.
⟨ Prototype for *Find_G_fn* 210 ⟩ Used in sections 128 and 211.
⟨ Prototype for *Gain_11* 133 ⟩ Used in sections 128 and 134.
⟨ Prototype for *Gain_22* 135 ⟩ Used in sections 128 and 136.
⟨ Prototype for *Gain* 131 ⟩ Used in sections 128 and 132.
⟨ Prototype for *Get_Calc_State* 144 ⟩ Used in sections 128 and 145.
⟨ Prototype for *Grid_ABG* 150 ⟩ Used in sections 128 and 151.
⟨ Prototype for *Initialize_Measure* 73 ⟩ Used in sections 46 and 74.
⟨ Prototype for *Initialize_Result* 65 ⟩ Used in sections 46 and 66.
⟨ Prototype for *Inverse_RT* 48 ⟩ Used in sections 46 and 49.
⟨ Prototype for *Max_Light_Loss* 220 ⟩ Used in sections 128 and 221.
⟨ Prototype for *MinMax_MR_MT* 86 ⟩ Used in sections 46 and 87.
⟨ Prototype for *Near_Grid_Points* 160 ⟩ Used in sections 128 and 161.
⟨ Prototype for *Print_Invert_Type* 323 ⟩ Used in sections 267 and 324.
⟨ Prototype for *Print_Measure_Type* 325 ⟩ Used in sections 267 and 326.
⟨ Prototype for *RT_Flip* 162 ⟩ Used in sections 128 and 163.
⟨ Prototype for *Read_Data_Legend* 125 ⟩ Used in section 126.
⟨ Prototype for *Read_Data_Line* 104 ⟩ Used in sections 97 and 105.
⟨ Prototype for *Read_Header* 99 ⟩ Used in sections 97 and 100.
⟨ Prototype for *Same_Calc_State* 146 ⟩ Used in sections 128 and 147.
⟨ Prototype for *Set_Calc_State* 142 ⟩ Used in sections 128 and 143.
⟨ Prototype for *Set_Debugging* 319 ⟩ Used in sections 267 and 320.
⟨ Prototype for *Spheres_Inverse_RT2* 88 ⟩ Used in sections 46, 47, and 89.
⟨ Prototype for *Spheres_Inverse_RT* 75 ⟩ Used in sections 47 and 76.
⟨ Prototype for *Two_Sphere_R* 137 ⟩ Used in sections 128 and 138.
⟨ Prototype for *Two_Sphere_T* 139 ⟩ Used in sections 128 and 140.
⟨ Prototype for *U_Find_AB* 225 ⟩ Used in sections 224 and 226.
⟨ Prototype for *U_Find_AG* 245 ⟩ Used in sections 224 and 246.
⟨ Prototype for *U_Find_A* 238 ⟩ Used in sections 224 and 239.
⟨ Prototype for *U_Find_BG* 250 ⟩ Used in sections 224 and 251.
⟨ Prototype for *U_Find_BaG* 256 ⟩ Used in sections 224 and 257.
⟨ Prototype for *U_Find_Ba* 236 ⟩ Used in sections 224 and 237.

⟨ Prototype for *U_Find_BsG* 261 ⟩ Used in sections 224 and 262.
⟨ Prototype for *U_Find_Bs* 234 ⟩ Used in sections 224 and 235.
⟨ Prototype for *U_Find_B* 242 ⟩ Used in sections 224 and 243.
⟨ Prototype for *U_Find_G* 240 ⟩ Used in sections 224 and 241.
⟨ Prototype for *Valid_Grid* 152 ⟩ Used in sections 128 and 153.
⟨ Prototype for *What_Is_B* 268 ⟩ Used in sections 267 and 269.
⟨ Prototype for *Write_Header* 113 ⟩ Used in sections 97 and 114.
⟨ Prototype for *a2acalc* 281 ⟩ Used in sections 267 and 282.
⟨ Prototype for *abg_distance* 158 ⟩ Used in sections 128 and 159.
⟨ Prototype for *abgb2ag* 299 ⟩ Used in sections 267 and 300.
⟨ Prototype for *abgg2ab* 297 ⟩ Used in sections 267 and 298.
⟨ Prototype for *acalc2a* 283 ⟩ Used in sections 267 and 284.
⟨ Prototype for *b2bcalc* 289 ⟩ Used in sections 267 and 290.
⟨ Prototype for *bcalc2b* 291 ⟩ Used in sections 267 and 292.
⟨ Prototype for *check_magic* 111 ⟩ Used in section 112.
⟨ Prototype for *determine_search* 61 ⟩ Used in sections 46 and 62.
⟨ Prototype for *ez_Inverse_RT* 71 ⟩ Used in sections 46, 47, and 72.
⟨ Prototype for *g2gcalc* 285 ⟩ Used in sections 267 and 286.
⟨ Prototype for *gcalc2g* 287 ⟩ Used in sections 267 and 288.
⟨ Prototype for *maxloss* 218 ⟩ Used in sections 128 and 219.
⟨ Prototype for *measure_OK* 54 ⟩ Used in sections 46 and 55.
⟨ Prototype for *quick_guess* 306 ⟩ Used in sections 267 and 307.
⟨ Prototype for *read_number* 109 ⟩ Used in section 110.
⟨ Prototype for *skip_white* 107 ⟩ Used in section 108.
⟨ Prototype for *slow_guess* 301 ⟩ Used in section 302.
⟨ Prototype for *twoprime* 293 ⟩ Used in sections 267 and 294.
⟨ Prototype for *twounprime* 295 ⟩ Used in sections 267 and 296.
⟨ Put final values in result 232 ⟩ Used in sections 226, 235, 237, 239, 241, 243, 246, 251, 257, and 262.
⟨ Read coefficients for reflection sphere 101 ⟩ Used in section 100.
⟨ Read coefficients for transmission sphere 102 ⟩ Used in section 100.
⟨ Read info about measurements 103 ⟩ Used in section 100.
⟨ Save command-line for use later 5 ⟩ Used in section 2.
⟨ Slow guess for a alone 303 ⟩ Used in section 302.
⟨ Slow guess for a and b or a and g 305 ⟩ Used in section 302.
⟨ Slow guess for b alone 304 ⟩ Used in section 302.
⟨ Solve if multiple internal reflections are not present 272 ⟩ Used in section 269.
⟨ Structs to export from IAD Types 42, 43, 44 ⟩ Used in section 39.
⟨ Tests for invalid grid 154, 155, 156, 157 ⟩ Used in section 153.
⟨ Two parameter deviation 196 ⟩ Used in section 194.
⟨ Two parameter search 64 ⟩ Used in section 62.
⟨ Unused diffusion fragment 222 ⟩
⟨ Warn and quit for bad options 18 ⟩ Used in section 12.
⟨ Write Header 15 ⟩ Used in section 12.
⟨ Write first sphere info 118 ⟩ Used in section 114.
⟨ Write general sphere info 117 ⟩ Used in section 114.
⟨ Write irradiation info 116 ⟩ Used in section 114.
⟨ Write measure and inversion info 120 ⟩ Used in section 114.
⟨ Write second sphere info 119 ⟩ Used in section 114.
⟨ Write slab info 115 ⟩ Used in section 114.
⟨ Zero *GG* 171 ⟩ Used in sections 166, 170, 173, 175, and 177.
⟨ calculate coefficients function 22, 23 ⟩ Used in section 2.
⟨ handle analysis 78 ⟩ Used in section 76.