

Running the session console

For the few CU staff who provision forms, run sessions and review check-ins.

Starting

```
make db-up
cufa serve
```

- Serves `http://127.0.0.1:8000`. Local only.
- `make demo-console` runs it on demo data with `FakeGoogleClient`: zero Google calls.
- Every screen is also a `cufa` command, so the pipeline runs without the console.

Screens

Path	Screen	Command
<code>/</code>	Connect Google	<code>cufa google connect / status / disconnect</code>
<code>/template</code>	Template setup, both parts	<code>cufa template create / verify / status --part a b</code>
<code>/sessions</code>	Sessions	<code>cufa session list / create / edit</code>
<code>/sessions/{id}</code>	Session detail	<code>cufa provision, cufa session announce, cufa pull</code>
<code>/sessions/{id}/responses</code>	Part B responses	<code>cufa themes</code>
<code>/rotation</code>	Weekly questions	<code>cufa rotation</code>
<code>/shoutouts</code>	Names to link	<code>cufa shoutouts review / link</code>
<code>/review</code>	Review queues	<code>cufa review, cufa decide</code>
<code>/help-requests</code>	Help requests (gated)	<code>cufa help-requests list / ack / close</code>

- `/healthz` checks the database.

Sign-in

- Google sign-in against an allowlist in `.env`. No passwords.

```
CUFA_CONSOLE_ALLOWLIST=alice@civicsunplugged.org,bob@civicsunplugged.org
CUFA_CONSOLE_SECRET=<a long random string>
CUFA_HELP_ALLOWLIST=alice@civicsunplugged.org
```

- **Change `CUFA_CONSOLE_SECRET` from the default.** It signs the session cookie.
- `CUFA_HELP_ALLOWLIST` is a separate subset for `/help-requests`. Blank falls back to `config/help_routing.json` (`docs/safeguarding.md`).

Connect Google (once)

- One staff member grants `.../auth/forms.body` (create, edit, publish) and `.../auth/drive.file` (copy template, read responses).
- Don't drop `drive.file: forms.responses.list` won't accept `forms.body`.
- **Connect as a CU staff account.** It owns the forms (`google-cloud.md`).
- The refresh token is encrypted with `CUFA_ENCRYPTION_KEY`:

```
python -m cufa.crypto keygen
```

Template (once, manual)

- Setting `emailCollectionType` via `forms.batchUpdate` → `updateSettings` has returned `400 INVALID_ARGUMENT`, so a person sets it.
1. Press **Create template**.
 2. Open the link, set **Settings → Responses → Collect email addresses → Verified**.
 3. Press **Verify template**. Green only when the API reads back `VERIFIED`.
- Provisioning is blocked until then. The template is re-verified before every provisioning run; copies keep the setting.

Creating a session

- Fields: title, date and time (local), timezone, duration, grace minutes (default 15, applied both sides), passphrase, cohort.
- Passphrase: one word, 5-10 letters, no homophones (`their/there`), not from this week's materials, never reused (the console warns).
- No passphrase is legal and adjudicates as `not_set`.

During the lesson

1. **Provision form**: copies, sets title and question, publishes, verifies. Safe to press twice.
 2. Share the link (copy button, QR code).
 3. Say the passphrase aloud and show it on screen, for deaf and hard-of-hearing fellows.
 4. **Announce now** as you say it. It stamps `announced_at_utc`, the latency baseline.
 5. **Pull responses** ingests on demand.
- Release the form 15-25 minutes in.

Review

- Needs review, oldest first: one click records a human decision, which is never overwritten.
- AI decisions with reasoning, to spot-check.
- Unresolved addresses: fix the roster and the check-in re-attributes.

Troubleshooting

- Verify stays red: redo the step on the template, not a session copy.
- Publish error, or form not "ready": provision again; it resumes the same form (trap 1).

- No responses: check the form is ready, then time, duration and grace (see ingest warnings).
- Database unreachable: `make db-up`.
- Provision Part B greyed out: Part B template unverified, or teacher question missing. The banner says which.
- "question map is missing": press **Re-check Part B**. It changes no questions.
- Help checkbox missing: nobody in `config/help_routing.json`. Deliberate.
- No "Help requests" nav: not on `CUFA_HELP_ALLOWLIST` (or `config/help_routing.json` if unset).

See also

- `docs/setup/local-dev.md`
- `docs/setup/google-cloud.md`
- `docs/setup/part-b-form.md`
- `docs/safeguarding.md`
- `docs/google-api-traps.md`