Nolan Anderson

EE 384 Classwork 6 Due 26 September 2021


```
clear all; clc; close all;
```


Problem 1:

Histogram Equalization

```
figure
im = imread('lowcontrast.jpg');
subplot(2,1,1); imshow(im), title('Original low contrast jpg');
subplot(2,1,2); imhist(im);

L = 256;
figure
FinVal = my_histeq(im, L); % see function at bottom of PDF.
subplot(2,1,1); imshow(FinVal), title('My histeq function');
subplot(2,1,2); imhist(FinVal);
```





Problem 2:

Edge detection

```
figure
A = imread('lena.bmp');
B = rgb2gray(A);
subplot(2,2,1), imshow(B), title('Original lena.bmp');

% a - roberts
rob = edge(B, 'roberts');
subplot(2,2,2), imshow(rob), title('Roberts Operator');

% b - prewitt
pre = edge(B, 'prewitt');
subplot(2,2,3), imshow(pre), title('Prewitt Operator');
```

```
% c - sobel
sob = edge(B, 'sobel', 'both');
subplot(2,2,4), imshow(sob), title('sobel Operator');
```

Original lena.bmp




Roberts Operator



Prewitt Operator



Sobel Operator



Problem 3:

Laplacian edge sharpening

```
%Input Image
A = im2double(imread('blur_image.jpg'));
mask = [-1 -1 -1; -1 8 -1; -1 -1 -1];

% imfilter for convolution of image and mask
ConvImg = imfilter(A, mask);

% Normalize convolved image
minC = min(ConvImg(:));
maxC = max(ConvImg(:));
ConvImg = (ConvImg - minC) / (maxC - minC);

% Add to original image
Sharp = A + ConvImg;
minA = min(Sharp(:));
```

```
maxA = max(Sharp(:));
Sharp = (Sharp - minA) / (maxA - minA);

Sharp = imadjust(Sharp, [60/255 200/255], [0 1]);

figure
subplot(1,3,1); imshow(A); title('Original Image');
subplot(1,3,2); imshow(ConvImg); title('Laplacian filtered image');
subplot(1,3,3); imshow(Sharp); title('Sharpened Image');
```

Original Image



Laplacian filtered image



Sharpened Image



Functions

```
hist_img(im == k-1) = s(k);
end
end
```

Published with MATLAB® R2020b