

Lexing

Checkpoint 0

Remember that the lexer is responsible for reading in an input program/string and producing a stream of tokens/symbols that are then later consumed by the parser. As an exercise, try lexing the following segment of a C0 program. You may choose whatever textual representation you deem best for each symbol (i.e "(" → "LPAREN").

```
1  if (score < 100) {  
2      return 1;  
3  }
```

Grammars & Parsing

Now once you have a stream of tokens from the lexer, the parser can now construct a parse tree from the stream of tokens. Recall from lecture a grammar G for a language $L(G)$ is defined by a set of productions $\alpha \rightarrow \beta$ and a start symbol S , a distinguished non-terminal symbol.

For a given grammar G with start symbol S , a derivation in G is a sequence of rewritings $S \rightarrow \gamma_1 \rightarrow \dots \rightarrow \gamma_n = w \in L(G)$ in which we apply productions from G . **Parsing** uses this derivation process to produce a parse tree (derivation) for w , in which the nodes represent the non-terminal symbols and the root being S .

We run into ambiguities when there are multiple possible parse trees for the same token stream. Below we'll take a closer look at possible ambiguities.

Grammar Ambiguities

Ambiguities can result as a consequence of the production rules and symbols chosen in defining a grammar G . An ambiguity in the grammar arises when there are multiple possible valid parse trees for the same token stream.

Checkpoint 1

Given the context-free grammar G containing productions of the form:

$$\begin{array}{llll} \gamma_1 & : & A & \rightarrow & \mathbf{A + A} \\ \gamma_2 & : & A & \rightarrow & \mathbf{A - A} \\ \gamma_3 & : & A & \rightarrow & \text{int} \\ \gamma_4 & : & A & \rightarrow & \text{id} \end{array}$$

Prove that the grammar G is ambiguous by showing two parse trees for the stream $1 + 2 - \text{id}_x$.

Conflicts in a LR(k) Parser

Now we will discuss shift-reduce and reduce-reduce conflicts common in LR(k) parsers. Remember from lecture that a bottom-up LR(k) parser parses from left-to-right in a single-pass with right-most derivation using k look-ahead tokens. A shift-reduce parser holds viable prefixes on a stack along with k lookahead symbols with the input stream containing remaining symbols.

LR(k) parsers at each step must determine whether the parser should *shift* or *reduce*. *Shifting* saves the current token on the maintained stack and reads another token while *reducing* applies some rule from the grammar to the front of the current token stack. As such, LR(k) parsers are prone to two common issues when dealing with certain grammars: **shift-reduce** and **reduce-reduce** conflicts.

Shift-Reduce Conflicts

A shift-reduce conflict occurs when it is ambiguous whether the parser should *shift* or *reduce*.

Checkpoint 2

Show that the following grammar has a shift-reduce conflict by showing two different ways to parse the string $200 * 2 + 11$.

Then, explain how you would resolve this conflict.

$$E \rightarrow E + E$$

$$E \rightarrow E * E$$

$$E \rightarrow [0 - 9]^*$$

$$E \rightarrow (E)$$

Reduce-Reduce Conflicts

A reduce-reduce conflict occurs when more than one rule in the grammar can be applied.

Checkpoint 3

Show that the following grammar has a reduce-reduce conflict by showing a successful and an unsuccessful parse of the string $bbbc$.

Then, explain how you would resolve this conflict.

$$S \rightarrow Cc$$

$$S \rightarrow Dd$$

$$C \rightarrow \epsilon$$

$$C \rightarrow Cb$$

$$D \rightarrow \epsilon$$

$$D \rightarrow Db$$