Hierarchy placement, per focal type

Highest-priority type first; every merge, reparent, and consolidation decision below is a dedicated LLM call.

Priority queue over T*

types ranked by Weeds-precision in-degree (τ); ties within δ share a band — seeds, if any, pinned at the top

pop highest-priority node

Current level's candidates

siblings under this anchor (or the live root set)

level size > B (candidate batch size)?

no / now ≤ B → continue

yes

CONSOLIDATE — fires BETWEEN types, never on one pair

LLM groups the TRUE siblings in this level under a synthesized (or reused) shared parent; everything else is left out.

```
film's children: {documentary film, war film, action film}
3 > B(=2) → group war film + action film → genre film
```

→ level is now ≤ B; the focal type's own checks below run against the consolidated level

PARENT CHECK — does focal belong under ANY ONE candidate?

match, same_concept = true → MERGE

focal and the matched candidate are the identical concept, just worded differently.

```
movie vs {film} → same_concept=true
→ merge movie into film
```

→ next node

match, not same concept → DESCEND

focal IS-A the matched candidate; recurse into that candidate's own children.

```
documentary film vs {audiovisual work} → match
→ descend into audiovisual work's children
```

→ recurse: back to the level/capacity check, one level deeper

no match on EITHER candidate

→ proceed to CHILD CHECK below

CHILD CHECK — does focal subsume ONE OR MORE candidates?

only asked if PARENT CHECK matched nothing

match (one or more) → REPARENT

insert focal above the matched candidate(s); corrects an earlier too-shallow attachment.

```
film subsumes documentary film
→ reparent documentary film: audiovisual work → film
```

→ focal settles at this level; next node

no match either → NONE

neither check found anything; focal settles right here.

```
war film vs {documentary film} → no match in either check
→ settle as a plain sibling under film
```

→ new root (top level) or plain child of the current anchor; next node

Depth bound D_{max}

exceeds it ⇒ defer into unresolved_children, never forced or discarded

repeat until the priority queue is empty