

# PAGE\_07\_GOOGLE\_ADS

**URL:** <https://securityblogs.com.au/services/google-ads/> **Airtable table:** SB · 07 · Google Ads for Security **Page kind:** detail **Sections in spec:** 7

---

## Business Purpose

Service detail for Google Ads. Live ad-metrics preview, conversion funnel, remarketing visuals.

## Sections (top to bottom)

| # | Section                            | Block type    |
|---|------------------------------------|---------------|
| 1 | Hero                               | hero          |
| 2 | Live ad metrics demo               | rich-text     |
| 3 | Capabilities (funnel, remarketing) | capabilities  |
| 4 | Process                            | process-steps |
| 5 | Stats                              | stats         |
| 6 | FAQs                               | faqs          |
| 7 | CTA band                           | cta-band      |

## Airtable Tables

| Table                             | Use                                                              |
|-----------------------------------|------------------------------------------------------------------|
| SB · 07 · Google Ads for Security | Per-section spec for /services/google-ads/ (one row per section) |
| SB · 00 · Pages Index             | Master index entry                                               |
| SB · DOCS · Index (proposed)      | Links this MD/PDF to the Airtable page record                    |

## PostgreSQL Tables (used by this page)

| Table    | Use                                     |
|----------|-----------------------------------------|
| services | Service catalogue + per-card data       |
| media    | Image attachments (hero, covers, logos) |
| settings | Brand, contact, footer, GTM injection   |

## API Endpoints

| Endpoint                                         | Method | Cached  | Purpose        |
|--------------------------------------------------|--------|---------|----------------|
| GET /api/services?where[slug][equals]=google-ads | GET    | ISR 60s | Service record |

| Endpoint                                        | Method           | Cached   | Purpose                  |
|-------------------------------------------------|------------------|----------|--------------------------|
| GET /api/globals/settings                       | GET              | ISR 600s | Brand + contact + footer |
| GET /api/redirects?where[isActive][equals]=true | GET (middleware) | 60s mem  | Redirect rules           |

## Request Schemas

No request body — this page only consumes GET endpoints.

## Response Schemas

GET /api/services?where[slug][equals]=google-ads

```
{
  "docs": [{
    "id": "rec...",
    "slug": "google-ads",
    "title": "Google Ads for Security",
    "shortDesc": "...",
    "intro": "...",
    "accentColor": "#1e5fe0",
    "capabilities": [{ "title": "...", "description": "...", "previewVariant": "schema" }],
    "processSteps": [...],
    "stats": [...],
    "faqs": [...],
    "benefits": [...],
    "status": "published"
  }],
  "totalDocs": 1
}
```

## React Components

| Component                        | Purpose                                      |
|----------------------------------|----------------------------------------------|
| app/services/google-ads/page.tsx | Server component — fetches CMS data, renders |
| app/services/google-ads/*.tsx    | Component used on this page                  |
| components/layout/Navbar.tsx     | Component used on this page                  |
| components/layout/Footer.tsx     | Component used on this page                  |
| components/layout/Navbar.tsx     | Shared header                                |
| components/layout/Footer.tsx     | Shared footer                                |

## Node.js Services

| Service / module | Purpose                               |
|------------------|---------------------------------------|
| lib/cms.ts       | Typed Payload REST client — all reads |
| middleware.ts    | Edge middleware — CMS redirect rules  |

## Environment Variables

| Var                  | Required?  | Purpose                       |
|----------------------|------------|-------------------------------|
| NEXT_PUBLIC_SITE_URL | Yes        | Canonical site URL            |
| CMS_URL              | Yes        | Where lib/cms.ts fetches from |
| PAYLOAD_API_KEY      | Yes (prod) | Server-side CMS write auth    |
| SENTRY_DSN           | Yes (prod) | Error tracking                |

## Validation Rules

No user input on this page. Read-only validation: ISR cache freshness, CMS reachability.

## Authentication Rules

- Public read of all page-driving CMS endpoints.
- No user session required.
- Middleware runs on every request but reads via server-only PAYLOAD\_API\_KEY.

## Deployment Notes

- Server-rendered Next.js page (ISR). NOT compatible with output: 'export'.
- First deploy requires `pnpm payload migrate + relevant pnpm seed:*` before booting.
- Caddy reverse-proxies port 3000 (marketing) — see DEPLOYMENT\_GUIDE §6.

## Testing Procedures

### Local smoke

1. `pnpm dev` (marketing site at `http://localhost:3000`)
2. Navigate to `/services/google-ads/`
3. Verify hero renders, navigation works, no console errors

### Production checks

- Lighthouse Performance  $\geq 85$  on landing pages
- Lighthouse Accessibility  $\geq 95$
- Lighthouse SEO = 100
- Sentry: no new error fingerprints after deploy
- Uptime monitor green

## Troubleshooting

| Symptom          | Likely cause    | Fix                                |
|------------------|-----------------|------------------------------------|
| Page returns 500 | CMS unreachable | Check CMS_URL + CMS service status |

| Symptom                        | Likely cause                   | Fix                                                          |
|--------------------------------|--------------------------------|--------------------------------------------------------------|
| Content stale after admin edit | Cache not purged               | <code>revalidateTag()</code> or wait for revalidate interval |
| Sitemap missing this page      | CMS Pages record not published | Set <code>status=published</code>                            |
| Navbar/footer shows defaults   | Settings global missing        | Run <code>pnpm seed:settings</code>                          |

## Change Impact Analysis

### If you change...

- **Copy / hero text:** Low impact. Edit the CMS record (or `app/services/google-ads/page.tsx` if still hardcoded). Wait for ISR.
- **Sections order:** Medium impact. Re-order modules in admin. Renders instantly on next ISR.
- **Add a new module type:** High impact. Add block to `cms/src/collections/Pages.ts`, add component to `components/modules/blocks/`, add dispatch in `ModuleRenderer.tsx`.
- **Slug: CRITICAL — breaks every URL.** Add a `Redirects` record from old slug → new BEFORE updating. Notify SEO if any external links exist.
- **Authentication scope:** Edit `cms/src/access/*.ts`. Roles changes only by `super_admin`.
- **API endpoint shape:** Breaking change. Bump version, dual-route for 30 days, document migration.

## Rollback Procedures

1. **CMS content rollback:** Use Payload versions UI (`/admin/collections/pages/<id>` → Versions tab). Revert to a prior snapshot.
2. **Code rollback:** `git revert <bad-commit>` on `phase-c-frontend-rewire`, push, redeploy.
3. **Schema migration rollback:** Restore Postgres from nightly backup (see `DEPLOYMENT_GUIDE §7`).
4. **Deploy rollback:** `systemctl stop sb-web && git checkout <prev-commit> && pnpm build && systemctl start sb-web`. <5 min.
5. **DNS-level rollback (emergency only):** Revert A record to the last static-export Hostinger IP (5-minute propagation).

---

*Notes:* Live ad-metrics widget proposed to pull from Supermetrics MCP in Phase D; currently hardcoded.

*End of PAGE\_07\_GOOGLE\_ADS.md*