

PAGE_36_CONTENT_GUIDELINES

URL: <https://securityblogs.com.au/content-guidelines/> **Airtable table:** SB · 36 · Content Guidelines **Page kind:** legal **Sections in spec:** 4

Business Purpose

Editorial standards for guest posts + sponsored content.

Sections (top to bottom)

#	Section	Block type
1	Hero	hero
2	Guidelines (rich-text)	rich-text
3	Submission flow	rich-text
4	Contact info	rich-text

Airtable Tables

Table	Use
SB · 36 · Content Guidelines	Per-section spec for /content-guidelines/ (one row per section)
SB · 00 · Pages Index	Master index entry
SB · DOCS · Index (proposed)	Links this MD/PDF to the Airtable page record

PostgreSQL Tables (used by this page)

Table	Use
pages	Page record + module blocks (Phase C.2 migration target)
settings	Brand, contact, footer, GTM injection

API Endpoints

Endpoint	Method	Cached	Purpose
GET /api/pages?where[slug][equals]=content-guidelines	GET	ISR 60s	Page record + modules
GET /api/globals/settings	GET	ISR 600s	Brand + contact + footer
GET /api/redirects?where[isActive][equals]=true	GET (middleware)	60s mem	Redirect rules

Request Schemas

No request body — this page only consumes GET endpoints.

Response Schemas

GET /api/pages?where[slug][equals]=...

```
{
  "docs": [{
    "id": "rec...",
    "slug": "content-guidelines",
    "title": "Content Guidelines",
    "modules": [
      { "blockType": "hero", "h1": "...", "subtitle": "...", "ctas": [...] },
      { "blockType": "rich-text", "title": "...", "body": { /* Lexical JSON */ } }
    ],
    "status": "published"
  }],
  "totalDocs": 1
}
```

React Components

Component	Purpose
app/content-guidelines/page.tsx	Server component — fetches CMS data, renders
components/layout/Navbar.tsx	Component used on this page
components/layout/Footer.tsx	Component used on this page
components/layout/Navbar.tsx	Shared header
components/layout/Footer.tsx	Shared footer

Node.js Services

Service / module	Purpose
lib/cms.ts	Typed Payload REST client — all reads
middleware.ts	Edge middleware — CMS redirect rules

Environment Variables

Var	Required?	Purpose
NEXT_PUBLIC_SITE_URL	Yes	Canonical site URL
CMS_URL	Yes	Where lib/cms.ts fetches from
PAYLOAD_API_KEY	Yes (prod)	Server-side CMS write auth
SENTRY_DSN	Yes (prod)	Error tracking

Validation Rules

No user input on this page. Read-only validation: ISR cache freshness, CMS reachability.

Authentication Rules

- Public read of all page-driving CMS endpoints.
- No user session required.
- Middleware runs on every request but reads via server-only `PAYLOAD_API_KEY`.

Deployment Notes

- Server-rendered Next.js page (ISR). NOT compatible with `output: 'export'`.
- First deploy requires `pnpm payload migrate + relevant pnpm seed:*` before booting.
- Caddy reverse-proxies port 3000 (marketing) — see `DEPLOYMENT_GUIDE` §6.

Testing Procedures

Local smoke

1. `pnpm dev` (marketing site at `http://localhost:3000`)
2. Navigate to `/content-guidelines/`
3. Verify hero renders, navigation works, no console errors

Production checks

- Lighthouse Performance ≥ 85 on landing pages
- Lighthouse Accessibility ≥ 95
- Lighthouse SEO = 100
- Sentry: no new error fingerprints after deploy
- Uptime monitor green

Troubleshooting

Symptom	Likely cause	Fix
Page returns 500	CMS unreachable	Check <code>CMS_URL</code> + CMS service status
Content stale after admin edit	Cache not purged	<code>revalidateTag()</code> or wait for revalidate interval
Sitemap missing this page	CMS Pages record not published	Set <code>status=published</code>
Navbar/footer shows defaults	Settings global missing	Run <code>pnpm seed:settings</code>

Change Impact Analysis

If you change...

- **Copy / hero text:** Low impact. Edit the CMS record (or `app/content-guidelines/page.tsx` if still hardcoded). Wait for ISR.
- **Sections order:** Medium impact. Re-order modules in admin. Renders instantly on next ISR.

- **Add a new module type:** High impact. Add block to `cms/src/collections/Pages.ts`, add component to `components/modules/blocks/`, add dispatch in `ModuleRenderer.tsx`.
- **Slug: CRITICAL — breaks every URL.** Add a `Redirects` record from old slug → new BEFORE updating. Notify SEO if any external links exist.
- **Authentication scope:** Edit `cms/src/access/*.ts`. Roles changes only by `super_admin`.
- **API endpoint shape:** Breaking change. Bump version, dual-route for 30 days, document migration.

Rollback Procedures

1. **CMS content rollback:** Use Payload versions UI (`/admin/collections/pages/<id>` → Versions tab). Revert to a prior snapshot.
2. **Code rollback:** `git revert <bad-commit>` on `phase-c-frontend-rewire`, push, redeploy.
3. **Schema migration rollback:** Restore Postgres from nightly backup (see `DEPLOYMENT_GUIDE` §7).
4. **Deploy rollback:** `systemctl stop sb-web && git checkout <prev-commit> && pnpm build && systemctl start sb-web.` <5 min.
5. **DNS-level rollback (emergency only):** Revert A record to the last static-export Hostinger IP (5-minute propagation).

Notes: Referenced from `/publish-with-us/*` pages. Must stay in sync with editorial standards.

End of PAGE_36_CONTENT_GUIDELINES.md