

```
oc get pods -n openshift-etcd etcd-master01 -o json | jq '.status.conditions'
```

```
oc adm must-gather --dest-dir /home/student/DO180/labs/cli-review/debugging
```

```
oc adm inspect clusteroperator/kube-apiserver --dest-dir  
/home/student/DO180/labs/cli-review/inspect --since 5m
```

```
oc api-resources --api-group oauth.openshift.io
```

```
kubectl get node master01 -o jsonpath='{.status.conditions[*].type}'
```

```
oc run webphp --image
```

```
registry.ocp4.example.com:8443/redhattraining/webphp:v1
```

```
oc debug pod/webphp
```

```
oc edit pod webphp
```

```
oc port-forward pod/webphp 8080:8080
```

```
oc cp ~/DO180/labs/pods-review/phpinfo.php webphp:/var/www/html/
```

```
curl 127.0.0.1:8080/phpinfo.php
```

```
skopeo login registry.ocp4.example.com:8443 -u developer -p developer
```

```
Username: developer
```

```
Password: developer
```

```
skopeo list-tags docker://registry.ocp4.example.com:8443/ubi8/php-74:latest
```

```
skopeo inspect docker://registry.ocp4.example.com:8443/rhel8/mysql-80 | jq  
'tags'
```

```
oc image info registry.ocp4.example.com:8443/rhel8/postgresql-13:latest
```

```
oc image info registry.ocp4.example.com:8443/ubi8/php-74:latest
```

```
oc image info registry.ocp4.example.com:8443/ubi8/nodejs-16:latest
```

```
oc image info registry.ocp4.example.com:8443/rhel8/mysql-80:latest
```

```
oc image info registry.ocp4.example.com:8443/ubi8/python-39
```

```
registry.ocp4.example.com:8443/rhel8/mysql-80
```

```
oc login -u developer -p developer https://api.ocp4.example.com:6443
```

```
oc create deployment mysql-app --image
registry.ocp4.example.com:8443/redhattraining/mysql-app:v1
```

```
oc logs deploy/mysql-app
```

```
oc set env deployment/mysql-app MYSQL_USER=redhat MYSQL_PASSWORD=redhat123
MYSQL_DATABASE=world_x
```

```
oc exec -it mysql-app -- /bin/bash -c "mysql -uredhat -predhat123
</tmp/world_x.sql"
```

```
mysql -uredhat -predhat123
```

```
oc expose deployment mysql-app --name mysql-service --port 3306
--target-port 3306
```

```
oc create deployment sakila-app \
--image
```

```
oc create deployment php-app --image
registry.ocp4.example.com:8443/redhattraining/php-webapp:v1
```

```
oc expose deployment php-app --name php-svc --port 8080 --target-port 8080
```

```
oc create secret generic world-cred --from-literal user=redhat --from-literal
password=redhat123 --from-literal database=world_x
```

```
oc create configmap dbfiles --from-file
~/DO180/labs/storage-review/insertdata.sql
```

```
oc set env deployment/dbserver --from secret/world-cred --prefix MYSQL_
```

```
oc create deployment dbserver --image
registry.ocp4.example.com:8443/redhattraining/mysql-app:v1
```

```
oc set volumes deployment/dbserver --add --name dbserver-lvm --type
persistentVolumeClaim --claim-mode rwo --claim-size 1Gi --mount-path
/var/lib/mysql --claim-name dbserver-lvm-pvc --claim-class lvms-vgl
```

```
oc expose deployment dbserver --name mysql-service --port 3306
--target-port 3306
```

```
oc set volume deployment/file-sharing --add --type configmap --configmap-name
dbfiles --name config-map-pvc --mount-path /home/database-files
```

```
oc exec -it pod/file-sharing- -- head /home/database-files/insertdata.sql
```

```
oc create deployment file-sharing --image
registry.ocp4.example.com:8443/redhattraining/php-webapp-mysql:v1
```

```
oc scale deployment file-sharing --replicas 2
```

```
oc expose deployment file-sharing --name file-sharing --port 8080
--target-port 8080
```

Expose the `satir-svc` service to create a route named `satir` for the `satir-app` web application. (create a route named `satir-app` to expose the web application to external access. )

```
[student@workstation ~]$ oc expose service file-sharing --name file-sharing
```

```
oc set volume deployment/file-sharing --add --name shared-volume --type
persistentVolumeClaim --claim-mode rwo --claim-size 1Gi --mount-path
/home/sharedfiles --claim-name shared-pvc --claim-class nfs-storage
```

```
oc set volume deployment/file-sharing --remove --name=config-map-pvc
```

```
oc set volume deployment/dbserver --add --name shared-volume --claim-name
shared-pvc --mount-path /home/sharedfiles
```

```
oc exec -it pod/web-server-5fb94fd568-48n8t \
-- head /home/sharedfiles/insertdata.sql
```

```
mysql -u$MYSQL_USER -p$MYSQL_PASSWORD world_x <
/home/sharedfiles/insertdata.sql
```

```
oc set resources deploy/longload --requests memory=512Mi
```

```
oc scale deploy/longload --replicas 3
```

```
oc set probe deploy/longload --readiness --get-url http://:3000/health
```

```
oc autoscale deployment/longload --min 1 --max 3 \  
--cpu-percent 60
```

```
oc set triggers deployment/app2 \  
--from-image versioned-hello:1 --containers versioned-hello
```

```
oc set triggers deployment/app2 --from-image php-ssl:1 --containers php-ssl
```

```
oc create istag php-ssl:1-234 --from-image  
registry.ocp4.example.com:8443/redhattraining/php-ssl:1-234
```