

PROGRAM:1

```
statuses = ("DELIVERED", "PENDING", "DELIVERED", "CANCELLED", "DELIVERED")

count = statuses.count("DELIVERED")

print("DELIVERED count:", count)

S=("A","B","A")
print(S.count("A"))
d=("pass","fail","pass")
print(d.count("pass"))
f=("new","new","new")
print(f.count("new"))
print("pass fail count=",count)
```

OUTPUT

```
DELIVERED count: 3
2
2
3
pass fail count= 3
```

PROGRAM :2

```
subjects=("python","java","mysql")
print("OUTPUT-subject=",subjects[2])
print("index=",subjects.index("mysql"))
S=("A","B","C")
print(S.index("A"))
```

OUTPUT

```
pass fail count= 3
OUTPUT-subject= mysql
index= 2
0
```

PROGRAM:3

```
subjects=("python","java","mysql")
print("OUTPUT-subject=",subjects[2])
print("index=",subjects.index("mysql"))
S=("A","B","C")
print(S.index("A"))
```

```
student_id=57
name="saksri"
department="IT"
year=2
```

```
student=student_id,name,department,year
print("student tuple=",student)
```

```
student_id=923
name="srisakthi"
department="IT"
year=4
student=student_id,name,department,year
print("student tuple=",student)
```

```
student_id=750
name="asvy"
department="IT"
year=2
student=student_id,name,department,year
print("student tuple=",student)
```

OUTPUT

```
student tuple= (57, 'saksri', 'IT', 2)
student tuple= (923, 'srisakthi', 'IT', 4)
student tuple= (207, 'sakthi', 'IT', 2)
student tuple= (957, 'sriram', 'AIML', 2)
student tuple= (750, 'asvy', 'IT', 2)
```

PROGRAM:4

```
#UNPACK
student=(104,"yuvaraj","orts",1)
studentid,name,department,year=student
print("ID=", studentid)
print("Name=", name)
print("department=",department)
print("year=",year)
```

OUTPUT

```
ID= 104
Name= yuvaraj
department= orts
year= 1
```