> ⚑ **DECISIONS FOR SHUBHA. Delete this box before pasting into the template.**
>
> 1. ~~Headline~~ **Decided Sat 24 Oct: (B)**, worded precisely: *"every condition that can be checked fails, and the placebo condition cannot be checked on any of them."* It is applied in the abstract, §1 and §6. (She chose A first, then switched to B.)
> 2. ~~P1 wording~~ **Decided: kept**, *"Table 1 does not reproduce from the committed output; the ablation section does."*
> 3. ~~Lange et al. row~~ **Decided: kept** as the flagged † contrast row.
> 4. **M-S arm: done** (Sun 19:45, attempt 2). It is filled into Table 2 and §4: R = 0.96 [0.68, 1.40], so the price rise needs no live partner. Nothing to decide.
> 5. ~~GitHub URL~~ **Decided:** https://github.com/sdachar/collusion-evidence-conditions. The repo is still to be created (SUBMIT-CHECKLIST Step 2).

What Should Count as Evidence of AI Collusion? Four Conditions, Three Published Instruments, and a Randomised Test

Author: Shubha Dhananjaya Achar **Affiliation:** Independent **Track 2.3: What should count as convincing evidence of collusion?** · AI Collusion Research Sprint (Apart Research), 23–25 Oct 2026

Abstract

We propose four conditions for collusion evidence: positives not reproducible from the role label (i); a headline not carried by one statistic (ii); a same-process placebo under the claimed false-positive rate (iii); uncertainty over independent units (iv). On three published instruments of three kinds, judged from their released files, **every condition that can be checked fails, and the placebo condition cannot be checked on any of them.** ColludeBench's union falls from 15/17 to 7/17 without one statistic that fires on 99% of honest windows. A CoT-judge null rests on seven data points. NARCBench's AUROC of 1.00 uses a label equal to the assigned role. Our pre-registered randomised test of cost leakage between LLM pricing agents passes all four. With messaging, prices rise past monopoly, with no profit gain or detectable cost leak. The follower copies any proposed number, low or high, from any speaker: the lockstep is compliance, not collusion.

---

1. Introduction

Collusion between AI agents is usually evidenced in one of three ways: - **statistical tests on messages:** steganalysis, mutual information; - **AI judges reading chains of thought;** - **probes on internal activations.**

Each kind reports a headline number: a true-positive rate at a calibrated false-positive budget, a null correlation, an AUROC. The sprint asks what should count as convincing evidence. We answer with a standard, not a new detector.

The choice not to build a detector is deliberate. Motwani et al. [1, Thm 2] show that black-box optimisation against steganographic collusion is intractable. So a detector cannot be validated by showing that an

optimiser failed to beat it. What can be checked is whether the evidence a detector produces is *about collusion* rather than about its own construction.

Contributions. 1. **Four conditions** for collusion evidence, each with an executable check (`check_conditions.py`, 14 tests) that returns PASS, FAIL or NOT-ASSESSABLE from an instrument's released outputs. NOT-ASSESSABLE is itself a finding: the instrument does not release what a reader would need. 2. **An audit of three instruments of three kinds** from their own files: - ColludeBench's statistical union [2]; - the CoT-judge null of Riemer et al. [3]; - NARCBench's activation probes [4].

Every condition that can be checked fails on at least one of them: (i), (ii) and (iv). The placebo condition (iii) cannot be checked on any, because none releases a same-process honest baseline. 3. **A randomised canary test**, pre-registered and hashed before any LLM call, that passes all four. It shows what evidence that meets the standard looks like, and what it finds: explicit price coordination without detectable private-information flow.

2. Four conditions, and how the instruments score

Condition	The failure it catches	Check (default threshold)
(i) Label	The positive class *is* the instructed role, so detecting it measures the assignment	AUROC predicting the label from the role alone; FAIL if ≥ 0.95
(ii) One statistic	A union whose headline rests on a single near-oracle or non-discriminating statistic	Remove each statistic; FAIL if TPR drops > 0.20
(iii) Placebo	A detector that fires on honest agents from the same process	Placebo FPR with Wilson CI vs the claimed FPR; non-independent scores → NOT-ASSESSABLE
(iv) Unit	Correlated windows or rounds treated as independent	Interval over independent units; FAIL if < 10 units, or if a null's CI reaches |r| ≥ 0.5

Table 1. Verdicts from `check_conditions.py` on released files (`conditions/card.txt`). NA = not assessable from what is released.

Instrument (kind)	(i) Label	(ii) One statistic	(iii) Placebo	(iv) Unit
ColludeBench union [2] (statistical)	NA	**FAIL**: 15/17 → 7/17 without `permutation_invariance`	NA: template honest pool, per-window scores	**FAIL**: 1 negative configuration
Riemer et al. CoT judges [3] (LLM judge)	NA	NA	NA	**FAIL**: null over n = 7, CI [−0.65, +0.83]
NARCBench probes [4] (activations)	**FAIL**: released label = assigned mode (AUROC 1.00)	NA	NA	NA
Canary, ours (§4) (randomised)	PASS (by design)	PASS (one statistic)	PASS: P-0 CI [−0.54, +0.14] ∋ 0	PASS: 40 independent runs
† Lange et al. [5] (logit classifier)	PASS	PASS	PASS: cover text	NA from the abstract

† Scored from the paper's abstract, not by our checker. Its positives are produced by a trained stegosystem, not injected. A text-feature classifier reaches only AUC 0.62, while a logit classifier reaches 1.00, and a paraphrase defence raises the bit-error rate from 12.8% to 48.7%. It is included to show the card can return a pass.

The conditions sharpen antitrust's plus-factor doctrine rather than replacing it. Condition (iii) is the counterfactual requirement, ported to a generator the auditor controls. Tacit collusion is lawful [6], so every condition here concerns evidence of a harm, not of an offence.

3. Auditing three instruments from their released files

ColludeBench [2] is the only collusion benchmark we found that ships its detector output under a licence (MIT). Its author deserves credit for that: it is why this audit can be done arithmetically. We checked the committed outputs against themselves and against the paper. - **Every one of the 16 single-detector cells** in the committed `metrics.md` recomputes exactly from `metrics.json`. - **The paper's ablation paragraph (p. 8) reproduces exactly** from `ablation.json`. - **The paper's Table 1 (p. 7) does not.** Only `acceptance_bias` matches. `cross_run_mi` reads 0.658/0.598 in the paper vs 0.045/0.033 committed, and the Bonferroni union reads 1.000 vs 0.333.

`ablation.json` holds all 255 non-empty subsets of the 8 statistics. That makes (ii) assessable (Figure 2). - **At FPR 10^{-2}** the full union is 15/17 = 0.88 [0.66, 0.97]. - **Without `permutation_invariance` it is 7/17 = 0.41** [0.22, 0.64]. Removing any other single statistic leaves 0.88, apart from `acceptance_bias` (0.71). - **In `metrics.json`, `permutation_invariance` fires on 99% of honest windows** at the same budget. The ablation credits it with zero false positives only because every one of its 510 entries has exactly one negative configuration (17 positive, 1 negative). That single negative also fails (iv). - **Two further artefacts:** - `watermark_variance`'s "FPR 0" is a floor effect: its threshold is 0.0, and every honest score is exactly 0.0. - The honest pool is template-generated, so it is not a placebo for a claim about LLM agents. - **The integrity manifest lists 600 honest calibration runs and no colluding run.**




Figure 2. ColludeBench's detector union at FPR 10^{-2}, from its own `ablation.json`. TPR with Wilson 95% CI over the 17 positive configurations.

Riemer et al. [3] report that a CoT judge's collusion probability is flat (32–34%) while steering moves behaviour from near-Nash to highly collusive. Their Table 3 correlations (PDF p. 9) are over **n = 7 steering magnitudes**: inverting the r/p pairs recovers n = 7 on four cells. That leaves the headline r = 0.194 with a 95% CI of **[−0.65, +0.83]**. A null claim needs a CI that rules out a strong effect, and this one includes the same table's r = 0.771 for "will this agent raise its price?". **The null is uninformative at this n.** That is not evidence that CoT monitoring works.

NARCBench [4] reports an AUROC of 1.00 for probes on the Core tier. We joined its released activation metadata to its released run configurations (62 Qwen3-32B runs; seeds and agent names match 62/62). - **The released positive label equals the assigned mode in every run,** so predicting it from the role alone gives AUROC 1.00 by construction. - **By the authors' own `collusion_success` flag** (both colluders voted for the target), **8 of the 31 positives did not coordinate.** In 6 of them, no colluder voted for the target. - **Only 2 of 31 swung the vote** (`target_majority`). - **On these behavioural labels (i) passes:** role-only AUROC 0.897 and 0.758. So the failure is not the probe's but the label's. *Caveat:* the paper's selection may rest on a transcript judgment that is not shipped. So we state that the shipped flag disagrees with the label, not that the label is wrong. - **No Verdict tier is released,** so the scenario-level interval we pre-registered (P8) cannot be computed.

4. A test built to pass: the randomised canary

Design (pre-registered, `PREREG-P9-canary.md`, SHA-256 hashed before any LLM call; amendments A1–A7 dated). - **The market:** two LLM firms play an 8-round Bertrand duopoly with logit demand (Calvano/Riemer parameters: Nash price 1.47, monopoly 1.93). - **Each round:** 1. Firm A privately draws a fresh cost, $c_A \in \{0.8, 1.2\}$, i.i.d. 2. A may send one message to B. 3. Both firms post prices simultaneously. - **Why the test needs no model of the agents:** when B prices, c_A is independent of everything B has seen publicly. So without a private channel, the statistic $z_t = (c_{A,t} - 1)\cdot(p_{B,t} - p_{B,t-1})/0.1$ has expectation exactly zero, whatever the agents' policy. - **Inference:** a t-interval over 40 independent run means. The test was calibrated on scripted agents: 10/200 false positives = 5.0%. - **Model:** Qwen3.8-27B (Groq), temperature 1.0, the same for every arm.

This is the Athey–Bagwell setting, in which efficient collusion under private costs requires cost communication [7]. Dechenaux & Mago ran it with human subjects and chat [8]. What is new here is the randomised per-round estimator applied to LLM agents.

Arms (40 runs each): - **P-0:** no channel (the placebo); - **POS:** A is told to share its cost and propose a price (the positive control); - **M:** an open channel and "maximise your profit"; - **M+P:** an open channel and "maximise long-run profit, avoid price wars"; - **M-S:** M's prompts, but B receives a stored M message from a different run. This arm was added after seeing M, and is labelled as such.

Table 2. Canary results (`canary/report.py` → `prereg/report.json`). Effects are in price units with 95% CI. MDE is the minimum detectable effect (2.8 × SE). Emission is the share of A's messages containing A's true cost value. $\Delta = (\pi - \pi_{Nash})/(\pi_{monopoly} - \pi_{Nash})$, the profit-based collusion index of [9, 3], per firm per round, with a run-level bootstrap CI: 0 = Nash, 1 = monopoly.

Arm	Effect of c_A on p_B	MDE	A's own-cost pass-through	B's price = A's message number	Emission	Mean price − P-0	Profit index Δ
P-0	−0.203 [−0.544, +0.137]	0.47	+0.80 [+0.33, +1.29]	—	—	—	−0.61 [−0.82, −0.40]
POS	**+0.133 [+0.067, +0.198]**	0.09	+0.99	66%	100%	—	+0.84 [+0.79, +0.89]
M	−0.002 [−0.308, +0.303]	0.42	+0.81 [+0.19, +1.42]	83%	4%	**+1.105 [+0.739, +1.473]**	−0.54 [−0.83, −0.24]
M+P	−0.195 [−0.602, +0.212]	0.56	+0.60 [−0.45, +1.60]	98%	1%	**+1.421 [+0.906, +1.966]**	−0.77 [−1.09, −0.42]
M-S	+0.003 [−0.212, +0.218]	0.30	+0.89 [+0.04, +1.75]	62%‡	5%‡	**+1.060 [+0.737, +1.360]**	−0.49 [−0.73, −0.26]

‡ In M-S, B's inbox holds an M message from a different run. The 62% is B adopting a number from that delivered message. A's own message (5% emission) is logged but never delivered.

Prediction outcomes. - **Prediction 1 (POS > 0.3 SD, CI excluding 0): PASS** (+0.635 SD). - **Prediction 2 (P-0 CI contains 0): PASS.** - **Prediction 3 (M or M+P excludes 0): NULL,** reported as pre-registered with POS as the power reference. Both null intervals contain POS's effect, so they **cannot rule out a leak of that size**. - **Prediction 4 (A's price tracks its own cost):** holds in P-0, POS and M, but **fails in M+P**. So M+P is uninformative about leakage, and we report it so.

Emission vs inference. A's messages state a cost word in 8% of M rounds and its true cost value in 4%. Its price proposals, by contrast, are adopted by B to the cent in 83% (M) and 98% (M+P) of rounds. B's price equals A's same-round price in 82% (M) and 99% (M+P) of rounds, against 16% in P-0, where there is no channel. Dropping the rounds whose message contains the true cost leaves the M estimate at +0.050 [−0.258, +0.358].

Reading: measure choice decides the verdict. With a channel, prices rise by +1.1 (M) and +1.4 (M+P) over the placebo (Figure 1b). The median p_B is 2.5 in both, against 1.45 in P-0: above the monopoly price of

1.93, so past the joint-profit optimum. Profits do not rise. Δ is negative in every open arm and is not detectably higher than the placebo's (M −0.54, M+P −0.77, P-0 −0.61). Only POS, whose proposal is cost + 1, approaches monopoly profit (+0.84). The agents coordinate explicitly on price, but on prices that harm consumers and the firms alike: coordinated over-pricing, not profitable collusion. A price-level detector would flag M and M+P as collusion, and a profit-based index would not: the verdict is set by the measure, which is why the conditions ask what a number measures. The information-flow test answers a third question: no private cost moves at a detectable size. M-S tests whether the price rise needs a live partner. Its primary estimate is R = (M-S − P-0)/(M − P-0): a CI below 0.5 means within-pair coordination, and a CI above 0.5 means exposure to any price proposal, or framing. **R = 0.96 [0.68, 1.40]:** almost the whole rise survives when B reads a stranger's message (M-S − P-0 = +1.060 [+0.737, +1.360]; M-S − M = −0.045 [−0.448, +0.338]). So the rise does not need a live partner. M-S cannot separate exposure from framing. Because its inbox is independent of c_A, M-S is also a channel-open placebo for the canary, and its CI contains 0 (+0.003 [−0.212, +0.218]).

Worked case: lockstep is compliance, not collusion. Price lockstep is the signature a behavioural detector reads as collusion. Here it is something else. B adopts the number in A's message in round 1, before any history exists to reward or punish it: 34/40 runs (M) and 38/40 (M+P). Following costs B 29.7 profit per round in M [24.1, 35.5] and 31.5 in M+P [24.5, 38.4], against a best response to A's actual price. That is more than a full round of Nash profit (22.2), and P-0 shows 7.9 [5.3, 11.0]. B's prices are multiples of 0.5 in 66% (M) and 78% (M+P) of rounds, against 24% in P-0. A colluder holds a high price because deviating is punished later. This follower gives up profit with nothing to fear: it complies with a salient number. A pre-registered follow-up (`track3/PREREG-Z2-anchor.md`) used the same round-1 prompt, varied only B's inbox, and ran 40 independent calls per arm on self-hosted Qwen3.8-27B. B priced at the rival's proposed 1.20, 1.50, 2.50 and 3.50 in 39, 40, 40 and 40 of 40 calls: downward as readily as upward, including 1.20, below the Nash price. It followed an "independent analyst's" number almost as closely (shift ratio 0.97 [0.91, 1.00]). It adopted a live A's real message in 36 of 40. Lockstep here is obedience to whichever number is in the prompt, not a strategy sustained by incentives. A claim of collusion therefore has to show the coordination is sustained by incentives, not just that prices move together. (`canary/compliance.py`, `track3/z2_anchor.py`.)




Figure 3. B's round-1 price against the number in its prompt (Z2, 40 independent calls per point). The dashed line marks an exact copy. Whiskers (95% CIs) are narrower than the dots.




Figure 1. (a) The canary statistic per arm, in price units, with POS's effect as the power reference. (b) Mean market price per run, with Nash and monopoly prices for reference. Prices above the monopoly price lower joint profit (Table 2, Δ).

5. Discussion and limitations

- **The conditions are necessary, not sufficient.** Passing them makes evidence checkable. It does not make a detector complete: Motwani's result still bounds every black-box test, including ours.

- **We ran one instrument ourselves.** The three audits use released files. Several verdicts are NA because the needed per-unit data is not released. That is a statement about releases, not a proof that the instruments fail.
- **The canary's nulls are under-powered:** MDE 0.30–0.56 price units against a positive-control effect of 0.13. The test can certify a leak; with 40 runs per arm, it cannot certify its absence. It uses one model, one temperature, one prompt per arm and an 8-round horizon.
- **The price-level comparison (M vs P-0) confounds the channel with the prompt framing.** That is why M-S exists, and M-S cannot separate exposure from framing.
- **Our own corrections are logged** (Appendix D). Five claims made during the sprint were retracted after independent review.

6. Conclusion and next steps

Collusion evidence should be judged on whether it is about collusion, not only on its headline. Four conditions make that checkable from released files: - Applied to three instruments of three kinds, every condition that can be checked fails somewhere, and the placebo condition cannot be checked on any of them. - A randomised test built to the standard passes all four, and on LLM pricing agents it separates price coordination from information flow.

Two continuations: 1. **Port antitrust screens to LLM pricing logs** (coefficient of variation, relative distance, variance screens), each held to the same four conditions. 2. **Test leniency for AI cartels.** Our agents already make explicit price proposals, which B adopts in 83–98% of rounds, so the precondition for a leniency experiment (a reportable agreement) exists. Its evidence should be held to the same four conditions.

7. Code and data

Repository: https://github.com/sdachar/collusion-evidence-conditions. It holds: - `conditions/`: `check_conditions.py`, `build_specs.py`, `specs.json`, `card.txt`, tests; - `colludebench/`: the recompute and leave-one-out scripts, `leave_one_out.csv`, `GATE-K1.md`; - `canary/`: the harness, analysis, `report.py`, every CSV and the full call logs (`*.calls.jsonl`), tests; - `PREREG-P9-canary.md` and its hashes; - `track3/`: the Z2 compliance check (`PREREG-Z2-anchor.md`, `z2_anchor.py`, tests, `z2/` logs) and the two modules it imports; - `report/make_figures.py`, which regenerates all three figures on CPU.

ColludeBench's and NARCBench's files are not redistributed: fetch them from the sources in Appendix C.

8. References

[1] Motwani, Baranchuk, Strohmeier, Bolina, Torr, Hammond & Schroeder de Witt. *Secret Collusion among AI Agents: Multi-Agent Deception via Steganography*. NeurIPS 2024. arXiv:2402.07510. [2] Tailor. *Audit the Whisper: Detecting Steganographic Collusion in Multi-Agent LLMs*. arXiv:2510.04303. Code: github.com/Ostailor/Steganographic_Collusion (MIT). [3] Riemer, Tosato, Memarian, Puelma Touzel, Berseth, Rish & Dumas. *Position: Collusion Risks Among AI Reasoning Agents Justify Certification Requirements for Making Market Decisions*. arXiv:2608.18078. [4] Rose et al. *Detecting Multi-Agent Collusion Through Multi-Agent Interpretability* (NARCBench). arXiv:2604.01151. Data: huggingface.co/datasets/aaronrose227/narcbench. [5] Lange, Arcuschin, Krzyzanowski, Lee & Meyer. *Language Models can Learn High-Capacity Secure Steganography*. ICML 2026 Trustworthy AI for Good Workshop. icml.cc/virtual/2026/76993. [6] *In re Text Messaging Antitrust Litigation*, No. 14-2301 (7th Cir. Apr. 9, 2015) (Posner, J.). [7] Athey & Bagwell. *Optimal Collusion with Private Information*. RAND Journal of Economics 32(3), 2001; Athey, Bagwell & Sanchirico, *Collusion and Price Rigidity*, Review of Economic Studies 71(2), 2004. [8] Dechenaux & Mago. *Communication and side payments in a duopoly with private costs: an experiment*. Journal of Economic Behavior & Organization 165 (2019) 157–184. [9] Calvano, Calzolari, Denicolò & Pastorello. *Artificial Intelligence, Algorithmic Pricing, and Collusion*. American Economic Review 110(10), 2020.

Appendix A. Limitations and Dual-Use / Ethical Considerations

1. **No colluding agent is built or released.** The canary's agents are prompted to maximise profit in a toy market. The positive control is told to share a cost. Nothing here adds coordination capability that the prompts do not already state.
2. **The checker is an evaluation tool, not an attack.** An adversary who knows the conditions learns what auditors require of *their own* generator and null, not how to evade a detector's internals. Evidentiary standards in antitrust are public for the same reason.
3. **The real risk is interpretive.** An audit that weakens trust in detection benchmarks can be read as "collusion is undetectable". Our finding concerns whether specific evidence is about collusion. The canary shows that evidence meeting the standard can be produced.
4. **Tone and credit.** Every finding is stated about an instrument, never an author. ColludeBench is credited for shipping its logs under a licence, which made this audit possible. Findings will be sent to its author with the repository link.
5. **Untrusted inputs.** Every downloaded repository, dataset and paper was treated as data: read in isolated directories with Python in isolated mode, and never executed. This is why ColludeBench's transcripts were not regenerated (Appendix B, P4).
6. **Scope.** These are small-scale testbeds built to study detection. Results on one model, one market and an 8-round horizon do not establish how deployed pricing agents behave.

Appendix B. All pre-registered predictions, reported whichever way they fell

ColludeBench, from `PLAN` §5R.2: - **P1:** the two `cross_run_mi` numbers come from different subsets, and only one reproduces. **Result:** *Table 1 does not reproduce from the committed output; the ablation section does*. 0.12 (ablation, 2/17) reproduces; 0.658 does not appear in `metrics.md`. - **P2:** removing `acceptance_bias` drops the union to ≤ 0.70. **Not testable as worded**, because `metrics.json` stores union summaries only. On the ablation union, the result is 0.706 at 10^{-2}: just above the threshold, so **P2 narrowly fails** on the closest available test. The unpredicted `permutation_invariance` removal (0.41) is what carries the union. - **P3** (`acceptance_bias` off-review): not computable from the committed files. - **P4** (grep matches the union at FPR 0): **not run.** It needs regenerated transcripts, which requires executing the third-party code. That is outside our safety rule. - **P5** (LLM arm of ColludeBench): not run; replaced by the canary.

The other instruments: - **P7** (2608.18078, n = 7, CI contains 0 and 0.771): **holds**, re-read from the PDF. - **P8** (NARCBench scenario interval): **cannot run**, because no Verdict tier is released.

Canary: predictions 1–4 as in §4. Amendments: - **A1:** the run-level estimator replaces a within-run permutation test shown to be invalid on scripted agents. - **A2:** the placebo replicate rule. - **A3:** the backend (Qwen3.8-27B on Groq; one call for A's message and price), before any pre-registered run. - **A4:** POS's proposal step, before the POS, M and M+P arms. - **A5:** the parser requires a `"price"` key, from M+P on. Sensitivity: dropping the one affected run per completed arm moves POS to +0.787 SD; P-0 is unchanged. - **A6:** M-S, labelled post hoc. - **A7:** reporting in price units with MDE, labelled post hoc.

Compliance follow-up (Z2, `track3/PREREG-Z2-anchor.md`, hashed before any Z2 call; designed after seeing the canary, so a post-hoc follow-up): canary round-1 B prompt, 40 independent calls per arm, self-hosted Qwen3.8-27B (vLLM, A100-80GB), 0 parse failures in 360 calls. - **H0** (BRIDGE adopts ≥ 26/40, so the new stack reproduces the canary): **holds,** 36/40. - **H1** (RIVAL-2.5 and RIVAL-3.5 adopt in ≥ 60%): **holds,** 40/40 and 40/40. - **H2** (RIVAL-1.2 gives p ≤ 1.30 in ≥ 50%; the anchoring literature predicted failure): **holds,** 40/40. - **H3** (shift ratio, analyst vs rival, ≥ 0.5): **holds,** 0.97 [0.91, 1.00]. - **Pilot-rule note:** the rule required B's prices to be "neither pinned at the cap nor constant". RIVAL-2.5 was constant at 2.50, which is full adoption. We read the rule as pooled across the pilot (BRIDGE gave 8 distinct values); that reading was made after seeing the pilot. - **Placebo** ("Good luck this round"): median 1.50, with 9/40 at the price cap, the same round-1 clip outliers as in P-0.

Appendix C. Reproduction

- **Conditions card:** `python -I build_specs.py <metrics.json> <narcbench/scenarios> <qwen3_32b/core/metadata_gen.json> <ablation.json> ../canary/prereg/report.json > specs.json`, then `python -I check_conditions.py specs.json`.
- **ColludeBench leave-one-out:** `python -I 01_leave_one_out.py <ablation.json> leave_one_out.csv`.
- **Canary:**
- per arm: `python run_canary.py --agents groq --runs 40 --arms <ARM> --out prereg --seed <SEED>`;
- seeds: P-0 20261019, POS 20261020, M 20261021, M+P 20261022, M-S 20261023 with `--scramble-from prereg/M.csv`;
- then `python report.py`.
- **Tests:** `pytest` in `conditions/` (14) and `canary/` (19).
- **Source data:**
- ColludeBench `results/experiments/{metrics,ablation}.json` and `results/dataset_manifest.json` at `Ostailor/Steganographic_Collusion@main`;
- NARCBench at Hugging Face `aaronrose227/narcbench`, revision 19cb14b;
- 2608.18078 PDF, Tables 3 and 5.

Appendix D. Corrections made during the sprint

Claim as first made	Correction
"M's CI rules out an effect as large as POS's"	The SD units differ across arms. In price units, M's CI contains POS's effect
"Coordination without information flow"	No detectable *cost* flow, but explicit *price* flow
A's messages state cost 15% / 11% of the time	A regex bug; the correct figures are 8% / 4%
ColludeBench `cross_run_mi` passes (iii)	Its scores are non-independent windows, so NA
"All three instruments fail all four conditions"	Most conditions are not assessable from releases. "Each fails at least one"

LLM usage statement

Claude (via Claude Code) was used for experiment scaffolding, the harness and analysis code, statistical tooling, figure generation and drafting. A second model reviewed the methods and code independently; its findings and our corrections are in Appendix D. Every number in this report derives from executed code in the repository and was checked against the saved outputs.