# On Task Type Diversity


| | |
|---|---|
| Document Number: | D4050R0 |
| Date: | 2026-03-11 |
| Audience: | LEWG |


| | |
|---|---|
| Reply-to: | Vinnie Falco vinnie.falco@gmail.com |


## Table of Contents


Abstract

Revision History

- R0: March 2026 (post-Croydon mailing)

1. Disclosure

2. Task Types in Production

- 2.1 The Allocator Ceremony
- 2.2 Two Empty Structs
- 2.3 Library Upgrade Breaks Downstream

3. Why the Invariants Differ

- 3.1 Frame Allocator
- 3.2 Foreign Awaitables
- 3.3 Timing
- 3.4 Symmetric Transfer

4. Cross-Domain Bridges

5. Recommendation

6. Suggested Straw Polls

Acknowledgements

- References
  - WG21 Papers
  - Other

## Abstract

Every C++ coroutine library ships its own task type. Six libraries independently converged on a one-parameter declaration. Each extends the C++20 awaitable protocol with domain-specific safety invariants - frame allocator propagation for networking, cancellation models for structured concurrency, fiber scheduler integration for large-scale deployments. Cross-domain composition requires explicit bridges that translate these invariants. This paper surveys the evidence, documents why the invariants differ by design, and recommends that `std::execution::task` (P3552R3[1]) be documented as the standard task type for the sender domain rather than presented as a general-purpose task type for all coroutine users.

---

## Revision History

### R0: March 2026 (post-Croydon mailing)

- Initial version.

---

## 1. Disclosure

The author developed P4003R0[2] ("Coroutines for I/O"), P4007R1[3] ("Senders and Coroutines"), P4014R0[4] ("The Sender Sub-Language"), and P2583R1[5] ("Symmetric Transfer and Sender Composition"). A coroutine-only design cannot express compile-time work graphs, does not support heterogeneous dispatch, and assumes a cooperative runtime. Those are real costs.

The frame allocator propagation gap described in Section 3 was identified by Peter Dimov. The cross-library bridge evidence in Section 4 was produced by Klemens Morgenstern, the author of Boost.Cobalt, to test the cross-domain composition claim. Neither is a co-author of this paper or any paper in this series.

---

## 2. Task Types in Production

Six coroutine libraries independently converged on a one-parameter task type. Of these, folly::coro and Boost.Cobalt are in active production use at scale. cppcoro was deployed at Facebook before folly::coro replaced it. The remaining three are smaller libraries that independently arrived at the same interface.

| Library | Declaration | Params | Source |
|---|---|---|---|
| asyncpp | `template<class T> class task` | 1 | task.hpp |
| Boost.Cobalt | `template<class T> class task` | 1 | task.hpp |
| cppcoro | `template<typename T> class task` | 1 | task.hpp |
| aiopp | `template<typename Result> class Task` | 1 | task.hpp |
| libcoro | `template<typename return_type> class task` | 1 | task.hpp |
| folly::coro | `template<typename T> class Task` | 1 | Task.h |
| P3552R3 (std) | `template<class T, class Environment> class task` | 2 | task.hpp |

The external interface converged. The internal machinery diverged. Boost.Cobalt embeds intrusive linked list elements in the promise for its cancellation model. folly::coro::Task integrates with Facebook's fiber scheduler and `CancellationToken`. Boost.Asio's `awaitable` is coupled to `io_context`. cppcoro targets platform-specific I/O primitives. Each library optimizes for its domain.

P3552R3[1] adds a second template parameter: `Environment`. This means `std::execution::task<int>` and `std::execution::task<int, MyEnvironment>` are different types. The sender environment - which every production library independently chose not to expose in the type signature - is now part of the public type.

P3552R3[1]'s wording declares `template<class T, class Environment> class task` with no default for `Environment` ([execution.syn][10], [task.class][10]). The design section states that "any empty type provides the default behaviour" but does not name or standardize such a type. The paper's own examples use `task<int>` with one parameter - a usage that is ill-formed against its own wording.

The consequence is twofold. First, every function signature that returns `task` is coupled to the sender environment model - a networking function advertises the sender environment in its return type even though the environment is not a networking concern and the networking programmer did not choose it. Second, generic code that accepts `task<T>` does not accept `task<T, MyEnvironment>`. The interoperability that one-parameter task types enjoy through the awaitable protocol breaks the moment the environment parameter diverges. Whether a default is eventually provided does not change the fragmentation: the moment any library in the dependency chain provides a non-default `Environment`, every function in the chain must agree on the type.

Consider a generic function that accepts the "standard task" and a library that returns a task with a custom environment:

```
void spawn_work(std::execution::task<void> work);

std::execution::task<void, net_env> do_network();

spawn_work(do_network());  // does not compile:
                           // task<void, net_env> is not task<void>
```

The types are different template instantiations. Both are "the standard task." They are incompatible. The fragmentation is invisible until the user tries to compose them.

**One-parameter task types compose by construction. Two-parameter task types fragment by default.**

## 2.1 The Allocator Ceremony

P3552R3[1] Section 4.6 shows how to enable allocator awareness. The user must define a custom environment struct and use it in every function signature:

```
struct alloc_env {
    using allocator_type =
        std::pmr::polymorphic_allocator<std::byte>;
};

std::execution::task<std::string, alloc_env>
read_body(tcp_socket& sock);

std::execution::task<json, alloc_env>
parse(std::string_view body);

std::execution::task<void, alloc_env>
write_response(tcp_socket& sock, std::string_view body);
```

Every production library:

```
task<std::string> read_body(tcp_socket& sock);
task<json>        parse(std::string_view body);
task<void>        write_response(tcp_socket& sock,
                                 std::string_view body);
```

P3552R3[1] does not provide a standard allocator-aware environment type. The user must define it. Two users who independently define semantically identical structs produce incompatible task types.

### 2.2 Two Empty Structs

Two libraries both define empty environments. Both get identical default behavior. The types are incompatible:

```
// Library A
struct env_a {};
std::execution::task<int, env_a> compute();

// Library B
struct env_b {};
std::execution::task<int, env_b> fetch();

// Both environments are empty. Both produce identical
// default behavior. The types are incompatible.
```

The C++ type system distinguishes them even though the sender model does not. This is fragmentation with zero semantic basis.

### 2.3 Library Upgrade Breaks Downstream

A library that upgrades from the default environment to a custom one changes the return type and breaks every downstream caller:

```
// v1.0: default environment
std::execution::task<response> http_get(url_view);

// v2.0: needs allocator awareness
std::execution::task<response, http_env> http_get(url_view);

// Every downstream caller has a type mismatch.
```

A networking task type can use thread-local propagation for frame allocators. A GPU task type can use device memory APIs. A high-frequency trading task type can enforce zero allocation at compile time. Solutions exist when the promise is free to serve its domain rather than forced to serve a model it does not participate in.

**The diversity in the table above is not fragmentation. It is fitness.**

## 3. Why the Invariants Differ

Every production coroutine library extends the base C++20 awaitable protocol. The extensions enforce domain-specific safety invariants. P3552R3[1]'s `await_transform` + `affine_on` maintains executor continuity and stop token propagation for recognized senders within the `std::execution` (P2300R10[9]) framework. Four gaps remain, each independently documented.

### 3.1 Frame Allocator

`affine_on` returns the coroutine to the correct scheduler thread after completion. The thread-local frame allocator value on that thread is whatever was left by the previous coroutine that executed on it - not the allocator for this chain. There is no hook between `affine_on` completing and the coroutine body resuming where TLS can be restored. Peter Dimov identified this gap. It is unsolved in the published record: P3980R0[6] addresses allocator sourcing from the receiver environment but does not restore TLS on resumption.

### 3.2 Foreign Awaitables

P3552R3[1]'s `await_transform` recognizes senders. If a user `co_await` s a non-sender awaitable - a `cppcoro::task<int>` , a Boost.Cobalt awaitable, any basic C++20 awaitable - it passes through without `affine_on` , without stop token wiring, without any environment propagation. All three invariants are lost. Networking libraries reject non-conforming awaitables at compile time because permissiveness breaks their safety invariants. P3552R3[1] permits the permissive case. This is a deliberate scope boundary: `task` is designed for sender composition. The consequence for non-sender domains is that `task` cannot enforce their safety invariants, which is why those domains require their own task types.

### 3.3 Timing

The sender extension delivers context through `connect` / `start` after the coroutine frame is allocated. The networking extension delivers context at `co_await` time through the `await_suspend` parameter. The frame allocator must be available before the child's `operator new` fires, and `operator new` fires at the call site ([dcl.fct.def.coroutine][10]) - before any sender machinery runs. No mechanism in `std::execution` (P2300R10[9]) delivers any allocator to `operator new` without `allocator_arg_t` in the parameter list. A single task type cannot satisfy both timing requirements: deferred delivery serves the sender model, immediate delivery serves networking. The requirements are contradictory by design.

### 3.4 Symmetric Transfer

When `task` bridges into the sender pipeline, the sender-awaitable's `await_suspend` returns `void`, foreclosing symmetric transfer. Jonathan Müller confirmed in P3801R0[7]: ***"a thorough fix is non-trivial and requires support for guaranteed tail calls."*** Dietmar Kühl documented the gap as an open issue in P3796R1[8]. This gap is independent of the frame allocator timing in Section 3.3.

---

## 4. Cross-Domain Bridges

The cross_await[11] repository, authored by Klemens Morgenstern, contains four working cross-library composition examples. None compose natively through the base C++20 protocol alone. All four require explicit adaptor code.

| Outer library | Inner library | Adaptor file | Lines |
|---|---|---|---|
| Cobalt | Capy | `cobalt_capy.cpp` | 67 |
| TMC | Capy | `tmc_capy.cpp` | 51 |
| Capy | Cobalt | `corosio_cobalt.cpp` | 105 |
| Capy | TMC | `corosio_tmc.cpp` | 60 |

Each adaptor translates execution context between two domain protocols. From `cobalt_capy.cpp`:

```
template<typename T>
struct capy_task_adaptor {
    capy::task<T> tt;
    capy::io_env env;
    std::stop_source src;
    boost::asio::cancellation_slot slt;

    template<typename Promise>
    auto await_suspend(std::coroutine_handle<Promise> h) {
        auto& p = h.promise();
        env.executor        = p.get_executor();
        env.stop_token      = src.get_token();
        env.frame_allocator = p.get_allocator().resource();
        slt = p.get_cancellation_slot();
        slt.assign([this](auto ct) {
            if ((ct & boost::asio::cancellation_type::terminal) !=
                      boost::asio::cancellation_type::none)
                src.request_stop();
        });
        return tt.await_suspend(h, &env);
    }
};
```

The bridge knows both Cobalt's internal API and Capy's protocol. It is specific to the pair of libraries. There is no generic bridge because the invariants being translated are domain-specific. Cross-domain composition is achievable but requires library authors with knowledge of both protocols. The C++20 awaitable protocol is the surface all four bridges bottom out to.

---

## 5. Recommendation

`std::execution::task` is correctly positioned in `namespace std::execution`. The committee should not present it as the general-purpose coroutine task type in tutorials, examples, or guidance. Domain-specific task types are the norm in production and should be recognized as the intended model for coroutine composition. The design space for coroutine-to-execution-context integration is open. The committee should not foreclose it.

---

## 6. Suggested Straw Polls

1. "Domain-specific task types that extend the C++20 awaitable protocol are the intended model for coroutine composition in C++."
2. "`std::execution::task` should be documented as the standard task type for the sender domain, not as a general-purpose task type for all coroutine users."

---

# Acknowledgements

The author would like to thank Peter Dimov for identifying the frame allocator propagation gap and requiring the `IoAwaitable` fix that clarified the relationship between domain-specific invariants and the base protocol; Klemens Morgenstern for authoring Boost.Cobalt and producing the cross_await bridge evidence that demonstrates cross-domain composition in practice; Dietmar Kühl for authoring P3552R3 and P3796R1, whose thorough design discussion in P3552R3 Section 4.1 and open documentation of task issues in P3796R1 reflect the standard of care the committee depends on; Jonathan Müller for independently confirming the symmetric transfer gap in P3801R0; and Mungo Gill, Mohammad Nejati, and Michael Vandeberg for their feedback during development.

---

## References

### WG21 Papers

1. P3552R3 - "Add a Coroutine Task Type" (Dietmar Kühl, Maikel Nadolski, 2025). https://wg21.link/p3552r3
2. P4003R0 - "Coroutines for I/O" (Vinnie Falco, Steve Gerbino, Mungo Gill, 2026). https://wg21.link/p4003r0
3. P4007R1 - "Senders and Coroutines" (Vinnie Falco, Mungo Gill, 2026). https://wg21.link/p4007r1
4. P4014R0 - "The Sender Sub-Language" (Vinnie Falco, 2026). https://wg21.link/p4014r0
5. P2583R1 - "Symmetric Transfer and Sender Composition" (Mungo Gill, Vinnie Falco, 2026). https://wg21.link/p2583r1
6. P3980R0 - "Task's Allocator Use" (Dietmar Kühl, 2026). https://www.open-std.org/jtc1/sc22/wg21/docs/papers/2026/p3980r0.html
7. P3801R0 - "Concerns about the design of `std::execution::task`" (Jonathan Müller, 2025). https://wg21.link/p3801r0
8. P3796R1 - "Coroutine Task Issues" (Dietmar Kühl, 2025). https://wg21.link/p3796r1

9. P2300R10 - ‘‘std::execution’’ (Michał Dominiak et al., 2024). https://wg21.link/p2300r10

## Other

10. C++ Working Draft - (Richard Smith, ed.). https://eel.is/c++draft/
11. Klemens Morgenstern, cross_await - ‘‘co_await one coroutine library from another’’ (2026). https://github.com/klemens-morgenstern/cross_await
12. cppcoro - C++ coroutine library (Lewis Baker). https://github.com/lewissbaker/cppcoro
13. libcoro - C++20 coroutine library (Josh Baldwin). https://github.com/jbaldwin/libcoro
14. asyncpp - Async coroutine library (Péter Kardos). https://github.com/petiaccja/asyncpp
15. aiopp - Async I/O library (Joel Schumacher). https://github.com/pfirsich/aiopp
16. beman::task - P3552R3 reference implementation. https://github.com/bemanproject/task
17. folly::coro - Facebook coroutine task type. https://github.com/facebook/folly/blob/main/folly/experimental/coro/Task.h
18. Boost.Cobalt - Boost coroutine task type (Klemens Morgenstern). https://github.com/boostorg/cobalt/blob/develop/include/boost/cobalt/task.hpp
19. Capy - Coroutine-native I/O library (Vinnie Falco). https://github.com/cppalliance/capy