Consuming Senders from Coroutine-Native Code

Document Number:	P4055R0
Date:	2026-03-13
Audience:	LEWG

Reply-to:	Vinnie Falco vinnie.falco@gmail.com Steve Gerbino steve@gerbino.co

Table of Contents

Abstract

Revision History

R0: March 2026 (post-Croydon mailing)

1. Disclosure

2. The Bridge

3. Demonstration

4. What the Bridge Does

5. What the Bridge Does Not Require

6. The Narrowest Abstraction

7. Acknowledgments

References

Appendix A. Bridge Implementation

Abstract

An `IoAwaitable` bridge (P4003R0[3]) consumes `std::execution` (P2300R10[1]) senders with inline operation state, correct stop token propagation, and automatic executor dispatch-back. The bridge is one class template. The complete implementation is in Appendix A.

This paper is one of a suite of six that examines the relationship between compound I/O results and the sender three-channel model. The companion papers are P4050R0[13], "On the Diversity of Coroutine Task Types"; P4053R0[2], "Sender I/O: A Constructed Comparison"; P4054R0[11], "Two Error Models"; P4056R0[12], "Producing Senders from Coroutine-Native Code"; and P4058R0[14], "The Case for Coroutines."

Revision History

R0: March 2026 (post-Croydon mailing)

- Initial version.

---

1. Disclosure

The authors developed Capy[4] and Corosio[6] and believe coroutine-native I/O is the correct foundation for networking in C++. The bridge depends on Capy[4] (coroutine primitives, no sockets, no platform I/O) and `beman::execution` [5]. The authors provide information, ask nothing, and serve at the pleasure of the chair.

The authors regard `std::execution` as an important contribution to C++ and support its standardization for the domains it serves well - GPU dispatch, heterogeneous execution, and compile-time work-graph composition among them. Nothing in this paper or its companions argues for removing, delaying, or diminishing `std::execution`.

The authors' position is narrower: that networking and stream I/O present a compound-result structure that the three-channel model was not designed to carry, and that this domain is better served by a coroutine-native facility that can coexist with senders and interoperate where the domains meet. Two models, each correct for its domain, is a stronger standard than one model asked to serve both.

---

2. The Bridge

`await_sender` consumes a `std::execution` sender from inside a coroutine. The sender runs on whatever scheduler it was given; the coroutine resumes on its own executor.

```
capy::task<int> compute(auto sched)
{
    int result = co_await capy::await_sender(
        ex::schedule(sched)
            | ex::then([] {
                std::cout
                    << "  sender running on thread "
                    << std::this_thread::get_id()
                    << "\n";
                return 42 * 42;
            }));

    std::cout
        << "  coroutine resumed on thread "
        << std::this_thread::get_id() << "\n";

    co_return result;
}
```

`await_sender` returns a `sender_awaitable` satisfying `IoAwaitable` (P4003R0[3]). Any coroutine type that propagates `io_env` through `await_suspend(h, io_env const*)` can use it. The two-argument form is deliberate: the compiler rejects any coroutine type that does not propagate `io_env`, enforcing the sandbox boundary at compile time. Complete implementation in Appendix A.

---

3. Demonstration

Output from the example in Section 2, compiled with MSVC 19.43 against Capy[4] and `beman::execution` [5] (a community implementation of `std::execution`):

```
main thread: 32208
  sender running on thread 9560
  coroutine resumed on thread 34356
result: 1764
```

The sender ran on the `run_loop` thread. The coroutine resumed on the Capy thread pool. Zero bytes allocated beyond the coroutine frame.

---

4. What the Bridge Does

The bridge consumes any `std::execution` sender whose value completion signature is a single type or `void`. Operation state stored inline. `set_value`, `set_error`, `set_stopped` handled. Standard pipelines - `when_all`, `then`, `let_value`, `on` - compose with the bridge.

The bridge inspects error completion signatures at compile time. If the sender advertises `set_error(std::error_code)`, `await_resume` returns `io_result<T>`:

```
auto [ec, val] = co_await await_sender(sndr);
```

No exceptions for `error_code`. Otherwise `await_resume` returns `T` directly; genuine exceptions are rethrown and cancellation is surfaced as an exception. Static dispatch, zero runtime cost. The `operation_cancelled` type in Appendix A is illustrative; a production implementation would use a project-appropriate cancellation exception.

The error-code dispatch is the consuming side of the **abstraction floor** (P4056R0[12] Section 4):

Region	What the code sees
Above the floor	`error_code` alone - composition works
Below the floor	`(error_code, size_t)` - both values intact

When the sender completes, the bridge posts the resumption back to the coroutine's originating executor. The coroutine resumes in the correct context regardless of where the sender executed.

Does not use `execution::task`.

---

5. What the Bridge Does Not Require

P3552R3[15], "Add a Coroutine Task Type," defines `std::execution::task`. Its `connect` operation type-erases the operation state, and its error path converts `error_code` to `exception_ptr` via `AS-EXCEPT-PTR`. The bridge avoids both mechanisms:

Property	**`execution::task`**	Bridge
Routine I/O errors become exceptions	Yes (via `AS-EXCEPT-PTR`)	No

Property	`execution::task`	Bridge
Type erasure on connect	Yes	No
Allocation beyond coroutine frame	Yes (type-erased state)	No
Requires `std::execution::task`	-	No

The bridge consumes senders without `std::execution::task`.

---

6. The Narrowest Abstraction

The bridge depends on two things: Capy[4] (coroutine primitives) and `std::execution` (sender/receiver protocol). No platform I/O. No networking headers. No additional coroutine type. The implementation in Appendix A uses `beman::execution` [5], a community implementation of `std::execution`, but the bridge requires only the standard sender/receiver concepts.

Narrower than `execution::task`: the bridge does not type-erase, does not allocate, and does not impose an `Environment` parameter. Narrower than a completion-token adapter: the bridge does not require Asio or any I/O service. The coroutine type the programmer already uses does not change when the bridge is added.

The bridge is the proof that coexistence works. Senders compose. Coroutines do I/O. One class template connects them.

---

7. Acknowledgments

The authors thank Dietmar Kühl for `beman::execution` [5] and for the channel-routing enumeration in P2762R2[7], Michał Dominiak, Eric Niebler, and Lewis Baker for `std::execution`, Chris Kohlhoff for identifying the partial-success problem in P2430R0[8], Kirk Shoop for the completion-token heuristic analysis in P2471R1[9], Fabio Fracassi for P3570R2[10], Ville Voutilainen and Jens Maurer for reflector discussion on dispatch patterns, Herb Sutter for identifying the need for tutorials and documentation, Mark Hoemmen for insights on `std::linalg` and the layered abstraction model, and Peter Dimov for the refined channel mapping.

References

1. P2300R10 - ‘‘std::execution’’ (Michał Dominiak et al., 2024). https://wg21.link/p2300r10
2. P4053R0 - ‘‘Sender I/O: A Constructed Comparison’’ (Vinnie Falco, Steve Gerbino, 2026). https://isocpp.org/files/papers/P4053R0.pdf
3. P4003R0 - ‘‘Coroutines for I/O’’ (Vinnie Falco, Steve Gerbino, Mungo Gill, 2026). https://wg21.link/p4003r0
4. cppalliance/capy - Coroutine primitives library. https://github.com/cppalliance/capy
5. bemanproject/execution - Community implementation of `std::execution`. https://github.com/bemanproject/execution
6. cppalliance/corosio - Coroutine-native networking library. https://github.com/cppalliance/corosio
7. P2762R2 - ‘‘Sender/Receiver Interface For Networking’’ (Dietmar Kühl, 2023). https://wg21.link/p2762r2
8. P2430R0 - ‘‘Partial success scenarios with P2300’’ (Chris Kohlhoff, 2021). https://wg21.link/p2430r0
9. P2471R1 - ‘‘NetTS, ASIO and Sender Library Design Comparison’’ (Kirk Shoop, 2021). https://wg21.link/p2471r1
10. P3570R2 - ‘‘Optional variants in sender/receiver’’ (Fabio Fracassi, 2025). https://wg21.link/p3570r2
11. P4054R0 - ‘‘Two Error Models’’ (Vinnie Falco, 2026). https://isocpp.org/files/papers/P4054R0.pdf
12. P4056R0 - ‘‘Producing Senders from Coroutine-Native Code’’ (Vinnie Falco, Steve Gerbino, 2026). https://isocpp.org/files/papers/P4056R0.pdf
13. P4050R0 - ‘‘On the Diversity of Coroutine Task Types’’ (Vinnie Falco, 2026). https://isocpp.org/files/papers/P4050R0.pdf
14. P4058R0 - ‘‘The Case for Coroutines’’ (Vinnie Falco, 2026). https://isocpp.org/files/papers/P4058R0.pdf
15. P3552R3 - ‘‘Add a Coroutine Task Type’’ (Dietmar Kühl, Maikel Nadolski, 2025). https://wg21.link/p3552r3

Appendix A. Bridge Implementation

```
#include <boost/capy/error.hpp>
#include <boost/capy/ex/io_env.hpp>
#include <boost/capy/io_result.hpp>

#include <beman/execution/execution.hpp>

#include <coroutine>
#include <exception>
#include <new>
#include <stop_token>
#include <system_error>
#include <tuple>
#include <type_traits>
#include <utility>
#include <variant>

namespace boost::capy {

namespace detail {

struct stopped_t {};

struct operation_cancelled {};

struct bridge_env
{
    std::stop_token st_;

    auto query(
        beman::execution::get_stop_token_t const&)
            const noexcept
    {
        return st_;
    }
};

template<class Sender>
using sender_single_value_t =
    beman::execution::value_types_of_t<
        Sender,
        bridge_env,
        std::tuple,
        std::type_identity_t>;
```

```
template<class Sender>
struct has_error_code_completion
{
    template<class... Es>
    struct checker
    {
        static constexpr bool value =
            (std::is_same_v<
                Es, std::error_code> || ...);
    };

    static constexpr bool value =
        beman::execution::error_types_of_t<
            Sender,
            bridge_env,
            checker>::value;
};

template<class Sender>
constexpr bool has_error_code_v =
    has_error_code_completion<Sender>::value;

// Variant when sender can complete with
// set_error(error_code): separate slot for
// error_code so it is not wrapped in
// exception_ptr.
template<class ValueTuple>
using ec_result_variant = std::variant<
    std::monostate,
    ValueTuple,
    std::error_code,
    std::exception_ptr,
    stopped_t>;

// Variant when sender does not complete with
// set_error(error_code).
template<class ValueTuple>
using no_ec_result_variant = std::variant<
    std::monostate,
    ValueTuple,
    std::exception_ptr,
    stopped_t>;

template<class ValueTuple, bool HasEc>
using result_variant = std::conditional_t<
    HasEc,
```

```
    ec_result_variant<ValueTuple>,
    no_ec_result_variant<ValueTuple>>;

template<class ValueTuple, bool HasEc>
struct bridge_receiver
{
    using receiver_concept =
        beman::execution::receiver_t;

    result_variant<ValueTuple, HasEc>* result_;
    std::coroutine_handle<>            cont_;
    io_env const*                      env_;

    auto get_env() const noexcept -> bridge_env
    {
        return {env_->stop_token};
    }

    template<class... Args>
    void set_value(Args&&... args) && noexcept
    {
        result_->template emplace<1>(
            std::forward<Args>(args)...);
        env_->executor.post(cont_);
    }

    template<class E>
    void set_error(E&& e) && noexcept
    {
        if constexpr (
            HasEc &&
            std::is_same_v<
                std::decay_t<E>,
                std::error_code>)
            result_->template emplace<2>(
                std::forward<E>(e));
        else if constexpr (
            std::is_same_v<
                std::decay_t<E>,
                std::exception_ptr>)
        {
            constexpr auto idx = HasEc ? 3 : 2;
            result_->template emplace<idx>(
                std::forward<E>(e));
        }
        else
        {
```

```
            constexpr auto idx = HasEc ? 3 : 2;
            result_->template emplace<idx>(
                std::make_exception_ptr(
                    std::forward<E>(e)));
        }
        env_->executor.post(cont_);
    }

    void set_stopped() && noexcept
    {
        constexpr auto idx = HasEc ? 4 : 3;
        result_->template emplace<idx>(
            stopped_t{});
        env_->executor.post(cont_);
    }
};

} // namespace detail

template<class Sender>
struct sender_awaitable
{
    static constexpr bool has_ec =
        detail::has_error_code_v<Sender>;

    using value_tuple =
        detail::sender_single_value_t<Sender>;
    using variant_type =
        detail::result_variant<
            value_tuple, has_ec>;
    using receiver_type =
        detail::bridge_receiver<
            value_tuple, has_ec>;
    using op_state_type = decltype(
        beman::execution::connect(
            std::declval<Sender>(),
            std::declval<receiver_type>()));

    Sender sndr_;
    variant_type result_{};

    alignas(op_state_type)
    unsigned char op_buf_[sizeof(op_state_type)];
    bool op_constructed_ = false;

    explicit sender_awaitable(Sender sndr)
        : sndr_(std::move(sndr))
```

```
    {
    }

    sender_awaitable(sender_awaitable&& o)
        noexcept(
            std::is_nothrow_move_constructible_v<
                Sender>)
        : sndr_(std::move(o.sndr_))
    {
    }

    sender_awaitable(
        sender_awaitable const&) = delete;
    sender_awaitable& operator=(
        sender_awaitable const&) = delete;
    sender_awaitable& operator=(
        sender_awaitable&&) = delete;

    ~sender_awaitable()
    {
        if(op_constructed_)
            std::launder(
                reinterpret_cast<op_state_type*>(
                    op_buf_))->~op_state_type();
    }

    bool await_ready() const noexcept
    {
        return false;
    }

    std::coroutine_handle<>
    await_suspend(
        std::coroutine_handle<> h,
        io_env const* env)
    {
        ::new(op_buf_) op_state_type(
            beman::execution::connect(
                std::move(sndr_),
                receiver_type{
                    &result_, h, env}));
        op_constructed_ = true;
        beman::execution::start(
            *std::launder(
                reinterpret_cast<
                    op_state_type*>(
                        op_buf_)));
```

```
        return std::noop_coroutine();
    }

    auto await_resume()
    {
        if constexpr (has_ec)
            return await_resume_ec();
        else
            return await_resume_no_ec();
    }

private:
    // Sender can complete with
    // set_error(error_code). Return io_result
    // so the error code is a value, not an
    // exception.
    auto await_resume_ec()
    {
        // exception_ptr at index 3
        if(result_.index() == 3)
            std::rethrow_exception(
                std::get<3>(result_));

        if constexpr (
            std::tuple_size_v<
                value_tuple> == 0)
        {
            // stopped at index 4
            if(result_.index() == 4)
                return io_result<>{
                    make_error_code(
                        error::canceled)};
            if(result_.index() == 2)
                return io_result<>{
                    std::get<2>(result_)};
            return io_result<>{};
        }
        else if constexpr (
            std::tuple_size_v<
                value_tuple> == 1)
        {
            using T = std::tuple_element_t<
                0, value_tuple>;
            if(result_.index() == 4)
                return io_result<T>{
                    make_error_code(
                        error::canceled)};
```

```
            if(result_.index() == 2)
                return io_result<T>{
                    std::get<2>(result_)};
            return io_result<T>{
                {},
                std::get<0>(
                    std::get<1>(
                        std::move(result_)))};
        }
        else
        {
            if(result_.index() == 4)
                return io_result<value_tuple>{
                    make_error_code(
                        error::canceled)};
            if(result_.index() == 2)
                return io_result<value_tuple>{
                    std::get<2>(result_)};
            return io_result<value_tuple>{
                {},
                std::get<1>(
                    std::move(result_))};
        }
    }

    // Sender does not complete with
    // set_error(error_code). Return the value
    // directly; rethrow exceptions.
    auto await_resume_no_ec()
    {
        // exception_ptr at index 2
        if(result_.index() == 2)
            std::rethrow_exception(
                std::get<2>(result_));
        // stopped at index 3
        if(result_.index() == 3)
            throw detail::operation_cancelled{};

        if constexpr (
            std::tuple_size_v<
                value_tuple> == 0)
            return;
        else if constexpr (
            std::tuple_size_v<
                value_tuple> == 1)
            return std::get<0>(
                std::get<1>(
```

```
                    std::move(result_)));
        else
            return std::get<1>(
                std::move(result_));
    }
};

template<class Sender>
auto await_sender(Sender&& sndr)
{
    return sender_awaitable<
        std::decay_t<Sender>>(
            std::forward<Sender>(sndr));
}

} // namespace boost::capy
```