

React Day 14

For faster and easiest way

we are using the useActionState hook for form validation

useAction State Hook

```
import React from 'react';
import { useActionState } from 'react';

const handleLogin = async (prevState, formData) => {
  const name = formData.get('name');
  const password = formData.get('password');

  const regex = /^[A-Z0-9]{2,}$/;

  if (name.length > 5) {
    return { error: 'Name should not exceed 5 characters.' };
  } else if (!regex.test(password)) {
    return { error: 'Password must contain only capital letters and digits, at least 2 characters.' };
  }

  console.log('Form submitted');
  return { success: true };
};

const UseAction = () => {
  const [state, formAction, isPending] = useActionState(handleLogin, { error: null, success: false });

  return (
    <div>
      <h2>Validation with useActionState Hook in React</h2>
      <form action={formAction}>
        <input type="text" name="name" placeholder="Enter name" />
        <br /><br />
        <input type="text" name="password" placeholder="Enter password" />
        <br /><br />
        <button type="submit" disabled={isPending}>
          {isPending ? 'Logging in...' : 'Login'}
        </button>
      </form>

      {state?.error && <p style={{ color: 'red' }}>{state.error}</p>}
      {state?.success && <p style={{ color: 'green' }}>Login Successful!</p>}
    </div>
  );
};

export default UseAction;
```

UseReducer Hook

what is useReducer Hook ?

The useReducer hook is a React Hook used for state management, especially when:

- The state object is complex (like a form with many fields),
 - You need to perform multiple related state updates,
 - Or want more control than useState gives.
-
- **state:** The current state.
 - **dispatch:** Function to send actions to update the state.
 - **reducerFunction:** A function that decides how to update the state.
 - **initialState:** The initial state value.

```
import React from 'react'
import { useReducer } from 'react'

let emptyData = {
  name:'',
  password:'',
  city:'',
  age:'',
}

const reducer = (data,action) =>{
  return {...data,[action.type]:action.val}
}

const UseReducer = () => {

  const [state,dispatch] = useReducer(reducer,emptyData);
  console.log(state);

  return (
    <div>
      <h3>Use Reducer Hook use</h3>
      <form action="">
        <input type="text" onChange={(event)=>dispatch({val:event.target.value,type:'name'})} placeholder='Enter name' />
        <br /> <br />
        <input type="text" onChange={(event)=>{dispatch({val:event.target.value,type:'password'})}} placeholder='Enter p' />
        <br /> <br />
        <input type="text" onChange={(event)=>{dispatch({val:event.target.value,type:'city'})}} placeholder='Enter city' />
        <br /> <br />
        <input type="text" onChange={(event)=>{dispatch({val:event.target.value,type:'age'})}} placeholder='Enter age' />
        <br /> <br />

        <ul>
          <li> name :{state.name}</li>
          <li> password : {state.password}</li>
          <li>city :{state.city}</li>
          <li>age :{state.age}</li>
        </ul>
      </form>
    </div>
  )
}
```