Metrics:

Total lines of code: 77
Total lines skipped (#nosec): 0

hardcoded_sql_expressions: Possible SQL injection vector through string-based query construction.
Test ID: B608
Severity: MEDIUM
Confidence: LOW
CWE: CWE-89
File: src/app.py
Line number: 32
More info: https://bandit.readthedocs.io/en/1.9.4/plugins/b608_hardcoded_sql_expressions.html

```
31          # INTENTIONAL SQL INJECTION
32          sql = f"SELECT id, title, body FROM posts WHERE title LIKE '%{q}%' OR body LIKE '%{q}%'"
33          rows = cur.execute(sql).fetchall()
```

flask_debug_true: A Flask app appears to be run with debug=True, which exposes the Werkzeug debugger and allows the execution of arbitrary code.
Test ID: B201
Severity: HIGH
Confidence: MEDIUM
CWE: CWE-94
File: src/app.py
Line number: 63
More info: https://bandit.readthedocs.io/en/1.9.4/plugins/b201_flask_debug_true.html

```
62      if __name__ == "__main__":
63          app.run(host="0.0.0.0", port=5000, debug=True)
```

hardcoded_bind_all_interfaces: Possible binding to all interfaces.
Test ID: B104
Severity: MEDIUM
Confidence: MEDIUM
CWE: CWE-605
File: src/app.py
Line number: 63
More info: https://bandit.readthedocs.io/en/1.9.4/plugins/b104_hardcoded_bind_all_interfaces.html

```
62      if __name__ == "__main__":
63          app.run(host="0.0.0.0", port=5000, debug=True)
```