





# pySLM2: A full-stack python package for holographic beam shaping

Chung-You Shih<sup>1</sup>, Jingwen Zhu<sup>1</sup>, and Rajibul Islam<sup>1</sup>

<sup>1</sup> Institute for Quantum Computing and Department of Physics and Astronomy, University of Waterloo,  
200 University Ave. West, Waterloo, Ontario N2L 3G1, Canada  Corresponding author

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

## Software

- [Review](#) 
- [Repository](#) 
- [Archive](#) 

Editor: [Rohit Goswami](#) 

## Reviewers:

- [@brandondube](#)
- [@sidihamady](#)
- [@ktahar](#)

Submitted: 13 December 2023

Published: unpublished

## License

Authors of papers retain copyright  
and release the work under a  
Creative Commons Attribution 4.0  
International License ([CC BY 4.0](#)).

## Summary

Holographic beam shaping using spatial light modulators (SLMs) as a reprogrammable hologram offers a powerful tool for precise and flexible optical controls. It has been adopted for a wide range of research, including atom trapping ([Gaunt & Hadzibabic, 2012](#)), optical addressing of individual quantum objects ([Motlakunta et al., 2023](#)), preparation of exotic quantum states ([Islam et al., 2015](#)), and multi-beam laser machining ([Obata et al., 2010](#)).

pySLM2 is a python package designed for full-stack control of SLMs for holographic beam shaping, encompassing hologram generation, simulation, and hardware controls.

The package implements the hologram generation algorithms of the Lee hologram ([Lee, 1978](#)) and its improved predecessors ([Shih et al., 2021](#); [Zupancic et al., 2016](#)), targeting the digital micromirror device (DMD) based SLM with binary amplitude controls. It also implements the Gerchberg-Saxton algorithm ([Gerhberg & Saxton, 1972](#)) suitable for liquid crystal on silicon (LCoS) based SLMs with pure phase controls.

Under the hood, the package uses TensorFlow for numerical computations. By leveraging TensorFlow, the package harnesses the power of GPUs for faster computation without the need for code modification. This results in a significant speed-up for algorithms that are computationally expensive but benefit from parallelization, such as many hologram generation algorithms relying on iterative Fourier transformations.

Additionally, the package offers a universal interface for different SLMs, ensuring that code written for one device can be seamlessly adapted to another. As of this writing, the package supports DMD controllers from two commercial vendors, Visitech, INC and ViALUX GmbH.

## Statement of need

High-quality optical controls are crucial for numerous scientific and engineering applications. For instance, in atom-based quantum information processors, quantum states of individual atoms are often manipulated by individually addressing laser beams. The quality of these addressing beams directly impacts the fidelity of quantum operations ([Motlakunta et al., 2023](#)).

Holographic beam shaping using SLMs provides a way for precise and adaptive optical controls. Compared to using conventional optical elements, holographic beam shaping has several advantages. Firstly, it can generate arbitrary beam profiles that are challenging to create with standard optical elements. For example, the Laguerre-Gaussian beam with a non-zero azimuthal index (often referred to as a doughnut beam), which can be used to trap atoms in a tube-like potential ([Kuga et al., 1997](#)), apply angular momentum to Bose-Einstein Condensation ([Andersen et al., 2006](#)), or achieve super-resolution imaging ([Drechsler et al., 2021](#); [Qian et al., 2021](#)).

Secondly, holographic beam shaping can actively correct optical aberrations in the system, thereby achieving diffraction-limited performance. This enables the faithful production of target beam profiles with high accuracy. It has been shown that residual aberrations can be corrected to less than  $\lambda/20$  root-mean-square (RMS) (Shih et al., 2021; Zupancic et al., 2016), which is smaller than most of the manufacturing tolerances of optical elements.

At the time of writing, the pySLM2 package, as detailed in this manuscript, has been used in the trapped ion quantum information processing research (Kotibhaskar et al., 2023; Motlakunta et al., 2023; Shih et al., 2021). The authors believe that the package will benefit a broader community of researchers and engineers by offering turnkey solutions for applying holographic beam shaping to their work. Moreover, the primitives included in the package can assist researchers in rapidly prototyping new hologram generation algorithms.

## Fourier Holography Basics

pySLM2 is designed for holographic beam shaping using Fourier holography. The name “Fourier” comes from the fact that the electric fields of the beam at the hologram plane and the target plane are related by a Fourier transformation.

In a paraxial lens system, the lens act as a Fourier transform operator mapping the electric field in one focal plane to the electric field in the another focal plane. In the context of Fourier Holography, the two focal plane are referred as the image plane (IP) and the Fourier plane (FP). The electric field at the two planes,  $E_{IP}(\mathbf{x}')$  and  $E_{FP}(\mathbf{x})$  respectively, are related by the following equation:

$$E_{FP}(\mathbf{x})e^{i\Phi_{ab}} = \frac{\lambda f}{2\pi} \mathcal{F}[E_{IP}(\mathbf{x}')] (\mathbf{k}') \Big|_{\mathbf{k}' = \frac{2\pi}{\lambda f} \mathbf{x}}$$

In which,  $\mathbf{x}'$  and  $\mathbf{k}'$  denote the spatial coordinate and the wave vector at the image plane respectively, and  $\mathcal{F}$  denotes Fourier transformation. The wave vector  $\mathbf{k}'$  is related to the spatial coordinate  $\mathbf{x}$  at FP by  $\mathbf{x} = \frac{\lambda f}{2\pi} \mathbf{k}'$  where  $f$  is the effective focal length of lens and  $\lambda$  is the wavelength of the light.

The aberrations of the optical system can be modeled as a phase map  $\Phi_{ab}$  in the Fourier plane. In pySLM2's convention, the plane SLM is placed is Fourier plane, and the image plane is where the targeted beam profile is desired. The SLM modulates the beam at Fourier plane to engineer the desired beam profiles at the image plane.

## Hologram Generation Algorithm


Currently, pySLM2 supports two type of the spatial light modulator (SLM), liquid crystal on silicon (LCoS) SLM and digital micromirror device (DMD). The LCoS SLM modulates the phase profile purely without modifying the amplitude. As the time of writing, Gerchberg-Saxton (GS) (Gerhberg & Saxton, 1972) algorithm and the mixed-region amplitude freedom (MRAF) algorithm (Gaunt & Hadzibabic, 2012) are included.

On the other hand, DMDs use micromirrors to locally turn on and off the light by toggling the micromirrors between two directions. This allows binary amplitude control. By periodically turning on and off the micromirrors across the DMD to form grating patterns, diffracted beams with controllable phase and amplitude can be engineered to have the desired beam profiles. As the time of writing, a randomized algorithm (Zupancic et al., 2016) and an iterative Fourier transformation algorithm (Motlakunta et al., 2023; Shih et al., 2021) are provided for hologram generation.

## Usages


pySLM2 offers commonly used optics profiles right out of the box, including Hermite Gaussian, Laguerre Gaussian, super Gaussian (also known as “flat top”), and Zernike polynomials. These profiles are implemented as functional objects, and pySLM2 automatically handles the profile sampling during hologram calculations.

For profiles that are not included by default, users have the option to either inherit from the base class and implement their custom profiles or generate the sampled profiles in an array format to pass them to the hologram calculation function. As illustrated in Fig. Figure 1, here’s an example of creating a hologram to generate a Laguerre Gaussian beam with a mode of  $l = 1$ ,  $p = 0$ , which often referred to as a “doughnut beam”, from the fundamental Gaussian mode. Unless specified, the simulation shown in this paper is simulated with the following conditions:  $\lambda = 369$  nm wavelength,  $f = 200$  mm Fourier lens focal length, and with Texas Instrument DLP9500 as the SLM (1 px = 10  $\mu$ m micromirror size).



**Figure 1:** Hologram simulation for creating Laguerre Gaussian beam of  $l = 1$ ,  $p = 0$  mode from fundamental mode. (a) DMD mirror configuration. Bright pixels represent “on” and dark pixels represent “off”. (b) Intensity profile of input fundamental Gaussian beam. (c) Intensity profile of the output Laguerre ( $l = 1$ ,  $p = 0$ ) Gaussian beam at the image plane. (d) Phase map of the output beam. An optical vortex can be observed at the center of the Laguerre  $l = 1$ ,  $p = 0$  mode (Source code: examples/create\_donut\_beam.py)

The arithmetic operations of the profiles are also overloaded, so one can easily combine different profiles through addition or rescale the profiles through multiplication. Shown in Fig. Figure 2, we create a hologram to generate two Gaussian beams. In the source code, it is written as adding two Gaussian profiles together at different positions.




**Figure 2:** Hologram simulation for creating two Gaussian beams from one input Gaussian beam. (a) DMD mirror configuration. Bright pixels represent “on” and dark pixels represent “off”. (b) Intensity profile of input single Gaussian beam. (c) Intensity profile of the two output Gaussian beams at the image plane. (d) Phase map of the output beam. An example of two Gaussian beams having opposite phases is shown. (Source code: `examples/create_donut_beam.py`)

## Aberration Correction

One of the key advantages of holographic beam shaping is its capability to correct optical aberrations, and pySLM2 provides an easy method to achieve this correction. By supplying the aberration information during the hologram calculation, pySLM2 generates a hologram imprinted with a phase profile opposite to the aberration, effectively canceling the aberration out.

In the example depicted in Figure 3, we simulate the beam profile at the image plane both with and without aberration correction. Without aberration correction, the beam profile becomes distorted and broadened. In this particular simulation, spherical aberration is used, but pySLM2 is capable of correcting other types of aberrations as well.



**Figure 3:** Simulation of the beam profiles at the image plane with and without aberration correction. (a) Phase map of the input beam with  $\mathbb{Z}_4^0$  spherical aberration. (b) Intensity profile of the input beam. (c) Intensity profile of the first order beam without aberration correction. (d) Intensity profile of the first order beam with aberration correction. (Source code: `examples/aberration_correction.py`)

To obtain the phase map of the aberration, one can either use a wavefront sensor, such as a Shack–Hartmann sensor (Shack, 1971), to measure the wavefront, or one can allow light from different parts of the Fourier plane to interfere with each other to reconstruct the aberration phase profile from the resulting interference patterns. For a detailed description of the latter method, one can refer to Shih et al. (Shih et al., 2021).

## Hardware Controls [not-reviewed]

pySLM2 provides hardware controls for DMD controllers from both Visitech, INC and ViALUX GmbH. The controllers from these two companies use different communication protocols and architectures. The Visitech controller uses UDP over Ethernet, while the ViALUX controller uses USB3.

One of the goals of pySLM2 is to abstract the hardware details and offer a unified application interface for interacting with these devices. For instance, we have implemented the same `load_single` and `load_multiple` functions within the controller classes for both manufacturers' devices. These functions allow for the display of single holograms or the loading of multiple holograms that can be switched by triggers. Apart from the hardware agnostic functions, it also exposed the lower-level access for advanced users to implement device specific controls.

## Acknowledgements

The hardware controls for the DMDs from ViALUX GmbH in the package is built on top of the AL4lib (Popoff et al., 2022). We appreciate the work of the authors of AL4lib. We express gratitude to Kaleb Ruscitti for assisting with hardware testing and to Sainath Motlakunta and Nikhil Kotibhaskar for providing valuable feedback on the package.

## References

- Andersen, M., Ryu, C., Cladé, P., Natarajan, V., Vaziri, A., Helmerson, K., & Phillips, W. D. (2006). Quantized rotation of atoms from photons with orbital angular momentum. *Physical Review Letters*, 97(17), 170406.
- Drechsler, M., Wolf, S., Schmiegelow, C. T., & Schmidt-Kaler, F. (2021). Optical superresolution sensing of a trapped ion's wave packet size. *Physical Review Letters*, 127(14), 143602.
- Gaunt, A. L., & Hadzibabic, Z. (2012). Robust digital holography for ultracold atom trapping. *Scientific Reports*, 2(1), 721.
- Gerhberg, R., & Saxton, W. (1972). A practical algorithm for the determination of phase from image and diffraction plane picture. *Optik*, 35, 237–246.
- Islam, R., Ma, R., Preiss, P. M., Eric Tai, M., Lukin, A., Rispoli, M., & Greiner, M. (2015). Measuring entanglement entropy in a quantum many-body system. *Nature*, 528(7580), 77–83.
- Kotibhaskar, N., Shih, C.-Y., Motlakunta, S., Vogliano, A., Hahn, L., Chen, Y.-T., & Islam, R. (2023). Programmable XY-type couplings through parallel spin-dependent forces on the same trapped ion motional modes. *arXiv Preprint arXiv:2307.04922*.
- Kuga, T., Torii, Y., Shiokawa, N., Hirano, T., Shimizu, Y., & Sasada, H. (1997). Novel optical trap of atoms with a doughnut beam. *Physical Review Letters*, 78(25), 4713.
- Lee, W.-H. (1978). III computer-generated holograms: Techniques and applications. In *Progress in optics* (Vol. 16, pp. 119–232). Elsevier.
- Motlakunta, S., Kotibhaskar, N., Shih, C.-Y., Vogliano, A., McLaren, D., Hahn, L., Zhu, J., Hablützel, R., & Islam, R. (2023). Preserving a qubit during adjacent measurements at a few micrometers distance. *arXiv Preprint arXiv:2306.03075*.
- Obata, K., Koch, J., Hinze, U., & Chichkov, B. N. (2010). Multi-focus two-photon polymerization technique based on individually controlled phase modulation. *Optics Express*, 18(16), 17193–17200.
- Popoff, S. M., Shih, G., B., D., & GustavePariente. (2022). *Wavefrontshaping/ALP4lib: 1.0.1* (Version 1.0.1). Zenodo. <https://doi.org/10.5281/zenodo.6121191>
- Qian, Z.-H., Cui, J.-M., Luo, X.-W., Zheng, Y.-X., Huang, Y.-F., Ai, M.-Z., He, R., Li, C.-F., & Guo, G.-C. (2021). Super-resolved imaging of a single cold atom on a nanosecond timescale. *Physical Review Letters*, 127(26), 263603.
- Shack, R. V. (1971). Production and use of a lenticular hartmann screen. *Spring Meeting of Optical Society of America*, 1971, 656.
- Shih, C.-Y., Motlakunta, S., Kotibhaskar, N., Sajjan, M., Hablützel, R., & Islam, R. (2021). Reprogrammable and high-precision holographic optical addressing of trapped ions for scalable quantum control. *Npj Quantum Information*, 7(1), 57.
- Zupancic, P., Preiss, P. M., Ma, R., Lukin, A., Tai, M. E., Rispoli, M., Islam, R., & Greiner, M. (2016). Ultra-precise holographic beam shaping for microscopic quantum control. *Optics Express*, 24(13), 13881–13893.