





validateHOT - an R package for holdout task validation and market simulations

Joshua Benjamin Schramm ^{1,2} and Marcel Lichters ²

¹ Chemnitz University of Technology, Germany ² Otto von Guericke University of Magdeburg, Germany
 Corresponding author

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#) 
- [Repository](#) 
- [Archive](#) 

Editor: 

Submitted: 23 January 2024

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

validateHOT is an R package that provides functions to both validate a validation/holdout task and run market simulations for results obtained in a (adaptive) choice-based conjoint analysis (hereafter ACBC and CBC, respectively) and maximum difference scaling (hereafter MaxDiff) using, for example, ChoiceModelR ([Sermas, 2022](#)) or Sawtooth's Lighthouse Studio.

Statement of need

Preference measurement techniques' (e.g., (A)CBC or MaxDiff) aim is to predict behavior ([Green & Srinivasan, 1990](#)). Hence, it is essential to ensure that the collected data is valid and predicts outside tasks (i.e., the model has external validity) well. The easiest way for testing validity is by including validation tasks ([Orme, 2015](#); e.g., [Rao, 2014](#)), which are fixed tasks (i.e., same across participants) and not used for estimating the part-worth utilities (raw logit utilities) in hierarchical Bayes (HB) estimation. Despite their importance, practitioners don't always include them ([Yang et al., 2018](#)). This is unsatisfactory given the fact that the model is used to estimate market shares which poses the basis for relevant marketing decisions.

validateHOT combines both validation and market simulation in one package and has three key advantages, it (1) helps opting for the best model and (2) runs relevant market simulations that help finding the right product combinations or assortments, and (3) is an open source tool which helps especially researchers reporting accompanied scripts for their research papers.

State of the field in R

Other packages provide functions to calculate validation metrics, however, these are not always specified for individual part-worth utilities. Metrics ([Hamner & Frasco, 2018](#)), for example, provide functions to run validation metrics such as *mean absolute error*, *root mean squared error*, or the five metrics of the confusion matrix. However, to get the output of, for example, Sawtooth Software or ChoiceModelR ([Sermas, 2022](#)) into the right format, the user needs some data wrangling. The package conjoint ([Bak & Bartlomowicz, 2012](#)) provides functions that are most similar to validateHOT's ones, but no validation functions are included and the package focuses on classical conjoint analysis, thus it is limited when applying more common conjoint methods. support.BWS ([Aizaki & Fogarty, 2023](#)) only covers best-worst scaling case 1 (i.e., MaxDiff). logitr ([Helveston, 2023](#)) provides market simulations tools, however, no validation metrics such as mean hit probability ([Voleti et al., 2017](#)) or hit rate ([Netzer & Srinivasan, 2011](#)). [Figure 1](#) shows a comparison of validateHOT's functions with current R packages. To the best of our knowledge, a package that converts raw utility scores into validation metrics or running a variety of marketing simulations (especially TURF) is missing.

Key functionalities	validateHOT (v 1.0.0)	Metrics (v 0.1.4)	caret (v 6.0-94)	conjoint (v 1.4)	philentropy (v 0.7.0)	logitr (v 1.1.1)	mlogit (v 1.1-1)	support.bws (v 0.4-6)
Confusion matrix	✓	✓	✓					
Creating design matrix				✓		✓	✓	✓
Creating holdout / market scenario	✓			✓		✓		
Estimate utilities				✓		✓	✓	✓
Estimate WTP						✓		
Hit rate	✓							
Kullback-Leibler-Divergence	✓				✓			
MAE, MedAe, RMSE	✓	✓	✓					
Market Shares	✓		✓	✓		✓		✓
Mean hit probability	✓							
TURF	✓							

Figure 1: Comparison of validateHOT's function to existing R packages

validateHOT is introduced with data estimated with Lighthouse Studio using effects-coding for creating the design matrix. It, however, can easily be used with data estimated with ChoiceModelR (Sermas, 2022), bayesm (Rossi, 2023), or STAN (2023), if used with similar settings (ChoiceModelR, for example, automatically implements effects-coding).

Key functions

validateHOT's functions can be categorized into four main components, see Table 1. To bring the data into the right format for some functions, the createHOT() function can be applied, which creates each alternatives' total utility by applying the additive utility model (Rao, 2014, p. 82).

Table 1: Overview of validateHOT's main components and their corresponding functions

Validation metrics	Confusion matrix	Market simulations	Rescaling scores
hitrate()	accuracy()	freqassort()	att_imp()
kl()	f1()	marksim()	prob_scores()
mae()	precision()	reach()	zc_diffs()
medae()	recall()	turf()	zero_anchored()
mhp()	specificity()		
rmse()			

Typical workflow

We provide the workflow for a MaxDiff study and a CBC study with only part-worth coded attributes (the vignette provides detailed examples for other CBCs and an ACBC).

MaxDiff

Creating Holdout Task / Market Scenario

After running the HB estimation (Allenby & Ginter, 1995; Lenk et al., 1996), the raw utility scores have to be exported and read into an R data frame. Assuming you included a validation task with seven alternatives plus the no-buy alternative (`none`). To create this validation task in R, we use the `createHOT()` function.

```
HOT <- createHOT(
  data = MaxDiff,
  id = "ID",
  none = "none",
  prod.levels = list(3, 10, 11, 15, 16, 17, 18),
  method = "MaxDiff",
  choice = "HOT",
  varskip = "Group"
)
```

Validating Holdout Task

To get the relevant validation metrics that are reported in conjoint studies, for example, hit rate (e.g., Ding et al., 2005) or mean hit probability (mhp, Voleti et al., 2017), we provide the data, the alternatives in the validation task (`opts`), and the actual choice (`choice`). The function can be implemented using the tidyverse (Wickham et al., 2019) logic.

```
hitrate(
  data = HOT,
  opts = c(Option_1:None),
  choice = choice
) %>%
  round(2)

## # A tibble: 1 x 5
##   HR      se chance   cor     n
##   <dbl> <dbl> <dbl> <dbl> <dbl>
## 1  55.7  5.98  12.5   39    70
```

Market Simulations

We also introduce two functions for market simulations, namely `marksim()` and `turf()`. In the following example, the market share is calculated according to the multinomial logit model (McFadden, 1974).

```
marksim(
  data = HOT,
  opts = c(Option_1:None),
  method = "sop"
) %>%
  mutate_if(is.numeric, round, 2)

## # A tibble: 8 x 5
##   Option      mw      se lo.ci up.ci
```

```

72 ##      <chr>      <dbl> <dbl> <dbl> <dbl>
73 ## 1 Option_1 18.3    4.12 10.2 26.4
74 ## 2 Option_2 11.3    2.69 6.05 16.6
75 ## 3 Option_3 4.08    1.49 1.16 6.99
76 ## 4 Option_4 32.5    4.45 23.8 41.2
77 ## 5 Option_5 1.93    0.92 0.13 3.72
78 ## 6 Option_6 10.4    2.68 5.12 15.6
79 ## 7 Option_7 5.58    1.75 2.15 9.01
80 ## 8 None     16.0    3.29 9.53 22.4

```

Next, `turf()`, a “product line extension model” (Miaoulis et al., 1990, p. 29), is a tool to find the perfect assortment that creates the highest reach and is especially powerful for MaxDiff studies (Chrzan & Orme, 2019, p. 108). To optimize the search for the optimal assortment, we also include the arguments `fixed`, to define alternatives that have to be part of the assortment, and `prohib`, to prohibit certain item combinations in the assortment (see the vignette for more details and how to apply `turf()` with data obtained using a likert scale).

For the following example, let’s assume that the user conducted an anchored MaxDiff analysis with 10 items (`opts`) and now wants to find the best assortment with a size of 3 items. The user uses the anchor (no-buy alternative) as a threshold.

```

turf(
  data = MaxDiff,
  opts = c(Option_01:Option_10),
  none = none,
  size = 3,
  approach = "thres"
) %>%
  head(., n = 5) %>%
  mutate_if(is.numeric, round, 2) %>%
  t() %>%
  as.data.frame() %>%
  slice(-1) %>%
  rename_all(., ~ paste0("Combo ", c(1:5)))

```

```

90 ##      Combo 1 Combo 2 Combo 3 Combo 4 Combo 5
91 ## reach    82.86   81.43   81.43   81.43   80.00
92 ## freq      1.46    1.57    1.43    1.41    1.44
93 ## Option_01      1      1      1      1      1
94 ## Option_02      0      0      1      0      0
95 ## Option_03      0      1      0      0      0
96 ## Option_04      1      0      1      1      0
97 ## Option_05      0      0      0      0      0
98 ## Option_06      1      1      0      0      1
99 ## Option_07      0      0      0      0      0
100 ## Option_08      0      0      0      0      1
101 ## Option_09      0      0      0      0      0
102 ## Option_10      0      0      0      1      0

```

103 CBC

104 Creating Holdout Task / Market Scenario

The setup is almost the same, only the arguments `prod.levels`, `coding`, and `method` are different or new, respectively.

```

H0T_CBC <- createH0T(
  data = CBC,

```

```

id = "ID",
none = "none",
prod.levels = list(c(4, 9, 19), c(8, 12, 17), c(5, 10, 17)),
coding = c(0, 0, 0),
method = "CBC",
choice = "HOT"
)

```

107 Rescaling Scores

108 We can also display the attributes importance scores. Therefore, we need to define the attribute
109 levels as well as the coding of the attributes.

```

att_imp(
  data = CBC,
  attrib = list(
    c(4:8),
    c(9:13),
    c(14:20)
  ),
  coding = c(rep(0, 3)),
  res = "agg"
) %>%
mutate_if(is.numeric, round, 2)

```

```

110 ## # A tibble: 3 x 3
111 ##   Option      mw    std
112 ##   <chr>    <dbl> <dbl>
113 ## 1 att_imp_1 35.7 11.3
114 ## 2 att_imp_2 27.7 10.0
115 ## 3 att_imp_3 36.6  9.32

```

116 Availability

117 validateHOT is available on [Github](#).

118 Acknowledgments

119 We would like to thank [Sawtooth Software](#) for their great transparent documentation.

120 References

- 121 Aizaki, H., & Fogarty, J. (2023). *R packages and tutorial for case 1 best-worst scaling*. 46,
122 100394. <https://doi.org/10.1016/j.jocm.2022.100394>
- 123 Allenby, G. M., & Ginter, J. L. (1995). Using Extremes to Design Products and Segment
124 Markets. *Journal of Marketing Research*, 32(4), 392–403. <https://doi.org/10.1177/002224379503200402>
- 125
- 126 Bak, A., & Bartlomowicz, T. (2012). *Conjoint analysis method and its implementation*
127 *in conjoint r package*. 239–248. [http://keii.ue.wroc.pl/pracownicy/tb/Bak_A_and_](http://keii.ue.wroc.pl/pracownicy/tb/Bak_A_and_Bartlomowicz_T_Conjoint_analysis_method_and_its_implementation_in_conjoint_R_package.pdf)
128 [Bartlomowicz_T_Conjoint_analysis_method_and_its_implementation_in_conjoint_R_](http://keii.ue.wroc.pl/pracownicy/tb/Bak_A_and_Bartlomowicz_T_Conjoint_analysis_method_and_its_implementation_in_conjoint_R_package.pdf)
129 [package.pdf](http://keii.ue.wroc.pl/pracownicy/tb/Bak_A_and_Bartlomowicz_T_Conjoint_analysis_method_and_its_implementation_in_conjoint_R_package.pdf)
- 130 Chrzan, K., & Orme, B. K. (2019). *Applied MaxDiff: A practitioner's guide to best-worst*
131 *scaling*. Sawtooth Software. ISBN: 9780999367728

- 132 Ding, M., Grewal, R., & Liechty, J. (2005). Incentive-Aligned Conjoint Analysis. *Journal of*
133 *Marketing Research*, 42(1), 67–82. <https://doi.org/10.1509/jmkr.42.1.67.56890>
- 134 Green, P. E., & Srinivasan, V. (1990). Conjoint Analysis in Marketing: New Developments
135 with Implications for Research and Practice. *Journal of Marketing*, 54(4), 3–19. <https://doi.org/10.1177/002224299005400402>
- 136
- 137 Hamner, B., & Frasco, M. (2018). *Metrics: Evaluation metrics for machine learning*. <https://CRAN.R-project.org/package=Metrics>
- 138
- 139 Helveston, J. P. (2023). *{Logitr}: Fast estimation of multinomial and mixed logit models*
140 *with preference space and willingness-to-pay space utility parameterizations*. 105. <https://doi.org/10.18637/jss.v105.i10>
- 141
- 142 Lenk, P. J., DeSarbo, W. S., Green, P. E., & Young, M. R. (1996). Hierarchical Bayes
143 Conjoint Analysis: Recovery of Partworth Heterogeneity from Reduced Experimental
144 Designs. *Marketing Science*, 15(2), 173–191. <https://doi.org/10.1287/mksc.15.2.173>
- 145 McFadden, D. (1974). Conditional logit analysis of qualitative choice behavior. In P. Zarembka
146 (Ed.), *Frontiers in econometrics* (pp. 105–142). Academic Press. ISBN: 0127761500
- 147 Miaoulis, G., Parsons, H., & Free, V. (1990). Turf: A new planning approach for product line
148 extensions. *Marketing Research*, 2(1), 28–40.
- 149 Netzer, O., & Srinivasan, V. (2011). Adaptive Self-Explication of Multiattribute Preferences.
150 *Journal of Marketing Research*, 48(1), 140–156. <https://doi.org/10.1509/jmkr.48.1.140>
- 151 Orme, B. K. (2015). *Including holdout choice tasks in conjoint studies*.
- 152 Rao, V. R. (2014). *Applied conjoint analysis*. Springer Berlin Heidelberg. <https://doi.org/10.1007/978-3-540-87753-0>
- 153
- 154 Rossi, P. (2023). *Bayesm: Bayesian inference for marketing/micro-econometrics*. <https://CRAN.R-project.org/package=bayesm>
- 155
- 156 Sermas, R. (2022). *ChoiceModelR: Choice modeling in r*. <https://CRAN.R-project.org/package=ChoiceModelR>
- 157
- 158 Stan Development Team. (2023). *{RStan}: The {r} interface to {stan}*. <https://mc-stan.org/>
- 159 Voleti, S., Srinivasan, V., & Ghosh, P. (2017). An approach to improve the predictive power
160 of choice-based conjoint analysis. *International Journal of Research in Marketing*, 34(2),
161 325–335. <https://doi.org/10.1016/j.ijresmar.2016.08.007>
- 162 Wickham, H., Averick, M., Bryan, J., Chang, W., McGowan, L. D., François, R., Grolemond,
163 G., Hayes, A., Henry, L., Hester, J., Kuhn, M., Pedersen, T. L., Miller, E., Bache, S. M.,
164 Müller, K., Ooms, J., Robinson, D., Seidel, D. P., Spinu, V., ... Yutani, H. (2019). *Welcome*
165 *to the {tidyverse}*. 4, 1686. <https://doi.org/10.21105/joss.01686>
- 166 Yang, L. (Cathy), Toubia, O., & Jong, M. G. de. (2018). Attention, Information Processing,
167 and Choice in Incentive-Aligned Choice Experiments. *Journal of Marketing Research*, 55(6),
168 783–800. <https://doi.org/10.1177/0022243718817004>