

nnR: A package to perform algebraic operations on neural networks

Shakil Rafi^{1,2*} and Joshua Lee Padgett^{3*}

¹ Department of Mathematical Sciences, University of Arkansas, Fayetteville, AR, 72701. ² Department of Data Science, University of Arkansas, Fayetteville, AR, 72701. ³ Toyota Financial Services, Plano, TX, 75024. * These authors contributed equally.

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#)
- [Repository](#)
- [Archive](#)

Editor: [↗](#)

Submitted: 20 February 2024

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

There exists an algebraic way of viewing feedforward multi-layer perceptrons as an ordered tuple of ordered pairs. That is to say a neural network is $\nu = ((W_1, b_1), (W_2, b_2), \dots (W_L, b_L))$, for some collection of weight matrices W_i and bias vectors b_i .

These were first introduced in Petersen & Voigtlaender (2018), extended in (Grohs et al., 2018), and (Jentzen et al., 2023), and along with that several operations such as composition, stacking, scalar left and right multiplication, neural network sums and finally neural networks for squaring and products of real numbers were introduced.

This was extended in (Rafi et al., 2024) to include neural networks for raising to a power, neural network polynomials, neural network exponentials, sines, cosines, and a rudimentary trapezoidal rule implementation.

This is not the standard way neural networks are envisioned, which are as piecewise linear approximants. This way of building out networks that approximate transcendental functions, using algebraic operations of sum, scalar multiplication, stacking, products, and raising to powers, differs markedly from deep learning orthodoxy. It is hoped that this package will find use in the community.

A full explanation of what these algebraic operations are, and what these neural network sines, cosines, and exponents are is explained in (Rafi et al., 2024).

Statement of need

Despite this framework's wide use in e.g. (Grohs et al., 2018), (Grohs et al., 2022), and (Ackermann et al., 2023), in addition to (Grohs et al., 2023) and (Jentzen et al., 2023), this framework has lacked a consistent implementation in a widely available language.

A custom solution is needed as widely available artificial neural network software like PyTorch or TensorFlow are inadequate to the task. Specifically the authors believe that operations such as the Pwr network with its associated tunnel networks cannot adequately be described using the layer structure that PyTorch or indeed TensorFlow require. This is because of the way this network is defined, purely in terms of its associated parameters q and ε . This would lead to an uncountably infinitely many versions of the same network, each needing to be implemented separately.

In addition, this framework only envisions neural networks whose weight and bias parameters are already given. Typical neural network libraries require training via backpropagation, and it is somewhat difficult to see how one may implement a neural network in these common libraries without actually specifying backpropagation.

40 Finally, all neural network architectures posited to exist in (Rafi et al., 2024), such as Pwr,
 41 Xpn, Csn, Sne, and the 1-D interpolation scheme have associated with theme extensive, and
 42 sometimes very convoluted bounds for parameter, depth, and accuracy. It is nice to have an
 43 implementation in R if only to run simulations, but also to test out some of these bounds that
 44 are proposed, and further as pedagogical tools to promote a wider dissemination of this rather
 45 new neural network calculus.

46 As a bonus, R's widely known and easy to use infix notation with `%function%` allows us
 47 to translate directly, theorems in (Rafi et al., 2024), (Grohs et al., 2023), and (Jentzen et
 48 al., 2023) to software. For instance $\frac{1}{2} \triangleright (\nu_1 \bullet \nu_2)$ is rendered directly as `0.5 %slm% (nu_1`
 49 `%comp% nu_2)`.

50 A concerted effort has been made to make this software as fast as possible, with R vectorization.
 51 Future work will be focused on re-implementing this, but using Rcpp. The source code repository
 52 for nnR has been archived to Zenodo with <https://doi.org/10.5281/zenodo.10672209>

53 Acknowledgements

54 This work was conducted fully or in part on computational resources at the Arkansas High
 55 Performance Computing Center

56 References

- 57 Ackermann, J., Jentzen, A., Kruse, T., Kuckuck, B., & Padgett, J. L. (2023). *Deep neural*
 58 *networks with ReLU, leaky ReLU, and softplus activation provably overcome the curse of*
 59 *dimensionality for kolmogorov partial differential equations with lipschitz nonlinearities in*
 60 *the L^p -sense*. <https://arxiv.org/abs/2309.13722>
- 61 Grohs, P., Hornung, F., Jentzen, A., & Wurstemberger, P. von. (2018). *A proof that artificial*
 62 *neural networks overcome the curse of dimensionality in the numerical approximation of*
 63 *Black-Scholes partial differential equations* (Papers No. 1809.02362). arXiv.org. [https://](https://ideas.repec.org/p/arx/papers/1809.02362.html)
 64 ideas.repec.org/p/arx/papers/1809.02362.html
- 65 Grohs, P., Hornung, F., Jentzen, A., & Zimmermann, P. (2023). Space-time error estimates for
 66 deep neural network approximations for differential equations. *Advances in Computational*
 67 *Mathematics*, 49(1), 4. <https://doi.org/10.1007/s10444-022-09970-2>
- 68 Grohs, P., Jentzen, A., & Salimova, D. (2022). Deep neural network approximations for
 69 solutions of PDEs based on monte carlo algorithms. *Partial Differential Equations and*
 70 *Applications*, 3(4). <https://doi.org/10.1007/s42985-021-00100-z>
- 71 Jentzen, A., Kuckuck, B., & Wurstemberger, P. von. (2023). *Mathematical introduction to*
 72 *deep learning: Methods, implementations, and theory*. <https://arxiv.org/abs/2310.20360>
- 73 Petersen, P., & Voigtlaender, F. (2018). Optimal approximation of piecewise smooth functions
 74 using deep ReLU neural networks. *Neural Netw*, 108, 296–330. [https://doi.org/10.1016/j.](https://doi.org/10.1016/j.neunet.2018.08.019)
 75 [neunet.2018.08.019](https://doi.org/10.1016/j.neunet.2018.08.019)
- 76 Rafi, S., Padgett, J. L., & Nakarmi, U. (2024). Towards an Algebraic Framework For
 77 Approximating Functions Using Neural Network Polynomials. In *arXiv.org*. [https://arxiv.](https://arxiv.org/abs/2402.01058v1)
 78 [org/abs/2402.01058v1](https://arxiv.org/abs/2402.01058v1)