

ReLax: Efficient and Scalable Recourse Explanation Benchmarking using JAX

Hangzhi Guo¹, Xinchang Xiong², Wenbo Zhang¹, and Amulya Yadav¹

¹ Penn State University, USA ² Duke University, USA ¶ Corresponding author

DOI: [10.xxxxxx/draft](https://doi.org/10.xxxxxx/draft)

Software

- [Review](#)
- [Repository](#)
- [Archive](#)

Editor: ¶

Submitted: 24 January 2024

Published: unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.0 International License ([CC BY 4.0](#)).

Summary

From healthcare to criminal justice, machine learning (ML) models have permeated society to support domain experts in making decisions. Given the high-stakes nature of decision outcomes in some real-world domains, concerns over the trustworthiness of ML model predictions have raised increasing attention. These concerns have spurred surging research interests in explainable artificial intelligence (XAI), whose mission is to equip end-users with an understanding (or explanation) of AI decision making, and to help provide assessments to end-users about when to rely on ML models and when to exercise caution.

Within the XAI domain, recourse¹ has emerged as a notable technique, which provides alternative scenarios (which lead to desirable AI decisions) to individuals adversely affected by ML predictions, thereby elucidating the underlying decision-making mechanisms to end users. For instance, recourse methods can provide corrective suggestions for loan applicants who have been rejected by a bank's ML algorithm, or give practical advice to teachers handling students at risk of dropping out from school. Numerous recourse explanation methods have been recently proposed. Yet, the substantial runtime overhead imposed by many recourse explanation methods compels current research to limit their evaluation and benchmarking to medium-sized datasets (i.e., ~50k data points). This limitation has significantly impeded progress in the field of algorithmic recourse, while it also raises valid concerns about the scalability of existing approaches.

To address this challenge, we propose ReLax, a JAX-based benchmarking library, designed for efficient and scalable recourse generation. ReLax supports a variety of recourse methods and datasets, demonstrating performance improvements of at least two orders of magnitude over current libraries. Notably, ReLax can benchmark real-world datasets up to 10 million data points, a 200-fold increase over existing norms, without imposing prohibitive computational costs.

Statement of need

Recourse and counterfactual explanation methods concentrate on the generation of new instances that lead to contrastive predicted outcomes (Karimi et al., 2020; Stepin et al., 2021; Verma et al., 2020). Given their ability to provide actionable recourse, these explanations are often favored by human end-users (Bhatt et al., 2020; Binns et al., 2018; Miller, 2019).

Despite progress made in counterfactual explanation research (Guo, Jia, et al., 2023; Guo, Nguyen, et al., 2023; Mothilal et al., 2020; Upadhyay et al., 2021; Ustun et al., 2019; Vo et al., 2023; Wachter et al., 2017), current research practices often restrict the evaluation of recourse explanation methods on medium-sized datasets (with under 50k data points). This constraint

¹Algorithmic recourse (Ustun et al., 2019) and counterfactual explanation (Wachter et al., 2017) share close connections (Stepin et al., 2021; Verma et al., 2020), which leads us to use these terms interchangeably

39 primarily stems from the excessive runtime overhead of recourse generation by existing open-
40 source recourse libraries (Klaise et al., 2021; Mothilal et al., 2020; Pawelczyk et al., 2021). For
41 instance, as shown in Figure 1, the CARLA library (Pawelczyk et al., 2021) requires roughly 30
42 minutes to benchmark the *adult* dataset (Kohavi & Becker, 1996) containing $\sim 32,000$ data
43 points. At this speed, because the runtime scales linearly with the number of data points, it
44 would take CARLA approximately 15 hours to benchmark a dataset with 1 million samples, and
45 nearly one week to benchmark a 10-million sized dataset. Consequently, this severe runtime
46 overhead hinders the large-scale analysis of recourse explanations and the research development
47 of new recourse methods.




Figure 1: Runtime comparison of the *adult* dataset (Kohavi & Becker, 1996) between ReLax and three open-source recourse libraries (CARLA (Pawelczyk et al., 2021), DiCE (Mothilal et al., 2020), and alibi (Klaise et al., 2021)).

48 In this work, we present ReLax (Recourse Explanation Library using Jax), the *first* recourse
49 explanation library in JAX (Bradbury et al., 2018; Frostig et al., 2018). Our contributions are
50 three-fold:

- 51 ■ (Fast and Scalable System) ReLax is an *efficient and scalable benchmarking library* for
52 recourse and counterfactual explanations.
- 53 ■ (Comprehensive set of Methods) ReLax implements 9 widely-used and popular recourse
54 explanation methods. In addition, ReLax includes 14 medium-sized publicly available
55 datasets, and one large-scale publicly available dataset.
- 56 ■ (Extensive Experiments) We perform comprehensive experiments on both medium-sized
57 and large-sized datasets, which showcases the usability and scalability of ReLax.

58 Efficiency and Scalability in ReLax

59 ReLax supports three recourse generation strategies: *sequential*, *vectorized*, and *parallelized*
60 strategy. In particular, the *sequential* generation strategy involves generating recourse explana-
61 tions one after another. Unfortunately, while widely used in existing recourse libraries (Klaise
62 et al., 2021; Mothilal et al., 2020; Pawelczyk et al., 2021), this strategy is inefficient when
63 benchmarking large datasets.

64 On the other hand, the *vectorized* and *parallelized* strategies play a vital role in equipping
65 ReLax to benchmark large-scale datasets with a practical computational cost. The *vectorized*
66 strategy takes advantage of modern hardware by applying recourse generation operations to the
67 entire dataset *at once*. This strategy considerably accelerates recourse generation by performing
68 Single Instruction on Multiple Data (SIMD). Additionally, the *parallelized* strategy enables the
69 usage of multiple computing devices (e.g., multiple GPUs/TPUs) to further improve scalability.
70 Furthermore, ReLax further enhances its performance by fusing inner recourse generation steps
71 via the Just-In-Time (JIT) compilation feature provided by jax. Together, ReLax ensures
72 efficient and scalable performance across diverse data scales and complexities.

73 Recourse Methods & Datasets

74 ReLax implements nine recourse methods using JAX including (i) three non-parametric methods
75 (VanillaCF (Wachter et al., 2017), DiverseCF (Mothilal et al., 2020), GrowingSphere (Laugel
76 et al., 2017)); (ii) three semi-parametric methods (ProtoCF (Van Looveren & Klaise, 2019),
77 C-CHVAE (Pawelczyk et al., 2020), CLUE (Antoran et al., 2021)); and (iii) three parametric
78 methods (VAE-CF (Mahajan et al., 2019), CounterNet (Guo, Nguyen, et al., 2023), L2C (Vo
79 et al., 2023)).

80 Furthermore, we gather 14 medium-sized binary-classification tabular datasets. We also
81 benchmark over the forktable dataset (Ding et al., 2021) for predicting individuals' annual
82 income. This US censuring dataset contains ~ 10 million data points. To our knowledge,
83 this is the first attempt to benchmark a dataset at the scale of 10 million data points in the
84 recourse explanation community.




Figure 2: Comparison of recourse method performance across 14 medium-sized datasets. It is desirable to achieve *high* validity, *low* proximity, and *low* runtime.




Figure 3: Runtime comparison of different recourse generation strategies on the forktable dataset (Ding et al., 2021).

85 Experimental Results

86 **Figure 2** compares the validity, proximity, and runtime achieved by nine recourse methods
87 averaged on 14 medium-sized datasets. In particular, validity and proximity measure the quality
88 of the generated counterfactual explanations. We observe that CounterNet and Growing
89 Sphere achieve the best validity score, and C-CHVAE achieves the best proximity score. In
90 terms of runtime, all recourse methods complete the entire recourse generation process within

91 10 seconds, while CounterNet and VAE CF outperform others by finishing execution under 2
92 seconds.

93 **Figure 3** compares the runtime for each recourse explanation method in adopting the vectorized
94 and parallelized strategies on the forktable dataset (with 10M data points). First, ReLax is
95 highly efficient in benchmarking the large-scale dataset, with the maximum runtime being under
96 30 minutes. On the other hand, by estimation, existing libraries should take at least one week
97 to complete recourse generation on datasets at this scale. In addition, the parallelized strategy
98 cuts the runtime by roughly 4X, which demonstrates ReLax's potential in benchmarking even
99 larger datasets.

100 References

- 101 Antoran, J., Bhatt, U., Adel, T., Weller, A., & Hernández-Lobato, J. M. (2021). Getting
102 a {CLUE}: A method for explaining uncertainty estimates. *International Conference on*
103 *Learning Representations*. <https://openreview.net/forum?id=XSLF1XFq5h>
- 104 Bhatt, U., Xiang, A., Sharma, S., Weller, A., Taly, A., Jia, Y., Ghosh, J., Puri, R., Moura, J.
105 M. F., & Eckersley, P. (2020). Explainable machine learning in deployment. *Proceedings*
106 *of the 2020 Conference on Fairness, Accountability, and Transparency*, 648–657. <https://doi.org/10.1145/3351095.3375624>
- 107
- 108 Binns, R., Van Kleek, M., Veale, M., Lyngs, U., Zhao, J., & Shadbolt, N. (2018). 'It's reducing
109 a human being to a percentage' perceptions of justice in algorithmic decisions. *Proceedings*
110 *of the 2018 CHI Conference on Human Factors in Computing Systems*, 1–14.
- 111 Bradbury, J., Frostig, R., Hawkins, P., Johnson, M. J., Leary, C., Maclaurin, D., Necula, G.,
112 Paszke, A., VanderPlas, J., Wanderman-Milne, S., & Zhang, Q. (2018). *JAX: Composable*
113 *transformations of Python+NumPy programs* (Version 0.4.10). <http://github.com/google/jax>
- 114
- 115 Ding, F., Hardt, M., Miller, J., & Schmidt, L. (2021). Retiring adult: New datasets for fair
116 machine learning. *Advances in Neural Information Processing Systems*, 34.
- 117 Frostig, R., Johnson, M. J., & Leary, C. (2018). Compiling machine learning programs via
118 high-level tracing. *Systems for Machine Learning*, 4(9).
- 119 Guo, H., Jia, F., Chen, J., Squicciarini, A., & Yadav, A. (2023). RoCourseNet: Robust
120 training of a prediction aware recourse model. *Proceedings of the 32nd ACM International*
121 *Conference on Information and Knowledge Management*, 619–628.
- 122 Guo, H., Nguyen, T., & Yadav, A. (2023). CounterNet: End-to-end training of prediction
123 aware counterfactual explanation. *Proceedings of the 29th ACM SIGKDD Conference on*
124 *Knowledge Discovery and Data Mining (KDD '23), August 6–10, 2023, Long Beach, CA,*
125 *USA*. <https://doi.org/10.1145/3580305.3599290>
- 126 Karimi, A.-H., Barthe, G., Schölkopf, B., & Valera, I. (2020). A survey of algorithmic recourse:
127 Definitions, formulations, solutions, and prospects. *arXiv Preprint arXiv:2010.04050*.
- 128 Klaise, J., Loooveren, A. V., Vacanti, G., & Coca, A. (2021). Alibi explain: Algorithms for
129 explaining machine learning models. *Journal of Machine Learning Research*, 22(181), 1–7.
130 <http://jmlr.org/papers/v22/21-0017.html>
- 131 Kohavi, R., & Becker, B. (1996). UCI machine learning repository: Adult data set. In
132 *1996-05-01[2014-10-01]*. <http://archive.ics.uci.edu/ml/data-sets/Adult>.
- 133 Laugel, T., Lesot, M.-J., Marsala, C., Renard, X., & Detyniecki, M. (2017). Inverse classification
134 for comparison-based interpretability in machine learning. *arXiv Preprint arXiv:1712.08443*.
- 135 Mahajan, D., Tan, C., & Sharma, A. (2019). Preserving causal constraints in counterfactual
136 explanations for machine learning classifiers. *arXiv Preprint arXiv:1912.03277*.

- 137 Miller, T. (2019). Explanation in artificial intelligence: Insights from the social sciences.
138 *Artificial Intelligence*, 267, 1–38.
- 139 Mothilal, R. K., Sharma, A., & Tan, C. (2020). Explaining machine learning classifiers through
140 diverse counterfactual explanations. *Proceedings of the 2020 Conference on Fairness,*
141 *Accountability, and Transparency*, 607–617.
- 142 Pawelczyk, M., Bielawski, S., Heuvel, J. van den, Richter, T., & Kasneci, G. (2021). CARLA: A
143 python library to benchmark algorithmic recourse and counterfactual explanation algorithms.
144 *Advances in Neural Information Processing Systems Track on Datasets and Benchmarks*.
- 145 Pawelczyk, M., Broelemann, K., & Kasneci, G. (2020). Learning model-agnostic counterfactual
146 explanations for tabular data. *Proceedings of the Web Conference 2020*, 3126–3132.
- 147 Stepin, I., Alonso, J. M., Catala, A., & Pereira-Fariña, M. (2021). A survey of contrastive and
148 counterfactual explanation generation methods for explainable artificial intelligence. *IEEE*
149 *Access*, 9, 11974–12001.
- 150 Upadhyay, S., Joshi, S., & Lakkaraju, H. (2021). Towards robust and reliable algorithmic
151 recourse. *arXiv Preprint arXiv:2102.13620*.
- 152 Ustun, B., Spangher, A., & Liu, Y. (2019). Actionable recourse in linear classification.
153 *Proceedings of the Conference on Fairness, Accountability, and Transparency*, 10–19.
- 154 Van Looveren, A., & Klaise, J. (2019). Interpretable counterfactual explanations guided by
155 prototypes. *arXiv Preprint arXiv:1907.02584*.
- 156 Verma, S., Dickerson, J., & Hines, K. (2020). Counterfactual explanations for machine learning:
157 A review. *arXiv Preprint arXiv:2010.10596*.
- 158 Vo, V., Le, T., Nguyen, V., Zhao, H., Bonilla, E. V., Haffari, G., & Phung, D. (2023). Feature-
159 based learning for diverse and privacy-preserving counterfactual explanations. *Proceedings of*
160 *the 29th ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, 2211–2222.
- 161 Wachter, S., Mittelstadt, B., & Russell, C. (2017). Counterfactual explanations without
162 opening the black box: Automated decisions and the GDPR. *Harv. JL & Tech.*, 31, 841.