

OptiCommPy: Open-source Simulation of Fiber Optic

- 2 Communications with Python
- Edson Porto da Silva 1 and Adolfo Fernandes Herbster **
- 1 Electrical Engineering Department, Federal University of Campina Grande (UFCG), Brazil * These
- authors contributed equally.

DOI: 10.xxxxx/draft

Software

- Review 🗗
- Repository 🗗
- Archive ♂

Editor: ♂

Submitted: 15 February 2024 **Published:** unpublished

License

Authors of papers retain copyright and release the work under a Creative Commons Attribution 4.8 International License (CC BY 4.0).

Summary

OptiCommPy is an open-source Python package designed for simulating fiber optical communication systems and subsystems. OptiCommPy is freely accessible, providing researchers, students, and engineers with the option to simulate various fiber optical communication systems at the physical layer. Additionally, the toolbox incorporates numerous digital signal processing (DSP) algorithms, particularly essential for coherent optical systems.

Statement of need

Optical fiber communication dominates the transmission of high-speed data traffic, owing to various physical, engineering, and economic factors. Worldwide efforts are continuously being made to research and develop optical communication technologies that can support both current and future Internet infrastructure. The expansion of optical networks necessitates a swift transition from scientific breakthroughs in research labs to telecommunications industry products and solutions. Furthermore, the ever-increasing demand for bandwidth and connectivity places constant pressure on the development of faster and more efficient optical fiber communications (Winzer & Neilson, 2017).

Today, optical communication systems engineering is a multidisciplinary field encompassing various areas of science and technology, including laser science, photonic devices, fiber optics modeling and engineering, digital signal processing, and communications theory. As we approach the limits of information transmission through optical fibers, more sophisticated engineering is required for the construction of optical transmitters and receivers, involving advanced digital signal processing (DSP) (Essiambre et al., 2010), (Savory, 2010). The emergence of high-speed application-specific integrated circuits (ASICs) and advanced DSP algorithms has propelled coherent optical transmission systems to the forefront of high-capacity transmission via optical fibers (Sun et al., 2020).

Whether in the research or development stages, the study of optical communication systems typically necessitates the use of robust computational models to simulate various aspects of the system. For instance, it may be essential to comprehend how information-carrying signals transmitted over fibers will be affected by propagation phenomena such as chromatic dispersion (CD), polarization mode dispersion (PMD), nonlinear effects, and noise (Agrawal, 2002). This information ultimately determines the performance metrics of the transmission system, which play a crucial role in selecting the most suitable technology to become an industrial standard.

Presently, a variety of optical communication simulation toolboxes are accessible. While the majority of these are proprietary software packages (Optiwave, 2023), (VPIphotonics, 2023), (Synopsys, 2023), a few are open-source but are designed to operate within proprietary software environments such as Matlab® (dtu-dsp, 2015), (Paolo Serena, 2021).



- The module structure of the OptiCommPy package is illustrated in Fig. 1. At the top level,
- the package is named optic, containing five sub-packages: comm, models, dsp, utils, and
- 43 plot.




Figure 1: Structure of modules of the OptiCommPy package.

The comm sub-package comprises three modules designed for implementing various digital modulation and demodulation schemes (Proakis, 2001), including pulse amplitude modulation (PAM), quadrature amplitude modulation (QAM), phase-shift keying (PSK), and on-off keying (OOK). Evaluating the performance of these diverse digital communication schemes is made possible through different metrics, such as bit-error-rate (BER), symbol-error-rate (SER), error vector magnitude (EVM), mutual information (MI), and generalized mutual information (GMI) (Alvarado et al., 2018), all available within the comm.metrics module.

The models sub-package contains the majority of the mathematical/physical models used to build OptiCommPy simulations. Within the models.devices module, one can access models for a range of optical devices, encompassing optical Mach-Zehnder modulators, photodiodes, optical hybrids, optical coherent receivers, and more. These functions serve as fundamental building blocks for constructing simulations of optical transmitters and receivers. In the models.channels module, a collection of mathematical models for the fiber optic channel is provided, spanning from basic additive white Gaussian noise (AWGN) and linear propagation models to more sophisticated non-linear propagation models rooted in variants of the splitstep Fourier method (SSFM)(Agrawal, 2002). In particular, it includes an implementation of the Manakov model to simulate nonlinear transmission over a fiber optic channel with polarization-multiplexing (Marcuse et al., 1997). Certain computationally intensive models, such as the Manakov SSFM, have a CuPy-based version (Okuta et al., 2017) accessible via models.modelsGPU, designed specifically for execution with CUDA GPU acceleration (NVIDIA et al., 2020).

The dsp sub-package is a collection of DSP algorithms ranging from basic signal processing operations, such as linear finite impulse response filtering, to more advanced algorithms, e.g. blind adaptive equalization. Currently, the dsp sub-package contains three specialized modules: dsp.clockRecovery provides algorithms for clock and timing synchronization; dsp.equalization contains implementations of common digital equalization algorithms used in optical communications; dsp.carrierRecovery provides algorithms for carrier frequency and phase recovery. These sub-packages covers all the basic DSP functionalities required in



- most of the modern coherent optical transceivers.
- Finally, the utils and the plot sub-packages provide functions that implement a few general
- utilities and custom plotting functions to visualize signals (eyediagram plots, constellation
- 75 plots, etc).
- Several types of analysis can be conducted to characterize transmission performance across
- 77 various system parameters. For instance, one can generate performance curves that depict
- 78 BER and Q-factor as functions of received optical power at varying transmission distances, as
- 79 illustrated in Fig.~3.




Figure 2: Performance metrics for different transmission distances and received optical powers, characterizing the increasing penalty from chromatic dispersion with the distance in a 10 Gb/s OOK transmission system. (a) BER vs received optical power for different transmission distances; (b) Q-factor vs received optical power for different transmission distances.

- 80 A collection of examples of utilization of OptiCommPy to build several different simulation
- setups, including advanced setups with non-linear fiber propagation models, WDM trans-
- mission, and coherent detection can be found in https://github.com/edsonportosilva/Opti-
- 83 CommPy/tree/main/examples.

Acknowledgements

- $_{85}$ This work was supported by the National Council for Scientific and Technological Development
- 86 (CNPq), Brazil, grant 406684/2021-9.

References

- 88 Agrawal, G. P. (2002). Fiber-optic communication systems (3rd ed.). John Wiley & Sons.
- Alvarado, A., Fehenberger, T., Chen, B., & Willems, F. M. J. (2018). Achievable Information Rates for Fiber Optics: Applications and Computations. *J. Light. Technol.*, 36(2), 424–439. https://doi.org/10.1109/JLT.2017.2786351
- dtu-dsp. (2015). Robochameleon: A matlab coding framework and component library for optical communication systems (Version 0.1). https://github.com/dtu-dsp/Robochameleon
- Essiambre, R. J., Foschini, G. J., Winzer, P. J., Kramer, G., & Goebel, B. (2010). Capacity Limits of Optical Fiber Networks. *J. Light. Technol.*, 28(4), 662–701. https://doi.org/10.1109/JLT.2009.2039464
- Marcuse, D., Menyuk, C. R., & Wai, P. K. A. (1997). Application of the Manakov-PMD equation to studies of signal propagation in optical fibers with randomly varying birefringence.



J. Light. Technol., 15(9), 1735–1745. https://doi.org/10.1109/50.622902 NVIDIA, Vingelmann, P., & Fitzek, F. H. P. (2020). CUDA, release: 10.2.89. https: 100 //developer.nvidia.com/cuda-toolkit 101 Okuta, R., Unno, Y., Nishino, D., Hido, S., & Loomis, C. (2017). CuPy: A NumPy-102 compatible library for NVIDIA GPU calculations. Proceedings of Workshop on Machine 103 Learning Systems (LearningSys) in the Thirty-First Annual Conference on Neural Information Processing Systems (NIPS). 105 Optiwave. (2023). OptiSystem. https://optiwave.com/products/optisystem/ 106 Paolo Serena. (2021). Optilux, the optical simulatr toolbox. https://optilux.sourceforge.io/ 107 Proakis, J. G. (2001). Digital communications (4th ed.). McGraw Hill. 108 Savory, S. J. (2010). Digital coherent optical receivers: Algorithms and subsystems. IEEE J. 109 Sel. Top. Quantum Electron., 16(5), 1164-1179. https://doi.org/10.1109/JSTQE.2010. 110 2044751 111 Sun, H., Torbatian, M., Karimi, M., Maher, R., Thomson, S., Tehrani, M., Gao, Y., Kumpera, 112 A., Soliman, G., Kakkar, A., Osman, M., El-Sahn, Z. A., Doggart, C., Hou, W., Sutarwala, 113 S., Wu, Y., Chitgarha, M. R., Lal, V., Tsai, H.-S., ... Kandappan, P. (2020). 800G DSP 114 ASIC design using probabilistic shaping and digital sub-carrier multiplexing. Journal of 115 Lightwave Technology, 38(17), 4744-4756. https://doi.org/10.1109/JLT.2020.2996188 116 Synopsys. (2023). Synopsys OptSim for optical communication. https://www.synopsys.com/ 117 photonic-solutions/optsim.html/ 118 VPIphotonics. (2023). VPItransmissionMaker™ optical systems. https://www.vpiphotonics. 119 com/Tools/OpticalSystems/ 120 Winzer, P. J., & Neilson, D. T. (2017). From scaling disparities to integrated parallelism: 121 A decathlon for a decade. Journal of Lightwave Technology, 35(5), 1099-1115. https: 122 //doi.org/10.1109/JLT.2017.2662082 123