FACT

AD 2.1 AERODROME LOCATION INDICATOR AND NAME

FACT - CAPE TOWN INTERNATIONAL

AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	*ARP co-ordinates and site at AD*	335816.93S 0183615.45E
2	*Direction and distance from city*	7 NM SE
3	*Reference elevation/Reference temperature*	151 FT 22,2°C
4	*Geoid undulation at aerodrome elevation position*	101.2 FT
5	*MAG VAR* *annual change*	27°W (2025) 0°14' W
6	*AD operator, address, telephone, telefax, email, AFS address and, if available, website address.*	Airports Company SA Ltd. Postal address: P/Bag X9002 Cape Town International Airport, 7525. Telephone numbers: AD Exchange +27 21 937 1200 ATC: +27 21 937 1116/7 ATIS: +27 21 937 1179 MET: Admin: +27 21 935 5700, Forecaster: +27 60 819 7346, Observer: +27 21 937 1250.
7	*Types of traffic permitted (IFR / VFR)*	IFR/VFR
8	*Remarks*	NIL

AD 2.3 OPERATIONAL HOURS

1	*AD Operator*	H24
2	*Customs and immigration*	Immigration: MON-SUN: H24 Full shift: 0230-2230; 1x standby person: 2230-0230 Customs: MON-SUN: H24 Due to new immigration law, all international and regional flights arriving or departing from FACT must park on the main aprons to clear immigration. A list of service providers are available from the Apron Office as assistance may be required to and from the International Terminal. TEL: +27 21 937 1308.
3	*Health and sanitation*	Services available during scheduled operations
4	*AIS briefing office*	H24 Central AIS TEL: +27 86 035 9669, +27 11 928 6517/8
5	*ATS reporting office (ARO)*	NIL
6	*MET briefing office*	MON-SUN: 0200 - 1830
7	*ATS*	H24

8	*Fuelling*	-Cape Town International Fuelling Services: H24 TEL: +27 82 714 9123 - Signature Flight support: 24 HR on request TEL: +27 21 934 0350. -Execujet Aviation Group: 24 HR on request. TEL: +27 21 934 5764/ +27 82 902 3719.
9	*Handling*	H24
10	*Security*	H24
11	*De-icing*	NIL INFO AVBL
12	*Remarks*	For slots, refer to ENR 1.9

AD 2.4 HANDLING SERVICES AND FACILITIES

1	*Cargo-handling facilities*	Capable of handling B74F. Equipment to handle single items up to 20 tonnes by special arrangement. - Menzies Aviation TEL: +27 11 920 7000, Cell: +27 83 290 2556 Email: gertvd.merwe@menziesaviation.com www.menziesaviation.com - Swissport Cargo Services TEL: +27 21 812 3815, Cell: +27 82 805 2960 Email: moenier.vardy@swissport.com - Bidair Cargo TEL: +27 21 935 6102, After HR: +27 83 283 8836 Email: wayned@bidaircargo.co.za
2	*Fuel and Oil types*	Fuel grades: JET A1, AVGAS 100; Oil grades: ASO W100, W120, 15W50 Oxygen and related servicing: Oxygen for First Aid; oxygen AVBL for replenishment of high flying ACFT.
3	*Fuelling facilities and capacity*	Jet A1 Hydrant rate 3000 L/MIN available aprons A, B and C. Two Jet A1 tankers for remote and general aviation areas rate 600 to 900 L/MIN. AVGAS-tanker refuelling only.
4	*De-icing facilities*	NIL INFO AVBL
5	*Hangar space for visiting aircraft*	Available by prior arrangement.
6	*Repair facilities for visiting aircraft*	Repair facilities normally available: Major and minor for all types; maintenance hangars with facilities for change of engine by prior arrangement.
7	*Remarks*	NIL

AD 2.5 PASSENGER FACILITIES

1	*Hotels*	AVBL, Unlimited in Cape Town and suburb hotels; northern areas hotels.
2	*Restaurants*	Restaurants AVBL, MON-SUN: 0345 - 2230.
3	*Transportation*	Transportation: Bus to Cape Town taxis to all areas
4	*Medical facilities*	Pharmacy AVBL, MON-SUN: 0345 - 2230. TEL: +27 21 935 4445. Hospitals and clinics in town.
5	*Bank and Post Office*	AVBL, MON-SUN: 0345 - 2230.
6	*Tourist office*	AVBL, MON-SUN: 0345 - 2230.
7	*Remarks*	NIL

AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	*Aerodrome category for fire fighting*	CAT 9; 24HR daily with trained personnel. 4 shifts, 15 firefighters per day shift and 14 firefighters per night shift. Total number of personnel is 72.
2	*Rescue equipment*	Standard firefighting equipment carried on all fire tenders in accordance with ICAO and SACAA requirements for Category 9 airport. 4 Rosenbauer CA7 - 8 x 8 fire fighting vehicles, Extinguishing medium excluding reserves: 60 000 litres water, 7200 litres foam concentrate, 2000 kg Dry chemical powder, 36 kg of Carbon dioxide. Total foam solution discharge rate: 4 x 9000 litres/minute. Reserve extinguishing medium :200% Aqueous Film Forming Foam / 220 000 litres water + 40 000 litres Rainwater / borehole water + 35 hydrants 5500kg Dry chemical powder.
3	*Capability for removal of disabled aircraft*	Airport has limited equipment for light aircraft removal only. For the removal of medium to large aircraft, equipment may be sourced as per emergency management response plan when required. Aircraft operator obliged to remove disabled aircraft from manoeuvring area within agreed time frames.
4	*Remarks*	Memorandum of understanding in place with the City of Cape Town Fire & Emergency Services.

AD 2.7 SEASONAL AVAILABILITY - CLEARING

1	*Types of clearing equipment*	NIL INFO AVBL
2	*Clearance priorities*	NIL INFO AVBL
3	*Remarks*	Seasonal availability: All seasons

AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	*Apron designation, surface and strength*	Apron A, B, C and F, concrete, PCR 700/R/B/W/U
2	*Taxiway designation, width, surface and strength*	Width: TWY A1, A2, B1, B3, D1-D5, G1, G2, E and L: 23M; B2: 22.8M, C: 21M, M: 22M Surface: ASPH; Strength: TWY A, B, C, and E: PCR 700/F/B/X/U TWY D,G, L and M: PCR 410/F/B/X/U.
3	*Altimeter checkpoint location and elevation*	Pre-flight altimeter check points and ELEV; Centre of apron 143FT; THR RWY 01-144 FT; THR RWY 16 -143 FT; THR RWY 19 - 147 FT; THR RWY 34 - 151 FT
4	*VOR checkpoints*	NIL INFO AVBL
5	*INS checkpoints*	See AD Chart
6	*Remarks*	- TWY “D3” and D4 restricted to light and medium ACFT only - TWY “H1” lit and marked operated by security personnel on site. - No appropriate markings and lights, pilots to EXER CTN while using TWY “T”. - ACFT manoeuvring on TWY “H1” are to EXER CTN as TWY H1, is not managed by SMC. RDO CTC to be established with SMC prior to MOV past security gate. - Juliet TWY CLSD except for MAINT of SAA ACFT. - Compass swing area on Taxiway ‘G’ closed. All related activities to move to threshold Runway 34. - 5 Power in out bays C1 - C5 in use and can be used to park aircraft nose in - No TWY shoulders provided on certain portions of B1 and B2.

AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	*Use of aircraft stand ID signs, TWY guide lines and visual docking / parking guidance system of aircraft stands.*	1) Allocation of parking i) ACFT landing to CTC apron office on FREQ 122.65 MHz prior to top of descent or when within VHF range for parking bay allocation. Parking bays to be confirmed upon landing. ACFT to give the following INFO, ACFT type, REG, ETA, POB and last AP of DEP ii) Parking bay INFO and REG is to be transmitted to SMC on FREQ 121.9 MHz on vacating RWY for TAX instructions iii) Before entering the apron ACFT are to contact ACSA Apron office on FREQ 122.65 MHz to verify if their gate is still available. Pilots are not to enter into discussion with SMC with reference to bay allocation as this is not their function. iv) TWY G2 access into South African Police Service Airwing unavailable. 2) Operators of non-scheduled flights requiring use of the main apron must inform ACSA apron office on email address CIAApron@airports.co.za not later than 24 hours prior for parking bay allocation. The notification must contain the following information: date and time of arrival, date and time of departure, long term parking arrangements (i.e. main apron or general aviation area), Name of aircraft operator and contact details, Name of ground handler and contact details. 3) A docking system is installed on parking bays A3-A17. The system works as FLW: i. The system will display the ACFT type which means that is the type of ACFT that will park in that stand. ii. The pilot must follow the arrows displayed by the azimuth for this will guide the ACFT on the centreline of the PRKG bay. iii. The system will also display speed of ACFT. ACFT must approach at a speed of not more than 5.40 knots. iv. If it is too fast it will display slow down. v. The system will also display distance from stopping position in meters and will count down in meters as it approaches. vi. As the ACFT moves closer than 3M stopping position it will count down in 0.2 of a meter. vii. Should system be inoperative then marshalling will be as normal. 4) Pushback Procedures i) Pilots leaving AD must advise the Airport Manager, via the Apron Office of destination and the number of PAX and crew on board. Apron Office FREQ 122,65MHz, call sign “CAPE TOWN APRON”. Operators and companies may pass the above INFO by telephone to (021) 9371280 or by FAX *(021) 9340932.

1	*Use of aircraft stand ID signs, TWY guide lines and visual docking / parking guidance system of aircraft stands.*	ii) Only the following information is to be passed to Cape Town Ground Control FREQ 121.9MHz prior to start up: Call-sign, Aircraft Registration, FL requested and PRKG Bay. iii) ACFT are not to request pushback until the tug is connected and ready to push. iv) An ACFT will commence pushback within 1 minute of being given pushback. v) The pilot is deemed responsible for the pushback and is to ensure that no incidents arise. vi) Essential local traffic information will be passed by air traffic control to the pilot in command for onward relay to the engineer. vii) All aircraft in addition will monitor frequency 122.65 MHz whilst on the aprons. 5) Due to reduced wing-tip clearance distances all ACFT with a wing span of 52m or greater must use apron taxiways to only access the ACFT stands on the main aprons and not as a throughfare. ACFT using apron taxiways must reduce taxi speed to 10 knots or below. 6) Due to the proximity of the service road to B10 ACFT parking bay, ACFT that power out of this bay must adhere to the taxi guide lines markings. 7) 4 power in power out parking bays (B19, B22, B25 and B28) in use on B north apron. These parking bays can also be used to park aircraft nose in. 8) All pilots operating the Boeing 777X (777-900) shall not extend the wingtips when taxing on taxiways & taxilanes. The wingtips must then remain folded for taxing to and from the parking bay. Taxiways & taxilanes are not configured to accommodate taxing code F aircrafts. The wingtips must only be extended when the aircraft is lined up at departure threshold.
2	*RWY and TWY markings and LGT*	RWY 01/19 marked and lighted, RWY 16/34 marked and lighted except the centreline only marked. All TWY centreline, holding positions and TWY/RWY intersections marked.
3	*Stop bar*	All TWY intersections leading onto RWY 01/19, TWY C and E have two stop bars each. RWY 16/34 which is part of ACFT taxi circulation is not fitted with stop bars at the intersection onto RWY 01/19. RWY 01/19 guard LGT AVBL only on the western side, nil guard LGT on the eastern side.

4	*Remark*	1) Taxiing guidance system: NIL 2) Visual aids to location: NIL 3) Indicators and ground signalling devices: WDI - LGTD 4) Gate installed across TWY “H1”. Presently lit and marked. 5) Operators wishing to use SAAF Apron must contact SAPS Airwing by TEL: +27 21 935 5109, FAX +27 21 935 5110 or email: airwingysterplaat@saps.org.za. 6) Due to the PSN of the B APN, ACFT parked at times reduce the ATC visibility of RWY 16/34 and TWY A2. OPR are to take note that although LDG and TKOF clearances are issued by ATC, these clearances are based only on these portions that are visible to ATC at the time the clearance is issued as well as the known and reported situation on the RWY at that time. 7) Marshalling signals to be strictly followed by pilots when entering parking bays. 8) For aerodrome restricted visibility refer to chart AD - 05

AD 2.10 AERODROME OBSTACLES

In Area 2					
OBST ID/ Designation	*OBST type*	*OBST position*	*ELEV/HGT*	*Markings/type, colour*	*Remarks*
a	*b*	*c*	*d*	*e*	*f*
NIL INFO AVBL	Radio mast	NIL INFO AVBL	184/115 FT	Lit	2.2 NM ENE
NIL INFO AVBL	Radio mast	NIL INFO AVBL	43/115 FT	Lit	3.4 NM WNW
NIL INFO AVBL	Radio mast	340754.9S 0204926E	787/196. 85 FT	Day Markings Lit	NIL INFO AVBL
NIL INFO AVBL	Radio mast	335840S 0183611E	/100 FT	Lit	50 M N TWR
NIL INFO AVBL	Radar mast	335754.25S 0183640.73E	263/99 FT	Day Markings Red/White Lit	Open topped Lattice mast
NIL INFO AVBL	Radar Tower	335730.88S 0183627.04E	/302 FT	Lit	Topped by Golf ball
NIL INFO AVBL	Standby ATC Tower	335832.26S 0183552.51E	/338 FT	Lit	Topped by Golf ball
NIL INFO AVBL	Athlone Power Station	335653.10S 0183048.55E	NIL INFO AVBL	Lit	Twin Chimneys
NIL INFO AVBL	Radio Mast	335230.78S 0183544.27E	1691/330 FT	Day Markings Red/White Lit	Tygerberg
NIL INFO AVBL	COM TWR	334931.85S 0183617.52E	NIL INFO AVBL	Day Markings Lit	Durbanville Hills

In Area 2					
OBST ID/ Designation	*OBST type*	*OBST position*	*ELEV/HGT*	*Markings/type, colour*	*Remarks*
a	*b*	*c*	*d*	*e*	*f*
NIL INFO AVBL	COM TWR	340316.22S 0182312.56E	3525/480 FT	Day Markings Red/White Lit	Constantia
NIL INFO AVBL	Radio Mast	335600.45S 0185040.10E	992/500 FT	Day Markings Lit	Papegaaiberg Stellenbosch
NIL INFO AVBL	Radio Mast	334251.16S 0185622.54E	2470/470 FT	Day Markings Red/White Lit	Paarlberg
NIL INFO AVBL	COM TWR	335352.12S 0183747.26E	/265 FT	Lit	Bellville
Simon van der Stel rifle range 1.7 NM ESE. Area 335718S 0193812E - 335730S 0183752E - 335822S 0183000E - 335908S 0183849E - 3355815S 0183843E+ GND/5000 FT. Pilots are warned to exercise CTN when flying in the Camps Bay, Lion's Head and Clifton (4th) beach. Paragliding will take place on a DLY basis in a corridor 2.5 NM wide BTN the above-mentioned points.					

In Area 3					
OBST ID/ Designation	*OBST Type*	*OBST position*	*ELEV/HGT*	*Markings/type, colour*	*Remarks*
a	*b*	*c*	*d*	*e*	*f*
NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL

AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	*Associated MET office*	Cape Town
2	*Hours of service* *MET office responsible outside hours*	Observations: H24 Forecasting: 0200 - 1830 FAOR AWC +27 84 279 1151
3	*Office responsible for TAF preparation and periods of validity*	Cape Town 30 HR, 6 hourly
4	*Type of trend forecast and interval of issuance*	METAR and Trend. Every half hour between 0200 and 1900. Hourly between 1900 and 0200.
5	*Briefing / consultation provide*	Personally and telephonically
6	*Flight documentation / language(s) used*	In ICAO format available for all flight levels. English
7	*Charts and other information available for briefing or consultation*	Standard MET charts
8	*Supplementary equipment available for providing information*	Internet: http://aviation.weathersa.co.za, TEL: +27 11 390 9329 / 9330 or +27 21 367 6210 Observer's TEL: +27 11 390 9331
9	*ATS units provided with information*	TWR, APP, AREA and SMC.
10	*Additional information (limitation of service, e.t.c.)*	Normal OBS will continue and forecasting can be AVBL with 24 HR prior notice.

AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	*TRUE BRG*	*Dimensions of RWY (M)*	*Strength of the pavement classification rating (PCR) and surface of RWY and SWY*	*THR coordinates RWY end coordinates THR geoid undulation*	*THR elevation and highest elevation of TDZ of precision APP RWY*	*Slope of RWY-SWY*
1	*2*	*3*	*4*	*5*	*6*	*7*
01	345°T	3201 x 61	PCR 700/F/B/X/U ASPH	335915.86S 0183632.01E	THR: 144FT TDZ: 144FT	+0.03
19	165°T	3201 x 61	PCR 700/F/B/X/U ASPH	335735.43S 0183600.18E	THR: 147FT TDZ: 147FT	-0.03
16	135°T	1701 x 46	PCR 410/F/B/X/U ASPH	335740.96S 0183550.89E	THR: 143FT	+0.14
34	315°T	1701 x 46	PCR 410/F/B/X/U ASPH	335820.14S 0183637.56E	THR: 151FT	-0.14
SWY dimensions (M)	*CWY dimensions (M)*	*Strip dimensions (M)*	*RESA dimensions (M)*	*Location (which runway end) and description of arresting system (if any);*	*OFZ*	*Remarks*
8	*9*	*10*	*11*	*12*	*13*	*14*
NIL	329 X 61	3322 X 300	240 X 120	NIL INFO AVBL	NIL INFO AVBL	See below
NIL	240 X 61	3322 X 300	190 X 120	NIL INFO AVBL	NIL INFO AVBL	See below
NIL	NIL	1820 X 150	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	See below
NIL	NIL	1820 X 150	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	See below

Remarks

1) Local flying instructions: The intentional use of the AD is restricted to ACFT equipped with a functioning TRANS and REC which will permit two-way communication with the TWR.

2) RWY 16/34 available as TWY for all Classes of aircraft.

3) When RWY 19 is in use all ARR ACFT to EXP CLR for ILS Z unless otherwise directed by ATC.

4) Forward scatter metres used to assess RVR along RWY 01/19. Observation representative of TDZ, RWY mid-point and stop end of RWY 01/19

5) No 180º turns for medium and heavy ACFT on RWY 01/19 other than at the RWY THR and INT of TWY E and TWY C for instances of TWY closures.

6) For Light/Medium ACFT:

a. When RWY 19 is in use, plan to vacate at TWY C without DLA.

b. When RWY 01 is in use, plan to vacate at TWY E or RWY 34 without DLA.

For heavy ACFT:

a. When RWY 19 is in use, plan to vacate at TWY B or C without DLA.

b. When RWY 01 is in use, plan to vacate at TWY A, TWY E or RWY 34 without DLA.

AD 2.13 DECLARED DISTANCES

RWY	*TORA (M)*	*TODA (M)*	*ASDA (M)*	*LDA (M)*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*
01	3201	3530	3201	3201	See Below
19	3201	3441	3201	3201	NIL
16	1701	1701	1701	1701	NIL
34	1701	1701	1701	1701	NIL
Note: RWY 01 INT TWY C TORA and ASDA 2080, RWY 19 INT TWY E TORA and ASDA 1875, RWY 19/RWY 16/34 INT TORA and ASDA 2630					

AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	*APCH LGT Type, LEN and INTST*	*THR LGT Colour and WBAR*	*VASIS (MEHT) PAPI*	*TDZ, LGT LEN*	*RWY Centre Line LGT LEN, spacing, colour, INTST*	*RWY Edge LGT, LEN, Spacing, Colour, INTST*	*RWY End LGT Colour and WBAR*	*SWY LGT LEN (M) colour*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*	*7*	*8*	*9*	*10*
01	PALS CAT III	Green	3°	600M	3200M 15M White last 600M Red	3201M 60M White last 600M Yellow	Red	NIL	Centre-line, touchdown zone and edge lights
19	PALS CAT II	Green	3.2°	600M	3200M 15M White last 600M Red	3201M 60M White last 600M Yellow	Red	NIL	Centre-line, touchdown zone and edge lights
16	NIL	Green	3° LHS	NIL	NIL	1701M, 60M White and last 600M Yellow	Red	NIL	NIL INFO AVBL
34	NIL	Green	3° LHS	NIL	NIL	1701M, 60M White and last 600M Yellow	Red	NIL	NIL INFO AVBL

Remarks: **Note:** (PAPI RWY 19) A mast on top of the Tygerberg Mountain is situated within the PAPI coverage area for RWY 19. The mast is situated outside the obstacle limitation surface applicable to instrument approaches. Pilots on VFR flights must note that as the mast is situated at 11.8° azimuth from the extended centerline and has a vertical angle of 2.41° VFR flights are not to establish a glideslope on the PAPI beyond 5 NM from the threshold of RWY 19. Guard lights available on the western side of RWY 01/19.

AD 2.15 OTHER LIGHTING, SECONDARY POWER SUPPLY

1	*ABN/IBN location, characteristics and hours of operation*	NIL INFO AVBL
2	*LDI location & LGT and anemometer location and LGT*	NIL Four on AD, two LGT
3	*TWY edge and centre line lighting*	Edge: blue
4	*Secondary power supply and switch-over time*	AVBL to all lighting/APP and RWY LGT on UPS TWY LGT 15 SEC
5	*Remarks*	Apron edge, OBST and Apron floodlights

AD 2.16 HELICOPTER LANDING AREA

1	*Coordinates TLOF or THR of FATO / Geoid undulation*	NIL INFO AVBL
2	*TLOF / FATO elevation (m/ft)*	NIL INFO AVBL
3	*TLOF and FATO area dimensions, surface, strength, marking*	NIL INFO AVBL
4	*True BRG of FATO*	NIL INFO AVBL
5	*Declared distance available*	NIL INFO AVBL
6	*APP and FATO lighting*	NIL INFO AVBL
7	*Remarks*	Helicopter arrival and departure zone. AD -07 a) Helicopters must arrive/depart by making use of the designated approved arrival/departure zones, either zone 1 at the intersection of TWY H1 and H3 or zone 2 at TWY H5. At these points, on departure FREQ 118.1 MHz b) Helicopters to remain at designated points for the minimum amount of time coincident with a safe departure or arrival. On arrival they must monitor FREQ 121.9 MHz for movement within general aviation area. c) Pilots to EXER CTN when arriving/departing as these arrival/departure zones are on active fixed wing aircraft taxiways. d) Helicopters may not over-fly the fuel farms, Airport Terminal and ATC TWR.

AD 2.17 ATS AIRSPACE

1	*Designation and lateral limits*	CTR The area bounded by lines drawn as follows: excluding FAP 33 a. From a point at 340900S 0183430E a straight line to a point at 335900S 0183130E b. Thence a straight line to a point at 335900S 0182900E c. Thence a straight line to a point 335630S 0182900E d. Thence clockwise along the arc of a circle radius 2.5 NM centred at 335404S 0182951E, to a point 335135.65S 0183018.35E. e. Thence a straight line to a point 334930S 0182830E. f. Thence clockwise along the arc of a circle, radius 11 NM and centre at 335810S 0183621E, to a point 334900S 0184300E g. Thence a straight line to a point 340330S 0184800E. h. Thence clockwise along the arc of a circle, radius 11 NM and centre at 335810S 0183621E, to the starting point 340900S 0183430E
2	*Vertical limits*	Upper limit CTR: 2 500 FT ALT
3	*Airspace classification*	Class C
4	*ATS unit call sign* *Language(s)*	English
5	*Transition altitude*	Transition altitude: 7 500 FT
6	*Remarks*	1. Except where otherwise authorized, no aircraft is to be operated within this airspace unless two-way radio contact is maintained with air traffic control.

AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	*Call sign*	*Channel(s)*	*Hours of operation*	*Remarks*
1	*2*	*3*	*4*	*5*
ACC RSR	Cape Town Control	125.1 MHz transmits/receives	H24	VHF extended range relay STN 125.1 MHz - FASL, FABW, FAGG, FAAB, FAAG, FAPK, FAVW, Leliefontein, Piketberg

Service designation	*Call sign*	*Channel(s)*	*Hours of operation*	*Remarks*
1	*2*	*3*	*4*	*5*
ACC RSR	Cape Town Information West	131.125 MHz transmits/receives	DLY BTN 0500 - 1700	VHF extended range relay STN 131.125 MHz - FASL, FABW, FANV, FAAG, Jonaskop. Pilots to follow unmanned procedures outside hours of service.
ACC RSR	Cape Town Information East	127.575 MHz, 124.7 MHz FPL and SAR	DLY BTN 0500-1700	Pilots to follow unmanned procedures outside hours of service.
APP TAR	Cape Town Approach	119.7 MHz transmits/receives	H24	VHF extended range relay STN 119.7 MHz Jonaskop.
TWR	Cape Town Tower	118.1 MHz transmits/receives	H24	OPR-monitoring of TFC only
Cape Town Director	Cape Town Director	124.35 MHz	During high traffic volumes	NIL
Cape Town Clearance Delivery	Delivery	122.100 MHz	MON-FRI: 0330-1700 SAT: 0500-1500 SUN: 0500-1700	NIL
SMC	Cape Town Ground	121.9 MHz transmits/receives	H24	OPR-monitoring of TFC only
ATIS VHF	NIL INFO AVBL	127.000 MHz	0330 - 2200	Remote broadcast STN located at FASL on FREQ. 127.600 MHz.

Remarks

ATC training taking place on all operational frequencies. Exact time and frequencies available on ATIS.

IFR traffic departing during hours of service is to contact Cape Town Clearance Delivery prior to start to obtain Aerodrome After Departure ATC Clearance.

IFR traffic departing outside hours of service of Cape Town Clearance Delivery to contact SMC to obtain Aerodrome information and to receive After Departure ATC Clearance.

ADDITIONAL ATS OPERATIONAL SERVICE & FREQUENCY

a) In order to ease pressure on the Aerodrome control service at Cape Town during periods of high traffic demand an additional Aerodrome control Sector will be in operation during times of high traffic demand.

b) The additional Aerodrome service will be provided on frequency 122.100 MHz and will use the callsign “Cape Town Clearance Delivery”. Only aircraft departing from Cape Town will use this service.

c) Hours of duty of the service will be Monday to Friday 0330 to 1700, Saturday 0500 to 1500 and Sundays 0500 to 1700.

d) IFR Aircraft departing during hours of service is to contact Cape Town Clearance Delivery prior to start to obtain aerodrome information and to receive After Departure Air Traffic Control Clearance.

e) IFR aircraft departing outside Cape Town Clearance Delivery hours of duty is to contact SMC on frequency 121.9 MHz to obtain Aerodrome information and to receive After Departure Air Traffic Control Clearance.

AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid, MAG VAR, Type of supported OPS (for VOR/ILS/ MLS, give declination)	*ID*	*Frequency*	*Hours of operation*	*Position of transmitting antenna coordinates*	*Elevation of DME transmitting antenna*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*	*7*
ILS LOC (RWY 19) CAT II	KSI	109.1 MHz	H24	335924.5S 0183634.8E	NIL INFO AVBL	NIL INFO AVBL
ILS GP (RWY 19) CAT II	NIL INFO AVBL	331.4 MHz	H24	335745.3S 0183608.1E	NIL INFO AVBL	GP angle 3.2° GP ALT. at 5.4d “KS” 1973FT. GP ALT. at 2d “KS” 826 FT. Reference datum height (RDH) 63 FT.
ILS LOC (RWY 01)	CTI	110.3 MHz	H24	335724.1S 0183556.6E	NIL INFO AVBL	OPR WI ICAO CAT IIIB tolerances and is AVBL without any restrictions.
ILS GP (RWY 01)	NIL INFO AVBL	335 MHz	H24	335903.6S 0183634.2E	NIL INFO AVBL	OPR WI ICAO CAT IIIB tolerances and is AVBL without any restrictions. GP angle 3.0°. GP ALT. at 5.8d “CT” 2000 FT. GP ALT. at 3.7d “CT” 1320 FT. GP ALT at 0.8d “CT” 390 FT. RDH 65 FT.
VOR	CTV	115.7 MHz	H24	335810.82S 0183618.19E	146 FT	NIL INFO AVBL
UHF DME	CTV	1191 MHz 104X	H24	335810.82S 0183618.19E	NIL INFO AVBL	Channel 104 X coaxially collocated with the VOR
DME	CTI	110.3 MHz	H24	335903.6S 0183634.2E	NIL INFO AVBL	DME CT collocated with ILS GP antenna
DME	KSI	109.1 MHz	H24	335745.3S 0183608.1E	NIL INFO AVBL	DME KS collocated with ILS GP antenna

AD 2.20 LOCAL AERODROME REGULATIONS

Parking Area for small aircraft

(General Aviation)

1. The general aviation area comprises of TWY H1 west of the taxiway gate and all associated taxiways. There is no SMC service provided on these taxiways.
2. Operators must exercise caution when operating in the area as there is a mixture of fixed wing and rotary wing operations. Standard operating procedures have been developed to accommodate this mixed operations and visiting operators are advised to request for Standard operating procedures from the hangar service provider where they will be parking.
3. Operators must exercise caution when operating in the area as there may be vehicles on taxiways and/or pedestrians crossing.
4. During hover and taxiing, helicopters must avoid blowing down wash into hangars or onto other objects.
5. All helicopters operating in the vicinity of a taxiway on the movement area, including those landing and taking off from General aviation hangar area shall comply with Air Taxi Regulations. Therefore any helicopter operating in the aforementioned areas, below 100FT AGL, shall not exceed a speed of 20 knots.

AD 2.21 NOISE ABATEMENT PROCEDURES

1) Unless otherwise authorised by ATC the maximum speed applicable to jet aircraft shall comply with noise abatement as laid down in ENR 1.5.
2) Noise abatement SID procedures for jet aircraft laid down in ENR 1.5.
3) Avoid over flying Tygerberg hospital, 3 NM N of AD, when taking off from RWY 01 and 34.
4) No jet aircraft to use RWY/TWY intersection for take off between 2000 to 0400.
5) No engine run-ups shall be allowed between 2000 to 0400, unless in an emergency.

AD 2.22 FLIGHT PROCEDURES

For IFR Operations

a) All IFR operations (fixed and rotary wing) are to call ATC on FREQ 121.9 MHz for start up clearance, indicating their position and TWY. All other traffic within general flying area shall maintain a listening watch on this FREQ in order to establish other aircraft operations.
b) All aircraft shall monitor FREQ 121.9 MHz, prior to and during any movement under power and all aircraft shall maintain a listening watch on 121.9 MHz until required by ATC to change FREQ 118.1 MHz as appropriate.
c) It is the responsibility of the Pilot in Command to see and be seen at all times.
d) RNAV equipped aircraft departing from the FACT TMA for destinations: FAGC, FAWB, FASK and FAWK, are to use the RNAV route: KODES UQ42 OKLOK UQ52 EGPOP. RNAV equipped aircraft departing from the FACT TMA for destination: FAGM, are to use RNAV route TETAN UZ2 NIBEX.
e) Non-standard clearance for RWY 01: AFT DEP RWY 01 climb to FL090 MNTN RWY track to 3DME CTV, then turn left 330DEG to intercept RDL 354 CTV OUBD. Further climb and routing will be under radar CTL. At OKTED/ TETAN set course as per FPL. RCF PROC (squawk 7600): MNTN FLT ALT if higher than MSA for a period of 7MIN. Further CONT as per FPL RTE and climb to FPL LVL.
f) Non-standard clearance for RWY 19: AFT DEP RWY19 climb to FL090 MNTN RWY track. Further climb and routing via KODES will be under radar CTL. At KODES set course as per FPL. RCF PROC (squawk 7600): MNTN FLT ALT if higher than MSA for a period of 7MIN. Further CONT as per FPL RTE and climb to FPL LVL.

Procedures for VFR flights within the TMA

All Helicopters departing to contact Ground on frequency 121.9 MHz for start approval.

Circuit: 1500 FT ALT

AD 2.23 ADDITIONAL INFORMATION

1. All signals relating to flight plans and ACFT movements or delays to be addressed to both FACTZQZX and FACTYFYR.
2. EVUKI and DUGLU are not to be used on FPL for arriving ACFT to DEST FACT. FPL to be filed VIA ASPIK, ERDAS OR GETEN
3. All VFR fixed wing ACFT, including local FLT, INBD and OUBD FM FACT to file FLT plans. Rotary wing ACFT will be accommodated on AD-HOC basis at ATC discretion.
4. All fixed wing VFR FLT INBD and OUBD FM CTR to file FPL. All police, MIL, MEDEVAC and HOSP VFR FLT are exempted. All VFR FLT requesting circuit training to contact TWR on +27 21 937 1116/1101 at least 30MIN prior to requesting start.
5. High bird prevalence at AD FM OCT to MAR. Pilots to EXER CTN DRG take-off and LDG.

AD 2.24 CHARTS RELATED TO AN AERODROME

Aerodrome Chart	-AD-01
Ground Movement Chart	-AD-02
Aircraft Parking/Docking Chart	-AD-03
Aircraft Parking/Docking Chart	-AD-04
Restricted Visibility Chart	-AD-05
Hot Spot	-AD-06
Helicopters ARR/DEP Zone Chart	-AD-07
ILS RWY 01	-ILS-01
Data tabulation	-ILS-01A
ILS Z RWY 19	-ILS-02
Data tabulation	-ILS-02A
VOR Z RWY 01	-VOR-01
ERDAS 1B STAR 19	-ARR-06
GETEN 1B STAR 19	-ARR-07
ASPIK 1B STAR 19	-ARR-08
ERDAS 1C STAR 01	-ARR-10
Data tabulation	-ARR-10A
ASPIK 1C STAR 01	-ARR-11
Data tabulation	-ARR-11A
GETEN 1C STAR 01	-ARR-12
Data tabulation	-ARR-12A
KODES 1A SID 01	-DEP-02
IMSOM 1A SID 01	-DEP-03
TETAN 1A SID 19	-DEP-05
TETAN 1B SID 19	-DEP-06
IMSOM 1B SID 19	-DEP-08
OKTED 1B SID 19	-DEP-09
OKTED 1C SID 19	-DEP-10
RNAV (RNP) Z RWY 01	-RNAV-01
Data tabulation	-RNAV-01A
RNAV (RNP) Y RWY 01	-RNAV-02
Data tabulation	-RNAV-02A
RNAV (RNP) Z RWY 19	-RNAV-03
Data tabulation	-RNAV-03A
RNAV (RNP) Z RWY 34	-RNAV-04

Data tabulation RNAV (GNSS) RWY 01 Data tabulation RNAV (GNSS) RWY 19 Data tabulation Radar Terrain Clearance Chart The following charts are AVBL on CAA website: www.caa.co.za Precision APCH Terrain Chart RWY 01 Precision APCH Terrain Chart RWY 19 AD OBST Type A AD OBST Type A	-RNAV-04A -RNAV-05 -RNAV-05A -RNAV-06 -RNAV-06A -RAD-01 The following charts are AVBL on CAA website: www.caa.co.za -PATC-01 -PATC-02 -OBST Type A-01 -OBST Type A-02

THIS PAGE INTENTIONALLY LEFT BLANK