FALA

FALA AD 2.1 AERODROME LOCATION INDICATOR AND NAME

FALA - LANSERIA INTERNATIONAL

FALA AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	*ARP co-ordinates and site at AD*	255622.89S 0275532.07E
2	*Direction and distance from city*	22 NM NW of O R Tambo INTL Airport
3	*Elevation/Reference temperature*	4521 FT/ 24°C
4	*Geoid undulation at AD ELEV PSN*	82.6 FT
5	*MAG VAR* *Annual change*	18 W (2018) 0°6' W
6	AD operator, address, telephone, telefax, email, AFS address and, if available, *website address*	PUB AD CHF: Lanseria (Pty) Ltd. Private Bag X1, Lanseria 1748 TEL: +27 11 367 0300 FAX: +27 11 7013261 ATSU: P. O. BOX 165, Lanseria 1748 TEL: ATC: +27 11 701 3262/701 3278 FAX ATC: +27 11 701 3505 AFS Address: FALAZTZX E-mail: info@lanseria.co.za
7	*Types of traffic permitted (IFR / VFR)*	IFR/VFR
8	*Remarks*	International Airport. Use of AD by microlight aircraft prohibited. 24 HR notice of International flights see AD 2.20 note 3. Terms and conditions for the use of the aerodrome is available from the Management Offices and or on the web www.lanseria.co.za

FALA AD 2.3 OPERATIONAL HOURS

1	*AD operator*	AD Operational hours: H24
2	*Customs and immigration*	H24, TEL: +27 11 367 0300
3	*Health and sanitation*	Available daily H24; TEL: +27 11 659 2750 (All Departments)
4	*AIS briefing office*	MON - SUN 0345 - 1800
5	*ATS reporting office (ARO)*	NIL INFO AVBL
6	*MET briefing office*	NIL INFO AVBL
7	*ATS*	H24
8	*Fuelling*	HOD: H24,Supplier: ENGEN/Lanseria Management Board. TEL: +27 11 367 0300. AFT HR +27 82 447 6026
9	*Handling*	NIL INFO AVBL
10	*Security*	NIL INFO AVBL

11	*De-icing*	NIL INFO AVBL
12	*Remarks*	SMC hours of service: MON-SUN: 0345-1700,

FALA AD 2.4 HANDLING SERVICES AND FACILITIES

1	*Cargo-handling facilities*	Forklift off loading, MAX pallet 10 tons, contact AD for INFO
2	*Fuel and Oil types*	AVGAS 100, JET A1. OIL: AVHYD E, JET OIL 11, EXXON 100, EXXON EE.
3	*Fuelling facilities and capacity*	2 bowser refuelling 800L/MIN, capacity 60 000L Hydrant refuelling on Apron B 1 000L/MIN Maximum fuel storage 700 000L (10 Days) JET A 1 and operating capacity 600 000L (8 days) JET A1.
4	*De-icing facilities*	NIL
5	*Hangar space for visiting aircraft*	Various
6	*Repair facilities for visiting aircraft*	Various AMO's
7	*Remarks*	NIL

FALA AD 2.5 PASSENGER FACILITIES

1	*Hotels*	In City. Contact AD Info
2	Restaurants	At AD. Contact AD Info for HR of service.
3	*Transportation*	Taxi's on request, car rentals at AD.
4	*Medical facilities*	First aid at AD Hospitals 15KM away Contact AD for INFO.
5	*Bank and Post Office*	At AD. Contact AD Info.
6	*Tourist office*	In City. Contact AD Info
7	*Remarks*	NIL

FALA AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	*AD category for fire fighting*	H24 CAT VII 4 shift system with 9 crew per shift. 12 hour shifts from 0500-1700 and 1700-0500. Crew strength maintained at MNM 8 at any given time.
2	*Rescue equipment*	2x Rosenbauer 6x6 crash tender, 12000L water, 720L foam, 500kg dry chemical powder each. 1x Rosenbauer 8x8 crash tender, 12000L water, 720L foam, 500kg dry chemical powder each.
3	*Capability for removal of disabled aircraft*	Lifting bags and hydraulic equipment AVBL for up to CAT B aircraft.
4	*Remarks*	1) Mutual Aid agreements with Local Authorities. 2) Rescue and Fire Fighting Upgradable to CAT VIII by prior arrangement. 12 HR PN

FALA AD 2.7 SEASONAL AVAILABILITY - CLEARING

1	*Types of clearing equipment*	NIL
2	*Clearance priorities*	NIL
3	*Remarks*	NIL

FALA AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	*Apron surface and strength*	ASPH APN A PCR 680/R/C/W/T, APN B PCR 660/R/C/W/T, APN C PCR 720/R/C/W/T
2	*Taxiways width* *Taxiway surface* *Taxiway strength*	Width: TWY A 15m with 2.5m shoulders, all others 15m no shoulders Surface: ASPH Strength: TWY A PCR 580/F/B/X/T, TWY A1 PCR 800/F/B/X/T, TWY A2 PCR 1660/F/C/X/T, TWY A3 PCR 1350/F/C/X/T, TWY A4 PCR 1820/F/B/X/T, TWY B PCR 1640/F/C/X/T, TWY B2 PCR 1750/F/C/X/T, TWY B3 PCR 2020/F/C/X/T, TWY C PCR 720/R/C/W/T, TWY R PCR 800/F/C/X/T, TWY S AND U PCR 1370/F/C/X/T, TWY P PCR 1180/F/C/X/T, TWY N PCR 1310/F/C/X/T.
3	*Altimeter checkpoint location and elevation*	RWY 07: 4521 FT, RWY 25: 4394 FT,
4	*VOR checkpoints*	THR RWY 07 - 64°M/0.10NM THR RWY 25 - 64°M/1.68 NM
5	*INS checkpoints*	See AD Chart
6	*Remarks*	The main apron has a slope factor that necessitates the following: 1) The use of extra power during taxing. All operators of multi-engine aircraft must taxi with a minimum of two (2) engines running. 2) All aircraft parked on the apron must be properly choked when left unattended.

FALA AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	*Use of aircraft stand ID signs, TWY guide lines and visual docking / parking guidance system of aircraft stands.*	1. Only class B and smaller aircraft will be accommodated on apron A. 2. Class C and larger aircraft will be accommodated on apron C (own power) or nose in on apron B. 3. Aircraft may not park on apron A, B and C for a period longer than four (4) hours without prior approval from Apron Office (freq 122.85 MHz or +27 11 659 2220) 4. Allocation of parking bays: * Pilots landing and using the main apron to contact FALA Apron control before entering the apron and provide the following information: Aircraft REG and Type, passengers on board, departure point and duration of apron occupation. * Pilots departing from the main apron must contact FALA Apron control prior to start and provide the following information: Aircraft REG, ETD, passengers on board and destination. 5. For aerodrome restricted visibility refer to chart AD - 03.

2	*RWY and TWY markings and LGT*	STD
3	*Stop bars*	NIL
4	*Remark*	NIL

FALA AD 2.10 AERODROME OBSTACLES

In Area 2					
OBST ID/ Designation	*OBST type*	*OBST position*	*ELEV/HGT*	*Markings/ Type, colour*	*Remarks*
a	*b*	*c*	*d*	*e*	*f*
NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL

Remarks:
1) During night operations and in conditions or poor visibility, pilots should exercise caution in maintaining terrain clearance towards the west of the airfield, due to high ground of 5338 FT (Swart koppies) at approximately 5.5NM.
2) Category C or greater aircraft exercise caution on taxiway A3 opposite apron C due to a steep embankment 16 M north of the edge of the taxiway.
3) Hot air balloon operations 25 NM radius Kloofzicht Lodge, Cradle of Humankind (2558S 02749E) excluding controlled airspace, DLY SR - SS, GND/7500 FT AMSL.
4) Hang/Paragliding activity GND/6400 FT AMSL Krugersdorp Ridge 260400S 274932E, 260332S 0274851E, 260459S 0274738E and 260528S 0274857E DLY SR - SS.

In Area 3					
OBST ID/ Designation	*OBST type*	*OBST position*	*ELEV/HGT*	*Markings/ Type, colour*	*Remarks*
a	*b*	*c*	*d*	*e*	*f*
NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL

FALA AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	*Associated MET office*	O R Tambo INTL
2	*Hours of service* *MET Office outside hours*	Observation: 0400 - 2000 Forecasting: H24 FAOR (+27 82 233 9600/8800)
3	*Office responsible for TAF preparation* *Periods of validity*	O R Tambo INTL 30 HR, 6 Hourly
4	*Trend forecast* *Interval of issuance*	Yes 0400 - 2000 Hourly
5	*Briefing / consultation provided*	NIL

6	*Flight documentation / Language(s) used*	Standard ICAO format English
7	*Charts and other information available for briefing or consultation*	Standard MET Charts
8	*Supplementary equipment available for providing information*	NIL
9	*ATS units provided with information*	TWR/Approach
10	*Additional information (limitation of service, etc.)*	Observation by ATS outside MET Stations hour of service. Other aviation related information available on web page http://aviation.weathersa.co.za

FALA AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	*TRUE BRG*	*Dimensions of RWY (M)*	*Strength (PCR) and surface of RWY and SWY*	*THR coordinates RWY end coordinates THR geoid undulation*	*THR elevation and highest elevation of TDZ of precision APP RWY*	*Slope of RWY-SWY*
1	*2*	*3*	*4*	*5*	*6*	*7*
07	047°T	2996 x 45	ASPH PCR 950/F/C/X/T	255653.84S 0275455.55E	4521 FT	-1,30%
25	227°T	2996 x 45	ASPH PCR 950/F/C/X/T	255549.55S 0275612.98E	4394 FT	+1,30%
SWY dimensions (M)	*CWY dimensions (M)*	*Strip dimensions (M)*	*RESA dimensions (M)*	*Location (which runway end) and description of arresting system (if any);*	*OFZ*	*Remarks*
8	*9*	*10*	*11*	*12*	*13*	*14*
0	1500 x 150	3116 x 300	150 x 90	NIL	NIL	NIL
0	1500 x 150	3116 x 300	90 x 90	NIL	NIL	NIL

FALA AD 2.13 DECLARED DISTANCES

RWY Designator	*TORA (M)*	*TODA (M)*	*ASDA (M)*	*LDA (M)*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*
07	2996	4496	2996	2996	NIL
25	2996	4547	2996	2925	NIL

FALA AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	*APCH LGT Type, LEN and INTST*	*THR LGT colour and WBAR*	*VASIS (MEHT) PAPI*	*TDZ, LGT LEN*	*RWY Centre Line LGT, LEN, spacing, colour, INTST*	*RWY Edge LGT LEN, spacing, colour, INTST*	*RWY End LGT colour and WBAR*	*SWY LGT LEN (M) colour*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*	*7*	*8*	*9*	*10*
07	PALS CAT1 300M High	Green NIL WBAR	PAPI 3°	NIL	NIL	2926M 60M White High	Red NIL WBAR	NIL	NIL
25	NIL	Green NIL WBAR	PAPI 3.5°	NIL	NIL	2926M 60M White High	Red NIL WBAR	NIL	NIL
Notes: 1) Airfield identification light on TWR roof.									

FALA AD 2.15 OTHER LIGHTING SYSTEMS, SECONDARY POWER SUPPLY

1	*ABN/IBN location, characteristics and hours of operation*	Location: Tower roof Colour: three white lights, 1 hour before sunset to 1 hour after sunrise and during IMC.
2	*LDI location and LGT Anemometer location and LGT*	LDI: NIL Anemometer: At AD reference point.
3	*TWY edge and centre line lighting*	Edge: All TWY edge lights blue. Only lead in lights provided, excluding TWY H
4	*Secondary power supply and switch-over time*	Diesel power standby generator supplying normal facilities and installations
5	*Remarks*	NIL

FALA AD 2.16 HELICOPTER LANDING AREA

1	*Coordinates TLOF or THR of FATO Geoid undulation*	NIL
2	*TLOF and/or FATO elevation M/FT*	NIL
3	*TLOF and FATO area dimensions, surface, strength, marking*	NIL

4	*True BRG of FATO*	NIL
5	*Declared distance available*	NIL
6	*APP and FATO lighting*	NIL
7	*Remarks*	1) Inbound non-wheeled helicopters will be directed by ATC onto Heliports on C apron. 2) No helicopter may land, taxi or take off between the hangars. 3) No dedicated helicopter landing area available. 4) All helicopters must approach and land on TWY/RWY only. 5) All helicopters must take-off from TWY/RWY only. 6) If heliport occupied, helicopters will be directed to land on TWY and make contact with apron to allocate alternative parking bay. Helicopter will then contact ATC to reposition to bay. 7) Helicopters may not hover/air taxi between hangers.

FALA AD 2.17 ATS AIRSPACE

1	*Designation and lateral limits*	CTR The area bounded by lines drawn as follows excluding FAP64 – Pelindaba: a) From a point at 255228.70S 0275159.44E along a straight line to a point at 254923.60S 0275542.43E. b) Thence a straight line along the eastern border of FAP64 to a point at 254754.23S 0275729.06E. c) Thence a straight line to a point at 254729.47S 0275758.82E. d) Thence a straight line to a point at 254837.17S 0275932.41E. e) Thence a straight line to a point at 255048.61S 0280126.98E. f) Thence a straight line to a point at 255810.04S 0280131.85E. g) Thence a straight line to a point at 255932.73S 0275951.61E. h) Thence a straight line to a point at 260426.99S 0275357.29E. i) Thence clockwise along the arc of a circle, radius 5NM, and centered at 260037.25S 0275022.33E to a point at 255705.60S 0274625.81E. j) Thence a straight line back to the starting point at 255228.70S 0275159.44E.
2	*Vertical limits*	6500FT ALT/GND
3	*Airspace classification*	C
4	*ATS unit call-sign* *Language*	English
5	*Transition altitude*	8000FT
6	*Remarks*	Except where otherwise authorized, no aircraft is to be operated within this airspace unless two-way radio contact is maintained with ATC. Warning: Sky Lanterns released within the aerodrome vicinity

FALA AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	*Call sign*	*Frequency*	*Hours of operation*	*Remarks*
1	*2*	*3*	*4*	*5*
TWR/APP	Lanseria Tower	124.0 MHz transmits and receives	H24	NIL
ATIS	NIL INFO AVBL	127.65 MHz	H24	Dedicated ATIS
SMC	Lanseria Ground	121.65 MHz transmits and receives	MON -SUN: 0400-1700	NIL
Apron	Lanseria Apron	122.85 MHz	H24	Non ATC service, only parking allocation and hazard information.

FALA AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid, MAG VAR, Type of supported OPS (VOR/ ILS/ MLS, give declination)	*ID*	*Frequency*	*Hours of operation*	*Position of transmitting antenna coordinates*	*Elevation of DME Transmitting antenna*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*	*7*
DVOR	LIV	117.4 MHz transmits	H24	255656.14S 0275448.86E	NIL INFO AVBL	NIL
UHF DME	LIV	1145 MHz transmits & 1208 MHz receives	H24	255656.14S 0275448.86E	1393M	Channel 121x Co-axially collocated with DVOR.
ILS LOC RWY 07	LAI	110.7 MHz	H24	255544.60S 0275618.80E	1337M	NIL
ILS GP RWY 07	-	330.2 MHz	H24	255649.80S 0275507.10E	1374M	Channel 44x Angle 3º
UHF DME	LAI	110.7 MHz	H24	255649.70S 0275507.10E	1379M	Co-located with ILS LOC

FALA AD 2.20 LOCAL AERODROME REGULATIONS

1) Apron procedure
* Landing aircraft intending using main apron, to contact Apron Control on VHF frequency122.85 MHz on top of descent to request parking bay and provide the following information.
- Aircraft registration, type, ETA, POB and departure point (local or international). This may be done prior landing in VHF range. The parking bay information, aircraft registration and POB to be transmitted to SMC on frequency 121.65 MHz on vacating the RWY for taxi instructions.
- IFR flights departures departing from the main apron to obtain start clearance first from SMC on VHF frequency 121.65 MHz, then request traffic and hazard information from Apron Control prior to taxi.
- VFR flights departing from the main Apron to request traffic and hazard information from Apron Control prior to taxi.
* Push back must be done along the centreline marking of the apron.
* Traffic positioning across active runways to do so under instructions from SMC who will liaise with Tower for authorisation.
2) Pilots on VFR departures from AD must ensure that they do not commence their turn outs over the apron and hangar areas.
3) Only Micro Lights on International flights will be granted landing rights at AD, pending a 24 HR notice of intentions to use AD. Landing rights will only be approved by the Airport Authority. No micro lights on domestic flights are allowed to land at AD.
4) Air-gates have been erected at all entrances to taxiway A and B, illuminated at night, to open call ground on 121.65 MHz

FALA AD 2.21 NOISE ABATEMENT PROCEDURES

1) No engine testing may be performed daily between 1700 and 0300 on the AD.
2) Engine tests may only be conducted in designates areas or as instructed by ATC. The designated areas are the runup bays of RWY 07 and 25 and the turning circle TWY C.
3) No jets may perform engine test in the turning circle of TWY C.
4) Refer ENR 1.5.

FALA AD 2.22 FLIGHT PROCEDURES

All International flight must park on the main apron (Apron A or B)
1. Procedure for the straight in VOR/DME APCH RWY 07 at FALA using LIV:
a) FAOR APP will inform ACFT that they are being vectored for the straight-in VOR/DME APCH for RWY 07.
b) FAOR APP will then vector ACFT to intercept RADIAL 245 LIV inbound by no later than 14DME LIV. The ACFT will then be handed over to FALA APP by no later than 12DME LIV.
c) Lanseria APP will clear the ACFT for the straight-in VOR/DME APCH.

2. Procedure for the straight in ILS APCH RWY 07 at FALA using LIV:
a) FAOR APP will inform ACFT that they are being vectored for the straight-in ILS APCH for RWY 07.
b) FAOR APP will then vector ACFT to intercept RADIAL 245 LIV inbound by no later than 14DME LIV. The ACFT will then be handed over to FALA APP by no later than 12DME LIV.
c) Lanseria APP will clear the ACFT for the straight-in ILS APCH.

FALA AD 2.23 ADDITIONAL INFORMATION

1) Bird activity in the vicinity of AD. 2) Hot air Balloon activity in the vicinity of the AD. 3) No international Transit facilities. 4) Parking charges will amount to three times normal parking for all aircraft parked on taxiways.

FALA AD 2.24 CHARTS RELATED TO AN AERODROME

Aerodrome Chart	-AD-01
Aircraft parking/docking chart	-AD-02
Restricted Visibility Chart	-AD-03
VOR Z RWY 07	-VOR-01
VOR Y RWY 07	-VOR-02
RNAV RWY 07	-RNAV-01
Data tabulation	-RNAV-01A
RNAV RWY 25	-RNAV-02
Data tabulation	-RNAV-02A
ILS Z RWY 07	-ILS-01
Data tabulation	-ILS-01A