FALE

FALE AD 2.1 AERODROME LOCATION INDICATOR AND NAME

FALE - KING SHAKA INTERNATIONAL

FALE AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	*ARP co-ordinates and site at AD*	Ref. Point: 293642.38S 0310709.53E
2	*Direction and distance from city*	16 NM NNE
3	*Elevation/Reference temperature*	307FT/29° C
4	*Geoid undulation at AD ELEV PSN*	92.2 FT
5	*MAG VAR* *Annual change*	25°W (2018) 0°9' W
6	*AD Operator, address, telephone, telefax, e-mail, AFS address and, if available, website address*	Airports Company of S A Limited. Postal address: P.O. BOX 2620, Country Club 4301 Commercial: Aviation Telephone numbers: ACSA: +2732 436 6494 ATS: ATC TWR:+2732 436 5002 ATC Filter:+2732 436 5001 ATC Reception:+2732 436 5000 Manager ATS:+2732 436 5020, Manager ATS Secretary:+2732 436 5019, PM: +2732 436 5028, PATSA:+2732 436 5027 Flight planning Fax: +2732 436 3811 AFTN: FALEZTZX MET: Observer +2782 233 9500, Forecaster +2782 233 8700, Admin +2732 436 3817, Fax +2732 436 3815 Rescue and Fire fighting: +27 32 436 6767
7	*Types of traffic permitted (IFR / VFR)*	IFR/VFR
8	*Remarks*	NIL

FALE AD 2.3 OPERATIONAL HOURS

1	*AD Operator*	H24
2	*Customs and immigration*	H24
3	*Health and sanitation*	MON - SUN: 0500 - 2100. All international and cross border flight arrivals will be attended to accordingly. International arrivals outside these times will be dealt with on a call out basis. TEL: +2732 436 0200; FAX: +2732 436 2669 CELL: +2783 457 1148 / +2764 847 9655 Email: ksiaporthealthservices@health.gov.za
4	*AIS briefing office*	Nil service. For slot after hours, operators to contact O R Tambo International AIS Unit. Contact details: TEL No: +27860 359 669; +2711 928 6517/8 Fax No: +2711 928 6514

5	*ATS reporting office (ARO)*	H24
6	*MET briefing office*	H24
7	*ATS*	H24
8	*Fuelling*	Fuel Operator: Sky Tanking. Additional information available via ACSA help desk on TEL: +2732 436 6584
9	*Handling*	H24
10	*Security*	H24
11	*De-icing*	Not applicable
12	*Remarks*	ATNS CAMU provides coordination services for South Africa's coordinated airports: MON-FRI 0600-14h00 (excluding public holidays). Tel: + 2711 928 6433; Fax: + 2711 928 6420 E-mail: coord@atns.co.za After hours service is handled by the Capacity and Demand Management Office, which will only deal with short-term ad-hoc schedule changes and new requests that are sent before 1900. All other changes must be submitted to the coordinator during normal office hours. The contact numbers for after hours assistance for King Shaka International Airport are: Tel: +2710 207 2001; E-mail: slots@airports.co.za

FALE AD 2.4 HANDLING SERVICES AND FACILITIES

1	*Cargo-handling facilities*	ETV operated ULD storage with 200ULD storage locations, of which 50 are temperature controlled(0 to 10 Deg C), 6 build up and breakdown workstations, of which 2 are temperature controlled,20 truck docks, of which 2 are ULD hand overstations, Euro pallet storage for shipments, on site government agencies (including customs) and facilities for express cargo processing.
2	*Fuel and Oil types*	Fuel grades: JET A1. Oil grades: AO 100, D100, D120, ASO100, W100,W120, ASTO 750 Oxygen and related servicing: Limited quantities of oxygen for first aid and oxygen for high flying aircraft available for replenishment. Nitrogen available for tyre or Oleo inflation. Air start units, tow bars and ground powers units available O/R by prior arrangement. No PCA units available. See remarks below.
3	*Fuelling facilities and capacity*	Refuelling facilities and limitations: A, B, C and D aprons: Aprons equipped with JET A1 hydrant refuelling system. NIL AVGAS available.
4	*De-icing facilities*	N/A
5	*Hangar space for visiting aircraft*	NIL
6	*Repair facilities for visiting aircraft*	No repair facilities available. Major emergency repairs and minor maintenance on apron by consent of the AD authority.

7	*Remarks*	Handling services and facilities are provided by different companies on the AD, and hence prior arrangements need to be made to ensure availability of requested technical services/ equipment.

FALE AD 2.5 PASSENGER FACILITIES

1	*Hotels*	Overnight accommodation: Hotels AVBL in adjacent areas and city.
2	Restaurants	AVBL during operational hours of AD
3	*Transportation*	Taxis and tour operators
4	*Medical facilities*	Emergency medical services are available H24 at the AD. Transfers to nearby hospitals are arranged by the contracted EMS services; Hospitals 10KM and 17KM away.
5	*Bank and Post Office*	NIL
6	*Tourist office*	INFO AVBL via ACSA help desk TEL: +27 32 436 6584.
7	*Remarks*	NIL

FALE AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	*AD category for fire fighting*	CAT 9 within AD HOD. 16 responding personnel per shift.
2	*Rescue equipment*	3 x major fire fighting vehicles Water: 24 300L Foam Discharge rate: 9 000 L/MIN Dry Chemical Powder 450KG at a discharge rate of 4.5 KG/SEC 200% extinguishing media stock maintained. 2 x Power saws 1 x hydraulic jaws of life
3	*Capability for removal of disabled aircraft*	Equipment for removal of aircraft will be sourced as per emergency plan. ACFT operator to remove disable aircraft from active RWY within a maximum of 2 hours.
4	*Remarks*	1) Memorandum of understanding with Ethekwini Municipality fire and emergency services. 2) ACSA spokesperson in case of an emergency: Ofentse Dijoe, Cell: +27 72 798 8486, TEL: +27 10 207 2601, Email: ofentse.dijoe@airports.co.za.

FALE AD 2.7 SEASONAL AVAILABILITY - CLEARING

1	*Types of clearing equipment*	NIL
2	*Clearance priorities*	NIL
3	*Remarks*	Seasonal availability: All seasons

FALE AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	*Apron designation, surface and strength*	Apron A and B, concrete, PCR 531/F/B/X/U Apron C and D, concrete, PCR 531/F/B/X/U Apron E (AMS), concrete, PCR 531/F/B/X/U
2	*Taxiway designation, width, surface and strength*	TWY A to C, TWY E to H, M and N Width: 25 M with 2M x 17.5 M sealed shoulders Surface: ASPH Strength: PCR 531/F/B/X/U TWY P Width:10.5 M with 2 M x 7.25 M sealed shoulders Surface: ASPH Strength: PCR 531/F/B/X/U
3	*Altimeter checkpoint location and elevation*	Pre-flight altimeter check points and ELEV: THR RWY 06 - 287.47 FT; THR RWY 24 - 300.83 FT
4	*VOR checkpoints*	NIL
5	*INS checkpoints*	See AD Chart
6	*Remarks*	TWY P and E apron restricted to maximum size ICAO code B fixed wing aircraft (24M wingspan) and helicopters with a rotor diameter of 16M only. A and B apron and taxiing between these aprons are restricted to maximum ICAO code C aircraft (36M wingspan).

FALE AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	*Use of aircraft stand ID signs, TWY guide lines and visual docking / parking guidance system of aircraft stands.*	1) Aircraft stand ID signs provided on all stands 2) Taxing guidance signs and markings provided at all intersections and runway holding positions. 3) Allocation of parking bays: ACFT LDG are to contact the apron office, call-sign Apron Control on FREQ 122.65 MHz when within VHF range and prior to landing to obtain PRKG bay information. Parking bays to be confirmed upon landing. ACFT to give the following INFO, ACFT type, REG, ETA, POB and last AP of DEP This information must be transmitted to SMC on FREQ 121.65 MHz on first contact. Operators or companies may obtain this INFO direct from the apron office on TEL: 032 436 6514. 4) MAX sizes of ACFT at parking bays: A1-A16 and B1-B9: ICAO code C ACFT (MAX 36m wingspan) C2,C5: ICAO code F (MAX 80m wingspan) C1,C3, C4, C6: ICAO code C (MAX 36m wingspan) in MARS configuration D2,D5: ICAO code F (MAX 80m wingspan) D1,D3, D4, D6: ICAO code C (MAX 36m wingspan) in MARS configuration 5) All non-scheduled flights to contact Apron Control on FREQ 122.65 MHz on arrival and prior to departure, provide with the following INFO: Call sign/flight number, last point of departure, destination, number of people on board and parking bay. 6) A visual guidance docking system installed at PRKG A5-A16 and C2,C5. The system works as follows: i) The system will display the ACFT type which must be checked by the pilot for accuracy. ii) The pilot must follow the arrows displayed by the azimuth for this will guide the ACFT on the centerline of the PRKG. iii) The system will also display speed of ACFT. iv) If it is too fast it will display slow down. v) The system will also display distance from stopping position (closing rate) in meters and will count down in meters as it approaches the stopping position. vi) When the ACFT is in position it will display stop. vii) When docking system is complete the OK will be displayed. viii) Should the system be inoperative then the ACFT will be marshalled manually.

2	*RWY and TWY markings and LGT*	RWY: designation: THR, TDZ, center line, edge and runway end marked and lighted.TWY: centerline and holding positions at all TWY/RWY intersections marked and lighted; Edge markedand lighted; center line and TWY holdingpositions at other locations marked only.RET: RETILs and TWY center line lights providedon RET G and H. The intersection around TWY N, G and A is a designated Hotspot and as such extra vigilance is required by pilots. No aircraft may pass each other on the taxiways at this intersection.
3	*Stop bars*	Provided at TWY/RWY intersections at TWY C, G, H AND TWY M.
4	*Remark*	Indicators and ground signalling devices:3 WDI LGTD provided. Start and push back procedures 1) Push back, start and taxi clearances are to be requested on SMC FREQ 121.65 MHz. 2) ACFT are not to request pushback until the tug is connected and ready to push. 3) Before start is requested, ACFT must be ready for immediate push back. 4) ACFT to be pushed back onto center line under the authority of the pilot in command. 5) ACFT parked on C apron stands are required to push back and pull forward to designated point on apron for start up. 6) All entry, push back and exiting of parking bays must be done via feeder lines. 7) No ACFT is to pass another ACFT positioned on the center line. 8) All airline operators are responsible for ensuring procedures are adhered to. 9) RWY holding point markings and stop bars layout as per FAA Advisory Circular 150/5340-1J. (SACAA Exemption)

FALE AD 2.10 AERODROME OBSTACLES

In Area 2					
OBST ID/ Designation	*OBST type*	*OBST position*	*ELEV/HGT*	*Markings/ Type, colour*	*Remarks*
a	*b*	*c*	*d*	*e*	*f*
Nil INFO AVBL	Umdloti VODACOM	S293940.90 E0310616.38	473.155 FT	Nil INFO AVBL	Nil INFO AVBL
Nil INFO AVBL	MTN TWR	S293628.82 E0310828.63	634.585 FT	Nil INFO AVBL	Nil INFO AVBL
Nil INFO AVBL	CELL C TWR	S293634.01 E0310506.35	573.562 FT	Nil INFO AVBL	Nil INFO AVBL
Nil INFO AVBL	MICROWAVE TWR	S293333.89 E0310535.56	774.313 FT	Nil INFO AVBL	Nil INFO AVBL

In Area 2					
OBST ID/ Designation	*OBST type*	*OBST position*	*ELEV/HGT*	*Markings/ Type, colour*	*Remarks*
a	*b*	*c*	*d*	*e*	*f*
NIL INFO AVBL	MTN/CELLC MAST	293556.80S 0310938.04E	481.735 FT	NIL INFO AVBL	NIL
NIL INFO AVBL	WTANK	293951.50S 0310412.75E	590.896 FT	NIL INFO AVBL	NIL
NIL INFO AVBL	TLIGHT1	293519.63S 0310826.96E	363.900 FT	NIL INFO AVBL	NIL
NIL INFO AVBL	TLIGHT2	293535.16S 0310823.50E	357.732 FT	NIL INFO AVBL	NIL
NIL INFO AVBL	EPTL1	293811.08S 0310415.88E	448.539 FT	NIL INFO AVBL	NIL
NIL INFO AVBL	VODACOM	294327.75S 0310416.27E	661.688 FT	NIL INFO AVBL	NIL
NIL INFO AVBL	TRENANCE TWR	293907.96S 0310049.55E	996.881 FT	NIL INFO AVBL	NIL

In Area 3					
OBST ID/ Designation	*OBST type*	*OBST position*	*ELEV/HGT*	*Markings/ Type, colour*	*Remarks*
a	*b*	*c*	*d*	*e*	*f*
NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL

FALE AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	*Associated MET office*	FAOR
2	*Hours of service* *MET Office outside hours*	Observations H24 Forecaster 0200-1900 (+27 82 233 8700/8500) FAOR (+27 82 233 9600/8800)
3	*Office responsible for TAF preparation* *Periods of validity*	FALE, 30 hours issued every 6 hours, daily
4	*Trend forecast* *Interval of issuance*	Trend type (extension on Metar valid for 2 hours from time Metar/Speci is issued. Every half hour
5	*Briefing / consultation provided*	Personal and telephonically
6	*Flight documentation /* *Language(s) used*	In ICAO format available for all flight levels English

7	*Charts and other information available for briefing or consultation*	Standard MET charts
8	*Supplementary equipment available for providing information*	Radar/Satellite/LDN
9	*ATS units provided with information*	TWR and APP
10	*Additional information (limitation of service, etc.)*	Flight documentation and other Aviation related information available on website http:/aviation.weathersa.co.za

FALE AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	*TRUE BRG*	*Dimensions of RWY (M)*	*Strength of the pavement classification rating (PCR) and surface of RWY and SWY*	*THR coordinates RWY end coordinates THR geoid undulation*	*THR elevation and highest elevation of TDZ of precision APP RWY*	*Slope of RWY-SWY*
1	*2*	*3*	*4*	*5*	*6*	*7*
06	037°T	3700 x 60	PCR 531/F/B/X/U ASPH	293730.19S 0310627.89E	THR: 287 FT	+0.11%
24	217°T	3700 x 60	PCR 531/F/B/X/U ASPH	293554.56S 0310751.16E	THR: 301 FT	-0.11%
SWY dimensions (M)	*CWY dimensions (M)*	*Strip dimensions (M)*	*RESA dimensions (M)*	*Location (which runway end) and description of arresting system (if any);*	*OFZ*	*Remarks*
8	*9*	*10*	*11*	*12*	*13*	*14*
NIL	300 x 150	3820 x 300	240 x 120	NIL INFO AVBL	15 KM	NIL
NIL	300 x 150	3820 x 300	240 x 120	NIL INFO AVBL	15 KM	NIL

Remarks 12
(1) Pilots to exercise caution when on final for RWY 24 at night, especially in IMC, Toll booth flood lights immediately to the left of CL about 1 NM from touchdown are being mistaken for RWY 24 APCH light
(2) Forward scatter metres used to assess RVR Along RWY 06/24. Observations representative of TDZ, RWY mid-point and stop end of RWY 06/24.
(3) RWY 06/24 RESA is 240M X 120M FM the end of the RWY (60M) strip.

FALE AD 2.13 DECLARED DISTANCES

RWY Designator	*TORA (M)*	*TODA (M)*	*ASDA (M)*	*LDA (M)*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*
06	3700	4000	3700	3700	Intersection departure TORA 2100M
24	3700	4000	3700	3700	Intersection departure TORA 2100M

FALE AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	*APCH LGT Type, LEN and INTST*	*THR LGT Colour and WBAR*	*VASIS (MEHT) PAPI*	*TDZ, LGT LEN*	*RWY Centre Line LGT LEN, spacing, colour, INTST*	*RWY Edge LGT, LEN, Spacing, Colour, IN-TST*	*RWY End LGT Colour and WBAR*	*SWY LGT LEN (M) colour*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*	*7*	*8*	*9*	*10*
06	PALS, CAT II, 900m LIH	Green, No WBAR	PAPI 3 DEG	White 30m apart	CAT II;LIH white to 900m from end; from 300m to 900 m from end alternative white and red; last 300m red. 15 m apart.	White until 600m from end, from 600m to end yellow. 60m apart.	Red, No WBAR	Nil INFO AVBL	Nil
24	PALS, CAT II, 900m LIH	Green, No WBAR	PAPI 3 DEG	White 30m apart	CAT II;LIH white to 900m from end; from 300m to 900 m from end alternative white and red; last 300m red. 15 m apart.	White until 600m from end, from 600m to end yellow. 60m apart.	Red, No WBAR	Nil INFO AVBL	Nil
Remarks Pilots to EXER CTN when on final for RWY 24 at NGT, especially in IMC. Toll booth flood LGT immediately to the left of CL about 1NM FM touchdown are being mistaken for RWY 24 APCH LGT.									

FALE AD 2.15 OTHER LIGHTING SYSTEMS, SECONDARY POWER SUPPLY

1	*ABN/IBN location, characteristics and hours of operation*	Nil INFO AVBL
2	*LDI location and LGT Anemometer location and LGT*	Nil INFO AVBL
3	*TWY edge and centre line lighting*	Edge all TWY and center line TWY G and H, rapid exit TWY off RWY only.
4	*Secondary power supply and switch-over time*	Uninterruptible Power Supply and Emergency Generator Power Supply: Available time for switchover – 1SEC for UPS & 15SEC for Generator Power Supply.
5	*Remarks*	Nil

FALE AD 2.16 HELICOPTER LANDING AREA

1	*Coordinates TLOF or THR of FATO Geoid undulation*	NIL INFO
2	*TLOF and/or FATO elevation M/FT*	NIL INFO
3	*TLOF and FATO area dimensions, surface, strength, marking*	NIL INFO
4	*True BRG of FATO*	NIL INFO
5	*Declared distance available*	NIL INFO
6	*APP and FATO lighting*	NIL INFO
7	*Remarks*	Nil specified ATC will provide taxi and parking instructions.

FALE AD 2.17 ATS AIRSPACE

1	*Designation and lateral limits*	CTR 1) From a point at 293747.94S 0305750.69E to a point at 292721.07S 0310656.95E 2) Thence clockwise around the arc of a circle, radius 6NM, centred at 293059.50S 0311225.31E to a point at 293437.71S 0311754.06E. 3) Thence a straight line to a point at 294505.32S 0310848.27E 4) Thence clockwise around the arc of a circle, radius 6NM, centred at 294126.74S 0310319.28E to the starting point at 293747.94S 0305750.69E
2	*Vertical limits*	GND/3000 FT ALT
3	*Airspace classification*	Class C
4	*ATS unit call-sign* *Language*	English
5	*Transition altitude*	5 500 FT
6	*Remarks*	Except where otherwise authorized, no aircraft is to be operated in this airspace unless two way radio contact is maintained with ATC, and a serviceable transponder is carried.

FALE AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	*Call sign*	*Channel (s)*	*Hours of operation*	*Remarks*
1	*2*	*3*	*4*	*5*
APP	Durban Approach	125.75 MHz transmits and receives	H24	Within 50 NM of TGV
DATIS	King Shaka	127.00 MHz	H24	INFO can be accessed by telephone

Service designation	*Call sign*	*Channel (s)*	*Hours of operation*	*Remarks*
1	*2*	*3*	*4*	*5*
TWR	King Shaka INTL TWR	118.45 MHz transmits and receives	H24	NIL
SMC	King Shaka INTL Ground	121.65 MHz transmits and receives	H24	NIL

FALE AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid, MAG VAR, Type of supported OP (for VOR/ILS/ MLS, give declination)	*ID*	*Frequency*	*Hours of operation*	*Position of transmitting antenna coordinates*	*Elevation of DME transmitting antenna*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*	*7*
DVOR	TGV	115.6 MHz	H24	293640.20S 0310729.03E	108M	Power output 50W
UHF DME (TACAN)	NIL INFO	CH103x. 1190 MHz	H24	293640.20S 0310729.03E	108M	Coaxially colocated with VOR
ILS GP 24 CAT II	TGI	333.2 MHz	HS	293605.46S 0310747.28E	89.492M	NIL
ILS LOC 24 CAT II	NIL INFO	109.7 MHz	HS	293738.59S 0310620.57E	88.419M	NIL
DME 24	TGI	Channel 34X INT FREQ RX 1058 MHz, RE TX 995 MHz	HS	293605.46S 0310747.28E	89.492M	NIL
ILS GP 06 CAT II	TNI	332.3 MHz	HS	293724.46S 0310638.48E	88.419M	NIL
ILS LOC 06 CAT II	NIL INFO	111.3MHz	HS	293544.61S 0310759.82E	89.492M	NIL
DME 06	TNI	Channel 50x INT FREQ RX 1074 MHz, RE TX 1011 MHz	HS	293724.46S 0310638.48E	88.419M	NIL

FALE AD 2.20 LOCAL AERODROME REGULATIONS

1) Aerodrome regulations, INFO required by Airport manager, taxiing to and from stands, parking area for small ACFT (general aviation), taxing limitations and removal of disabled ACFT from runways to be notified.
2) Parking areas for helicopters to be advised by ATC.
3) School and training flights -Technical test flights -use of runways to be notified.
4) Helicopter traffic limitation nil.

FALE AD 2.21 NOISE ABATEMENT PROCEDURES

1) Aircraft noise and flight track adherence is monitored at AD.
2) Use Noise Abatement Departure Procedure 1, as per ENR 1.5.
3) No engine tests and run-ups between 2000 to 0400. Unforeseen engine test runs outside of these times only permitted by consent of the AD Authority.
4) No intersection take-offs between 2000 to 0400.
5) After landing minimize the use of reverse thrust, as far as possible, for braking purposes.
6) Pilots to be considerate towards inhabitants of areas adjacent to aerodrome by minimizing aircraft noise.

FALE AD 2.22 FLIGHT PROCEDURES

General
1) The pilot in command wishing to cross or join controlled or advisory airspace shall: call the responsible ATC unit on the designated frequency 10 minutes before joining such airspace and maintain two way radio communication on the appropriate radio frequency. When RWY 06 is in use ACFT will not be permitted to depart from TWY H, and may not enter TWY H from TWY A for any reason.When RWY 24 is in use ACFT will not be permitted to depart from TWY G, and may not enter TWY G from TWY A for any reason. Intersection takeoffs will not be permitted between 2000 and 0400. The intersection around TWY N, G and A is a designated Hotspot and as such extra vigilance is required by pilots. No ACFT may pass each other on the taxiways at this intersection.
2) All ARR ACFT to EXP CLR for ILS Y unless otherwise directed by ATC.

FALE AD 2.23 ADDITIONAL INFORMATION

NIL INFO AVBL

FALE AD 2.24 CHARTS RELATED TO AN AERODROME

Aerodrome Chart	-AD-01
Aircraft Parking/Docking Chart	-AD-02
ILS Z RWY 06	-ILS-01
ILS Y RWY 06	-ILS-02
Data tabulation	-ILS-02A
LS Z RWY 24	-ILS-03
ILS Y RWY 24	-ILS-04
VOR Z RWY 06	-VOR-01
VOR Z RWY 24	-VOR-02
Radar Minimum Altitude Chart	-RAD-01
RWY 06 APMAT 1A	-ARR-01
Data tabulation	-ARR-01A
RWY 06 DUNSA 1A	-ARR-02
Data tabulation	-ARR-02A
RWY 06 GETOK 1C	-ARR-03
Data tabulation	-ARR-03A
RWY 06 ITMIL 1A	-ARR-04
Data tabulation	-ARR-04A
RWY 24 APMAT 1B	-ARR-05
Data tabulation	-ARR-05A
RWY 24 DUNSA 1B	-ARR-06
Data tabulation	-ARR-06A
RWY GETOK 1D	-ARR-07
Data tabulation	-ARR-07A
RWY24 ITMIL 1B	-ARR-08
Data tabulation	-ARR-08A
RWY 06 ITMIL 1C	-DEP-01
Data tabulation	-DEP-01A
RWY 24 OKTAN 1A	-DEP-02
Data tabulation	-DEP-02A
RWY 06 TUBIN 1A	-DEP-03
Data tabulation	-DEP-03A
RWY 24 TUBIN 1B	-DEP-04
Data tabulation	-DEP-04A
Greytown 1A	-DEP-05
Data tabulation	-DEP-05A
Greytown 2B	-DEP-06
Data tabulation	-DEP-06A
RNAV RWY 06	-RNAV-01
Data tabulation	-RNAV-01A
RNAV RWY 24	-RNAV-02
Data tabulation	-RNAV-02A
The following charts are AVBL on CAA website: www.caa.co.za	The following charts are AVBL on CAA website: www.caa.co.za
Precision APCH Terrain Chart RWY 06	-PATC-01
Precision APCH Terrain Chart RWY 24	-PATC-02
AD OBST TYPE A	-OBST Type A-01

THIS PAGE INTENTIONALLY LEFT BLANK