FAOR

AD 2.1 AERODROME LOCATION INDICATOR AND NAME

FAOR - O R TAMBO INTERNATIONAL

AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	*ARP co-ordinates and site at AD*	260801.30S 0281432.34E Mid-point of aerodrome APRX 860M WNW of ATNS CTL TWR
2	*Direction and distance from city*	10 NM ENE of Johannesburg Central. JOHANNESBURG
3	*AD elevation/Reference temperature*	5558FT (1694M) Circuit: 7000 FT ALT 21.2 C
4	*Geoid undulation at aerodrome elevation position*	88.9 FT
5	*MAG VAR* *annual change*	20° W (2024) 0.16° W
6	*AD Operator, address, telephone, telefax, e-mail, AFS address and, if available, website address*	AD Operator: Airport Company SA Ltd. (ACSA) P/Bag X1 OR TAMBO INTL Airport 1627 SITA Addresses: QRACY7X Telex: 87807 SA TEL: +27 11 921 6911 FAX: +27 11 394 0806 INFO ACSA: +27 11 921 6262 WEB: www.acsa.co.za ATS ATNS: D-ATS TEL: +27 11 928 6461 Central Airspace Management Unit (CAMU): TEL: +27 11 928 6433 FAX: +27 11 928 6420 Johannesburg ACC: TEL: +27 11 928 6448/9 Johannesburg FIS: TEL: +27 11 928 6450 Avionics Fault Reporting: TEL: +27 11 928 6477 or +27 11 921 6500 Weather Services Aviation Weather Centre PO Box 1194 OR TAMBO INTL AP 1627 Forecaster: +27 11 390 9329/30 Observers: +27 11 390 9331 Administration: +27 11 390 9333 FAX: +27 11 390 9332

7	*Types of traffic permitted (IFR / VFR)*	IFR/VFR
8	*Remarks*	NIL

AD 2.3 OPERATIONAL HOURS

1	*AD Operator*	H24
2	*Customs and immigration*	H24
3	*Health and sanitation*	H24
4	*AIS briefing office*	H24
5	*ATS reporting office (ARO)*	H24
6	*MET briefing office*	H24
7	*ATS*	H24
8	*Fuelling*	H24
9	*Handling*	H24
10	*Security*]	H24
11	*De-icing*	NIL
12	*Remarks*	NIL

AD 2.4 HANDLING SERVICES AND FACILITIES

1	*Cargo-handling facilities*	1) Capable of handling 74F/A380. 2) EQPT AVBL at AD to handle single item up to a weight of 20 tons. Single items greater than 20 tons in weight can be handled by special arrangement. CTC any handling agent for further details. 3) Handling Agents: Colossal: +27 11 300 8536/+27 10 201 2526 Menzies: +27 83 726 1977
2	*Fuel and Oil types*	Fuel grades: Jet A1 only ORTAFS TEL: +27 11 397 1606/7/8/9 Oil grades: GND engineer or handling agent to arrange
3	*Fuelling facilities and capacity*	No Limitations a) Hydrant system, 3000L/MIN all aprons EXC APN M b) 2 Bowsers total capacity 40000L c) 1 X De-fuel truck capacity 20000L. d) 19 hydrant dispenser trucks
4	*De-icing facilities*	NIL
5	*Hangar space for visiting aircraft*	By special arrangement with SAA, contact Technical Operations Centre at +27 11 978 3603, ask for Third party

6	*Repair facilities for visiting aircraft*	By special arrangement with SAA, contact Technical Operations Centre at +27 11 978 3603, ask for Third party
7	*Remarks*	All aircraft operating for repairs should contact Apron Office on +27 11 921 6536 and report intention and contact information.

AD 2.5 PASSENGER FACILITIES

1	*Hotels*	AVBL at AD in terminal A transit area, near AD and in city. CTC Help Desk - +27 11 921 6262 or INFO counter in all terminals
2	Restaurants	At AD, CTC Help Desk - +27 11 921 6262 or INFO counter in all terminals
3	*Transportation*	Taxis, Shuttles, Buses, E-hailing, Car Rental and train (Gautrain) AVBL at AD. CTC Help Desk - +27 11 921 6262 or INFO counter in all terminals
4	*Medical facilities*	Clinic at AD in terminal B, CTC - +27 11 921 6609: H24. Nearest hospital in Kempton Park - 4KM
5	*Bank and Post Office*	AVBL at AD. CTC Help Desk - +27 11 921 6262 or INFO counter in all terminals
6	*Tourist office*	At AD CTC Help Desk - +27 11 921 6262 or INFO counter in all terminals
7	*Remarks*	Self-service and Information kiosks available in all terminals to assist passengers and public regarding service queries

AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	*Aerodrome category for fire fighting*	CAT 9. 1. Can accommodate CAT 10 requirements 2. H24 daily with trained personnel. 3. 4 shifts with minimum 14 personnel per shift on duty.
2	*Rescue equipment*	Level B Foam 6% and Dry Chemical Powder 15 000L X 4 responding Fire tenders, Total 60 000L +27 11 921 6603
3	*Capability for removal of disabled aircraft*	IATA kit AVBL - staged at South African Airways Technical
4	*Remarks*	Mutual aid agreements with local authorities.

AD 2.7 SEASONAL AVAILABILITY - CLEARING

1	*Types of clearing equipment*	N/A

2	*Clearance priorities*	N/A
3	*Remarks*	N/A

AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATION DATA

1	*Apron designation, surface and strength*	Surface: concrete APN A1R to A13 PCR 681/R/A/W/U APN B1 to B13 PCR 377/R/A/W/U APN C1 to C8 and C19 to C24 PCR 377/R/A/W/U APN C9 to C18 PCR 200/R/A/W/U APN D1 to D50 PCR 681/R/A/W/U APN E1 to E13 PCR 681/R/A/W/U APN F1 to F7 PCR 681/R/A/W/U APN G1 to G7 PCR 377/R/A/W/U
2	*Taxiways width, surface and strength*	Width: 30.5M EXC Echo which is 60M wide Surface: ASPH TWY A, B, C south of TWY N, D, E, and G8 to G11, F, H, I (west of RWY 03L/21R), L, P, Q, RR, RS, J (east and west of RWY 03L/21R), Y PCR 681/F/A/X/U. TWY C north of TWY N, TWY I east of RWY 03L/21R, K, T, N PCR 377/F/A/X/U.
3	*ACL location and elevation*	Pre-flight altimeter check points and ELEV THR RWY 03L - 5558FT THR RWY 21R - 5505FT THR RWY 03R - 5510FT THR RWY 21L - 5494FT
4	*VOR check points*	VOR: See AD Chart
5	*INS check points*	INS: See AD Chart
6	*Remarks*	1. Lead-in lights and signage will indicate the beginning of RE on RWY 03R positioned at TWY E intersection.

AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	*Use of aircraft stand ID signs, TWY guide lines and visual docking / parking guidance system of aircraft stands.*	1.Only Class C ACFT and smaller will be accommodated on C APN. (MAX ACFT type B737-900) 2. Any operation of B747-400 ACFT into the SAA Technical area will not provide the ICAO recommended clearance DIST. 3. ACFT of 12000 kg or more and wingspan exceeding 24 meters when parked at A, B, C, D, E, F and G APN, must push back from ACFT stand. All aircraft parked on APN stand shall push back from stand unless authorised by AD authority to power out. Selective stands are identified for self-manoeuvring. Stands compatible for self-manoeuvring aircraft with wingspan not exceeding 15 meters: C9-C12 Stands compatible for self-manoeuvring aircraft with wingspan not exceeding 24 meters: C13-C24, D31-D48, G1, G3, G5 and F1-F7. 4. Pilots to CTC APN CTL on FREQ 122.65MHz, prior to top of DES or when in VHF range for allocation of PRKG bays or hangar and provide the FLW INFO: ETA, ACFT REG, PAX onboard and last AP departed. The PRKG bay INFO and ACFT REG is to be transmitted to TWR on FREQ 118.6/118.1 MHz on vacating the RWY for TAX instructions. 5. Unscheduled ACFT to notify APN office 24HR prior to operation for PRKG stand allocation. APN office TEL: +2711 921 6209 APN office e-mail: opscentre@airports.co.za PRKG stands are not guaranteed to unscheduled ACFT operating without prior notification. 6. Aircraft with ground time exceeding 14 hours on parking stands will be required to re-position to an alternative stand, hangar or location. 7. All flights, EXC training and test flights, must make use of the aprons and terminals at FAOR as allocated by APN CTL. No flights may operate directly to and FM hangars unless agreed with the AD authority. 8. No ACFT with a wingspan of 52M or greater (Code E and F) are allowed on D APN taxi lane when ACFT with a wing span of 65M or greater (Code F) are TAX on Northern portion of TWY A past D APN (FM D APN stands D2-D50). Wing tip clearance is restricted and BLW ICAO recommendation. 9. ACFT pushing back FM PRKG stand D2, D3 and D4 must be pushed back to face N and exit onto TWY G8 onto TWY A. 10. ACFT with a wingspan of 65M or greater (CODE F) PRKG at PRKG stand D3A must enter and exit D APN via TWY G9. When manoeuvring on taxi lane D, Pilots to EXER CTN and remain on the taxilane CL to maintain wingtip CLR FM other parked ACFT. DIST FM taxilane CL to the back of ACFT stands is 42.5M. 11. Automated DCKG system PRKG stands Alpha 1R to Alpha 13, Charlie 1 to Charlie 8 and stands E1-E13. Pilots are to ensure the FLW: a) The stands are clear of objects; b) Correct INFO is displayed on monitor - including ACFT type and series. c) DCKG instructions will be displayed on monitor, pilots to intercept CL and FLW the AZM guidance display. d) AZM guidance can be used from both the Captain seat (left of closing rate display) and the First Officer's seat (right of closing rate display).

1	*Use of aircraft stand ID signs, TWY guide lines and visual docking / parking guidance system of aircraft stands.*	e) EXER CTN when DCKG on stands on Apron A, especially A4, A5 and A6 due to sunlight reflecting off the Automatic DCKG panels at sunrise. Should DCKG INFO be impaired, CTC APN CTL on 122,65MHz for assistance. 12. The taxi lane BTN APN A and B deviates to the right at PRKG stands B7 and B8. Pilots to follow new line when taxiing through the APN. 13. TWY RE distance from 03R THR is 1777.73M. Pilot to plan for appropriate exit speeds. 14. Pilots are REQ not to exceed 10KT when taxiing on any of the aprons, when low VIS PROC is in force. 15 ACFT entering PRKG bays on APN A, B, E and F to use minimal thrust required so as to avoid adverse jet blast effects to GND handling OPS on opposite APN. 16. Operators need to notify APN CTL on TEL +27 11 921 6209 or FREQ 122.65MHz prior to positioning FM the hangars to the APN. 17. When taxiing on TWY A towards RWY 21R HLDG point at ABM TWY Q the centre line deviates 10M to the west. 18. ACFT entering APN A and B via TWY E or ACFT XNG RWY 03L/21R at TWY E in a westerly direction to use minimal thrust required so as to avoid adverse jet blast effect to ACFT TKOFF or LDG on RWY 03L/21R. ACFT taking-off or LDG on RWY 03L/21R to be aware of XNG TAX ACFT jet blast when passing TWY E INT. 19. ACFT LDG or TKOF on RWY 03L/21R to be aware of jet blast FM ACFT XNG or vacating RWY 03L/21R at any of the intermediate INT & to EXER CTN. 20. When code F ACFT (B748, A380 and AN124) push back FM or to ACFT PRKG bay D50 on TWY D the ACFT encroach into TWY A. ACFT using TWY A to hold short of TWY D when code F ACFT are pushing back FM or to enter PRKG bay D50. 21. ACFT HLDG at RWY HLDG PSN TWY N west of RWY 03L/21R encroach into TWY A. ACFT using TWY A to hold short of TWY N when there is another ACFT HLDG on TWY N. 22. Intersection Taxiway B and TWY M, aircraft to exercise caution when taxiing south bound to threshold runway 03L as taxiway B bends to the east, approximately 450M after passing intersection taxiway India and TWY M continues straight ahead. Only Code C aircraft, wingspan less than 36M or outer main gear wheel span less than 9M are allowed on TWY M. All aircraft entering APN M shall be under tow. 23. Jet Centre hangar gate is 47M in width. Pilots to ensure wingtip CLR is adequate for ACFT TYP when TAX through gate. 24. PRKG Stands G1, G3, G5 and G7 are multiconfigured for ACFT PWR out and ACFT pushback. PWR out is LTD to ACFT wingspan of 23.24M or smaller and ACFT length of 32.51M or smaller. 25. Code F ACFT into PRKG Stand D1 to enter and/or exit via TWY G8. Pushback OPS to face N, pull forward TIL port wingtip is aligned with PRKG bay D2R and exit via TWY G8. 26. Wide body ACFT pushing back FM PRKG stand E12, is recommended to follow guidance strip leading FM the PRKG stand into the taxilane. 27. When code F ACFT (B748, A380) pushback FM ACFT PRKG stand E12, the ACFT will be pushed tail first into PRKG stand F6, before aligned on the taxilane centre line.

		28. Pilots to take caution when cleared past the CAT II holding points on taxiways Alpha and Bravo to the CAT I holding point for RWY03L as the green centreline lights will illuminate all the way onto the RWY when the stopbars are deselected, giving the impression that clearance onto the RWY was obtained. Visual cues may thus differ from the actual ATC clearance received. 29. TWY M CLSD to all ACFT EXC when under tow. All ACFT with a MAX wingspan of 36M requiring to utilise TWY M when OPR under own PWR to CTC AP management centre (AMC) +27 10 207 2818, +27 82 787 8629 or APN CTL on 122.65 MHZ for APV. 30. TWY C from TWY N intersection to THR 21R is restricted to MAX code C ACFT, ACFT with Wingspan of up to including 36m and/or out main gear wheelspan of less than 9M. 31. B777-9 Operations: a) B777-9 must taxi or tow as a Code E aircarft (i.e., with Folding Wing Tips (FWTs) folded) if unable to advise ATC before RWY exit or pushback. b) In case of non-normal FWT operations, the aircraft must use Code F taxiways and Code F parking stands.
2	*RWY and TWY markings and LGT*	1. Marking aids: RWY 03L/21R & 03R/21L: THR, RWY designation, Centre line fixed distance, touchdown zone, side stripes. 2. TWY A edge lights replaced with TWY centre line lights. 3. RWY centre line lights only operational in CAT II operations. 4. TWY centre line markings and LGT for RET RS and RET RR designed for ACFT with long wheel bases (example A340-600). ACFT exiting RWY 03R via RET RS turning left into TWY Y and ACFT exiting RWY 21 L via RET RR turning right into TWY Y to EXER CTN to avoid the main undercarriage running of the TWY. 5. RWY 21L edge LGT white until 600M FM end, FM 600M to end yellow. RWY 21R edge LGT white until 600M FM end, FM 600M to end yellow. RWY 03L edge LGT white until 600M FM end, FM 600M to end yellow. RWY 03R edge LGT white until 600M FM end, FM 600M to end yellow. 6. Enhanced paint markings on all RWY intersections. 7. Parts of TWY L, K, and I (east of RWY 03L/21R) shoulders are unpaved for aircraft with outer engines span of 28M or wider. Pilots to exercise caution when taxiing.
3	*Stop bar*	Stop bars on all RWY/TWY intersections. No crossing of 3 Stop bars red stop bar LGT will be allowed unless specifically approved by ATC and accompanied by a leader vehicle.
4	*Remark*	Taxiing Guidance System - Nil Visual Guidance System - Nil Indicators and ground signalling devices - WDI LGTD.

AD 2.10 AERODROME OBSTACLES

In Circling Area and at AD					
In Area 2					
OBST ID/ Designation	*OBST Type*	*OBST position*	*ELEV/HGT*	*Markings/Type, Colour*	*Remarks*
a	*b*	*c*	*d*	*e*	*f*
FAOR 01	Mast	260904.30S 0281418.06E	5668.46FT	NIL LGT: NIL	NIL
FAOR 02	L Band Radar Building	260859.36S 0281329.11E	5771FT	Day/Night, LGT: NIL	NIL
FAOR 03	Mast	260706.70S 0281452.81E	5665.91FT	NIL LGT: Red	NIL
FAOR 04	Hangar	260842.65S 0281341.64E	5698.86FT	NIL LGT: NIL	NIL
FAOR 05	Hangar	260832.74S 0281347.80E	5709.66FT	Night LGT: NIL	NIL
FAOR 06	ATC Tower	260813.00S 0281459.47E	5729.03FT	White LGT: Red	NIL
FAOR 07	Koffie Huis Building	260802.91S 0281253.11E	5733.32FT	Night LGT: NIL INFO AVBL	NIL
FAOR 08	S-Band Radar	260747.00S 0281508.00E	5703FT	NIL LGT: Red	NIL
FAOR 09	VHF Transmitter	260856.43S 0281531.11E	45M (147.6FT AGL)	Day/Night LGT: Red	NIL
FAOR 10	VHF Transmitter	260812.96S 0281507.87E	35M (114.8FT AGL)	Day/Night LGT: Red	NIL
FAOR 11	VHF Antenna	260856.00S 0281531.00E & S260855.00S 0281531.00E	45M (150FT AGL)	Day/Night LGT: Red	NIL
FAOR 12	Mast on BLDG	260618.95S 0281344.85E	ELEV: 5716.27FT	Day markings: Red and White Night markings: Red LGT	NIL
FAOR 13	Building	260840.28S 281231.77E	1757.76M AMSL	NIL LGT: NIL	Obstacle group consolidated under apex height.
REMARK: Iron and Steel works, 5NM SE of the AD REF point at position 261230S 0281730E, releases hot gas at unspecified times - day and night - which is ignited and may cause severe turbulence to 500FT AGL - A BLDG obstruction ADJ TWY A (BTN TWY E and TWY F). BLDG DIST FM TWY CL is 53.258M. All code F ACFT (total wingspan: 80M) to taxi with extreme CTN. -Boksburg South, Boksburg (261356.6S 0281609.5E): Tower (249FT AGL) Obstacle light unserviceable.					

AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	*Associated MET office*	OR Tambo INTL
2	*MET office responsible outside hours*	H24
3	*Office responsible for TAF preparation and periods of validity*	FAOR +27 82 233 9600/8800 30HR, 6 hourly
4	*Type of trend forecast and interval of issuance*	METAR and TREND Every half hour between 0200-2000 and hourly between 2000-0200
5	*Briefing / consultation provide*	Personal and telephonically
6	*Flight documentation / language(s) used*	In ICAO format AVBL for all flight levels. English
7	*Charts and other information available for briefing or consultation*	Standard MET charts
8	*Supplementary equipment available for providing information*	Radar/Satellite/LDN
9	*ATS units provided with information*	TWR, APP, Area
10	*Additional information (limitation of service, etc.)*	Internet: http://aviation.weathersa.co.za Fax-on-demand: +27 82 289 2010

AD 2.12 RWY PHYSICAL CHARACTERISTICS

Designations RWY NR	*True BRG*	*Dimensions of RWY (M)*	*Strength of the pavement classification rating (PCR) and surface of RWY and SWY*	*THR coordinates*	*THR elevation and highest elevation of TDZ of precision APP RWY*	*Slope of RWY-SWY*
1	*2*	*3*	*4*	*5*	*6*	*7*
03L	016º	4421 x 60	PCR 681/F/A/X/U ASPH	260847.11S 0281403.62E	5558FT	0.004D
21R	196º	4421 x 60	PCR 681/F/A/X/U ASPH	260642.86S 0281442.09E	5505FT	0.004U
03R	016º	3405 x 60	PCR 681/F/A/X/U ASPH	260953.17S 0281453.22E	5510FT	0.001D
21L	196º	3405 x 60	PCR 681/F/A/X/U ASPH	260806.64S 0281526.20E	5494FT	0.001U

SWY Dimensions (M)	*CWY Dimensions (M)*	*Strip Dimensions (M)*	*RESA dimensions (M)*	*Location (which runway end) and description of arresting system (if any);*	*OFZ*	*Remarks*
8	*9*	*10*	*11*	*12*	*13*	*14*
00	270	4689 x 300	240 x 120	NIL INFO AVBL	NIL INFO AVBL	See below
00	100	4689 x 300	240 x 120	NIL INFO AVBL	NIL INFO AVBL	See below
57	60	3639 x 300	240 x 120	NIL INFO AVBL	NIL INFO AVBL	See below
57	60	3639 x 300	240 x 120	NIL INFO AVBL	NIL INFO AVBL	See below

Remarks
1. RWY 03L/21R CLSD for MAINT:
MON 2230 till TUE 0300.
WED 2230 till THU 0300.
2. RWY 03R/21L CLSD for MAINT:
TUE 2100 till WED 0300.
THU 2100 till FRI 0300.
3. No construction will be permitted DRG low visibility operation or IMC.

AD 2.13 DECLARED DISTANCES

RWY	*TORA (M)*	*TODA (M)*	*ASDA (M)*	*LDA (M)*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*
03L	4421	4691	4421	4421	NIL
21R	4421	4521	4421	3971	THR displaced 450M
03R	3405	3465	3462	3405	NIL
21L	3405	3465	3462	3405	NIL

AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY	*APCH LGT Type, LEN and INTST*	*THR LGT Colour and WBAR*	*VASIS (MEHT) PAPI*	*TDZ, LGT LEN*	*RWY Centre Line LGT, LEN, Spacing, colour INTST*	*RWY Edge LGT, LEN, Spacing, Colour, INTST*	*RWY End LGT Colour and WBAR*	*SWY LGT LEN (m) Colour*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*	*7*	*8*	*9*	*10*
21L	PALS; CATII; LIH; White to 900M FM end; FM 900M to 300M FM end alternative white & red; last 300M red. DIST BTN lights - 30M	Green	PAPI; both 3º	White	CAT II; LIH; white to 600M FM end, FM 600M to 300M FM end alternative white & red; last 300M red. DIST BTN lights - 30M	White until 600M FM end; FM 600M to end yellow. DIST BTN lights - 60M	Red	NIL	NIL
21R	PALS; CAT II; 900M; LIH; white CL Barrette, RED side row Barrette last 270M, white cross bars at 150M & 300M FM THR	Green	PAPI; both 3º	White	White to 900M FM end, FM 900M to 300M FM end alternate white and red; last 300M red. DIST BTN lights - 30M	White until 600M FM end; FM 600M to end yellow. Spacing 60M BTN LGT	Red	NIL	THR displaced by 450M
03L	PALS; CAT II; 900M; LIH; white CL, red side bars last 270M, white cross bars at 150M and 300M FM THR	Green	PAPI; both 3º	White	CAT II; LIH; CL white to 600M FM end, FM 600M to 300M FM end alternative white & red; last 300M red. DIST BTN lights - 30M	White until 600M FM end; FM 600M to end yellow. DIST BTN lights - 60M	Red	NIL	NIL

03R	PALS; CAT II; 900M; LIH; white CL, red side bars last 270M, white cross bars at 150M and 300M FM THR	Green	PAPI; both 3º	White	CAT II; LIH; CL white to 600M FM end, FM 600M to 300M FM end alternative white & red; last 300M red. DIST BTN lights - 30M	White until 600M FM end; FM 600M to end yellow DIST BTN lights - 60M	Red	NIL	NIL

AD 2.15 OTHER LIGHTING SYSTEMS, SECONDARY POWER SUPPLY

1	*IBN location, characteristics and hours of operation*	NIL INFO AVBL
2	*LDI location & LGT and anemometer location and LGT*	LDI: NIL Anemometer: THR RWY 03R electronic LGT THR RWY 21L THR RWY 03L electronic LGT THR RWY 21R electronic LGT
3	*TWY edge and centre line lighting*	Edge: All TWY edge lights blue. Only lead in lights provided. All rapid taxiways have green CL lights. The following TWY have green CL lights: TWY A FM RWY 21R to INT TWY B, TWY B FM TWY I to APN A, TWY I FM RWY 03L/21R to APN C TWY L FM RWY 03L/21R to APN C, TWY E FM RWY 03L/21R to APN A, TWY H BTN RWY 03L/21R and TWY A TWY N west of RWY 03L/21R; TWY B at the curve at INT WITH APN taxilane M and all rapid exit TWY. All other TWY have blue TWY edge LGT. TWY E east of 03R/21L to Denel (Taxiways with centreline lights). TWY B FM CAT II to APN A (Green centreline lighting) Below taxiways with no centreline lights for CAT II LVP: TWY D, TWY H (west of TWY A),TWY Q, TWY F, TWY J (East and West of RWY 03L/21R), TWY C, TWY N (East of 03L/21R), TWY E (between 03L/21R and 03R/21L), TWY E (east of RWY 03R/21L) TWY H (between 03L/21R and 03R/21L), TWY P, TWY K, TWY L (between TWY Y and RWY 03L/21R), TWY I (East of 03L/21R) TWY Y.
4	*Secondary power supply and switch-over time*	A diesel operated standby generator supplies power to the normal facilities and installations, including all runways, taxiways and apron edge lighting; all radio, radar and NAV aid systems including PAPIs. The UPS is powered by the local municipal supply and secondly by the diesel operated stand-by generator.

5	*Remarks*	a) Stop bars red. b) Obstacle lighting c) Apron floodlights. d) All RWY holding positions have RWY guard lights installed

AD 2.16 HELICOPTER LANDING AREA

1	*Coordinates TLOF or THR of FATO / Geoid undulation*	TLOF 260638.4S 0281433.8E
2	*TLOF and/or FATO elevation (M/FT)*	NIL INFO AVBL
3	*TLOF and FATO area dimensions, surface, strength, marking*	Landing area: 50M x 40M Surface: Concrete Touchdown area: 16M x 16M Strength: 20t
4	*True BRG of FATO*	NIL
5	*Declared distance available*	N/A
6	*APP and FATO lighting*	NIL
7	*Remarks*	a) APN W 2 helipads (north of G APN) b) Use by prior arrangement with AD REF 2.9.1 c) Contact APN office prior to landing.

AD 2.17 ATS AIRSPACE

1	*Designation and lateral limits*	CTR The area bounded by lines drawn as follows, excluding the Rand ATZ. a. From a point at 260002S 0282344E a straight line joining the FLW points: 261632S 0282014E, 262232S 0281429E, 262332S 0281139E, 261602S 0280439E. b. Thence clockwise along the Rand ATZ to a point at 261117S 0280559E. c. Thence a straight line joining the following points 255902S 0280959E, 255222S 0280629E. d. Thence anticlockwise along the arc of a circle, radius 7NM and centred on a point at 254931S 0281347E, to a point at 255632S 0281139E. e.Thence a straight line to the starting point.
2	*Vertical limits*	7 600 FT ALT Note:- Lower limit ABV Rand ATZ 6500FT ALT
3	*Airspace classification*	Class C
4	*ATS unit call sign* *Language(s)*	O R Tambo Radar/O R Tambo Tower. English
5	*Transition altitude*	Transition altitude: 8000FT
6	*Remarks*	EXC where otherwise AUTH, no ACFT is to be operated in this airspace unless two-way RDO CTC is maintained with ATC & the ACFT is equipped with SER mode C transponder.

AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	*Call sign*	*Frequencies*	*Hours of operation*	*Remarks*
1	*2*	*3*	*4*	*5*
APP	Johannesburg Radar West	123.7MHz	DLY 0500-1700	Radar West combined onto 124.5MHz 1700-0500. See Note (2)
APP	Johannesburg Radar South	124.5MHz	H24	See Note (2)
APP	Johannesburg Radar East	124.5MHz	H24	NIL INFO
APP	Johannesburg Radar Director	121.4MHz	As required DRG peak hours	Radar Director combined onto 124.5MHz outside peak hours.
ACC	Johannesburg Area North	126.7MHz	H24	See Notes (1), (2)
ACC	Johannesburg Area South	128.3MHz 126.7MHz	DLY 0430-1800 DLY1800-0430	See Notes (2)
FIS	Johannesburg Information North	127.4MHz 126.7MHz	DLY 0430-1600 DLY1600-0430	See Note (2)
FIS	Johannesburg Information South	127.4MHz 119.5MHz 127.4MHz 126.7MHz	DLY 0430-0600 DLY 0600-1400 DLY 1400-1600 DLY 1600-0430	See Note (2)
FIC/ACC FIC/ACC RSR	Johannesburg Central Information/ Control	120.3MHz transmits and receives	H24	Extended range VHF relay stations. FAKM, FAVW, FABL, FABM. New VHF relay station “FABO” FREQ 120.3MHz. OPS as HOD.
TWR West	Tower West	118.1MHz	DLY 0400-1900	See Note (2) Outside TWR hours of SER, SER provided by SMC on FREQ 121.9MHz
TWR East	Tower East	118.6MHz	MON-FRI 0500-1700, SAT 0700-1600, SUN 0700-1700	After hours SER will be provided by TWR W.
SMC	OR Tambo Ground	121.9MHz	H24	Arriving ACFT to pass registration and prior arranged parking bay from Apron Office on first contact.
Clearance delivery	Clearance Delivery	121.7MHz 121.7MHz	MON-FRI 0400-1830. SAT/SUN 0500-1830.	Outside CLR hours of duty, SER provided by Ground CTL on FREQ 121.9MHz

Service designation	*Call sign*	*Frequencies*	*Hours of operation*	*Remarks*
1	*2*	*3*	*4*	*5*
Apron	OR Tambo Apron	122.65MHz	H24	See Note (3)
ATIS	NIL INFO AVBL	126.20MHz	H24	Dedicated ATIS
JHB Oceanic information, South Atlantic Ocean (SAT)		3452kHz 5565kHz 6535kHz 8861kHz 11291kHz 13315khz 17955kHz	H24	
JHB Oceanic Information, Indian Ocean (INO)		3476kHz 5634kHz 8879kHz 13306kHz 17961kHz	H24	

NOTES:
(1) ATS services sectored into North and South Sector BTN 1500FT AGL to FI105. The line dividing the sectors is as follows: 254457S 0245914E to 260926S 0281352S to 262802S 0304749E.
(2) ATC training daily on all sectors. FIS S FREQ 119.5MHz HR of SER. DLY BTN 0600-1400. Outside of these HR of SER FIS N FREQ 127.4MHz will be responsible for SER provision BTN 0430-0600 and 1400-1600. Outside of these HR of SER Johannesburg ACC N FREQ 126.7MHz will be responsible for SER provision. 1500FT AGL/FL105.
(3) Non ATC Service. Arrival frequency only. Check FAOR AD 2.9 paragraph 5 for information to be provided on arrival.
(4) Non ATC service. Departure frequency only. Check FAOR AD 2.9 for information to be provided on departure.
(5) Area North will provide traffic information services in the area designated as the Lowveld airspace sector BTN FL110 and FL460 outside of Lowveld hours of service.
(6) Information North will provide TFC information services in the area designated as the Lowveld Airspace sector BTN 1500FT AGL and FL105 outside of Lowveld hours of SER.
(7) For domestic flights WI RSA: The flight level REQ to Clearance Delivery, Ground CTL or TWR will not necessarily be the final flight level allocated by ACC for the cruise. The REQ flight level will be accommodated as far as possible, subject to TFC. When it is anticipated by ACC that flight level for the cruise may be FL260 or below. The ACFT will be notified prior to DEP.
(8) Johannesburg Central ACC & FIS on FREQ 120.3MHz remoted FM FAOR. TEL +27 11 9286452.
(9) Johannesburg Area Central will issue inbound CLR for all TFC FL110 and above inbound to Johannesburg TMA. Should TFC patterns dictate, Johannesburg area South controller can reclear TFC as required. When required Johannesburg Central can REQ TFC inbound to FAOR to increase/decrease speed (MACH number if above Flay and AS below FL270) for purposes of sequencing. FL110/FL460.
(10) Pilots are reminded not to REQ RWY 03L for landing on FREQ, as it is predominantly used as a departure RWY.
(11) In the possible event of the Johannesburg VHF system becoming U/S, ACFT operating within the Johannesburg FIR are reminded to:

a. CTC Johannesburg ACC North on 134.0 MHz for ACFT operating within the FAJA ACC North/South airspace.
b. CTC Johannesburg APP on 134.4 MHz for ACFT operating within the FAJA APP airspace.
c. CTC FAOR TWR on 120.85 MHz for ACFT operating within FAOR CTR.
d. For ACFT operating within the FAJA ACC EAST airspace, ACFT shall remain on 129.1 MHz. If 129.1 MHz is also U/S ACFT shall CTC Durban APP on 125.75 MHz.
e. For ACFT operating within FAJA ACC central airspace, ACFT shall remain on 120.3 MHz. If 120.3 MHz is also U/S ACFT shall CTC Bloemfontein APP on 124.3 MHz.
(12) All INTL OPR FLY into and out of South Africa and particularly those departing FM O R Tambo INTL airport (FAOR) are to appreciate and accept that the cruising FL issued by FAOR CLR delivery are issued as a guide only and may be SUBJ to change by FAJA ACC. The final CRZ LVL will be confirmed by FAJA ACC as and when changes are REQ.

AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid (VAR)	*ID*	*Frequency*	*Hours of operation*	*Site of transmitting antenna coordinates*	*DME transmitting antenna Altitude*	*Remarks*
1	2	3	4	5	6	7
DVOR	JSV	115.2 MHz	H24	260925.63S 0281351.70E	5579	Scalloping may be experienced on radial 090. Power output 50W
UHF DME	JSV	1186 MHz transmits and receives	H24	260925.63S 0281351.70E	5579	Channel 99X co-axially co-located with DVOR
ILS LOC (RWY 03L)	JSI	110.3 MHz	H24	260616.8S 0281450.2E	5499	NIL INFO AVBL
Front course sector angle 2,5° coverage outside +/- 35° sector NIL.						
ILS GP (RWY 03L) CAT II	-	335 MHz	H24	260834.2S 0281403.0E	5549	Angle 3°. HGT of ILS ref datum-68FT. ALT of GP over OM 6871FT MM 5797FT
ILS LOC (RWY 03R)	JNI	109.1 MHz	H24	260757.6S 0281528.9E	5495	
Front course sector angle 1° 38'. Coverage outside +/- 35° sector - NIL.						
ILS GP (RWY 03R) CAT II	-	331.4 MHz	H24	260945.9S 0281500.0E	5514	Angle 3°. HGT of ILS ref datum 50FT. ALT of GP over OM 6680FT MM 5731 FT.
ILS LOC (RWY 21L)	JAI	109.9 MHz	H24	261004.5S 0281449.7E	5518	
Front course sector angle 1°36'. Coverage outside +/- 35° sector NIL.						
ILS GP (RWY 21L) CAT II.	-	333.8 MHz	H24	260815.9S 0281527.8E	5499	Angle 3°. HGT of ILS ref datum 50FT. ALT of GP over OM 6696FT MM 5699FT.
ILS/DME	JBI	110.9 MHz	H24	260653.43S 0281443.29E	5557	NIL INFO AVBL
NOTE: All aircraft to expect clearance for ILS Z unless otherwise directed by ATC.						
ILS GP (RWY 21R) CAT II.	NIL INFO AVBL	330.8 MHz	H24	260653.43S 0281443.29E	NIL INFO AVBL	NIL INFO AVBL
Top of Glide path mast. (15.6M above concrete foundation).						
ILS LOC (RWY 21R)	JBI	110.9 MHz	H24	260903.63S 0281358.51E	NIL INFO AVBL	NIL INFO AVBL
Survey nail with washer in concrete. (2.5 M above concrete foundation).						

AD 2.20 LOCAL AERODROME REGULATIONS

1. Pilots of VFR departures from OR Tambo International Airport must ensure that they do not commence their turn outs over the apron areas.
2. Aircraft taxiing on the apron in low visibility procedures are not to exceed 10knots, until they have left the apron area and are on a demarcated taxiway.

Procedures for VFR flights within FAOR CTR Helicopter Operations

1. TWR W is responsible for all helicopter TFC in the western sector of the CTR as well as LDG and departing TFC on RWY 03L/21R and TFC XNG RWY 03L/21R.
2. With RWY 03 in use all helicopter TFC have to CTC TWR E on 118.6 MHz before entering the FAOR CTR FM the E BTN points 260348S 0282246E and 260629S 0281500E and 261313S 0281254E and 261419S 0281041E.
3. All helicopter TFC have to CTC TWR W on 118.1 MHz before entering the FAOR CTR FM the W BTN points 261419S 0281041E and 261313S 0281254E and 260629S 0281500E and 260348S 0282246E.
Note: After hours of service, TWR W assumes responsibility for the eastern sector of the CTR as well as RWY 03R/21L. SMC assumes responsibility for taxiways E of RWY 03L/21R.
4. With RWY 21 in use all helicopter TFC have to CTC TWR E on 118.6 MHz before entering the CTR from the E BTN points 261433S 0282038E and 260952S 0281409E and 260434S 0281551E and 260241S 0280645E.
5. All helicopter TFC have to CTC TWR W on FREQ 118.1 MHz before entering the CTR FM the W BTN points 260241S 0280845E and 260434S 0281551E and 260952S 0281409E and 261433S 0282038E.
6. Helicopters pilots to verify the RWY in use on ATIS FREQ 126.2 MHz prior to entering CTR.
7. TWY's with no centreline lights as published in AD 2.15 for CAT II LVP,OPS below RVR 350M follow me vehicle will be provided O/R for arriving ACFT.

AD 2.21 NOISE ABATEMENT PROCEDURES

1. Pilots are to be considerate towards the inhabitants of areas adjacent to AD by minimizing ACFT noise.
2. ACFT noise and flight track adherence is monitored at AD.
3. Use noise abatement procedure as per AIP ENR 1.5.
4. No RWY intersection take-off BTN 2000 to 0400.
5. No ACFT engine run ups shall be allowed BTN 2000 to 0400 without prior permission FM the AP manager or in an emergency.

AD 2.22 FLIGHT PROCEDURES

NIL INFO AVBL

AD 2.23 ADDITIONAL INFORMATION

1. Bird activity on AP
2. Dog will be present on airfield DRG daylight HR. In support of bird and wildlife CTL. Handler will be present with the dog at all times.

AD 2.24 CHARTS RELATED TO AN AERODROME

Aerodrome Chart	-AD-01
Ground movement	-AD-02
Aircraft Parking/Docking Chart	-AD-03
Aerodrome Parking and Docking Chart	-AD-04
Aircraft Parking/Docking Chart	-AD-05
Aircraft Parking/Docking Chart	-AD-06
Ground Movement Chart	-AD-07
Hot spot chart	-AD-08
ILS Z RWY 03L	-ILS-01
ILS Y RWY 03L	-ILS-02
ILS Z RWY 03R	-ILS-03
Data tabulation	-ILS-03A
ILS X RWY 03R	-ILS-05
ILS W RWY 03R	-ILS-06
ILS RWY 21L	-ILS-07
Data tabulation	-ILS-07A
ILS RWY 21R	-ILS-10
Data tabulation	-ILS-10A
VOR Z RWY 21R	-VOR-01
VOR Y RWY 21R	-VOR-02
AVILO 1A 03R STAR	-ARR-07
AVAGO 1C 03R STAR	-ARR-08
Data tabulation	-ARR-08A
NIBEX 1B RNAV RWY 03R STAR	-ARR-09
Data tabulation	-ARR-09A
AVILO 1B RNAV RWY 03R STAR	-ARR-12
Data tabulation	-ARR-12A
AVAGO 1D STAR 21L	-ARR-18
Data tabulation	-ARR-18A
NIBEX 1D STAR 21L	-ARR-19
Data tabulation	-ARR-19A
EGMEN 2A SID 03L	-DEP-01
APDAK 3A RWY 03L SID	-DEP-02
VASUR 3A SID 03L/R	-DEP-03
RAGUL 3A RWY 03L/R SID	-DEP-04
NESAN 1A SID 03L/R	-DEP-06
GRASMERE 5B RWY 03L/R SID	-DEP-07
EXOBI 1A SID 03L/R	-DEP-08
EGMEN 1C SID 03L	-DEP-10
Data tabulation	-DEP-10A
APDAK 1 B RNAV 03L SID	-DEP-11
Data tabulation	-DEP-11A
EGMEN 2B SID 21R	-DEP-12
APDAK 2B RWY 21R SID	-DEP-13
VASUR 3B SID 21L/R	-DEP-14
OVALA 1B RWY 21L/R SID	-DEP-16
GRASMERE 6C RWY 21R SID	-DEP-17
EXOSI 3B SID 21L/R	-DEP-18
HEIDELBERG 5D RWY 21L/R SID	-DEP-19
LANSERIA 1C SID 21R	-DEP-20
EGMEN 1D SID 21R	-DEP-21
Data tabulation	-DEP-21A
APDAK 1 D RNAV RWY 21R SID	-DEP-22
Data tabulation	-DEP-22A
GEROX 1C RNAV RWY 21R SID	-DEP-23
Data tabulation	-DEP-23A
RAGUL 1D RWY 21R	-DEP-24
Data tabulation	-DEP-24A
Radar Minimum Altitude Chart	-RAD-01

RNAV RWY 03R Data tabulation RNAV RWY 21L Data tabulation	-RNAV-01 -RNAV-01A -RNAV-02 -RNAV-02A
The following charts are AVBL on CAA website: www.caa.co.za AD OBST Type A RWY 03L 21R AD OBST Type A RWY 03R 21L Precision APCH Terrain Chart RWY 03L Precision APCH Terrain Chart RWY 21R Precision APCH Terrain Chart RWY 03R Precision APCH Terrain Chart RWY 21L	The following charts are AVBL on CAA website: www.caa.co.za -OBST Type A-01 -OBST Type A-02 -PATC-01 -PATC-02 -PATC-03 -PATC-04

THIS PAGE INTENTIONALLY LEFT BLANK