FAPE

FAPE AD 2.1 AERODROME LOCATION INDICATOR AND NAME

FAPE - CHIEF DAWID STUURMAN INTERNATIONAL

FAPE AD 2.2 AERODROME GEOGRAPHICAL AND ADMINISTRATIVE DATA

1	*ARP co-ordinates and site at AD*	335924.05S 0253637.00E ± 800M South West of ATC tower
2	*Direction and distance from city*	5NM S
3	*Elevation/Reference temperature*	229FT / 22.4° C
4	*Geoid undulation at AD ELEV PSN*	91.5FT
5	*MAG VAR /* *Annual change*	28°W (2018) 0°11' W
6	*AD Operator, address, telephone, telefax, email, AFS Address and, if available, website address*	Airports Company South Africa Ltd P.O Box 5787 Walmer, Gqeberha, 6065 Switchboard: +27 41 507 7348 FAX: +27 41 507 7340 E-mail: fape@airports.co.za Website: www.airports.co.za Administration, office hours Airport Information, Office hours 27 41 507 7319 Airport manager: Claudia Daniels TEL: +27 41 507 7378 CELL: +27 62 414 6379 E-mail: claudia.daniels@airports.co.za ATNS Co Ltd: Box 5360, Walmer, 6065 ATC TEL: +27 41 501 5900 Cell: +27 82 553 3776 Fax: +27 41 501 5959 MATS TEL: +27 41 501 5920 Cell: +27 82 553 3776 E-mail: vellym@atns.co.za Watch manager ATS TEL: +27 41 501 5932 Cell: +27 81 542 5569 E-mail: delycet@atns.co.za MTS TEL: +27 41 501 5906 FAX: +27 41 501 5957 ATS Filter TEL: +27 41 501 5948 AFS: FAPEYFYX E-mail: fapebrief@atns.co.za ATS TWR AFS: FAPEZTZX MET admin TEL: +27 41 581 1476/1795 Forecaster TEL: +27 41 581 0403 Cell: +27 66 056 6254 E-mail:info@weathersa.co.za / fapefc@weathersa.co.za

		Customs and excise TEL: +27 41 503 0100 / 0228 FAX: +27 41 503 0690 Cell: +27 82 697 6623, +27 79 112 4103 Mr. Msinga +27 79 884 7464 Immigration: TEL: +27 41 404 8301 FAX: +27 41 487 2191/1078 or +27 86 562 1859 Cell: +27 82 809 5237/8, +27 66 306 8777 and +27 66 306 8789 Border police: TEL: +27 41 507 7423, FAX: +27 41 507 7418 Cell: +27 82 828 4932 E-mail: gouwscharl@saps.org.za RFFS, all hours (emergency only) TEL: +27 41 507 7314/5 Department of health: TEL: +27 41 391 8100 FAX: +27 41 373 4516 Cell: +27 72 293 4923 / +27 83 378 2198 / +27 83 378 2014 Department of agriculture: TEL: +27 41 484 2725 FAX: +27 41 484 2785 Cell: +27 82 392 4801 / +27 83 542 4267
7	*Types of traffic permitted (IFR / VFR)*	IFR/VFR
8	*Remarks*	No microlight operations permitted.

FAPE AD 2.3 OPERATIONAL HOURS

1	*AD Operator*	MON-THU: 0600-1430 FRI: BTN 0600-1400 SAT BTN: 0300-1730 SUN: BTN 0300-1930 and Public holidays: same as weekdays Aerodrome Rescue and Fire Fighting Services: H24 Airport Operations and Infrastructure Asset Management: MON-FRI: 0300-1930 SAT: BTN 0300-1730 SUN: BTN 0300-1930 public holidays: same as weekdays Apron Office: H24 Airport INFO SER: MON-FRI: 0300-1930 SAT: 0300-1730, SUN: 0300-1930 and Public HOL: Same as weekends
2	*Customs and immigration*	H24 on Call-out REF. FAPE AD 2.20 Office HR: MON-FRI: 0530-1415 Border police: H24 on Call-out REF. FAPE AD 2.20 Office HR: MON-FRI: 0530-1400
3	*Health and sanitation*	H24
4	*AIS briefing office*	AIS Filter: MON-SUN: 0400-1800

5	*ATS reporting office (ARO)*	NIL INFO AVBL
6	*MET briefing office*	MON-SUN: H24 except closed for 3HR from SAT: 1900-2200
7	*ATS*	H24
8	*Fuelling*	Shell aviation service: MON: 0300-2200 TUE-FRI: H24 to SAT 1800 SUN: 0300-1900 Public HOL: Same as weekdays Depot TEL: +27 41 581 2284 AFT HR +27 82 902 2270 Eastcoast Airways MON-FRI: 0600-1500, SAT: 0600-1200, SUN: 0600-0900 Public HOL: 0900-1200 TEL: +27 41 581 4194. AFT HR: +27 73 891 5335 After hour call out fee R350.00 plus value added Tax (VAT) will be applicable. Payment VISA, Master card, Diners or Cash. No cheques will be accepted.
9	*Handling*	Nascolossal MON-FRI: 0300-2000 SAT-SUN: 0430-1800 TEL: +27 41 507 7412 AFT HR: +27 82 836 7802, +27 82 898 2847 Menzies Aviation SA MON-FRI: 0300-1830 SAT: 0300-1100 SUN: 0300-1930 Swissport MON-FRI: H24 SAT: 0400-1830 SUN: 0300-2000 TEL: +27 41 507 7284; AFT HR: +27 79 511 8293
10	*Security*	Passenger screening: MON-SUN: 0300-1930 Public HOL: same as weekdays Perimeter: H24
11	*De-icing*	NIL

12	*Remarks*	• Pilot Training: No training BTN 2000 and 0400. • AIRAC procedures to be followed • Ad-Hoc extension including delays to scheduled flights, AD operator's hours for terminal services can be requested for consideration by the Airport Authority at an 'After Hours' rate. • Requests by operators involving an Ad-hoc or additional (not a delayed flights may follow this procedure). The applicant / ACFT operator must route their relevant request to the Airport Authority for consideration. The request must reach the Airport Authority at least 7 working days in advance of the intended effective date. ATS - Route queries. • Handling of scheduled flights after hours of operation:- The provision of an ATC and associated airport services after the published hours of operation, of the aforementioned services, will be left to the discretion of the relevant service providers when the aircraft is delayed beyond the control of the pilot in command or the operator. However this will not negate the pilot in command or the operator from complying with any requirements as laid down in the Air Navigation Regulations. For any delayed flight, where the delay exceeds 30 minutes into non-operational hours, special arrangements need to be made with the Airport Authority, who will charge a standard after hours rate. AP terminal SER OPR FM 0300 TIL 1900. Commercial PAX FLT to and FM FAPE after 1900 to CTC AP management 7 days prior to OPS, excluding diversions. All queries may be directed to Claudia Daniels +27 624146379, Andrae Pillay +27 740218878 and Matthews Stemele +27 629261624.

FAPE AD 2.4 HANDLING SERVICES AND FACILITIES

1	*Cargo-handling facilities*	All modern facilities handling weights of up to 30 000KG; Nascolossal TEL +27 41 507 7412 after HR +27 82 836 7802 / +27 82 898 2847 Menzies Aviation TEL: +27 83 671 8964, +27 83 280 2549 Swissport SUN 0900-2200 TEL: +27 41 507 7284 / after hours: +27 79 511 8293
2	*Fuel and Oil types*	JET A1 - Shell AVGAS and JET A1: Eastcoast Airways.
3	*Fuelling facilities and capacity*	Shell Fuel hydrant line (all bays) 4 x 70 000L above ground storage tanks 2 x 18 000L bowser 1 x hydrant dispenser Eastcoast Airways 23 000L underground storage tank and 29 000L container - Avgas 2 000L bowser - Jet A1 2 000L bowser - Avgas 3 000L bowser - Avgas
4	*De-icing facilities*	NIL
5	*Hangar space for visiting aircraft*	Limited availability, by prior arrangement only, up to King Air 200 size aircraft. Contact Eastcoast Airways.

6	*Repair facilities for visiting aircraft*	NIL
7	*Remarks*	NIL

FAPE AD 2.5 PASSENGER FACILITIES

1	*Hotels*	Roadlodge at AD: +27 41 506 7000 A number of hotels in city ranging from one to five star. Also a variety of guest houses. Information AVBL at Information desk.
2	*Restaurants*	1. Wimpy in departures hall (1st Floor) 2. Mile high pub in departures hall (1st Floor) including a smoking area. 3. Primi in arrivals hall - Halaal 4. Mugg & Bean - in sterile area licenced to sell liquor HOD: same as AD operator hours.
3	*Transportation*	Transportation available: • Car rentals and metered taxis • Transfer buses, coaches and shuttle services to be arranged through Blunden tours and travel • Office HR +27 41 581 0411 • AFT +27 41 451 4803
4	*Medical facilities*	No ambulance on AD. Basic first aid facilities on AD (Basic first aid level 3). Airport has one AED machine at security check point. Basic medical facility in international arrivals and one in fire station. Navomix Clinic at arrivals Hall HOD: TUE, WED, FRI: 0600-1430 Nearest hospitals: St Georges Life (2.61KM); Private Gqeberha Provincial hospital (3.42KM); Netcare Greenacres hospital (3.21KM); Private Livingston Provincial hospital (8.01KM); Life Mercantile hospital (6.37KM). Metro ambulance service available within 15KM of AD
5	*Bank and Post Office*	ABSA, FNB, Standard Bank, Nedbank ATM's AVBL at AD. Post office in Walmer, 8th avenue, stand alone post box at AD. Forex facility in arrivals
6	*Tourist office*	Nelson Mandela Bay tourism office AVBL at arrivals: +27 41 581 0456/7. PE tourism.
7	*Remarks*	NIL

FAPE AD 2.6 RESCUE AND FIRE FIGHTING SERVICES

1	*AD category for fire fighting*	CAT 7, H24 Four shifts (7 MNM, 6 AD Rescue and Fire Fighters plus 1 Officer per shift) covering AD operational hours. 1 watchroom operator will be available per shift.

2	*Rescue equipment*	2 power saws, 2 power breakers, (jaws of life) and breathing apparatus. 2 macro Aerodrome Rescue and Fire Fighting vehicles with total water capacity of not less than 12100L and 2000 Aqueous Film Forming Foam. Complementary agents: 250KG dry chemical powder 200% extinguishing media stock is maintained, as per ICAO requirements for CAT 7 - DOC 9137/AN-898 Part 1.
3	*Capability for removal of disabled aircraft*	Limited AVBL on airport for light aircraft only. Equipment for removal of other aircraft will be sourced as per emergency plan.
4	*Remarks*	AD Rescue and Fire Fighting Services: H24 Terminal after hours services available on request, at a cost. See FAPE AD 2.3(12) 1. Memorandum of understandings - MOU has been concluded with the NMB Disaster Management who will facilitate the emergency response of all external role players during all aircraft emergencies, Hazmat incidents, and will facilitate the supply of equipment and facilities for a decontamination area. This MOU includes but is not limited to: Mountain clubs, NSRI, SAPS and SANDF/SAAF are included in the disaster management agreement. 2. Search and rescue in South Africa, refer to GEN 3.6.

FAPE AD 2.7 SEASONAL AVAILABILITY - CLEARING

1	*Types of clearing equipment*	NIL
2	*Clearance priorities*	NIL
3	*Remarks*	Occasionally fog bound at the end of the winter period

FAPE AD 2.8 APRONS, TAXIWAYS AND CHECK LOCATIONS/POSITIONS DATA

1	*Apron surface and strength*	Alpha Surface: Jointed concrete panels Strength: PCR 524/F/B/X/U. General Aviation (Charlie) Surface: Interlocking paving strength: PCR 524/F/B/X/U.
2	*Taxiways width* *Taxiway surface* *Taxiway strength*	A, A1, A2, A4 Surface: ASPH Strength: PCR 524/F/B/X/U; Width: 22.5M Taxiway ‘A3’ leading off RWY 08/26 Strength: PCR 524/F/B/X/U; Width; 7.5M See limitation for use of TWY A3’ under remarks.
3	*Altimeter checkpoint location and elevation*	NIL INFO AVBL
4	*VOR checkpoints*	NIL INFO AVBL
5	*INS checkpoints*	See AD chart

6	*Remarks*	Parking Procedures: • Marshal parking on bays allocated by apron office (Refer AD 2.9.1) • Park large aircraft nose-in • No engine run-ups allowed on apron without permission from AD CHF. Limitations on the use of taxiway A3 • Only to be used by aircraft with MTW not exceeding 6500KG. • Take-off from A3 intersection will not be permitted by any aircraft. • No hardened shoulders on any TWY's at FAPE. • WT limitations for use of General Aviation pavement surfaces, MAX 6500KG unless prior approval has been granted.

FAPE AD 2.9 SURFACE MOVEMENT GUIDANCE AND CONTROL SYSTEM AND MARKINGS

1	*Use of aircraft stand ID signs, TWY guide lines and visual docking / parking guidance system of aircraft stands.*	a. ACFT stand ID signs: A1, A2, A3, A4, A5, A6, A7, A8, A9, A10, A10(A), A11, A12. Allocation of parking bays: Pilot contacts the Apron control office, call sign "AO" on the FREQ 122.65 MHz, while still on taxiway A or enroute to FAPE. Follow guide lines from TWY centre line into allocated parking bay. Stand ID number painted on surface. Marshalling guidance at aircraft stands. b. On pushback an engineer escorts departing aircraft from apron. Aircraft contacts ATC on FREQ 118.10 MHz for pushback, start and taxi clearance. c. Schedule passenger aircraft are to park nose in on the Apron. d. Pushback on departure, except where power-out procedures have been approved by AD. Marshallers are to be attendants during power outs.
2	*RWY and TWY markings and LGT*	RWY Marking: THR markings, RWY designators, RWY centre line, touchdown zone markings, aiming points & side stripes, and lead on/ lead off lines. TWY marking: Centre line, RWY holding points, ILS holding point and TWY intersection lines and enhanced markings. RWY Lights: THR lights, edge lights, centre line lights and touch down zone lights on RWY 26. TWY Lights: Edge lights Stop bars Lead on/Lead off lights Guard lights Approach, RWY and threshold lights leading to displaced threshold RWY 26 Approach, RWY and threshold lights RWY 08
3	*Stop bars*	Fully operational in all conditions.
4	*Remark*	On push back an engineer escorts departing aircrafts from parking stand, Aircraft to contact ATC on FREQ 118.10 MHz for pushback clearance, start and taxi clearance. Scheduled passenger aircrafts to park nose in, in parking bay stands. Push back on departure, except where power-out procedures have been approved by AD, marshallers to be in attendance during power-outs. All aircraft operating on movement area are requested to follow mandatory and information signs, markings, and lights erected in accordance with ICAO regulations.

FAPE AD 2.10 AERODROME OBSTACLES

In Area 2					
OBST ID/ Designation	*OBST type*	*OBST position*	*ELEV/HGT*	*Markings/ Type, colour*	*Remarks*
a	*b*	*c*	*d*	*e*	*f*
NIL INFO AVBL	Radio mast on Botha's Kop	335951S 0252926E	950 / 150FT	NIL INFO AVBL	NIL
NIL INFO AVBL	Four lighting masts	340020S 0253411E	354 / 48FT	NIL INFO AVBL	NIL
NIL INFO AVBL	Five lighting masts	335922S 0253526E	225 / 110FT	White	NIL
NIL INFO AVBL	Radio masts	NIL INFO AVBL	328 / 115FT 203 / 115FT 49 / 115FT	NIL INFO AVBL	3.6 NM WNW 1.0 NM NNW 2.7 NM ESE
NIL INFO AVBL	One lighting mast	335922S 0253526E	225 / 115FT	White	NIL
NIL INFO AVBL	Nine lighting masts	335904S 0253643E	200 / 83FT	Grey	New Apron lights (25M masts)
NIL INFO AVBL	One lighting mast	335900S 0253649E	197 / 54FT	Grey	New Apron lights (16M masts)
(1) Power line on APCH RWY 35. (2) 3 x light masts in parking area.					

In Area 3					
OBST ID/ Designation	*OBST type*	*OBST position*	*ELEV/HGT*	*Markings/ Type, colour*	*Remarks*
a	*b*	*c*	*d*	*e*	*f*
NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL

FAPE AD 2.11 METEOROLOGICAL INFORMATION PROVIDED

1	*Associated MET office*	OR Tambo INTL
2	*Hours of service* *MET Office outside hours*	Observation: H24, SAT 2201-1900 Forecasting: 0200-1900, TEL: (041) 581 0403 O R Tambo INTL, TEL: (011) 3909 329/30
3	*Office responsible for TAF preparation* *Periods of validity*	Chief Dawid Stuurman, H24, 06-06, 12-12, 18-18. OR Tambo, 00-24

4	*Trend forecast* *Interval of issuance*	0200-1900 1/2 hourly by FAPE 1900-0200 hourly by FAOR
5	*Briefing / consultation provided*	Personal and telephonically
6	*Flight documentation / Language(s) used*	Standard ICAO format English
7	*Charts and other information available for briefing or consultation*	Standard meteorological charts.
8	*Supplementary equipment available for providing information*	Satellite / LDN
9	*ATS units provided with information*	YES
10	*Additional information (limitation of service, etc.)*	Flight documentation and other aviation related information AVBL on web page http://aviation.weathersa.co.za. Chief Dawid Stuurman WX radar (335938.44S 0253638.58E) decommissioned. Affected area 150KM radius around FAPE. Enquiries CTC Hugh Van Niekerk +27 71 682 5467. NIL disruption to MET data SER.

FAPE AD 2.12 RUNWAY PHYSICAL CHARACTERISTICS

Designations RWY NR	*True BRG*	*Dimensions of RWY (M)*	*Strength (PCR) and surface of RWY and SWY*	*THR coordinates RWY end coordinates THR geoid undulation*	*THR elevation and highest elevation of TDZ of precision APP RWY*	*Slope of RWY-SWY*
1	*2*	*3*	*4*	*5*	*6*	*7*
08	058°T	1980 x 46	ASPH PCR 524/F/B/X/U	335937.89S 0253600.00E	229FT	0.006 D
26	238°T	1980 x 46	ASPH PCR 524/F/B/X/U	335903.93S 0253705.57E	189FT	0.006 U
17	146°T	1677 x 46	ASPH PCR 524/F/B/X/U	335901.81S 0253658.63E	192FT	0.001 D
35	326°T	1677 x 46	ASPH PCR 524/F/B/X/U	335946.78S 0253735.51E	184FT	0.001 U

SWY Dimensions (M)	*CWY Dimen-sions (M)*	*Strip Dimensions (M)*	*RESA dimensions (M)*	*Location (which runway end) and description of arresting system (if any);*	*OFZ*	*Remarks*
8	*9*	*10*	*11*	*12*	*13*	*14*
60 x 46	60 x150	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	See below
NIL	60 x 150	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	See below
NIL	60 x 150	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	See below
NIL	NIL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	NIL INFO AVBL	See below

SWY Dimensions (M)	*CWY Dimen-sions (M)*	*Strip Dimensions (M)*	*RESA dimensions (M)*	*Location (which runway end) and description of arresting system (if any);*	*OFZ*	*Remarks*
8	*9*	*10*	*11*	*12*	*13*	*14*

Remarks

(1) Circuit: Turbine powered ACFT-1729 FT ALT; Reciprocating ENG-powered ACFT-1229 FT ALT.
(2) OBST at RWY THR LGT and in GS SFC beyond RWY 08 THR and RWY 26 THR. THR LGT CONC base are 2 CM ABV the RWY SFC and must be regarded as an OBST. Unsafe ditches caused by jet blast beyond the THR must be regarded as OBST.
(3) No hardened shoulders along runways at FAPE.
(4) Distance markers touch down zones and landing mat does not line up.
(a) Only 3 distance markers on RWY 17 due to RWY intersection, the primary RWY 08/26 takes preference. SA CAA approved.
(b) RWY 26 RTZL extends 300M past TDZ paint markings. Remaining LDA FM end of RTZL 1080M.

FAPE AD 2.13 DECLARED DISTANCES

RWY Designator	*TORA (M)*	*TODA (M)*	*ASDA (M)*	*LDA (M)*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*
08	1980	2040	2040	1980	NIL
26	2160	2220	2160	1980	NIL
17	1677	1737	1677	1677	NIL
35	1677	1677	1677	1677	NIL

FAPE AD 2.14 APPROACH AND RUNWAY LIGHTING

RWY Designator	*APCH LGT Type, LEN and INTST*	*THR LGT Colour and WBAR*	*VASIS (MEHT) PAPI*	*TDZ, LGT LEN*	*RWY Centre Line LGT LEN, spacing, colour, INTST*	*RWY Edge LGT, LEN, Spacing, Colour, INTST*	*RWY End LGT Colour and WBAR*	*SWY LGT LEN (M) colour*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*	*7*	*8*	*9*	*10*
08	PALS CAT II Barette 30M spacing, 900M, high	Green, No	PAPI 3° L/R	60M, White, 3 each side of RCL, run for 900M FM THR	30M, White to 900M FM THR, NXT 600M red/white, last 300M red.	Full, 60M, white, last 600M yellow high	Red, NIL	NIL	NIL

26	PALS CAT II Barette 30 M spacing, 900 M, high	Green, No	PAPI 3° L/R	60 M, white, 3 each side of RCL, run for 900 M FM THR.	30 M, White to 900 M FM THR, NXT 600 M red/white, last 300 M red.	Full, 60 M, white, last 600 M yellow high	Red, NIL	NIL	First TDZ LGT 11.25 M FM RCL
17	NIL	Green, No	PAPI 3° L	NIL	NIL	Full, 60 M, white, last 600 M yellow medium	Red, NIL	NIL	NIL
35	NIL	Green, No	PAPI 3° L	NIL	NIL	Full, 60 M, white, last 600 M yellow medium	Red, NIL	NIL	NIL

*RWY 26 First TDZ LGT 11.25M FM RCL
*RWY 26 and 08 APCH LGT - Crossbars at 150 M and 300 M
*Deviation Approved by SACAA on approach light spacing's on RWY 26 between distances 420 M to 644 M from Threshold.
*Taxiway edge and centre line lighting AVBL.

FAPE AD 2.15 OTHER LIGHTING SYSTEMS, SECONDARY POWER SUPPLY

1	*ABN/IBN location, characteristics and hours of operation*	NIL INFO AVBL
2	*LDI location and LGT Anemometer location and LGT*	NIL INFO AVBL
3	*TWY edge and centre line lighting*	AVBL
4	*Secondary power supply and switch-over time*	As per ICAO recommendations
5	*Remarks*	OBST X 10 APN high mast floodlights. New high mast flood lights.

FAPE AD 2.16 HELICOPTER LANDING AREA

1	*Coordinates TLOF or THR of FATO Geoid undulation*	NIL INFO AVBL
2	*TLOF and/or FATO elevation M/FT*	NIL INFO AVBL
3	*TLOF and FATO area dimensions, surface, strength, marking*	NIL INFO AVBL
4	*True BRG of FATO*	NIL INFO AVBL
5	*Declared distance available*	NIL INFO AVBL
6	*APP and FATO lighting*	NIL INFO AVBL

7	*Remarks*	a) On APN - not marked marshallers in attendance to ensure safe distances when landing between fixed wing and rotary wing aircrafts. b) At General aviation - not marked - TWR to coordinate helicopter OPS in / out of General Aviation area. c) 2 Heli parkings available in GA, refer to procedure FAPE AD 2.22 flight procedures.

FAPE AD 2.17 ATS AIRSPACE

1	*Designation and lateral limits*	CTR (a) From a point at 340955.82S 0253153E.49 clockwise along the arc of a circle, radius11 NM, and centered at 335933.01S 0253620.75E to a point at 335713.35S 0252324.83E (b) Thence a straight line to a point at 334857.77S 0254001.15E (c) Thence clockwise along the arc of a circle, radius 11 NM, and centered at 335933.01S 0253620.75E to a point at 340111.93S 0254925.79E (d) Thence a straight line to the starting point at 340955.82S 0253153.49E *Note: Radar faded in the area bounded by, (335906S 0252036E, 340008S 0252754E, 340255S 0252756E, 340221S 0252030E) TFC advised to avoid area due to separation difficulties.*
2	*Vertical limits*	GND - 2000FT ALT
3	*Airspace classification*	Class C
4	*ATS unit call-sign* *Language*	English
5	*Transition altitude*	5500FT
6	*Hours of applicability*	H24
7	*Remarks*	EXC where otherwise authorized, no ACFT is to be operated in this airspace unless two-way RDO CTC is maintained with ATC.

FAPE AD 2.18 ATS COMMUNICATION FACILITIES

Service designation	*Call sign*	*Frequency*	*Hours of operation*	*Remarks*
1	*2*	*3*	*4*	*5*
ATIS	PEV	126.8 MHz	0400-1800	NIL
APP APP RSR	Port Elizabeth approach	120.4 MHz Transmits and receives	H24	NIL
APP	Port Elizabeth approach	120.4 MHz Transmits and receives	H24	Location MAG 262.08, 8 NM RWY 08
TWR	Port Elizabeth tower	118.1 MHz Transmits and receives	H24	NIL
Clearance delivery	Port Elizabeth clearance	122.10 MHz Transmits and receives	MON-SUN BTN 0400-1800	Outside CLR delivery HOD, SER will be provided by TWR on FREQ 118.1 MHz

FAPE AD 2.19 RADIO NAVIGATION AND LANDING AIDS

Type of aid, MAG VAR, Type of supported OP (for VOR/ILS/ MLS, give declination)	*ID*	*Frequency*	*Hours of operation*	*Position of transmitting antenna coordinates*	*Elevation of DME transmitting antenna*	*Remarks*
1	*2*	*3*	*4*	*5*	*6*	*7*
ILS LOC (RWY 26)	PDI	109.5 MHz Transmits	HS	335942.88S 0253550.38E	236 FT	Location MAG 084°MM 0,5 NM THR RWY 26. No OM.
ILS GP (RWY 26) CAT II	NIL INFO AVBL	332.6 MHz Transmits	HS	335912.04S 0253658.78E	192 FT	Angle 3° nominal. RDH 74 FT ALT above 429 FT
ILS LOC (RWY 08)	PEI	111.1 MHz Transmits	HS	335858.40S 0253716.25E	176 FT	OM 3,9 NM THR RWY 08
ILS GP (RWY 08)	NIL INFO AVBL	331.7 MHz	HS	335928.42S 0253609.44E	213FT	CAT II angle 3° nominal. RDH 70FT ALT above OM 1534 FT.
UHF DME	PEV	CH 76x	H24	335933.01S 0253620.75E	NIL INFO AVBL	CH 76x co-axially co-located with the VOR
VOR	PEV	112.9 MHz transmits.	HS	335933.01S 0253620.75E	215 FT	Letdown radial 080° intercepts centreline of RWY 26, and letdown radial 269° intercepts centreline of RWY 08, APRX 1 NM from THR.

FAPE AD 2.20 LOCAL AERODROME REGULATIONS

1. Call-out procedure for across border flight clearance (International Flights)

a. Arriving International Flights

•The pilot in charge of an arriving international flight must ensure that customs and excise, Immigrations, border police and the department of health, department of agriculture as well as the Airport Manager, are informed of the flight, at least one (1) hour before landing, see landing details FAPE AD 2.2.

The following INFO must have been provided to the relevant authorities.
- ACFT Registration;
- Pilot name;
- Point of origin;
- Landing clearance reference number or FOP where required,
- Number of people on board;
- Time of arrival

• After arrival, taxi clearance will be given to the pilot to taxi to an allocated parking bay on the main apron, in front of the terminal building. No international flights are to park at any other location than on the main apron bays 1-5.
• Representatives from the relevant authorities will meet the aircraft, on arrival, at the allocated parking bay.
• Neither the pilot, nor any of the passengers or cargo, may leave the aircraft prior to all the relevant authorities present.
•The pilot to ensure that closed doors and windows of international flights from South America, Africa and Asia remain closed until arrival of department of health.
• Pilots are requested to familiarise themselves with the PROC REF to ABV, Failure to comply with ABV PROC will result in the pilot and PAX having to remain on board the ACFT until the government organisations ARR.
• International galley waste must be handled by a ground handling company. If no arrangements in place no waste to leave the aircraft, waste to remain on the aircraft for return flight.

b. Departing international flights

•All international flights departing from Chief Dawid Stuurman airport will do so from the main apron, and only after such flight has been cleared by all the relevant clearing authorities.

•The pilot in charge of a departing international flight must ensure that his ACFT is cleared, and parked on an allocated bay on the main apron prior to the arrival of any of the clearing authorities.

•The pilot in charge of a departing international flight must ensure that the clearing authorities, as well as the Airport Manager, have been informed of the planned flight at least one and a half (1½) hours prior to the planned time of departure.

•The following information must have been provided to the relevant authorities:-

- ACFT Registration;
- Pilot name;
- Point of destination;
- Number of people on board;
- Cargo shipped
- Time of Departure (ETD)

•Representatives of the relevant authorities will meet the pilot or the charter company in the departure hall of the terminal at least forty-five (45) minutes prior to the ETD, in order to process clearance.

•No international flight is to depart prior to clearance having been given by all the relevant authorities.

FAPE AD 2.21 NOISE ABATEMENT PROCEDURES

1. Incorporated in the Chief Dawid Stuurman Standard Instrument Departures.
2. See FAPE AD 2.3 (12)
3. See ENR 1.5, Noise Abatement Procedures.

FAPE AD 2.22 FLIGHT PROCEDURES

1. Low visibility procedures implemented.
2. Traffic under radar control being vectored for an ILS approach RWY 08 can expect to leave 3000FT on the glide slope due to limited radar coverage to the west of VOR PEV.

HELICOPTER PROCEDURES

Inbound flights

1. All helicopters to avoid overflying any buildings (incl. the terminal, tower), the Shell fuel depot and the General Aviation Area at all times.
2. All helicopters routing into Chief Dawid Stuurman International Airport, whether landing at the General Aviation Area or Main Apron, must route inbound via the grass centre block, north of runway 08/26, in line with the RWY08 Glide path hut.
3. Helicopters wishing to park on the Main Apron must liaise their parking bay with Apron Office on frequency 122.65 MHz, and report the bay to tower timeously for inbound routing.
4. Helicopters wishing to land in the General Aviation Area must route via the grass centre block, north of runway 08/26 at all times to Taxiway A3, where they must enter and touch down to terminate the flight at the holding point and request that the gates be opened by Apron Office on frequency 122.65 MHz. They must then obtain clearance from Tower on frequency 118.1MHz to cross Taxiway A.
5. Once this clearance has been given, they must then air taxi (not above 15 feet above the ground), to taxi through the gates.
6. They must follow the centerline markings on Charlie taxiway inside the GA to the heli parking where they must land in a easterly/westerly direction.
7. After landing the helicopter must be towed to its parking spot to make room for the next helicopter to land.
8. All fixed wing aircraft shall hold at the holding points on Taxiway Charlie whilst helicopters hover taxi to the heli parking.

Outbound flights

1. All helicopters to avoid overflying any buildings (incl. the terminal, tower), the Shell fuel depot and the General aviation area at all times.
2. All helicopters in the General aviation area wishing to start must be towed to and on the helipad, request to do so on frequency 122.1 MHz, and when ready contact Apron Office on frequency 122.65 MHz to open the gate, thereafter contact TWR on frequency 118.1 MHz to lift.
3. Once they have been given lift, helicopters must air taxi (not above 15 feet) via the center line markings on Charlie taxiway to the gate.
4. All fixed wing aircraft shall hold at the holding points on Taxiway C whilst helicopters hover taxi from the heli parking.
5. Once the gate is open, helicopters must air taxi through the gate to Taxiway A3 – keeping a look out for other taxiing aircraft. From there, helicopters must route as per Tower instructions via the grass centre block north of runway 08/26.
6. The emergency EMS helicopter, as well as helicopters involved in Netstar tracking operations will be exempt from departing from the heli parking when they are called out. These pilots are to ensure safety around their aircraft before starting and lifting.
7. Fixed wing procedure in GA. All fixed wing aircrafts shall hold at designated holding points on Charlie taxi way, and GA taxi lanes whilst helicopters air taxi to and from the heli parking.

FAPE AD 2.23 ADDITIONAL INFORMATION

1. VFR TFC routing along the coastline BTN Chief Dawid Stuurman and Progress Airfield / Maitland River Mouth should EXER CTN for TFC operating in Seaview Airfield. The Seaview (Private) Airfield is situated WI the Chief Dawid Stuurman CTR: (340005S 0252111E).
The circuit ALT is 1000FT and the circuit pattern is to the South.
2. Hazard: Bird activity on AD.
3. Warning: Cape Receife Rifle Range 3.5NM SSE of AD.
Area 340100S 0253900E - 340100S 025400E - 340300S 025400E - 340300S 0253900E.
Danger height GND/5000 FT GND. Co-ordination BTN Range & ATC in force DRG exercises.
4. RWY Inspections: No circuit training flights will be permitted DRG the mandatory dawn and dusk RWY inspections: Times: Dawn: 0400-0430
Dusk: JAN-APR BTN 1600-1630, MAY-AUG BTN 1500-1530, SEP-DEC BTN 1600-1630.
5. No Microlight operations permitted at FAPE.

FAPE AD 2.24 CHARTS RELATED TO AN AERODROME

AD	-AD-01
Aircraft parking/Docking Chart	-AD-02
ILS RWY 08	-ILS-01
Data tabulation 08	-ILS-01A
ILS Z RWY 26	-ILS-02
VOR Z RWY 08	-VOR-01
VOR Z RWY 26	-VOR-02
Radar Terrain Clearance	-RAD-01
RNAV RWY 08	-RNAV-01
Data tabulation 08	-RNAV-01A
RNAV RWY 26	-RNAV-02
Data tabulation 26	-RNAV-02A
The following charts are AVBL on the CAA website: www.caa.co.za	The following charts are AVBL on the CAA website: www.caa.co.za
Precision APCH Terrain Chart RWY 01	-PATC-01
Precision APCH Terrain Chart RWY 02	-PATC-02
AD OBST Type A	-OBST Type A-01